

Makefile

Page 1/1

```

1: # fiwix/Makefile
2: #
3: # Copyright 2018, Jordi Sanfeliu. All rights reserved.
4: # Distributed under the terms of the Fiwix License.
5: #
6:
7: TOPDIR := $(shell if [ "$$PWD" != "" ] ; then echo $$PWD ; else pwd ; fi)
8: INCLUDE = $(TOPDIR)/include
9:
10: ARCH = -m32
11: CPU = -march=i386
12:
13: DEBUG = -D__DEBUG__ #-D__2DEBUG__
14:
15: CC = $(CROSS_COMPILE)gcc $(ARCH) $(CPU) #$(DEBUG)
16: LD = $(CROSS_COMPILE)ld
17:
18: CFLAGS = -I$(INCLUDE) -Wall -Wstrict-prototypes -ffreestanding -O2 #-Wextra
19: LDFLAGS = -m elf_i386 -nostartfiles -nostdlib -nodefaultlibs -nostdinc
20:
21: DIRS = kernel kernel/syscalls mm fs drivers/block drivers/char lib
22: OBJS = kernel/kernel.o kernel/syscalls/syscalls.o mm/mm.o fs/fs.o \
23:       drivers/block/block.o drivers/char/char.o lib/lib.o
24:
25: export CC LD CFLAGS LDFLAGS INCLUDE
26:
27: all:
28:     @echo "#define UTS_VERSION \"`date`\"" > include/fiwix/version.h
29:     @for n in $(DIRS) ; do (cd $$n ; $(MAKE)) ; done
30:     $(LD) -N -T fiwix.ld $(LDFLAGS) $(OBJS) -o fiwix
31:     nm fiwix | sort | gzip -9c > System.map.gz
32:
33: clean:
34:     @for n in $(DIRS) ; do (cd $$n ; $(MAKE) clean) ; done
35:     rm -f *.o fiwix System.map.gz
36:
37: floppy:
38:     mkfs.minix -n 30 /dev/fd0
39:     mount -t minix /dev/fd0 /mnt/floppy
40:     @mkdir -p /mnt/floppy/boot/grub
41:     @echo "(fd0) /dev/fd0" > /mnt/floppy/boot/grub/device.map
42:     @grub-install --root-directory=/mnt/floppy /dev/fd0
43:     @tools/MAKEBOOTDISK
44:     @cp -prf tools/etc/* /mnt/floppy/etc
45:     @cp fiwix /mnt/floppy/boot
46:     @cp System.map.gz /mnt/floppy/boot
47:     @cp tools/install.sh /mnt/floppy/sbin
48:     umount /mnt/floppy
49:
50: floppy_update:
51:     mount -t minix /dev/fd0 /mnt/floppy
52:     cp fiwix /mnt/floppy/boot
53:     cp System.map.gz /mnt/floppy/boot
54:     umount /mnt/floppy
55:
56:

```

fiwix.ld

Page 1/1

```
1: /*
2:  * Linker script for the Fiwix kernel (3GB user / 1GB kernel).
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: OUTPUT_FORMAT("elf32-i386")
9: OUTPUT_ARCH(i386)
10: ENTRY(start)          /* entry point */
11: vaddr = 0xC0000000;    /* virtual base address at 3GB */
12: paddr = 0x100000;     /* physical address at 1MB */
13:
14: /* define output sections */
15: SECTIONS
16: {
17:     . = paddr;
18:
19:     /* kernel setup code */
20:     .setup ALIGN(4096) :
21:     {
22:         *(.setup)
23:     }
24:
25:     . += vaddr;
26:
27:     /* kernel code */
28:     .text : AT(ADDR(.text) - vaddr)
29:     {
30:         *(.text)
31:     }
32:     _etext = .;
33:
34:     /* initialized data */
35:     .data ALIGN(4096) : AT(ADDR(.data) - vaddr)
36:     {
37:         *(.data)
38:         *(.rodata*)
39:     }
40:     _edata = .;
41:
42:     /* uninitialized data */
43:     .bss ALIGN(4096) : AT(ADDR(.bss) - vaddr)
44:     {
45:         *(COMMON*)
46:         *(.bss*)
47:     }
48:     _end = .;
49:
50:     /* remove information not needed */
51:     /DISCARD/ :
52:     {
53:         *(.eh_frame)
54:     }
55: }
```

kernel/boot.S

Page 1/3

```

1: /*
2:  * fiwix/kernel/boot.S
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/const.h>
9:
10: #define ASM      1          /* GRUB stuff */
11: #include <fiwix/multiboot.h>
12:
13: #define CRO_MP   0x00000002 /* CRO bit-01 MP (Monitor Coprocessor) */
14: #define CRO_NE   0x00000020 /* CRO bit-05 NE (Numeric Error) */
15: #define CRO_WP   0x00010000 /* CRO bit-16 WP (Write Protect) */
16: #define CRO_AM   0x00040000 /* CRO bit-18 AM (Alignment Mask) */
17: #define CRO_PG   0x80000000 /* CRO bit-31 PG (Paging) */
18:
19: .section .setup, "a"      /* "a" attribute means Allocatable section */
20:
21: .align 4
22: tmp_gdtr:
23:     .word ((3 * 8) - 1)
24:     .long tmp_gdt
25:
26: .align 4
27: tmp_gdt:
28:     /* NULL DESCRIPTOR */
29:     .word 0x0000
30:     .word 0x0000
31:     .word 0x0000
32:     .word 0x0000
33:
34:     /* KERNEL CODE */
35:     .word 0xFFFF          /* segment limit 15-00 */
36:     .word 0x0000          /* base address 15-00 */
37:     .byte 0x00            /* base address 23-16 */
38:     .byte 0x9A           /* P=1 DPL=00 S=1 TYPE=1010 (exec/read) */
39:     .byte 0xCF           /* G=1 DB=1 0=0 AVL=0 SEGLIM=1111 */
40:     .byte 0x40           /* base address 31-24 */
41:
42:     /* KERNEL DATA */
43:     .word 0xFFFF          /* segment limit 15-00 */
44:     .word 0x0000          /* base address 15-00 */
45:     .byte 0x00            /* base address 23-16 */
46:     .byte 0x92           /* P=1 DPL=00 S=1 TYPE=0010 (read/write) */
47:     .byte 0xCF           /* G=1 DB=1 0=0 AVL=0 SEGLIM=1111 */
48:     .byte 0x40           /* base address 31-24 */
49:
50:
51: .text
52:
53: .globl start; start:
54:     cli
55:     jmp     multiboot_entry
56:
57: .align 4
58: multiboot_header:          /* multiboot header */
59:     .long MULTIBOOT_HEADER_MAGIC /* magic */
60:     .long MULTIBOOT_HEADER_FLAGS /* flags */
61:     /* checksum */
62:     .long -(MULTIBOOT_HEADER_MAGIC + MULTIBOOT_HEADER_FLAGS)
63:
64: #ifndef __ELF__
65:     .long multiboot_header      /* header_addr */
66:     .long _start                /* load_addr */
67:     .long _edata                /* load_end_addr */

```

kernel/boot.S

Page 2/3

```

68:      .long   _end                /* bss_end_addr */
69:      .long   multiboot_entry     /* entry_addr */
70: #endif /* ! __ELF__ */
71:
72: /*
73:  * We use the CX register in order to keep intact the values in AX and BX
74:  * registers, since they are holding the Multiboot values 'magic' and 'info'
75:  * respectively.
76:  */
77: multiboot_entry:
78:      lgdt    tmp_gdtr            /* load GDTR with the temporary GDT */
79:      movw   $KERNEL_DS, %cx
80:      movw   %cx, %ds
81:      movw   %cx, %es
82:      movw   %cx, %fs
83:      movw   %cx, %gs
84:      movw   %cx, %ss
85:      ljmp   $KERNEL_CS, $1f
86: 1:
87:
88:
89: /*
90:  * WARNING WARNING WARNING WARNING WARNING WARNING WARNING WARNING WARNING !!!
91:  * -----
92:  * The minimal page directory of 4MB only works if the in-memory size of the
93:  * kernel is lesser than 3MB. If you need more space go to the setup_minmem()
94:  * function and set the 'mb4' variable accordingly.
95:  *
96:  * In order to know the current size of the Fiwix kernel, just follow this:
97:  *
98:  * # readelf -l fiwix
99:  * Elf file type is EXEC (Executable file)
100:  * Entry point 0xc0100020
101:  * There are 2 program headers, starting at offset 52
102:  *
103:  * Program Headers:
104:  *   Type           Offset   VirtAddr   PhysAddr   FileSiz MemSiz  Flg Align
105:  *   LOAD           0x000074 0x00100000 0x00100000 0x00020 0x00020 R  0x4
106:  *   LOAD           0x0000a0 0xc0100020 0x00100020 0x33f8c 0x859a0 RWE 0x20
107:  *
108:  *                   check this value --> ^^^^^^^
109:  */
109:      movl   $0xc0010000, %esp     /* default stack address */
110:      pushl  $0                    /* reset EFLAGS */
111:      popf
112:
113:      pushl  %eax                  /* save Multiboot magic value */
114:      call   setup_minmem         /* setup a minimal page directory */
115:      movl   %eax, %cr3
116:
117:      movl   %cr0, %eax
118:      andl   $0x00000011, %eax    /* disable all, preserve ET & PE (GRUB)
*/
119:      orl   $CR0_PG, %eax         /* enable PG (Paging) */
120:      orl   $CR0_AM, %eax         /* enable AM (Alignment Mask) */
121:      orl   $CR0_WP, %eax         /* enable WP (Write Protect) */
122:      orl   $CR0_NE, %eax         /* enable NE (Numeric Error) */
123:      orl   $CR0_MP, %eax         /* enable MP (Monitor Coprocessor) */
124:      movl   %eax, %cr0
125:
126:      call   bss_init             /* initialize BSS segment */
127:      call   gdt_init             /* setup and load the definitive GDT */
128:
129:      pushl  %ebx                  /* save Multiboot info structure */
130:      call   get_last_elf_addr
131:      add    $4, %esp
132:      popl   %ecx                  /* restore Multiboot magic value */
133:      andl   $0xFFFFF000, %eax    /* page aligned */

```

kernel/boot.S

Page 3/3

```
134:      addl    $0x3000, %eax      /* 2 whole pages for kernel stack */
135:      subl    $4, %eax
136:      movl    %eax, %esp        /* set kernel stack */
137:
138:      pushl   %esp              /* save kernel stack address */
139:      pushl   %ebx              /* save Multiboot info structure */
140:      pushl   %ecx              /* save Multiboot magic value */
141:      call   start_kernel
142:
143:      .align 4
144:      .globl cpu_idle; cpu_idle:
145:          hlt
146:          jmp     cpu_idle
147:
148:      .align 4
149:      .org 0x1000
150:      .globl _fdc_transfer_area
151:      _fdc_transfer_area:      .fill 512*2*18,1,0
```

kernel/cmos.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/cmos.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/cmos.h>
10:
11: int cmos_update_in_progress(void)
12: {
13:     return(cmos_read(CMOS_STATA) & CMOS_STATA_UIP);
14: }
15:
16: unsigned char cmos_read_date(unsigned char addr)
17: {
18:     /* make sure an update isn't in progress */
19:     while(cmos_update_in_progress());
20:
21:     if(!(cmos_read(CMOS_STATB) & CMOS_STATB_DM)) {
22:         return BCD2BIN(cmos_read(addr));
23:     }
24:     return cmos_read(addr);
25: }
26:
27: void cmos_write_date(unsigned char addr, unsigned char value)
28: {
29:     /* make sure an update isn't in progress */
30:     while(cmos_update_in_progress());
31:
32:     if(!(cmos_read(CMOS_STATB) & CMOS_STATB_DM)) {
33:         cmos_write(addr, BIN2BCD(value));
34:     }
35:     cmos_write(addr, value);
36: }
37:
38: unsigned char cmos_read(unsigned char addr)
39: {
40:     unsigned long int flags;
41:
42:     SAVE_FLAGS(flags); CLI();
43:     outport_b(CMOS_INDEX, addr);
44:     RESTORE_FLAGS(flags);
45:
46:     return inport_b(CMOS_DATA);
47: }
48:
49: void cmos_write(unsigned char addr, unsigned char value)
50: {
51:     unsigned long int flags;
52:
53:     SAVE_FLAGS(flags); CLI();
54:     outport_b(CMOS_INDEX, addr);
55:     outport_b(CMOS_DATA, value);
56:     RESTORE_FLAGS(flags);
57: }
```

kernel/core386.S

Page 1/15

```

1: /*
2:  * fiwix/kernel/core386.S
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/const.h>
9: #include <fiwix/unistd.h>
10:
11: #define CRO_MP    ~(0x00000002)    /* CRO bit-01 MP (Monitor Coprocessor) */
12: #define CRO_EM    0x00000004    /* CRO bit-02 EM (Emulation) */
13:
14: #define SS_RPL3    0x03    /* Request Privilege Level 3 */
15:
16: #define GS    0x00
17: #define FS    0x04
18: #define ES    0x08
19: #define DS    0x0C
20: #define EDI    0x10    /* \
21: #define ESI    0x14    /* |
22: #define EBP    0x18    /* |
23: #define ESP    0x1C    /* | saved by
24: #define EBX    0x20    /* | 'pusha'
25: #define EDX    0x24    /* |
26: #define ECX    0x28    /* |
27: #define EAX    0x2C    /* /
28: #define ERR    0x30    /* error code or padding
29: #define EIP    0x34    /* \
30: #define CS    0x38    /* | saved by processor
31: #define FLAGS    0x3C    /* /
32: #define OLDESP    0x40    /* \ saved by processor on
33: #define OLDSS    0x44    /* / privilege level change
34:
35: #define SAVE_ALL
36:     pushal
37:     pushl    %ds
38:     pushl    %es
39:     pushl    %fs
40:     pushl    %gs
41:
42: #define EXCEPTION(exception)
43:     pushl    $exception
44:     call    trap_handler
45:     addl    $4, %esp
46:
47: #define IRQ(irq)
48:     pushl    $irq
49:     call    irq_handler
50:     addl    $4, %esp
51:
52: /*
53:  * Check only for signals if we are returning from user-mode. issig() function
54:  * returns 1 if there are signals or 0 otherwise. If there are signals psig()
55:  * function is called with the stack as the first argument.
56:  */
57: #define CHECK_SIGNALS
58:     cmpw    $KERNEL_CS, CS(%esp)
59:     je     1f
60:     call    issig
61:     cmpl    $0, %eax
62:     je     1f
63:     movl    %esp, %eax
64:     pushl    %eax
65:     call    psig
66:     addl    $4, %esp
67: 1:

```

kernel/core386.S

Page 2/15

```

68:
69: #define SCHEDULE                                     \
70:     cml     $0, need_resched                       ;\
71:     je     1f                                      ;\
72:     call   do_sched                               ;\
73: 1:
74:
75: #define BOTTOM_HALVES                               \
76: /*     sti                                     */ ;\
77:     call   do_bh
78:
79: #define RESTORE_ALL                                 \
80:     popl   %gs                                     ;\
81:     popl   %fs                                     ;\
82:     popl   %es                                     ;\
83:     popl   %ds                                     ;\
84:     popal                                     ;\
85:     addl   $4, %esp                                # suppress error code (or padding) from stack
86:
87:
88: .text
89:
90: .align 4
91: .globl except0; except0:                            # DIVIDE ERROR
92:     pushl  $0                                       # save simulated error code to stack
93:     SAVE_ALL
94:     EXCEPTION(0x0)
95:     SCHEDULE
96:     CHECK_SIGNALS
97:     BOTTOM_HALVES
98:     RESTORE_ALL
99:     iret
100:
101: .align 4
102: .globl except1; except1:                            # DEBUG
103:     pushl  $0                                       # save simulated error code to stack
104:     SAVE_ALL
105:     EXCEPTION(0x1)
106:     SCHEDULE
107:     CHECK_SIGNALS
108:     BOTTOM_HALVES
109:     RESTORE_ALL
110:     iret
111:
112: .align 4
113: .globl except2; except2:                            # NMI INTERRUPT
114:     pushl  $0                                       # save simulated error code to stack
115:     SAVE_ALL
116:     EXCEPTION(0x2)
117:     SCHEDULE
118:     CHECK_SIGNALS
119:     BOTTOM_HALVES
120:     RESTORE_ALL
121:     iret
122:
123: .align 4
124: .globl except3; except3:                            # BREAKPOINT INT3
125:     pushl  $0                                       # save simulated error code to stack
126:     SAVE_ALL
127:     EXCEPTION(0x3)
128:     SCHEDULE
129:     CHECK_SIGNALS
130:     BOTTOM_HALVES
131:     RESTORE_ALL
132:     iret
133:
134: .align 4

```


kernel/core386.S

Page 3/15

```

135: .globl except4; except4:           # OVERFLOW
136:     pushl  $0                       # save simulated error code to stack
137:     SAVE_ALL
138:     EXCEPTION(0x4)
139:     SCHEDULE
140:     CHECK_SIGNALS
141:     BOTTOM_HALVES
142:     RESTORE_ALL
143:     iret
144:
145: .align 4
146: .globl except5; except5:           # BOUND
147:     pushl  $0                       # save simulated error code to stack
148:     SAVE_ALL
149:     EXCEPTION(0x5)
150:     SCHEDULE
151:     CHECK_SIGNALS
152:     BOTTOM_HALVES
153:     RESTORE_ALL
154:     iret
155:
156: .align 4
157: .globl except6; except6:           # INVALID OPCODE
158:     pushl  $0                       # save simulated error code to stack
159:     SAVE_ALL
160:     EXCEPTION(0x6)
161:     SCHEDULE
162:     CHECK_SIGNALS
163:     BOTTOM_HALVES
164:     RESTORE_ALL
165:     iret
166:
167: .align 4
168: .globl except7; except7:           # NO MATH COPROCESSOR
169:     pushl  $0                       # save simulated error code to stack
170:     SAVE_ALL
171:     EXCEPTION(0x7)
172:     clds                             # floating-opcode cached!
173:     SCHEDULE
174:     CHECK_SIGNALS
175:     BOTTOM_HALVES
176:     RESTORE_ALL
177:     iret
178:
179: .align 4
180: .globl except8; except8:           # DOUBLE FAULT
181:     SAVE_ALL
182:     EXCEPTION(0x8)
183:     SCHEDULE
184:     CHECK_SIGNALS
185:     BOTTOM_HALVES
186:     RESTORE_ALL
187:     iret
188:
189: .align 4
190: .globl except9; except9:           # COPROCESSOR SEGMENT OVERRUN
191:     pushl  $0                       # save simulated error code to stack
192:     SAVE_ALL
193:     EXCEPTION(0x9)
194:     SCHEDULE
195:     CHECK_SIGNALS
196:     BOTTOM_HALVES
197:     RESTORE_ALL
198:     iret
199:
200: .align 4
201: .globl exceptA; exceptA:           # INVALID TSS

```

kernel/core386.S

Page 4/15

```

202:         SAVE_ALL
203:         EXCEPTION(0xA)
204:         SCHEDULE
205:         CHECK_SIGNALS
206:         BOTTOM_HALVES
207:         RESTORE_ALL
208:         iret
209:
210: .align 4
211: .globl exceptB; exceptB:         # SEGMENT NOT PRESENT
212:         SAVE_ALL
213:         EXCEPTION(0xB)
214:         SCHEDULE
215:         CHECK_SIGNALS
216:         BOTTOM_HALVES
217:         RESTORE_ALL
218:         iret
219:
220: .align 4
221: .globl exceptC; exceptC:         # STACK SEGMENT FAULT
222:         SAVE_ALL
223:         EXCEPTION(0xC)
224:         SCHEDULE
225:         CHECK_SIGNALS
226:         BOTTOM_HALVES
227:         RESTORE_ALL
228:         iret
229:
230: .align 4
231: .globl exceptD; exceptD:         # GENERAL PROTECTION FAULT
232:         SAVE_ALL
233:         EXCEPTION(0xD)
234:         SCHEDULE
235:         CHECK_SIGNALS
236:         BOTTOM_HALVES
237:         RESTORE_ALL
238:         iret
239:
240: .align 4
241: .globl exceptE; exceptE:         # PAGE FAULT
242:         SAVE_ALL
243:         EXCEPTION(0xE)
244:         SCHEDULE
245:         CHECK_SIGNALS
246:         BOTTOM_HALVES
247:         RESTORE_ALL
248:         iret
249:
250: .align 4
251: .globl exceptF; exceptF:         # INTEL RESERVED
252:         pushl    $0              # save simulated error code to stack
253:         SAVE_ALL
254:         EXCEPTION(0xF)
255:         SCHEDULE
256:         CHECK_SIGNALS
257:         BOTTOM_HALVES
258:         RESTORE_ALL
259:         iret
260:
261: .globl except10; except10:       # FLOATING POINT ERROR
262:         pushl    $0              # save simulated error code to stack
263:         SAVE_ALL
264:         EXCEPTION(0x10)
265:         SCHEDULE
266:         CHECK_SIGNALS
267:         BOTTOM_HALVES
268:         RESTORE_ALL

```

kernel/core386.S

Page 5/15

```

269:         ired
270:
271: .globl except11; except11:         # ALIGNMENT CHECK
272:         EXCEPTION(0x11)
273:         SAVE_ALL
274:         SCHEDULE
275:         CHECK_SIGNALS
276:         BOTTOM_HALVES
277:         RESTORE_ALL
278:         ired
279:
280: .globl except12; except12:         # MACHINE CHECK
281:         pushl $0                   # save simulated error code to stack
282:         SAVE_ALL
283:         EXCEPTION(0x12)
284:         SCHEDULE
285:         CHECK_SIGNALS
286:         BOTTOM_HALVES
287:         RESTORE_ALL
288:         ired
289:
290: .globl except13; except13:         # SIMD FLOATING POINT
291:         pushl $0                   # save simulated error code to stack
292:         SAVE_ALL
293:         EXCEPTION(0x13)
294:         SCHEDULE
295:         CHECK_SIGNALS
296:         BOTTOM_HALVES
297:         RESTORE_ALL
298:         ired
299:
300: .globl except14; except14:         # INTEL RESERVED
301: .globl except15; except15:         # INTEL RESERVED
302: .globl except16; except16:         # INTEL RESERVED
303: .globl except17; except17:         # INTEL RESERVED
304: .globl except18; except18:         # INTEL RESERVED
305: .globl except19; except19:         # INTEL RESERVED
306: .globl except1A; except1A:         # INTEL RESERVED
307: .globl except1B; except1B:         # INTEL RESERVED
308: .globl except1C; except1C:         # INTEL RESERVED
309: .globl except1D; except1D:         # INTEL RESERVED
310: .globl except1E; except1E:         # INTEL RESERVED
311: .globl except1F; except1F:         # INTEL RESERVED
312:         pushl $0                   # save simulated error code to stack
313:         SAVE_ALL
314:         EXCEPTION(0x14)
315:         SCHEDULE
316:         CHECK_SIGNALS
317:         BOTTOM_HALVES
318:         RESTORE_ALL
319:         ired
320:
321: .align 4
322: .globl irq0; irq0:                 # TIMER
323:         pushl $0                   # save simulated error code to stack
324:         SAVE_ALL
325:         IRQ(0)
326:         SCHEDULE
327:         CHECK_SIGNALS
328:         BOTTOM_HALVES
329:         RESTORE_ALL
330:         ired
331:
332: .align 4
333: .globl irq1; irq1:                 # KEYBOARD
334:         pushl $0                   # save simulated error code to stack
335:         SAVE_ALL

```

kernel/core386.S

Page 6/15

```
336:         IRQ(1)
337:         SCHEDULE
338:         CHECK_SIGNALS
339:         BOTTOM_HALVES
340:         RESTORE_ALL
341:         iret
342:
343: .align 4
344: .globl irq2; irq2:         # CASCADE
345:         pushl    $0         # save simulated error code to stack
346:         SAVE_ALL
347:         IRQ(2)
348:         SCHEDULE
349:         CHECK_SIGNALS
350:         BOTTOM_HALVES
351:         RESTORE_ALL
352:         iret
353:
354: .align 4
355: .globl irq3; irq3:         # SERIAL
356:         pushl    $0         # save simulated error code to stack
357:         SAVE_ALL
358:         IRQ(3)
359:         SCHEDULE
360:         CHECK_SIGNALS
361:         BOTTOM_HALVES
362:         RESTORE_ALL
363:         iret
364:
365: .align 4
366: .globl irq4; irq4:         # SERIAL
367:         pushl    $0         # save simulated error code to stack
368:         SAVE_ALL
369:         IRQ(4)
370:         SCHEDULE
371:         CHECK_SIGNALS
372:         BOTTOM_HALVES
373:         RESTORE_ALL
374:         iret
375:
376: .align 4
377: .globl irq5; irq5:         # save simulated error code to stack
378:         pushl    $0
379:         SAVE_ALL
380:         IRQ(5)
381:         SCHEDULE
382:         CHECK_SIGNALS
383:         BOTTOM_HALVES
384:         RESTORE_ALL
385:         iret
386:
387: .align 4
388: .globl irq6; irq6:         # FLOPPY
389:         pushl    $0         # save simulated error code to stack
390:         SAVE_ALL
391:         IRQ(6)
392:         SCHEDULE
393:         CHECK_SIGNALS
394:         BOTTOM_HALVES
395:         RESTORE_ALL
396:         iret
397:
398: .align 4
399: .globl irq7; irq7:         # save simulated error code to stack
400:         pushl    $0
401:         SAVE_ALL
402:         IRQ(7)
```

kernel/core386.S

Page 7/15

```
403:         SCHEDULE
404:         CHECK_SIGNALS
405:         BOTTOM_HALVES
406:         RESTORE_ALL
407:         iret
408:
409: .align 4
410: .globl irq8; irq8:
411:     pushl    $0                # save simulated error code to stack
412:     SAVE_ALL
413:     IRQ(8)
414:     SCHEDULE
415:     CHECK_SIGNALS
416:     BOTTOM_HALVES
417:     RESTORE_ALL
418:     iret
419:
420: .align 4
421: .globl irq9; irq9:
422:     pushl    $0                # save simulated error code to stack
423:     SAVE_ALL
424:     IRQ(9)
425:     SCHEDULE
426:     CHECK_SIGNALS
427:     BOTTOM_HALVES
428:     RESTORE_ALL
429:     iret
430:
431: .align 4
432: .globl irq10; irq10:
433:     pushl    $0                # save simulated error code to stack
434:     SAVE_ALL
435:     IRQ(10)
436:     SCHEDULE
437:     CHECK_SIGNALS
438:     BOTTOM_HALVES
439:     RESTORE_ALL
440:     iret
441:
442: .align 4
443: .globl irq11; irq11:
444:     pushl    $0                # save simulated error code to stack
445:     SAVE_ALL
446:     IRQ(11)
447:     SCHEDULE
448:     CHECK_SIGNALS
449:     BOTTOM_HALVES
450:     RESTORE_ALL
451:     iret
452:
453: .align 4
454: .globl irq12; irq12:
455:     pushl    $0                # save simulated error code to stack
456:     SAVE_ALL
457:     IRQ(12)
458:     SCHEDULE
459:     CHECK_SIGNALS
460:     BOTTOM_HALVES
461:     RESTORE_ALL
462:     iret
463:
464: .align 4
465: .globl irq13; irq13:
466:     pushl    $0                # save simulated error code to stack
467:     SAVE_ALL
468:     IRQ(13)
469:     SCHEDULE
```

kernel/core386.S

Page 8/15

```

470:         CHECK_SIGNALS
471:         BOTTOM_HALVES
472:         RESTORE_ALL
473:         iret
474:
475: .align 4
476: .globl irq14; irq14:           # IDE Primary
477:     pushl    $0                # save simulated error code to stack
478:     SAVE_ALL
479:     IRQ(14)
480:     SCHEDULE
481:     CHECK_SIGNALS
482:     BOTTOM_HALVES
483:     RESTORE_ALL
484:     iret
485:
486: .align 4
487: .globl irq15; irq15:           # IDE Secondary
488:     pushl    $0                # save simulated error code to stack
489:     SAVE_ALL
490:     IRQ(15)
491:     SCHEDULE
492:     CHECK_SIGNALS
493:     BOTTOM_HALVES
494:     RESTORE_ALL
495:     iret
496:
497: .align 4
498: .globl unknown_irq; unknown_irq:
499:     pushl    $0                # save simulated error code to stack
500:     SAVE_ALL
501:     IRQ(-1)
502:     RESTORE_ALL
503:     iret
504:
505: .align 4
506: .globl switch_to_user_mode; switch_to_user_mode:
507:     cli
508:     xorl    %eax, %eax          # initialize %eax
509:     movl    %eax, %ebx          # initialize %ebx
510:     movl    %eax, %ecx          # initialize %ecx
511:     movl    %eax, %edx          # initialize %edx
512:     movl    %eax, %esi          # initialize %esi
513:     movl    %eax, %edi          # initialize %edi
514:     movl    %eax, %ebp          # initialize %ebp
515:     movl    $(USER_DS | SS_RPL3), %eax
516:     movw    %ax, %ds
517:     movw    %ax, %es
518:     movw    %ax, %fs
519:     movw    %ax, %gs
520:     pushl   %eax
521:     pushl   $KERNEL_BASE_ADDR - 4    # user stack address
522:     pushl   $0x202                    # initialize eflags (Linux 2.2 = 0x292)
523:     popfl
524:     pushfl
525:     movl    $(USER_CS | SS_RPL3), %eax
526:     pushl   %eax
527:     pushl   $KERNEL_BASE_ADDR - 0x1000 # go to init_trampoline() in use
r mode
528:     iret
529:
530: .align 4
531: .globl sighandler_trampoline; sighandler_trampoline:
532:     pushl   %eax
533:     call    *%ecx
534:     popl    %ebx
535:

```

kernel/core386.S

Page 9/15

```

536:      movl    $SYS_sigreturn, %eax
537:      int     $0x80
538:
539:      # never reached, otherwise call sys_exit()
540:      movl    $SYS_exit, %eax
541:      int     $0x80
542:      ret
543: .align 4
544: .globl end_sighandler_trampoline; end_sighandler_trampoline:
545:      nop
546:
547: .align 4
548: .globl syscall; syscall:                # SYSTEM CALL ENTRY
549:      pushl  %eax                        # save the system call number
550:      SAVE_ALL
551:
552:      pushl  %edi                        # \ 5th parameter
553:      pushl  %esi                        # | 4th parameter
554:      pushl  %edx                        # | 3rd parameter
555:      pushl  %ecx                        # | 2nd parameter
556:      pushl  %ebx                        # / 1st parameter
557:      pushl  %eax                        # system call number
558:      call   do_syscall
559:      addl   $24, %esp                   # suppress all 6 pushl from the stack
560:      movl   %eax, EAX(%esp)            # save the return value
561:
562:      SCHEDULE
563:      CHECK_SIGNALS
564:      BOTTOM_HALVES
565: .align 4
566: .globl return_from_syscall; return_from_syscall:
567:      RESTORE_ALL
568:      iret
569:
570: .align 4
571: .globl do_switch; do_switch:
572:      movl   %esp, %ebx
573:      pushal
574:      pushfl
575:      movl   0x4(%ebx), %eax             # save ESP to 'prev->tss.esp'
576:      movl   %esp, (%eax)
577:      movl   0x8(%ebx), %eax             # save EIP to 'prev->tss.eip'
578:      movl   $1f, (%eax)
579:      movl   0xC(%ebx), %esp            # load 'next->tss.esp' into ESP
580:      pushl  0x10(%ebx)                  # push 'next->tss.eip' into ESP
581:      movl   0x14(%ebx), %eax           # load 'next->tss.cr3' into CR3
582:      ltr   0x18(%ebx)                   # load TSS
583:      movl   %eax, %cr3
584:      ret
585: 1:
586:      popfl
587:      popal
588:
589: .align 4
590: .globl cpuid; cpuid:
591:      pushl  %ebp
592:      movl   %esp, %ebp
593:      pushl  %edi
594:      pushl  %esi
595:      pushl  %ebx
596:
597:      pushf
598:      pop    %eax                        # put original EFLAGS in EAX
599:      mov    %eax, %ecx                   # save original EFLAGS in ECX
600:      xor    $0x200000, %eax              # change bit 21 (ID) in EFLAGS
601:      push   %eax                        # save new EFLAGS on stack
602:      popf

```

kernel/core386.S

Page 10/15

```

603:        pushf
604:        pop     %eax                # put EFLAGS in EAX
605:        cmp     %ecx, %eax         # compare if both EFLAGS are equal
606:
607:        je     test386            # can't toggle ID bit, no CPUID
608:        xor     %ebx, %ebx         # CPUID available, will return 0
609:        jmp     end_cpuid
610:
611: test386:
612:        mov     %ecx, %eax         # get original EFLAGS
613:        xor     $0x40000, %eax     # change bit 18 (AC) in EFLAGS
614:        push   %eax               # save new EFLAGS on stack
615:        popf
616:        pushf
617:        pop     %eax
618:        cmp     %ecx, %eax         # compare if both EFLAGS are equal
619:        movb   $3, %bl           # looks like an i386, return 3
620:        je     end_cpuid
621:        movb   $4, %bl           # otherwise is an old i486, return 4
622:
623: end_cpuid:
624:        push   %ecx               # push original EFLAGS
625:        popf
626:        xor     %eax, %eax         # restore original EFLAGS
627:        movb   %bl, %al          # put return value to AL
628:
629:        popl   %ebx
630:        popl   %esi
631:        popl   %edi
632:        popl   %ebp
633:        ret
634:
635: .align 4
636: .globl getfpu; getfpu:
637:        pushl  %ebp
638:        movl  %esp, %ebp
639:        pushl  %edi
640:        pushl  %esi
641:        pushl  %ebx
642:
643:        fninit
644:        movl  $0x5a5a, _fpstatus
645:        fnstsw _fpstatus
646:        movl  _fpstatus, %eax
647:        cmp   $0, %al
648:        movl  $0, _fpstatus
649:        jne  end_getfpu
650:
651: check_control_word:
652:        fnstcw _fpstatus
653:        movl  _fpstatus, %eax
654:        andl  $0x103f, %eax
655:        cmp   $0x3f, %ax
656:        movl  $0, _fpstatus
657:        jne  end_getfpu
658:        movl  $1, _fpstatus
659:
660: end_getfpu:
661:        movl  _fpstatus, %eax
662:        cmp   $0, %al
663:        jne  1f                  # return if there is a coprocessor
664:        movl  %cr0, %eax         # otherwise (no math processor):
665:        orl   $CR0_EM, %eax     # - set EM (Emulation)
666:        andl  $CR0_MP, %eax     # - clear MP (Monitor Coprocessor)
667:        movl  %eax, %cr0
668:        movl  $0, %eax
669: 1:

```


kernel/core386.S

Page 11/15

```

670:        popl    %ebx
671:        popl    %esi
672:        popl    %edi
673:        popl    %ebp
674:        ret
675:
676:        .align 4
677:        .globl vendor_id; vendor_id:
678:        pushl   %ebp
679:        movl    %esp, %ebp
680:        pushl   %ebx
681:        pushl   %edx
682:        pushl   %ecx
683:
684:        mov     $0, %eax
685:        cpuid
686:        movl    %ebx, _vendorid        # save the 12 bytes of vendor ID string
687:        movl    %edx, _vendorid+4
688:        movl    %ecx, _vendorid+8
689:
690:        popl    %ecx
691:        popl    %edx
692:        popl    %ebx
693:        popl    %ebp
694:        ret                    # EAX returns the highest CPUID value
695:
696:        .align 4
697:        .globl signature_flags; signature_flags:
698:        pushl   %ebp
699:        movl    %esp, %ebp
700:        pushl   %edi
701:        pushl   %esi
702:        pushl   %ebx
703:        pushl   %edx
704:
705:        mov     $1, %eax
706:        cpuid
707:        movl    %eax, _cpusignature    # signature (model and stepping)
708:        movl    %ebx, _brandid        # misc. information
709:        movl    %edx, _cpuflags      # feature flags
710:        shrl   $8, %eax
711:        andl   $0xF, %eax
712:        movl    %eax, _cputype        # family
713:
714:        popl    %edx
715:        popl    %ebx
716:        popl    %esi
717:        popl    %edi
718:        popl    %ebp
719:        ret
720:
721:        .align 4
722:        .globl brand_str; brand_str:
723:        pushl   %ebp
724:        movl    %esp, %ebp
725:        pushl   %edi
726:        pushl   %esi
727:        pushl   %ebx
728:
729:        movl    $0x80000000, %eax
730:        cpuid
731:        cmp     $0x80000000, %eax      # check if brand string is supported
732:        jbe    no_brand_str
733:        movl    $0x80000002, %eax      # get first 16 bytes of brand string
734:        cpuid
735:        movl    %eax, _brandstr
736:        movl    %ebx, _brandstr+4

```

kernel/core386.S

Page 12/15

```

737:      movl    %ecx, _brandstr+8
738:      movl    %edx, _brandstr+12
739:      movl    $0x80000003, %eax      # get more 16 bytes of brand string
740:      cpuid
741:      movl    %eax, _brandstr+16
742:      movl    %ebx, _brandstr+20
743:      movl    %ecx, _brandstr+24
744:      movl    %edx, _brandstr+28
745:      movl    $0x80000004, %eax      # get last 16 bytes of brand string
746:      cpuid
747:      movl    %eax, _brandstr+32
748:      movl    %ebx, _brandstr+36
749:      movl    %ecx, _brandstr+40
750:      movl    %edx, _brandstr+44
751:      jmp     end_brand_str
752:
753: no_brand_str:
754:      movl    $1, %eax
755:
756: end_brand_str:
757:      movl    $0, %eax
758:      popl   %ebx
759:      popl   %esi
760:      popl   %edi
761:      popl   %ebp
762:      ret
763:
764: .align 4
765: .globl tlbinfo; tlbinfo:
766:      pushl  %edx
767:      pushl  %ecx
768:      mov    $2, %eax
769:      cpuid
770:      movl    %eax, _tlbinfo_eax      # store cache information
771:      movl    %ebx, _tlbinfo_ebx
772:      movl    %edx, _tlbinfo_ecx
773:      movl    %ecx, _tlbinfo_edx
774:      popl   %ecx
775:      popl   %edx
776:      ret
777:
778: .align 4
779: .globl inport_b; inport_b:
780:      pushl  %ebp
781:      movl    %esp, %ebp
782:
783:      movw   0x08(%ebp), %dx      # port addr
784:      inb    %dx, %al
785:
786:      jmp    1f                  # recovery time
787: 1:      jmp    1f                  # recovery time
788: 1:      popl   %ebp
789:      ret
790:
791: .align 4
792: .globl inport_w; inport_w:
793:      pushl  %ebp
794:      movl    %esp, %ebp
795:
796:      movw   0x08(%ebp), %dx      # port addr
797:      inw    %dx, %ax
798:
799:      jmp    1f                  # recovery time
800: 1:      jmp    1f                  # recovery time
801: 1:      popl   %ebp
802:      ret
803:

```

kernel/core386.S

Page 13/15

```

804: .align 4
805: .globl inport_sw; inport_sw:
806:     pushl    %ebp
807:     movl    %esp, %ebp
808:     pushl    %edx
809:     pushl    %edi
810:     pushl    %ecx
811:
812:     cld
813:     mov     0x8(%ebp), %edx        # port addr
814:     mov     0xC(%ebp), %edi       # dest
815:     mov     0x10(%ebp), %ecx      # count
816:     rep
817:     insw
818:
819:     popl    %ecx
820:     popl    %edi
821:     popl    %edx
822:     popl    %ebp
823:     ret
824:
825: .align 4
826: .globl outport_b; outport_b:
827:     pushl    %ebp
828:     movl    %esp, %ebp
829:
830:     movw    0x8(%ebp), %dx        # port addr
831:     movb    0xC(%ebp), %al       # data
832:     outb    %al, %dx
833:
834:     jmp     1f                    # recovery time
835: 1:     jmp     1f                    # recovery time
836: 1:     popl    %ebp
837:     ret
838:
839: .align 4
840: .globl outport_w; outport_w:
841:     pushl    %ebp
842:     movl    %esp, %ebp
843:
844:     movw    0x8(%ebp), %dx        # port addr
845:     movw    0xC(%ebp), %ax       # data
846:     outw    %ax, %dx
847:
848:     jmp     1f                    # recovery time
849: 1:     jmp     1f                    # recovery time
850: 1:     popl    %ebp
851:     ret
852:
853: .align 4
854: .globl outport_sw; outport_sw:
855:     pushl    %ebp
856:     movl    %esp, %ebp
857:     pushl    %edx
858:     pushl    %esi
859:     pushl    %ecx
860:
861:     cld
862:     mov     0x8(%ebp), %edx        # port addr
863:     mov     0xC(%ebp), %esi       # src
864:     mov     0x10(%ebp), %ecx      # count
865:     rep
866:     outsw
867:
868:     popl    %ecx
869:     popl    %esi
870:     popl    %edx

```

kernel/core386.S

Page 14/15

```

871:      popl    %ebp
872:      ret
873:
874: .align 4
875: .globl load_gdt; load_gdt:
876:      movl    0x4(%esp), %eax
877:      lgdt    (%eax)
878:      movw    $KERNEL_DS, %ax
879:      movw    %ax, %ds
880:      movw    %ax, %es
881:      movw    %ax, %fs
882:      movw    %ax, %gs
883:      movw    %ax, %ss
884:      ljmp   $KERNEL_CS, $1f
885: 1:
886:      ret
887:
888: .align 4
889: .globl load_idt; load_idt:
890:      movl    0x4(%esp), %eax
891:      lidt    (%eax)
892:      ret
893:
894: .align 4
895: .globl activate_kpage_dir; activate_kpage_dir:
896:      movl    kpage_dir, %eax
897:      movl    %eax, %cr3
898:      ret
899:
900: .align 4
901: .globl load_tr; load_tr:
902:      mov     0x4(%esp), %ax
903:      ltr     %ax
904:      ret
905:
906: .align 4
907: .globl get_rdtsc; get_rdtsc:
908:      cpuid
909:      rdtsc
910:      ret
911:
912: .align 4
913: .globl invalidate_tlb; invalidate_tlb:
914:      movl    %cr3, %eax
915:      movl    %eax, %cr3
916:      ret
917:
918:
919: .data
920:
921: .globl _cputype
922: .globl _cpusignature
923: .globl _cpuflags
924: .globl _fpstatus
925: .globl _brandid
926: .globl _vendorid
927: .globl _brandstr
928: .globl _tlbinfo_eax
929: .globl _tlbinfo_ebx
930: .globl _tlbinfo_ecx
931: .globl _tlbinfo_edx
932:
933: _cputype:      .int    0
934: _cpusignature: .int    0
935: _cpuflags:     .int    0
936: _fpstatus:     .int    0
937: _brandid:      .int    0

```

kernel/core386.S

Page 15/15

```
938:  _vendorid:    .fill  13,1,0
939:  _brandstr:    .fill  49,1,0
940:  _tlbinfo_eax: .int    0
941:  _tlbinfo_ebx: .int    0
942:  _tlbinfo_ecx: .int    0
943:  _tlbinfo_edx: .int    0
```

kernel/cpu.c

Page 1/5

```

1: /*
2:  * fiwix/kernel/cpu.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/kernel.h>
10: #include <fiwix/utsname.h>
11: #include <fiwix/pic.h>
12: #include <fiwix/pit.h>
13: #include <fiwix/cpu.h>
14: #include <fiwix/timer.h>
15: #include <fiwix/stdio.h>
16: #include <fiwix/string.h>
17:
18: char UTS_MACHINE[_UTSNAME_LENGTH];
19:
20: static struct cpu_type intel[] = {
21:     { 4,
22:       { "i486 DX", "i486 DX", "i486 SX", "i486 DX/2",
23:         "i486 SL", "i486 SX/2", NULL, "i486 DX/2 WBE",
24:         "i486 DX/4", NULL, NULL, NULL, NULL, NULL, NULL, NULL }
25:     },
26:     { 5,
27:       { NULL, "Pentium 60/66", "Pentium 75-200", "Pentium ODfor486",
28:         "PentiumMMX", NULL, NULL, NULL, NULL, NULL, NULL, NULL, NULL,
29:         NULL, NULL, NULL }
30:     },
31:     { 6,
32:       { NULL, "Pentium Pro", NULL, "Pentium II", NULL, "Pentium II",
33:         "Intel Celeron", "Pentium III", "Pentium III", NULL,
34:         "Pentium III Xeon", "Pentium III", NULL, NULL, NULL, NULL }
35:     }
36: };
37:
38: static const char *cpu_flags[] = {
39:     "FPU", "VME", "DE", "PSE", "TSC", "MSR", "PAE", "MCE", "CX8", "APIC",
40:     "10", "SEP", "MTRR", "PGE", "MCA", "CMOV", "PAT", "PSE-36", "PSN",
41:     "CLFSH", "20", "DS", "ACPI", "MMX", "FXSR", "SSE", "SSE2", "SS",
42:     "HTT", "TM", "30", "PBE"
43: };
44:
45: static unsigned long int detect_cpuspeed(void)
46: {
47:     unsigned long long int tsc1, tsc2;
48:
49:     outport_b(MODEREG, SEL_CHAN2 | LSB_MSB | TERM_COUNT | BINARY_CTR);
50:     outport_b(CHANNEL2, (OSCIL / HZ) & 0xFF);
51:     outport_b(CHANNEL2, (OSCIL / HZ) >> 8);
52:     outport_b(PS2_SYSCTRL_B, inport_b(PS2_SYSCTRL_B) | ENABLE_SDATA | ENABLE
_TMR2G);
53:
54:     tsc1 = 0;
55:     tsc1 = get_rdtsc();
56:
57:     while(!(inport_b(PS2_SYSCTRL_B) & 0x20));
58:
59:     tsc2 = 0;
60:     tsc2 = get_rdtsc();
61:
62:     outport_b(PS2_SYSCTRL_B, inport_b(PS2_SYSCTRL_B) & ~(ENABLE_SDATA | ENAB
LE_TMR2G));
63:
64:     return (tsc2 - tsc1) * HZ;
65: }

```

kernel/cpu.c

Page 2/5

```

66:
67: /*
68:  * These are the 2nd and 3rd level cache values according to Intel Processor
69:  * Identification and the CPUID Instruction.
70:  * Application Note 485. Document Number: 241618-031. September 2006.
71:  */
72: static void show_cache(int value)
73: {
74:     switch(value) {
75:         /* 2nd level cache */
76:         case 0x39:
77:         case 0x3B:
78:         case 0x41:
79:         case 0x79:
80:             cpu_table.cache = "128KB L2";
81:             break;
82:         case 0x3A:
83:             cpu_table.cache = "192KB L2";
84:             break;
85:         case 0x3C:
86:         case 0x42:
87:         case 0x7A:
88:         case 0x82:
89:             cpu_table.cache = "256KB L2";
90:             break;
91:         case 0x3D:
92:             cpu_table.cache = "384KB L2";
93:             break;
94:         case 0x3E:
95:         case 0x43:
96:         case 0x7B:
97:         case 0x7F:
98:         case 0x83:
99:         case 0x86:
100:            cpu_table.cache = "512KB L2";
101:            break;
102:         case 0x44:
103:         case 0x78:
104:         case 0x7C:
105:         case 0x84:
106:         case 0x87:
107:            cpu_table.cache = "1MB L2";
108:            break;
109:         case 0x45:
110:         case 0x7D:
111:         case 0x85:
112:            cpu_table.cache = "2MB L2";
113:            break;
114:
115:         /* 3rd level cache */
116:         case 0x22:
117:             cpu_table.cache = "512KB L3";
118:             break;
119:         case 0x23:
120:             cpu_table.cache = "1MB L3";
121:             break;
122:         case 0x25:
123:             cpu_table.cache = "2MB L3";
124:             break;
125:         case 0x29:
126:         case 0x46:
127:             cpu_table.cache = "4MB L3";
128:             break;
129:         case 0x49:
130:             cpu_table.cache = "4MB L3 & L2";
131:             break;
132:         case 0x4A:

```

kernel/cpu.c

Page 3/5

```

133:             cpu_table.cache = "6MB L3";
134:             break;
135:         case 0x47:
136:         case 0x4B:
137:             cpu_table.cache = "8MB L3";
138:             break;
139:         case 0x4C:
140:             cpu_table.cache = "12MB L3";
141:             break;
142:         case 0x4D:
143:             cpu_table.cache = "16MB L3";
144:             break;
145:         default:
146:             break;
147:     }
148: }
149:
150: static void check_cache(int maxcpuid)
151: {
152:     int n, maxcpuids;
153:
154:     maxcpuids = 1;
155:     if(maxcpuid >= 2) {
156:         for(n = 0; n < maxcpuids; n++) {
157:             tlbinfo();
158:             maxcpuids = _tlbinfo_eax & 0xFF;
159:             show_cache((_tlbinfo_eax >> 8) & 0xFF);
160:             show_cache((_tlbinfo_eax >> 16) & 0xFF);
161:             show_cache((_tlbinfo_eax >> 24) & 0xFF);
162:             if(!(_tlbinfo_ebx & RESERVED_DESC)) {
163:                 show_cache(_tlbinfo_ebx & 0xFF);
164:                 show_cache((_tlbinfo_ebx >> 8) & 0xFF);
165:                 show_cache((_tlbinfo_ebx >> 16) & 0xFF);
166:                 show_cache((_tlbinfo_ebx >> 24) & 0xFF);
167:             }
168:             if(!(_tlbinfo_ecx & RESERVED_DESC)) {
169:                 show_cache(_tlbinfo_ecx & 0xFF);
170:                 show_cache((_tlbinfo_ecx >> 8) & 0xFF);
171:                 show_cache((_tlbinfo_ecx >> 16) & 0xFF);
172:                 show_cache((_tlbinfo_ecx >> 24) & 0xFF);
173:             }
174:             if(!(_tlbinfo_edx & RESERVED_DESC)) {
175:                 show_cache(_tlbinfo_edx & 0xFF);
176:                 show_cache((_tlbinfo_edx >> 8) & 0xFF);
177:                 show_cache((_tlbinfo_edx >> 16) & 0xFF);
178:                 show_cache((_tlbinfo_edx >> 24) & 0xFF);
179:             }
180:         }
181:     }
182: }
183:
184: int get_cpu_flags(char *buffer, int offset)
185: {
186:     int n, size;
187:     unsigned int mask;
188:
189:     size = sprintf(buffer + offset, "flags          :");
190:     for(n = 0, mask = 1; n < 32; n++, mask <=< 1) {
191:         if(_cpuflags & mask) {
192:             size += sprintf(buffer + offset + size, " %s", cpu_flags
[n]);
193:         }
194:     }
195:     size += sprintf(buffer + offset + size, "\n");
196:     return size;
197: }
198:

```


kernel/cpu.c

Page 5/5

```
259:             printk("80%d86\n", cpu_table.family);
260:             cpu_table.has_cpuid = 0;
261:         }
262:         cpu_table.has_fpu = getfpu();
263: }
```

kernel/gdt.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/gdt.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/const.h>
10: #include <fiwix/types.h>
11: #include <fiwix/segments.h>
12: #include <fiwix/process.h>
13: #include <fiwix/limits.h>
14: #include <fiwix/string.h>
15:
16: struct seg_desc gdt[NR_GDT_ENTRIES];
17:
18: struct desc_r gdtr = {
19:     sizeof(gdt) - 1,
20:     (unsigned int)&gdt
21: };
22:
23: static void gdt_set_entry(int num, unsigned int base_addr, unsigned int limit, c
har loflags, char hiflags)
24: {
25:     num /= sizeof(struct seg_desc);
26:     gdt[num].sd_lolimit = limit & 0xFFFF;
27:     gdt[num].sd_lobase = base_addr & 0xFFFFFFFF;
28:     gdt[num].sd_loflags = loflags;
29:     gdt[num].sd_hilimit = (limit >> 16) & 0x0F;
30:     gdt[num].sd_hiflags = hiflags;
31:     gdt[num].sd_hibase = (base_addr >> 24) & 0xFF;
32: }
33:
34: void gdt_init(void)
35: {
36:     unsigned char loflags;
37:
38:     gdt_set_entry(0, 0, 0, 0, 0); /* null descriptor */
39:
40:     loflags = SD_CODE | SD_CD | SD_DPL0 | SD_PRESENT;
41:     gdt_set_entry(KERNEL_CS, 0, 0xFFFFFFFF, loflags, SD_OPSIZE32 | SD_PAGE4K
B);
42:     loflags = SD_DATA | SD_CD | SD_DPL0 | SD_PRESENT;
43:     gdt_set_entry(KERNEL_DS, 0, 0xFFFFFFFF, loflags, SD_OPSIZE32 | SD_PAGE4K
B);
44:
45:     loflags = SD_CODE | SD_CD | SD_DPL3 | SD_PRESENT;
46:     gdt_set_entry(USER_CS, 0, 0xFFFFFFFF, loflags, SD_OPSIZE32 | SD_PAGE4KB)
;
47:     loflags = SD_DATA | SD_CD | SD_DPL3 | SD_PRESENT;
48:     gdt_set_entry(USER_DS, 0, 0xFFFFFFFF, loflags, SD_OPSIZE32 | SD_PAGE4KB)
;
49:
50:     loflags = SD_TSSPRESENT;
51:     gdt_set_entry(TSS, 0, sizeof(struct proc) - 1, loflags, SD_OPSIZE32);
52:
53:     load_gdt((unsigned int)&gdtr);
54: }

```

kernel/idt.c

Page 1/2

```

1: /*
2:  * fiwix/kernel/idt.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/const.h>
10: #include <fiwix/types.h>
11: #include <fiwix/segments.h>
12: #include <fiwix/string.h>
13:
14: struct gate_desc idt[NR_IDT_ENTRIES];
15:
16: struct desc_r idtr = {
17:     sizeof(idt) - 1,
18:     (unsigned int)idt
19: };
20:
21: static void set_idt_entry(int num, __off_t handler, unsigned int flags)
22: {
23:     idt[num].gd_looffset = handler & 0x0000FFFF;
24:     idt[num].gd_selector = KERNEL_CS;
25:     idt[num].gd_flags = flags << 8;
26:     idt[num].gd_hioffset = handler >> 16;
27: }
28:
29: void idt_init(void)
30: {
31:     int n;
32:
33:     memset_b(idt, NULL, sizeof(idt));
34:     for(n = 0; n < NR_IDT_ENTRIES; n++) {
35:         set_idt_entry(n, (__off_t)&unknown_irq, SD_32INTRGATE | SD_PRESE
NT);
36:     }
37:
38:     /* FIXME: must be SD_32TRAPGATE for true multitasking */
39:     set_idt_entry(0x00, (__off_t)&except0, SD_32INTRGATE | SD_PRESENT);
40:     set_idt_entry(0x01, (__off_t)&except1, SD_32INTRGATE | SD_PRESENT);
41:     set_idt_entry(0x02, (__off_t)&except2, SD_32INTRGATE | SD_PRESENT);
42:     set_idt_entry(0x03, (__off_t)&except3, SD_32INTRGATE | SD_PRESENT);
43:     set_idt_entry(0x04, (__off_t)&except4, SD_32INTRGATE | SD_PRESENT);
44:     set_idt_entry(0x05, (__off_t)&except5, SD_32INTRGATE | SD_PRESENT);
45:     set_idt_entry(0x06, (__off_t)&except6, SD_32INTRGATE | SD_PRESENT);
46:     set_idt_entry(0x07, (__off_t)&except7, SD_32INTRGATE | SD_PRESENT);
47:     set_idt_entry(0x08, (__off_t)&except8, SD_32INTRGATE | SD_PRESENT);
48:     set_idt_entry(0x09, (__off_t)&except9, SD_32INTRGATE | SD_PRESENT);
49:     set_idt_entry(0x0A, (__off_t)&exceptA, SD_32INTRGATE | SD_PRESENT);
50:     set_idt_entry(0x0B, (__off_t)&exceptB, SD_32INTRGATE | SD_PRESENT);
51:     set_idt_entry(0x0C, (__off_t)&exceptC, SD_32INTRGATE | SD_PRESENT);
52:     set_idt_entry(0x0D, (__off_t)&exceptD, SD_32INTRGATE | SD_PRESENT);
53:     set_idt_entry(0x0E, (__off_t)&exceptE, SD_32INTRGATE | SD_PRESENT);
54:     set_idt_entry(0x0F, (__off_t)&exceptF, SD_32INTRGATE | SD_PRESENT);
55:     set_idt_entry(0x10, (__off_t)&except10, SD_32INTRGATE | SD_PRESENT);
56:     set_idt_entry(0x11, (__off_t)&except11, SD_32INTRGATE | SD_PRESENT);
57:     set_idt_entry(0x12, (__off_t)&except12, SD_32INTRGATE | SD_PRESENT);
58:     set_idt_entry(0x13, (__off_t)&except13, SD_32INTRGATE | SD_PRESENT);
59:     set_idt_entry(0x14, (__off_t)&except14, SD_32INTRGATE | SD_PRESENT);
60:     set_idt_entry(0x15, (__off_t)&except15, SD_32INTRGATE | SD_PRESENT);
61:     set_idt_entry(0x16, (__off_t)&except16, SD_32INTRGATE | SD_PRESENT);
62:     set_idt_entry(0x17, (__off_t)&except17, SD_32INTRGATE | SD_PRESENT);
63:     set_idt_entry(0x18, (__off_t)&except18, SD_32INTRGATE | SD_PRESENT);
64:     set_idt_entry(0x19, (__off_t)&except19, SD_32INTRGATE | SD_PRESENT);
65:     set_idt_entry(0x1A, (__off_t)&except1A, SD_32INTRGATE | SD_PRESENT);
66:     set_idt_entry(0x1B, (__off_t)&except1B, SD_32INTRGATE | SD_PRESENT);

```

kernel/idt.c

Page 2/2

```

67:     set_idt_entry(0x1C, (__off_t)&except1C, SD_32INTRGATE | SD_PRESENT);
68:     set_idt_entry(0x1D, (__off_t)&except1D, SD_32INTRGATE | SD_PRESENT);
69:     set_idt_entry(0x1E, (__off_t)&except1E, SD_32INTRGATE | SD_PRESENT);
70:     set_idt_entry(0x1F, (__off_t)&except1F, SD_32INTRGATE | SD_PRESENT);
71:
72:     set_idt_entry(0x20, (__off_t)&irq0, SD_32INTRGATE | SD_PRESENT);
73:     set_idt_entry(0x21, (__off_t)&irq1, SD_32INTRGATE | SD_PRESENT);
74:     set_idt_entry(0x22, (__off_t)&irq2, SD_32INTRGATE | SD_PRESENT);
75:     set_idt_entry(0x23, (__off_t)&irq3, SD_32INTRGATE | SD_PRESENT);
76:     set_idt_entry(0x24, (__off_t)&irq4, SD_32INTRGATE | SD_PRESENT);
77:     set_idt_entry(0x25, (__off_t)&irq5, SD_32INTRGATE | SD_PRESENT);
78:     set_idt_entry(0x26, (__off_t)&irq6, SD_32INTRGATE | SD_PRESENT);
79:     set_idt_entry(0x27, (__off_t)&irq7, SD_32INTRGATE | SD_PRESENT);
80:     set_idt_entry(0x28, (__off_t)&irq8, SD_32INTRGATE | SD_PRESENT);
81:     set_idt_entry(0x29, (__off_t)&irq9, SD_32INTRGATE | SD_PRESENT);
82:     set_idt_entry(0x2A, (__off_t)&irq10, SD_32INTRGATE | SD_PRESENT);
83:     set_idt_entry(0x2B, (__off_t)&irq11, SD_32INTRGATE | SD_PRESENT);
84:     set_idt_entry(0x2C, (__off_t)&irq12, SD_32INTRGATE | SD_PRESENT);
85:     set_idt_entry(0x2D, (__off_t)&irq13, SD_32INTRGATE | SD_PRESENT);
86:     set_idt_entry(0x2E, (__off_t)&irq14, SD_32INTRGATE | SD_PRESENT);
87:     set_idt_entry(0x2F, (__off_t)&irq15, SD_32INTRGATE | SD_PRESENT);
88:
89:     /* FIXME: must be SD_32TRAPGATE for true multitasking */
90:     set_idt_entry(0x80, (__off_t)&syscall, SD_32INTRGATE | SD_DPL3 | SD_PRESENT);
ENT);
91:
92:     load_idt((unsigned int)&idtr);
93: }

```

kernel/init.c

```

1: /*
2:  * fiwix/kernel/init.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/kernel.h>
10: #include <fiwix/system.h>
11: #include <fiwix/mm.h>
12: #include <fiwix/timer.h>
13: #include <fiwix/sched.h>
14: #include <fiwix/fcntl.h>
15: #include <fiwix/stat.h>
16: #include <fiwix/process.h>
17: #include <fiwix/syscalls.h>
18: #include <fiwix/unistd.h>
19: #include <fiwix/stdio.h>
20: #include <fiwix/string.h>
21:
22: #define INIT_TRAMPOLINE_SIZE    128    /* max. size of init_trampoline() */
23:
24: char *init_argv[] = { "init", NULL };
25: char *init_envp[] = { "HOME=/", "TERM=linux", NULL };
26:
27: static void init_trampoline(void)
28: {
29:     USER_SYSCALL(SYS_open, "/dev/console", O_RDWR, 0);    /* stdin */
30:     USER_SYSCALL(SYS_dup, 0, NULL, NULL);                  /* stdout */
31:     USER_SYSCALL(SYS_dup, 0, NULL, NULL);                  /* stderr */
32:     USER_SYSCALL(SYS_execve, INIT_PROGRAM, init_argv, init_envp);
33:
34:     /* only reached in case of error in sys_execve() */
35:     USER_SYSCALL(SYS_exit, NULL, NULL, NULL);
36: }
37:
38: void init_init(void)
39: {
40:     int n;
41:     unsigned int page;
42:     struct inode *i;
43:     unsigned int *pgdir;
44:     struct proc *init;
45:
46:     if(namei(INIT_PROGRAM, &i, NULL, FOLLOW_LINKS)) {
47:         PANIC("can't find %s.\n", INIT_PROGRAM);
48:     }
49:     if(!S_ISREG(i->i_mode)) {
50:         PANIC("%s is not a regular file.\n", INIT_PROGRAM);
51:     }
52:     iput(i);
53:
54:     /* INIT slot was already created in main.c */
55:     init = &proc_table[INIT];
56:
57:     /* INIT process starts with the current (kernel) Page Directory */
58:     if(!(pgdir = (void *)kmalloc())) {
59:         goto init_init__die;
60:     }
61:     init->rss++;
62:     memcpy_b(pgdir, kpage_dir, PAGE_SIZE);
63:     init->tss.cr3 = V2P((unsigned int)pgdir);
64:
65:     if(!(init->vma = (void *)kmalloc())) {
66:         goto init_init__die;
67:     }

```

kernel/init.c

Page 2/2

```

68:         init->rss++;
69:         memset_b(init->vma, NULL, PAGE_SIZE);
70:
71:         init->ppid = 0;
72:         init->pgid = 0;
73:         init->sid = 0;
74:         init->flags = 0;
75:         init->children = 0;
76:         init->priority = DEF_PRIORITY;
77:         init->start_time = CURRENT_TIME;
78:         init->sleep_address = NULL;
79:         init->uid = init->gid = 0;
80:         init->euid = init->egid = 0;
81:         init->suid = init->sgid = 0;
82:         memset_b(init->fd, NULL, sizeof(init->fd));
83:         memset_b(init->fd_flags, NULL, sizeof(init->fd_flags));
84:         init->root = current->root;
85:         init->pwd = current->pwd;
86:         strcpy(init->argv0, init_argv[0]);
87:         sprintfk(init->pidstr, "%d", init->pid);
88:         init->sigpending = 0;
89:         init->sigblocked = 0;
90:         init->sigexecuting = 0;
91:         memset_b(init->sigaction, NULL, sizeof(init->sigaction));
92:         memset_b(&init->usage, NULL, sizeof(struct rusage));
93:         memset_b(&init->cusage, NULL, sizeof(struct rusage));
94:         init->timeout = 0;
95:         for(n = 0; n < RLIM_NLIMITS; n++) {
96:             init->rlim[n].rlim_cur = init->rlim[n].rlim_max = RLIM_INFINITY;
97:         }
98:         init->rlim[RLIMIT_NOFILE].rlim_cur = OPEN_MAX;
99:         init->rlim[RLIMIT_NOFILE].rlim_max = NR_OPENS;
100:        init->rlim[RLIMIT_NPROC].rlim_cur = CHILD_MAX;
101:        init->rlim[RLIMIT_NPROC].rlim_max = NR_PROCS;
102:        init->umask = 0022;
103:
104:        /* setup the stack */
105:        if(!(init->tss.esp0 = kmalloc())) {
106:            goto init_init_die;
107:        }
108:        init->tss.esp0 += PAGE_SIZE - 4;
109:        init->rss++;
110:        init->tss.ss0 = KERNEL_DS;
111:
112:        /* setup the init_trampoline */
113:        page = map_page(init, KERNEL_BASE_ADDR - PAGE_SIZE, 0, PROT_READ | PROT_
WRITE);
114:        memcpy_b((void *)page, init_trampoline, INIT_TRAMPOLINE_SIZE);
115:
116:        init->tss.eip = (unsigned int)switch_to_user_mode;
117:        init->tss.esp = page + PAGE_SIZE - 4;
118:
119:        init->state = PROC_RUNNING;
120:        nr_processes++;
121:        return;
122:
123:    init_init_die:
124:        PANIC("unable to run init process.\n");
125:    }

```

kernel/main.c

Page 1/6

```

1: /*
2:  * fiwix/kernel/main.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/kernel.h>
10: #include <fiwix/mm.h>
11: #include <fiwix/system.h>
12: #include <fiwix/timer.h>
13: #include <fiwix/sched.h>
14: #include <fiwix/sleep.h>
15: #include <fiwix/cpu.h>
16: #include <fiwix/pic.h>
17: #include <fiwix/fs.h>
18: #include <fiwix/devices.h>
19: #include <fiwix/console.h>
20: #include <fiwix/keyboard.h>
21: #include <fiwix/ramdisk.h>
22: #include <fiwix/version.h>
23: #include <fiwix/limits.h>
24: #include <fiwix/segments.h>
25: #include <fiwix/syscalls.h>
26: #include <fiwix/stdio.h>
27: #include <fiwix/string.h>
28: #include <fiwix/kparms.h>
29: #include <fiwix/i386elf.h>
30: #include <fiwix/bios.h>
31:
32: /*
33:  * check if the bit BIT in Multiboot FLAGS is set
34:  * -----
35:  * bit 11 -> vbe_*
36:  * bit 10 -> apm_table
37:  * bit 9 -> boot_loader_name
38:  * bit 8 -> config_table
39:  * bit 7 -> drives_length and drives_addr
40:  * bit 6 -> mmap_length and mmap_addr
41:  * bit 5 -> ELF symbols
42:  * bit 4 -> a.out symbols
43:  * bit 3 -> mods_count and mods_addr
44:  * bit 2 -> cmdline
45:  * bit 1 -> boot_device
46:  * bit 0 -> mem_lower and mem_upper values
47:  */
48: #define CHECK_FLAG(flags,bit) ((flags) & (1 << (bit)))
49:
50: Elf32_Shdr *symtab, *strtab;
51: unsigned int _last_data_addr;
52: int _memsize;
53: int _extmemsize;
54: int _rootdev;
55: int _noramdisk;
56: int _ramdisksize;
57: char _rootfstype[10];
58: char _rootdevname[DEVNAME_MAX + 1];
59: int _syscondev;
60:
61: char cmdline[NAME_MAX + 1];
62:
63: struct new_utsname sys_utsname = {
64:     UTS_SYSNAME,
65:     UTS_NODENAME,
66:     UTS_RELEASE,
67:     UTS_VERSION,

```


kernel/main.c

Page 2/6

```

68:         "",
69:         UTS_DOMAINNAME,
70:     };
71:
72:     struct kernel_stat kstat;
73:
74:     /*
75:      * This function returns the last address used by kernel symbols. This is
76:      * intended to setup the kernel stack beyond this address.
77:      */
78:     unsigned int get_last_elf_addr(unsigned int info)
79:     {
80:         multiboot_info_t *info_boot;
81:         Elf32_Shdr *shdr;
82:         elf_section_header_table_t *hdr;
83:         unsigned short int n;
84:
85:         symtab = strtab = NULL;
86:         info_boot = (multiboot_info_t *)info;
87:         hdr = &(info_boot->u.elf_sec);
88:         for(n = 0; n < hdr->num; n++) {
89:             shdr = (Elf32_Shdr *) (hdr->addr + (n * hdr->size));
90:             if(shdr->sh_type == SHT_SYMTAB) {
91:                 symtab = shdr;
92:             }
93:             if(shdr->sh_type == SHT_STRTAB) {
94:                 strtab = shdr;
95:             }
96:         }
97:         return P2V((strtab->sh_addr + strtab->sh_size));
98:     }
99:
100:     /* check the validity of a command line parameter */
101:     static int check_parm(struct kparms *parm, const char *value)
102:     {
103:         int n;
104:
105:         if(!strcmp(parm->name, "root=")) {
106:             for(n = 0; parm->value[n]; n++) {
107:                 if(!strcmp(parm->value[n], value)) {
108:                     _rootdev = parm->sysval[n];
109:                     strncpy(_rootdevname, value, DEVNAME_MAX);
110:                     return 0;
111:                 }
112:             }
113:             return 1;
114:         }
115:         if(!strcmp(parm->name, "noramdisk")) {
116:             _noramdisk = 1;
117:             return 0;
118:         }
119:         if(!strcmp(parm->name, "ramdisksize=")) {
120:             int size = atoi(value);
121:             if(!size || size > RAMDISK_MAXSIZE) {
122:                 printk("WARNING: 'ramdisksize' value is out of limits, d
efaulting to 4096KB.\n");
123:                 _ramdisksize = 0;
124:             } else {
125:                 _ramdisksize = size;
126:             }
127:             return 0;
128:         }
129:         if(!strcmp(parm->name, "rootfstype=")) {
130:             for(n = 0; parm->value[n]; n++) {
131:                 if(!strcmp(parm->value[n], value)) {
132:                     strncpy(_rootfstype, value, sizeof(_rootfstype))
;

```

kernel/main.c

Page 3/6

```

133:                                     return 0;
134:                                     }
135:                                 }
136:                                 return 1;
137: }
138: if(!strcmp(parm->name, "console=")) {
139:     for(n = 0; parm->value[n]; n++) {
140:         if(!strcmp(parm->value[n], value)) {
141:             _syscondev = parm->sysval[n];
142:             return 0;
143:         }
144:     }
145:     return 1;
146: }
147: printk("WARNING: the parameter '%s' looks valid but it's not defined!\n"
, parm->name);
148: return 0;
149: }
150:
151: static void parse_arg(const char *arg)
152: {
153:     int n;
154:     char *str;
155:
156:     str = (char *)arg;
157:     while(*(str++)) {
158:         if(*str == ' ') {
159:             return;
160:         }
161:     }
162:
163:     for(n = 0; parm_table[n].name; n++) {
164:         if(!strncmp(arg, parm_table[n].name, strlen(parm_table[n].name))
) {
165:             arg += strlen(parm_table[n].name);
166:             if(check_parm(&parm_table[n], arg)) {
167:                 printk("WARNING: invalid value '%s' in the '%s'
parameter.\n", arg, parm_table[n].name);
168:             }
169:             return;
170:         }
171:     }
172:     printk("WARNING: invalid cmdline parameter: '%s'.\n", arg);
173: }
174:
175: static void parse_cmdline(const char *str)
176: {
177:     char *from, *to;
178:     char arg[CMDL_ARG_LEN];
179:     char c;
180:
181:     from = to = (char *)str;
182:     for(;;) {
183:         c = *(str++);
184:         if(c == ' ' || !c) {
185:             if(to - from < CMDL_ARG_LEN) {
186:                 memcpy_b(arg, from, to - from);
187:                 arg[to - from] = NULL;
188:                 if(arg[0] != NULL) {
189:                     parse_arg(arg);
190:                 }
191:             } else {
192:                 memcpy_b(arg, from, CMDL_ARG_LEN);
193:                 arg[CMDL_ARG_LEN - 1] = NULL;
194:                 printk("WARNING: invalid length of the cmdline p
arameter '%s'.\n", arg);
195:             }

```

kernel/main.c

Page 4/6

```

196:         from = ++to;
197:         if(!c) {
198:             break;
199:         }
200:         continue;
201:     }
202:     to++;
203: }
204: }
205:
206: void start_kernel(unsigned long magic, unsigned long info, unsigned int stack)
207: {
208:     struct proc *init, *p_kswapd;
209:     multiboot_info_t mbi;
210:
211:     /* default kernel values */
212:     strcpy(_rootfstype, "minix"); /* filesystem is minix */
213:     _syscondev = MKDEV(VCONSOLES_MAJOR, 0); /* console is /dev/tty0 */
214:
215:     pic_init();
216:     idt_init();
217:     dev_init();
218:     tty_init();
219:
220:     printk("                                Welcome to %s\n", UTS_SYSNAME);
221:     printk("                                Copyright (c) 2018, Jordi Sanfeliu\n");
222:     printk("\n");
223:     printk("                                kernel v%s for i386 architecture\n", UTS_R
RELEASE);
224:     printk("                                (GCC %s, built on %s)\n", __VERSION__, UTS_VERSIO
N);
225:     printk("\n");
226:     printk("DEVICE      ADDRESS      IRQ      COMMENT\n");
227:     printk("-----\n");
228:
229:     if(magic != MULTIBOOT_BOOTLOADER_MAGIC) {
230:         printk("WARNING: invalid multiboot-bootloader magic number: 0x%x
.\n\n", (unsigned long)magic);
231:         memset_b(&mbi, NULL, sizeof(struct multiboot_info));
232:     } else {
233:         memcpy_b(&mbi, (void *)info, sizeof(struct multiboot_info));
234:     }
235:
236:     memset_b(&kstat, NULL, sizeof(kstat));
237:
238:     cpu_init();
239:
240:     /* check if a command line was supplied */
241:     if(CHECK_FLAG(mbi.flags, 2)) {
242:         int n, len;
243:         char c;
244:         char *p;
245:
246:         p = (char *)mbi.cmdline;
247:         len = strlen(p);
248:         /* suppress 'fiwix' */
249:         for(n = 0; n < len; n++) {
250:             c = *(p++);
251:             if(c == ' ') {
252:                 break;
253:             }
254:         }
255:         strcpy(cmdline, p);
256:         parse_cmdline(cmdline);
257:     } else {
258:         printk("WARNING: no cmdline detected!\n");

```

kernel/main.c

Page 5/6

```

259:         }
260:
261:         printk("kernel    0x%08X    -    cmdline='%s'\n", KERNEL_ENTRY_ADDR,
cmdline);
262:
263:         timer_init();
264:         vconsole_init();
265:         keyboard_init();
266:
267:         if(!CHECK_FLAG(mbi.flags, 0)) {
268:             printk("WARNING: values in mem_lower and mem_upper are not valid
!\n");
269:         }
270:         _memsize = (unsigned int)mbi.mem_lower;
271:         _extmemsize = (unsigned int)mbi.mem_upper;
272:
273:         if(CHECK_FLAG(mbi.flags, 6)) {
274:             bios_map_init((memory_map_t *)mbi.mmap_addr, mbi.mmap_length);
275:         } else {
276:             bios_map_init(NULL, 0);
277:         }
278:
279:         _last_data_addr = stack - KERNEL_BASE_ADDR;
280:         mem_init();
281:         proc_init();
282:
283:         if(!(CHECK_FLAG(mbi.flags, 5))) {
284:             printk("WARNING: ELF section header table is not valid!\n");
285:         }
286:
287:         /* IDLE is now the current process */
288:         set_tss(current);
289:         load_tr(TSS);
290:         current->tss.cr3 = (unsigned int)kpage_dir;
291:         current->flags |= PF_KPROC;
292:
293:         /* reserve the slot 1 for the INIT process */
294:         init = get_proc_free();
295:         proc_slot_init(init);
296:         init->pid = get_unused_pid();
297:
298:         /* create and setup kswapd process */
299:         p_kswapd = kernel_process(kswapd);
300:
301:         /* kswapd will take over the rest of the kernel initialization */
302:         p_kswapd->state = PROC_RUNNING;
303:         need_resched = 1;
304:
305:         STI();          /* let's rock! */
306:         cpu_idle();
307:     }
308:
309:     void stop_kernel(void)
310:     {
311:         struct proc *p;
312:
313:         printk("\n");
314:         printk("***    Safe to Power Off    **\n");
315:         printk("    -or-\n");
316:         printk("*** Press Any Key to Reboot **\n");
317:         any_key_to_reboot = 1;
318:
319:         /* put all processes to sleep and reset all pending signals */
320:         FOR_EACH_PROCESS(p) {
321:             p->state = PROC_SLEEPING;
322:             p->sigpending = 0;
323:         }

```

```
324:
325:     /* TODO: disable all interrupts */
326:     CLI();
327:     disable_irq(TIMER_IRQ);
328:
329:     /* switch to IDLE process */
330:     if(current) {
331:         do_sched();
332:     }
333:
334:     STI();
335:     enable_irq(KEYBOARD_IRQ);
336:     cpu_idle();
337: }
```

kernel/Makefile

Page 1/1

```
1: # fiwix/kernel/Makefile
2: #
3: # Copyright 2018, Jordi Sanfeliu. All rights reserved.
4: # Distributed under the terms of the Fiwix License.
5: #
6: #
7: .S.o:
8:     $(CC) -traditional -I$(INCLUDE) -c -o $@ $<
9: .c.o:
10:     $(CC) $(CFLAGS) -c -o $@ $<
11:
12: OBJS = boot.o core386.o main.o init.o gdt.o idt.o syscalls.o pic.o pit.o \
13:     traps.o cpu.o cmos.o timer.o sched.o sleep.o signal.o process.o
14:
15: kernel: $(OBJS)
16:     $(LD) $(LDFLAGS) -r $(OBJS) -o kernel.o
17:
18: clean:
19:     rm -f *.o
20:
```

kernel/pic.c

Page 1/5

```

1: /*
2:  * fiwix/kernel/pic.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/kernel.h>
10: #include <fiwix/config.h>
11: #include <fiwix/limits.h>
12: #include <fiwix/errno.h>
13: #include <fiwix/pic.h>
14: #include <fiwix/stdio.h>
15: #include <fiwix/string.h>
16: #include <fiwix/sigcontext.h>
17:
18: /* interrupt vector base addresses */
19: #define IRQ0_ADDR      0x20
20: #define IRQ8_ADDR     0x28
21:
22: /*
23:  * pic.c implements a bottom half table using a singly linked list.
24:  *
25:  *   head                                     tail
26:  * +-----+ +-----+ ... +-----+
27:  * |data|next| |data|next| ... |data|next|
28:  * |   |   --> |   |   --> ... |   |   /   |
29:  * +-----+ +-----+ ... +-----+
30:  *   (bh)         (bh)         (bh)
31:  */
32:
33: struct bh bh_pool[NR_BH];
34: struct bh *bh_pool_head;
35: struct bh *bh_head;
36: struct bh *bh_tail;
37:
38: static struct bh *get_free_bh(void)
39: {
40:     struct bh *new;
41:
42:     new = NULL;
43:     if(bh_pool_head) {
44:         new = bh_pool_head;
45:         bh_pool_head = bh_pool_head->next;
46:         new->next = NULL;
47:     }
48:     return new;
49: }
50:
51: static void put_free_bh(struct bh *old)
52: {
53:     old->next = bh_pool_head;
54:     bh_pool_head = old;
55: }
56:
57: /*
58:  * This sends the command OCW3 to PIC (master or slave) to obtain the register
59:  * values. Slave is chained and represents IRQs 8-15. Master represents IRQs
60:  * 0-7, with IRQ 2 being the chain.
61:  */
62: static unsigned short int pic_get_irq_reg(int ocw3)
63: {
64:     outport_b(PIC_MASTER, ocw3);
65:     outport_b(PIC_SLAVE, ocw3);
66:     return (inport_b(PIC_SLAVE) << 8) | inport_b(PIC_MASTER);
67: }

```

kernel/pic.c

Page 2/5

```

68:
69: void add_bh(void (*fn)(void))
70: {
71:     unsigned long int flags;
72:     struct bh *b;
73:
74:     SAVE_FLAGS(flags); CLI();
75:
76:     if(!(b = get_free_bh())) {
77:         RESTORE_FLAGS(flags);
78:         PANIC("no more bottom half slots!\n");
79:     }
80:
81:     /* initialize bh */
82:     memset_b(b, NULL, sizeof(struct bh));
83:     b->fn = fn;
84:
85:     if(!bh_tail) {
86:         bh_head = bh_tail = b;
87:     } else {
88:         bh_tail->next = b;
89:         bh_tail = b;
90:     }
91:
92:     RESTORE_FLAGS(flags);
93:     return;
94: }
95:
96: void del_bh(void)
97: {
98:     unsigned long int flags;
99:     struct bh *b;
100:
101:     if(!bh_head) {
102:         return;
103:     }
104:
105:     SAVE_FLAGS(flags); CLI();
106:
107:     b = bh_head;
108:     if(bh_head == bh_tail) {
109:         bh_head = bh_tail = NULL;
110:     } else {
111:         bh_head = bh_head->next;
112:     }
113:     put_free_bh(b);
114:
115:     RESTORE_FLAGS(flags);
116:     return;
117: }
118:
119: void enable_irq(int irq)
120: {
121:     int addr;
122:
123:     addr = (irq > 7) ? PIC_SLAVE + DATA : PIC_MASTER + DATA;
124:     irq &= 0x0007;
125:
126:     outport_b(addr, inport_b(addr) & ~(1 << irq));
127: }
128:
129: void disable_irq(int irq)
130: {
131:     int addr;
132:
133:     addr = (irq > 7) ? PIC_SLAVE + DATA : PIC_MASTER + DATA;
134:     irq &= 0x0007;

```



```

135:
136:     outport_b(addr, inport_b(addr) | (1 << irq));
137: }
138:
139: int register_irq(int irq, char *name, void *addr)
140: {
141:     if(irq < 0 || irq >= NR_IRQS) {
142:         return -EINVAL;
143:     }
144:
145:     if(irq_table[irq].registered) {
146:         printk("WARNING: %s(): interrupt %d already registered!\n", __FU
NCTION__, irq);
147:         return -EINVAL;
148:     }
149:     irq_table[irq].ticks = 0;
150:     irq_table[irq].name = name;
151:     irq_table[irq].registered = 1;
152:     irq_table[irq].handler = addr;
153:     return 0;
154: }
155:
156: int unregister_irq(int irq)
157: {
158:     if(irq < 0 || irq >= NR_IRQS) {
159:         return -EINVAL;
160:     }
161:
162:     if(!irq_table[irq].registered) {
163:         printk("WARNING: %s(): trying to unregister an unregistered inte
rrupt %d.\n", __FUNCTION__, irq);
164:         return -EINVAL;
165:     }
166:     memset_b(&irq_table[irq], NULL, sizeof(struct interrupts));
167:     return 0;
168: }
169:
170: /* each ISR points to this function */
171: void irq_handler(int irq, struct sigcontext sc)
172: {
173:     int real;
174:
175:     /* this should help to detect hardware problems */
176:     if(irq == -1) {
177:         printk("Unknown IRQ received!\n");
178:         return;
179:     }
180:
181:     /* spurious interrupt treatment */
182:     if(!irq_table[irq].handler) {
183:         real = pic_get_irq_reg(PIC_READ_ISR);
184:         if(!real) {
185:             /*
186:              * If IRQ was not real and came from slave, then send
187:              * an EOI to master because it doesn't know if the IRQ
188:              * was a spurious interrupt from slave.
189:              */
190:             if(irq > 7) {
191:                 outport_b(PIC_MASTER, EOI);
192:             }
193:             printk("WARNING: spurious interrupt detected (unregister
ed IRQ %d).\n", irq);
194:             kstat.sirqs++;
195:             return;
196:         }
197:         if(irq > 7) {
198:             outport_b(PIC_SLAVE, EOI);

```

kernel/pic.c

Page 4/5

```

199:         }
200:         outport_b(PIC_MASTER, EOI);
201:         return;
202:     }
203:
204:     disable_irq(irq);
205:     if(irq > 7) {
206:         outport_b(PIC_SLAVE, EOI);
207:     }
208:     outport_b(PIC_MASTER, EOI);
209:
210:     kstat.irqs++;
211:     irq_table[irq].ticks++;
212:     irq_table[irq].handler(&sc);
213:     enable_irq(irq);
214: }
215:
216: /* do bottom halves (interrupts are (FIXME) enabled) */
217: void do_bh(void)
218: {
219:     struct bh *b;
220:     void (*fn)(void);
221:
222:     if((b = bh_head)) {
223:         while(b) {
224:             fn = b->fn;
225:             b = b->next;
226:             del_bh();
227:             (*fn)();
228:         }
229:     }
230: }
231:
232: void pic_init(void)
233: {
234:     int n;
235:     struct bh *b;
236:
237:     memset_b(irq_table, NULL, sizeof(irq_table));
238:     memset_b(bh_pool, NULL, sizeof(bh_pool));
239:
240:     /* bh free list initialization */
241:     bh_pool_head = NULL;
242:     n = NR_BH;
243:     while(n--) {
244:         b = &bh_pool[n];
245:         put_free_bh(b);
246:     }
247:     bh_head = bh_tail = NULL;
248:
249:     /* remap interrupts for PIC1 */
250:     outport_b(PIC_MASTER, ICW1_RESET);
251:     outport_b(PIC_MASTER + DATA, IRQ0_ADDR); /* ICW2 */
252:     outport_b(PIC_MASTER + DATA, 1 << CASCADE_IRQ); /* ICW3 */
253:     outport_b(PIC_MASTER + DATA, ICW4_8086EOI);
254:
255:     /* remap interrupts for PIC2 */
256:     outport_b(PIC_SLAVE, ICW1_RESET);
257:     outport_b(PIC_SLAVE + DATA, IRQ8_ADDR); /* ICW2 */
258:     outport_b(PIC_SLAVE + DATA, CASCADE_IRQ); /* ICW3 */
259:     outport_b(PIC_SLAVE + DATA, ICW4_8086EOI);
260:
261:     /* mask all IRQs except cascade */
262:     outport_b(PIC_MASTER + DATA, ~(1 << CASCADE_IRQ));
263:
264:     /* mask all IRQs */
265:     outport_b(PIC_SLAVE + DATA, OCW1);

```

```
266: }
```

kernel/pit.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/pit.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/pit.h>
10:
11: void pit_beep_on(void)
12: {
13:     outport_b(MODEREG, SEL_CHAN2 | LSB_MSB | SQUARE_WAVE | BINARY_CTR);
14:     outport_b(CHANNEL2, (OSCIL / BEEP_FREQ) & 0xFF);          /* LSB */
15:     outport_b(CHANNEL2, (OSCIL / BEEP_FREQ) >> 8);          /* MSB */
16:     outport_b(PS2_SYSCTRL_B, inport_b(PS2_SYSCTRL_B) | ENABLE_SDATA | ENABLE
_LE_TMR2G);
17: }
18:
19: void pit_beep_off(unsigned int unused)
20: {
21:     outport_b(PS2_SYSCTRL_B, inport_b(PS2_SYSCTRL_B) & ~(ENABLE_SDATA | ENAB
LE_TMR2G));
22: }
23:
24: void pit_init(unsigned short int hertz)
25: {
26:     outport_b(MODEREG, SEL_CHAN0 | LSB_MSB | RATE_GEN | BINARY_CTR);
27:     outport_b(CHANNEL0, (OSCIL / hertz) & 0xFF);          /* LSB */
28:     outport_b(CHANNEL0, (OSCIL / hertz) >> 8);          /* MSB */
29: }
```

kernel/process.c

Page 1/7

```

1: /*
2:  * fiwix/kernel/process.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/mm.h>
10: #include <fiwix/errno.h>
11: #include <fiwix/process.h>
12: #include <fiwix/timer.h>
13: #include <fiwix/sched.h>
14: #include <fiwix/sleep.h>
15: #include <fiwix/stdio.h>
16: #include <fiwix/string.h>
17:
18: struct proc *proc_table;
19: struct proc *current;
20:
21: struct proc *proc_pool_head;
22: struct proc *proc_table_head;
23: struct proc *proc_table_tail;
24: unsigned int free_proc_slots = 0;
25:
26: static struct resource slot_resource = { NULL, NULL };
27: static struct resource pid_resource = { NULL, NULL };
28:
29: int nr_processes = 0;
30: __pid_t lastpid = 0;
31:
32: int kill_pid(__pid_t pid, __sigset_t signum)
33: {
34:     struct proc *p;
35:
36:     FOR_EACH_PROCESS(p) {
37:         if(p->pid == pid && (p->state && p->state != PROC_ZOMBIE)) {
38:             return send_sig(p, signum);
39:         }
40:     }
41:     return -ESRCH;
42: }
43:
44: int kill_pgrp(__pid_t pgid, __sigset_t signum)
45: {
46:     struct proc *p;
47:     int found;
48:
49:     found = 0;
50:     FOR_EACH_PROCESS(p) {
51:         if(p->pgid == pgid && (p->state && p->state != PROC_ZOMBIE)) {
52:             send_sig(p, signum);
53:             found = 1;
54:         }
55:     }
56:
57:     if(!found) {
58:         return -ESRCH;
59:     }
60:     return 0;
61: }
62:
63: /* sum up child (and its children) statistics */
64: void add_crusage(struct proc *p, struct rusage *cru)
65: {
66:     cru->ru_utime.tv_sec = p->usage.ru_utime.tv_sec + p->cusage.ru_utime.tv_
sec;

```

kernel/process.c

Page 2/7

```

67:         cru->ru_utime.tv_usec = p->usage.ru_utime.tv_usec + p->cusage.ru_utime.t
v_usec;
68:         if(cru->ru_utime.tv_usec >= 1000000) {
69:             cru->ru_utime.tv_sec++;
70:             cru->ru_utime.tv_usec -= 1000000;
71:         }
72:         cru->ru_stime.tv_sec = p->usage.ru_stime.tv_sec + p->cusage.ru_stime.tv_
sec;
73:         cru->ru_stime.tv_usec = p->usage.ru_stime.tv_usec + p->cusage.ru_stime.t
v_usec;
74:         if(cru->ru_stime.tv_usec >= 1000000) {
75:             cru->ru_stime.tv_sec++;
76:             cru->ru_stime.tv_usec -= 1000000;
77:         }
78:         cru->ru_maxrss = p->usage.ru_maxrss + p->cusage.ru_maxrss;
79:         cru->ru_ixrss = p->usage.ru_ixrss + p->cusage.ru_ixrss;
80:         cru->ru_idrss = p->usage.ru_idrss + p->cusage.ru_idrss;
81:         cru->ru_isrss = p->usage.ru_isrss + p->cusage.ru_isrss;
82:         cru->ru_minflt = p->usage.ru_minflt + p->cusage.ru_minflt;
83:         cru->ru_majflt = p->usage.ru_majflt + p->cusage.ru_majflt;
84:         cru->ru_nswap = p->usage.ru_nswap + p->cusage.ru_nswap;
85:         cru->ru_inblock = p->usage.ru_inblock + p->cusage.ru_inblock;
86:         cru->ru_oublock = p->usage.ru_oublock + p->cusage.ru_oublock;
87:         cru->ru_msgsnd = p->usage.ru_msgsnd + p->cusage.ru_msgsnd;
88:         cru->ru_msgrcv = p->usage.ru_msgrcv + p->cusage.ru_msgrcv;
89:         cru->ru_nsignals = p->usage.ru_nsignals + p->cusage.ru_nsignals;
90:         cru->ru_nvcsw = p->usage.ru_nvcsw + p->cusage.ru_nvcsw;
91:         cru->ru_nivcsw = p->usage.ru_nivcsw + p->cusage.ru_nivcsw;
92:     }
93:
94: void get_rusage(struct proc *p, struct rusage *ru)
95: {
96:     struct rusage cru;
97:
98:     /*
99:      * Conforms with SUSv3 which specifies that if SIGCHLD is being ignored
100:      * then the child statistics should not be added to the values returned
101:      * by RUSAGE_CHILDREN.
102:      */
103:     if(current->sigaction[SIGCHLD - 1].sa_handler == SIG_IGN) {
104:         return;
105:     }
106:
107:     add_crusage(p, &cru);
108:     memcpy_b(ru, &cru, sizeof(struct rusage));
109: }
110:
111: /* add child statistics to parent */
112: void add_rusage(struct proc *p)
113: {
114:     struct rusage cru;
115:
116:     add_crusage(p, &cru);
117:     current->cusage.ru_utime.tv_sec += cru.ru_utime.tv_sec;
118:     current->cusage.ru_utime.tv_usec += cru.ru_utime.tv_usec;
119:     if(current->cusage.ru_utime.tv_usec >= 1000000) {
120:         current->cusage.ru_utime.tv_sec++;
121:         current->cusage.ru_utime.tv_usec -= 1000000;
122:     }
123:     current->cusage.ru_stime.tv_sec += cru.ru_stime.tv_sec;
124:     current->cusage.ru_stime.tv_usec += cru.ru_stime.tv_usec;
125:     if(current->cusage.ru_stime.tv_usec >= 1000000) {
126:         current->cusage.ru_stime.tv_sec++;
127:         current->cusage.ru_stime.tv_usec -= 1000000;
128:     }
129:     current->cusage.ru_maxrss += cru.ru_maxrss;
130:     current->cusage.ru_ixrss += cru.ru_ixrss;

```

kernel/process.c

Page 3/7

```

131:         current->cusage.ru_idrss += cru.ru_idrss;
132:         current->cusage.ru_isrss += cru.ru_isrss;
133:         current->cusage.ru_minflt += cru.ru_minflt;
134:         current->cusage.ru_majflt += cru.ru_majflt;
135:         current->cusage.ru_nswap += cru.ru_nswap;
136:         current->cusage.ru_inblock += cru.ru_inblock;
137:         current->cusage.ru_oublock += cru.ru_oublock;
138:         current->cusage.ru_msgsnd += cru.ru_msgsnd;
139:         current->cusage.ru_msgrcv += cru.ru_msgrcv;
140:         current->cusage.ru_nsignals += cru.ru_nsignals;
141:         current->cusage.ru_nvcsw += cru.ru_nvcsw;
142:         current->cusage.ru_nivcsw += cru.ru_nivcsw;
143:     }
144:
145:     struct proc * get_next_zombie(struct proc *parent)
146:     {
147:         struct proc *p;
148:
149:         if(proc_table_head == NULL) {
150:             PANIC("process table is empty!\n");
151:         }
152:
153:         FOR_EACH_PROCESS(p) {
154:             if(p->ppid == parent->pid && p->state == PROC_ZOMBIE) {
155:                 return p;
156:             }
157:         }
158:
159:         return NULL;
160:     }
161:
162:     __pid_t remove_zombie(struct proc *p)
163:     {
164:         __pid_t pid;
165:
166:         pid = p->pid;
167:         kfree((unsigned int)p->vma);         current->rss--;
168:         kfree(p->tss.esp0);                 current->rss--;
169:         kfree(P2V(p->tss.cr3));             current->rss--;
170:         release_proc(p);
171:         current->children--;
172:         return pid;
173:     }
174:
175:     /*
176:      * An orphaned process group is a process group in which the parent of every
177:      * member is either itself a member of the group or is not a member of the
178:      * group's session.
179:      */
180:     int is_orphaned_pgrp(__pid_t pgid)
181:     {
182:         struct proc *p, *pp;
183:
184:         FOR_EACH_PROCESS(p) {
185:             if(p->pgid != pgid) {
186:                 continue;
187:             }
188:             if(p->state && p->state != PROC_ZOMBIE) {
189:                 pp = get_proc_by_pid(p->ppid);
190:                 /* return if only one is found that breaks the rule */
191:                 if(pp->pgid != pgid || pp->sid == p->sid) {
192:                     return 0;
193:                 }
194:             }
195:         }
196:         return 1;
197:     }

```

kernel/process.c

Page 4/7

```

198:
199: struct proc * get_proc_free(void)
200: {
201:     struct proc *p = NULL;
202:
203:     if(free_proc_slots <= SAFE_SLOTS && !IS_SUPERUSER) {
204:         printk("WARNING: %s(): the remaining slots are only for root use
r!\n", __FUNCTION__);
205:         return NULL;
206:     }
207:
208:     lock_resource(&slot_resource);
209:
210:     if(proc_pool_head) {
211:
212:         /* get (remove) a process slot from the free list */
213:         p = proc_pool_head;
214:         proc_pool_head = proc_pool_head->next;
215:
216:         free_proc_slots--;
217:     } else {
218:         printk("WARNING: %s(): no more slots free in proc table!\n", __F
UNCTION__);
219:     }
220:
221:     unlock_resource(&slot_resource);
222:     return p;
223: }
224:
225: void release_proc(struct proc *p)
226: {
227:     lock_resource(&slot_resource);
228:
229:     /* remove a process from the proc_table */
230:     if(p == proc_table_tail) {
231:         if(proc_table_head == proc_table_tail) {
232:             proc_table_head = proc_table_tail = NULL;
233:         } else {
234:             proc_table_tail = proc_table_tail->prev;
235:             proc_table_tail->next = NULL;
236:         }
237:     } else {
238:         p->prev->next = p->next;
239:         p->next->prev = p->prev;
240:     }
241:
242:     /* initialize and put a process slot back in the free list */
243:     memset_b(p, NULL, sizeof(struct proc));
244:     p->next = proc_pool_head;
245:     proc_pool_head = p;
246:     free_proc_slots++;
247:
248:     unlock_resource(&slot_resource);
249: }
250:
251: int get_unused_pid(void)
252: {
253:     short int loop;
254:     struct proc *p;
255:
256:     loop = 0;
257:     lock_resource(&pid_resource);
258:
259: loop:
260:     lastpid++;
261:     if(lastpid > MAX_PID_VALUE) {
262:         loop++;

```


kernel/process.c

Page 5/7

```

263:         lastpid = INIT;
264:     }
265:     if(loop > 1) {
266:         printk("WARNING: %s(): system ran out of PID numbers!\n");
267:         return 0;
268:     }
269:     FOR_EACH_PROCESS(p) {
270:         if(p->state != PROC_UNUSED) {
271:             /*
272:              * Make sure the kernel never reuses active pid, pgid
273:              * or sid values.
274:              */
275:             if(lastpid == p->pid || lastpid == p->pgid || lastpid ==
p->sid) {
276:                 goto loop;
277:             }
278:         }
279:     }
280:
281:     unlock_resource(&pid_resource);
282:     return lastpid;
283: }
284:
285: struct proc * get_proc_by_pid(__pid_t pid)
286: {
287:     struct proc *p;
288:
289:     FOR_EACH_PROCESS(p) {
290:         if(p->state && p->pid == pid) {
291:             return p;
292:         }
293:     }
294:
295:     PANIC("would return NULL! (current->pid=%d pid=%d)\n", current->pid, pid
);
296:     return NULL;
297: }
298:
299: int get_new_user_fd(int fd)
300: {
301:     int n;
302:
303:     for(n = fd; n < OPEN_MAX && n < current->rlim[RLIMIT_NOFILE].rlim_cur; n
++) {
304:         if(current->fd[n] == 0) {
305:             current->fd[n] = -1;
306:             current->fd_flags[n] = 0;
307:             return n;
308:         }
309:     }
310:
311:     return -EMFILE;
312: }
313:
314: void release_user_fd(int ufd)
315: {
316:     current->fd[ufd] = 0;
317: }
318:
319: struct proc * kernel_process(int (*fn)(void))
320: {
321:     struct proc *p;
322:
323:     p = get_proc_free();
324:     proc_slot_init(p);
325:     p->pid = get_unused_pid();
326:     p->ppid = 0;

```

kernel/process.c

Page 6/7

```

327:     p->flags |= PF_KPROC;
328:     p->priority = DEF_PRIORITY;
329:     if(!(p->tss.esp0 = kmalloc())) {
330:         release_proc(p);
331:         return NULL;
332:     }
333:     p->tss.esp0 += PAGE_SIZE - 4;
334:     p->rss++;
335:     p->tss.cr3 = (unsigned int)kpage_dir;
336:     p->tss.eip = (unsigned int)fn;
337:     p->tss.esp = p->tss.esp0;
338:     sprintk(p->pidstr, "%d", p->pid);
339:     p->state = PROC_RUNNING;
340:     return p;
341: }
342:
343: void proc_slot_init(struct proc *p)
344: {
345:     int n;
346:
347:     /* insert process at the end of proc_table */
348:     lock_resource(&slot_resource);
349:     if(proc_table_head == NULL) {
350:         p->prev = NULL;
351:         p->next = NULL;
352:         proc_table_head = proc_table_tail = p;
353:     } else {
354:         p->prev = proc_table_tail;
355:         p->next = NULL;
356:         proc_table_tail->next = p;
357:         proc_table_tail = p;
358:     }
359:     p->sleep_prev = p->sleep_next = NULL;
360:     unlock_resource(&slot_resource);
361:
362:     memset_b(&p->tss, NULL, sizeof(struct i386tss));
363:     p->tss.io_bitmap_addr = (unsigned int)&p->io_bitmap;
364:
365:     /*
366:      * At the moment, all io_bitmap bits are setup to 0, which means full
367:      * access. This must be changed to 1 once we have fixed the ioperm()
368:      * system call.
369:      */
370:     for(n = 0; n < IO_BITMAP_SIZE + 1; n++) {
371:         p->io_bitmap[n] = 0; /* FIXME: change it to 1 */
372:     }
373:     p->state = PROC_IDLE;
374: }
375:
376: void proc_init(void)
377: {
378:     int n;
379:     struct proc *p;
380:
381:     memset_b(proc_table, NULL, proc_table_size);
382:
383:     /* free list initialization */
384:     proc_pool_head = NULL;
385:     n = (proc_table_size / sizeof(struct proc)) - 1;
386:     do {
387:         p = &proc_table[n];
388:
389:         /* fill the free list */
390:         p->next = proc_pool_head;
391:         proc_pool_head = p;
392:         free_proc_slots++;
393:     } while(n--);

```

kernel/process.c

Page 7/7

```
394:         proc_table_head = proc_table_tail = NULL;
395:
396:         /* slot 0 is for the IDLE process */
397:         current = get_proc_free();
398:         proc_slot_init(current);
399:     }
```

kernel/sched.c

Page 1/2

```

1: /*
2:  * fiwix/kernel/sched.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/kernel.h>
10: #include <fiwix/const.h>
11: #include <fiwix/sched.h>
12: #include <fiwix/process.h>
13: #include <fiwix/segments.h>
14: #include <fiwix/timer.h>
15: #include <fiwix/pic.h>
16: #include <fiwix/stdio.h>
17: #include <fiwix/string.h>
18:
19: extern struct seg_desc gdt[NR_GDT_ENTRIES];
20: int need_resched = 0;
21:
22: static void context_switch(struct proc *next)
23: {
24:     struct proc *prev;
25:
26:     kstat.ctxt++;
27:     prev = current;
28:     set_tss(next);
29:     current = next;
30:     do_switch(&prev->tss.esp, &prev->tss.eip, next->tss.esp, next->tss.eip,
next->tss.cr3, TSS);
31: }
32:
33: void set_tss(struct proc *p)
34: {
35:     struct seg_desc *g;
36:
37:     g = &gdt[TSS / sizeof(struct seg_desc)];
38:
39:     g->sd_lobase = (unsigned int)p;
40:     g->sd_loflags = SD_TSSPRESENT;
41:     g->sd_hibase = (char)(((unsigned int)p) >> 24);
42: }
43:
44: /* Round Robin algorithm */
45: void do_sched(void)
46: {
47:     int count;
48:     struct proc *p, *selected;
49:
50:     /* let the current running process consume its time slice */
51:     if(!need_resched && current->state == PROC_RUNNING && current->cpu_count
> 0) {
52:         return;
53:     }
54:
55:     need_resched = 0;
56:     for(;;) {
57:         count = -1;
58:         selected = &proc_table[IDLE];
59:
60:         FOR_EACH_PROCESS(p) {
61:             if(p->state == PROC_RUNNING && p->cpu_count > count) {
62:                 count = p->cpu_count;
63:                 selected = p;
64:             }
65:

```

kernel/sched.c

Page 2/2

```
66:             if(count) {
67:                 break;
68:             }
69:
70:             /* reassigns new quantum to all processes */
71:             FOR_EACH_PROCESS(p) {
72:                 if(p->state) {
73:                     p->cpu_count = p->priority;
74:                 }
75:             }
76:         }
77:         if(current != selected) {
78:             context_switch(selected);
79:         }
80:     }
81:
82: void sched_init(void)
83: {
84:     get_system_time();
85: }
```

kernel/signal.c

Page 1/4

```

1: /*
2:  * fiwix/kernel/signal.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/kernel.h>
10: #include <fiwix/errno.h>
11: #include <fiwix/process.h>
12: #include <fiwix/signal.h>
13: #include <fiwix/sigcontext.h>
14: #include <fiwix/sleep.h>
15: #include <fiwix/sched.h>
16: #include <fiwix/syscalls.h>
17: #include <fiwix/mm.h>
18: #include <fiwix/stdio.h>
19: #include <fiwix/string.h>
20:
21: int send_sig(struct proc *p, __sigset_t signum)
22: {
23:     struct proc *z;
24:
25:     if(signum > NSIG || !p) {
26:         return -EINVAL;
27:     }
28:
29:     if(!IS_SUPERUSER && current->euid != p->euid && current->sid != p->sid)
30:         return -EPERM;
31: }
32:
33: /* kernel processes can't receive signals */
34: if(p->flags & PF_KPROC) {
35:     return 0;
36: }
37:
38: switch(signum) {
39:     case 0:
40:         return 0;
41:     case SIGKILL:
42:     case SIGCONT:
43:         if(p->state == PROC_STOPPED) {
44:             p->state = PROC_RUNNING;
45:         }
46:         /* discard all pending stop signals */
47:         p->sigpending &= SIG_MASK(SIGSTOP);
48:         p->sigpending &= SIG_MASK(SIGTSTP);
49:         p->sigpending &= SIG_MASK(SIGTTIN);
50:         p->sigpending &= SIG_MASK(SIGTTOU);
51:         break;
52:     case SIGSTOP:
53:     case SIGTSTP:
54:     case SIGTTIN:
55:     case SIGTTOU:
56:         /* discard all pending SIGCONT signals */
57:         p->sigpending &= SIG_MASK(SIGCONT);
58:         break;
59:     default:
60:         break;
61: }
62:
63: if(p->sigaction[signum - 1].sa_handler == SIG_IGN && signum != SIGCHLD)
64:     return 0;
65: }

```

kernel/signal.c

Page 2/4

```

66:
67:     /* SIGCHLD is ignored by default */
68:     if(p->sigaction[signum - 1].sa_handler == SIG_DFL) {
69:         /*
70:            if(p->pid == INIT) {
71:                return 0;
72:            }
73:         */
74:         if(signum == SIGCHLD) {
75:             return 0;
76:         }
77:     }
78:
79:     /* if SIGCHLD is ignored reap its children (prevent zombies) */
80:     if(p->sigaction[signum - 1].sa_handler == SIG_IGN) {
81:         if(signum == SIGCHLD) {
82:             while((z = get_next_zombie(p))) {
83:                 remove_zombie(z);
84:             }
85:             return 0;
86:         }
87:     }
88:
89:     p->sigpending |= 1 << (signum - 1);
90:     p->usage.ru_nsignals++;
91:
92:     /* wake up the process only if that signal is not blocked */
93:     if(!(p->sigblocked & (1 << (signum - 1)))) {
94:         wakeup_proc(p);
95:     }
96:
97:     return 0;
98: }
99:
100: int issig(void)
101: {
102:     __sigset_t signum;
103:     unsigned int mask;
104:     struct proc *p;
105:
106:     if(!(current->sigpending & ~current->sigblocked)) {
107:         return 0;
108:     }
109:
110:     for(signum = 1, mask = 1; signum < NSIG; signum++, mask <= 1) {
111:         if(current->sigpending & mask) {
112:             if(signum == SIGCHLD) {
113:                 if(current->sigaction[signum - 1].sa_handler ==
SIG_IGN) {
114:                     /* this process ignores SIGCHLD */
115:                     while((p = get_next_zombie(current))) {
116:                         remove_zombie(p);
117:                     }
118:                 } else {
119:                     if(current->sigaction[signum - 1].sa_han
dler != SIG_DFL) {
120:                         return signum;
121:                     }
122:                 }
123:             } else {
124:                 if(current->sigaction[signum - 1].sa_handler !=
SIG_IGN) {
125:                     return signum;
126:                 }
127:             }
128:             current->sigpending &= ~mask;
129:         }

```

kernel/signal.c

Page 3/4

```

130:         }
131:         return 0;
132:     }
133:
134: void psig(unsigned int stack)
135: {
136:     int len;
137:     __sigset_t signum;
138:     unsigned int mask;
139:     struct sigcontext *sc;
140:
141:     sc = (struct sigcontext *)stack;
142:     for(signum = 1, mask = 1; signum < NSIG; signum++, mask <= 1) {
143:         if(current->sigpending & mask) {
144:             current->sigpending &= ~mask;
145:
146:             if((unsigned int)current->sigaction[signum - 1].sa_handler) {
147:                 current->sigexecuting = mask;
148:                 if(!(current->sigaction[signum - 1].sa_flags & S
A_NODEFER)) {
149:                     current->sigblocked |= mask;
150:                 }
151:
152:                 /* save the current sigcontext */
153:                 memcpy_b(&current->sc[signum - 1], sc, sizeof(st
ruct sigcontext));
154:                 /* setup the jump to the user signal handler */
155:                 len = ((int)end_sighandler_trampoline - (int)sig
handler_trampoline);
156:                 sc->oldesp -= len;
157:                 sc->oldesp -= 4;
158:                 sc->oldesp &= ~3;          /* round up */
159:                 memcpy_b((void *)sc->oldesp, sighandler_trampoline, len);
160:                 sc->ecx = (unsigned int)current->sigaction[signu
m - 1].sa_handler;
161:                 sc->eax = signum;
162:                 sc->eip = sc->oldesp;
163:
164:                 if(current->sigaction[signum - 1].sa_flags & SA_
RESETHAND) {
165:                     current->sigaction[signum - 1].sa_handler
r = SIG_DFL;
166:                 }
167:                 return;
168:             }
169:             if(current->sigaction[signum - 1].sa_handler == SIG_DFL)
{
170:                 switch(signum) {
171:                     case SIGCONT:
172:                         current->state = PROC_RUNNING;
173:                         need_resched = 1;
174:                         break;
175:                     case SIGSTOP:
176:                     case SIGTSTP:
177:                     case SIGTTIN:
178:                     case SIGTTOU:
179:                         current->exit_code = signum;
180:                         current->state = PROC_STOPPED;
181:                         if(!(current->sigaction[signum -
1].sa_flags & SA_NOCLDSTOP)) {
182:                             send_sig(get_proc_by_pid
(current->ppid), SIGCHLD);
183:                         }
184:                         need_resched = 1;
185:                         break;

```


kernel/signal.c

Page 4/4

```
186:                                     case SIGCHLD:
187:                                         break;
188:                                     default:
189:                                         do_exit(signum);
190:                                     }
191:                                 }
192:                    }
193:    }
194:
195:    /* coming from a system call that needs to be restarted */
196:    if(sc->err > 0) {
197:        if(sc->eax == -ERESTART) {
198:            sc->eax = sc->err;          /* syscall was saved in 'err' */
199:            sc->eip -= 2;              /* point again to 'int 0x80' */
200:        }
201:    }
202: }
```

kernel/sleep.c

Page 1/3

```

1: /*
2:  * fiwix/kernel/sleep.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/kernel.h>
10: #include <fiwix/limits.h>
11: #include <fiwix/sleep.h>
12: #include <fiwix/sched.h>
13: #include <fiwix/signal.h>
14: #include <fiwix/process.h>
15: #include <fiwix/stdio.h>
16: #include <fiwix/string.h>
17:
18: #define NR_BUCKETS          (NR_PROCS * 10) / 100    /* 10% of NR_PROCS */
19: #define SLEEP_HASH(addr)   ((addr) % NR_BUCKETS)
20:
21: struct proc *sleep_hash_table[NR_BUCKETS];
22: static unsigned int area = 0;
23:
24: int sleep(void *address, int state)
25: {
26:     unsigned long int flags;
27:     struct proc **h;
28:     int signum, i;
29:
30:     /* return if it has signals */
31:     if(state == PROC_INTERRUPTIBLE) {
32:         if((signum = issig())) {
33:             return signum;
34:         }
35:     }
36:
37:     if(current->state == PROC_SLEEPING) {
38:         printk("WARNING: %s(): process with pid '%d' is already sleeping
!\n", __FUNCTION__, current->pid);
39:         return 0;
40:     }
41:
42:     SAVE_FLAGS(flags); CLI();
43:     i = SLEEP_HASH((unsigned int)address);
44:     h = &sleep_hash_table[i];
45:
46:     /* insert process in the head */
47:     if(!*h) {
48:         *h = current;
49:         (*h)->sleep_prev = (*h)->sleep_next = NULL;
50:     } else {
51:         current->sleep_prev = NULL;
52:         current->sleep_next = *h;
53:         (*h)->sleep_prev = current;
54:         *h = current;
55:     }
56:     current->sleep_address = address;
57:     current->state = PROC_SLEEPING;
58:
59:     do_sched();
60:
61:     signum = 0;
62:     if(state == PROC_INTERRUPTIBLE) {
63:         signum = issig();
64:     }
65:
66:     RESTORE_FLAGS(flags);

```

kernel/sleep.c

Page 2/3

```

67:         return signum;
68:     }
69:
70: void wakeup(void *address)
71: {
72:     unsigned long int flags;
73:     struct proc **h;
74:     int i;
75:
76:     SAVE_FLAGS(flags); CLI();
77:     i = SLEEP_HASH((unsigned int)address);
78:     h = &sleep_hash_table[i];
79:
80:     while(*h) {
81:         if((*h)->sleep_address == address) {
82:             (*h)->sleep_address = NULL;
83:             (*h)->state = PROC_RUNNING;
84:             need_resched = 1;
85:             if((*h)->sleep_next) {
86:                 (*h)->sleep_next->sleep_prev = (*h)->sleep_prev;
87:             }
88:             if((*h)->sleep_prev) {
89:                 (*h)->sleep_prev->sleep_next = (*h)->sleep_next;
90:             }
91:             if(h == &sleep_hash_table[i]) { /* if it's the head */
92:                 *h = (*h)->sleep_next;
93:                 continue;
94:             }
95:         }
96:         if(*h) {
97:             h = &(*h)->sleep_next;
98:         }
99:     }
100:     RESTORE_FLAGS(flags);
101: }
102:
103: void wakeup_proc(struct proc *p)
104: {
105:     unsigned long int flags;
106:     struct proc **h;
107:     int i;
108:
109:     if(p->state != PROC_SLEEPING && p->state != PROC_STOPPED) {
110:         return;
111:     }
112:
113:     SAVE_FLAGS(flags); CLI();
114:
115:     /* stopped processes don't have sleep address */
116:     if(p->sleep_address) {
117:         if(p->sleep_next) {
118:             p->sleep_next->sleep_prev = p->sleep_prev;
119:         }
120:         if(p->sleep_prev) {
121:             p->sleep_prev->sleep_next = p->sleep_next;
122:         }
123:
124:         i = SLEEP_HASH((unsigned int)p->sleep_address);
125:         h = &sleep_hash_table[i];
126:         if(*h == p) { /* if it's the head */
127:             *h = (*h)->sleep_next;
128:         }
129:     }
130:     p->sleep_address = NULL;
131:     p->state = PROC_RUNNING;
132:     need_resched = 1;
133:

```

kernel/sleep.c

Page 3/3

```
134:     RESTORE_FLAGS(flags);
135:     return;
136: }
137:
138: void lock_resource(struct resource *resource)
139: {
140:     unsigned long int flags;
141:
142:     for(;;) {
143:         SAVE_FLAGS(flags); CLI();
144:         if(resource->locked) {
145:             resource->wanted = 1;
146:             RESTORE_FLAGS(flags);
147:             sleep(resource, PROC_UNINTERRUPTIBLE);
148:         } else {
149:             break;
150:         }
151:     }
152:     resource->locked = 1;
153:     RESTORE_FLAGS(flags);
154: }
155:
156: void unlock_resource(struct resource *resource)
157: {
158:     unsigned long int flags;
159:
160:     SAVE_FLAGS(flags); CLI();
161:     resource->locked = 0;
162:     if(resource->wanted) {
163:         resource->wanted = 0;
164:         wakeup(resource);
165:     }
166:     RESTORE_FLAGS(flags);
167: }
168:
169: int lock_area(unsigned int flag)
170: {
171:     unsigned long int flags;
172:     int retval;
173:
174:     SAVE_FLAGS(flags); CLI();
175:     retval = area & flag;
176:     area |= flag;
177:     RESTORE_FLAGS(flags);
178:
179:     return retval;
180: }
181:
182: int unlock_area(unsigned int flag)
183: {
184:     unsigned long int flags;
185:     int retval;
186:
187:     SAVE_FLAGS(flags); CLI();
188:     retval = area & flag;
189:     area &= ~flag;
190:     RESTORE_FLAGS(flags);
191:
192:     return retval;
193: }
194:
195: void sleep_init(void)
196: {
197:     memset_b(sleep_hash_table, NULL, sizeof(sleep_hash_table));
198: }
```

kernel/syscalls.c

Page 1/7

```

1: /*
2:  * fiwix/kernel/syscalls.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/syscalls.h>
10: #include <fiwix/mm.h>
11: #include <fiwix/errno.h>
12: #include <fiwix/string.h>
13:
14: #ifdef __DEBUG__
15: #include <fiwix/stdio.h>
16: #endif /* __DEBUG__ */
17:
18: void free_name(const char *name)
19: {
20:     kfree((unsigned int)name);
21: }
22:
23: /*
24:  * This function has two objectives:
25:  * 1. to check the memory address validity of the char pointer supplied by the
26:  *    user, while at the same time limit its length to PAGE_SIZE (4096) bytes.
27:  * 2. to create a copy of 'filename' in the kernel data space before using it.
28:  */
29: int malloc_name(const char *filename, char **name)
30: {
31:     struct vma *vma;
32:     unsigned int start;
33:     short int n, len;
34:     char *b;
35:
36:     /*
37:      * Verifies if the 'vma' array of that process is not empty. It can
38:      * only be empty during the initialization of INIT, when it calls to
39:      * sys_execve and sys_open without having yet a proper setup.
40:      */
41:     if(current->vma[0].s_type != 0) {
42:         if(!filename) {
43:             return -EFAULT;
44:         }
45:         start = (unsigned int)filename;
46:         if(!(vma = find_vma_region(start))) {
47:             return -EFAULT;
48:         }
49:         if(!(vma->prot & PROT_READ)) {
50:             return -EFAULT;
51:         }
52:         len = MIN(vma->end - start, PAGE_SIZE);
53:         if(len < PAGE_SIZE) {
54:             if((vma = find_vma_region(vma->end))) {
55:                 if(vma->prot & PROT_READ) {
56:                     len = PAGE_SIZE;
57:                 }
58:             }
59:         }
60:     } else {
61:         len = PAGE_SIZE;
62:     }
63:     if(!(b = (char *)kmalloc())) {
64:         return -ENOMEM;
65:     }
66:     *name = b;
67:     for(n = 0; n < len; n++) {

```

kernel/syscalls.c

Page 2/7

```

68:             if(!(*b = *filename)) {
69:                 return 0;
70:             }
71:             b++;
72:             filename++;
73:         }
74:
75:         free_name(*name);
76:         return -ENAMETOOLONG;
77:     }
78:
79: int check_user_permission(struct inode *i)
80: {
81:     if(!IS_SUPERUSER) {
82:         if(current->euid != i->i_uid) {
83:             return 1;
84:         }
85:     }
86:     return 0;
87: }
88:
89: int check_group(struct inode *i)
90: {
91:     int n;
92:     __gid_t gid;
93:
94:     if(current->flags & PF_USEREAL) {
95:         gid = current->gid;
96:     } else {
97:         gid = current->egid;
98:     }
99:
100:    if(i->i_gid == gid) {
101:        return 0;
102:    }
103:
104:    for(n = 0; n < NGROUPS_MAX; n++) {
105:        if(current->groups[n] == -1) {
106:            break;
107:        }
108:        if(current->groups[n] == i->i_gid) {
109:            return 0;
110:        }
111:    }
112:    return 1;
113: }
114:
115: int check_user_area(int type, const void *addr, unsigned int size)
116: {
117:     struct vma *vma;
118:     unsigned int start;
119:
120:     /*
121:      * Verifies if the 'vma' array of that process is not empty. It can
122:      * only be empty during the initialization of INIT, when it calls to
123:      * sys_execve and sys_open without having yet a proper setup.
124:      */
125:     if(current->vma[0].s_type != 0) {
126:         start = (unsigned int)addr;
127:         if(!(vma = find_vma_region(start))) {
128:             return -EFAULT;
129:         }
130:
131:         for(;;) {
132:             if(type == VERIFY_WRITE) {
133:                 if(!(vma->prot & PROT_WRITE)) {
134:                     return -EFAULT;

```

kernel/syscalls.c

Page 3/7

```

135:         }
136:     } else {
137:         if(!(vma->prot & PROT_READ)) {
138:             return -EFAULT;
139:         }
140:     }
141:     if(start + size <= vma->end) {
142:         break;
143:     }
144:     if(!(vma = find_vma_region(vma->end))) {
145:         return -EFAULT;
146:     }
147: }
148: }
149:
150: return 0;
151: }
152:
153: int check_permission(int mask, struct inode *i)
154: {
155:     __uid_t uid;
156:
157:     if(current->flags & PF_USEREAL) {
158:         uid = current->uid;
159:     } else {
160:         uid = current->euid;
161:     }
162:
163:     if(uid == 0) {
164:         return 0;
165:     }
166:     if(i->i_uid == uid) {
167:         if((((i->i_mode >> 6) & 7) & mask) == mask) {
168:             return 0;
169:         }
170:     }
171:     if(!check_group(i)) {
172:         if((((i->i_mode >> 3) & 7) & mask) == mask) {
173:             return 0;
174:         }
175:     }
176:     if(((i->i_mode & 7) & mask) == mask) {
177:         return 0;
178:     }
179:
180:     return -EACCES;
181: }
182:
183: /* Linux 2.0.40 ABI system call (some from 2.2.26) */
184: void *syscall_table[] = {
185:     NULL, /* 0 */ /* sys_setup (-ENOSYS) */
186:     sys_exit,
187:     sys_fork,
188:     sys_read,
189:     sys_write,
190:     sys_open, /* 5 */
191:     sys_close,
192:     sys_waitpid,
193:     sys_creat,
194:     sys_link,
195:     sys_unlink, /* 10 */
196:     sys_execve,
197:     sys_chdir,
198:     sys_time,
199:     sys_mknod,
200:     sys_chmod, /* 15 */
201:     sys_chown,

```

kernel/syscalls.c

Page 4/7

```

202:         NULL,                                /* sys_break (-ENOSYS) */
203:         sys_stat,
204:         sys_lseek,
205:         sys_getpid,                            /* 20 */
206:         sys_mount,
207:         sys_umount,
208:         sys_setuid,
209:         sys_getuid,
210:         sys_stime,                            /* 25 */
211:         NULL, // sys_ptrace
212:         sys_alarm,
213:         sys_fstat,
214:         sys_pause,
215:         sys_utime,                            /* 30 */
216:         NULL,                                /* sys_stty (-ENOSYS) */
217:         NULL,                                /* sys_gtty (-ENOSYS) */
218:         sys_access,
219:         NULL, // sys_nice
220:         sys_ftime,                            /* 35 */
221:         sys_sync,
222:         sys_kill,
223:         sys_rename,
224:         sys_mkdir,
225:         sys_rmdir,                            /* 40 */
226:         sys_dup,
227:         sys_pipe,
228:         sys_times,
229:         NULL, // sys_prof
230:         sys_brk,                              /* 45 */
231:         sys_setgid,
232:         sys_getgid,
233:         sys_signal,
234:         sys_geteuid,
235:         sys_getegid,                          /* 50 */
236:         NULL, // sys_acct
237:         sys_umount2,
238:         NULL,                                /* sys_lock (-ENOSYS) */
239:         sys_ioctl,
240:         sys_fcntl,                            /* 55 */
241:         NULL,                                /* sys_mpx (-ENOSYS) */
242:         sys_setpgid,
243:         NULL,                                /* sys_ulimit (-ENOSYS) */
244:         sys_olduname,
245:         sys_umask,                            /* 60 */
246:         sys_chroot,
247:         sys_ustat,
248:         sys_dup2,
249:         sys_getppid,
250:         sys_getpgrp,                          /* 65 */
251:         sys_setsid,
252:         sys_sigaction,
253:         sys_sgetmask,
254:         sys_ssetmask,
255:         sys_setreuid,                          /* 70 */
256:         sys_setregid,
257:         sys_sigsuspend,
258:         sys_sigpending,
259:         sys_sethostname,
260:         sys_setrlimit,                        /* 75 */
261:         sys_getrlimit,
262:         sys_getrusage,
263:         sys_gettimeofday,
264:         sys_settimeofday,
265:         sys_getgroups,                        /* 80 */
266:         sys_setgroups,
267:         old_select,
268:         sys_symlink,

```


kernel/syscalls.c

Page 5/7

```

269:      sys_lstat,
270:      sys_readlink,                /* 85 */
271:      NULL, // sys_uselib
272:      NULL, // sys_swapon
273:      sys_reboot,
274:      NULL, // old_readdir
275:      old_mmap,                    /* 90 */
276:      sys_munmap,
277:      sys_truncate,
278:      sys_ftruncate,
279:      sys_fchmod,
280:      sys_fchown,                  /* 95 */
281:      NULL, // sys_getpriority
282:      NULL, // sys_setpriority
283:      NULL,                        /* sys_profil (-ENOSYS) */
284:      sys_statfs,
285:      sys_fstatfs,                 /* 100 */
286:      sys_ioperm,
287:      sys_socketcall, // sys_socketcall XXX
288:      NULL, // sys_syslog
289:      sys_setitimer,
290:      sys_getitimer,              /* 105 */
291:      sys_newstat,
292:      sys_newlstat,
293:      sys_newfstat,
294:      sys_uname,
295:      sys_iopl,                   /* 110 */
296:      NULL, // sys_vhangup
297:      NULL,                        /* sys_idle (-ENOSYS) */
298:      NULL, // sys_vm86old
299:      sys_wait4,
300:      NULL, // sys_swapoff        /* 115 */
301:      sys_sysinfo,
302:      NULL, // sys_ipc
303:      sys_fsync,
304:      sys_sigreturn,
305:      NULL, // sys_clone          /* 120 */
306:      sys_setdomainname,
307:      sys_newuname,
308:      NULL, // sys_modify_ldt
309:      NULL, // sys_adjtimex
310:      sys_mprotect,               /* 125 */
311:      sys_sigprocmask,
312:      NULL, // sys_create_module
313:      NULL, // sys_init_module
314:      NULL, // sys_delete_module
315:      NULL, // sys_get_kernel_syms /* 130 */
316:      NULL, // sys_quotactl
317:      sys_getpgid,
318:      sys_fchdir,
319:      NULL, // sys_bdflush
320:      NULL, // sys_sysfs         /* 135 */
321:      sys_personality,
322:      NULL,                        /* afs_syscall (-ENOSYS) */
323:      sys_setfsuid,
324:      sys_setfsgid,
325:      sys_llseek,                 /* 140 */
326:      sys_getdents,
327:      sys_select,
328:      sys_flock,
329:      NULL, // sys_msync
330:      NULL, // sys_readv         /* 145 */
331:      NULL, // sys_writev
332:      sys_getsid,
333:      sys_fdatasync,
334:      NULL, // sys_sysctl
335:      NULL, // sys_mlock        /* 150 */

```

kernel/syscalls.c

Page 6/7

```

336:     NULL,    // sys_munlock
337:     NULL,    // sys_mlockall
338:     NULL,    // sys_munlockall
339:     NULL,    // sys_sched_setparam
340:     NULL,    // sys_sched_getparam /* 155 */
341:     NULL,    // sys_sched_setscheduler
342:     NULL,    // sys_sched_getscheduler
343:     NULL,    // sys_sched_yield
344:     NULL,    // sys_sched_get_priority_max
345:     NULL,    // sys_sched_get_priority_min /* 160 */
346:     NULL,    // sys_sched_rr_get_interval
347:     sys_nanosleep,
348:     NULL,    // sys_mremap
349:
350:     NULL,
351:     NULL,
352:     NULL,
353:     NULL,
354:     NULL,
355:     NULL,
356:     NULL,
357:     NULL,
358:     NULL,
359:     NULL,
360:     NULL,
361:     NULL,
362:     NULL,
363:     NULL,
364:     NULL,
365:     NULL,
366:     NULL,
367:     NULL,
368:     sys_chown,                /* 182 */
369:     sys_getcwd,
370:     NULL,
371:     NULL,
372:     NULL,
373:     NULL,
374:     NULL,
375:     NULL,
376:     sys_fork,                /* 190 (sys_vfork) */
377: };
378:
379: static void do_bad_syscall(unsigned int num)
380: {
381: #ifdef __DEBUG__
382:     printk("***** (pid %d) system call %d not supported yet *****\n", current->pid, num);
383: #endif /* __DEBUG__ */
384: }
385:
386: /*
387:  * The argument 'struct sigcontext' is needed because there are some system
388:  * calls (such as sys_iopl and sys_fork) that need to get information from
389:  * certain registers (EFLAGS and ESP). The rest of system calls will ignore
390:  * such extra argument.
391:  */
392: int do_syscall(unsigned int num, int arg1, int arg2, int arg3, int arg4, int arg
5, struct sigcontext sc)
393: {
394:     int (*sys_func)(int, ...);
395:
396:     if(num > NR_SYSCALLS) {
397:         do_bad_syscall(num);
398:         return -ENOSYS;
399:     }
400:     sys_func = syscall_table[num];

```

kernel/syscalls.c

Page 7/7

```
401:         if(!sys_func) {
402:             do_bad_syscall(num);
403:             return -ENOSYS;
404:         }
405:         current->sp = (unsigned int)&sc;
406:         return sys_func(arg1, arg2, arg3, arg4, arg5, &sc);
407:     }
```

kernel/timer.c

Page 1/7

```

1: /*
2:  * fiwix/kernel/timer.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/kernel.h>
10: #include <fiwix/const.h>
11: #include <fiwix/cmos.h>
12: #include <fiwix/pit.h>
13: #include <fiwix/timer.h>
14: #include <fiwix/time.h>
15: #include <fiwix/pic.h>
16: #include <fiwix/sched.h>
17: #include <fiwix/pic.h>
18: #include <fiwix/cmos.h>
19: #include <fiwix/signal.h>
20: #include <fiwix/process.h>
21: #include <fiwix/sleep.h>
22: #include <fiwix/errno.h>
23: #include <fiwix/stdio.h>
24: #include <fiwix/string.h>
25:
26: /*
27:  * timer.c implements a callout table using a singly linked list.
28:  *
29:  * head
30:  * +-----+ +-----+ ... +-----+
31:  * |data|next| |data|next| ... |data|next|
32:  * |      | --> |      | --> ... |      | / |
33:  * +-----+ +-----+ ... +-----+
34:  * (callout) (callout)      (callout)
35:  */
36:
37: struct callout callout_pool[NR_CALLOUTS];
38: struct callout *callout_pool_head;
39: struct callout *callout_head;
40:
41: static char month[12] = { 31, 28, 31, 30, 31, 30, 31, 31, 30, 31, 30, 31 };
42: unsigned int avenrun[3] = { 0, 0, 0 };
43:
44: static unsigned int count_active_procs(void)
45: {
46:     int counter;
47:     struct proc *p;
48:
49:     counter = 0;
50:     FOR_EACH_PROCESS(p) {
51:         if(p->state == PROC_RUNNING) {
52:             counter += FIXED_1;
53:         }
54:     }
55:     return counter;
56: }
57:
58: static void calc_load(void)
59: {
60:     unsigned int active_procs;
61:     static int count = LOAD_FREQ;
62:
63:     if(count-- > 0) {
64:         return;
65:     }
66:
67:     count = LOAD_FREQ;

```

kernel/timer.c

Page 2/7

```

68:     active_procs = count_active_procs();
69:     CALC_LOAD(avenrun[0], EXP_1, active_procs);
70:     CALC_LOAD(avenrun[1], EXP_5, active_procs);
71:     CALC_LOAD(avenrun[2], EXP_15, active_procs);
72: }
73:
74: static struct callout *get_free_callout(void)
75: {
76:     struct callout *new;
77:
78:     new = NULL;
79:     if(callout_pool_head) {
80:         new = callout_pool_head;
81:         callout_pool_head = callout_pool_head->next;
82:         new->next = NULL;
83:     }
84:     return new;
85: }
86:
87: static void put_free_callout(struct callout *old)
88: {
89:     old->next = callout_pool_head;
90:     callout_pool_head = old;
91: }
92:
93: static void do_del_callout(struct callout *c)
94: {
95:     struct callout **tmp;
96:
97:     if(callout_head) {
98:         tmp = &callout_head;
99:         while(*tmp) {
100:             if((*tmp) == c) {
101:                 if((*tmp)->next != NULL) {
102:                     *tmp = (*tmp)->next;
103:                     (*tmp)->expires += c->expires;
104:                 } else {
105:                     *tmp = NULL;
106:                 }
107:                 put_free_callout(c);
108:                 break;
109:             }
110:             tmp = &(*tmp)->next;
111:         }
112:     }
113:     return;
114: }
115:
116: void add_callout(struct callout_req *creq, unsigned int ticks)
117: {
118:     unsigned long int flags;
119:     struct callout *c, **tmp;
120:
121:     del_callout(creq);
122:     SAVE_FLAGS(flags); CLI();
123:
124:     if(!(c = get_free_callout())) {
125:         printk("WARNING: %s(): no more callout slots!\n", __FUNCTION__);
126:         RESTORE_FLAGS(flags);
127:         return;
128:     }
129:
130:     /* setup the new callout */
131:     memset_b(c, NULL, sizeof(struct callout));
132:     c->expires = ticks;
133:     c->fn = creq->fn;
134:     c->arg = creq->arg;

```

```

135:
136:     if(!callout_head) {
137:         callout_head = c;
138:     } else {
139:         tmp = &callout_head;
140:         while(*tmp) {
141:             if((*tmp)->expires > c->expires) {
142:                 (*tmp)->expires -= c->expires;
143:                 c->next = *tmp;
144:                 break;
145:             }
146:             c->expires -= (*tmp)->expires;
147:             tmp = &(*tmp)->next;
148:         }
149:         *tmp = c;
150:     }
151:     RESTORE_FLAGS(flags);
152:     return;
153: }
154:
155: void del_callout(struct callout_req *creq)
156: {
157:     unsigned long int flags;
158:     struct callout *c;
159:
160:     SAVE_FLAGS(flags); CLI();
161:     c = callout_head;
162:     while(c) {
163:         if(c->fn == creq->fn && c->arg == creq->arg) {
164:             do_del_callout(c);
165:             break;
166:         }
167:         c = c->next;
168:     }
169:     RESTORE_FLAGS(flags);
170:     return;
171: }
172:
173: void do_timer(struct sigcontext *sc)
174: {
175:     if((++kstat.ticks % HZ) == 0) {
176:         CURRENT_TIME++;
177:         kstat.uptime++;
178:     }
179:
180:     add_bh(timer_bh);
181:
182:     /* FIXME: put this in 'timer_bh' */
183:     if(sc->cs == KERNEL_CS) {
184:         current->usage.ru_stime.tv_usec += TICK;
185:         if(current->usage.ru_stime.tv_usec >= 1000000) {
186:             current->usage.ru_stime.tv_sec++;
187:             current->usage.ru_stime.tv_usec -= 1000000;
188:         }
189:         if(current->pid != IDLE) {
190:             kstat.cpu_system++;
191:         }
192:     } else {
193:         current->usage.ru_utime.tv_usec += TICK;
194:         if(current->usage.ru_utime.tv_usec >= 1000000) {
195:             current->usage.ru_utime.tv_sec++;
196:             current->usage.ru_utime.tv_usec -= 1000000;
197:         }
198:         if(current->pid != IDLE) {
199:             kstat.cpu_user++;
200:         }
201:         if(current->it_virt_value > 0) {

```

kernel/timer.c

Page 4/7

```

202:         current->it_virt_value--;
203:         if(!current->it_virt_value) {
204:             current->it_virt_value = current->it_virt_interv
al;
205:             send_sig(current, SIGVTALRM);
206:         }
207:     }
208: }
209: }
210:
211: unsigned long int tv2ticks(const struct timeval *tv)
212: {
213:     return((tv->tv_sec * HZ) + tv->tv_usec * HZ / 1000000);
214: }
215:
216: void ticks2tv(long int ticks, struct timeval *tv)
217: {
218:     tv->tv_sec = ticks / HZ;
219:     tv->tv_usec = (ticks % HZ) * 1000000 / HZ;
220:     return;
221: }
222:
223: int setitimer(int which, const struct itimerval *new_value, struct itimerval *ol
d_value)
224: {
225:     switch(which) {
226:         case ITIMER_REAL:
227:             if((unsigned int)old_value) {
228:                 ticks2tv(current->it_real_interval, &old_value->
it_interval);
229:                 ticks2tv(current->it_real_value, &old_value->it_
value);
230:             }
231:             current->it_real_interval = tv2ticks(&new_value->it_inte
rval);
232:             current->it_real_value = tv2ticks(&new_value->it_value);
233:             break;
234:         case ITIMER_VIRTUAL:
235:             if((unsigned int)old_value) {
236:                 ticks2tv(current->it_virt_interval, &old_value->
it_interval);
237:                 ticks2tv(current->it_virt_value, &old_value->it_
value);
238:             }
239:             current->it_virt_interval = tv2ticks(&new_value->it_inte
rval);
240:             current->it_virt_value = tv2ticks(&new_value->it_value);
241:             break;
242:         case ITIMER_PROF:
243:             if((unsigned int)old_value) {
244:                 ticks2tv(current->it_prof_interval, &old_value->
it_interval);
245:                 ticks2tv(current->it_prof_value, &old_value->it_
value);
246:             }
247:             current->it_prof_interval = tv2ticks(&new_value->it_inte
rval);
248:             current->it_prof_value = tv2ticks(&new_value->it_value);
249:             break;
250:         default:
251:             return -EINVAL;
252:     }
253:
254:     return 0;
255: }
256:
257: unsigned long int mktime(struct mt *mt)

```

kernel/timer.c

Page 5/7

```

258: {
259:     int n, total_days;
260:     unsigned long int seconds;
261:
262:     total_days = 0;
263:
264:     for(n = UNIX_EPOCH; n < mt->mt_year; n++) {
265:         total_days += DAYS_PER_YEAR(n);
266:     }
267:     for(n = 0; n < (mt->mt_month - 1); n++) {
268:         total_days += month[n];
269:         if(n == 1) {
270:             total_days += LEAP_YEAR(mt->mt_year) ? 1 : 0;
271:         }
272:     }
273:
274:     total_days += (mt->mt_day - 1);
275:     seconds = total_days * SECS_PER_DAY;
276:     seconds += mt->mt_hour * SECS_PER_HOUR;
277:     seconds += mt->mt_min * SECS_PER_MIN;
278:     seconds += mt->mt_sec;
279:     return seconds;
280: }
281:
282: void timer_bh(void)
283: {
284:     struct proc *p;
285:
286:     if(current->usage.ru_utime.tv_sec + current->usage.ru_stime.tv_sec > current->rlim[RLIMIT_CPU].rlim_cur) {
287:         send_sig(current, SIGXCPU);
288:     }
289:
290:     if(current->it_prof_value > 0) {
291:         current->it_prof_value--;
292:         if(!current->it_prof_value) {
293:             current->it_prof_value = current->it_prof_interval;
294:             send_sig(current, SIGPROF);
295:         }
296:     }
297:
298:     calc_load();
299:     FOR_EACH_PROCESS(p) {
300:         if(!p->state) {
301:             continue;
302:         }
303:         if(p->timeout > 0 && p->timeout < INFINITE_WAIT) {
304:             p->timeout--;
305:             if(!p->timeout) {
306:                 wakeup_proc(p);
307:             }
308:         }
309:         if(p->it_real_value > 0) {
310:             p->it_real_value--;
311:             if(!p->it_real_value) {
312:                 p->it_real_value = p->it_real_interval;
313:                 send_sig(p, SIGALRM);
314:             }
315:         }
316:     }
317:
318:     /* callouts */
319:     if(callout_head) {
320:         if(callout_head->expires > 0) {
321:             callout_head->expires--;
322:             if(!callout_head->expires) {
323:                 add_bh(callouts_bh);

```


kernel/timer.c

Page 6/7

```

324:         }
325:     } else {
326:         printk("%s(): callout losing ticks.\n", __FUNCTION__);
327:         add_bh(callouts_bh);
328:     }
329: }
330:
331:     if(current->pid > IDLE && --current->cpu_count <= 0) {
332:         current->cpu_count = 0;
333:         need_resched = 1;
334:     }
335: }
336:
337: void callouts_bh(void)
338: {
339:     struct callout *c;
340:     void (*fn)(unsigned int);
341:     unsigned int arg;
342:
343:     while(callout_head) {
344:         if(callout_head->expires) {
345:             break;
346:         }
347:         if(lock_area(AREA_CALLOUT)) {
348:             continue;
349:         }
350:         fn = callout_head->fn;
351:         arg = callout_head->arg;
352:         c = callout_head;
353:         callout_head = callout_head->next;
354:         put_free_callout(c);
355:         unlock_area(AREA_CALLOUT);
356:         fn(arg);
357:     }
358: }
359:
360: void get_system_time(void)
361: {
362:     short int cmos_century;
363:     struct mt mt;
364:
365:     /* read date and time from CMOS */
366:     mt.mt_sec = cmos_read_date(CMOS_SEC);
367:     mt.mt_min = cmos_read_date(CMOS_MIN);
368:     mt.mt_hour = cmos_read_date(CMOS_HOUR);
369:     mt.mt_day = cmos_read_date(CMOS_DAY);
370:     mt.mt_month = cmos_read_date(CMOS_MONTH);
371:     mt.mt_year = cmos_read_date(CMOS_YEAR);
372:     cmos_century = cmos_read_date(CMOS_CENTURY);
373:     mt.mt_year += cmos_century * 100;
374:
375:     kstat.boot_time = CURRENT_TIME = mktime(&mt);
376: }
377:
378: void set_system_time(__time_t t)
379: {
380:     int sec, spm, min, hour, d, m, y;
381:
382:     sec = t;
383:     y = 1970;
384:     while(sec >= (DAYS_PER_YEAR(y) * SECS_PER_DAY)) {
385:         sec -= (DAYS_PER_YEAR(y) * SECS_PER_DAY);
386:         y++;
387:     }
388:
389:     m = 0;
390:     while(sec > month[m] * SECS_PER_DAY) {

```

kernel/timer.c

Page 7/7

```

391:         spm = month[m] * SECS_PER_DAY;
392:         if(m == 1) {
393:             spm = LEAP_YEAR(y) ? spm + SECS_PER_DAY : spm;
394:         }
395:         sec -= spm;
396:         m++;
397:     }
398:     m++;
399:
400:     d = 1;
401:     while(sec >= SECS_PER_DAY) {
402:         sec -= SECS_PER_DAY;
403:         d++;
404:     }
405:
406:     hour = 0;
407:     while(sec >= SECS_PER_HOUR) {
408:         sec -= SECS_PER_HOUR;
409:         hour++;
410:     }
411:
412:     min = 0;
413:     while(sec >= SECS_PER_MIN) {
414:         sec -= SECS_PER_MIN;
415:         min++;
416:     }
417:
418:     /* write date and time to CMOS */
419:     cmos_write_date(CMOS_SEC, sec);
420:     cmos_write_date(CMOS_MIN, min);
421:     cmos_write_date(CMOS_HOUR, hour);
422:     cmos_write_date(CMOS_DAY, d);
423:     cmos_write_date(CMOS_MONTH, m);
424:     cmos_write_date(CMOS_YEAR, y % 100);
425:     cmos_write_date(CMOS_CENTURY, (y - (y % 100)) / 100);
426:
427:     CURRENT_TIME = t;
428: }
429:
430: void timer_init(void)
431: {
432:     int n;
433:     struct callout *c;
434:
435:     pit_init(HZ);
436:     memset_b(callout_pool, NULL, sizeof(callout_pool));
437:
438:     /* callout free list initialization */
439:     callout_pool_head = NULL;
440:     n = NR_CALLOUTS;
441:     while(n--) {
442:         c = &callout_pool[n];
443:         put_free_callout(c);
444:     }
445:     callout_head = NULL;
446:
447:     printk("clock      -           %d      type=PIT Hz=%d\n", TIMER_IRQ, H
Z);
448:     if(!register_irq(TIMER_IRQ, "timer", do_timer)) {
449:         enable_irq(TIMER_IRQ);
450:     }
451: }

```

kernel/traps.c

Page 1/6

```

1: /*
2:  * fiwix/kernel/traps.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/kernel.h>
10: #include <fiwix/traps.h>
11: #include <fiwix/cpu.h>
12: #include <fiwix/mm.h>
13: #include <fiwix/process.h>
14: #include <fiwix/signal.h>
15: #include <fiwix/stdio.h>
16: #include <fiwix/string.h>
17: #include <fiwix/sched.h>
18:
19: /*
20:  * PS/2 System Control Port B
21:  * -----
22:  * bit 7 -> system board RAM parity check
23:  * bit 6 -> channel check
24:  * bit 5 -> timer 2 (speaker time) output
25:  * bit 4 -> refresh request (toggle)
26:  * bit 3 -> channel check status
27:  * bit 2 -> parity check status
28:  * bit 1 -> speaker data status
29:  * bit 0 -> timer 2 gate to speaker status
30:  */
31: #define PS2_SYSCtrl_B 0x61 /* PS/2 system control port B (read) */
32:
33: struct traps traps_table[NR_EXCEPTIONS] = {
34:     { "Divide Error", do_divide_error, 0 },
35:     { "Debug", do_debug, 0 },
36:     { "NMI Interrupt", do_nmi_interrupt, 0 },
37:     { "Breakpoint", do_breakpoint, 0 },
38:     { "Overflow", do_overflow, 0 },
39:     { "BOUND Range Exceeded", do_bound, 0 },
40:     { "Invalid Opcode", do_invalid_opcode, 0 },
41:     { "Device Not Available (No Math Coprocessor)", do_no_math_coprocessor,
0 },
42:     { "Double Fault", do_double_fault, 1 },
43:     { "Coprocessor Segment Overrun", do_coprocessor_segment_overrun, 0 },
44:     { "Invalid TSS", do_invalid_tss, 1 },
45:     { "Segment Not Present", do_segment_not_present, 1 },
46:     { "Stack-Segment Fault", do_stack_segment_fault, 1 },
47:     { "General Protection", do_general_protection, 1 },
48:     { "Page Fault", do_page_fault, 1 },
49:     { "Intel reserved", do_reserved, 0 },
50:     { "x87 FPU Floating-Point Error", do_floating_point_error, 0 },
51:     { "Alignment Check", do_alignment_check, 1 },
52:     { "Machine Check", do_machine_check, 0 },
53:     { "SIMD Floating-Point Exception", do_simd_fault, 0 },
54:     { "Intel reserved", do_reserved, 0 },
55:     { "Intel reserved", do_reserved, 0 },
56:     { "Intel reserved", do_reserved, 0 },
57:     { "Intel reserved", do_reserved, 0 },
58:     { "Intel reserved", do_reserved, 0 },
59:     { "Intel reserved", do_reserved, 0 },
60:     { "Intel reserved", do_reserved, 0 },
61:     { "Intel reserved", do_reserved, 0 },
62:     { "Intel reserved", do_reserved, 0 },
63:     { "Intel reserved", do_reserved, 0 },
64:     { "Intel reserved", do_reserved, 0 },
65:     { "Intel reserved", do_reserved, 0 }
66: };

```

kernel/traps.c

Page 2/6

```

67:
68: void do_divide_error(unsigned int trap, struct sigcontext *sc)
69: {
70:     if(dump_registers(trap, sc)) {
71:         PANIC("");
72:     }
73:     send_sig(current, SIGFPE);
74:     return;
75: }
76:
77: void do_debug(unsigned int trap, struct sigcontext *sc)
78: {
79:     if(dump_registers(trap, sc)) {
80:         PANIC("");
81:     }
82:     send_sig(current, SIGTRAP);
83:     return;
84: }
85:
86: void do_nmi_interrupt(unsigned int trap, struct sigcontext *sc)
87: {
88:     unsigned char error;
89:
90:     error = inport_b(PS2_SYSCTRL_B);
91:
92:     printk("NMI received: ", error);
93:     switch(error) {
94:         case 0x80:
95:             printk("parity check occurred. Defective RAM chips?\n");
96:             break;
97:         default:
98:             printk("unknown error 0x%x\n", error);
99:             break;
100:    }
101:
102:    if(dump_registers(trap, sc)) {
103:        PANIC("");
104:    }
105:    send_sig(current, SIGSEGV);
106:    return;
107: }
108:
109: void do_breakpoint(unsigned int trap, struct sigcontext *sc)
110: {
111:     if(dump_registers(trap, sc)) {
112:         PANIC("");
113:     }
114:     send_sig(current, SIGTRAP);
115:     return;
116: }
117:
118: void do_overflow(unsigned int trap, struct sigcontext *sc)
119: {
120:     if(dump_registers(trap, sc)) {
121:         PANIC("");
122:     }
123:     send_sig(current, SIGSEGV);
124:     return;
125: }
126:
127: void do_bound(unsigned int trap, struct sigcontext *sc)
128: {
129:     if(dump_registers(trap, sc)) {
130:         PANIC("");
131:     }
132:     send_sig(current, SIGSEGV);
133:     return;

```

```
134: }
135:
136: void do_invalid_opcode(unsigned int trap, struct sigcontext *sc)
137: {
138:     if(dump_registers(trap, sc)) {
139:         PANIC("");
140:     }
141:     send_sig(current, SIGILL);
142:     return;
143: }
144:
145: void do_no_math_coprocessor(unsigned int trap, struct sigcontext *sc)
146: {
147:     /* floating-point emulation would go here */
148:
149:     if(dump_registers(trap, sc)) {
150:         PANIC("No coprocessor/emulation found.\n");
151:     }
152:     send_sig(current, SIGILL);
153:     return;
154: }
155:
156: void do_double_fault(unsigned int trap, struct sigcontext *sc)
157: {
158:     if(dump_registers(trap, sc)) {
159:         PANIC("");
160:     }
161:     send_sig(current, SIGSEGV);
162:     return;
163: }
164:
165: void do_coprocessor_segment_overrun(unsigned int trap, struct sigcontext *sc)
166: {
167:     if(dump_registers(trap, sc)) {
168:         PANIC("");
169:     }
170:     send_sig(current, SIGFPE);
171:     return;
172: }
173:
174: void do_invalid_tss(unsigned int trap, struct sigcontext *sc)
175: {
176:     if(dump_registers(trap, sc)) {
177:         PANIC("");
178:     }
179:     send_sig(current, SIGSEGV);
180:     return;
181: }
182:
183: void do_segment_not_present(unsigned int trap, struct sigcontext *sc)
184: {
185:     if(dump_registers(trap, sc)) {
186:         PANIC("");
187:     }
188:     send_sig(current, SIGBUS);
189:     return;
190: }
191:
192: void do_stack_segment_fault(unsigned int trap, struct sigcontext *sc)
193: {
194:     if(dump_registers(trap, sc)) {
195:         PANIC("");
196:     }
197:     send_sig(current, SIGBUS);
198:     return;
199: }
200:
```

kernel/traps.c

Page 4/6

```
201: void do_general_protection(unsigned int trap, struct sigcontext *sc)
202: {
203:     if(dump_registers(trap, sc)) {
204:         PANIC("");
205:     }
206:     send_sig(current, SIGSEGV);
207:     return;
208: }
209:
210: /* do_page_fault() resides in mm/fault.c */
211:
212: void do_reserved(unsigned int trap, struct sigcontext *sc)
213: {
214:     if(dump_registers(trap, sc)) {
215:         PANIC("");
216:     }
217:     send_sig(current, SIGSEGV);
218:     return;
219: }
220:
221: void do_floating_point_error(unsigned int trap, struct sigcontext *sc)
222: {
223:     if(dump_registers(trap, sc)) {
224:         PANIC("");
225:     }
226:     send_sig(current, SIGFPE);
227:     return;
228: }
229:
230: void do_alignment_check(unsigned int trap, struct sigcontext *sc)
231: {
232:     if(dump_registers(trap, sc)) {
233:         PANIC("");
234:     }
235:     send_sig(current, SIGSEGV);
236:     return;
237: }
238:
239: void do_machine_check(unsigned int trap, struct sigcontext *sc)
240: {
241:     if(dump_registers(trap, sc)) {
242:         PANIC("");
243:     }
244:     send_sig(current, SIGSEGV);
245:     return;
246: }
247:
248: void do_simd_fault(unsigned int trap, struct sigcontext *sc)
249: {
250:     if(dump_registers(trap, sc)) {
251:         PANIC("");
252:     }
253:     send_sig(current, SIGSEGV);
254:     return;
255: }
256:
257: void trap_handler(unsigned int trap, struct sigcontext sc)
258: {
259:     traps_table[trap].handler(trap, &sc);
260:
261:     /* avoids confusion with -RESTART return value */
262:     sc.err = -sc.err;
263: }
264:
265: static const char * elf_lookup_symbol(unsigned int addr)
266: {
267:     Elf32_Sym *sym;
```

kernel/traps.c

Page 5/6

```

268:         unsigned int n;
269:
270:         sym = (Elf32_Sym *)symtab->sh_addr;
271:         for(n = 0; n < symtab->sh_size / sizeof(Elf32_Sym); n++, sym++) {
272:             if(ELF32_ST_TYPE(sym->st_info) != STT_FUNC) {
273:                 continue;
274:             }
275:             if(addr >= sym->st_value && addr < (sym->st_value + sym->st_size
)) {
276:                 return (const char *)strtab->sh_addr + sym->st_name;
277:             }
278:         }
279:         return NULL;
280:     }
281:
282: int dump_registers(unsigned int trap, struct sigcontext *sc)
283: {
284:     unsigned int cr2, addr, n;
285:     unsigned int *sp;
286:     const char *str;
287:
288:     printk("\n");
289:     if(trap == 14) { /* Page Fault */
290:         GET_CR2(cr2);
291:         printk("%s at 0x%08x (%s) with error code 0x%08x (0b%b)\n", trap
s_table[trap].name, cr2, sc->err & PFAULT_W ? "writing" : "reading", sc->err, sc->err);
292:     } else {
293:         printk("EXCEPTION: %s", traps_table[trap].name);
294:         if(traps_table[trap].errcode) {
295:             printk(": error code 0x%08x (0b%b)", sc->err, sc->err);
296:         }
297:         printk("\n");
298:     }
299:
300:     printk("Process '%s' with pid %d", current->argv0, current->pid);
301:     if(sc->cs == KERNEL_CS) {
302:         printk(" in '%s()'"., elf_lookup_symbol(sc->eip));
303:     }
304:     printk("\n");
305:
306:     printk(" cs: 0x%08x\teip: 0x%08x\tefl: 0x%08x\t ss: 0x%08x\tesp: 0x%08x\
n", sc->cs, sc->eip, sc->eflags, sc->oldss, sc->oldesp);
307:     printk("eax: 0x%08x\tebx: 0x%08x\tecx: 0x%08x\tedx: 0x%08x\n", sc->eax,
sc->ebx, sc->ecx, sc->edx);
308:     printk("esi: 0x%08x\tedi: 0x%08x\tesp: 0x%08x\tebp: 0x%08x\n", sc->esi,
sc->edi, sc->esp, sc->ebp);
309:     printk(" ds: 0x%08x\t es: 0x%08x\t fs: 0x%08x\t gs: 0x%08x\n", sc->ds, s
c->es, sc->fs, sc->gs);
310:
311:     if(sc->cs == KERNEL_CS) {
312:         printk("Stack:\n");
313:         GET_ESP(sp);
314:         sp = (unsigned int *)sp;
315:         for(n = 1; n <= 32; n++) {
316:             printk(" %08x", *sp);
317:             sp++;
318:             if(!(n % 8)) {
319:                 printk("\n");
320:             }
321:         }
322:         printk("Backtrace:\n");
323:         GET_ESP(sp);
324:         sp = (unsigned int *)sp;
325:         for(n = 0; n < 128; n++) {
326:             addr = *sp;
327:             str = elf_lookup_symbol(addr);
328:             if(str) {

```

kernel/traps.c

Page 6/6

```
329:                                     printk("<0x%08x> %s()\n", addr, str);
330:                                     }
331:                                     sp++;
332:                                 }
333:                             }
334:
335:                             /* panics if the exception has been in kernel mode */
336:                             if(current->flags & PF_KPROC || sc->cs == KERNEL_CS) {
337:                                 return 1;
338:                             }
339:
340:                             return 0;
341: }
```


kernel/syscalls/access.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/access.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/stat.h>
11: #include <fiwix/errno.h>
12: #include <fiwix/string.h>
13:
14: #ifdef __DEBUG__
15: #include <fiwix/stdio.h>
16: #include <fiwix/process.h>
17: #endif /* __DEBUG__ */
18:
19: int sys_access(const char *filename, __mode_t mode)
20: {
21:     struct inode *i;
22:     char *tmp_name;
23:     int errno;
24:
25: #ifdef __DEBUG__
26:     printk("(pid %d) sys_access('%s', %d)", current->pid, filename, mode);
27: #endif /* __DEBUG__ */
28:
29:     if((mode & S_IRWXO) != mode) {
30:         return -EINVAL;
31:     }
32:     if((errno = malloc_name(filename, &tmp_name)) < 0) {
33:         return errno;
34:     }
35:     current->flags |= PF_USEREAL;
36:     if((errno = namei(tmp_name, &i, NULL, FOLLOW_LINKS))) {
37:         current->flags &= ~PF_USEREAL;
38:         free_name(tmp_name);
39:         return errno;
40:     }
41:     if(mode & TO_WRITE) {
42:         if(S_ISREG(i->i_mode) || S_ISDIR(i->i_mode) || S_ISLNK(i->i_mode
)) {
43:             if(IS_RDONLY_FS(i)) {
44:                 current->flags &= ~PF_USEREAL;
45:                 iput(i);
46:                 free_name(tmp_name);
47:                 return -EROFS;
48:             }
49:         }
50:     }
51:     errno = check_permission(mode, i);
52:
53: #ifdef __DEBUG__
54:     printk(" -> returning %d\n", errno);
55: #endif /* __DEBUG__ */
56:
57:     current->flags &= ~PF_USEREAL;
58:     iput(i);
59:     free_name(tmp_name);
60:     return errno;
61: }

```

kernel/syscalls/alarm.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/alarm.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/time.h>
10:
11: #ifdef __DEBUG__
12: #include <fiwix/stdio.h>
13: #include <fiwix/process.h>
14: #endif /* __DEBUG__ */
15:
16: int sys_alarm(unsigned int secs)
17: {
18:     struct itimerval value, ovalue;
19:
20: #ifdef __DEBUG__
21:     printk("(pid %d) sys_alarm(%d)\n", current->pid, secs);
22: #endif /* __DEBUG__ */
23:
24:     value.it_interval.tv_sec = 0;
25:     value.it_interval.tv_usec = 0;
26:     value.it_value.tv_sec = secs;
27:     value.it_value.tv_usec = 0;
28:     setitimer(ITIMER_REAL, &value, &ovalue);
29:
30:     /*
31:      * If there are still some usecs left and since the return value has
32:      * not enough granularity for them, then just add 1 second to it.
33:      */
34:     if(ovalue.it_value.tv_usec) {
35:         ovalue.it_value.tv_sec++;
36:     }
37:
38:     return ovalue.it_value.tv_sec;
39: }
```

kernel/syscalls/brk.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/brk.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/process.h>
9: #include <fiwix/mm.h>
10: #include <fiwix/mman.h>
11: #include <fiwix/errno.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_brk(unsigned int brk)
18: {
19:     unsigned int newbrk;
20:
21: #ifdef __DEBUG__
22:     printk("(pid %d) sys_brk(0x%08x) -> ", current->pid, brk);
23: #endif /* __DEBUG__ */
24:
25:     if(!brk || brk < current->brk_lower) {
26: #ifdef __DEBUG__
27:         printk("0x%08x\n", current->brk);
28: #endif /* __DEBUG__ */
29:         return current->brk;
30:     }
31:
32:     newbrk = PAGE_ALIGN(brk);
33:     if(newbrk == current->brk || newbrk < current->brk_lower) {
34: #ifdef __DEBUG__
35:         printk("0x%08x\n", current->brk);
36: #endif /* __DEBUG__ */
37:         return brk;
38:     }
39:
40:     if(brk < current->brk) {
41:         do_munmap(newbrk, current->brk - newbrk);
42:         current->brk = brk;
43:         return brk;
44:     }
45:     if(!expand_heap(newbrk)) {
46:         current->brk = brk;
47:     } else {
48:         return -ENOMEM;
49:     }
50: #ifdef __DEBUG__
51:     printk("0x%08x\n", current->brk);
52: #endif /* __DEBUG__ */
53:     return current->brk;
54: }
```

kernel/syscalls/chdir.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/chdir.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/stat.h>
10: #include <fiwix/errno.h>
11: #include <fiwix/string.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #include <fiwix/process.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_chdir(const char *dirname)
19: {
20:     struct inode *i;
21:     char *tmp_name;
22:     int errno;
23:
24: #ifdef __DEBUG__
25:     printk("(pid %d) sys_chdir('%s')\n", current->pid, dirname);
26: #endif /* __DEBUG__ */
27:
28:     if((errno = malloc_name(dirname, &tmp_name)) < 0) {
29:         return errno;
30:     }
31:     if((errno = namei(tmp_name, &i, NULL, FOLLOW_LINKS))) {
32:         free_name(tmp_name);
33:         return errno;
34:     }
35:     if(!S_ISDIR(i->i_mode)) {
36:         iput(i);
37:         free_name(tmp_name);
38:         return -ENOTDIR;
39:     }
40:     if((errno = check_permission(TO_EXEC, i))) {
41:         iput(i);
42:         free_name(tmp_name);
43:         return errno;
44:     }
45:     iput(current->pwd);
46:     current->pwd = i;
47:     free_name(tmp_name);
48:     return 0;
49: }
```

kernel/syscalls/chmod.c

Page 1/1

```

1:  /*
2:  * fiwix/kernel/syscalls/chmod.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8:  #include <fiwix/types.h>
9:  #include <fiwix/kernel.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/stat.h>
12: #include <fiwix/errno.h>
13: #include <fiwix/string.h>
14:
15: #ifdef __DEBUG__
16: #include <fiwix/stdio.h>
17: #include <fiwix/process.h>
18: #endif /* __DEBUG__ */
19:
20: int sys_chmod(const char *filename, __mode_t mode)
21: {
22:     struct inode *i;
23:     char *tmp_name;
24:     int errno;
25:
26: #ifdef __DEBUG__
27:     printk("(pid %d) sys_chmod('%s', %d)\n", current->pid, filename, mode);
28: #endif /* __DEBUG__ */
29:
30:     if((errno = malloc_name(filename, &tmp_name)) < 0) {
31:         return errno;
32:     }
33:     if((errno = namei(tmp_name, &i, NULL, FOLLOW_LINKS))) {
34:         free_name(tmp_name);
35:         return errno;
36:     }
37:
38:     if(IS_RDONLY_FS(i)) {
39:         iput(i);
40:         free_name(tmp_name);
41:         return -EROFS;
42:     }
43:     if(check_user_permission(i)) {
44:         iput(i);
45:         free_name(tmp_name);
46:         return -EPERM;
47:     }
48:
49:     i->i_mode &= S_IFMT;
50:     i->i_mode |= mode & ~S_IFMT;
51:     i->i_ctime = CURRENT_TIME;
52:     i->dirty = 1;
53:     iput(i);
54:     free_name(tmp_name);
55:     return 0;
56: }

```

kernel/syscalls/chown.c

Page 1/2

```

1: /*
2:  * fiwix/kernel/syscalls/chown.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/kernel.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/stat.h>
12: #include <fiwix/errno.h>
13: #include <fiwix/string.h>
14:
15: #ifdef __DEBUG__
16: #include <fiwix/stdio.h>
17: #include <fiwix/process.h>
18: #endif /* __DEBUG__ */
19:
20: int sys_chown(const char *filename, __uid_t owner, __gid_t group)
21: {
22:     struct inode *i;
23:     char *tmp_name;
24:     int errno;
25:
26: #ifdef __DEBUG__
27:     printk("(pid %d) sys_chown('%s', %d, %d)\n", current->pid, filename, own
er, group);
28: #endif /* __DEBUG__ */
29:
30:     if((errno = malloc_name(filename, &tmp_name)) < 0) {
31:         return errno;
32:     }
33:     if((errno = namei(tmp_name, &i, NULL, FOLLOW_LINKS))) {
34:         free_name(tmp_name);
35:         return errno;
36:     }
37:
38:     if(IS_RDONLY_FS(i)) {
39:         iput(i);
40:         free_name(tmp_name);
41:         return -EROFS;
42:     }
43:     if(check_user_permission(i)) {
44:         iput(i);
45:         free_name(tmp_name);
46:         return -EPERM;
47:     }
48:
49:     if(owner == (__uid_t)-1) {
50:         owner = i->i_uid;
51:     } else {
52:         i->i_mode &= ~(S_ISUID);
53:         i->i_ctime = CURRENT_TIME;
54:     }
55:     if(group == (__gid_t)-1) {
56:         group = i->i_gid;
57:     } else {
58:         i->i_mode &= ~(S_ISGID);
59:         i->i_ctime = CURRENT_TIME;
60:     }
61:
62:     i->i_uid = owner;
63:     i->i_gid = group;
64:     i->dirty = 1;
65:     iput(i);
66:     free_name(tmp_name);

```

kernel/syscalls/chown.c

Page 2/2

```
67:         return 0;
68:     }
```

kernel/syscalls/chroot.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/chroot.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/stat.h>
10: #include <fiwix/errno.h>
11: #include <fiwix/string.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #include <fiwix/process.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_chroot(const char *dirname)
19: {
20:     struct inode *i;
21:     char *tmp_name;
22:     int errno;
23:
24: #ifdef __DEBUG__
25:     printk("(pid %d) sys_chroot('%s')\n", current->pid, dirname);
26: #endif /* __DEBUG__ */
27:
28:     if((errno = malloc_name(dirname, &tmp_name)) < 0) {
29:         return errno;
30:     }
31:     if((errno = namei(tmp_name, &i, NULL, FOLLOW_LINKS))) {
32:         free_name(tmp_name);
33:         return errno;
34:     }
35:     if(!S_ISDIR(i->i_mode)) {
36:         iput(i);
37:         free_name(tmp_name);
38:         return -ENOTDIR;
39:     }
40:     iput(current->root);
41:     current->root = i;
42:     free_name(tmp_name);
43:     return 0;
44: }
```


kernel/syscalls/close.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/close.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/syscalls.h>
9: #include <fiwix/locks.h>
10: #include <fiwix/errno.h>
11: #include <fiwix/stdio.h>
12:
13: int sys_close(unsigned int ufd)
14: {
15:     unsigned int fd;
16:     struct inode *i;
17:
18: #ifdef __DEBUG__
19:     printk("(pid %d) sys_close(%d)\n", current->pid, ufd);
20: #endif /* __DEBUG__ */
21:
22:     CHECK_UFD(ufd);
23:     fd = current->fd[ufd];
24:     release_user_fd(ufd);
25:
26:     if(--fd_table[fd].count) {
27:         return 0;
28:     }
29:     i = fd_table[fd].inode;
30:     flock_release_inode(i);
31:     if(i->fsop && i->fsop->close) {
32:         i->fsop->close(i, &fd_table[fd]);
33:         release_fd(fd);
34:         iput(i);
35:         return 0;
36:     }
37:     printk("WARNING: %s(): ufd %d without the close() method!\n", __FUNCTION
__, ufd);
38:     return -EINVAL;
39: }

```

kernel/syscalls/creat.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/creat.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/syscalls.h>
10: #include <fiwix/fcntl.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #include <fiwix/process.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_creat(const char *filename, __mode_t mode)
18: {
19: #ifdef __DEBUG__
20:     printk("(pid %d) sys_creat('%s', %d)\n", current->pid, filename, mode);
21: #endif /* __DEBUG__ */
22:     return sys_open(filename, O_CREAT | O_WRONLY | O_TRUNC, mode);
23: }
```

kernel/syscalls/dup2.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/dup2.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/syscalls.h>
9: #include <fiwix/process.h>
10: #include <fiwix/errno.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #endif /* __DEBUG__ */
15:
16: int sys_dup2(int old_ufd, int new_ufd)
17: {
18: #ifdef __DEBUG__
19:     printk("(pid %d) sys_dup2(%d, %d)", current->pid, old_ufd, new_ufd);
20: #endif /* __DEBUG__ */
21:
22:     CHECK_UFD(old_ufd);
23:     if(new_ufd < 0 || new_ufd > OPEN_MAX) {
24:         return -EINVAL;
25:     }
26:     if(old_ufd == new_ufd) {
27:         return new_ufd;
28:     }
29:     if(current->fd[new_ufd]) {
30:         sys_close(new_ufd);
31:     }
32:     if((new_ufd = get_new_user_fd(new_ufd)) < 0) {
33:         return new_ufd;
34:     }
35:     current->fd[new_ufd] = current->fd[old_ufd];
36:     fd_table[current->fd[new_ufd]].count++;
37: #ifdef __DEBUG__
38:     printk(" --> returning %d\n", new_ufd);
39: #endif /* __DEBUG__ */
40:     return new_ufd;
41: }
```

kernel/syscalls/dup.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/dup.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/syscalls.h>
10: #include <fiwix/errno.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #include <fiwix/process.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_dup(unsigned int ufd)
18: {
19:     int new_ufd;
20:
21: #ifdef __DEBUG__
22:     printk("(pid %d) sys_dup(%d)", current->pid, ufd);
23: #endif /* __DEBUG__ */
24:
25:     CHECK_UFD(ufd);
26:     if((new_ufd = get_new_user_fd(0)) < 0) {
27:         return new_ufd;
28:     }
29:
30: #ifdef __DEBUG__
31:     printk(" -> %d\n", new_ufd);
32: #endif /* __DEBUG__ */
33:
34:     current->fd[new_ufd] = current->fd[ufd];
35:     fd_table[current->fd[new_ufd]].count++;
36:     return new_ufd;
37: }
```

kernel/syscalls/execve.c

Page 1/2

```

1: /*
2:  * fiwix/kernel/syscalls/execve.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/syscalls.h>
10: #include <fiwix/stat.h>
11: #include <fiwix/fcntl.h>
12: #include <fiwix/errno.h>
13: #include <fiwix/string.h>
14:
15: #ifdef __DEBUG__
16: #include <fiwix/stdio.h>
17: #include <fiwix/process.h>
18: #endif /* __DEBUG__ */
19:
20: int sys_execve(const char *filename, char *argv[], char *envp[], int arg4, int a
rg5, struct sigcontext *sc)
21: {
22:     int n, errno;
23:     struct inode *i;
24:     char *tmp_name;
25:
26: #ifdef __DEBUG__
27:     printk("(pid %d) sys_execve('%s', ...)\n", current->pid, filename);
28: #endif /* __DEBUG__ */
29:
30:     if((errno = malloc_name(filename, &tmp_name)) < 0) {
31:         return errno;
32:     }
33:     if((errno = namei(tmp_name, &i, NULL, FOLLOW_LINKS))) {
34:         free_name(tmp_name);
35:         return errno;
36:     }
37:     if(!S_ISREG(i->i_mode)) {
38:         iput(i);
39:         free_name(tmp_name);
40:         return -EACCES;
41:     }
42:     if(check_permission(TO_EXEC, i) < 0) {
43:         iput(i);
44:         free_name(tmp_name);
45:         return -EACCES;
46:     }
47:
48:     if((errno = elf_load(i, &(*argv), &(*envp), sc))) {
49:         iput(i);
50:         free_name(tmp_name);
51:         return errno;
52:     }
53:
54:     if(i->i_mode & S_ISUID) {
55:         current->euid = i->i_uid;
56:     }
57:     if(i->i_mode & S_ISGID) {
58:         current->egid = i->i_gid;
59:     }
60:
61:     for(n = 0; n < OPEN_MAX; n++) {
62:         if(current->fd[n] && (current->fd_flags[n] & FD_CLOEXEC)) {
63:             sys_close(n);
64:         }
65:     }
66:

```

kernel/syscalls/execve.c

Page 2/2

```
67:         current->suid = current->euid;
68:         current->sgid = current->egid;
69:         current->sigpending = 0;
70:         current->sigexecuting = 0;
71:         for(n = 0; n < NSIG; n++) {
72:             current->sigaction[n].sa_mask = 0;
73:             current->sigaction[n].sa_flags = 0;
74:             if(current->sigaction[n].sa_handler != SIG_IGN) {
75:                 current->sigaction[n].sa_handler = SIG_DFL;
76:             }
77:         }
78:         current->sleep_address = NULL;
79:         current->flags |= PF_PEXEC;
80:         iput(i);
81:         free_name(tmp_name);
82:         return 0;
83:     }
```

kernel/syscalls/exit.c

Page 1/2

```

1: /*
2:  * fiwix/kernel/syscalls/exit.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/kernel.h>
10: #include <fiwix/syscalls.h>
11: #include <fiwix/process.h>
12: #include <fiwix/sched.h>
13: #include <fiwix/mman.h>
14: #include <fiwix/sleep.h>
15: #include <fiwix/stdio.h>
16: #include <fiwix/string.h>
17:
18: void do_exit(int exit_code)
19: {
20:     int n;
21:     struct proc *p, *init;
22:
23: #ifdef __DEBUG__
24:     printk("\n");
25:     printk("sys_exit(pid %d, ppid %d)\n", current->pid, current->ppid);
26:     printk("-----\n");
27: #endif /*__DEBUG__ */
28:
29:     CLI();
30:     current->state = PROC_ZOMBIE;
31:
32:     release_binary();
33:     current->argv = NULL;
34:     current->envp = NULL;
35:     current->sigpending = 0;
36:     current->sigblocked = 0;
37:     current->sigexecuting = 0;
38:     for(n = 0; n < NSIG; n++) {
39:         current->sigaction[n].sa_mask = 0;
40:         current->sigaction[n].sa_flags = 0;
41:         current->sigaction[n].sa_handler = SIG_IGN;
42:     }
43:
44:     init = get_proc_by_pid(INIT);
45:     FOR_EACH_PROCESS(p) {
46:         if(SESS_LEADER(current)) {
47:             if(p->sid == current->sid && p->state != PROC_ZOMBIE) {
48:                 p->pgid = 0;
49:                 p->sid = 0;
50:                 p->ctty = NULL;
51:                 send_sig(p, SIGHUP);
52:                 send_sig(p, SIGCONT);
53:             }
54:         }
55:
56:         /* make INIT inherit the children of this exiting process */
57:         if(p->state && p->ppid == current->pid) {
58:             p->ppid = INIT;
59:             init->children++;
60:             if(p->state == PROC_ZOMBIE) {
61:                 send_sig(init, SIGCHLD);
62:             }
63:         }
64:     }
65:
66:     if(SESS_LEADER(current)) {
67:         disassociate_ctty(current->ctty);

```

kernel/syscalls/exit.c

Page 2/2

```

68:         }
69:
70:         for(n = 0; n < OPEN_MAX; n++) {
71:             if(current->fd[n]) {
72:                 sys_close(n);
73:             }
74:         }
75:
76:         iput(current->root);
77:         current->root = NULL;
78:         iput(current->pwd);
79:         current->pwd = NULL;
80:         current->exit_code = exit_code;
81:         if(!--nr_processes) {
82:             printk("\n");
83:             printk("WARNING: the last user process has exited. The kernel wi
ll stop itself.\n");
84:             stop_kernel();
85:         }
86:
87:         /* notify the parent about the child's death */
88:         if((p = get_proc_by_pid(current->ppid)) {
89:             send_sig(p, SIGCHLD);
90:             if(p->sleep_address == &sys_wait4) {
91:                 wakeup_proc(p);
92:             }
93:         }
94:
95:         need_resched = 1;
96:
97:         /* make sure to recover if the process returns from the death (!?) */
98:         for(;;) {
99:             current->state = PROC_ZOMBIE;
100:            do_sched();
101:        }
102:    }
103:
104: int sys_exit(int exit_code)
105: {
106: #ifdef __DEBUG__
107:     printk("(pid %d) sys_exit()\n", current->pid);
108: #endif /*__DEBUG__ */
109:
110:     /* exit code in the second byte.
111:      * 15          8 7          0
112:      * +-----+-----+
113:      * | exit code (0-255) |          0          |
114:      * +-----+-----+
115:      */
116:     do_exit((exit_code & 0xFF) << 8);
117:     return 0;
118: }

```


kernel/syscalls/fchdir.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/fchdir.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/process.h>
10: #include <fiwix/stat.h>
11: #include <fiwix/errno.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_fchdir(unsigned int ufd)
18: {
19:     struct inode *i;
20:
21: #ifdef __DEBUG__
22:     printk("(pid %d) sys_fchdir(%d)\n", current->pid, ufd);
23: #endif /* __DEBUG__ */
24:
25:     CHECK_UFD(ufd);
26:     i = fd_table[current->fd[ufd]].inode;
27:     if(!S_ISDIR(i->i_mode)) {
28:         return -ENOTDIR;
29:     }
30:     iput(current->pwd);
31:     current->pwd = i;
32:     current->pwd->count++;
33:     return 0;
34: }
```

kernel/syscalls/fchmod.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/fchmod.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/types.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/stat.h>
12: #include <fiwix/errno.h>
13:
14: #ifdef __DEBUG__
15: #include <fiwix/stdio.h>
16: #include <fiwix/process.h>
17: #endif /* __DEBUG__ */
18:
19: int sys_fchmod(int ufd, __mode_t mode)
20: {
21:     struct inode *i;
22:
23: #ifdef __DEBUG__
24:     printk("(pid %d) sys_fchmod(%d, %d)\n", current->pid, ufd, mode);
25: #endif /* __DEBUG__ */
26:
27:     CHECK_UFD(ufd);
28:     i = fd_table[current->fd[ufd]].inode;
29:
30:     if(IS_RDONLY_FS(i)) {
31:         return -EROFS;
32:     }
33:     if(check_user_permission(i)) {
34:         return -EPERM;
35:     }
36:
37:     i->i_mode &= S_IFMT;
38:     i->i_mode |= mode & ~S_IFMT;
39:     i->i_ctime = CURRENT_TIME;
40:     i->dirty = 1;
41:     return 0;
42: }
```

kernel/syscalls/fchown.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/fchown.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/types.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/stat.h>
12: #include <fiwix/process.h>
13: #include <fiwix/errno.h>
14:
15: #ifdef __DEBUG__
16: #include <fiwix/stdio.h>
17: #endif /* __DEBUG__ */
18:
19: int sys_fchown(int ufd, __uid_t owner, __gid_t group)
20: {
21:     struct inode *i;
22:
23: #ifdef __DEBUG__
24:     printk("(pid %d) sys_fchown(%d, %d, %d)\n", current->pid, ufd, owner, gr
oup);
25: #endif /* __DEBUG__ */
26:
27:     CHECK_UFD(ufd);
28:     i = fd_table[current->fd[ufd]].inode;
29:
30:     if(IS_RDONLY_FS(i)) {
31:         return -EROFS;
32:     }
33:     if(check_user_permission(i)) {
34:         return -EPERM;
35:     }
36:
37:     if(owner == (__uid_t)-1) {
38:         owner = i->i_uid;
39:     } else {
40:         i->i_mode &= ~(S_ISUID);
41:     }
42:     if(group == (__gid_t)-1) {
43:         group = i->i_gid;
44:     } else {
45:         i->i_mode &= ~(S_ISGID);
46:     }
47:
48:     i->i_uid = owner;
49:     i->i_gid = group;
50:     i->i_ctime = CURRENT_TIME;
51:     i->dirty = 1;
52:     return 0;
53: }
```

kernel/syscalls/fcntl.c

Page 1/2

```

1: /*
2:  * fiwix/kernel/syscalls/fcntl.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/syscalls.h>
9: #include <fiwix/fcntl.h>
10: #include <fiwix/locks.h>
11: #include <fiwix/errno.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #include <fiwix/process.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_fcntl(int ufd, int cmd, unsigned long int arg)
19: {
20:     int new_ufd, errno;
21:
22: #ifdef __DEBUG__
23:     printk("(pid %d) sys_fcntl(%d, %d, 0x%08x)\n", current->pid, ufd, cmd, a
rg);
24: #endif /* __DEBUG__ */
25:
26:     CHECK_UFD(ufd);
27:     switch(cmd) {
28:         case F_DUPFD:
29:             CHECK_UFD(ufd);
30:             if(arg >= OPEN_MAX) {
31:                 return -EINVAL;
32:             }
33:             if((new_ufd = get_new_user_fd(arg)) < 0) {
34:                 return new_ufd;
35:             }
36:             current->fd[new_ufd] = current->fd[ufd];
37:             fd_table[current->fd[new_ufd]].count++;
38: #ifdef __DEBUG__
39:             printk("\t--> returning %d\n", new_ufd);
40: #endif /* __DEBUG__ */
41:             return new_ufd;
42:         case F_GETFD:
43:             return (current->fd_flags[ufd] & FD_CLOEXEC);
44:         case F_SETFD:
45:             current->fd_flags[ufd] = (arg & FD_CLOEXEC);
46:             break;
47:         case F_GETFL:
48:             return fd_table[current->fd[ufd]].flags;
49:         case F_SETFL:
50:             fd_table[current->fd[ufd]].flags &= ~(O_APPEND | O_NONBL
OCK);
51:             fd_table[current->fd[ufd]].flags |= arg & (O_APPEND | O_
NONBLOCK);
52:             break;
53:         case F_GETLK:
54:         case F_SETLK:
55:         case F_SETLKW:
56:             if((errno = check_user_area(VERIFY_READ, (void *)arg, si
zeof(struct flock)))) {
57:                 return errno;
58:             }
59:             return posix_lock(ufd, cmd, (struct flock *)arg);
60:         default:
61:             return -EINVAL;
62:     }
63:     return 0;

```

```
64: }
```

kernel/syscalls/fdatasync.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/fdatasync.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/syscalls.h>
9:
10: #ifdef __DEBUG__
11: #include <fiwix/stdio.h>
12: #include <fiwix/process.h>
13: #endif /*__DEBUG__*/
14:
15: int sys_fdatasync(int ufd)
16: {
17: #ifdef __DEBUG__
18:     printk("(pid %d) sys_fdatasync(%d)\n", current->pid, ufd);
19: #endif /*__DEBUG__*/
20:
21:     return sys_fsync(ufd);
22: }
```

kernel/syscalls/flock.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/flock.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/process.h>
10: #include <fiwix/locks.h>
11: #include <fiwix/errno.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_flock(int ufd, int op)
18: {
19:     struct inode *i;
20:
21: #ifdef __DEBUG__
22:     printk("(pid %d) sys_flock(%d, %d)\n", current->pid, ufd, op);
23: #endif /* __DEBUG__ */
24:
25:     CHECK_UFD(ufd);
26:     i = fd_table[current->fd[ufd]].inode;
27:     return flock_inode(i, op);
28: }
```

kernel/syscalls/fork.c

Page 1/3

```

1: /*
2:  * fiwix/kernel/syscalls/fork.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/kernel.h>
10: #include <fiwix/types.h>
11: #include <fiwix/const.h>
12: #include <fiwix/sigcontext.h>
13: #include <fiwix/process.h>
14: #include <fiwix/sched.h>
15: #include <fiwix/mm.h>
16: #include <fiwix/errno.h>
17: #include <fiwix/stdio.h>
18: #include <fiwix/string.h>
19:
20: int sys_fork(int arg1, int arg2, int arg3, int arg4, int arg5, struct sigcontext
*sc)
21: {
22:     int count, pages;
23:     unsigned int n;
24:     unsigned int *child_pgid;
25:     struct sigcontext *stack;
26:     struct proc *child, *p;
27:     struct vma *vma;
28:     __pid_t pid;
29:
30: #ifdef __DEBUG__
31:     printk("(pid %d) sys_fork()\n", current->pid);
32: #endif /*__DEBUG__*/
33:
34:     /* check the number of processes already allocated by this UID */
35:     count = 0;
36:     FOR_EACH_PROCESS(p) {
37:         if(p->state && p->uid == current->uid) {
38:             count++;
39:         }
40:     }
41:     if(count > current->rlim[RLIMIT_NPROC].rlim_cur) {
42:         printk("WARNING: %s(): RLIMIT_NPROC exceeded.\n", __FUNCTION__);
43:         return -EAGAIN;
44:     }
45:
46:     if(!(pid = get_unused_pid())) {
47:         return -EAGAIN;
48:     }
49:     if(!(child = get_proc_free())) {
50:         return -EAGAIN;
51:     }
52:
53:     /*
54:      * This memcpy() will overwrite the prev and next pointers, so that's
55:      * the reason why proc_slot_init() is separated from get_proc_free().
56:      */
57:     memcpy_b(child, current, sizeof(struct proc));
58:
59:     proc_slot_init(child);
60:     child->pid = pid;
61:     memset_b(&child->tss, NULL, sizeof(struct i386tss));
62:     sprintf(child->pidstr, "%d", child->pid);
63:     child->state = PROC_IDLE;
64:
65:     if(!(child_pgid = (void *)kmalloc())) {
66:         release_proc(child);

```


kernel/syscalls/fork.c

Page 2/3

```

67:         return -ENOMEM;
68:     }
69:     child->rss++;
70:     memcpy_b(child_pgdir, kpage_dir, PAGE_SIZE);
71:     child->tss.cr3 = V2P((unsigned int)child_pgdir);
72:
73:     child->ppid = current->pid;
74:     child->flags = 0;
75:     child->children = 0;
76:     child->cpu_count = child->priority;
77:     child->start_time = CURRENT_TIME;
78:     child->sleep_address = NULL;
79:
80:     if(!(child->vma = (void *)kmalloc())) {
81:         kfree((unsigned int)child_pgdir);
82:         release_proc(child);
83:         return -ENOMEM;
84:     }
85:     child->rss++;
86:     memcpy_b(child->vma, current->vma, PAGE_SIZE);
87:     vma = child->vma;
88:     for(n = 0; n < VMA_REGIONS && vma->start; n++, vma++) {
89:         if(vma->inode) {
90:             vma->inode->count++;
91:         }
92:     }
93:
94:     child->sigpending = 0;
95:     child->sigexecuting = 0;
96:     memset_b(&child->sc, NULL, sizeof(struct sigcontext));
97:     memset_b(&child->usage, NULL, sizeof(struct rusage));
98:     memset_b(&child->cusage, NULL, sizeof(struct rusage));
99:     child->it_real_interval = 0;
100:    child->it_real_value = 0;
101:    child->it_virt_interval = 0;
102:    child->it_virt_value = 0;
103:    child->it_prof_interval = 0;
104:    child->it_prof_value = 0;
105:
106:    if(!(child->tss.esp0 = kmalloc())) {
107:        kfree((unsigned int)child_pgdir);
108:        kfree((unsigned int)child->vma);
109:        release_proc(child);
110:        return -ENOMEM;
111:    }
112:
113:    if(!(pages = clone_pages(child))) {
114:        printk("WARNING: %s(): not enough memory, can't clone pages.\n",
__FUNCTION__);
115:        free_page_tables(child);
116:        kfree((unsigned int)child_pgdir);
117:        kfree((unsigned int)child->vma);
118:        release_proc(child);
119:        return -ENOMEM;
120:    }
121:    child->rss += pages;
122:    invalidate_tlb();
123:
124:    child->tss.esp0 += PAGE_SIZE - 4;
125:    child->rss++;
126:    child->tss.ss0 = KERNEL_DS;
127:
128:    memcpy_b((unsigned int *) (child->tss.esp0 & PAGE_MASK), (void *) ((unsigned
ed int)(sc) & PAGE_MASK), PAGE_SIZE);
129:    stack = (struct sigcontext *) ((child->tss.esp0 & PAGE_MASK) + ((unsigned
int)(sc) & ~PAGE_MASK));
130:

```

kernel/syscalls/fork.c

Page 3/3

```
131:         child->tss.eip = (unsigned int)return_from_syscall;
132:         child->tss.esp = (unsigned int)stack;
133:         stack->eax = 0;           /* child returns 0 */
134:
135:         child->state = PROC_RUNNING;
136:
137:         /* increase file descriptors usage */
138:         for(n = 0; n < OPEN_MAX; n++) {
139:             if(current->fd[n]) {
140:                 fd_table[current->fd[n]].count++;
141:             }
142:         }
143:         if(current->root) {
144:             current->root->count++;
145:         }
146:         if(current->pwd) {
147:             current->pwd->count++;
148:         }
149:
150:         kstat.processes++;
151:         nr_processes++;
152:         current->children++;
153:
154:         return child->pid;       /* parent returns child's PID */
155:     }
```

kernel/syscalls/fstat.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/fstat.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/syscalls.h>
10: #include <fiwix/statbuf.h>
11: #include <fiwix/errno.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #include <fiwix/process.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_fstat(unsigned int ufd, struct old_stat *statbuf)
19: {
20:     struct inode *i;
21:     int errno;
22:
23: #ifdef __DEBUG__
24:     printk("(pid %d) sys_fstat(%d, 0x%08x) -> returning structure\n", current->pid, ufd, (unsigned int)statbuf);
25: #endif /* __DEBUG__ */
26:
27:     CHECK_UFD(ufd);
28:     if((errno = check_user_area(VERIFY_WRITE, statbuf, sizeof(struct old_stat)))) {
29:         return errno;
30:     }
31:     i = fd_table[current->fd[ufd]].inode;
32:     statbuf->st_dev = i->dev;
33:     statbuf->st_ino = i->ino;
34:     statbuf->st_mode = i->i_mode;
35:     statbuf->st_nlink = i->i_nlink;
36:     statbuf->st_uid = i->i_uid;
37:     statbuf->st_gid = i->i_gid;
38:     statbuf->st_rdev = i->rdev;
39:     statbuf->st_size = i->i_size;
40:     statbuf->st_atime = i->i_atime;
41:     statbuf->st_mtime = i->i_mtime;
42:     statbuf->st_ctime = i->i_ctime;
43:     return 0;
44: }

```

kernel/syscalls/fstatfs.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/fstatfs.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/statfs.h>
10: #include <fiwix/errno.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #include <fiwix/process.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_fstatfs(unsigned int ufd, struct statfs *statfsbuf)
18: {
19:     struct inode *i;
20:     int errno;
21:
22: #ifdef __DEBUG__
23:     printk("(pid %d) sys_fstatfs(%d, 0x%08x)\n", current->pid, ufd, (unsigned
d int)statfsbuf);
24: #endif /* __DEBUG__ */
25:
26:     CHECK_UFD(ufd);
27:     if((errno = check_user_area(VERIFY_WRITE, statfsbuf, sizeof(struct statf
s)))) {
28:         return errno;
29:     }
30:     i = fd_table[current->fd[ufd]].inode;
31:     if(i->sb && i->sb->fsop && i->sb->fsop->statfs) {
32:         i->sb->fsop->statfs(i->sb, statfsbuf);
33:         return 0;
34:     }
35:     return -ENOSYS;
36: }
```

kernel/syscalls/fsync.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/fsync.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/filesystems.h>
10: #include <fiwix/process.h>
11: #include <fiwix/stat.h>
12: #include <fiwix/buffer.h>
13: #include <fiwix/errno.h>
14:
15: #ifdef __DEBUG__
16: #include <fiwix/stdio.h>
17: #endif /* __DEBUG__ */
18:
19: int sys_fsync(int ufd)
20: {
21:     struct inode *i;
22:
23: #ifdef __DEBUG__
24:     printk("(pid %d) sys_fsync(%d)\n", current->pid, ufd);
25: #endif /* __DEBUG__ */
26:
27:     CHECK_UFD(ufd);
28:     i = fd_table[current->fd[ufd]].inode;
29:     if(!S_ISREG(i->i_mode)) {
30:         return -EINVAL;
31:     }
32:     if(IS_RDONLY_FS(i)) {
33:         return -EROFS;
34:     }
35:     sync_superblocks(i->dev);
36:     sync_inodes(i->dev);
37:     sync_buffers(i->dev);
38:     return 0;
39: }
```

kernel/syscalls/ftime.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/ftime.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/timeb.h>
11: #include <fiwix/timer.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #include <fiwix/process.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_ftime(struct timeb *tp)
19: {
20:     int errno;
21:
22: #ifdef __DEBUG__
23:     printk("(pid %d) sys_ftime()\n", current->pid);
24: #endif /* __DEBUG__ */
25:
26:     if((errno = check_user_area(VERIFY_WRITE, tp, sizeof(struct timeb)))) {
27:         return errno;
28:     }
29:     tp->time = CURRENT_TIME;
30:     tp->millitm = ((kstat.ticks % HZ) * 1000000) / HZ;
31:     /* FIXME: 'timezone' and 'dstflag' fields are not used */
32:
33:     return 0;
34: }
```

kernel/syscalls/ftruncate.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/ftruncate.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/fcntl.h>
11: #include <fiwix/stat.h>
12: #include <fiwix/errno.h>
13:
14: #ifdef __DEBUG__
15: #include <fiwix/stdio.h>
16: #include <fiwix/process.h>
17: #endif /* __DEBUG__ */
18:
19: int sys_ftruncate(int ufd, __off_t length)
20: {
21:     struct inode *i;
22:     int errno;
23:
24: #ifdef __DEBUG__
25:     printk("(pid %d) sys_ftruncate(%d, %d)\n", current->pid, ufd, length);
26: #endif /* __DEBUG__ */
27:
28:     CHECK_UFD(ufd);
29:     i = fd_table[current->fd[ufd]].inode;
30:     if((fd_table[current->fd[ufd]].flags & O_ACCMODE) == O_RDONLY) {
31:         return -EINVAL;
32:     }
33:     if(S_ISDIR(i->i_mode)) {
34:         return -EISDIR;
35:     }
36:     if(IS_RDONLY_FS(i)) {
37:         return -EROFS;
38:     }
39:     if(check_permission(TO_WRITE, i) < 0) {
40:         return -EPERM;
41:     }
42:     if(length == i->i_size) {
43:         return 0;
44:     }
45:
46:     errno = 0;
47:     if(i->fsop && i->fsop->truncate) {
48:         inode_lock(i);
49:         errno = i->fsop->truncate(i, length);
50:         inode_unlock(i);
51:     }
52:     return errno;
53: }
```

kernel/syscalls/getcwd.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/getcwd.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/errno.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #include <fiwix/process.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_getcwd(char *buf, __size_t size)
18: {
19:     int errno;
20:
21: #ifdef __DEBUG__
22:     printk("(pid %d) sys_getcwd(0x%08x, %d)\n", current->pid, (unsigned int)
buf, size);
23: #endif /* __DEBUG__ */
24:
25:     if((errno = check_user_area(VERIFY_WRITE, buf, size))) {
26:         return errno;
27:     }
28:     return -ENOSYS;
29: }
```


kernel/syscalls/getdents.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/getdents.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/dirent.h>
10: #include <fiwix/process.h>
11: #include <fiwix/stat.h>
12: #include <fiwix/errno.h>
13:
14: #ifdef __DEBUG__
15: #include <fiwix/stdio.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_getdents(unsigned int ufd, struct dirent *dirent, unsigned int count)
19: {
20:     struct inode *i;
21:     int errno;
22:
23: #ifdef __DEBUG__
24:     printk("(pid %d) sys_getdents(%d, 0x%08x, %d)", current->pid, ufd, (unsi
gned int)dirent, count);
25: #endif /* __DEBUG__ */
26:
27:     CHECK_UFD(ufd);
28:     if((errno = check_user_area(VERIFY_WRITE, dirent, sizeof(struct dirent))
)) {
29:         return errno;
30:     }
31:     i = fd_table[current->fd[ufd]].inode;
32:
33:     if(!S_ISDIR(i->i_mode)) {
34:         return -ENOTDIR;
35:     }
36:
37:     if(i->fsop && i->fsop->readdir) {
38:         errno = i->fsop->readdir(i, &fd_table[current->fd[ufd]], dirent,
count);
39:     }
40:     #ifdef __DEBUG__
41:     printk(" -> returning %d\n", errno);
42:     #endif /* __DEBUG__ */
43:     return errno;
44: }
45: }

```

kernel/syscalls/getegid.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/getegid.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/process.h>
9:
10: #ifdef __DEBUG__
11: #include <fiwix/stdio.h>
12: #endif /* __DEBUG__ */
13:
14: int sys_getegid(void)
15: {
16: #ifdef __DEBUG__
17:     printk("(pid %d) sys_getegid() -> %d\n", current->pid, current->egid);
18: #endif /* __DEBUG__ */
19:     return current->egid;
20: }
```

kernel/syscalls/geteuid.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/geteuid.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/process.h>
9:
10: #ifdef __DEBUG__
11: #include <fiwix/stdio.h>
12: #endif /* __DEBUG__ */
13:
14: int sys_geteuid(void)
15: {
16: #ifdef __DEBUG__
17:     printk("(pid %d) sys_geteuid() -> %d\n", current->pid, current->euid);
18: #endif /* __DEBUG__ */
19:     return current->euid;
20: }
```

kernel/syscalls/getgid.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/getgid.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/process.h>
9:
10: #ifdef __DEBUG__
11: #include <fiwix/stdio.h>
12: #endif /* __DEBUG__ */
13:
14: int sys_getgid(void)
15: {
16: #ifdef __DEBUG__
17:     printk("(pid %d) sys_getgid() -> %d\n", current->pid, current->gid);
18: #endif /* __DEBUG__ */
19:     return current->gid;
20: }
```

kernel/syscalls/getgroups.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/getgroups.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/process.h>
11: #include <fiwix/errno.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_getgroups(__ssize_t size, __gid_t *list)
18: {
19:     int n, errno;
20:
21: #ifdef __DEBUG__
22:     printk("(pid %d) sys_getgroups(%d, 0x%08x)\n", current->pid, size, (unsi
gned int)list);
23: #endif /* __DEBUG__ */
24:
25:     if((errno = check_user_area(VERIFY_WRITE, list, sizeof(__gid_t)))) {
26:         return errno;
27:     }
28:     for(n = 0; n < NGROUPS_MAX; n++) {
29:         if(current->groups[n] == -1) {
30:             break;
31:         }
32:         if(size) {
33:             if(n > size) {
34:                 return -EINVAL;
35:             }
36:             list[n] = (__gid_t)current->groups[n];
37:         }
38:     }
39:     return n;
40: }
```

kernel/syscalls/getitimer.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/getitimer.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/time.h>
10: #include <fiwix/process.h>
11: #include <fiwix/errno.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_getitimer(int which, struct itimerval *curr_value)
18: {
19:     int errno;
20:
21: #ifdef __DEBUG__
22:     printk("(pid %d) sys_getitimer(%d, 0x%08x) -> \n", current->pid, which,
(unsigned int)curr_value);
23: #endif /* __DEBUG__ */
24:
25:     if((unsigned int)curr_value) {
26:         if((errno = check_user_area(VERIFY_WRITE, curr_value, sizeof(struct itimerval)))) {
27:             return errno;
28:         }
29:     }
30:
31:     switch(which) {
32:         case ITIMER_REAL:
33:             ticks2tv(current->it_real_interval, &curr_value->it_interval);
34:             ticks2tv(current->it_real_value, &curr_value->it_value);
35:             break;
36:         case ITIMER_VIRTUAL:
37:             ticks2tv(current->it_virt_interval, &curr_value->it_interval);
38:             ticks2tv(current->it_virt_value, &curr_value->it_value);
39:             break;
40:         case ITIMER_PROF:
41:             ticks2tv(current->it_prof_interval, &curr_value->it_interval);
42:             ticks2tv(current->it_prof_value, &curr_value->it_value);
43:             break;
44:         default:
45:             return -EINVAL;
46:     }
47:     return 0;
48: }

```

kernel/syscalls/getpgid.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/getpgid.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/process.h>
10: #include <fiwix/sched.h>
11: #include <fiwix/errno.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_getpgid(__pid_t pid)
18: {
19:     struct proc *p;
20:
21: #ifdef __DEBUG__
22:     printk("(pid %d) sys_getpgid(%d)\n", current->pid, pid);
23: #endif /* __DEBUG__ */
24:
25:     if(pid < 0) {
26:         return -EINVAL;
27:     }
28:     if(!pid) {
29:         return current->pgid;
30:     }
31:     FOR_EACH_PROCESS(p) {
32:         if(p->state != PROC_UNUSED && p->pid == pid) {
33:             return p->pgid;
34:         }
35:     }
36:     return -ESRCH;
37: }
```

kernel/syscalls/getpgrp.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/getpgrp.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/process.h>
9:
10: #ifdef __DEBUG__
11: #include <fiwix/stdio.h>
12: #endif /* __DEBUG__ */
13:
14: int sys_getpgrp(void)
15: {
16: #ifdef __DEBUG__
17:     printk("(pid %d) sys_getpgrp() -> %d\n", current->pid, current->pgid);
18: #endif /* __DEBUG__ */
19:     return current->pgid;
20: }
```


kernel/syscalls/getpid.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/getpid.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/process.h>
9:
10: #ifdef __DEBUG__
11: #include <fiwix/stdio.h>
12: #endif /* __DEBUG__ */
13:
14: int sys_getpid(void)
15: {
16: #ifdef __DEBUG__
17:     printk("(pid %d) sys_getpid() -> %d\n", current->pid, current->pid);
18: #endif /* __DEBUG__ */
19:     return current->pid;
20: }
```

kernel/syscalls/getppid.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/getppid.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/process.h>
9:
10: #ifdef __DEBUG__
11: #include <fiwix/stdio.h>
12: #endif /* __DEBUG__ */
13:
14: int sys_getppid(void)
15: {
16: #ifdef __DEBUG__
17:     printk("(pid %d) sys_getppid() -> %d\n", current->pid, current->ppid);
18: #endif /* __DEBUG__ */
19:     return current->ppid;
20: }
```

kernel/syscalls/getrlimit.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/getrlimit.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/resource.h>
10: #include <fiwix/process.h>
11: #include <fiwix/errno.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_getrlimit(int resource, struct rlimit *rlim)
18: {
19:     int errno;
20:
21: #ifdef __DEBUG__
22:     printk("(pid %d) sys_getrlimit(%d, 0x%08x)\n", current->pid, resource, (
unsigned int)rlim);
23: #endif /* __DEBUG__ */
24:
25:     if((errno = check_user_area(VERIFY_WRITE, rlim, sizeof(struct rlimit))))
{
26:         return errno;
27:     }
28:     if(resource < 0 || resource >= RLIM_NLIMITS) {
29:         return -EINVAL;
30:     }
31:
32:     rlim->rlim_cur = current->rlim[resource].rlim_cur;
33:     rlim->rlim_max = current->rlim[resource].rlim_max;
34:     return 0;
35: }
```

kernel/syscalls/getrusage.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/getrusage.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/resource.h>
10: #include <fiwix/process.h>
11: #include <fiwix/errno.h>
12: #include <fiwix/string.h>
13:
14: #ifdef __DEBUG__
15: #include <fiwix/stdio.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_getrusage(int who, struct rusage *usage)
19: {
20:     int errno;
21:
22: #ifdef __DEBUG__
23:     printk("(pid %d) sys_getrusage(%d, 0x%08x)\n", current->pid, who, (unsi
ned int)usage);
24: #endif /* __DEBUG__ */
25:
26:     if((errno = check_user_area(VERIFY_WRITE, usage, sizeof(struct rusage)))
) {
27:         return errno;
28:     }
29:     switch(who) {
30:         case RUSAGE_SELF:
31:             memcpy_b(usage, &current->usage, sizeof(struct rusage));
32:             break;
33:         case RUSAGE_CHILDREN:
34:             memcpy_b(usage, &current->cusage, sizeof(struct rusage))
;
35:             break;
36:         default:
37:             return -EINVAL;
38:     }
39:     return 0;
40: }

```

kernel/syscalls/getsid.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/getsid.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/process.h>
10: #include <fiwix/sched.h>
11: #include <fiwix/errno.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_getsid(__pid_t pid)
18: {
19:     struct proc *p;
20:
21: #ifdef __DEBUG__
22:     printk("(pid %d) sys_getsid(%d)\n", current->pid, pid);
23: #endif /* __DEBUG__ */
24:
25:     if(pid < 0) {
26:         return -EINVAL;
27:     }
28:     if(!pid) {
29:         return current->sid;
30:     }
31:
32:     FOR_EACH_PROCESS(p) {
33:         if(p->state != PROC_UNUSED && p->pid == pid) {
34:             return p->sid;
35:         }
36:     }
37:     return -ESRCH;
38: }
```

kernel/syscalls/gettimeofday.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/gettimeofday.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/process.h>
11: #include <fiwix/time.h>
12: #include <fiwix/timer.h>
13:
14: #ifdef __DEBUG__
15: #include <fiwix/stdio.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_gettimeofday(struct timeval *tv, struct timezone *tz)
19: {
20:     int errno;
21:
22: #ifdef __DEBUG__
23:     printk("(pid %d) sys_gettimeofday()\n", current->pid);
24: #endif /* __DEBUG__ */
25:
26:     if(tv) {
27:         if((errno = check_user_area(VERIFY_WRITE, tv, sizeof(struct time
val)))) {
28:             return errno;
29:         }
30:         tv->tv_sec = CURRENT_TIME;
31:         tv->tv_usec = ((kstat.ticks % HZ) * 1000000) / HZ;
32:     }
33:     if(tz) {
34:         if((errno = check_user_area(VERIFY_WRITE, tz, sizeof(struct time
zone)))) {
35:             return errno;
36:         }
37:         tz->tz_minuteswest = kstat.tz_minuteswest;
38:         tz->tz_dsttime = kstat.tz_dsttime;
39:     }
40:     return 0;
41: }
```

kernel/syscalls/getuid.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/getuid.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/process.h>
9:
10: #ifdef __DEBUG__
11: #include <fiwix/stdio.h>
12: #endif /* __DEBUG__ */
13:
14: int sys_getuid(void)
15: {
16: #ifdef __DEBUG__
17:     printk("(pid %d) sys_getuid() -> %d\n", current->pid, current->uid);
18: #endif /* __DEBUG__ */
19:
20:     return current->uid;
21: }
```

kernel/syscalls/ioctl.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/ioctl.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/process.h>
9: #include <fiwix/errno.h>
10:
11: #ifdef __DEBUG__
12: #include <fiwix/stdio.h>
13: #endif /*__DEBUG__*/
14:
15: int sys_ioctl(unsigned int fd, int cmd, unsigned long int arg)
16: {
17:     int errno;
18:     struct inode *i;
19:
20: #ifdef __DEBUG__
21:     printk("(pid %d) sys_ioctl(%d, 0x%x, 0x%08x) -> ", current->pid, fd, cmd
, arg);
22: #endif /*__DEBUG__*/
23:
24:     CHECK_UFD(fd);
25:     i = fd_table[current->fd[fd]].inode;
26:     if(i->fsop && i->fsop->ioctl) {
27:         errno = i->fsop->ioctl(i, cmd, arg);
28:
29: #ifdef __DEBUG__
30:         printk("%d\n", errno);
31: #endif /*__DEBUG__*/
32:
33:         return errno;
34:     }
35:
36: #ifdef __DEBUG__
37:     printk("%d\n", -ENOTTY);
38: #endif /*__DEBUG__*/
39:
40:     return -ENOTTY;
41: }
```


kernel/syscalls/ioperm.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/ioperm.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/process.h>
9: #include <fiwix/errno.h>
10:
11: #ifdef __DEBUG__
12: #include <fiwix/stdio.h>
13: #endif /* __DEBUG__ */
14:
15: int sys_ioperm(unsigned long int from, unsigned long int num, int turn_on)
16: {
17: #ifdef __DEBUG__
18:     printk("(pid %d) sys_ioperm(0x%08x, 0x%08x, 0x%08x)\n", current->pid, fr
om, num, turn_on);
19: #endif /* __DEBUG__ */
20:
21:     if(!IS_SUPERUSER) {
22:         return -EPERM;
23:     }
24:
25:     /* FIXME: to be implemented */
26:
27:     return 0;
28: }
```

kernel/syscalls/iopl.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/iopl.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: /*
9:  * Chapter Input/Output of IA-32 Intel(R) Architecture Software Developer's
10:  * Manual Volume 1 Basic Architecture, says the processor permits applications
11:  * to access I/O ports in either of two ways: by using I/O address space or by
12:  * using memory-mapped I/O. Linux 2.0 and Fiwix uses the first one.
13:  *
14:  * This system call sets the IOPL field in the EFLAGS register to the value of
15:  * 'level' (which is presumably zero), so the current process will have
16:  * privileges to use any port, even if that port is beyond of the default size
17:  * of the I/O bitmap in TSS (which is IO_BITMAP_SIZE = 32). Otherwise the
18:  * processor checks the I/O permission bit map to determine if access to a
19:  * specific I/O port is allowed.
20:  *
21:  * So, we leave it here as in Linux 2.0. That means, leaving to I/O bit map to
22:  * control the ports up to 0x3FF, and the rest of ports will be controlled by
23:  * using this system call.
24:  */
25:
26: #include <fiwix/process.h>
27: #include <fiwix/segments.h>
28: #include <fiwix/sigcontext.h>
29: #include <fiwix/errno.h>
30:
31: #ifdef __DEBUG__
32: #include <fiwix/stdio.h>
33: #endif /* __DEBUG__ */
34:
35: int sys_iopl(int level, int arg2, int arg3, int arg4, int arg5, struct sigcontext
t *sc)
36: {
37: #ifdef __DEBUG__
38:     printk("(pid %d) sys_iopl(%d) -> ", current->pid, level);
39: #endif /* __DEBUG__ */
40:     if(level > USR_PL) {
41: #ifdef __DEBUG__
42:         printk("-EINVAL\n");
43: #endif /* __DEBUG__ */
44:         return -EINVAL;
45:     }
46:     if(!IS_SUPERUSER) {
47: #ifdef __DEBUG__
48:         printk("-EPERM\n");
49: #endif /* __DEBUG__ */
50:         return -EPERM;
51:     }
52:
53:     sc->eflags = (sc->eflags & 0xFFFFCFFF) | (level << EF_IOPL);
54: #ifdef __DEBUG__
55:     printk("0\n");
56: #endif /* __DEBUG__ */
57:     return 0;
58: }

```

kernel/syscalls/kill.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/kill.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/process.h>
10: #include <fiwix/errno.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #endif /* __DEBUG__ */
15:
16: int sys_kill(__pid_t pid, __sigset_t signum)
17: {
18:     int count;
19:     struct proc *p;
20:
21: #ifdef __DEBUG__
22:     printk("(pid %d) sys_kill(%d, %d)\n", current->pid, pid, signum);
23: #endif /* __DEBUG__ */
24:
25:     if(signum < 1 || signum > NSIG) {
26:         return -EINVAL;
27:     }
28:     if(pid == -1) {
29:         count = 0;
30:         FOR_EACH_PROCESS(p) {
31:             if(p->pid > 1 && p != current) {
32:                 count++;
33:                 send_sig(p, signum);
34:             }
35:         }
36:         return count ? 0 : -ESRCH;
37:     }
38:     if(!pid) {
39:         return kill_pgrp(current->pgrp, signum);
40:     }
41:     if(pid < 1) {
42:         return kill_pgrp(-pid, signum);
43:     }
44:
45:     return kill_pid(pid, signum);
46: }
```

kernel/syscalls/link.c

Page 1/2

```

1: /*
2:  * fiwix/kernel/syscalls/link.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/stat.h>
10: #include <fiwix/errno.h>
11: #include <fiwix/string.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #include <fiwix/process.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_link(const char *oldname, const char *newname)
19: {
20:     struct inode *i, *dir, *i_new, *dir_new;
21:     char *tmp_oldname, *tmp_newname, *basename;
22:     int errno;
23:
24: #ifdef __DEBUG__
25:     printk("(pid %d) sys_link('%s', '%s')\n", current->pid, oldname, newname
);
26: #endif /* __DEBUG__ */
27:
28:     if((errno = malloc_name(oldname, &tmp_oldname)) < 0) {
29:         return errno;
30:     }
31:     if((errno = malloc_name(newname, &tmp_newname)) < 0) {
32:         free_name(tmp_oldname);
33:         return errno;
34:     }
35:
36:     if((errno = namei(tmp_oldname, &i, &dir, !FOLLOW_LINKS))) {
37:         if(dir) {
38:             iput(dir);
39:         }
40:         free_name(tmp_oldname);
41:         free_name(tmp_newname);
42:         return errno;
43:     }
44:     if(S_ISDIR(i->i_mode)) {
45:         iput(i);
46:         iput(dir);
47:         free_name(tmp_oldname);
48:         free_name(tmp_newname);
49:         return -EPERM;
50:     }
51:     if(IS_RDONLY_FS(i)) {
52:         iput(i);
53:         iput(dir);
54:         free_name(tmp_oldname);
55:         free_name(tmp_newname);
56:         return -EROFS;
57:     }
58:     if(i->i_nlink == LINK_MAX) {
59:         iput(i);
60:         iput(dir);
61:         free_name(tmp_oldname);
62:         free_name(tmp_newname);
63:         return -EMLINK;
64:     }
65:
66:     basename = get_basename(tmp_newname);

```

kernel/syscalls/link.c

Page 2/2

```
67:         if((errno = namei(tmp_newname, &i_new, &dir_new, !FOLLOW_LINKS))) {
68:             if(!dir_new) {
69:                 iput(i);
70:                 iput(dir);
71:                 free_name(tmp_oldname);
72:                 free_name(tmp_newname);
73:                 return errno;
74:             }
75:         }
76:         if(!errno) {
77:             iput(i);
78:             iput(dir);
79:             iput(i_new);
80:             iput(dir_new);
81:             free_name(tmp_oldname);
82:             free_name(tmp_newname);
83:             return -EEXIST;
84:         }
85:         if(i->dev != dir_new->dev) {
86:             iput(i);
87:             iput(dir);
88:             iput(dir_new);
89:             free_name(tmp_oldname);
90:             free_name(tmp_newname);
91:             return -EXDEV;
92:         }
93:         if(check_permission(TO_EXEC | TO_WRITE, dir_new) < 0) {
94:             iput(i);
95:             iput(dir);
96:             iput(dir_new);
97:             free_name(tmp_oldname);
98:             free_name(tmp_newname);
99:             return -EACCES;
100:        }
101:
102:        if(dir_new->fsop && dir_new->fsop->link) {
103:            errno = dir_new->fsop->link(i, dir_new, basename);
104:        } else {
105:            errno = -EPERM;
106:        }
107:        iput(i);
108:        iput(dir);
109:        iput(dir_new);
110:        free_name(tmp_oldname);
111:        free_name(tmp_newname);
112:        return errno;
113:    }
```

kernel/syscalls/llseek.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/llseek.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/process.h>
11: #include <fiwix/errno.h>
12: #include <fiwix/string.h>
13:
14: #ifdef __DEBUG__
15: #include <fiwix/stdio.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_llseek(unsigned int ufd, unsigned long int offset_high, unsigned long in
t offset_low, __loff_t *result, unsigned int whence)
19: {
20:     struct inode *i;
21:     __loff_t offset;
22:     __loff_t new_offset;
23:     int errno;
24:
25: #ifdef __DEBUG__
26:     printk("(pid %d) sys_llseek(%d, %d, %d, %08x, %d)", current->pid, ufd, o
ffset_high, offset_low, result, whence);
27: #endif /* __DEBUG__ */
28:
29:     CHECK_UFD(ufd);
30:     if((errno = check_user_area(VERIFY_WRITE, result, sizeof(__loff_t)))) {
31:         return errno;
32:     }
33:     i = fd_table[current->fd[ufd]].inode;
34:     offset = (__loff_t) (((__loff_t)offset_high << 32) | offset_low);
35:     switch(whence) {
36:         case SEEK_SET:
37:             new_offset = offset;
38:             break;
39:         case SEEK_CUR:
40:             new_offset = fd_table[current->fd[ufd]].offset + offset;
41:             break;
42:         case SEEK_END:
43:             new_offset = i->i_size + offset;
44:             break;
45:         default:
46:             return -EINVAL;
47:     }
48:     fd_table[current->fd[ufd]].offset = new_offset;
49:
50: #ifdef __DEBUG__
51:     printk(" -> returning %d\n", new_offset);
52: #endif /* __DEBUG__ */
53:
54:     memcpy_b(result, &new_offset, sizeof(__loff_t));
55:     return 0;
56: }

```

kernel/syscalls/lseek.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/lseek.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/syscalls.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/errno.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #include <fiwix/process.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_lseek(unsigned int ufd, __off_t offset, unsigned int whence)
19: {
20:     struct inode *i;
21:     __off_t new_offset;
22:
23: #ifdef __DEBUG__
24:     printk("(pid %d) sys_lseek(%d, %d, %d)", current->pid, ufd, offset, when
ce);
25: #endif /* __DEBUG__ */
26:
27:     CHECK_UFD(ufd);
28:
29:     i = fd_table[current->fd[ufd]].inode;
30:     switch(whence) {
31:         case SEEK_SET:
32:             new_offset = offset;
33:             break;
34:         case SEEK_CUR:
35:             new_offset = fd_table[current->fd[ufd]].offset + offset;
36:             break;
37:         case SEEK_END:
38:             new_offset = i->i_size + offset;
39:             break;
40:         default:
41:             return -EINVAL;
42:     }
43:     if((int)new_offset < 0) {
44:         return -EINVAL;
45:     }
46:     if(i->fsop && i->fsop->lseek) {
47:         fd_table[current->fd[ufd]].offset = new_offset;
48:         new_offset = i->fsop->lseek(i, new_offset);
49:     } else {
50:         return -EPERM;
51:     }
52:
53: #ifdef __DEBUG__
54:     printk(" -> returning %d\n", new_offset);
55: #endif /* __DEBUG__ */
56:
57:     return new_offset;
58: }

```

kernel/syscalls/lstat.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/lstat.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/stat.h>
10: #include <fiwix/string.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #include <fiwix/process.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_lstat(const char *filename, struct old_stat *statbuf)
18: {
19:     struct inode *i;
20:     char *tmp_name;
21:     int errno;
22:
23: #ifdef __DEBUG__
24:     printk("(pid %d) sys_lstat('%s', 0x%08x) -> returning structure\n", curr
ent->pid, filename, (unsigned int )statbuf);
25: #endif /* __DEBUG__ */
26:
27:     if((errno = check_user_area(VERIFY_WRITE, statbuf, sizeof(struct old_sta
t)))) {
28:         return errno;
29:     }
30:     if((errno = malloc_name(filename, &tmp_name)) < 0) {
31:         return errno;
32:     }
33:     if((errno = namei(tmp_name, &i, NULL, !FOLLOW_LINKS))) {
34:         free_name(tmp_name);
35:         return errno;
36:     }
37:     statbuf->st_dev = i->dev;
38:     statbuf->st_ino = i->inode;
39:     statbuf->st_mode = i->i_mode;
40:     statbuf->st_nlink = i->i_nlink;
41:     statbuf->st_uid = i->i_uid;
42:     statbuf->st_gid = i->i_gid;
43:     statbuf->st_rdev = i->rdev;
44:     statbuf->st_size = i->i_size;
45:     statbuf->st_atime = i->i_atime;
46:     statbuf->st_mtime = i->i_mtime;
47:     statbuf->st_ctime = i->i_ctime;
48:     iput(i);
49:     free_name(tmp_name);
50:     return 0;
51: }

```


kernel/syscalls/Makefile

Page 1/1

```
1: # fiwix/kernel/syscalls/Makefile
2: #
3: # Copyright 2018, Jordi Sanfeliu. All rights reserved.
4: # Distributed under the terms of the Fiwix License.
5: #
6: #
7: .S.o:
8:     $(CC) -traditional -I$(INCLUDE) -c -o $@ $<
9: .c.o:
10:     $(CC) $(CFLAGS) -c -o $@ $<
11:
12: SRC = $(wildcard *.c)
13: OBJS = $(patsubst %.c,%.o,$(SRC))
14:
15: lib:    $(OBJS)
16:         $(LD) $(LDFLAGS) -r $(OBJS) -o syscalls.o
17:
18: clean:
19:     rm -f *.o
20:
```

kernel/syscalls/mkdir.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/mkdir.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/stat.h>
11: #include <fiwix/errno.h>
12: #include <fiwix/string.h>
13:
14: #ifdef __DEBUG__
15: #include <fiwix/stdio.h>
16: #include <fiwix/process.h>
17: #endif /* __DEBUG__ */
18:
19: int sys_mkdir(const char *dirname, __mode_t mode)
20: {
21:     struct inode *i, *dir;
22:     char *tmp_dirname, *basename;
23:     int errno;
24:
25: #ifdef __DEBUG__
26:     printk("(pid %d) sys_mkdir('%s', %o)\n", current->pid, dirname, mode);
27: #endif /* __DEBUG__ */
28:
29:     if((errno = malloc_name(dirname, &tmp_dirname)) < 0) {
30:         return errno;
31:     }
32:     basename = remove_trailing_slash(tmp_dirname);
33:     if((errno = namei(basename, &i, &dir, !FOLLOW_LINKS)) {
34:         if(!dir) {
35:             free_name(tmp_dirname);
36:             return errno;
37:         }
38:     }
39:     if(!errno) {
40:         iput(i);
41:         iput(dir);
42:         free_name(tmp_dirname);
43:         return -EEXIST;
44:     }
45:     if(IS_RDONLY_FS(dir)) {
46:         iput(dir);
47:         free_name(tmp_dirname);
48:         return -EROFS;
49:     }
50:
51:     if(check_permission(TO_EXEC | TO_WRITE, dir) < 0) {
52:         iput(dir);
53:         free_name(tmp_dirname);
54:         return -EACCES;
55:     }
56:
57:     basename = get_basename(basename);
58:     if(dir->fsop && dir->fsop->mkdir) {
59:         errno = dir->fsop->mkdir(dir, basename, mode);
60:     } else {
61:         errno = -EPERM;
62:     }
63:     iput(dir);
64:     free_name(tmp_dirname);
65:     return errno;
66: }

```

kernel/syscalls/mknod.c

Page 1/2

```

1: /*
2:  * fiwix/kernel/syscalls/mknod.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/stat.h>
11: #include <fiwix/errno.h>
12: #include <fiwix/string.h>
13:
14: #ifdef __DEBUG__
15: #include <fiwix/stdio.h>
16: #include <fiwix/process.h>
17: #endif /* __DEBUG__ */
18:
19: int sys_mknod(const char *pathname, __mode_t mode, __dev_t dev)
20: {
21:     struct inode *i, *dir;
22:     char *tmp_name, *basename;
23:     int errno;
24:
25: #ifdef __DEBUG__
26:     printk("(pid %d) sys_mknod('%s', %d, %x)\n", current->pid, pathname, mod
e, dev);
27: #endif /* __DEBUG__ */
28:
29:     if(!S_ISCHR(mode) && !S_ISBLK(mode) && !S_ISFIFO(mode)) {
30:         return -EINVAL;
31:     }
32:     if(!S_ISFIFO(mode) && !IS_SUPERUSER) {
33:         return -EPERM;
34:     }
35:
36:     if((errno = malloc_name(pathname, &tmp_name)) < 0) {
37:         return errno;
38:     }
39:     basename = get_basename(tmp_name);
40:     if((errno = namei(tmp_name, &i, &dir, !FOLLOW_LINKS))) {
41:         if(!dir) {
42:             free_name(tmp_name);
43:             return errno;
44:         }
45:     }
46:     if(!errno) {
47:         iput(i);
48:         iput(dir);
49:         free_name(tmp_name);
50:         return -EEXIST;
51:     }
52:     if(IS_RDONLY_FS(dir)) {
53:         iput(dir);
54:         free_name(tmp_name);
55:         return -EROFS;
56:     }
57:     if(check_permission(TO_EXEC | TO_WRITE, dir) < 0) {
58:         iput(dir);
59:         free_name(tmp_name);
60:         return -EACCES;
61:     }
62:
63:     if(dir->fsop && dir->fsop->mknod) {
64:         errno = dir->fsop->mknod(dir, basename, mode, dev);
65:     } else {
66:         errno = -EPERM;

```

kernel/syscalls/mknod.c

Page 2/2

```
67:         }
68:         iput(dir);
69:         free_name(tmp_name);
70:         return errno;
71:     }
```

kernel/syscalls/mount.c

Page 1/4

```

1: /*
2:  * fiwix/kernel/syscalls/mount.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/stat.h>
11: #include <fiwix/buffer.h>
12: #include <fiwix/mman.h>
13: #include <fiwix/filesystems.h>
14: #include <fiwix/mm.h>
15: #include <fiwix/errno.h>
16: #include <fiwix/string.h>
17:
18: #ifdef __DEBUG__
19: #include <fiwix/stdio.h>
20: #include <fiwix/process.h>
21: #endif /* __DEBUG__ */
22:
23: int sys_mount(const char *source, const char *target, const char *fstype, unsigned long int flags, const void *data)
24: {
25:     struct inode *i_source, *i_target;
26:     struct mount *mt;
27:     struct filesystems *fs;
28:     struct vma *vma;
29:     char *tmp_source, *tmp_target, *tmp_fstype;
30:     __dev_t dev;
31:     int len, errno;
32:
33: #ifdef __DEBUG__
34:     printk("(pid %d) sys_mount(%s, %s, %s, 0x%08x, 0x%08x\n", current->pid,
source, target, (int)fstype ? fstype : "<NULL>", flags, data);
35: #endif /* __DEBUG__ */
36:
37:     if(!IS_SUPERUSER) {
38:         return -EPERM;
39:     }
40:
41:     if((errno = malloc_name(target, &tmp_target)) < 0) {
42:         return errno;
43:     }
44:     if((errno = namei(tmp_target, &i_target, NULL, FOLLOW_LINKS))) {
45:         free_name(tmp_target);
46:         return errno;
47:     }
48:     if(!S_ISDIR(i_target->i_mode)) {
49:         iput(i_target);
50:         free_name(tmp_target);
51:         return -ENOTDIR;
52:     }
53:     if((flags & MS_MGC_VAL) == MS_MGC_VAL) {
54:         flags &= ~MS_MGC_MSK;
55:     }
56:
57:     if(flags & MS_REMOUNT) {
58:         if(!(mt = get_mount_point(i_target))) {
59:             iput(i_target);
60:             free_name(tmp_target);
61:             return -EINVAL;
62:         }
63:         fs = mt->fs;
64:         if(fs->fsop && fs->fsop->remount_fs) {
65:             if((errno = fs->fsop->remount_fs(&mt->sb, flags))) {

```

kernel/syscalls/mount.c

Page 2/4

```

66:             iput(i_target);
67:             free_name(tmp_target);
68:             return errno;
69:         }
70:     } else {
71:         iput(i_target);
72:         free_name(tmp_target);
73:         return -EINVAL;
74:     }
75:
76:     /* switching from RW to RO */
77:     if(flags & MS_RDONLY && !(mt->sb.flags & MS_RDONLY)) {
78:         dev = mt->dev;
79:         /*
80:          * FIXME: if there are files opened in RW mode then
81:          * we can't continue and must return -EBUSY.
82:          */
83:         if(fs->fsop && fs->fsop->release_superblock) {
84:             fs->fsop->release_superblock(&mt->sb);
85:         }
86:         sync_superblocks(dev);
87:         sync_inodes(dev);
88:         sync_buffers(dev);
89:     }
90:
91:     mt->sb.flags &= ~MS_RDONLY;
92:     mt->sb.flags |= (flags & MS_RDONLY);
93:     iput(i_target);
94:     free_name(tmp_target);
95:     return 0;
96: }
97:
98: if(i_target->mount_point) {
99:     iput(i_target);
100:    free_name(tmp_target);
101:    return -EBUSY;
102: }
103:
104: /* check the validity of fstype */
105: if(!(vma = find_vma_region((unsigned int)fstype))) {
106:     iput(i_target);
107:     free_name(tmp_target);
108:     return -EFAULT;
109: }
110: if(!(vma->prot & PROT_READ)) {
111:     iput(i_target);
112:     free_name(tmp_target);
113:     return -EFAULT;
114: }
115: len = MIN(vma->end - (unsigned int)fstype, PAGE_SIZE - 1);
116: if(!(tmp_fstype = (char *)kmalloc())) {
117:     iput(i_target);
118:     free_name(tmp_target);
119:     return -ENOMEM;
120: }
121: memcpy_b(tmp_fstype, fstype, len);
122:
123: if(!(fs = get_filesystem(fstype))) {
124:     iput(i_target);
125:     free_name(tmp_target);
126:     free_name(tmp_fstype);
127:     return -ENODEV;
128: }
129: dev = fs->fsop->fsdev;
130:
131: if((errno = malloc_name(source, &tmp_source)) < 0) {
132:     iput(i_target);

```

kernel/syscalls/mount.c

Page 3/4

```

133:         free_name(tmp_target);
134:         free_name(tmp_fstype);
135:         return errno;
136:     }
137:     if(fs->fsop->flags == FSOP_REQUIRES_DEV) {
138:         if((errno = namei(tmp_source, &i_source, NULL, FOLLOW_LINKS))) {
139:             iput(i_target);
140:             free_name(tmp_target);
141:             free_name(tmp_fstype);
142:             free_name(tmp_source);
143:             return errno;
144:         }
145:         if(!S_ISBLK(i_source->i_mode)) {
146:             iput(i_target);
147:             iput(i_source);
148:             free_name(tmp_target);
149:             free_name(tmp_fstype);
150:             free_name(tmp_source);
151:             return -ENOTBLK;
152:         }
153:         if(i_source->fsop && i_source->fsop->open) {
154:             if((errno = i_source->fsop->open(i_source, NULL))) {
155:                 iput(i_target);
156:                 iput(i_source);
157:                 free_name(tmp_target);
158:                 free_name(tmp_fstype);
159:                 free_name(tmp_source);
160:                 return errno;
161:             }
162:         } else {
163:             iput(i_target);
164:             iput(i_source);
165:             free_name(tmp_target);
166:             free_name(tmp_fstype);
167:             free_name(tmp_source);
168:             return -EINVAL;
169:         }
170:         dev = i_source->rdev;
171:     }
172:
173:     if(!(mt = get_free_mount_point(dev))) {
174:         if(fs->fsop->flags == FSOP_REQUIRES_DEV) {
175:             i_source->fsop->close(i_source, NULL);
176:             iput(i_source);
177:         }
178:         iput(i_target);
179:         free_name(tmp_target);
180:         free_name(tmp_fstype);
181:         free_name(tmp_source);
182:         return -EBUSY;
183:     }
184:
185:     mt->sb.flags = flags;
186:     if(fs->fsop && fs->fsop->read_superblock) {
187:         if((errno = fs->fsop->read_superblock(dev, &mt->sb))) {
188:             i_source->fsop->close(i_source, NULL);
189:             if(fs->fsop->flags == FSOP_REQUIRES_DEV) {
190:                 iput(i_source);
191:             }
192:             iput(i_target);
193:             release_mount_point(mt);
194:             free_name(tmp_target);
195:             free_name(tmp_fstype);
196:             free_name(tmp_source);
197:             return errno;
198:         }
199:     } else {

```

kernel/syscalls/mount.c

Page 4/4

```
200:             if(fs->fsop->flags == FSOP_REQUIRES_DEV) {
201:                 iput(i_source);
202:             }
203:             iput(i_target);
204:             release_mount_point(mt);
205:             free_name(tmp_target);
206:             free_name(tmp_fstype);
207:             free_name(tmp_source);
208:             return -EINVAL;
209:         }
210:
211:         mt->dev = dev;
212:         strncpy(mt->devname, tmp_source, DEVNAME_MAX);
213:         strcpy(mt->dirname, tmp_target);
214:         mt->sb.dir = i_target;
215:         mt->fs = fs;
216:         i_target->mount_point = mt->sb.root;
217:         free_name(tmp_target);
218:         free_name(tmp_fstype);
219:         free_name(tmp_source);
220:         return 0;
221:     }
```


kernel/syscalls/mprotect.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/mprotect.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/mman.h>
10: #include <fiwix/mm.h>
11: #include <fiwix/fcntl.h>
12: #include <fiwix/errno.h>
13:
14: #ifdef __DEBUG__
15: #include <fiwix/stdio.h>
16: #include <fiwix/process.h>
17: #endif /* __DEBUG__ */
18:
19: int sys_mprotect(unsigned int addr, __size_t length, int prot)
20: {
21:     struct vma *vma;
22:
23: #ifdef __DEBUG__
24:     printk("(pid %d) sys_mprotect(0x%08x, %d, %d)\n", current->pid, addr, le
ngth, prot);
25: #endif /* __DEBUG__ */
26:
27:     if((addr & ~PAGE_MASK) || length < 0) {
28:         return -EINVAL;
29:     }
30:     if(prot > (PROT_READ | PROT_WRITE | PROT_EXEC)) {
31:         return -EINVAL;
32:     }
33:     if(!(vma = find_vma_region(addr))) {
34:         return -ENOMEM;
35:     }
36:     length = PAGE_ALIGN(length);
37:     if((addr + length) > vma->end) {
38:         return -ENOMEM;
39:     }
40:     if(vma->inode && (vma->flags & MAP_SHARED)) {
41:         if(prot & PROT_WRITE) {
42:             if(!(vma->o_mode & (O_WRONLY | O_RDWR))) {
43:                 return -EACCES;
44:             }
45:         }
46:     }
47:
48:     return do_mprotect(vma, addr, length, prot);
49: }

```

kernel/syscalls/munmap.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/munmap.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/mman.h>
10:
11: #ifdef __DEBUG__
12: #include <fiwix/stdio.h>
13: #include <fiwix/process.h>
14: #endif /* __DEBUG__ */
15:
16: int sys_munmap(unsigned int addr, __size_t length)
17: {
18: #ifdef __DEBUG__
19:     printk("(pid %d) sys_munmap(0x%08x, %d)\n", current->pid, addr, length);
20: #endif /* __DEBUG__ */
21:     return do_munmap(addr, length);
22: }
```

kernel/syscalls/nanosleep.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/nanosleep.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/time.h>
10: #include <fiwix/timer.h>
11: #include <fiwix/process.h>
12: #include <fiwix/sched.h>
13: #include <fiwix/sleep.h>
14: #include <fiwix/errno.h>
15:
16: #ifdef __DEBUG__
17: #include <fiwix/stdio.h>
18: #endif /* __DEBUG__ */
19:
20: int sys_nanosleep(const struct timespec *req, struct timespec *rem)
21: {
22:     int errno;
23:
24: #ifdef __DEBUG__
25:     printk("(pid %d) sys_nanosleep(0x%08x, 0x%08x)\n", current->pid, (unsigned
ed int)req, (unsigned int)rem);
26: #endif /* __DEBUG__ */
27:
28:     if((errno = check_user_area(VERIFY_READ, req, sizeof(struct timespec))))
{
29:         return errno;
30:     }
31:     if(req->tv_sec < 0 || req->tv_nsec >= 1000000000L || req->tv_nsec < 0) {
32:         return -EINVAL;
33:     }
34:
35:     current->timeout = (req->tv_sec * HZ) + (req->tv_nsec * HZ / 1000000000L
);
36:     if(current->timeout) {
37:         sleep(&sys_nanosleep, PROC_INTERRUPTIBLE);
38:         if(current->timeout) {
39:             if(rem) {
40:                 if((errno = check_user_area(VERIFY_WRITE, rem, s
izeof(struct timespec)))) {
41:                     return errno;
42:                 }
43:                 rem->tv_sec = current->timeout / HZ;
44:                 rem->tv_nsec = (current->timeout % HZ) * 1000000
000L / HZ;
45:             }
46:             return -EINTR;
47:         }
48:     }
49:     return 0;
50: }

```

kernel/syscalls/newfstat.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/newfstat.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/statbuf.h>
10: #include <fiwix/process.h>
11: #include <fiwix/errno.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_newfstat(unsigned int ufd, struct new_stat *statbuf)
18: {
19:     struct inode *i;
20:     int errno;
21:
22: #ifdef __DEBUG__
23:     printk("(pid %d) sys_newfstat(%d, 0x%08x) -> returning structure\n", cur
rent->pid, ufd, (unsigned int )statbuf);
24: #endif /* __DEBUG__ */
25:
26:     CHECK_UFD(ufd);
27:     if((errno = check_user_area(VERIFY_WRITE, statbuf, sizeof(struct new_sta
t)))) {
28:         return errno;
29:     }
30:     i = fd_table[current->fd[ufd]].inode;
31:     statbuf->st_dev = i->dev;
32:     statbuf->__pad1 = 0;
33:     statbuf->st_ino = i->inode;
34:     statbuf->st_mode = i->i_mode;
35:     statbuf->st_nlink = i->i_nlink;
36:     statbuf->st_uid = i->i_uid;
37:     statbuf->st_gid = i->i_gid;
38:     statbuf->st_rdev = i->rdev;
39:     statbuf->__pad2 = 0;
40:     statbuf->st_size = i->i_size;
41:     statbuf->st_blksize = i->sb->s_blocksize;
42:     statbuf->st_blocks = i->i_blocks;
43:     if(!i->i_blocks) {
44:         statbuf->st_blocks = (i->i_size / i->sb->s_blocksize * 2);
45:         statbuf->st_blocks++;
46:     }
47:     statbuf->st_atime = i->i_atime;
48:     statbuf->__unused1 = 0;
49:     statbuf->st_mtime = i->i_mtime;
50:     statbuf->__unused2 = 0;
51:     statbuf->st_ctime = i->i_ctime;
52:     statbuf->__unused3 = 0;
53:     statbuf->__unused4 = 0;
54:     statbuf->__unused5 = 0;
55:     return 0;
56: }

```

kernel/syscalls/newlstat.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/newlstat.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/statbuf.h>
10: #include <fiwix/string.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #include <fiwix/process.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_newlstat(const char *filename, struct new_stat *statbuf)
18: {
19:     struct inode *i;
20:     char *tmp_name;
21:     int errno;
22:
23: #ifdef __DEBUG__
24:     printk("(pid %d) sys_newlstat('%s', 0x%08x) -> returning structure\n", c
urrent->pid, filename, (unsigned int)statbuf);
25: #endif /* __DEBUG__ */
26:
27:     if((errno = check_user_area(VERIFY_WRITE, statbuf, sizeof(struct new_sta
t)))) {
28:         return errno;
29:     }
30:     if((errno = malloc_name(filename, &tmp_name)) < 0) {
31:         return errno;
32:     }
33:     if((errno = namei(tmp_name, &i, NULL, !FOLLOW_LINKS))) {
34:         free_name(tmp_name);
35:         return errno;
36:     }
37:     statbuf->st_dev = i->dev;
38:     statbuf->__pad1 = 0;
39:     statbuf->st_ino = i->inode;
40:     statbuf->st_mode = i->i_mode;
41:     statbuf->st_nlink = i->i_nlink;
42:     statbuf->st_uid = i->i_uid;
43:     statbuf->st_gid = i->i_gid;
44:     statbuf->st_rdev = i->rdev;
45:     statbuf->__pad2 = 0;
46:     statbuf->st_size = i->i_size;
47:     statbuf->st_blksize = i->sb->s_blocksize;
48:     statbuf->st_blocks = i->i_blocks;
49:     if(!i->i_blocks) {
50:         statbuf->st_blocks = (i->i_size / i->sb->s_blocksize) * 2;
51:         statbuf->st_blocks++;
52:     }
53:     statbuf->st_atime = i->i_atime;
54:     statbuf->__unused1 = 0;
55:     statbuf->st_mtime = i->i_mtime;
56:     statbuf->__unused2 = 0;
57:     statbuf->st_ctime = i->i_ctime;
58:     statbuf->__unused3 = 0;
59:     statbuf->__unused4 = 0;
60:     statbuf->__unused5 = 0;
61:     iput(i);
62:     free_name(tmp_name);
63:     return 0;
64: }

```

kernel/syscalls/newstat.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/newstat.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/statbuf.h>
10: #include <fiwix/string.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #include <fiwix/process.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_newstat(const char *filename, struct new_stat *statbuf)
18: {
19:     struct inode *i;
20:     char *tmp_name;
21:     int errno;
22:
23: #ifdef __DEBUG__
24:     printk("(pid %d) sys_newstat('%s', 0x%08x) -> returning structure\n", cu
rrent->pid, filename, (unsigned int )statbuf);
25: #endif /* __DEBUG__ */
26:
27:     if((errno = check_user_area(VERIFY_WRITE, statbuf, sizeof(struct new_sta
t)))) {
28:         return errno;
29:     }
30:     if((errno = malloc_name(filename, &tmp_name)) < 0) {
31:         return errno;
32:     }
33:     if((errno = namei(tmp_name, &i, NULL, FOLLOW_LINKS))) {
34:         free_name(tmp_name);
35:         return errno;
36:     }
37:     statbuf->st_dev = i->dev;
38:     statbuf->__pad1 = 0;
39:     statbuf->st_ino = i->inode;
40:     statbuf->st_mode = i->i_mode;
41:     statbuf->st_nlink = i->i_nlink;
42:     statbuf->st_uid = i->i_uid;
43:     statbuf->st_gid = i->i_gid;
44:     statbuf->st_rdev = i->rdev;
45:     statbuf->__pad2 = 0;
46:     statbuf->st_size = i->i_size;
47:     statbuf->st_blksize = i->sb->s_blocksize;
48:     statbuf->st_blocks = i->i_blocks;
49:     if(!i->i_blocks) {
50:         statbuf->st_blocks = (i->i_size / i->sb->s_blocksize) * 2;
51:         statbuf->st_blocks++;
52:     }
53:     statbuf->st_atime = i->i_atime;
54:     statbuf->__unused1 = 0;
55:     statbuf->st_mtime = i->i_mtime;
56:     statbuf->__unused2 = 0;
57:     statbuf->st_ctime = i->i_ctime;
58:     statbuf->__unused3 = 0;
59:     statbuf->__unused4 = 0;
60:     statbuf->__unused5 = 0;
61:     iput(i);
62:     free_name(tmp_name);
63:     return 0;
64: }

```

kernel/syscalls/newuname.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/newuname.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/utsname.h>
10: #include <fiwix/errno.h>
11: #include <fiwix/string.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #include <fiwix/process.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_newuname(struct new_utsname *uname)
19: {
20:     int errno;
21:
22: #ifdef __DEBUG__
23:     printk("(pid %d) sys_newuname(0x%08x)\n", current->pid, (int)uname);
24: #endif /* __DEBUG__ */
25:
26:     if((errno = check_user_area(VERIFY_WRITE, uname, sizeof(struct new_utsna
me)))) {
27:         return errno;
28:     }
29:     if(!uname) {
30:         return -EFAULT;
31:     }
32:     memcpy_b(uname, &sys_utsname, sizeof(struct new_utsname));
33:     return 0;
34: }
```

kernel/syscalls/old_mmap.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/old_mmap.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/mman.h>
10: #include <fiwix/mm.h>
11: #include <fiwix/fcntl.h>
12: #include <fiwix/errno.h>
13: #include <fiwix/string.h>
14:
15: #ifdef __DEBUG__
16: #include <fiwix/stdio.h>
17: #include <fiwix/process.h>
18: #endif /* __DEBUG__ */
19:
20: int old_mmap(struct mmap *mmap)
21: {
22:     unsigned int page;
23:     struct inode *i;
24:     char flags;
25:     int errno;
26:
27: #ifdef __DEBUG__
28:     printk("(pid %d) old_mmap(0x%08x, %d, 0x%02x, 0x%02x, %d, 0x%08x) -> ",
current->pid, mmap->start, mmap->length, mmap->prot, mmap->flags, mmap->offse
t);
29: #endif /* __DEBUG__ */
30:
31:     if((errno = check_user_area(VERIFY_READ, mmap, sizeof(struct mmap)))) {
32:         return errno;
33:     }
34:     if(!mmap->length) {
35:         return -EINVAL;
36:     }
37:
38:     i = NULL;
39:     flags = 0;
40:     if(!(mmap->flags & MAP_ANONYMOUS)) {
41:         CHECK_UFD(mmap->fd);
42:         if(!(i = fd_table[current->fd[mmap->fd]].inode)) {
43:             return -EBADF;
44:         }
45:         flags = fd_table[current->fd[mmap->fd]].flags & O_ACCMODE;
46:     }
47:     page = do_mmap(i, mmap->start, mmap->length, mmap->prot, mmap->flags, mm
ap->offset, P_MMAP, flags);
48: #ifdef __DEBUG__
49:     printk("0x%08x\n", page);
50: #endif /* __DEBUG__ */
51:     return page;
52: }

```


kernel/syscalls/old_select.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/old_select.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/syscalls.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/sleep.h>
12: #include <fiwix/sched.h>
13:
14: #ifdef __DEBUG__
15: #include <fiwix/stdio.h>
16: #include <fiwix/process.h>
17: #endif /* __DEBUG__ */
18:
19: int old_select(unsigned long int *params)
20: {
21:     int nfds;
22:     fd_set *readfds;
23:     fd_set *writefds;
24:     fd_set *exceptfds;
25:     struct timeval *timeout;
26:     int errno;
27:
28: #ifdef __DEBUG__
29:     printk("(pid %d) old_select(0x%08x)\n", current->pid, (int)params);
30: #endif /* __DEBUG__ */
31:
32:     if((errno = check_user_area(VERIFY_READ, (void *)params, sizeof(unsigned
int) * 5))) {
33:         return errno;
34:     }
35:     nfds = *(int *)params;
36:     readfds = *(fd_set **)(params + 1);
37:     writefds = *(fd_set **)(params + 2);
38:     exceptfds = *(fd_set **)(params + 3);
39:     timeout = *(struct timeval **)(params + 4);
40:
41:     return sys_select(nfds, readfds, writefds, exceptfds, timeout);
42: }
```

kernel/syscalls/olduname.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/olduname.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/utsname.h>
10: #include <fiwix/string.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #include <fiwix/process.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_olduname(struct oldold_utsname *uname)
18: {
19:     int errno;
20:
21: #ifdef __DEBUG__
22:     printk("(pid %d) sys_olduname(0x%0x)", current->pid, uname);
23: #endif /* __DEBUG__ */
24:
25:     if((errno = check_user_area(VERIFY_WRITE, uname, sizeof(struct oldold_utsname)))) {
26:         return errno;
27:     }
28:     memcpy_b(&uname->sysname, &sys_utsname.sysname, _OLD_UTSNAME_LENGTH);
29:     memset_b(&uname->sysname + _OLD_UTSNAME_LENGTH, NULL, 1);
30:     memcpy_b(&uname->nodename, &sys_utsname.nodename, _OLD_UTSNAME_LENGTH);
31:     memset_b(&uname->nodename + _OLD_UTSNAME_LENGTH, NULL, 1);
32:     memcpy_b(&uname->release, &sys_utsname.release, _OLD_UTSNAME_LENGTH);
33:     memset_b(&uname->release + _OLD_UTSNAME_LENGTH, NULL, 1);
34:     memcpy_b(&uname->version, &sys_utsname.version, _OLD_UTSNAME_LENGTH);
35:     memset_b(&uname->version + _OLD_UTSNAME_LENGTH, NULL, 1);
36:     memcpy_b(&uname->machine, &sys_utsname.machine, _OLD_UTSNAME_LENGTH);
37:     memset_b(&uname->machine + _OLD_UTSNAME_LENGTH, NULL, 1);
38:     return 0;
39: }
```

kernel/syscalls/open.c

Page 1/3

```

1: /*
2:  * fiwix/kernel/syscalls/open.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/syscalls.h>
9: #include <fiwix/stat.h>
10: #include <fiwix/types.h>
11: #include <fiwix/fcntl.h>
12: #include <fiwix/errno.h>
13: #include <fiwix/stdio.h>
14: #include <fiwix/string.h>
15:
16: int sys_open(const char *filename, int flags, __mode_t mode)
17: {
18:     int fd, ufd;
19:     struct inode *i, *dir;
20:     char *tmp_name, *basename;
21:     int errno, follow_links, perms;
22:
23: #ifdef __DEBUG__
24:     printk("(pid %d) sys_open('%s', %o, %o)\n", current->pid, filename, flag
s, mode);
25: #endif /* __DEBUG__ */
26:
27:     if((errno = malloc_name(filename, &tmp_name)) < 0) {
28:         return errno;
29:     }
30:
31:     basename = get_basename(tmp_name);
32:     follow_links = flags & O_NOFOLLOW ? !FOLLOW_LINKS : FOLLOW_LINKS;
33:     if((errno = namei(tmp_name, &i, &dir, follow_links))) {
34:         if(!dir) {
35:             free_name(tmp_name);
36:             if(flags & O_CREAT) {
37:                 return -ENOENT;
38:             }
39:             return errno;
40:         }
41:     }
42:
43: #ifdef __DEBUG__
44:     printk("\t(inode = %d)\n", i ? i->inode : -1);
45: #endif /* __DEBUG__ */
46:
47:     if(flags & O_CREAT) {
48:         if(!errno && (flags & O_EXCL)) {
49:             iput(i);
50:             iput(dir);
51:             free_name(tmp_name);
52:             return -EEXIST;
53:         }
54:         if(check_permission(TO_EXEC | TO_WRITE, dir) < 0) {
55:             iput(i);
56:             iput(dir);
57:             free_name(tmp_name);
58:             return -EACCES;
59:         }
60:         if(errno) { /* assumes -ENOENT */
61:             if(dir->fsop && dir->fsop->create) {
62:                 errno = dir->fsop->create(dir, basename, mode, &
i);
63:             }
64:             if(errno) {
65:                 iput(dir);
66:                 free_name(tmp_name);

```

kernel/syscalls/open.c

Page 2/3

```

66:                                     return errno;
67:                                     }
68:             } else {
69:                 iput(dir);
70:                 free_name(tmp_name);
71:                 return -EACCES;
72:             }
73:         }
74:     } else {
75:         if(errno) {
76:             iput(dir);
77:             free_name(tmp_name);
78:             return errno;
79:         }
80:         if(S_ISDIR(i->i_mode) && (flags & (O_RDWR | O_WRONLY | O_TRUNC))
) {
81:             iput(i);
82:             iput(dir);
83:             free_name(tmp_name);
84:             return -EISDIR;
85:         }
86:         mode = 0;
87:     }
88:
89:     if((flags & O_ACCMODE) == O_RDONLY) {
90:         perms = TO_READ;
91:     } else if((flags & O_ACCMODE) == O_WRONLY) {
92:         perms = TO_WRITE;
93:     } else {
94:         perms = TO_READ | TO_WRITE;
95:     }
96:     if((errno = check_permission(perms, i))) {
97:         iput(i);
98:         iput(dir);
99:         free_name(tmp_name);
100:         return errno;
101:     }
102:     if((fd = get_new_fd(i)) < 0) {
103:         iput(i);
104:         iput(dir);
105:         free_name(tmp_name);
106:         return fd;
107:     }
108:     if((ufd = get_new_user_fd(0)) < 0) {
109:         release_fd(fd);
110:         iput(i);
111:         iput(dir);
112:         free_name(tmp_name);
113:         return ufd;
114:     }
115:
116: #ifdef __DEBUG__
117:     printk("\t(ufd = %d)\n", ufd);
118: #endif /*__DEBUG__*/
119:
120:     fd_table[fd].flags = flags;
121:     current->fd[ufd] = fd;
122:     if(i->fsop && i->fsop->open) {
123:         if((errno = i->fsop->open(i, &fd_table[fd])) < 0) {
124:             release_fd(fd);
125:             release_user_fd(ufd);
126:             iput(i);
127:             iput(dir);
128:             free_name(tmp_name);
129:             return errno;
130:         }
131:         iput(dir);

```

kernel/syscalls/open.c

Page 3/3

```
132:             free_name(tmp_name);
133:             return ufd;
134:         }
135:
136:         printk("WARNING: %s(): file '%s' (inode %d) without the open() method!\n
", __FUNCTION__, tmp_name, i->inode);
137:         release_fd(fd);
138:         release_user_fd(ufd);
139:         iput(i);
140:         iput(dir);
141:         free_name(tmp_name);
142:         return -EINVAL;
143:     }
```

kernel/syscalls/pause.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/pause.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/syscalls.h>
9: #include <fiwix/sched.h>
10: #include <fiwix/sleep.h>
11: #include <fiwix/errno.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #include <fiwix/process.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_pause(void)
19: {
20: #ifdef __DEBUG__
21:     printk("(pid %d) sys_pause()\n", current->pid);
22: #endif /* __DEBUG__ */
23:
24:     for(;;) {
25:         if(sleep(&sys_pause, PROC_INTERRUPTIBLE)) {
26:             break;
27:         }
28:     }
29:     return -EINTR;
30: }
```

kernel/syscalls/personality.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/personality.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifdef __DEBUG__
9: #include <fiwix/stdio.h>
10: #include <fiwix/process.h>
11: #endif /* __DEBUG__ */
12:
13: int sys_personality(unsigned long int persona)
14: {
15: #ifdef __DEBUG__
16:     printk("(pid %d) sys_personality(%d) -> %d\n", current->pid, persona, pe
rsona);
17: #endif /* __DEBUG__ */
18:     return persona;
19: }
```

kernel/syscalls/pipe.c

Page 1/2

```

1: /*
2:  * fiwix/kernel/syscalls/pipe.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/filesystems.h>
10: #include <fiwix/fcntl.h>
11: #include <fiwix/errno.h>
12: #include <fiwix/stdio.h>
13:
14: int sys_pipe(int pipefd[2])
15: {
16:     int rfd, rufd;
17:     int wfd, wufd;
18:     struct filesystems *fs;
19:     struct inode *i;
20:     int errno;
21:
22: #ifdef __DEBUG__
23:     printk("(pid %d) sys_pipe()", current->pid);
24: #endif /* __DEBUG__ */
25:
26:     if(!(fs = get_filesystem("pipefs"))) {
27:         printk("WARNING: %s(): pipefs filesystem is not registered!\n",
__FUNCTION__);
28:         return -EINVAL;
29:     }
30:     if((errno = check_user_area(VERIFY_WRITE, pipefd, sizeof(int) * 2))) {
31:         return errno;
32:     }
33:     if(!(i = ialloc(&fs->mt->sb))) {
34:         return -EINVAL;
35:     }
36:     if((rfd = get_new_fd(i)) < 0) {
37:         iput(i);
38:         return -ENFILE;
39:     }
40:     if((wfd = get_new_fd(i)) < 0) {
41:         release_fd(rfd);
42:         iput(i);
43:         return -ENFILE;
44:     }
45:     if((rufd = get_new_user_fd(0)) < 0) {
46:         release_fd(rfd);
47:         release_fd(wfd);
48:         iput(i);
49:         return -EMFILE;
50:     }
51:     if((wufd = get_new_user_fd(0)) < 0) {
52:         release_fd(rfd);
53:         release_fd(wfd);
54:         release_user_fd(rufd);
55:         iput(i);
56:         return -EMFILE;
57:     }
58:
59:     pipefd[0] = rufd;
60:     pipefd[1] = wufd;
61:     current->fd[rufd] = rfd;
62:     current->fd[wufd] = wfd;
63:     fd_table[rfd].flags = O_RDONLY;
64:     fd_table[wfd].flags = O_WRONLY;
65:
66: #ifdef __DEBUG__

```


kernel/syscalls/pipe.c

Page 2/2

```
67:         printk(" -> inode=%d, rufd=%d wufd=%d (rfd=%d wfd=%d)\n", i->inode, rufd
, wufd, rfd, wfd);
68: #endif /* __DEBUG__ */
69:
70:         return 0;
71: }
```

kernel/syscalls/read.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/read.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/fcntl.h>
10: #include <fiwix/errno.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #include <fiwix/process.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_read(unsigned int ufd, char *buf, int count)
18: {
19:     struct inode *i;
20:     int errno;
21:
22: #ifdef __DEBUG__
23:     printk("(pid %d) sys_read(%d, 0x%08x, %d) -> ", current->pid, ufd, buf,
count);
24: #endif /* __DEBUG__ */
25:
26:     CHECK_UFD(ufd);
27:     if((errno = check_user_area(VERIFY_WRITE, buf, count))) {
28:         return errno;
29:     }
30:     if(fd_table[current->fd[ufd]].flags & O_WRONLY) {
31:         return -EBADF;
32:     }
33:     if(!count) {
34:         return 0;
35:     }
36:     if(count < 0) {
37:         return -EINVAL;
38:     }
39:
40:     i = fd_table[current->fd[ufd]].inode;
41:     if(i->fsop && i->fsop->read) {
42:         errno = i->fsop->read(i, &fd_table[current->fd[ufd]], buf, count
);
43: #ifdef __DEBUG__
44:         printk("%d\n", errno);
45: #endif /* __DEBUG__ */
46:         return errno;
47:     }
48:     return -EINVAL;
49: }

```

kernel/syscalls/readlink.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/readlink.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/stat.h>
11: #include <fiwix/errno.h>
12: #include <fiwix/string.h>
13:
14: #ifdef __DEBUG__
15: #include <fiwix/stdio.h>
16: #include <fiwix/process.h>
17: #endif /* __DEBUG__ */
18:
19: int sys_readlink(const char *filename, char *buffer, __size_t bufsize)
20: {
21:     struct inode *i;
22:     char *tmp_name;
23:     int errno;
24:
25: #ifdef __DEBUG__
26:     printk("(pid %d) sys_readlink(%s, 0x%08x, %d)\n", current->pid, filename
, (unsigned int)buffer, bufsize);
27: #endif /* __DEBUG__ */
28:
29:     if(bufsize <= 0) {
30:         return -EINVAL;
31:     }
32:     if((errno = check_user_area(VERIFY_WRITE, buffer, bufsize)) {
33:         return errno;
34:     }
35:     if((errno = malloc_name(filename, &tmp_name)) < 0) {
36:         return errno;
37:     }
38:     if((errno = namei(tmp_name, &i, NULL, !FOLLOW_LINKS)) {
39:         free_name(tmp_name);
40:         return errno;
41:     }
42:     if(!S_ISLNK(i->i_mode)) {
43:         iput(i);
44:         free_name(tmp_name);
45:         return -EINVAL;
46:     }
47:
48:     if(i->fsop && i->fsop->readlink) {
49:         errno = i->fsop->readlink(i, buffer, bufsize);
50:         iput(i);
51:         free_name(tmp_name);
52:         return errno;
53:     }
54:     iput(i);
55:     free_name(tmp_name);
56:     return -EINVAL;
57: }
```

kernel/syscalls/reboot.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/reboot.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/syscalls.h>
10: #include <fiwix/reboot.h>
11: #include <fiwix/signal.h>
12: #include <fiwix/process.h>
13: #include <fiwix/errno.h>
14:
15: #ifdef __DEBUG__
16: #include <fiwix/stdio.h>
17: #endif /* __DEBUG__ */
18:
19: int sys_reboot(int magic1, int magic2, int flag)
20: {
21: #ifdef __DEBUG__
22:     printk("(pid %d) sys_reboot(0x%08x, %d, 0x%08x)\n", current->pid, magic1
, magic2, flag);
23: #endif /* __DEBUG__ */
24:
25:     if(!IS_SUPERUSER) {
26:         return -EPERM;
27:     }
28:     if((magic1 != BMAGIC_1) || (magic2 != BMAGIC_2)) {
29:         return -EINVAL;
30:     }
31:     switch(flag) {
32:         case BMAGIC_SOFT:
33:             ctrl_alt_del = 0;
34:             break;
35:         case BMAGIC_HARD:
36:             ctrl_alt_del = 1;
37:             break;
38:         case BMAGIC_REBOOT:
39:             reboot();
40:             break;
41:         case BMAGIC_HALT:
42:             sys_kill(-1, SIGKILL);
43:             stop_kernel();
44:             break;
45:         default:
46:             return -EINVAL;
47:     }
48:     return 0;
49: }
```

kernel/syscalls/rename.c

Page 1/2

```

1: /*
2:  * fiwix/kernel/syscalls/rename.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/stat.h>
10: #include <fiwix/errno.h>
11: #include <fiwix/string.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #include <fiwix/process.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_rename(const char *oldpath, const char *newpath)
19: {
20:     struct inode *i, *dir, *i_new, *dir_new;
21:     char *tmp_oldpath, *tmp_newpath;
22:     char *oldbasename, *newbasename;
23:     int errno;
24:
25: #ifdef __DEBUG__
26:     printk("(pid %d) sys_rename('%s', '%s')\n", current->pid, oldpath, newpa
th);
27: #endif /* __DEBUG__ */
28:
29:     if((errno = malloc_name(oldpath, &tmp_oldpath)) < 0) {
30:         return errno;
31:     }
32:     if((errno = namei(tmp_oldpath, &i, &dir, !FOLLOW_LINKS))) {
33:         if(dir) {
34:             iput(dir);
35:         }
36:         free_name(tmp_oldpath);
37:         return errno;
38:     }
39:     if(IS_RDONLY_FS(i)) {
40:         iput(i);
41:         iput(dir);
42:         free_name(tmp_oldpath);
43:         return -EROFS;
44:     }
45:
46:     if((errno = malloc_name(newpath, &tmp_newpath)) < 0) {
47:         iput(i);
48:         iput(dir);
49:         free_name(tmp_oldpath);
50:         return errno;
51:     }
52:     newbasename = remove_trailing_slash(tmp_newpath);
53:     if((errno = namei(newbasename, &i_new, &dir_new, !FOLLOW_LINKS))) {
54:         if(!dir_new) {
55:             iput(i);
56:             iput(dir);
57:             free_name(tmp_oldpath);
58:             free_name(tmp_newpath);
59:             return errno;
60:         }
61:     }
62:     if(dir->dev != dir_new->dev) {
63:         errno = -EXDEV;
64:         goto end;
65:     }
66:     newbasename = get_basename(newbasename);

```

kernel/syscalls/rename.c

Page 2/2

```

67:         if((newbasename[0] == '.' && newbasename[1] == NULL) || (newbasename[0]
== '.' && newbasename[1] == '.' && newbasename[2] == NULL)) {
68:             errno = -EINVAL;
69:             goto end;
70:         }
71:
72:         oldbasename = get_basename(tmp_oldpath);
73:         oldbasename = remove_trailing_slash(oldbasename);
74:         if((oldbasename[0] == '.' && oldbasename[1] == NULL) || (oldbasename[0]
== '.' && oldbasename[1] == '.' && oldbasename[2] == NULL)) {
75:             errno = -EINVAL;
76:             goto end;
77:         }
78:
79:         if(i_new) {
80:             if(S_ISREG(i->i_mode)) {
81:                 if(S_ISDIR(i_new->i_mode)) {
82:                     errno = -EISDIR;
83:                     goto end;
84:                 }
85:             }
86:             if(S_ISDIR(i->i_mode)) {
87:                 if(!S_ISDIR(i_new->i_mode)) {
88:                     errno = -ENOTDIR;
89:                     goto end;
90:                 }
91:             }
92:             if(i->inode == i_new->inode) {
93:                 errno = 0;
94:                 goto end;
95:             }
96:         }
97:
98:         if(check_permission(TO_EXEC | TO_WRITE, dir_new) < 0) {
99:             errno = -EACCES;
100:            goto end;
101:        }
102:
103:        if(dir_new->fsop && dir_new->fsop->rename) {
104:            errno = dir_new->fsop->rename(i, dir, i_new, dir_new, oldbasenam
e, newbasename);
105:        } else {
106:            errno = -EPERM;
107:        }
108:
109:    end:
110:        iput(i);
111:        iput(dir);
112:        iput(i_new);
113:        iput(dir_new);
114:        free_name(tmp_oldpath);
115:        free_name(tmp_newpath);
116:        return errno;
117:    }

```

kernel/syscalls/rmdir.c

Page 1/2

```

1: /*
2:  * fiwix/kernel/syscalls/rmdir.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/stat.h>
10: #include <fiwix/errno.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #include <fiwix/process.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_rmdir(const char *dirname)
18: {
19:     struct inode *i, *dir;
20:     char *tmp_dirname;
21:     int errno;
22:
23: #ifdef __DEBUG__
24:     printk("(pid %d) sys_rmdir(%s)\n", current->pid, dirname);
25: #endif /* __DEBUG__ */
26:
27:     if((errno = malloc_name(dirname, &tmp_dirname)) < 0) {
28:         return errno;
29:     }
30:     if((errno = namei(tmp_dirname, &i, &dir, !FOLLOW_LINKS))) {
31:         if(dir) {
32:             iput(dir);
33:         }
34:         free_name(tmp_dirname);
35:         return errno;
36:     }
37:     if(!S_ISDIR(i->i_mode)) {
38:         iput(i);
39:         iput(dir);
40:         free_name(tmp_dirname);
41:         return -ENOTDIR;
42:     }
43:     if(i == current->root || i->mount_point || i->count > 1) {
44:         iput(i);
45:         iput(dir);
46:         free_name(tmp_dirname);
47:         return -EBUSY;
48:     }
49:     if(IS_RDONLY_FS(i)) {
50:         iput(i);
51:         iput(dir);
52:         free_name(tmp_dirname);
53:         return -EROFS;
54:     }
55:     if(i == dir) {
56:         iput(i);
57:         iput(dir);
58:         free_name(tmp_dirname);
59:         return -EPERM;
60:     }
61:     if(check_permission(TO_EXEC | TO_WRITE, dir) < 0) {
62:         iput(i);
63:         iput(dir);
64:         free_name(tmp_dirname);
65:         return -EACCES;
66:     }
67:

```

kernel/syscalls/rmdir.c

Page 2/2

```
68:      /* check sticky permission bit */
69:      if(dir->i_mode & S_ISVTX) {
70:          if(check_user_permission(i)) {
71:              iput(i);
72:              iput(dir);
73:              free_name(tmp_dirname);
74:              return -EPERM;
75:          }
76:      }
77:
78:      if(i->fsop && i->fsop->rmdir) {
79:          errno = i->fsop->rmdir(dir, i);
80:      } else {
81:          errno = -EPERM;
82:      }
83:      iput(i);
84:      iput(dir);
85:      free_name(tmp_dirname);
86:      return errno;
87: }
```


kernel/syscalls/select.c

Page 1/3

```

1: /*
2:  * fiwix/kernel/syscalls/select.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/process.h>
11: #include <fiwix/timer.h>
12: #include <fiwix/sched.h>
13: #include <fiwix/sleep.h>
14: #include <fiwix/errno.h>
15: #include <fiwix/stdio.h>
16: #include <fiwix/string.h>
17:
18: static int check_fds(int nfd, fd_set *rfd, fd_set *wfd, fd_set *efd)
19: {
20:     int n, bit;
21:     unsigned long int set;
22:
23:     n = bit = 0;
24:     while(bit < nfd) {
25:         bit = n * __NFDBITS;
26:         set = rfd->fds_bits[n] | wfd->fds_bits[n] | efd->fds_bits[n];
27:         while(set) {
28:             if(__FD_ISSET(bit, rfd)) {
29:                 CHECK_UFD(bit);
30:             }
31:             set >>= 1;
32:             bit++;
33:         }
34:         n++;
35:     }
36:
37:     return 0;
38: }
39:
40: static int do_check(struct inode *i, int flag)
41: {
42:     if(i->fsop && i->fsop->select) {
43:         if(i->fsop->select(i, flag)) {
44:             return 1;
45:         }
46:     }
47:
48:     return 0;
49: }
50:
51: int do_select(int nfd, fd_set *rfd, fd_set *wfd, fd_set *efd, fd_set *res_rfd, fd_set *res_wfd, fd_set *res_efd)
52: {
53:     int n, count;
54:     struct inode *i;
55:
56:     count = 0;
57:     for(;;) {
58:         for(n = 0; n < nfd; n++) {
59:             if(!current->fd[n]) {
60:                 continue;
61:             }
62:             i = fd_table[current->fd[n]].inode;
63:             if(__FD_ISSET(n, rfd)) {
64:                 if(do_check(i, SEL_R)) {
65:                     __FD_SET(n, res_rfd);
66:                     count++;

```

kernel/syscalls/select.c

Page 2/3

```

67:         }
68:     }
69:     if(__FD_ISSET(n, wfds)) {
70:         if(do_check(i, SEL_W)) {
71:             __FD_SET(n, res_wfds);
72:             count++;
73:         }
74:     }
75:     if(__FD_ISSET(n, efds)) {
76:         if(do_check(i, SEL_E)) {
77:             __FD_SET(n, res_efds);
78:             count++;
79:         }
80:     }
81: }
82:
83:     if(count || !current->timeout || current->sigpending & ~current-
>sigblocked) {
84:         break;
85:     }
86:     sleep(&do_select, PROC_INTERRUPTIBLE);
87: }
88:
89:     return count;
90: }
91:
92: int sys_select(int nfds, fd_set *readfds, fd_set *writefds, fd_set *exceptfds, s
truct timeval *timeout)
93: {
94:     unsigned long int t;
95:     fd_set rfds, wfds, efds;
96:     fd_set res_rfds, res_wfds, res_efds;
97:     int errno;
98:
99: #ifdef __DEBUG__
100:     printk("(pid %d) sys_select(%d, 0x%08x, 0x%08x, 0x%08x, 0x%08x [%d])\n",
current->pid, nfds, (int)readfds, (int)writefds, (int)exceptfds, (int)timeout, (int)ti
meout ? tv2ticks(timeout): 0);
101: #endif /* __DEBUG__ */
102:
103:     if(nfds < 0) {
104:         return -EINVAL;
105:     }
106:     if(nfds > MIN(__FD_SETSIZE, NR_OPENS)) {
107:         nfds = MIN(__FD_SETSIZE, NR_OPENS);
108:     }
109:
110:     if(readfds) {
111:         if((errno = check_user_area(VERIFY_WRITE, readfds, sizeof(fd_set
)))) {
112:             return errno;
113:         }
114:         memcpy_b(&rfds, readfds, sizeof(fd_set));
115:     } else {
116:         __FD_ZERO(&rfds);
117:     }
118:     if(writefds) {
119:         if((errno = check_user_area(VERIFY_WRITE, writefds, sizeof(fd_se
t)))) {
120:             return errno;
121:         }
122:         memcpy_b(&wfds, writefds, sizeof(fd_set));
123:     } else {
124:         __FD_ZERO(&wfds);
125:     }
126:     if(exceptfds) {
127:         if((errno = check_user_area(VERIFY_WRITE, exceptfds, sizeof(fd_s

```

kernel/syscalls/select.c

Page 3/3

```
et)))) {
128:         return errno;
129:     }
130:     memcpy_b(&efds, exceptfds, sizeof(fd_set));
131: } else {
132:     __FD_ZERO(&efds);
133: }
134:
135: /* check the validity of all fds */
136: if((errno = check_fds(nfds, &rfd, &wfds, &efds)) < 0) {
137:     return errno;
138: }
139:
140: if(timeout) {
141:     t = tv2ticks(timeout);
142: } else {
143:     t = INFINITE_WAIT;
144: }
145:
146: __FD_ZERO(&res_rfd);
147: __FD_ZERO(&res_wfd);
148: __FD_ZERO(&res_efds);
149:
150: current->timeout = t;
151: if((errno = do_select(nfds, &rfd, &wfds, &efds, &res_rfd, &res_wfd, &
res_efds)) < 0) {
152:     return errno;
153: }
154: current->timeout = 0;
155:
156: if(readfds) {
157:     memcpy_b(readfds, &res_rfd, sizeof(fd_set));
158: }
159: if(writefds) {
160:     memcpy_b(writefds, &res_wfd, sizeof(fd_set));
161: }
162: if(exceptfds) {
163:     memcpy_b(exceptfds, &res_efds, sizeof(fd_set));
164: }
165: return errno;
166: }
```

kernel/syscalls/setdomainname.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/setdomainname.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/utsname.h>
10: #include <fiwix/errno.h>
11: #include <fiwix/string.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #include <fiwix/process.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_setdomainname(const char *name, int length)
19: {
20:     int errno;
21:
22: #ifdef __DEBUG__
23:     printk("(pid %d) sys_setdomainname('%s', %d)\n", current->pid, name, len
gth);
24: #endif /* __DEBUG__ */
25:
26:     if((errno = check_user_area(VERIFY_READ, name, length)) {
27:         return errno;
28:     }
29:     if(!IS_SUPERUSER) {
30:         return -EPERM;
31:     }
32:     if(length < 0 || length > _UTSNAME_LENGTH) {
33:         return -EINVAL;
34:     }
35:     memcpy_b(&sys_utsname.domainname, name, length);
36:     sys_utsname.domainname[length] = NULL;
37:     return 0;
38: }
```

kernel/syscalls/setfsgid.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/setfsgid.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9:
10: #ifdef __DEBUG__
11: #include <fiwix/stdio.h>
12: #include <fiwix/process.h>
13: #endif /*__DEBUG__*/
14:
15: int sys_setfsgid(__gid_t fsgid)
16: {
17: #ifdef __DEBUG__
18:     printk("(pid %d) sys_setfsgid(%d) -> %d\n", current->pid, fsgid);
19: #endif /*__DEBUG__*/
20:     return 0;
21: }
```

kernel/syscalls/setfsuid.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/setfsuid.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9:
10: #ifdef __DEBUG__
11: #include <fiwix/stdio.h>
12: #include <fiwix/process.h>
13: #endif /*__DEBUG__*/
14:
15: int sys_setfsuid(__uid_t fsuid)
16: {
17: #ifdef __DEBUG__
18:     printk("(pid %d) sys_setfsuid(%d) -> %d\n", current->pid, fsuid);
19: #endif /*__DEBUG__*/
20:     return 0;
21: }
```

kernel/syscalls/setgid.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/setgid.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/process.h>
10: #include <fiwix/errno.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #endif /* __DEBUG__ */
15:
16: int sys_setgid(__gid_t gid)
17: {
18: #ifdef __DEBUG__
19:     printk("(pid %d) sys_setgid(%d)\n", current->pid, gid);
20: #endif /* __DEBUG__ */
21:
22:     if(IS_SUPERUSER) {
23:         current->gid = current->egid = current->sgid = gid;
24:     } else {
25:         if((current->gid == gid) || (current->sgid == gid)) {
26:             current->egid = gid;
27:         } else {
28:             return -EPERM;
29:         }
30:     }
31:     return 0;
32: }
```

kernel/syscalls/setgroups.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/setgroups.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/process.h>
11: #include <fiwix/errno.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_setgroups(__ssize_t size, const __gid_t *list)
18: {
19:     int n, errno;
20:
21: #ifdef __DEBUG__
22:     printk("(pid %d) sys_setgroups(%d, 0x%08x)\n", current->pid, size, (unsi
gned int)list);
23: #endif /* __DEBUG__ */
24:
25:     if((errno = check_user_area(VERIFY_READ, list, sizeof(__gid_t)))) {
26:         return errno;
27:     }
28:     if(!IS_SUPERUSER) {
29:         return -EPERM;
30:     }
31:     if(size > NGROUPS_MAX) {
32:         return -EINVAL;
33:     }
34:     for(n = 0; n < NGROUPS_MAX; n++) {
35:         current->groups[n] = -1;
36:         if(n < size) {
37:             current->groups[n] = list[n];
38:         }
39:     }
40:     return 0;
41: }
```


kernel/syscalls/sethostname.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/sethostname.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/utsname.h>
10: #include <fiwix/process.h>
11: #include <fiwix/errno.h>
12: #include <fiwix/string.h>
13:
14: #ifdef __DEBUG__
15: #include <fiwix/stdio.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_sethostname(const char *name, int length)
19: {
20:     int errno;
21:     char *tmp_name;
22:
23: #ifdef __DEBUG__
24:     printk("(pid %d) sys_sethostname('%s', %d)\n", current->pid, name, length);
25: #endif /* __DEBUG__ */
26:
27:     if((errno = malloc_name(name, &tmp_name)) < 0) {
28:         return errno;
29:     }
30:     if(!IS_SUPERUSER) {
31:         free_name(tmp_name);
32:         return -EPERM;
33:     }
34:     if(length < 0 || length > _UTSNAME_LENGTH) {
35:         free_name(tmp_name);
36:         return -EINVAL;
37:     }
38:     memcpy_b(&sys_utsname.nodename, tmp_name, length);
39:     sys_utsname.nodename[length] = NULL;
40:     free_name(tmp_name);
41:     return 0;
42: }
```

kernel/syscalls/setitimer.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/setitimer.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/time.h>
10:
11: #ifdef __DEBUG__
12: #include <fiwix/stdio.h>
13: #include <fiwix/process.h>
14: #endif /* __DEBUG__ */
15:
16: int sys_setitimer(int which, const struct itimerval *new_value, struct itimerval
*old_value)
17: {
18:     int errno;
19:
20: #ifdef __DEBUG__
21:     printk("(pid %d) sys_setitimer(%d, 0x%08x, 0x%08x) -> \n", current->pid,
which, (unsigned int)new_value, (unsigned int)old_value);
22: #endif /* __DEBUG__ */
23:
24:     if((unsigned int)old_value) {
25:         if((errno = check_user_area(VERIFY_WRITE, old_value, sizeof(stru
ct itimerval)))) {
26:             return errno;
27:         }
28:     }
29:
30:     return setitimer(which, new_value, old_value);
31: }
```

kernel/syscalls/setpgid.c

Page 1/2

```

1: /*
2:  * fiwix/kernel/syscalls/setpgid.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/process.h>
10: #include <fiwix/sched.h>
11: #include <fiwix/errno.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_setpgid(__pid_t pid, __pid_t pgid)
18: {
19:     struct proc *p;
20:
21: #ifdef __DEBUG__
22:     printk("(pid %d) sys_setpgid(%d, %d)", current->pid, pid, pgid);
23: #endif /* __DEBUG__ */
24:
25:     if(pid < 0 || pgid < 0) {
26:         return -EINVAL;
27:     }
28:     if(!pid) {
29:         pid = current->pid;
30:     }
31:
32:     p = get_proc_by_pid(pid);
33:     if(!pgid) {
34:         pgid = p->pid;
35:     }
36:
37:     if(p != current && (p->state == PROC_UNUSED || p->ppid != current->pid))
{
38:         return -ESRCH;
39:     }
40:     if(p->sid == p->pid || p->sid != current->sid) {
41:         return -EPERM;
42:     }
43:
44:     {
45:         struct proc *p;
46:
47:         FOR_EACH_PROCESS(p) {
48:             if(p->state != PROC_UNUSED) {
49:                 if(p->pgid == pgid && p->sid != current->sid) {
50:                     return -EPERM;
51:                 }
52:             }
53:         }
54:     }
55:
56:     if(p != current && p->flags & PF_PEXEC) {
57:         return -EACCES;
58:     }
59:
60:     p->pgid = pgid;
61:
62: #ifdef __DEBUG__
63:     printk(" -> 0\n");
64: #endif /* __DEBUG__ */
65:
66:     return 0;

```

```
67: }
```

kernel/syscalls/setregid.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/setregid.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/process.h>
10: #include <fiwix/errno.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #endif /* __DEBUG__ */
15:
16: int sys_setregid(__gid_t gid, __gid_t egid)
17: {
18: #ifdef __DEBUG__
19:     printk("(pid %d) sys_setregid(%d, %d) -> ", current->pid, gid, egid);
20: #endif /* __DEBUG__ */
21:
22:     if(IS_SUPERUSER) {
23:         if(egid >= 0) {
24:             if(gid >= 0 || (current->egid >= 0 && current->gid != eg
id)) {
25:                 current->sgid = egid;
26:             }
27:             current->egid = egid;
28:         }
29:         if(gid >= 0) {
30:             current->gid = gid;
31:         }
32:     } else {
33:         if(egid >= 0 && (current->gid == egid || current->egid == egid |
| current->sgid == egid)) {
34:             if(gid >= 0 || (current->egid >= 0 && current->gid != eg
id)) {
35:                 current->sgid = egid;
36:             }
37:             current->egid = egid;
38:         } else {
39:             return -EPERM;
40:         }
41:         if(gid >= 0 && (current->gid == gid || current->egid == gid)) {
42:             current->gid = gid;
43:         } else {
44:             return -EPERM;
45:         }
46:     }
47:
48:     return 0;
49: }

```

kernel/syscalls/setreuid.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/setreuid.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/process.h>
10: #include <fiwix/errno.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #endif /*__DEBUG__*/
15:
16: int sys_setreuid(__uid_t uid, __uid_t euid)
17: {
18: #ifdef __DEBUG__
19:     printk("(pid %d) sys_setreuid(%d, %d) -> ", current->pid, uid, euid);
20: #endif /*__DEBUG__*/
21:
22:     if(IS_SUPERUSER) {
23:         if(euid >= 0) {
24:             if(uid >= 0 || (current->euid >= 0 && current->uid != eu
id)) {
25:                 current->suid = euid;
26:             }
27:             current->euid = euid;
28:         }
29:         if(uid >= 0) {
30:             current->uid = uid;
31:         }
32:     } else {
33:         if(euid >= 0 && (current->uid == euid || current->euid == euid |
| current->suid == euid)) {
34:             if(uid >= 0 || (current->euid >= 0 && current->uid != eu
id)) {
35:                 current->suid = euid;
36:             }
37:             current->euid = euid;
38:         } else {
39:             return -EPERM;
40:         }
41:         if(uid >= 0 && (current->uid == uid || current->euid == uid)) {
42:             current->uid = uid;
43:         } else {
44:             return -EPERM;
45:         }
46:     }
47:
48:     return 0;
49: }

```

kernel/syscalls/setrlimit.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/setrlimit.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/resource.h>
10: #include <fiwix/process.h>
11: #include <fiwix/errno.h>
12: #include <fiwix/string.h>
13:
14: #ifdef __DEBUG__
15: #include <fiwix/stdio.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_setrlimit(int resource, const struct rlimit *rlim)
19: {
20:     int errno;
21:
22: #ifdef __DEBUG__
23:     printk("(pid %d) sys_setrlimit(%d, 0x%08x)\n", current->pid, resource, (
unsigned int)rlim);
24: #endif /* __DEBUG__ */
25:
26:     if((errno = check_user_area(VERIFY_READ, rlim, sizeof(struct rlimit))))
{
27:         return errno;
28:     }
29:     if(resource < 0 || resource >= RLIM_NLIMITS) {
30:         return -EINVAL;
31:     }
32:     if(rlim->rlim_cur > rlim->rlim_max) {
33:         return -EINVAL;
34:     }
35:     if(!IS_SUPERUSER) {
36:         if(rlim->rlim_max > current->rlim[resource].rlim_max) {
37:             return -EPERM;
38:         }
39:     }
40:     memcpy_b(&current->rlim[resource], rlim, sizeof(struct rlimit));
41:     return 0;
42: }

```

kernel/syscalls/setsid.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/setsid.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/process.h>
9: #include <fiwix/errno.h>
10: #include <fiwix/string.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #endif /* __DEBUG__ */
15:
16: int sys_setsid(void)
17: {
18:     struct proc *p;
19:
20: #ifdef __DEBUG__
21:     printk("(pid %d) sys_setsid()\n", current->pid);
22: #endif /* __DEBUG__ */
23:
24:     if(PG_LEADER(current)) {
25:         return -EPERM;
26:     }
27:     FOR_EACH_PROCESS(p) { /* POSIX ANSI/IEEE Std 1003.1-1996 4.3.2 */
28:         if(p != current && p->pgid == current->pid) {
29:             return -EPERM;
30:         }
31:     }
32:
33:     current->sid = current->pgid = current->pid;
34:     current->ctty = NULL;
35:     return current->sid;
36: }
```


kernel/syscalls/settimeofday.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/settimeofday.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/time.h>
11: #include <fiwix/timer.h>
12: #include <fiwix/process.h>
13: #include <fiwix/errno.h>
14:
15: #ifdef __DEBUG__
16: #include <fiwix/stdio.h>
17: #endif /* __DEBUG__ */
18:
19: int sys_settimeofday(const struct timeval *tv, const struct timezone *tz)
20: {
21:     int errno;
22:
23: #ifdef __DEBUG__
24:     printk("(pid %d) sys_settimeofday()\n", current->pid);
25: #endif /* __DEBUG__ */
26:
27:     if(!IS_SUPERUSER) {
28:         return -EPERM;
29:     }
30:
31:     if(tv) {
32:         if((errno = check_user_area(VERIFY_READ, tv, sizeof(struct timev
al)))) {
33:             return errno;
34:         }
35:         CURRENT_TIME = tv->tv_sec;
36:         set_system_time(CURRENT_TIME);
37:     }
38:     if(tz) {
39:         if((errno = check_user_area(VERIFY_READ, tz, sizeof(struct timez
one)))) {
40:             return errno;
41:         }
42:         kstat.tz_minuteswest = tz->tz_minuteswest;
43:         kstat.tz_dsttime = tz->tz_dsttime;
44:     }
45:     return 0;
46: }

```

kernel/syscalls/setuid.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/setuid.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/process.h>
10: #include <fiwix/errno.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #endif /* __DEBUG__ */
15:
16: int sys_setuid(__uid_t uid)
17: {
18: #ifdef __DEBUG__
19:     printk("(pid %d) sys_setuid(%d)\n", current->pid, uid);
20: #endif /* __DEBUG__ */
21:
22:     if(IS_SUPERUSER) {
23:         current->uid = current->suid = uid;
24:     } else {
25:         if((current->uid != uid) && (current->suid != uid)) {
26:             return -EPERM;
27:         }
28:     }
29:     current->euid = uid;
30:     return 0;
31: }
```

kernel/syscalls/sgetmask.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/sgetmask.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/process.h>
9:
10: #ifdef __DEBUG__
11: #include <fiwix/stdio.h>
12: #endif /*__DEBUG__*/
13:
14: int sys_sgetmask(void)
15: {
16: #ifdef __DEBUG__
17:     printk("(pid %d) sys_sgetmask() -> \n", current->pid);
18: #endif /*__DEBUG__*/
19:     return current->sigblocked;
20: }
```

kernel/syscalls/sigation.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/sigation.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/signal.h>
10: #include <fiwix/errno.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #include <fiwix/process.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_sigation(__sigset_t signum, const struct sigaction *newaction, struct sigaction *oldaction)
18: {
19:     int errno;
20:
21: #ifdef __DEBUG__
22:     printk("(pid %d) sys_sigation(%d, 0x%08x, 0x%08x)\n", current->pid, signum, (unsigned int)newaction, (unsigned int)oldaction);
23: #endif /* __DEBUG__ */
24:
25:     if(signum < 1 || signum > NSIG) {
26:         return -EINVAL;
27:     }
28:     if(signum == SIGKILL || signum == SIGSTOP) {
29:         return -EINVAL;
30:     }
31:     if(oldaction) {
32:         if((errno = check_user_area(VERIFY_WRITE, oldaction, sizeof(struct sigaction)))) {
33:             return errno;
34:         }
35:         *oldaction = current->sigaction[signum - 1];
36:     }
37:     if(newaction) {
38:         if((errno = check_user_area(VERIFY_READ, newaction, sizeof(struct sigaction)))) {
39:             return errno;
40:         }
41:         current->sigaction[signum - 1] = *newaction;
42:         if(current->sigaction[signum - 1].sa_handler == SIG_IGN) {
43:             if(signum != SIGCHLD) {
44:                 current->sigpending &= SIG_MASK(signum);
45:             }
46:         }
47:         if(current->sigaction[signum - 1].sa_handler == SIG_DFL) {
48:             if(signum != SIGCHLD) {
49:                 current->sigpending &= SIG_MASK(signum);
50:             }
51:         }
52:     }
53:     return 0;
54: }

```

kernel/syscalls/signal.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/signal.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/syscalls.h>
9: #include <fiwix/signal.h>
10: #include <fiwix/process.h>
11: #include <fiwix/errno.h>
12: #include <fiwix/string.h>
13:
14: #ifdef __DEBUG__
15: #include <fiwix/stdio.h>
16: #endif /* __DEBUG__ */
17:
18: unsigned int sys_signal(__sigset_t signum, void(* sighandler)(int))
19: {
20:     struct sigaction s;
21:     int errno;
22:
23: #ifdef __DEBUG__
24:     printk("(pid %d) sys_signal()\n", current->pid);
25: #endif /* __DEBUG__ */
26:
27:     if(signum < 1 || signum > NSIG) {
28:         return -EINVAL;
29:     }
30:     if(signum == SIGKILL || signum == SIGSTOP) {
31:         return -EINVAL;
32:     }
33:     if(sighandler != SIG_DFL && sighandler != SIG_IGN) {
34:         if((errno = check_user_area(VERIFY_READ, sighandler, sizeof(void
)))) {
35:             return errno;
36:         }
37:     }
38:
39:     memset_b(&s, 0, sizeof(struct sigaction));
40:     s.sa_handler = sighandler;
41:     s.sa_mask = 0;
42:     s.sa_flags = SA_RESETHAND;
43:     sighandler = current->sigaction[signum - 1].sa_handler;
44:     current->sigaction[signum - 1] = s;
45:     if(current->sigaction[signum - 1].sa_handler == SIG_IGN) {
46:         if(signum != SIGCHLD) {
47:             current->sigpending &= SIG_MASK(signum);
48:         }
49:     }
50:     if(current->sigaction[signum - 1].sa_handler == SIG_DFL) {
51:         if(signum != SIGCHLD) {
52:             current->sigpending &= SIG_MASK(signum);
53:         }
54:     }
55:     return (unsigned int)sighandler;
56: }

```

kernel/syscalls/sigpending.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/sigpending.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/signal.h>
10: #include <fiwix/process.h>
11: #include <fiwix/string.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_sigpending(__sigset_t *set)
18: {
19:     int errno;
20:
21: #ifdef __DEBUG__
22:     printk("(pid %d) sys_sigpending(0x%08x) -> ", current->pid, set);
23: #endif /* __DEBUG__ */
24:
25:     if((errno = check_user_area(VERIFY_WRITE, set, sizeof(__sigset_t)))) {
26:         return errno;
27:     }
28:     memcpy_b(set, &current->sigpending, sizeof(__sigset_t));
29:     return 0;
30: }
```

kernel/syscalls/sigprocmask.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/sigprocmask.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/signal.h>
10: #include <fiwix/process.h>
11: #include <fiwix/errno.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_sigprocmask(int how, const __sigset_t *set, __sigset_t *oldset)
18: {
19:     int errno;
20:
21: #ifdef __DEBUG__
22:     printk("(pid %d) sys_sigprocmask(%d, 0x%08x, 0x%08x)\n", current->pid, h
ow, set, oldset);
23: #endif /* __DEBUG__ */
24:
25:     if(oldset) {
26:         if((errno = check_user_area(VERIFY_WRITE, oldset, sizeof(__sigse
t_t)))) {
27:             return errno;
28:         }
29:         *oldset = current->sigblocked;
30:     }
31:
32:     if(set) {
33:         if((errno = check_user_area(VERIFY_READ, set, sizeof(__sigset_t)
))) {
34:             return errno;
35:         }
36:         switch(how) {
37:             case SIG_BLOCK:
38:                 current->sigblocked |= (*set & SIG_BLOCKABLE);
39:                 break;
40:             case SIG_UNBLOCK:
41:                 current->sigblocked &= ~(*set & SIG_BLOCKABLE);
42:                 break;
43:             case SIG_SETMASK:
44:                 current->sigblocked = (*set & SIG_BLOCKABLE);
45:                 break;
46:             default:
47:                 return -EINVAL;
48:         }
49:     }
50:     return 0;
51: }

```

kernel/syscalls/sigreturn.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/sigreturn.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/process.h>
9: #include <fiwix/sigcontext.h>
10: #include <fiwix/string.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #endif /* __DEBUG__ */
15:
16: int sys_sigreturn(unsigned int signum, int arg2, int arg3, int arg4, int arg5, s
truct sigcontext *sc)
17: {
18: #ifdef __DEBUG__
19:     printk("(pid %d) sys_sigreturn(0x%08x)\n", current->pid, signum);
20: #endif /* __DEBUG__ */
21:
22:     current->sigblocked &= ~current->sigexecuting;
23:     current->sigexecuting = 0;
24:     memcpy_b(sc, &current->sc[signum - 1], sizeof(struct sigcontext));
25:
26:     /*
27:      * We return here the value that the syscall was returning when it was
28:      * interrupted by a signal.
29:      */
30:     return current->sc[signum - 1].eax;
31: }
```


kernel/syscalls/sigsuspend.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/sigsuspend.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/syscalls.h>
10: #include <fiwix/signal.h>
11: #include <fiwix/process.h>
12: #include <fiwix/errno.h>
13:
14: #ifdef __DEBUG__
15: #include <fiwix/stdio.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_sigsuspend(__sigset_t *mask)
19: {
20:     __sigset_t old_mask;
21:     int errno;
22:
23: #ifdef __DEBUG__
24:     printk("(pid %d) sys_sigsuspend(0x%08x) -> ", current->pid, mask);
25: #endif /* __DEBUG__ */
26:
27:     old_mask = current->sigblocked;
28:     if(mask) {
29:         if((errno = check_user_area(VERIFY_READ, mask, sizeof(__sigset_t
)))) {
30:             return errno;
31:         }
32:         current->sigblocked = (int)*mask & SIG_BLOCKABLE;
33:     } else {
34:         current->sigblocked = 0 & SIG_BLOCKABLE;
35:     }
36:     sys_pause();
37:     current->sigblocked = old_mask;
38:
39: #ifdef __DEBUG__
40:     printk("-EINTR\n");
41: #endif /* __DEBUG__ */
42:
43:     return -EINTR;
44: }

```

kernel/syscalls/socketcall.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/socketcall.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/errno.h>
9:
10: #ifdef __DEBUG__
11: #include <fiwix/stdio.h>
12: #include <fiwix/process.h>
13: #endif /* __DEBUG__ */
14:
15: int sys_socketcall(int call, unsigned long int *args)
16: {
17: #ifdef __DEBUG__
18:     printk("(pid %d) sys_socketcall(%d, 0x%08x) -> ENOENT\n", current->pid,
call, args);
19: #endif /* __DEBUG__ */
20:
21:     /* FIXME: to be implemented */
22:
23:     return -ENOENT;
24: }
```

kernel/syscalls/ssetmask.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/ssetmask.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/process.h>
9: #include <fiwix/signal.h>
10:
11: #ifdef __DEBUG__
12: #include <fiwix/stdio.h>
13: #endif /* __DEBUG__ */
14:
15: int sys_ssetmask(int newmask)
16: {
17:     int oldmask;
18:
19: #ifdef __DEBUG__
20:     printk("(pid %d) sys_ssetmask(0x%08x) -> \n", current->pid, newmask);
21: #endif /* __DEBUG__ */
22:
23:     oldmask = current->sigblocked;
24:     current->sigblocked = newmask & SIG_BLOCKABLE;
25:     return oldmask;
26: }
```

kernel/syscalls/stat.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/stat.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/statbuf.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/string.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #include <fiwix/process.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_stat(const char *filename, struct old_stat *statbuf)
19: {
20:     struct inode *i;
21:     char *tmp_name;
22:     int errno;
23:
24: #ifdef __DEBUG__
25:     printk("(pid %d) sys_stat(%s, 0x%08x) -> returning structure\n", current
->pid, filename, (unsigned int )statbuf);
26: #endif /* __DEBUG__ */
27:
28:     if((errno = check_user_area(VERIFY_WRITE, statbuf, sizeof(struct old_sta
t)))) {
29:         return errno;
30:     }
31:     if((errno = malloc_name(filename, &tmp_name)) < 0) {
32:         return errno;
33:     }
34:     if((errno = namei(tmp_name, &i, NULL, FOLLOW_LINKS))) {
35:         free_name(tmp_name);
36:         return errno;
37:     }
38:     statbuf->st_dev = i->dev;
39:     statbuf->st_ino = i->inode;
40:     statbuf->st_mode = i->i_mode;
41:     statbuf->st_nlink = i->i_nlink;
42:     statbuf->st_uid = i->i_uid;
43:     statbuf->st_gid = i->i_gid;
44:     statbuf->st_rdev = i->rdev;
45:     statbuf->st_size = i->i_size;
46:     statbuf->st_atime = i->i_atime;
47:     statbuf->st_mtime = i->i_mtime;
48:     statbuf->st_ctime = i->i_ctime;
49:     iput(i);
50:     free_name(tmp_name);
51:     return 0;
52: }

```

kernel/syscalls/statfs.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/statfs.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/statfs.h>
10: #include <fiwix/errno.h>
11: #include <fiwix/string.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #include <fiwix/process.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_statfs(const char *filename, struct statfs *statfsbuf)
19: {
20:     struct inode *i;
21:     char *tmp_name;
22:     int errno;
23:
24: #ifdef __DEBUG__
25:     printk("(pid %d) sys_statfs('%s', 0x%08x)\n", current->pid, filename, (u
nsigned int)statfsbuf);
26: #endif /* __DEBUG__ */
27:
28:     if((errno = check_user_area(VERIFY_WRITE, statfsbuf, sizeof(struct statf
s)))) {
29:         return errno;
30:     }
31:     if((errno = malloc_name(filename, &tmp_name)) < 0) {
32:         return errno;
33:     }
34:     if((errno = namei(tmp_name, &i, NULL, FOLLOW_LINKS))) {
35:         free_name(tmp_name);
36:         return errno;
37:     }
38:     if(i->sb && i->sb->fsop && i->sb->fsop->statfs) {
39:         i->sb->fsop->statfs(i->sb, statfsbuf);
40:         iput(i);
41:         free_name(tmp_name);
42:         return 0;
43:     }
44:     iput(i);
45:     free_name(tmp_name);
46:     return -ENOSYS;
47: }

```

kernel/syscalls/stime.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/stime.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/timer.h>
11: #include <fiwix/errno.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #include <fiwix/process.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_stime(__time_t *t)
19: {
20:     int errno;
21:
22: #ifdef __DEBUG__
23:     printk("(pid %d) sys_stime(0x%08x)\n", current->pid, (unsigned int)t);
24: #endif /* __DEBUG__ */
25:
26:     if(!IS_SUPERUSER) {
27:         return -EPERM;
28:     }
29:     if((errno = check_user_area(VERIFY_READ, t, sizeof(__time_t)))) {
30:         return errno;
31:     }
32:
33:     set_system_time(*t);
34:     return 0;
35: }
```

kernel/syscalls/symlink.c

Page 1/2

```

1: /*
2:  * fiwix/kernel/syscalls/symlink.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/stat.h>
10: #include <fiwix/errno.h>
11: #include <fiwix/string.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #include <fiwix/process.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_symlink(const char *oldpath, const char *newpath)
19: {
20:     struct inode *i, *dir;
21:     char *tmp_oldpath, *tmp_newpath, *basename;
22:     int errno;
23:
24: #ifdef __DEBUG__
25:     printk("(pid %d) sys_symlink('%s', '%s')\n", current->pid, oldpath, newp
ath);
26: #endif /* __DEBUG__ */
27:
28:     if((errno = malloc_name(oldpath, &tmp_oldpath)) < 0) {
29:         return errno;
30:     }
31:     if((errno = malloc_name(newpath, &tmp_newpath)) < 0) {
32:         free_name(tmp_oldpath);
33:         return errno;
34:     }
35:     basename = get_basename(tmp_newpath);
36:     if((errno = namei(tmp_newpath, &i, &dir, !FOLLOW_LINKS))) {
37:         if(!dir) {
38:             free_name(tmp_oldpath);
39:             free_name(tmp_newpath);
40:             return errno;
41:         }
42:     }
43:     if(!errno) {
44:         iput(i);
45:         iput(dir);
46:         free_name(tmp_oldpath);
47:         free_name(tmp_newpath);
48:         return -EEXIST;
49:     }
50:     if(IS_RDONLY_FS(dir)) {
51:         iput(dir);
52:         free_name(tmp_oldpath);
53:         free_name(tmp_newpath);
54:         return -EROFS;
55:     }
56:
57:     if(check_permission(TO_EXEC | TO_WRITE, dir) < 0) {
58:         iput(dir);
59:         free_name(tmp_oldpath);
60:         free_name(tmp_newpath);
61:         return -EACCES;
62:     }
63:
64:     if(dir->fsop && dir->fsop->symlink) {
65:         errno = dir->fsop->symlink(dir, basename, tmp_oldpath);
66:     } else {

```

kernel/syscalls/symlink.c

Page 2/2

```
67:             errno = -EPERM;
68:         }
69:         iput(dir);
70:         free_name(tmp_oldpath);
71:         free_name(tmp_newpath);
72:         return errno;
73: }
```


kernel/syscalls/sync.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/sync.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/buffer.h>
10: #include <fiwix/filesystems.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #include <fiwix/process.h>
15: #endif /* __DEBUG__ */
16:
17: void sys_sync(void)
18: {
19: #ifdef __DEBUG__
20:     printk("(pid %d) sys_sync()\n", current->pid);
21: #endif /* __DEBUG__ */
22:
23:     sync_superblocks(0);    /* in all devices */
24:     sync_inodes(0);        /* in all devices */
25:     sync_buffers(0);       /* in all devices */
26:     return;
27: }
```

kernel/syscalls/sysinfo.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/sysinfo.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/system.h>
11: #include <fiwix/sched.h>
12: #include <fiwix/mm.h>
13: #include <fiwix/string.h>
14:
15: #ifdef __DEBUG__
16: #include <fiwix/stdio.h>
17: #include <fiwix/process.h>
18: #endif /* __DEBUG__ */
19:
20: int sys_sysinfo(struct sysinfo *info)
21: {
22:     struct sysinfo tmp_info;
23:     struct proc *p;
24:     int errno;
25:
26: #ifdef __DEBUG__
27:     printk("(pid %d) sys_sysinfo(0x%08x)\n ", current->pid, (unsigned int)in
fo);
28: #endif /* __DEBUG__ */
29:
30:     if((errno = check_user_area(VERIFY_WRITE, info, sizeof(struct sysinfo)))
) {
31:         return errno;
32:     }
33:     memset_b(&tmp_info, NULL, sizeof(struct sysinfo));
34:     tmp_info.loads[0] = avenrun[0] << (SI_LOAD_SHIFT - FSHIFT);
35:     tmp_info.loads[1] = avenrun[1] << (SI_LOAD_SHIFT - FSHIFT);
36:     tmp_info.loads[2] = avenrun[2] << (SI_LOAD_SHIFT - FSHIFT);
37:     tmp_info.uptime = kstat.uptime;
38:     tmp_info.totalram = kstat.total_mem_pages << PAGE_SHIFT;
39:     tmp_info.freeram = kstat.free_pages << PAGE_SHIFT;
40:     tmp_info.sharedram = 0;
41:     tmp_info.bufferram = kstat.buffers * 1024;
42:     tmp_info.totalswap = 0;
43:     tmp_info.freeswap = 0;
44:     FOR_EACH_PROCESS(p) {
45:         if(p->state) {
46:             tmp_info.procs++;
47:         }
48:     }
49:
50:     memcpy_b(info, &tmp_info, sizeof(struct sysinfo));
51:     return 0;
52: }

```

kernel/syscalls/time.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/time.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/kernel.h>
10: #include <fiwix/fs.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #include <fiwix/process.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_time(__time_t *tloc)
18: {
19:     int errno;
20:
21: #ifdef __DEBUG__
22:     printk("(pid %d) sys_time() -> ", current->pid);
23: #endif /* __DEBUG__ */
24:
25:     if(tloc) {
26:         if((errno = check_user_area(VERIFY_WRITE, tloc, sizeof(__time_t)
))) {
27:             return errno;
28:         }
29:         *tloc = CURRENT_TIME;
30:     }
31:
32: #ifdef __DEBUG__
33:     printk("%d\n", CURRENT_TIME);
34: #endif /* __DEBUG__ */
35:
36:     return CURRENT_TIME;
37: }
```

kernel/syscalls/times.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/times.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/types.h>
10: #include <fiwix/syscalls.h>
11: #include <fiwix/times.h>
12:
13: #ifdef __DEBUG__
14: #include <fiwix/stdio.h>
15: #include <fiwix/process.h>
16: #endif /* __DEBUG__ */
17:
18: int sys_times(struct tms *buf)
19: {
20:     int errno;
21:
22: #ifdef __DEBUG__
23:     printk("(pid %d) sys_times(0x%08x) -> ", (unsigned int )buf);
24: #endif /* __DEBUG__ */
25:
26:     if((errno = check_user_area(VERIFY_WRITE, buf, sizeof(struct tms)))) {
27:         return errno;
28:     }
29:     if(buf) {
30:         buf->tms_utime = tv2ticks(&current->usage.ru_utime);
31:         buf->tms_stime = tv2ticks(&current->usage.ru_stime);
32:         buf->tms_cutime = tv2ticks(&current->cusage.ru_utime);
33:         buf->tms_cstime = tv2ticks(&current->cusage.ru_stime);
34:     }
35:
36:     return kstat.ticks;
37: }
```

kernel/syscalls/truncate.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/truncate.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/stat.h>
11: #include <fiwix/errno.h>
12: #include <fiwix/string.h>
13:
14: #ifdef __DEBUG__
15: #include <fiwix/stdio.h>
16: #include <fiwix/process.h>
17: #endif /* __DEBUG__ */
18:
19: int sys_truncate(const char *path, __off_t length)
20: {
21:     struct inode *i;
22:     char *tmp_name;
23:     int errno;
24:
25: #ifdef __DEBUG__
26:     printk("(pid %d) sys_truncate(%s, %d)\n", current->pid, path, length);
27: #endif /* __DEBUG__ */
28:
29:     if((errno = malloc_name(path, &tmp_name)) < 0) {
30:         return errno;
31:     }
32:     if((errno = namei(tmp_name, &i, NULL, FOLLOW_LINKS))) {
33:         free_name(tmp_name);
34:         return errno;
35:     }
36:     if(S_ISDIR(i->i_mode)) {
37:         iput(i);
38:         free_name(tmp_name);
39:         return -EISDIR;
40:     }
41:     if(IS_RDONLY_FS(i)) {
42:         iput(i);
43:         free_name(tmp_name);
44:         return -EROFS;
45:     }
46:     if(check_permission(TO_WRITE, i) < 0) {
47:         iput(i);
48:         free_name(tmp_name);
49:         return -EACCES;
50:     }
51:     if(length == i->i_size) {
52:         iput(i);
53:         free_name(tmp_name);
54:         return 0;
55:     }
56:
57:     errno = 0;
58:     if(i->fsop && i->fsop->truncate) {
59:         inode_lock(i);
60:         errno = i->fsop->truncate(i, length);
61:         inode_unlock(i);
62:     }
63:     iput(i);
64:     free_name(tmp_name);
65:     return errno;
66: }

```

kernel/syscalls/umask.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/umask.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/process.h>
10: #include <fiwix/stat.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #endif /* __DEBUG__ */
15:
16: int sys_umask(__mode_t mask)
17: {
18:     __mode_t old_umask;
19:
20: #ifdef __DEBUG__
21:     printk("(pid %d) sys_umask(%d)\n", current->pid, mask);
22: #endif /* __DEBUG__ */
23:
24:     old_umask = current->umask;
25:     current->umask = mask & (S_IRWXU | S_IRWXG | S_IRWXO);
26:     return old_umask;
27: }
```

kernel/syscalls/umount2.c

Page 1/2

```

1: /*
2:  * fiwix/kernel/syscalls/umount2.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/filesystems.h>
11: #include <fiwix/stat.h>
12: #include <fiwix/sleep.h>
13: #include <fiwix/devices.h>
14: #include <fiwix/buffer.h>
15: #include <fiwix/errno.h>
16: #include <fiwix/stdio.h>
17: #include <fiwix/string.h>
18:
19: static struct resource umount_resource = { NULL, NULL };
20:
21: int sys_umount2(const char *target, int flags)
22: {
23:     struct inode *i_target;
24:     struct mount *mt = NULL;
25:     struct filesystems *fs;
26:     struct device *d;
27:     struct inode dummy_i;
28:     struct superblock *sb;
29:     char *tmp_target;
30:     __dev_t dev;
31:     int errno;
32:
33: #ifdef __DEBUG__
34:     printk("(pid %d) sys_umount2(%s, 0x%08x)\n", current->pid, target, flags
);
35: #endif /*__DEBUG__ */
36:
37:     if(!IS_SUPERUSER) {
38:         return -EPERM;
39:     }
40:     if((errno = malloc_name(target, &tmp_target)) < 0) {
41:         return errno;
42:     }
43:     if((errno = namei(tmp_target, &i_target, NULL, FOLLOW_LINKS))) {
44:         free_name(tmp_target);
45:         return errno;
46:     }
47:     if(!S_ISBLK(i_target->i_mode) && !S_ISDIR(i_target->i_mode)) {
48:         iput(i_target);
49:         free_name(tmp_target);
50:         return -EINVAL;
51:     }
52:
53:     if(!(mt = get_mount_point(i_target))) {
54:         iput(i_target);
55:         free_name(tmp_target);
56:         return -EINVAL;
57:     }
58:     if(S_ISBLK(i_target->i_mode)) {
59:         dev = i_target->rdev;
60:     } else {
61:         dev = i_target->sb->dev;
62:     }
63:
64:     if(!(sb = get_superblock(dev))) {
65:         printk("WARNING: %s(): unable to get superblock from device %d,%
d\n", __FUNCTION__, MAJOR(dev), MINOR(dev));

```

kernel/syscalls/umount2.c

Page 2/2

```

66:         iput(i_target);
67:         free_name(tmp_target);
68:         return -EINVAL;
69:     }
70:
71:     /*
72:      * We must free now the inode in order to avoid having its 'count' to 2
73:      * when calling check_fs_busy(), specially if sys_umount() was called
74:      * using the mount-point instead of the device.
75:      */
76:     iput(i_target);
77:     free_name(tmp_target);
78:
79:     if(check_fs_busy(dev, sb->root)) {
80:         return -EBUSY;
81:     }
82:
83:     lock_resource(&umount_resource);
84:
85:     fs = mt->fs;
86:     if(fs->fsop && fs->fsop->release_superblock) {
87:         fs->fsop->release_superblock(sb);
88:     }
89:     if(sb->fsop->flags & FSOP_REQUIRES_DEV) {
90:         if(!(d = get_device(BLK_DEV, MAJOR(dev)))) {
91:             printk("WARNING: %s(): block device %d,%d not registered
!\n", __FUNCTION__, MAJOR(dev), MINOR(dev));
92:             unlock_resource(&umount_resource);
93:             return -EINVAL;
94:         }
95:         memset_b(&dummy_i, 0, sizeof(struct inode));
96:         dummy_i.dev = dummy_i.rdev = dev;
97:         if(d && d->fsop && d->fsop->close) {
98:             d->fsop->close(&dummy_i, NULL);
99:         }
100:     }
101:
102:     sb->dir->mount_point = NULL;
103:     iput(sb->root);
104:     iput(sb->dir);
105:
106:     sync_superblocks(dev);
107:     sync_inodes(dev);
108:     sync_buffers(dev);
109:     invalidate_buffers(dev);
110:     invalidate_inodes(dev);
111:
112:     release_mount_point(mt);
113:     unlock_resource(&umount_resource);
114:     return 0;
115: }

```


kernel/syscalls/umount.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/umount.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/syscalls.h>
9: #include <fiwix/process.h>
10:
11: #ifdef __DEBUG__
12: #include <fiwix/stdio.h>
13: #endif /*__DEBUG__*/
14:
15: int sys_umount(const char *target)
16: {
17: #ifdef __DEBUG__
18:     printk("(pid %d) sys_umount(%s)\n", current->pid, target);
19: #endif /*__DEBUG__*/
20:
21:     return sys_umount2(target, 0);
22: }
```

kernel/syscalls/uname.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/uname.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/utsname.h>
10: #include <fiwix/string.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #include <fiwix/process.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_uname(struct old_utsname *uname)
18: {
19:     int errno;
20:
21: #ifdef __DEBUG__
22:     printk("(pid %d) sys_uname(0x%08x) -> returning ", current->pid, (unsigned int)uname);
23: #endif /* __DEBUG__ */
24:
25:     if((errno = check_user_area(VERIFY_WRITE, uname, sizeof(struct old_utsname)))) {
26:         return errno;
27:     }
28:     memcpy_b(&uname->sysname, &sys_utsname.sysname, sizeof(sys_utsname.sysname));
29:     memcpy_b(&uname->nodename, &sys_utsname.nodename, sizeof(sys_utsname.nodename));
30:     memcpy_b(&uname->release, &sys_utsname.release, sizeof(sys_utsname.release));
31:     memcpy_b(&uname->version, &sys_utsname.version, sizeof(sys_utsname.version));
32:     memcpy_b(&uname->machine, &sys_utsname.machine, sizeof(sys_utsname.machine));
33:     return 0;
34: }
```

kernel/syscalls/unlink.c

Page 1/2

```

1: /*
2:  * fiwix/kernel/syscalls/unlink.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/syscalls.h>
10: #include <fiwix/stat.h>
11: #include <fiwix/errno.h>
12: #include <fiwix/string.h>
13:
14: #ifdef __DEBUG__
15: #include <fiwix/stdio.h>
16: #include <fiwix/process.h>
17: #endif /* __DEBUG__ */
18:
19: int sys_unlink(const char *filename)
20: {
21:     struct inode *i, *dir;
22:     char *tmp_name, *basename;
23:     int errno;
24:
25: #ifdef __DEBUG__
26:     printk("(pid %d) sys_unlink('%s')\n", current->pid, filename);
27: #endif /* __DEBUG__ */
28:
29:     if((errno = malloc_name(filename, &tmp_name)) < 0) {
30:         return errno;
31:     }
32:     if((errno = namei(tmp_name, &i, &dir, !FOLLOW_LINKS))) {
33:         if(dir) {
34:             iput(dir);
35:         }
36:         free_name(tmp_name);
37:         return errno;
38:     }
39:     if(S_ISDIR(i->i_mode)) {
40:         iput(i);
41:         iput(dir);
42:         free_name(tmp_name);
43:         return -EPERM; /* Linux returns -EISDIR */
44:     }
45:     if(IS_RDONLY_FS(i)) {
46:         iput(i);
47:         iput(dir);
48:         free_name(tmp_name);
49:         return -EROFS;
50:     }
51:     if(check_permission(TO_EXEC | TO_WRITE, dir) < 0) {
52:         iput(i);
53:         iput(dir);
54:         free_name(tmp_name);
55:         return -EACCES;
56:     }
57:
58:     /* check sticky permission bit */
59:     if(dir->i_mode & S_ISVTX) {
60:         if(check_user_permission(i)) {
61:             iput(i);
62:             iput(dir);
63:             free_name(tmp_name);
64:             return -EPERM;
65:         }
66:     }
67:

```

kernel/syscalls/unlink.c

Page 2/2

```
68:         basename = get_basename(filename);
69:         if(dir->fsop && dir->fsop->unlink) {
70:             errno = dir->fsop->unlink(dir, i, basename);
71:         } else {
72:             errno = -EPERM;
73:         }
74:         iput(i);
75:         iput(dir);
76:         free_name(tmp_name);
77:         return errno;
78: }
```

kernel/syscalls/ustat.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/ustat.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/filesystems.h>
11: #include <fiwix/ustat.h>
12: #include <fiwix/statfs.h>
13: #include <fiwix/errno.h>
14: #include <fiwix/string.h>
15:
16: #ifdef __DEBUG__
17: #include <fiwix/stdio.h>
18: #include <fiwix/process.h>
19: #endif /* __DEBUG__ */
20:
21: int sys_ustat(__dev_t dev, struct ustat *ubuf)
22: {
23:     struct superblock *sb;
24:     struct statfs statfsbuf;
25:     int errno;
26:
27: #ifdef __DEBUG__
28:     printk("(pid %d) sys_ustat(%d, 0x%08x)\n", current->pid, dev, (int)ubuf)
;
29: #endif /* __DEBUG__ */
30:     if((errno = check_user_area(VERIFY_WRITE, ubuf, sizeof(struct ustat))))
{
31:         return errno;
32:     }
33:     if(!(sb = get_superblock(dev))) {
34:         return -EINVAL;
35:     }
36:     if(sb->fsop && sb->fsop->statfs) {
37:         sb->fsop->statfs(sb, &statfsbuf);
38:         memset_b(ubuf, NULL, sizeof(struct ustat));
39:         ubuf->f_tfree = statfsbuf.f_bfree;
40:         ubuf->f_tinode = statfsbuf.f_ffree;
41:         return 0;
42:     }
43:     return -ENOSYS;
44: }

```

kernel/syscalls/utime.c

Page 1/2

```

1: /*
2:  * fiwix/kernel/syscalls/utime.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/utime.h>
11: #include <fiwix/stat.h>
12: #include <fiwix/errno.h>
13: #include <fiwix/string.h>
14:
15: #ifdef __DEBUG__
16: #include <fiwix/stdio.h>
17: #include <fiwix/process.h>
18: #endif /* __DEBUG__ */
19:
20: int sys_utime(const char *filename, struct utimbuf *times)
21: {
22:     struct inode *i;
23:     char *tmp_name;
24:     int errno;
25:
26: #ifdef __DEBUG__
27:     printk("(pid %d) sys_utime('%s', 0x%08x)\n", current->pid, filename, (in
t)times);
28: #endif /* __DEBUG__ */
29:
30:     if((errno = malloc_name(filename, &tmp_name)) < 0) {
31:         return errno;
32:     }
33:     if((errno = namei(tmp_name, &i, NULL, FOLLOW_LINKS))) {
34:         free_name(tmp_name);
35:         return errno;
36:     }
37:
38:     if(IS_RDONLY_FS(i)) {
39:         iput(i);
40:         free_name(tmp_name);
41:         return -EROFS;
42:     }
43:
44:     if(!times) {
45:         if(check_user_permission(i) || check_permission(TO_WRITE, i)) {
46:             iput(i);
47:             free_name(tmp_name);
48:             return -EACCES;
49:         }
50:         i->i_atime = CURRENT_TIME;
51:         i->i_mtime = CURRENT_TIME;
52:     } else {
53:         if((errno = check_user_area(VERIFY_READ, times, sizeof(struct ut
imbuf)))) {
54:             iput(i);
55:             free_name(tmp_name);
56:             return errno;
57:         }
58:         if(check_user_permission(i)) {
59:             iput(i);
60:             free_name(tmp_name);
61:             return -EPERM;
62:         }
63:         i->i_atime = times->actime;
64:         i->i_mtime = times->modtime;
65:     }

```

kernel/syscalls/utime.c

Page 2/2

```
66:
67:         i->i_ctime = CURRENT_TIME;
68:         i->dirty = 1;
69:         iput(i);
70:         free_name(tmp_name);
71:         return 0;
72: }
```

kernel/syscalls/wait4.c

Page 1/2

```

1: /*
2:  * fiwix/kernel/syscalls/wait4.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/resource.h>
11: #include <fiwix/signal.h>
12: #include <fiwix/sched.h>
13: #include <fiwix/sleep.h>
14: #include <fiwix/errno.h>
15:
16: #ifdef __DEBUG__
17: #include <fiwix/stdio.h>
18: #include <fiwix/process.h>
19: #endif /* __DEBUG__ */
20:
21: int sys_wait4(__pid_t pid, int *status, int options, struct rusage *ru)
22: {
23:     struct proc *p;
24:     int flag, signum, errno;
25:
26: #ifdef __DEBUG__
27:     printk("(pid %d) sys_wait4(%d, status, %d)\n", current->pid, pid, option
s);
28: #endif /* __DEBUG__ */
29:
30:     if(ru) {
31:         if((errno = check_user_area(VERIFY_WRITE, ru, sizeof(struct rusa
ge)))) {
32:             return errno;
33:         }
34:     }
35:     while(current->children) {
36:         flag = 0;
37:         FOR_EACH_PROCESS(p) {
38:             if(p->ppid != current->pid) {
39:                 continue;
40:             }
41:             if(pid > 0) {
42:                 if(p->pid == pid) {
43:                     flag = 1;
44:                 }
45:             }
46:             if(!pid) {
47:                 if(p->pgid == current->pgid) {
48:                     flag = 1;
49:                 }
50:             }
51:             if(pid < -1) {
52:                 if(p->pgid == -pid) {
53:                     flag = 1;
54:                 }
55:             }
56:             if(pid == -1) {
57:                 flag = 1;
58:             }
59:             if(flag) {
60:                 if(p->state == PROC_STOPPED) {
61:                     if(!p->exit_code) {
62:                         continue;
63:                     }
64:                     if(status) {
65:                         *status = (p->exit_code << 8) |

```


kernel/syscalls/wait4.c

Page 2/2

```
0x7F;
66:         }
67:         p->exit_code = 0;
68:         if(ru) {
69:             get_rusage(p, ru);
70:         }
71:         return p->pid;
72:     }
73:     if(p->state == PROC_ZOMBIE) {
74:         add_rusage(p);
75:         if(status) {
76:             *status = p->exit_code;
77:         }
78:         if(ru) {
79:             get_rusage(p, ru);
80:         }
81:         return remove_zombie(p);
82:     }
83: }
84:     flag = 0;
85: }
86: if(options & WNOHANG) {
87:     if(flag) {
88:         return 0;
89:     }
90:     break;
91: }
92: if((signum = sleep(&sys_wait4, PROC_INTERRUPTIBLE))) {
93:     return signum;
94: }
95: current->sigpending &= SIG_MASK(SIGCHLD);
96: }
97: return -ECHILD;
98: }
```

kernel/syscalls/waitpid.c

Page 1/1

```
1: /*
2:  * fiwix/kernel/syscalls/waitpid.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/syscalls.h>
10: #include <fiwix/string.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #include <fiwix/process.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_waitpid(__pid_t pid, int *status, int options)
18: {
19: #ifdef __DEBUG__
20:     printk("(pid %d) sys_waitpid(%d, 0x%08x, %d)\n", current->pid, pid, *st
atus, options);
21: #endif /* __DEBUG__ */
22:     return sys_wait4(pid, status, options, NULL);
23: }
```

kernel/syscalls/write.c

Page 1/1

```

1: /*
2:  * fiwix/kernel/syscalls/write.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/fs.h>
9: #include <fiwix/fcntl.h>
10: #include <fiwix/errno.h>
11:
12: #ifdef __DEBUG__
13: #include <fiwix/stdio.h>
14: #include <fiwix/process.h>
15: #endif /* __DEBUG__ */
16:
17: int sys_write(unsigned int ufd, const char *buf, int count)
18: {
19:     struct inode *i;
20:     int errno;
21:
22: #ifdef __DEBUG__
23: /*      printk("(pid %d) sys_write(%d, '%s', %d)\n", current->pid, ufd, buf, cou
nt);*/
24:     printk("(pid %d) sys_write(%d, 0x%08x, %d) -> ", current->pid, ufd, buf,
count);
25: #endif /* __DEBUG__ */
26:
27:     CHECK_UFD(ufd);
28:     if((errno = check_user_area(VERIFY_READ, buf, count))) {
29:         return errno;
30:     }
31:     if(fd_table[current->fd[ufd]].flags & O_RDONLY) {
32:         return -EBADF;
33:     }
34:     if(!count) {
35:         return 0;
36:     }
37:     if(count < 0) {
38:         return -EINVAL;
39:     }
40:     i = fd_table[current->fd[ufd]].inode;
41:     if(i->fsop && i->fsop->write) {
42:         errno = i->fsop->write(i, &fd_table[current->fd[ufd]], buf, coun
t);
43: #ifdef __DEBUG__
44:         printk("%d\n", errno);
45: #endif /* __DEBUG__ */
46:         return errno;
47:     }
48:     return -EINVAL;
49: }

```

drivers/block/dma.c

Page 1/2

```

1: /*
2:  * fiwix/drivers/block/dma.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/dma.h>
10: #include <fiwix/string.h>
11:
12: /*
13:  * DMA Channel Page Address Count
14:  * -----
15:  * 0 (8 bit)      87h      0h      1h
16:  * 1 (8 bit)      83h      2h      3h
17:  * 2 (8 bit)      81h      4h      5h
18:  * 3 (8 bit)      82h      6h      7h
19:  * 4 (16 bit)     8Fh      C0h     C2h
20:  * 5 (16 bit)     8Bh      C4h     C6h
21:  * 6 (16 bit)     89h      C8h     CAh
22:  * 7 (16 bit)     8Ah      CCh     CEh
23:  */
24:
25: #define LOW_BYTE(addr) (addr & 0x00FF)
26: #define HIGH_BYTE(addr) ((addr & 0xFF00) >> 8)
27:
28: unsigned char dma_mask[DMA_CHANNELS] =
29:     { 0x0A, 0x0A, 0x0A, 0x0A, 0xD4, 0xD4, 0xD4, 0xD4 };
30: unsigned char dma_mode[DMA_CHANNELS] =
31:     { 0x0B, 0x0B, 0x0B, 0x0B, 0xD6, 0xD6, 0xD6, 0xD6 };
32: unsigned char dma_clear[DMA_CHANNELS] =
33:     { 0x0C, 0x0C, 0x0C, 0x0C, 0xD8, 0xD8, 0xD8, 0xD8 };
34: unsigned char dma_page[DMA_CHANNELS] =
35:     { 0x87, 0x83, 0x81, 0x82, 0x8F, 0x8B, 0x89, 0x8A };
36: unsigned char dma_address[DMA_CHANNELS] =
37:     { 0x00, 0x02, 0x04, 0x06, 0xC0, 0xC4, 0xC8, 0xCC };
38: unsigned char dma_count[DMA_CHANNELS] =
39:     { 0x01, 0x03, 0x05, 0x07, 0xC2, 0xC6, 0xCA, 0xCE };
40:
41:
42: void start_dma(int channel, void *address, unsigned int count, int mode)
43: {
44:     /* setup (mask) the DMA channel */
45:     outport_b(dma_mask[channel], DMA_MASK_CHANNEL | channel);
46:
47:     /* clear any data transfers that are currently executing */
48:     outport_b(dma_clear[channel], 0);
49:
50:     /* set the specified mode */
51:     outport_b(dma_mode[channel], mode | channel);
52:
53:     /* set the offset address */
54:     outport_b(dma_address[channel], LOW_BYTE((unsigned int)address));
55:     outport_b(dma_address[channel], HIGH_BYTE((unsigned int)address));
56:
57:     /* set the physical page */
58:     outport_b(dma_page[channel], (unsigned int)address >> 16);
59:
60:     /* the true (internal) length sent to the DMA is actually length + 1 */
61:     count--;
62:
63:     /* set the length of the data */
64:     outport_b(dma_count[channel], LOW_BYTE(count));
65:     outport_b(dma_count[channel], HIGH_BYTE(count));
66:
67:     /* clear the mask */

```

drivers/block/dma.c

Page 2/2

```
68:         outport_b(dma_mask[channel], DMA_UNMASK_CHANNEL | channel);
69:     }
70:
71: int dma_register(int channel, char *dev_name)
72: {
73:     if(dma_resources[channel]) {
74:         return 1;
75:     }
76:     dma_resources[channel] = dev_name;
77:     return 0;
78: }
79:
80: int dma_unregister(int channel)
81: {
82:     if(!dma_resources[channel]) {
83:         return 1;
84:     }
85:
86:     dma_resources[channel] = NULL;
87:     return 0;
88: }
89:
90: void dma_init(void)
91: {
92:     memset_b(dma_resources, NULL, sizeof(dma_resources));
93: }
```

drivers/block/floppy.c

Page 1/14

```

1: /*
2:  * fiwix/drivers/block/floppy.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/floppy.h>
10: #include <fiwix/ioctl.h>
11: #include <fiwix/devices.h>
12: #include <fiwix/part.h>
13: #include <fiwix/fs.h>
14: #include <fiwix/buffer.h>
15: #include <fiwix/sleep.h>
16: #include <fiwix/timer.h>
17: #include <fiwix/sched.h>
18: #include <fiwix/errno.h>
19: #include <fiwix/pic.h>
20: #include <fiwix/cmos.h>
21: #include <fiwix/dma.h>
22: #include <fiwix/stdio.h>
23: #include <fiwix/string.h>
24:
25: #define WAIT_MOTOR_OFF (3 * HZ)      /* time waiting to turn the motor off */
26: #define WAIT_FDC        WAIT_MOTOR_OFF
27:
28: #define INVALID_TRACK  -1
29:
30: #define DEV_TYPE_SHIFT  2           /* right shift to match with the floppy
31:                                     type when minor > 3 */
32:
33: static int need_reset = 0;
34: static int fdc_wait_interrupt = 0;
35: static int fdc_timeout = 0;
36: static unsigned char fdc_results[MAX_FDC_RESULTS];
37: static struct resource floppy_resource = { NULL, NULL };
38:
39: static struct fddt fdd_type[] = {
40: /*
41:  * R (data rate): 0 = 500Kb/s, 2 = 250Kb/s, 3 = 1Mb/s
42:  * SPEC(IFY) 0xAF: SRT = 6ms, HUT = 240ms (500Kb/s)
43:  * SPEC(IFY) 0xD7: SRT = 6ms, HUT = 240ms (250Kb/s)
44:  * SPEC(IFY) 0xDF: SRT = 3ms, HUT = 240ms (500Kb/s)
45:  * Head Load Time 0x02: HLT = 4ms (500Kb/s), Non-DMA = 0 (DMA enabled)
46:  *
47:  *          SIZE      KB   T   S   H   G_RW  G_FM  R  SPEC  HLT  NAME
48:  *          -----
49:  *          {    0,    0,  0,  0,  0, 0x00, 0x00, 0, 0x00, 0x00, NULL
50:  *          {   720,   360, 40,  9,  2, 0x2A, 0x50, 2, 0xD7, 0x02, "360KB 5.25\""},
51:  *          { 2400, 1200, 80, 15,  2, 0x2A, 0x50, 0, 0xAF, 0x02, "1.2MB 5.25\""},
52:  *          { 1440,   720, 80,  9,  2, 0x1B, 0x54, 2, 0xD7, 0x02, "720KB 3.5\""},
53:  *          { 2880, 1440, 80, 18,  2, 0x1B, 0x54, 0, 0xAF, 0x02, "1.44MB 3.5\""},
54:  *          { 5760, 2880, 80, 36,  2, 0x38, 0x53, 3, 0xDF, 0x02, "2.88MB 3.5\""}, */
55: };
56:
57: /* maximum size of a track for floppy types of 1.44MB */
58: extern char _fdc_transfer_area[BPS * 2 * 18];
59:
60: struct fdd_status {
61:     char type;                /* floppy disk drive type */
62:     char motor;
63:     char recalibrated;
64:     char current_track;
65: };
66:
67: static struct fdd_status fdd_status[] = {

```

drivers/block/floppy.c

Page 2/14

```

68:         { 0, 0, 0, INVALID_TRACK },
69:         { 0, 0, 0, INVALID_TRACK },
70: };
71:
72: static unsigned char current_fdd = 0;
73: static struct fddt *current_fdd_type;
74: static unsigned int fdd_sizes[256];
75:
76: static struct fs_operations fdc_driver_fsop = {
77:     0,
78:     0,
79:
80:     fdc_open,
81:     fdc_close,
82:     NULL,                /* read */
83:     NULL,                /* write */
84:     fdc_ioctl,
85:     fdc_lseek,
86:     NULL,                /* readdir */
87:     NULL,                /* mmap */
88:     NULL,                /* select */
89:
90:     NULL,                /* readlink */
91:     NULL,                /* followlink */
92:     NULL,                /* bmap */
93:     NULL,                /* lockup */
94:     NULL,                /* rmdir */
95:     NULL,                /* link */
96:     NULL,                /* unlink */
97:     NULL,                /* symlink */
98:     NULL,                /* mkdir */
99:     NULL,                /* mknod */
100:    NULL,                /* truncate */
101:    NULL,                /* create */
102:    NULL,                /* rename */
103:
104:    fdc_read,
105:    fdc_write,
106:
107:    NULL,                /* read_inode */
108:    NULL,                /* write_inode */
109:    NULL,                /* ialloc */
110:    NULL,                /* ifree */
111:    NULL,                /* statfs */
112:    NULL,                /* read_superblock */
113:    NULL,                /* remount_fs */
114:    NULL,                /* write_superblock */
115:    NULL,                /* release_superblock */
116: };
117:
118: static struct device floppy_device = {
119:     "floppy",
120:     FLOPPY_IRQ,
121:     FDC_MAJOR,
122:     { 0, 0, 0, 0, 0, 0, 0, 0 },
123:     BLKSIZE_1K,
124:     &fdd_sizes,
125:     &fdc_driver_fsop,
126: };
127:
128: static int fdc_in(void)
129: {
130:     int n;
131:     unsigned char status;
132:
133:     if(need_reset) {
134:         return -1;

```

drivers/block/floppy.c

Page 3/14

```

135:         }
136:
137:         for(n = 0; n < 10000; n++) {
138:             status = inport_b(FDC_MSR) & (FDC_RQM | FDC_DIO);
139:             if(status == FDC_RQM) {
140:                 return 0;
141:             }
142:             if(status == (FDC_RQM | FDC_DIO)) {
143:                 return inport_b(FDC_DATA);
144:             }
145:         }
146:         need_reset = 1;
147:         printk("WARNING: %s(): fd%d: timeout on %s.\n", __FUNCTION__, current_fdd,
d, floppy_device.name);
148:         return -1;
149:     }
150:
151:     static void fdc_out(unsigned char value)
152:     {
153:         int n;
154:         unsigned char status;
155:
156:         if(need_reset) {
157:             return;
158:         }
159:
160:         for(n = 0; n < 10000; n++) {
161:             status = inport_b(FDC_MSR) & (FDC_RQM | FDC_DIO);
162:             if(status == FDC_RQM) {
163:                 outport_b(FDC_DATA, value);
164:                 return;
165:             }
166:         }
167:
168:         need_reset = 1;
169:         printk("WARNING: %s(): fd%d: unable to send byte 0x%x on %s.\n", __FUNCT
ION__, current_fdd, value, floppy_device.name);
170:     }
171:
172:     static void fdc_get_results(void)
173:     {
174:         int n;
175:
176:         memset_b(fdc_results, 0, sizeof(fdc_results));
177:         for(n = 0; n < MAX_FDC_RESULTS; n++) {
178:             fdc_results[n] = fdc_in();
179:         }
180:         return;
181:     }
182:
183:     static int fdc_motor_on(void)
184:     {
185:         struct callout_req creq;
186:         int errno;
187:
188:         if(fdd_status[current_fdd].motor) {
189:             return 0;
190:         }
191:
192:         /* select floppy disk drive and turn on its motor */
193:         outport_b(FDC_DOR, (FDC_DRIVE0 << current_fdd) | FDC_DMA_ENABLE | FDC_EN
ABLE | current_fdd);
194:         fdd_status[current_fdd].motor = 1;
195:         fdd_status[!current_fdd].motor = 0;
196:
197:         /* fixed spin-up time of 500ms for 3.5" and 5.25" */
198:         creq.fn = fdc_timer;

```


drivers/block/floppy.c

Page 4/14

```

199:         creq.arg = FDC_TR_MOTOR;
200:         add_callout(&creq, HZ / 2);
201:         sleep(&fdc_motor_on, PROC_UNINTERRUPTIBLE);
202:
203:         errno = 0;
204:
205:         /* check for a disk change */
206:         if(inport_b(FDC_DIR) & 0x80) {
207:             errno = 1;
208:         }
209:
210:         return errno;
211:     }
212:
213: static void do_motor_off(unsigned int fdd)
214: {
215:     outport_b(FDC_DOR, FDC_DMA_ENABLE | FDC_ENABLE | fdd);
216:     fdd_status[fdd].motor = 0;
217:     fdd_status[0].motor = fdd_status[1].motor = 0;
218: }
219:
220: static void fdc_motor_off(void)
221: {
222:     struct callout_req creq;
223:
224:     creq.fn = do_motor_off;
225:     creq.arg = current_fdd;
226:     add_callout(&creq, WAIT_FDC);
227: }
228:
229: static void fdc_reset(void)
230: {
231:     int n;
232:     struct callout_req creq;
233:
234:     need_reset = 0;
235:
236:     fdc_wait_interrupt = FDC_RESET;
237:     outport_b(FDC_DOR, 0); /* enter in reset mode */
238: /* outport_b(FDC_DOR, FDC_DMA_ENABLE); */
239:     for(n = 0; n < 1000; n++) { /* recovery time */
240:         NOP();
241:     }
242:     outport_b(FDC_DOR, FDC_DMA_ENABLE | FDC_ENABLE);
243:
244:     creq.fn = fdc_timer;
245:     creq.arg = FDC_TR_DEFAULT;
246:     add_callout(&creq, WAIT_FDC);
247:     sleep(&irq_floppy, PROC_UNINTERRUPTIBLE);
248:     if(fdc_timeout) {
249:         need_reset = 1;
250:         printk("WARNING: %s(): fd%d: timeout on %s.\n", __FUNCTION__, cu
rrrent_fdd, floppy_device.name);
251:     }
252:     del_callout(&creq);
253:
254:     fdd_status[0].motor = fdd_status[1].motor = 0;
255:     fdd_status[current_fdd].recalibrated = 0;
256:
257:     /* assumes drive polling mode is ON (by default) */
258:     for(n = 0; n < 4; n++) {
259:         fdc_out(FDC_SENSEI);
260:         fdc_get_results();
261:     }
262:
263:     /* keeps controller informed on the drive about to use */
264:     fdc_out(FDC_SPECIFY);

```

drivers/block/floppy.c

Page 5/14

```

265:         fdc_out(current_fdd_type->spec);
266:         fdc_out(current_fdd_type->hlt);
267:
268:         /* set data rate */
269:         outport_b(FDC_CCR, current_fdd_type->rate);
270:     }
271:
272:     static int fdc_recalibrate(void)
273:     {
274:         struct callout_req creq;
275:
276:         if(need_reset) {
277:             return 1;
278:         }
279:
280:         fdc_wait_interrupt = FDC_RECALIBRATE;
281:         fdc_motor_on();
282:         fdc_out(FDC_RECALIBRATE);
283:         fdc_out(current_fdd);
284:
285:         if(need_reset) {
286:             return 1;
287:         }
288:
289:         creq.fn = fdc_timer;
290:         creq.arg = FDC_TR_DEFAULT;
291:         add_callout(&creq, WAIT_FDC);
292:         sleep(&irq_floppy, PROC_UNINTERRUPTIBLE);
293:         if(fdc_timeout) {
294:             need_reset = 1;
295:             printk("WARNING: %s(): fd%d: timeout on %s.\n", __FUNCTION__, cu
rr
rent_fdd, floppy_device.name);
296:             return 1;
297:         }
298:
299:         del_callout(&creq);
300:         fdc_out(FDC_SENSEI);
301:         fdc_get_results();
302:
303:         /* PCN must be 0 indicating a successful position to track 0 */
304:         if((fdc_results[ST0] & (ST0_IC | ST0_SE | ST0_UC | ST0_NR)) != ST0_RECAL
IB
RATE || fdc_results[ST_PCN]) {
305:             need_reset = 1;
306:             printk("WARNING: %s(): fd%d: unable to recalibrate on %s.\n", __
FUN
CTION__, current_fdd, floppy_device.name);
307:             return 1;
308:         }
309:
310:         fdd_status[current_fdd].current_track = INVALID_TRACK;
311:         fdd_status[current_fdd].recalibrated = 1;
312:         fdc_motor_off();
313:         return 0;
314:     }
315:
316:     static int fdc_seek(int track, int head)
317:     {
318:         struct callout_req creq;
319:
320:         if(need_reset) {
321:             return 1;
322:         }
323:
324:         if(!fdd_status[current_fdd].recalibrated) {
325:             if(fdc_recalibrate()) {
326:                 return 1;
327:             }
328:         }

```

drivers/block/floppy.c

Page 6/14

```

329:
330:     if(fdd_status[current_fdd].current_track == track) {
331:         return 0;
332:     }
333:
334:     fdc_wait_interrupt = FDC_SEEK;
335:     fdc_motor_on();
336:     fdc_out(FDC_SEEK);
337:     fdc_out((head << 2) | current_fdd);
338:     fdc_out(track);
339:
340:     if(need_reset) {
341:         return 1;
342:     }
343:
344:     creq.fn = fdc_timer;
345:     creq.arg = FDC_TR_DEFAULT;
346:     add_callout(&creq, WAIT_FDC);
347:     sleep(&irq_floppy, PROC_UNINTERRUPTIBLE);
348:     if(fdc_timeout) {
349:         need_reset = 1;
350:         printk("WARNING: %s(): fd%d: timeout on %s.\n", __FUNCTION__, cu
rrrent_fdd, floppy_device.name);
351:         return 1;
352:     }
353:
354:     del_callout(&creq);
355:     fdc_out(FDC_SENSEI);
356:     fdc_get_results();
357:
358:     if((fdc_results[ST0] & (ST0_IC | ST0_SE | ST0_UC | ST0_NR)) != ST0_SEEK
|| fdc_results[ST_PCN] != track) {
359:         need_reset = 1;
360:         printk("WARNING: %s(): fd%d: unable to seek on %s.\n", __FUNCTIO
N__, current_fdd, floppy_device.name);
361:         return 1;
362:     }
363:
364:     fdc_motor_off();
365:     fdd_status[current_fdd].current_track = track;
366:     return 0;
367: }
368:
369: static int fdc_get_chip(void)
370: {
371:     unsigned char version, fifo, id;
372:
373:     fdc_out(FDC_VERSION);
374:     version = fdc_in();
375:     fdc_out(FDC_LOCK);
376:     fifo = fdc_in();
377:     fdc_out(FDC_PARTID);
378:     id = fdc_in();
379:
380:     if(version == 0x80) {
381:         if(fifo == 0x80) {
382:             printk("(NEC D765/Intel 8272A/compatible)\n");
383:             return 0;
384:         }
385:         if(fifo == 0) {
386:             printk("(Intel 82072)\n");
387:             return 0;
388:         }
389:     }
390:
391:     if(version == 0x81) {
392:         printk("(Very Early Intel 82077/compatible)\n");

```

drivers/block/floppy.c

Page 7/14

```

393:         return 0;
394:     }
395:
396:     if(version == 0x90) {
397:         if(fifo == 0x80) {
398:             printk("(Old Intel 82077, no FIFO)\n");
399:             return 0;
400:         }
401:         if(fifo == 0) {
402:             if(id == 0x80) {
403:                 printk("(New Intel 82077)\n");
404:                 return 0;
405:             }
406:             if(id == 0x41) {
407:                 printk("(Intel 82078)\n");
408:                 return 0;
409:             }
410:             if(id == 0x73) {
411:                 printk("(National Semiconductor PC87306)\n");
412:                 return 0;
413:             }
414:             printk("(Intel 82078 compatible)\n");
415:             return 0;
416:         }
417:         printk("(NEC 72065B)\n");
418:         return 0;
419:     }
420:
421:     if(version == 0xA0) {
422:         printk("(SMC FDC37c65C+)\n");
423:         return 0;
424:     }
425:     printk("(unknown controller chip)\n");
426:     return 1;
427: }
428:
429: static int fdc_block2chs(__blk_t block, int blksize, int *cyl, int *head, int *sector)
430: {
431:     int spb = blksize / FDC_SECTSIZE;
432:
433:     *cyl = (block * spb) / (current_fdd_type->spt * current_fdd_type->heads);
434:
435:     *head = ((block * spb) % (current_fdd_type->spt * current_fdd_type->heads)) / current_fdd_type->spt;
436:
437:     *sector = (((block * spb) % (current_fdd_type->spt * current_fdd_type->heads)) % current_fdd_type->spt) + 1;
438:
439:     if(*cyl >= current_fdd_type->tracks || *head >= current_fdd_type->heads || *sector > current_fdd_type->spt) {
440:         return 1;
441:     }
442:     return 0;
443: }
444: static void set_current_fdd_type(int minor)
445: {
446:     current_fdd = minor & 1;
447:
448:     /* minors 0 and 1 are directly assigned */
449:     if(minor < 2) {
450:         current_fdd_type = &fdd_type[(int)fdd_status[current_fdd].type];
451:     } else {
452:         current_fdd_type = &fdd_type[minor >> DEV_TYPE_SHIFT];
453:     }
454: }

```

drivers/block/floppy.c

Page 8/14

```

455:
456: void irq_floppy(void)
457: {
458:     if(!fdc_wait_interrupt) {
459:         printk("WARNING: %s(): fd%d: unexpected interrupt on %s.\n", __F
UNCTION__, current_fdd, floppy_device.name);
460:         need_reset = 1;
461:     } else {
462:         fdc_timeout = fdc_wait_interrupt = 0;
463:         wakeup(&irq_floppy);
464:     }
465: }
466:
467: void fdc_timer(unsigned int reason)
468: {
469:     switch(reason) {
470:         case FDC_TR_DEFAULT:
471:             fdc_timeout = 1;
472:             fdc_wait_interrupt = 0;
473:             wakeup(&irq_floppy);
474:             break;
475:         case FDC_TR_MOTOR:
476:             wakeup(&fdc_motor_on);
477:             break;
478:     }
479: }
480:
481: int fdc_open(struct inode *i, struct fd *fd_table)
482: {
483:     unsigned char minor;
484:
485:     minor = MINOR(i->rdev);
486:     if(!TEST_MINOR(floppy_device.minors, minor)) {
487:         return -ENXIO;
488:     }
489:
490:     lock_resource(&floppy_resource);
491:     set_current_fdd_type(minor);
492:     unlock_resource(&floppy_resource);
493:
494:     return 0;
495: }
496:
497: int fdc_close(struct inode *i, struct fd *fd_table)
498: {
499:     unsigned char minor;
500:
501:     minor = MINOR(i->rdev);
502:     if(!TEST_MINOR(floppy_device.minors, minor)) {
503:         return -ENXIO;
504:     }
505:
506:     lock_resource(&floppy_resource);
507:     set_current_fdd_type(minor);
508:     unlock_resource(&floppy_resource);
509:
510:     return 0;
511: }
512:
513: int fdc_read(__dev_t dev, __blk_t block, char *buffer, int blksize)
514: {
515:     unsigned char minor;
516:     unsigned int sectors_read;
517:     int cyl, head, sector;
518:     int retries;
519:     struct callout_req creq;
520:     struct device *d;

```

drivers/block/floppy.c

Page 9/14

```

521:
522:     minor = MINOR(dev);
523:     if(!TEST_MINOR(floppy_device.minors, minor)) {
524:         return -ENXIO;
525:     }
526:
527:     if(!blksize) {
528:         if(!(d = get_device(BLK_DEV, MAJOR(dev)))) {
529:             return -EINVAL;
530:         }
531:         blksize = d->blksize;
532:     }
533:     blksize = blksize ? blksize : BLKSIZE_1K;
534:
535:     lock_resource(&floppy_resource);
536:     set_current_fdd_type(minor);
537:
538:     if(fdc_block2chs(block, blksize, &cyl, &head, &sector)) {
539:         printk("WARNING: %s(): fd%d: invalid block number %d on %s device
e %d,%d.\n", __FUNCTION__, current_fdd, block, floppy_device.name, MAJOR(dev), MINOR(de
v));
540:         unlock_resource(&floppy_resource);
541:         return -EINVAL;
542:     }
543:
544:     for(retries = 0; retries < MAX_FDC_ERR; retries++) {
545:         if(need_reset) {
546:             fdc_reset();
547:         }
548:         if(fdc_motor_on()) {
549:             printk("%s(): %s disk was changed in device %d,%d!\n", _
__FUNCTION__, floppy_device.name, MAJOR(dev), MINOR(dev));
550:             invalidate_buffers(dev);
551:             fdd_status[current_fdd].recalibrated = 0;
552:         }
553:
554:         if(fdc_seek(cyl, head)) {
555:             printk("WARNING: %s(): fd%d: seek error on %s device %d,
%d during read operation.\n", __FUNCTION__, current_fdd, floppy_device.name, MAJOR(dev)
, MINOR(dev));
556:             continue;
557:         }
558:
559:         start_dma(FLOPPY_DMA, _fdc_transfer_area, blksize, DMA_MODE_WRIT
E | DMA_MODE_SINGLE);
560:
561:         /* send READ command */
562:         fdc_wait_interrupt = FDC_READ;
563:         fdc_out(FDC_READ);
564:         fdc_out((head << 2) | current_fdd);
565:         fdc_out(cyl);
566:         fdc_out(head);
567:         fdc_out(sector);
568:         fdc_out(2); /* sector size is 512 bytes */
569:         fdc_out(current_fdd_type->spt);
570:         fdc_out(current_fdd_type->gpl1);
571:         fdc_out(0xFF); /* sector size is 512 bytes */
572:
573:         if(need_reset) {
574:             printk("WARNING: %s(): fd%d: needs reset on %s device %d
,%d during read operation.\n", __FUNCTION__, current_fdd, floppy_device.name, MAJOR(dev)
), MINOR(dev));
575:             continue;
576:         }
577:         creq.fn = fdc_timer;
578:         creq.arg = FDC_TR_DEFAULT;
579:         add_callout(&creq, WAIT_FDC);

```

drivers/block/floppy.c

Page 10/14

```

580:         sleep(&irq_floppy, PROC_UNINTERRUPTIBLE);
581:         if(fdc_timeout) {
582:             need_reset = 1;
583:             printk("WARNING: %s(): fd%d: timeout on %s device %d,%d.
\n", __FUNCTION__, current_fdd, floppy_device.name, MAJOR(dev), MINOR(dev));
584:             continue;
585:         }
586:         del_callout(&creq);
587:         fdc_get_results();
588:         if(fdc_results[ST0] & (ST0_IC | ST0_UC | ST0_NR)) {
589:             need_reset = 1;
590:             continue;
591:         }
592:         break;
593:     }
594:
595:     if(retries >= MAX_FDC_ERR) {
596:         printk("WARNING: %s(): fd%d: error on %s device %d,%d during rea
d operation,\n", __FUNCTION__, current_fdd, floppy_device.name, MAJOR(dev), MINOR(dev))
;
597:         printk("\tblock=%d, sector=%d, cylinder/head=%d/%d\n", block, se
ctor, cyl, head);
598:         unlock_resource(&floppy_resource);
599:         fdc_motor_off();
600:         return -EIO;
601:     }
602:
603:     fdc_motor_off();
604:     sectors_read = (fdc_results[ST_CYL] - cyl) * (current_fdd_type->heads *
current_fdd_type->spt);
605:     sectors_read += (fdc_results[ST_HEAD] - head) * current_fdd_type->spt;
606:     sectors_read += fdc_results[ST_SECTOR] - sector;
607:     if(sectors_read * BPS != blksize) {
608:         printk("WARNING: %s(): fd%d: read error on %s device %d,%d (%d s
ectors read).\n", __FUNCTION__, current_fdd, floppy_device.name, MAJOR(dev), MINOR(dev)
, sectors_read);
609:         printk("\tblock=%d, sector=%d, cylinder/head=%d/%d\n", block, se
ctor, cyl, head);
610:         unlock_resource(&floppy_resource);
611:         fdc_motor_off();
612:         return -EIO;
613:     }
614:
615:     memcpy_b(buffer, (void *)_fdc_transfer_area, blksize);
616:
617:     unlock_resource(&floppy_resource);
618:     return sectors_read * BPS;
619: }
620:
621: int fdc_write(__dev_t dev, __blk_t block, char *buffer, int blksize)
622: {
623:     unsigned char minor;
624:     unsigned int sectors_written;
625:     int cyl, head, sector;
626:     int retries;
627:     struct callout_req creq;
628:     struct device *d;
629:
630:     minor = MINOR(dev);
631:     if(!TEST_MINOR(floppy_device.minors, minor)) {
632:         return -ENXIO;
633:     }
634:
635:     if(!blksize) {
636:         if(!(d = get_device(BLK_DEV, MAJOR(dev)))) {
637:             return -EINVAL;
638:         }

```

drivers/block/floppy.c

Page 11/14

```

639:             blksize = d->blksize;
640:         }
641:         blksize = blksize ? blksize : BLKSIZE_1K;
642:
643:         lock_resource(&floppy_resource);
644:         set_current_fdd_type(minor);
645:
646:         if(fdc_block2chs(block, blksize, &cyl, &head, &sector)) {
647:             printk("WARNING: %s(): fd%d: invalid block number %d on %s device
e %d,%d.\n", __FUNCTION__, current_fdd, block, floppy_device.name, MAJOR(dev), MINOR(de
v));
648:             unlock_resource(&floppy_resource);
649:             return -EINVAL;
650:         }
651:
652:         for(retries = 0; retries < MAX_FDC_ERR; retries++) {
653:             if(need_reset) {
654:                 fdc_reset();
655:             }
656:             if(fdc_motor_on()) {
657:                 printk("%s(): %s disk was changed in device %d,%d!\n", _
_FUNCTION__, floppy_device.name, MAJOR(dev), MINOR(dev));
658:                 invalidate_buffers(dev);
659:                 fdd_status[current_fdd].recalibrated = 0;
660:             }
661:
662:             if(fdc_seek(cyl, head)) {
663:                 printk("WARNING: %s(): fd%d: seek error on %s device %d,
%d during write operation.\n", __FUNCTION__, current_fdd, floppy_device.name, MAJOR(dev
), MINOR(dev));
664:                 continue;
665:             }
666:
667:             start_dma(FLOPPY_DMA, _fdc_transfer_area, blksize, DMA_MODE_READ
| DMA_MODE_SINGLE);
668:             memcpy_b((void *)_fdc_transfer_area, buffer, blksize);
669:
670:             /* send WRITE command */
671:             fdc_wait_interrupt = FDC_WRITE;
672:             fdc_out(FDC_WRITE);
673:             fdc_out((head << 2) | current_fdd);
674:             fdc_out(cyl);
675:             fdc_out(head);
676:             fdc_out(sector);
677:             fdc_out(2); /* sector size is 512 bytes */
678:             fdc_out(current_fdd_type->spt);
679:             fdc_out(current_fdd_type->gpl1);
680:             fdc_out(0xFF); /* sector size is 512 bytes */
681:
682:             if(need_reset) {
683:                 printk("WARNING: %s(): fd%d: needs reset on %s device %d
,%d during write operation.\n", __FUNCTION__, current_fdd, floppy_device.name, MAJOR(de
v), MINOR(dev));
684:                 continue;
685:             }
686:             creq.fn = fdc_timer;
687:             creq.arg = FDC_TR_DEFAULT;
688:             add_callout(&creq, WAIT_FDC);
689:             sleep(&irq_floppy, PROC_UNINTERRUPTIBLE);
690:             if(fdc_timeout) {
691:                 need_reset = 1;
692:                 printk("WARNING: %s(): fd%d: timeout on %s device %d,%d.
\n", __FUNCTION__, current_fdd, floppy_device.name, MAJOR(dev), MINOR(dev));
693:                 continue;
694:             }
695:             del_callout(&creq);
696:             fdc_get_results();

```


drivers/block/floppy.c

Page 12/14

```

697:             if(fdc_results[ST1] & ST1_NW) {
698:                 unlock_resource(&floppy_resource);
699:                 fdc_motor_off();
700:                 return -EROFS;
701:             }
702:             if(fdc_results[ST0] & (ST0_IC | ST0_UC | ST0_NR)) {
703:                 need_reset = 1;
704:                 continue;
705:             }
706:             break;
707:         }
708:
709:         if(retries >= MAX_FDC_ERR) {
710:             printk("WARNING: %s(): fd%d: error on %s device %d,%d during write
te operation,\n", __FUNCTION__, current_fdd, floppy_device.name, MAJOR(dev), MINOR(dev)
);
711:             printk("\tblock=%d, sector=%d, cylinder/head=%d/%d\n", block, se
ctor, cyl, head);
712:             unlock_resource(&floppy_resource);
713:             fdc_motor_off();
714:             return -EIO;
715:         }
716:
717:         fdc_motor_off();
718:         sectors_written = (fdc_results[ST_CYL] - cyl) * (current_fdd_type->heads
* current_fdd_type->spt);
719:         sectors_written += (fdc_results[ST_HEAD] - head) * current_fdd_type->spt
;
720:         sectors_written += fdc_results[ST_SECTOR] - sector;
721:         if(sectors_written * BPS != blksize) {
722:             printk("WARNING: %s(): fd%d: write error on %s device %d,%d (%d
sectors written).\n", __FUNCTION__, current_fdd, floppy_device.name, MAJOR(dev), MINOR(
dev), sectors_written);
723:             printk("\tblock=%d, sector=%d, cylinder/head=%d/%d\n", block, se
ctor, cyl, head);
724:             unlock_resource(&floppy_resource);
725:             fdc_motor_off();
726:             return -EIO;
727:         }
728:
729:         unlock_resource(&floppy_resource);
730:         return sectors_written * BPS;
731:     }
732:
733: int fdc_ioctl(struct inode *i, int cmd, unsigned long int arg)
734: {
735:     unsigned char minor;
736:     struct hd_geometry *geom;
737:     int errno;
738:
739:     minor = MINOR(i->rdev);
740:     if(!TEST_MINOR(floppy_device.minors, minor)) {
741:         return -ENXIO;
742:     }
743:
744:     lock_resource(&floppy_resource);
745:     set_current_fdd_type(minor);
746:     unlock_resource(&floppy_resource);
747:
748:     switch(cmd) {
749:         case HDIO_GETGEO:
750:             if((errno = check_user_area(VERIFY_WRITE, (void *)arg, s
izeof(struct hd_geometry)))) {
751:                 return errno;
752:             }
753:             geom = (struct hd_geometry *)arg;
754:             geom->heads = current_fdd_type->heads;

```

drivers/block/floppy.c

Page 13/14

```

755:             geom->sectors = current_fdd_type->spt;
756:             geom->cylinders = current_fdd_type->tracks;
757:             geom->start = 0;
758:             break;
759:         case BLKRRPART:
760:             break;
761:         case BLKGETSIZE:
762:             if((errno = check_user_area(VERIFY_WRITE, (void *)arg, s
sizeof(unsigned int)))) {
763:                 return errno;
764:             }
765:             *(int *)arg = fdd_sizes[MINOR(i->rdev)] * 2;
766:             break;
767:         default:
768:             return -EINVAL;
769:     }
770:     return 0;
771: }
772:
773: int fdc_lseek(struct inode *i, __off_t offset)
774: {
775:     unsigned char minor;
776:
777:     minor = MINOR(i->rdev);
778:     if(!TEST_MINOR(floppy_device.minors, minor)) {
779:         return -ENXIO;
780:     }
781:
782:     lock_resource(&floppy_resource);
783:     set_current_fdd_type(minor);
784:     unlock_resource(&floppy_resource);
785:
786:     return offset;
787: }
788:
789: void floppy_init(void)
790: {
791:     short int cmosval, master, slave;
792:
793:     cmosval = cmos_read(CMOS_FDDTYPE);
794:     set_current_fdd_type(0);          /* sets /dev/fd0 by default */
795:
796:     /* the high nibble describes the 'master' floppy drive */
797:     master = cmosval >> 4;
798:     if(master) {
799:         if(!register_irq(FLOPPY_IRQ, floppy_device.name, irq_floppy)) {
800:             enable_irq(FLOPPY_IRQ);
801:         }
802:         printk("fd0          0x%04X-0x%04X  %2d    ", FDC_SRA, FDC_CCR, FL
OPPY_IRQ);
803:         printk("%s ", fdd_type[master].name);
804:         fdd_status[0].type = fdd_status[1].type = master;
805:         SET_MINOR(floppy_device.minors, 0);
806:         SET_MINOR(floppy_device.minors, 4);
807:         SET_MINOR(floppy_device.minors, 8);
808:         SET_MINOR(floppy_device.minors, 12);
809:         SET_MINOR(floppy_device.minors, 16);
810:         fdd_sizes[0] = fdd_type[master].sizekb;
811:         fdd_sizes[4] = fdd_type[1].sizekb;
812:         fdd_sizes[8] = fdd_type[2].sizekb;
813:         fdd_sizes[12] = fdd_type[3].sizekb;
814:         fdd_sizes[16] = fdd_type[4].sizekb;
815:         fdc_reset();
816:         fdc_get_chip();
817:     }
818:
819:     /* the low nibble is for the 'slave' floppy drive */

```

drivers/block/floppy.c

Page 14/14

```

820:         slave = cmosval & 0x0F;
821:         if(slave) {
822:             if(!master) {
823:                 if(!register_irq(FLOPPY_IRQ, floppy_device.name, irq_flo
pppy)) {
824:                     enable_irq(FLOPPY_IRQ);
825:                 }
826:             }
827:             printk("fd1      0x%04X-0x%04X   %2d      ", FDC_SRA, FDC_CCR, FL
OPPY_IRQ);
828:             printk("%s ", fdd_type[slave].name);
829:             fdd_status[1].type = slave;
830:             SET_MINOR(floppy_device.minors, 1);
831:             SET_MINOR(floppy_device.minors, 5);
832:             SET_MINOR(floppy_device.minors, 9);
833:             SET_MINOR(floppy_device.minors, 13);
834:             SET_MINOR(floppy_device.minors, 17);
835:             fdd_sizes[1] = fdd_type[slave].sizekb;
836:             fdd_sizes[5] = fdd_type[1].sizekb;
837:             fdd_sizes[9] = fdd_type[2].sizekb;
838:             fdd_sizes[13] = fdd_type[3].sizekb;
839:             fdd_sizes[17] = fdd_type[4].sizekb;
840:             if(!master) {
841:                 fdc_get_chip();
842:             } else {
843:                 printk("\n");
844:             }
845:         }
846:
847:         if(master || slave) {
848:             need_reset = 1;
849:             dma_init();
850:             if(dma_register(FLOPPY_DMA, floppy_device.name)) {
851:                 printk("WARNING: %s(): fd%d: unable to register DMA chan
nel on %s.\n", __FUNCTION__, current_fdd, floppy_device.name);
852:             } else {
853:                 if(!register_device(BLK_DEV, &floppy_device)) {
854:                     do_motor_off(current_fdd);
855:                 }
856:             }
857:         }
858:     }

```

drivers/block/ide.c

Page 1/14

```

1: /*
2:  * fiwix/drivers/block/ide.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/ide.h>
10: #include <fiwix/ide_hd.h>
11: #include <fiwix/ide_cd.h>
12: #include <fiwix/devices.h>
13: #include <fiwix/sleep.h>
14: #include <fiwix/timer.h>
15: #include <fiwix/sched.h>
16: #include <fiwix/cpu.h>
17: #include <fiwix/pic.h>
18: #include <fiwix/fs.h>
19: #include <fiwix/mm.h>
20: #include <fiwix/errno.h>
21: #include <fiwix/stdio.h>
22: #include <fiwix/string.h>
23:
24: int ide0_need_reset = 0;
25: int ide0_wait_interrupt = 0;
26: int ide0_timeout = 0;
27: int idel_need_reset = 0;
28: int idel_wait_interrupt = 0;
29: int idel_timeout = 0;
30:
31: struct ide ide_table[NR_IDE_CTRL] = {
32:     { IDE_PRIMARY, IDE0_BASE, IDE0_CTRL, IDE0_IRQ,
33:       {
34:         { IDE_MASTER, "hda", IDE0_MAJOR, 0, -1, NULL, NULL, NULL
, NULL, NULL, { NULL }, {{ NULL }} },
35:         { IDE_SLAVE, "hdb", IDE0_MAJOR, 0, -1, NULL, NULL, NULL,
NULL, NULL, { NULL }, {{ NULL }} }
36:       }
37:     },
38:     { IDE_SECONDARY, IDE1_BASE, IDE1_CTRL, IDE1_IRQ,
39:       {
40:         { IDE_MASTER, "hdc", IDE1_MAJOR, 0, -1, NULL, NULL, NULL
, NULL, NULL, { NULL }, {{ NULL }} },
41:         { IDE_SLAVE, "hdd", IDE1_MAJOR, 0, -1, NULL, NULL, NULL,
NULL, NULL, { NULL }, {{ NULL }} }
42:       }
43:     }
44: };
45:
46: static char *ide_ctrl_name[] = { "primary", "secondary" };
47: static char *ide_drv_name[] = { "master", "slave" };
48:
49: static unsigned int ide0_sizes[256];
50: static unsigned int idel_sizes[256];
51:
52: static struct fs_operations ide_driver_fsop = {
53:     0,
54:     0,
55:
56:     ide_open,
57:     ide_close,
58:     NULL, /* read */
59:     NULL, /* write */
60:     ide_ioctl,
61:     NULL, /* lseek */
62:     NULL, /* readdir */
63:     NULL, /* mmap */

```

drivers/block/ide.c

Page 2/14

```

64:         NULL,                /* select */
65:
66:         NULL,                /* readlink */
67:         NULL,                /* followlink */
68:         NULL,                /* bmap */
69:         NULL,                /* lockup */
70:         NULL,                /* rmdir */
71:         NULL,                /* link */
72:         NULL,                /* unlink */
73:         NULL,                /* symlink */
74:         NULL,                /* mkdir */
75:         NULL,                /* mknod */
76:         NULL,                /* truncate */
77:         NULL,                /* create */
78:         NULL,                /* rename */
79:
80:         ide_read,
81:         ide_write,
82:
83:         NULL,                /* read_inode */
84:         NULL,                /* write_inode */
85:         NULL,                /* ialloc */
86:         NULL,                /* ifree */
87:         NULL,                /* statfs */
88:         NULL,                /* read_superblock */
89:         NULL,                /* remount_fs */
90:         NULL,                /* write_superblock */
91:         NULL,                /* release_superblock */
92: };
93:
94: static struct device ide0_device = {
95:     "ide0",
96:     IDE0_IRQ,
97:     IDE0_MAJOR,
98:     { 0, 0, 0, 0, 0, 0, 0, 0, 0 },
99:     0,
100:    &ide0_sizes,
101:    &ide_driver_fsop,
102: };
103:
104: static struct device idel_device = {
105:     "idel",
106:     IDE1_IRQ,
107:     IDE1_MAJOR,
108:     { 0, 0, 0, 0, 0, 0, 0, 0, 0 },
109:     0,
110:    &idel_sizes,
111:    &ide_driver_fsop,
112: };
113:
114: static int ide_identify(struct ide *ide, int drive)
115: {
116:     short int status, *buffer;
117:     struct callout_req creq;
118:
119:     if((status = ide_drvsel(ide, drive, IDE_CHS_MODE, 0)) {
120:         /* some controllers return 0xFF to indicate a non-drive conditio
n */
121:         if(status == 0xFF) {
122:             return status;
123:         }
124:         printk("WARNING: %s(): error on device '%s'.\n", __FUNCTION__, i
de->drive[drive].dev_name);
125:         ide_error(ide, status);
126:         return status;
127:     }
128:

```

drivers/block/ide.c

Page 3/14

```

129:         outport_b(ide->base + IDE_COMMAND, (ide->drive[drive].flags & DEVICE_IS_
ATAPI) ? ATA_IDENTIFY_PACKET : ATA_IDENTIFY);
130:         if(ide->channel == IDE_PRIMARY) {
131:             ide0_wait_interrupt = ide->base;
132:             creq.fn = ide0_timer;
133:             creq.arg = 0;
134:             add_callout(&creq, WAIT_FOR_IDE);
135:             sleep(&irq_ide0, PROC_UNINTERRUPTIBLE);
136:             if(ide0_timeout) {
137:                 status = inport_b(ide->base + IDE_STATUS);
138:                 if((status & (IDE_STAT_RDY | IDE_STAT_DRQ)) != (IDE_STAT
_RDY | IDE_STAT_DRQ)) {
139:                     return 1;
140:                 }
141:             }
142:             del_callout(&creq);
143:         }
144:         if(ide->channel == IDE_SECONDARY) {
145:             idel_wait_interrupt = ide->base;
146:             creq.fn = idel_timer;
147:             creq.arg = 0;
148:             add_callout(&creq, WAIT_FOR_IDE);
149:             sleep(&irq_idel, PROC_UNINTERRUPTIBLE);
150:             if(idel_timeout) {
151:                 status = inport_b(ide->base + IDE_STATUS);
152:                 if((status & (IDE_STAT_RDY | IDE_STAT_DRQ)) != (IDE_STAT
_RDY | IDE_STAT_DRQ)) {
153:                     return 1;
154:                 }
155:             }
156:             del_callout(&creq);
157:         }
158:
159:         status = inport_b(ide->base + IDE_STATUS);
160:         if((status & (IDE_STAT_RDY | IDE_STAT_DRQ)) != (IDE_STAT_RDY | IDE_STAT_
DRQ)) {
161:             return 1;
162:         }
163:
164:         if(!(buffer = (void *)kmalloc())) {
165:             return 1;
166:         }
167:
168:         inport_sw(ide->base + IDE_DATA, (void *)buffer, IDE_HD_SECTSIZE / sizeof
(short int));
169:         memcpy_b(&ide->drive[drive].ident, (void *)buffer, sizeof(struct ide_drv
_ident));
170:         kfree((unsigned int)buffer);
171:
172:         if(ide->drive[drive].ident.gen_config == IDE_SUPPORTS_CFA) {
173:             ide->drive[drive].flags |= DEVICE_IS_CFA;
174:         }
175:
176:         if(ide->drive[drive].flags & DEVICE_IS_ATAPI) {
177:             if(((ide->drive[drive].ident.gen_config >> 8) & 0x1F) == ATAPI_I
S_CDROM) {
178:                 ide->drive[drive].flags |= DEVICE_IS_CDROM;
179:             }
180:             if(ide->drive[drive].ident.gen_config & 0x3) {
181:                 printk("WARNING: %s(): packet size must be 16 bytes!\n")
;
182:             }
183:         }
184:
185:         /* only bits 0-7 are relevant */
186:         ide->drive[drive].ident.rw_multiple &= 0xFF;
187:         return 0;

```

drivers/block/ide.c

Page 4/14

```

188: }
189:
190: static void get_device_size(struct ide_drv *drive)
191: {
192:     if(drive->ident.capabilities & IDE_HAS_LBA) {
193:         drive->lba_cyls = drive->ident.logic_cyls;
194:         drive->lba_heads = drive->ident.logic_heads;
195:         drive->lba_factor = 0;
196:
197:         while(drive->lba_cyls > 1023) {
198:             if(drive->lba_heads < 255) {
199:                 drive->lba_cyls >>= 1;
200:                 drive->lba_heads <<= 1;
201:             } else {
202:                 break;
203:             }
204:             drive->lba_factor++;
205:         }
206:         drive->nr_sects = drive->ident.tot_sectors | (drive->ident.tot_s
ectors2 << 16);
207:     }
208:
209:     /* some old disk drives (ATA or ATA2) don't specify total sectors */
210:     if(!(drive->ident.capabilities & IDE_HAS_LBA)) {
211:         if(drive->nr_sects == 0) {
212:             drive->nr_sects = drive->ident.logic_cyls * drive->ident
.logic_heads * drive->ident.logic_spt;
213:         }
214:     }
215:
216: }
217:
218: static int get_udma(struct ide *ide, int drive)
219: {
220:     int udma;
221:
222:     if(ide->drive[drive].ident.fields_validity & IDE_HAS_UDMA) {
223:         if((ide->drive[drive].ident.ultradma >> 13) & 1) {
224:             udma = 5;
225:         } else if((ide->drive[drive].ident.ultradma >> 12) & 1) {
226:             udma = 4;
227:         } else if((ide->drive[drive].ident.ultradma >> 11) & 1) {
228:             udma = 3;
229:         } else if((ide->drive[drive].ident.ultradma >> 10) & 1) {
230:             udma = 2;
231:         } else if((ide->drive[drive].ident.ultradma >> 9) & 1) {
232:             udma = 1;
233:         } else {
234:             udma = 0;
235:         }
236:     } else {
237:         udma = -1;
238:     }
239:     return udma;
240: }
241:
242: static void ide_results(struct ide *ide, int drive)
243: {
244:     unsigned int cyl, hds, sect;
245:     __loff_t capacity;
246:     int udma;
247:     int udma_speed[] = { 16, 25, 33, 44, 66, 100 };
248:
249:     cyl = ide->drive[drive].ident.logic_cyls;
250:     hds = ide->drive[drive].ident.logic_heads;
251:     sect = ide->drive[drive].ident.logic_spt;
252:

```

drivers/block/ide.c

Page 5/14

```

253:         udma = get_udma(ide, drive);
254:         /*
255:          * After knowing if the device is UDMA capable we could choose between
256:          * the PIO transfer mode or the UDMA transfer mode.
257:          * FIXME: Currently only PIO mode is supported.
258:          */
259:
260:         capacity = (__loff_t)ide->drive[drive].nr_sects * BPS;
261:         capacity = capacity / 1024 / 1024;
262:
263:         printk("%s          0x%04X-0x%04X   %2d   ", ide->drive[drive].dev_name, i
de->base, ide->base + IDE_BASE_LEN, ide->irq);
264:         swap_asc_word(ide->drive[drive].ident.model_number, 40);
265:         printk("%s %s ", ide_ctrl_name[ide->channel], ide_drv_name[ide->drive[dr
ive].drive]);
266:
267:         if(!(ide->drive[drive].flags & DEVICE_IS_ATAPI)) {
268:             printk("ATA");
269:         } else {
270:             printk("ATAPI");
271:         }
272:
273:         if(ide->drive[drive].flags & DEVICE_IS_CFA) {
274:             printk(" CFA");
275:         }
276:
277:         if(ide->drive[drive].flags & DEVICE_IS_DISK) {
278:             printk(" DISK drive %dMB\n", (unsigned int)capacity);
279:             printk("
drive].ident.model_number);
280:             if(ide->drive[drive].nr_sects < IDE_MIN_LBA) {
281:                 printk("
yl, hds, sect);
282:             } else {
283:                 ide->drive[drive].flags |= DEVICE_REQUIRES_LBA;
284:                 printk("
->drive[drive].nr_sects);
285:             }
286:             printk(" cache=%dKB", ide->drive[drive].ident.buffer_cache >> 1)
;
287:         }
288:
289:         if(ide->drive[drive].flags & DEVICE_IS_CDROM) {
290:             printk(" CDROM drive\n");
291:             printk("
drive].ident.model_number);
292:             printk("
drive].ident.buffer_cache >> 1);
293:         }
294:
295:         if(udma >= 0) {
296:             printk(" UDMA%d(%d)", udma, udma_speed[udma]);
297:         }
298:         if(ide->drive[drive].ident.capabilities & IDE_HAS_LBA) {
299:             ide->drive[drive].flags |= DEVICE_REQUIRES_LBA;
300:             printk(" LBA");
301:         }
302:
303:         printk("\n");
304:
305:         if(ide->drive[drive].ident.rw_multiple > 1) {
306:             ide->drive[drive].flags |= DEVICE_HAS_RW_MULTIPLE;
307:         }
308:
309:         /*
310:         printk("\n");
311:         printk("%s -> %s\n", ide->drive[drive].dev_name, ide->drive[drive].flags

```


drivers/block/ide.c

Page 6/14

```

& DEVICE_IS_ATAPI ? "ATAPI" : "ATA");
312:     printk("general conf = %d (%b) (0x%x)\n", ide->drive[drive].ident.gen_c
onfig, ide->drive[drive].ident.gen_config, ide->drive[drive].ident.gen_config);
313:     printk("logic_cyls   = %d (%b)\n", ide->drive[drive].ident.logic_cyls,
ide->drive[drive].ident.logic_cyls);
314:     printk("reserved2    = %d (%b)\n", ide->drive[drive].ident.reserved2, i
de->drive[drive].ident.reserved2);
315:     printk("logic_heads  = %d (%b)\n", ide->drive[drive].ident.logic_heads,
ide->drive[drive].ident.logic_heads);
316:     printk("retired4     = %d (%b)\n", ide->drive[drive].ident.retired4, id
e->drive[drive].ident.retired4);
317:     printk("retired5     = %d (%b)\n", ide->drive[drive].ident.retired5, id
e->drive[drive].ident.retired5);
318:     printk("logic_spt    = %d (%b)\n", ide->drive[drive].ident.logic_spt, i
de->drive[drive].ident.logic_spt);
319:     printk("retired7     = %d (%b)\n", ide->drive[drive].ident.retired7, id
e->drive[drive].ident.retired7);
320:     printk("retired8     = %d (%b)\n", ide->drive[drive].ident.retired8, id
e->drive[drive].ident.retired8);
321:     printk("retired9     = %d (%b)\n", ide->drive[drive].ident.retired9, id
e->drive[drive].ident.retired9);
322:     printk("serial number = '%s'\n", ide->drive[drive].ident.serial_number);
323:     printk("vendor spec20 = %d (%b)\n", ide->drive[drive].ident.vendor_spec2
0, ide->drive[drive].ident.vendor_spec20);
324:     printk("buffer cache  = %d (%b)\n", ide->drive[drive].ident.buffer_cache
, ide->drive[drive].ident.buffer_cache);
325:     printk("vendor spec22 = %d (%b)\n", ide->drive[drive].ident.vendor_spec2
2, ide->drive[drive].ident.vendor_spec22);
326:     printk("firmware rev  = '%s'\n", ide->drive[drive].ident.firmware_rev);
327:     printk("model number  = '%s'\n", ide->drive[drive].ident.model_number);
328:     printk("rw multiple   = %d (%b)\n", ide->drive[drive].ident.rw_multiple,
ide->drive[drive].ident.rw_multiple);
329:     printk("reserved48    = %d (%b)\n", ide->drive[drive].ident.reserved48,
ide->drive[drive].ident.reserved48);
330:     printk("capabilities  = %d (%b)\n", ide->drive[drive].ident.capabilities
, ide->drive[drive].ident.capabilities);
331:     printk("reserved50    = %d (%b)\n", ide->drive[drive].ident.reserved50,
ide->drive[drive].ident.reserved50);
332:     printk("pio mode      = %d (%b)\n", ide->drive[drive].ident.pio_mode, id
e->drive[drive].ident.pio_mode);
333:     printk("dma mode      = %d (%b)\n", ide->drive[drive].ident.dma_mode, id
e->drive[drive].ident.dma_mode);
334:     printk("fields validi = %d (%b)\n", ide->drive[drive].ident.fields_valid
ity, ide->drive[drive].ident.fields_validity);
335:     printk("cur log cyls  = %d (%b)\n", ide->drive[drive].ident.cur_log_cyls
, ide->drive[drive].ident.cur_log_cyls);
336:     printk("cur log heads = %d (%b)\n", ide->drive[drive].ident.cur_log_head
s, ide->drive[drive].ident.cur_log_heads);
337:     printk("cur log spt   = %d (%b)\n", ide->drive[drive].ident.cur_log_spt,
ide->drive[drive].ident.cur_log_spt);
338:     printk("cur capacity  = %d (%b)\n", ide->drive[drive].ident.cur_capacity
| (ide->drive[drive].ident.cur_capacity2 << 16), ide->drive[drive].ident.cur_capacity
| (ide->drive[drive].ident.cur_capacity2 << 16));
339:     printk("mult sect set = %d (%b)\n", ide->drive[drive].ident.mult_sect_se
t, ide->drive[drive].ident.mult_sect_set);
340:     printk("tot sectors   = %d (%b)\n", ide->drive[drive].ident.tot_sectors
| (ide->drive[drive].ident.tot_sectors2 << 16), ide->drive[drive].ident.tot_sectors | (
ide->drive[drive].ident.tot_sectors2 << 16));
341:     printk("singleword dma= %d (%b)\n", ide->drive[drive].ident.singleword_d
ma, ide->drive[drive].ident.singleword_dma);
342:     printk("multiword dma = %d (%b)\n", ide->drive[drive].ident.multiword_dm
a, ide->drive[drive].ident.multiword_dma);
343:     printk("adv pio modes = %d (%b)\n", ide->drive[drive].ident.adv_pio_mode
s, ide->drive[drive].ident.adv_pio_modes);
344:     printk("min multiword = %d (%b)\n", ide->drive[drive].ident.min_multiwor
d, ide->drive[drive].ident.min_multiword);
345:     printk("rec multiword = %d (%b)\n", ide->drive[drive].ident.rec_multiwor

```

drivers/block/ide.c

Page 7/14

```

d, ide->drive[drive].ident.rec_multiword);
346:     printk("min pio wo fc = %d (%b)\n", ide->drive[drive].ident.min_pio_wo_fc,
c, ide->drive[drive].ident.min_pio_wo_fc);
347:     printk("min pio w fc = %d (%b)\n", ide->drive[drive].ident.min_pio_w_fc,
, ide->drive[drive].ident.min_pio_w_fc);
348:     printk("reserved69 = %d (%b)\n", ide->drive[drive].ident.reserved69,
ide->drive[drive].ident.reserved69);
349:     printk("reserved70 = %d (%b)\n", ide->drive[drive].ident.reserved70,
ide->drive[drive].ident.reserved70);
350:     printk("reserved71 = %d (%b)\n", ide->drive[drive].ident.reserved71,
ide->drive[drive].ident.reserved71);
351:     printk("reserved72 = %d (%b)\n", ide->drive[drive].ident.reserved72,
ide->drive[drive].ident.reserved72);
352:     printk("reserved73 = %d (%b)\n", ide->drive[drive].ident.reserved73,
ide->drive[drive].ident.reserved73);
353:     printk("reserved74 = %d (%b)\n", ide->drive[drive].ident.reserved74,
ide->drive[drive].ident.reserved74);
354:     printk("queue depth = %d (%b)\n", ide->drive[drive].ident.queue_depth,
ide->drive[drive].ident.queue_depth);
355:     printk("reserved76 = %d (%b)\n", ide->drive[drive].ident.reserved76,
ide->drive[drive].ident.reserved76);
356:     printk("reserved77 = %d (%b)\n", ide->drive[drive].ident.reserved77,
ide->drive[drive].ident.reserved77);
357:     printk("reserved78 = %d (%b)\n", ide->drive[drive].ident.reserved78,
ide->drive[drive].ident.reserved78);
358:     printk("reserved79 = %d (%b)\n", ide->drive[drive].ident.reserved79,
ide->drive[drive].ident.reserved79);
359:     printk("major version = %d (%b)\n", ide->drive[drive].ident.majorver, id
e->drive[drive].ident.majorver);
360:     printk("minor version = %d (%b)\n", ide->drive[drive].ident.minorver, id
e->drive[drive].ident.minorver);
361:     printk("cmdset1 = %d (%b)\n", ide->drive[drive].ident.cmdset1, ide
->drive[drive].ident.cmdset1);
362:     printk("cmdset2 = %d (%b)\n", ide->drive[drive].ident.cmdset2, ide
->drive[drive].ident.cmdset2);
363:     printk("cmdsfs_ext = %d (%b)\n", ide->drive[drive].ident.cmdsf_ext, i
de->drive[drive].ident.cmdsf_ext);
364:     printk("cmdsfs_enable1 = %d (%b)\n", ide->drive[drive].ident.cmdsf_enable
1, ide->drive[drive].ident.cmdsf_enable1);
365:     printk("cmdsfs_enable2 = %d (%b)\n", ide->drive[drive].ident.cmdsf_enable
2, ide->drive[drive].ident.cmdsf_enable2);
366:     printk("cmdsfs_default = %d (%b)\n", ide->drive[drive].ident.cmdsf_defaul
t, ide->drive[drive].ident.cmdsf_default);
367:     printk("ultra dma = %d (%b)\n", ide->drive[drive].ident.ultradma, id
e->drive[drive].ident.ultradma);
368:     printk("reserved89 = %d (%b)\n", ide->drive[drive].ident.reserved89,
ide->drive[drive].ident.reserved89);
369:     printk("reserved90 = %d (%b)\n", ide->drive[drive].ident.reserved90,
ide->drive[drive].ident.reserved90);
370:     printk("current apm = %d (%b)\n", ide->drive[drive].ident.curapm, ide
->drive[drive].ident.curapm);
371:     */
372: }
373:
374: void irq_ide0(void)
375: {
376:     if(!ide0_wait_interrupt) {
377:         printk("WARNING: %s(): unexpected interrupt!\n", __FUNCTION__);
378:         ide0_need_reset = 1;
379:     } else {
380:         ide0_timeout = ide0_wait_interrupt = 0;
381:         wakeup(&irq_ide0);
382:     }
383: }
384:
385: void irq_ide1(void)
386: {

```

drivers/block/ide.c

Page 8/14

```

387:         if(!idel_wait_interrupt) {
388:             printk("WARNING: %s(): unexpected interrupt!\n", __FUNCTION__);
389:             idel_need_reset = 1;
390:         } else {
391:             idel_timeout = idel_wait_interrupt = 0;
392:             wakeup(&irq_idel);
393:         }
394:     }
395:
396: void ide0_timer(unsigned int arg)
397: {
398:     ide0_timeout = 1;
399:     ide0_wait_interrupt = 0;
400:     wakeup(&irq_ide0);
401: }
402:
403: void idel_timer(unsigned int arg)
404: {
405:     idel_timeout = 1;
406:     idel_wait_interrupt = 0;
407:     wakeup(&irq_idel);
408: }
409:
410: void ide_error(struct ide *ide, int status)
411: {
412:     int error;
413:
414:     if(status & IDE_STAT_ERR) {
415:         error = inport_b(ide->base + IDE_ERROR);
416:         if(error) {
417:             printk("error=0x%x [", error);
418:         }
419:         if(error & IDE_ERR_AMNF) {
420:             printk("address mark not found, ");
421:         }
422:         if(error & IDE_ERR_TKONF) {
423:             printk("track 0 not found (no media) or media error, ");
424:         }
425:         if(error & IDE_ERR_ABRT) {
426:             printk("command aborted, ");
427:         }
428:         if(error & IDE_ERR_MCR) {
429:             printk("media change requested, ");
430:         }
431:         if(error & IDE_ERR_IDNF) {
432:             printk("id mark not found, ");
433:         }
434:         if(error & IDE_ERR_MC) {
435:             printk("media changer, ");
436:         }
437:         if(error & IDE_ERR_UNC) {
438:             printk("uncorrectable data, ");
439:         }
440:         if(error & IDE_ERR_BBK) {
441:             printk("bad block, ");
442:         }
443:         printk("]");
444:     }
445:     if(status & IDE_STAT_DWF) {
446:         printk("device fault, ");
447:     }
448:     if(status & IDE_STAT_BSY) {
449:         printk("device busy, ");
450:     }
451:     printk("\n");
452: }
453:

```

drivers/block/ide.c

Page 9/14

```

454: void ide_delay(void)
455: {
456:     int n;
457:
458:     for(n = 0; n < 10000; n++) {
459:         NOP();
460:     }
461: }
462:
463: void ide_wait400ns(struct ide *ide)
464: {
465:     int n;
466:
467:     /* wait 400ns */
468:     for(n = 0; n < 4; n++) {
469:         inport_b(ide->ctrl + IDE_ALT_STATUS);
470:     }
471: }
472:
473: int ide_ready(struct ide *ide)
474: {
475:     int n, retries, status;
476:
477:     SET_IDE_RDY_RETR(retries);
478:     for(n = 0; n < retries; n++) {
479:         status = inport_b(ide->ctrl + IDE_ALT_STATUS);
480:         if(!(status & IDE_STAT_BSY)) {
481:             return 0;
482:         }
483:         ide_delay();
484:     }
485:
486:     inport_b(ide->base + IDE_STATUS);          /* clear any pending interrupt */
487:
488:     return status;
489: }
490: int ide_drvsel(struct ide *ide, int drive, int mode, unsigned char lba24_head)
491: {
492:     int n;
493:     int status;
494:
495:     for(n = 0; n < MAX_IDE_ERR; n++) {
496:         if((status = ide_ready(ide))) {
497:             continue;
498:         }
499:         break;
500:     }
501:     if(status) {
502:         return status;
503:     }
504:
505:     outport_b(ide->base + IDE_DRVHD, (mode + (drive << 4)) | lba24_head);
506:     ide_wait400ns(ide);
507:
508:     for(n = 0; n < MAX_IDE_ERR; n++) {
509:         if((status = ide_ready(ide))) {
510:             continue;
511:         }
512:         break;
513:     }
514:     return status;
515: }
516:
517: int ide_softreset(struct ide *ide)
518: {
519:     int error;

```

drivers/block/ide.c

Page 10/14

```

520:
521:     error = 0;
522:
523:     outport_b(ide->base + IDE_DRVHD, IDE_CHS_MODE);
524:     ide_delay();
525:
526:     outport_b(ide->ctrl + IDE_DEV_CTRL, IDE_DEVCTR_SRST | IDE_DEVCTR_NIEN);
527:     ide_delay();
528:     outport_b(ide->ctrl + IDE_DEV_CTRL, 0);
529:     ide_delay();
530:
531:     outport_b(ide->base + IDE_DRVHD, IDE_CHS_MODE);
532:     ide_delay();
533:     if(ide_ready(ide)) {
534:         printk("WARNING: %s(): reset error on IDE(%d:0).\n", __FUNCTION_
_, ide->channel);
535:         error = 1;
536:     } else {
537:         /* device is disk by default */
538:         ide->drive[IDE_MASTER].flags |= DEVICE_IS_DISK;
539:
540:         /* check if it's an ATAPI device */
541:         if(inport_b(ide->base + IDE_SECCNT) == 1 && inport_b(ide->base +
IDE_SECNUM) == 1) {
542:             if(inport_b(ide->base + IDE_LCYL) == 0x14 && inport_b(id
e->base + IDE_HCYL) == 0xEB) {
543:                 ide->drive[IDE_MASTER].flags &= ~DEVICE_IS_DISK;
544:                 ide->drive[IDE_MASTER].flags |= DEVICE_IS_ATAPI;
545:             }
546:         }
547:     }
548:
549:     outport_b(ide->base + IDE_DRVHD, IDE_CHS_MODE + (1 << 4));
550:     ide_delay();
551:     if(ide_ready(ide)) {
552:         printk("WARNING: %s(): reset error on IDE(%d:1).\n", __FUNCTION_
_, ide->channel);
553:         outport_b(ide->base + IDE_DRVHD, IDE_CHS_MODE);
554:         ide_delay();
555:         ide_ready(ide);
556:         error |= (1 << 4);
557:     }
558:
559:     outport_b(ide->ctrl + IDE_DEV_CTRL, 0);
560:     ide_delay();
561:     if(error > 1) {
562:         return error;
563:     }
564:
565:     /* device is disk by default */
566:     ide->drive[IDE_SLAVE].flags |= DEVICE_IS_DISK;
567:
568:     /* check if it's an ATAPI device */
569:     if(inport_b(ide->base + IDE_SECCNT) == 1 && inport_b(ide->base + IDE_SEC
NUM) == 1) {
570:         if(inport_b(ide->base + IDE_LCYL) == 0x14 && inport_b(ide->base
+ IDE_HCYL) == 0xEB) {
571:             ide->drive[IDE_SLAVE].flags &= ~DEVICE_IS_DISK;
572:             ide->drive[IDE_SLAVE].flags |= DEVICE_IS_ATAPI;
573:         }
574:     }
575:
576:     return error;
577: }
578:
579: struct ide * get_ide_controller(__dev_t dev)
580: {

```

drivers/block/ide.c

Page 11/14

```

581:         int controller;
582:
583:         if(MAJOR(dev) == IDE0_MAJOR) {
584:             controller = IDE_PRIMARY;
585:         } else {
586:             if(MAJOR(dev) == IDE1_MAJOR) {
587:                 controller = IDE_SECONDARY;
588:             } else {
589:                 return NULL;
590:             }
591:         }
592:         return &ide_table[controller];
593:     }
594:
595: int get_ide_drive(__dev_t dev)
596: {
597:     int drive;
598:
599:     drive = MINOR(dev);
600:     if(drive) {
601:         if(drive & (1 << IDE_SLAVE_MSF)) {
602:             drive = IDE_SLAVE;
603:         } else {
604:             drive = IDE_MASTER;
605:         }
606:     }
607:     return drive;
608: }
609:
610: int ide_open(struct inode *i, struct fd *fd_table)
611: {
612:     int drive;
613:     struct ide *ide;
614:     struct device *d;
615:
616:     if(!(ide = get_ide_controller(i->rdev))) {
617:         return -EINVAL;
618:     }
619:
620:     if(!(d = get_device(BLK_DEV, MAJOR(i->rdev)))) {
621:         return -ENXIO;
622:     }
623:     if(!TEST_MINOR(d->minors, MINOR(i->rdev))) {
624:         return -ENXIO;
625:     }
626:
627:     drive = get_ide_drive(i->rdev);
628:     if(ide->drive[drive].fsop && ide->drive[drive].fsop->open) {
629:         return ide->drive[drive].fsop->open(i, fd_table);
630:     }
631:     return -EINVAL;
632: }
633:
634: int ide_close(struct inode *i, struct fd *fd_table)
635: {
636:     int drive;
637:     struct ide *ide;
638:     struct device *d;
639:
640:     if(!(ide = get_ide_controller(i->rdev))) {
641:         return -EINVAL;
642:     }
643:
644:     if(!(d = get_device(BLK_DEV, MAJOR(i->rdev)))) {
645:         return -ENXIO;
646:     }
647:     if(!TEST_MINOR(d->minors, MINOR(i->rdev))) {

```

drivers/block/ide.c

Page 12/14

```

648:         return -ENXIO;
649:     }
650:
651:     drive = get_ide_drive(i->rdev);
652:     if(ide->drive[drive].fsop && ide->drive[drive].fsop->close) {
653:         return ide->drive[drive].fsop->close(i, fd_table);
654:     }
655:     return -EINVAL;
656: }
657:
658: int ide_read(__dev_t dev, __blk_t block, char *buffer, int blksize)
659: {
660:     int drive;
661:     struct ide *ide;
662:     struct device *d;
663:
664:     if(!(ide = get_ide_controller(dev))) {
665:         printk("%s(): no ide controller!\n", __FUNCTION__);
666:         return -EINVAL;
667:     }
668:
669:     if(!(d = get_device(BLK_DEV, MAJOR(dev)))) {
670:         return -ENXIO;
671:     }
672:     if(!TEST_MINOR(d->minors, MINOR(dev))) {
673:         return -ENXIO;
674:     }
675:
676:     drive = get_ide_drive(dev);
677:     if(ide->drive[drive].fsop && ide->drive[drive].fsop->read_block) {
678:         return ide->drive[drive].fsop->read_block(dev, block, buffer, bl
ksize);
679:     }
680:     printk("WARNING: %s(): device %d,%d does not have the read_block() metho
d!\n", __FUNCTION__, MAJOR(dev), MINOR(dev));
681:     return -EINVAL;
682: }
683:
684: int ide_write(__dev_t dev, __blk_t block, char *buffer, int blksize)
685: {
686:     int drive;
687:     struct ide *ide;
688:     struct device *d;
689:
690:     if(!(ide = get_ide_controller(dev))) {
691:         printk("%s(): no ide controller!\n", __FUNCTION__);
692:         return -EINVAL;
693:     }
694:
695:     if(!(d = get_device(BLK_DEV, MAJOR(dev)))) {
696:         return -ENXIO;
697:     }
698:     if(!TEST_MINOR(d->minors, MINOR(dev))) {
699:         return -ENXIO;
700:     }
701:
702:     drive = get_ide_drive(dev);
703:     if(ide->drive[drive].fsop && ide->drive[drive].fsop->write_block) {
704:         return ide->drive[drive].fsop->write_block(dev, block, buffer, b
lksize);
705:     }
706:     printk("WARNING: %s(): device %d,%d does not have the write_block() meth
od!\n", __FUNCTION__, MAJOR(dev), MINOR(dev));
707:     return -EINVAL;
708: }
709:
710: int ide_ioctl(struct inode *i, int cmd, unsigned long int arg)

```

drivers/block/ide.c

Page 13/14

```

711: {
712:     int drive;
713:     struct ide *ide;
714:     struct device *d;
715:
716:     if(!(ide = get_ide_controller(i->rdev))) {
717:         return -EINVAL;
718:     }
719:
720:     if(!(d = get_device(BLK_DEV, MAJOR(i->rdev)))) {
721:         return -ENXIO;
722:     }
723:     if(!TEST_MINOR(d->minors, MINOR(i->rdev))) {
724:         return -ENXIO;
725:     }
726:
727:     drive = get_ide_drive(i->rdev);
728:     if(ide->drive[drive].fsop && ide->drive[drive].fsop->iocctl) {
729:         return ide->drive[drive].fsop->iocctl(i, cmd, arg);
730:     }
731:     return -EINVAL;
732: }
733:
734: void ide_init(void)
735: {
736:     int devices, errno;
737:     struct ide *ide;
738:
739:     if(!register_irq(IDE0_IRQ, ide0_device.name, irq_ide0)) {
740:         enable_irq(IDE0_IRQ);
741:     }
742:     devices = 0;
743:
744:     ide = &ide_table[IDE_PRIMARY];
745:     errno = ide_softreset(ide);
746:     if(!(errno & 1)) {
747:         if(!(ide_identify(ide, IDE_MASTER))) {
748:             get_device_size(&ide->drive[IDE_MASTER]);
749:             ide_results(ide, IDE_MASTER);
750:             register_device(BLK_DEV, &ide0_device);
751:             if(ide->drive[IDE_MASTER].flags & DEVICE_IS_DISK) {
752:                 if(!ide_hd_init(ide, IDE_MASTER)) {
753:                     devices++;
754:                 }
755:             }
756:             if(ide->drive[IDE_MASTER].flags & DEVICE_IS_CDROM) {
757:                 if(!ide_cd_init(ide, IDE_MASTER)) {
758:                     devices++;
759:                 }
760:             }
761:         }
762:     }
763:     if(!(errno & 0x10)) {
764:         if(!(ide_identify(ide, IDE_SLAVE))) {
765:             get_device_size(&ide->drive[IDE_SLAVE]);
766:             ide_results(ide, IDE_SLAVE);
767:             if(!devices) {
768:                 register_device(BLK_DEV, &ide0_device);
769:             }
770:             if(ide->drive[IDE_SLAVE].flags & DEVICE_IS_DISK) {
771:                 if(!ide_hd_init(ide, IDE_SLAVE)) {
772:                     devices++;
773:                 }
774:             }
775:             if(ide->drive[IDE_SLAVE].flags & DEVICE_IS_CDROM) {
776:                 if(!ide_cd_init(ide, IDE_SLAVE)) {
777:                     devices++;

```


drivers/block/ide.c

Page 14/14

```

778:                                     }
779:                                 }
780:                    }
781:    }
782:    if(!devices) {
783:        disable_irq(IDE0_IRQ);
784:        unregister_irq(IDE0_IRQ);
785:    }
786:
787:    if(!register_irq(IDE1_IRQ, idel_device.name, irq_idel)) {
788:        enable_irq(IDE1_IRQ);
789:    }
790:    devices = 0;
791:    ide = &ide_table[IDE_SECONDARY];
792:    errno = ide_softreset(ide);
793:    if(!(errno & 1)) {
794:        if(!(ide_identify(ide, IDE_MASTER))) {
795:            get_device_size(&ide->drive[IDE_MASTER]);
796:            ide_results(ide, IDE_MASTER);
797:            register_device(BLK_DEV, &idel_device);
798:            if(ide->drive[IDE_MASTER].flags & DEVICE_IS_DISK) {
799:                if(!ide_hd_init(ide, IDE_MASTER)) {
800:                    devices++;
801:                }
802:            }
803:            if(ide->drive[IDE_MASTER].flags & DEVICE_IS_CDROM) {
804:                if(!ide_cd_init(ide, IDE_MASTER)) {
805:                    devices++;
806:                }
807:            }
808:        }
809:    }
810:    if(!(errno & 0x10)) {
811:        if(!(ide_identify(ide, IDE_SLAVE))) {
812:            get_device_size(&ide->drive[IDE_SLAVE]);
813:            ide_results(ide, IDE_SLAVE);
814:            if(!devices) {
815:                register_device(BLK_DEV, &idel_device);
816:            }
817:            if(ide->drive[IDE_SLAVE].flags & DEVICE_IS_DISK) {
818:                if(!ide_hd_init(ide, IDE_SLAVE)) {
819:                    devices++;
820:                }
821:            }
822:            if(ide->drive[IDE_SLAVE].flags & DEVICE_IS_CDROM) {
823:                if(!ide_cd_init(ide, IDE_SLAVE)) {
824:                    devices++;
825:                }
826:            }
827:        }
828:    }
829:    if(!devices) {
830:        disable_irq(IDE1_IRQ);
831:        unregister_irq(IDE1_IRQ);
832:    }
833: }

```

drivers/block/ide_cd.c

Page 1/9

```

1: /*
2:  * fiwix/drivers/block/ide_cd.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/buffer.h>
10: #include <fiwix/ide.h>
11: #include <fiwix/ide_cd.h>
12: #include <fiwix/ioctl.h>
13: #include <fiwix/devices.h>
14: #include <fiwix/sleep.h>
15: #include <fiwix/timer.h>
16: #include <fiwix/sched.h>
17: #include <fiwix/cpu.h>
18: #include <fiwix/fs.h>
19: #include <fiwix/part.h>
20: #include <fiwix/process.h>
21: #include <fiwix/mm.h>
22: #include <fiwix/errno.h>
23: #include <fiwix/stdio.h>
24: #include <fiwix/string.h>
25:
26: /* default size of 1GB is enough to read a whole CDROM */
27: #define CDROM_DEFAULT_SIZE      (1024 * 1024) /* in KBs */
28:
29: static struct resource ide_cd_resource = { NULL, NULL };
30:
31: static struct fs_operations ide_cd_driver_fsop = {
32:     0,
33:     0,
34:
35:     ide_cd_open,
36:     ide_cd_close,
37:     NULL, /* read */
38:     NULL, /* write */
39:     ide_cd_ioctl,
40:     NULL, /* lseek */
41:     NULL, /* readdir */
42:     NULL, /* mmap */
43:     NULL, /* select */
44:
45:     NULL, /* readlink */
46:     NULL, /* followlink */
47:     NULL, /* bmap */
48:     NULL, /* lockup */
49:     NULL, /* rmdir */
50:     NULL, /* link */
51:     NULL, /* unlink */
52:     NULL, /* symlink */
53:     NULL, /* mkdir */
54:     NULL, /* mknod */
55:     NULL, /* truncate */
56:     NULL, /* create */
57:     NULL, /* rename */
58:
59:     ide_cd_read,
60:     NULL, /* write_block */
61:
62:     NULL, /* read_inode */
63:     NULL, /* write_inode */
64:     NULL, /* ialloc */
65:     NULL, /* ifree */
66:     NULL, /* statfs */
67:     NULL, /* read_superblock */

```

drivers/block/ide_cd.c

Page 2/9

```

68:         NULL,                /* remount_fs */
69:         NULL,                /* write_superblock */
70:         NULL,                /* release_superblock */
71:     };
72:
73:     static char *sense_key_err[] = {
74:         "NO SENSE",
75:         "RECOVERED ERROR",
76:         "NOT READY",
77:         "MEDIUM ERROR",
78:         "HARDWARE ERROR",
79:         "ILLEGAL REQUEST",
80:         "UNIT ATTENTION",
81:         "DATA PROTECT",
82:         "RESERVED",
83:         "RESERVED",
84:         "RESERVED",
85:         "ABORTED COMMAND",
86:         "MISCOMPARE",
87:         "RESERVED"
88:     };
89:
90:     enum {
91:         RS_NO_SENSE,
92:         RS_RECOVERED_ERROR,
93:         RS_NOT_READY,
94:         RS_MEDIUM_ERROR,
95:         RS_HARDWARE_ERROR,
96:         RS_ILLEGAL_REQUEST,
97:         RS_UNIT_ATTENTION,
98:         RS_DATA_PROTECT,
99:         RS_RESERVED1,
100:        RS_RESERVED2,
101:        RS_RESERVED3,
102:        RS_ABORTED_COMMAND,
103:        RS_MISCOMPARE,
104:        RS_RESERVED4
105:    };
106:
107:     static int send_packet_command(unsigned char *pkt, struct ide *ide, int drive, i
nt blksize)
108:     {
109:         int n, retries, status;
110:
111:         outport_b(ide->ctrl + IDE_DEV_CTRL, 0);
112:         ide_delay();
113:         outport_b(ide->base + IDE_DRVHD, IDE_CHS_MODE);
114:         ide_delay();
115:         if(ide_drvsel(ide, drive, IDE_CHS_MODE, 0)) {
116:             printk("WARNING: %s(): %s: drive not ready to receive PACKET com
mand.\n", __FUNCTION__, ide->drive[drive].dev_name);
117:             return 1;
118:         }
119:
120:         CLI();
121:         outport_b(ide->base + IDE_FEATURES, 0);
122:         outport_b(ide->base + IDE_SECCNT, 0);
123:         outport_b(ide->base + IDE_SECNUM, 0);
124:         outport_b(ide->base + IDE_LCYL, blksize & 0xFF);
125:         outport_b(ide->base + IDE_HCYL, blksize >> 8);
126:         outport_b(ide->base + IDE_DRVHD, drive << 4);
127:         outport_b(ide->base + IDE_COMMAND, ATA_PACKET);
128:         ide_wait400ns(ide);
129:
130:     /*
131:      * NOTE: Some devices prior to ATA/ATAPI-4 assert INTRQ if enabled at this
132:      * point. See IDENTIFY PACKET DEVICE, word 0, bits 5-6 to determine if an

```

drivers/block/ide_cd.c

Page 3/9

```

133:  * interrupt will occur.
134:  */
135:      SET_IDE_RDY_RETR(retries);
136:
137:      for(n = 0; n < retries; n++) {
138:          status = inport_b(ide->base + IDE_STATUS);
139:          if((status & (IDE_STAT_DRQ | IDE_STAT_BSY)) == IDE_STAT_DRQ) {
140:              break;
141:          }
142:          ide_delay();
143:      }
144:      if(n >= retries) {
145:          printk("WARNING: %s(): %s: drive not ready to receive command pa
cket (retries = %d).\n", __FUNCTION__, ide->drive[drive].dev_name, n);
146:          return 1;
147:      }
148:
149:      outport_sw(ide->base + IDE_DATA, pkt, 12 / sizeof(short int));
150:      return 0;
151:  }
152:
153:  static int atapi_read_data(__dev_t dev, char *data, struct ide *ide, int blksize
, int offset)
154:  {
155:      int errno, status;
156:      char *buffer;
157:      int retries, bytes;
158:      struct callout_req creq;
159:
160:      for(retries = 0; retries < MAX_IDE_ERR; retries++) {
161:          if(ide->channel == IDE_PRIMARY) {
162:              ide0_wait_interrupt = ide->base;
163:              creq.fn = ide0_timer;
164:              creq.arg = 0;
165:              add_callout(&creq, WAIT_FOR_IDE);
166:              sleep(&irq_ide0, PROC_UNINTERRUPTIBLE);
167:              if(ide0_timeout) {
168:                  status = inport_b(ide->base + IDE_STATUS);
169:                  if((status & (IDE_STAT_RDY | IDE_STAT_DRQ)) != (
IDE_STAT_RDY | IDE_STAT_DRQ)) {
170:                      continue;
171:                  }
172:              }
173:              del_callout(&creq);
174:          }
175:          if(ide->channel == IDE_SECONDARY) {
176:              idel_wait_interrupt = ide->base;
177:              creq.fn = idel_timer;
178:              creq.arg = 0;
179:              add_callout(&creq, WAIT_FOR_IDE);
180:              sleep(&irq_idel, PROC_UNINTERRUPTIBLE);
181:              if(idel_timeout) {
182:                  status = inport_b(ide->base + IDE_STATUS);
183:                  if((status & (IDE_STAT_RDY | IDE_STAT_DRQ)) != (
IDE_STAT_RDY | IDE_STAT_DRQ)) {
184:                      continue;
185:                  }
186:              }
187:              del_callout(&creq);
188:          }
189:          status = inport_b(ide->base + IDE_STATUS);
190:          if(status & IDE_STAT_ERR) {
191:              continue;
192:          }
193:
194:          if((status & (IDE_STAT_DRQ | IDE_STAT_BSY)) == 0) {
195:              break;

```

drivers/block/ide_cd.c

Page 4/9

```

196:         }
197:
198:         bytes = (inport_b(ide->base + IDE_HCYL) << 8) + inport_b(ide->ba
se + IDE_LCYL);
199:         if(!bytes || bytes > blksize) {
200:             break;
201:         }
202:
203:         bytes = MAX(bytes, IDE_CD_SECTSIZE);    /* read more than 2048 b
ytes is not supported */
204:         buffer = data + offset;
205:         inport_sw(ide->base + IDE_DATA, (void *)buffer, bytes / sizeof(s
hort int));
206:     }
207:
208:     if(status & IDE_STAT_ERR) {
209:         errno = inport_b(ide->base + IDE_ERROR);
210:         printk("WARNING: %s(): error on cdrom device %d,%d, status=0x%x
error=0x%x,\n", __FUNCTION__, MAJOR(dev), MINOR(dev), status, errno);
211:         return 1;
212:     }
213:
214:     if(retries >= MAX_IDE_ERR) {
215:         printk("WARNING: %s(): timeout on cdrom device %d,%d, status=0x%
x.\n", __FUNCTION__, MAJOR(dev), MINOR(dev), status);
216:         /* a reset may be required at this moment */
217:         return 1;
218:     }
219:     return 0;
220: }
221:
222: static int atapi_cmd_testunit(struct ide *ide, int drive)
223: {
224:     unsigned char pkt[12];
225:
226:     pkt[0] = ATAPI_TEST_UNIT;
227:     pkt[1] = NULL;
228:     pkt[2] = NULL;
229:     pkt[3] = NULL;
230:     pkt[4] = NULL;
231:     pkt[5] = NULL;
232:     pkt[6] = NULL;
233:     pkt[7] = NULL;
234:     pkt[8] = NULL;
235:     pkt[9] = NULL;
236:     pkt[10] = NULL;
237:     pkt[11] = NULL;
238:     return send_packet_command(pkt, ide, drive, 0);
239: }
240:
241: static int atapi_cmd_reqsense(struct ide *ide, int drive)
242: {
243:     unsigned char pkt[12];
244:
245:     pkt[0] = ATAPI_REQUEST_SENSE;
246:     pkt[1] = NULL;
247:     pkt[2] = NULL;
248:     pkt[3] = NULL;
249:     pkt[4] = 252;    /* this command can send up to 252 bytes */
250:     pkt[5] = NULL;
251:     pkt[6] = NULL;
252:     pkt[7] = NULL;
253:     pkt[8] = NULL;
254:     pkt[9] = NULL;
255:     pkt[10] = NULL;
256:     pkt[11] = NULL;
257:     return send_packet_command(pkt, ide, drive, 0);

```

drivers/block/ide_cd.c

Page 5/9

```

258: }
259:
260: static int atapi_cmd_startstop(int action, struct ide *ide, int drive)
261: {
262:     unsigned char pkt[12];
263:
264:     pkt[0] = ATAPI_START_STOP;
265:     pkt[1] = NULL;
266:     pkt[2] = NULL;
267:     pkt[3] = NULL;
268:     pkt[4] = action;
269:     pkt[5] = NULL;
270:     pkt[6] = NULL;
271:     pkt[7] = NULL;
272:     pkt[8] = NULL;
273:     pkt[9] = NULL;
274:     pkt[10] = NULL;
275:     pkt[11] = NULL;
276:     return send_packet_command(pkt, ide, drive, 0);
277: }
278:
279: static int atapi_cmd_mediumrm(int action, struct ide *ide, int drive)
280: {
281:     unsigned char pkt[12];
282:
283:     pkt[0] = ATAPI_MEDIUM_REMOVAL;
284:     pkt[1] = NULL;
285:     pkt[2] = NULL;
286:     pkt[3] = NULL;
287:     pkt[4] = action;
288:     pkt[5] = NULL;
289:     pkt[6] = NULL;
290:     pkt[7] = NULL;
291:     pkt[8] = NULL;
292:     pkt[9] = NULL;
293:     pkt[10] = NULL;
294:     pkt[11] = NULL;
295:     return send_packet_command(pkt, ide, drive, 0);
296: }
297:
298: static int request_sense(char *buffer, __dev_t dev, struct ide *ide, int drive)
299: {
300:     int errcode;
301:     int sense_key, sense_asc;
302:
303:     errcode = inport_b(ide->base + IDE_ERROR);
304:     sense_key = (errcode & 0xF0) >> 4;
305:     printk("\tSense Key code indicates a '%s' condition.\n", sense_key_err[sense_key & 0xF]);
306:     errcode = atapi_cmd_reqsense(ide, drive);
307:     printk("reqsense() returned %d\n", errcode);
308:     errcode = atapi_read_data(dev, buffer, ide, BLKSIZE_2K, 0);
309:     printk("atapi_read_data() returned %d\n", errcode);
310:     errcode = (int)(buffer[0] & 0x7F);
311:     sense_key = (int)(buffer[2] & 0xF);
312:     sense_asc = (int)(buffer[12] & 0xFF);
313:     printk("errcode = %x\n", errcode);
314:     printk("sense_key = %x\n", sense_key);
315:     printk("sense_asc = %x\n", sense_asc);
316:     return errcode;
317: }
318:
319: void ide_cd_timer(unsigned int arg)
320: {
321:     wakeup(&ide_cd_open);
322: }
323:

```

drivers/block/ide_cd.c

Page 6/9

```

324: int ide_cd_open(struct inode *i, struct fd *fd_table)
325: {
326:     int minor;
327:     int drive;
328:     char *buffer;
329:     int errcode;
330:     int sense_key, sense_asc;
331:     int retries;
332:     struct ide *ide;
333:
334:     if(!(ide = get_ide_controller(i->rdev))) {
335:         return -EINVAL;
336:     }
337:
338:     minor = MINOR(i->rdev);
339:     drive = get_ide_drive(i->rdev);
340:     if(drive) {
341:         minor &= ~(1 << IDE_SLAVE_MSF);
342:     }
343:
344:     CLI();
345:     lock_resource(&ide_cd_resource);
346:
347:     if(!(buffer = (void *)kmalloc())) {
348:         unlock_resource(&ide_cd_resource);
349:         return -ENOMEM;
350:     }
351:
352:     if((errcode = atapi_cmd_testunit(ide, drive))) {
353:         printk("WARNING: %s(): cdrom device %d,%d is not ready for TEST_
UNIT, error %d.\n", __FUNCTION__, MAJOR(i->rdev), MINOR(i->rdev), errcode);
354:         request_sense(buffer, i->rdev, ide, drive);
355:     }
356:
357:     for(retries = 0; retries < MAX_CD_ERR; retries++) {
358:         if(!(errcode = atapi_cmd_startstop(CD_LOAD, ide, drive))) {
359:             break;
360:         }
361:         printk("WARNING: %s(): cdrom device %d,%d is not ready for CD_LO
AD, error %d.\n", __FUNCTION__, MAJOR(i->rdev), MINOR(i->rdev), errcode);
362:         atapi_read_data(i->rdev, buffer, ide, BLKSIZE_2K, 0);
363:         errcode = request_sense(buffer, i->rdev, ide, drive);
364:         sense_key = (errcode & 0xF0) >> 4;
365:         /* trying to eject on slim drives may lead to an illegal request
*/
366:         if(!sense_key || sense_key == RS_ILLEGAL_REQUEST) {
367:             break;
368:         }
369:         if(errcode == 0x70 || errcode == 0x71) {
370:             sense_key = (int)(buffer[2] & 0xF);
371:             sense_asc = (int)(buffer[12] & 0xFF);
372:             if(sense_key == RS_NOT_READY && sense_asc == ASC_NO_MEDI
UM) {
373:                 kfree((unsigned int)buffer);
374:                 unlock_resource(&ide_cd_resource);
375:                 return -ENOMEDIUM;
376:             }
377:         }
378:     }
379:
380:     if(retries == MAX_CD_ERR) {
381:         if(sense_key == RS_NOT_READY) {
382:             kfree((unsigned int)buffer);
383:             unlock_resource(&ide_cd_resource);
384:             return -ENOMEDIUM;
385:         }
386:     }

```

drivers/block/ide_cd.c

Page 7/9

```

387:
388:     if(ata_pi_cmd_mediumrm(CD_LOCK_MEDIUM, ide, drive)) {
389:         printk("WARNING: %s(): error on cdrom device %d,%d while trying
to lock medium.\n", __FUNCTION__, MAJOR(i->rdev), MINOR(i->rdev), ATAPI_MEDIUM_REMOVAL)
;
390:         request_sense(buffer, i->rdev, ide, drive);
391:     }
392:
393:     /* this line just to catch interrupt */
394:     ata_pi_read_data(i->rdev, buffer, ide, BLKSIZE_2K, 0);
395:     kfree((unsigned int)buffer);
396:
397:     unlock_resource(&ide_cd_resource);
398:     return 0;
399: }
400:
401: int ide_cd_close(struct inode *i, struct fd *fd_table)
402: {
403:     int drive;
404:     char *buffer;
405:     struct ide *ide;
406:
407:     if(!(ide = get_ide_controller(i->rdev))) {
408:         return -EINVAL;
409:     }
410:
411:     if(!(buffer = (void *)kmalloc())) {
412:         return -ENOMEM;
413:     }
414:
415:     drive = get_ide_drive(i->rdev);
416:
417:     /* FIXME: only if device usage == 0 */
418:     invalidate_buffers(i->rdev);
419:
420:     if(ata_pi_cmd_mediumrm(CD_UNLOCK_MEDIUM, ide, drive)) {
421:         printk("WARNING: %s(): error on cdrom device %d,%d during 0x%x c
ommand.\n", __FUNCTION__, MAJOR(i->rdev), MINOR(i->rdev), ATAPI_MEDIUM_REMOVAL);
422:     }
423:
424:     /* this line just to catch interrupt */
425:     ata_pi_read_data(i->rdev, buffer, ide, BLKSIZE_2K, 0);
426:     kfree((unsigned int)buffer);
427:
428:     return 0;
429: }
430:
431: int ide_cd_read(__dev_t dev, __blk_t block, char *buffer, int blksize)
432: {
433:     int drive;
434:     int sectors_to_read;
435:     int n, retries;
436:     unsigned char pkt[12];
437:     struct ide *ide;
438:
439:     if(!(ide = get_ide_controller(dev))) {
440:         return -EINVAL;
441:     }
442:
443:     drive = get_ide_drive(dev);
444:     blksize = BLKSIZE_2K;
445:     sectors_to_read = blksize / IDE_CD_SECTSIZE;
446:
447:     pkt[0] = ATAPI_READ10;
448:     pkt[1] = NULL;
449:     pkt[2] = (block >> 24) & 0xFF;
450:     pkt[3] = (block >> 16) & 0xFF;

```


drivers/block/ide_cd.c

Page 8/9

```

451:     pkt[4] = (block >> 8) & 0xFF;
452:     pkt[5] = block & 0xFF;
453:     pkt[6] = NULL;
454:     pkt[7] = (sectors_to_read >> 8) & 0xFF;
455:     pkt[8] = sectors_to_read & 0xFF;
456:     pkt[9] = NULL;
457:     pkt[10] = NULL;
458:     pkt[11] = NULL;
459:
460:     lock_resource(&ide_cd_resource);
461:     for(n = 0; n < sectors_to_read; n++, block++) {
462:         for(retries = 0; retries < MAX_CD_ERR; retries++) {
463:             if(send_packet_command(pkt, ide, drive, blksize)) {
464:                 printk("\tblock=%d, offset=%d\n", block, block *
blksize);
465:                 unlock_resource(&ide_cd_resource);
466:                 return -EIO;
467:             }
468:             if(atapi_read_data(dev, buffer, ide, blksize, n * IDE_CD
_SECTSIZE)) {
469:                 int errcode;
470:                 int sense_key;
471:                 errcode = inport_b(ide->base + IDE_ERROR);
472:                 sense_key = (errcode & 0xF0) >> 4;
473:                 printk("\tSense Key code indicates a '%s' condit
ion.\n", sense_key_err[sense_key & 0xF]);
474:                 if(sense_key) {
475:                     continue;
476:                 }
477:             }
478:             break;
479:         }
480:         if(retries == MAX_CD_ERR) {
481:             printk("\tblock=%d, offset=%d\n", block, block * blksize
);
482:             unlock_resource(&ide_cd_resource);
483:             return -EIO;
484:         }
485:     }
486:     unlock_resource(&ide_cd_resource);
487:     return sectors_to_read * IDE_CD_SECTSIZE;
489: }
490:
491: int ide_cd_ioctl(struct inode *i, int cmd, unsigned long int arg)
492: {
493:     struct ide *ide;
494:
495:     if(!(ide = get_ide_controller(i->rdev))) {
496:         return -EINVAL;
497:     }
498:
499:     switch(cmd) {
500:         default:
501:             return -EINVAL;
502:             break;
503:     }
504:
505:     return 0;
506: }
507:
508: int ide_cd_init(struct ide *ide, int drive)
509: {
510:     struct device *d;
511:
512:     ide->drive[drive].fsop = &ide_cd_driver_fsop;
513:

```

drivers/block/ide_cd.c

Page 9/9

```
514:         if(!(d = get_device(BLK_DEV, ide->drive[drive].major))) {
515:             return -EINVAL;
516:         }
517:         if(drive == IDE_MASTER) {
518:             ide->drive[drive].minor_shift = IDE_MASTER_MSF;
519:             SET_MINOR(d->minors, 0);
520:             ((unsigned int *)d->device_data)[0] = CDROM_DEFAULT_SIZE;
521:         } else {
522:             ide->drive[drive].minor_shift = IDE_SLAVE_MSF;
523:             SET_MINOR(d->minors, 1 << IDE_SLAVE_MSF);
524:             ((unsigned int *)d->device_data)[1 << IDE_SLAVE_MSF] = CDROM_DEF
AULT_SIZE;
525:         }
526:
527:         return 0;
528:     }
```

drivers/block/ide_hd.c

Page 1/9

```

1: /*
2:  * fiwix/drivers/block/ide_hd.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/buffer.h>
10: #include <fiwix/ide.h>
11: #include <fiwix/ide_hd.h>
12: #include <fiwix/ioctl.h>
13: #include <fiwix/devices.h>
14: #include <fiwix/sleep.h>
15: #include <fiwix/timer.h>
16: #include <fiwix/sched.h>
17: #include <fiwix/cpu.h>
18: #include <fiwix/fs.h>
19: #include <fiwix/part.h>
20: #include <fiwix/process.h>
21: #include <fiwix/mm.h>
22: #include <fiwix/errno.h>
23: #include <fiwix/stdio.h>
24: #include <fiwix/string.h>
25:
26: static struct resource ide_hd_resource = { NULL, NULL };
27:
28: static struct fs_operations ide_hd_driver_fsop = {
29:     0,
30:     0,
31:
32:     ide_hd_open,
33:     ide_hd_close,
34:     NULL, /* read */
35:     NULL, /* write */
36:     ide_hd_ioctl,
37:     NULL, /* lseek */
38:     NULL, /* readdir */
39:     NULL, /* mmap */
40:     NULL, /* select */
41:
42:     NULL, /* readlink */
43:     NULL, /* followlink */
44:     NULL, /* bmap */
45:     NULL, /* lockup */
46:     NULL, /* rmdir */
47:     NULL, /* link */
48:     NULL, /* unlink */
49:     NULL, /* symlink */
50:     NULL, /* mkdir */
51:     NULL, /* mknod */
52:     NULL, /* truncate */
53:     NULL, /* create */
54:     NULL, /* rename */
55:
56:     ide_hd_read,
57:     ide_hd_write,
58:
59:     NULL, /* read_inode */
60:     NULL, /* write_inode */
61:     NULL, /* ialloc */
62:     NULL, /* ifree */
63:     NULL, /* statfs */
64:     NULL, /* read_superblock */
65:     NULL, /* remount_fs */
66:     NULL, /* write_superblock */
67:     NULL, /* release_superblock */

```

drivers/block/ide_hd.c

Page 2/9

```

68: };
69:
70: static void assign_minors(__dev_t rdev, struct ide *ide, struct partition *part)
71: {
72:     int n;
73:     int drive, minor;
74:     struct device *d;
75:
76:     minor = 0;
77:     drive = get_ide_drive(rdev);
78:
79:     if(ide->channel == IDE_PRIMARY) {
80:         if(!(d = get_device(BLK_DEV, IDE0_MAJOR))) {
81:             return;
82:         }
83:     } else if(ide->channel == IDE_SECONDARY) {
84:         if(!(d = get_device(BLK_DEV, IDE1_MAJOR))) {
85:             return;
86:         }
87:     } else {
88:         printk("WARNING: %s(): invalid device %d,%d.\n", __FUNCTION__, M
AJOR(rdev), MINOR(rdev));
89:         return;
90:     }
91:
92:     for(n = 0; n < NR_PARTITIONS; n++) {
93:         if(drive == IDE_MASTER) {
94:             minor = (1 << ide->drive[drive].minor_shift) + n;
95:         }
96:         if(drive == IDE_SLAVE) {
97:             minor = (1 << ide->drive[drive].minor_shift) + n + 1;
98:         }
99:         CLEAR_MINOR(d->minors, minor);
100:        if(part[n].type) {
101:            SET_MINOR(d->minors, minor);
102:            ((unsigned int *)d->device_data)[minor] = part[n].nr_sec
ts / 2;
103:        }
104:    }
105: }
106:
107: static __off_t block2sector(__off_t offset, int blksize, struct partition *part,
int minor)
108: {
109:     __off_t sector;
110:
111:     sector = offset * (blksize / IDE_HD_SECTSIZE);
112:     if(minor) {
113:         sector += part[minor - 1].startsect;
114:     }
115:     return sector;
116: }
117:
118: static void sector2chs(__off_t offset, int *cyl, int *head, int *sector, struct
ide_drv_ident *ident)
119: {
120:     *cyl = offset / (ident->logic_spt * ident->logic_heads);
121:     *head = (offset / ident->logic_spt) % ident->logic_heads;
122:     *sector = (offset % ident->logic_spt) + 1;
123: }
124:
125: int ide_hd_open(struct inode *i, struct fd *fd_table)
126: {
127:     return 0;
128: }
129:
130: int ide_hd_close(struct inode *i, struct fd *fd_table)

```

drivers/block/ide_hd.c

Page 3/9

```

131: {
132:     sync_buffers(i->rdev);
133:     return 0;
134: }
135:
136: int ide_hd_read(__dev_t dev, __blk_t block, char *buffer, int blksize)
137: {
138:     int minor;
139:     int drive;
140:     int sectors_to_read, cmd;
141:     int n, status, r, retries;
142:     int cyl, head, sector;
143:     __off_t offset;
144:     struct ide *ide;
145:     struct ide_drv_ident *ident;
146:     struct partition *part;
147:     struct callout_req creq;
148:
149:     if(!(ide = get_ide_controller(dev))) {
150:         return -EINVAL;
151:     }
152:
153:     minor = MINOR(dev);
154:     if((drive = get_ide_drive(dev))) {
155:         minor &= ~(1 << IDE_SLAVE_MSF);
156:     }
157:
158:     SET_IDE_RDY_RETR(retries);
159:
160:     blksize = blksize ? blksize : BLKSIZE_1K;
161:     sectors_to_read = MIN(blksize, PAGE_SIZE) / IDE_HD_SECTSIZE;
162:
163:     ident = &ide->drive[drive].ident;
164:     part = ide->drive[drive].part_table;
165:     offset = block2sector(block, blksize, part, minor);
166:
167:     CLI();
168:     lock_resource(&ide_hd_resource);
169:
170:     n = 0;
171:
172:     while(n < sectors_to_read) {
173:         if(ide->drive[drive].flags & DEVICE_HAS_RW_MULTIPLE) {
174:             output_b(ide->base + IDE_SECCNT, sectors_to_read);
175:             cmd = ATA_READ_MULTIPLE_PIO;
176:         } else {
177:             output_b(ide->base + IDE_SECCNT, 1);
178:             cmd = ATA_READ_PIO;
179:         }
180:
181:         if(ide->drive[drive].flags & DEVICE_REQUIRES_LBA) {
182:             output_b(ide->base + IDE_SECNUM, offset & 0xFF);
183:             output_b(ide->base + IDE_LCYL, (offset >> 8) & 0xFF);
184:             output_b(ide->base + IDE_HCYL, (offset >> 16) & 0xFF);
185:             if(ide_drvsel(ide, drive, IDE_LBA_MODE, (offset >> 24) &
0x0F)) {
186:                 printk("WARNING: %s(): %s: drive not ready.\n",
__FUNCTION__, ide->drive[drive].dev_name);
187:                 unlock_resource(&ide_hd_resource);
188:                 return -EIO;
189:             }
190:         } else {
191:             sector2chs(offset, &cyl, &head, &sector, ident);
192:             output_b(ide->base + IDE_SECNUM, sector);
193:             output_b(ide->base + IDE_LCYL, cyl);
194:             output_b(ide->base + IDE_HCYL, (cyl >> 8));
195:             if(ide_drvsel(ide, drive, IDE_CHS_MODE, head)) {

```

drivers/block/ide_hd.c

Page 4/9

```

196:                printk("WARNING: %s(): %s: drive not ready.\n",
__FUNCTION__, ide->drive[drive].dev_name);
197:                unlock_resource(&ide_hd_resource);
198:                return -EIO;
199:            }
200:        }
201:        outport_b(ide->base + IDE_COMMAND, cmd);
202:        if(ide->channel == IDE_PRIMARY) {
203:            ide0_wait_interrupt = ide->base;
204:            creq.fn = ide0_timer;
205:            creq.arg = 0;
206:            add_callout(&creq, WAIT_FOR_IDE);
207:            sleep(&irq_ide0, PROC_UNINTERRUPTIBLE);
208:            if(!ide0_timeout) {
209:                del_callout(&creq);
210:            }
211:        }
212:        if(ide->channel == IDE_SECONDARY) {
213:            idel_wait_interrupt = ide->base;
214:            creq.fn = idel_timer;
215:            creq.arg = 0;
216:            add_callout(&creq, WAIT_FOR_IDE);
217:            sleep(&irq_idel, PROC_UNINTERRUPTIBLE);
218:            if(!idel_timeout) {
219:                del_callout(&creq);
220:            }
221:        }
222:        for(r = 0; r < retries; r++) {
223:            status = inport_b(ide->base + IDE_STATUS);
224:            if(!(status & IDE_STAT_BSY) && (status & IDE_STAT_DRQ))
{
225:                break;
226:            }
227:            ide_delay();
228:        }
229:        if(status & IDE_STAT_ERR) {
230:            printk("WARNING: %s(): %s: error on hard disk dev %d,%d
during read.\n", __FUNCTION__, ide->drive[drive].dev_name, MAJOR(dev), MINOR(dev));
231:            printk("\tstatus=0x%x ", status);
232:            ide_error(ide, status);
233:            printk("\tblock %d, sector %d.\n", block, offset);
234:            inport_b(ide->base + IDE_STATUS);        /* clear any pen
ding interrupt */
235:            unlock_resource(&ide_hd_resource);
236:            return -EIO;
237:        }
238:
239:        if(cmd == ATA_READ_MULTIPLE_PIO) {
240:            inport_sw(ide->base + IDE_DATA, (void *)buffer, (IDE_HD_
SECTSIZE * sectors_to_read) / sizeof(short int));
241:            break;
242:        }
243:        inport_sw(ide->base + IDE_DATA, (void *)buffer, IDE_HD_SECTSIZE
/ sizeof(short int));
244:        inport_b(ide->ctrl + IDE_ALT_STATUS);    /* ignore results */
245:        inport_b(ide->base + IDE_STATUS);        /* clear any pending int
errupt */
246:        n++;
247:        offset++;
248:        buffer += IDE_HD_SECTSIZE;
249:    }
250:    inport_b(ide->ctrl + IDE_ALT_STATUS);    /* ignore results */
251:    inport_b(ide->base + IDE_STATUS);        /* clear any pending interrupt */
/
252:    unlock_resource(&ide_hd_resource);
253:    return sectors_to_read * IDE_HD_SECTSIZE;
254: }

```

drivers/block/ide_hd.c

Page 5/9

```

255:
256: int ide_hd_write(__dev_t dev, __blk_t block, char *buffer, int blksize)
257: {
258:     int minor;
259:     int drive;
260:     int sectors_to_write, cmd;
261:     int n, status, r, retries;
262:     int cyl, head, sector;
263:     __off_t offset;
264:     struct ide *ide;
265:     struct ide_drv_ident *ident;
266:     struct partition *part;
267:     struct callout_req creq;
268:
269:     if(!(ide = get_ide_controller(dev))) {
270:         return -EINVAL;
271:     }
272:
273:     minor = MINOR(dev);
274:     if((drive = get_ide_drive(dev)) {
275:         minor &= ~(1 << IDE_SLAVE_MSF);
276:     }
277:
278:     SET_IDE_RDY_RETR(retries);
279:
280:     blksize = blksize ? blksize : BLKSIZE_1K;
281:     sectors_to_write = MIN(blksize, PAGE_SIZE) / IDE_HD_SECTSIZE;
282:
283:     ident = &ide->drive[drive].ident;
284:     part = ide->drive[drive].part_table;
285:     offset = block2sector(block, blksize, part, minor);
286:
287:     CLI();
288:     lock_resource(&ide_hd_resource);
289:
290:     n = 0;
291:
292:     while(n < sectors_to_write) {
293:         if(ide->drive[drive].flags & DEVICE_HAS_RW_MULTIPLE) {
294:             outport_b(ide->base + IDE_SECCNT, sectors_to_write);
295:             cmd = ATA_WRITE_MULTIPLE_PIO;
296:         } else {
297:             outport_b(ide->base + IDE_SECCNT, 1);
298:             cmd = ATA_WRITE_PIO;
299:         }
300:
301:         if(ide->drive[drive].flags & DEVICE_REQUIRES_LBA) {
302:             outport_b(ide->base + IDE_SECNUM, offset & 0xFF);
303:             outport_b(ide->base + IDE_LCYL, (offset >> 8) & 0xFF);
304:             outport_b(ide->base + IDE_HCYL, (offset >> 16) & 0xFF);
305:             if(ide_drvsel(ide, drive, IDE_LBA_MODE, (offset >> 24) &
0x0F)) {
306:                 printk("WARNING: %s(): %s: drive not ready.\n",
__FUNCTION__, ide->drive[drive].dev_name);
307:                 unlock_resource(&ide_hd_resource);
308:                 return -EIO;
309:             }
310:         } else {
311:             sector2chs(offset, &cyl, &head, &sector, ident);
312:             outport_b(ide->base + IDE_SECNUM, sector);
313:             outport_b(ide->base + IDE_LCYL, cyl);
314:             outport_b(ide->base + IDE_HCYL, (cyl >> 8));
315:             if(ide_drvsel(ide, drive, IDE_CHS_MODE, head)) {
316:                 printk("WARNING: %s(): %s: drive not ready.\n",
__FUNCTION__, ide->drive[drive].dev_name);
317:                 unlock_resource(&ide_hd_resource);
318:                 return -EIO;

```

drivers/block/ide_hd.c

Page 6/9

```

319:         }
320:     }
321:     outport_b(ide->base + IDE_COMMAND, cmd);
322:     for(r = 0; r < retries; r++) {
323:         status = inport_b(ide->base + IDE_STATUS);
324:         if(!(status & IDE_STAT_BSY) && (status & IDE_STAT_DRQ))
{
325:             break;
326:         }
327:         ide_delay();
328:     }
329:     if(status & IDE_STAT_ERR) {
330:         printk("WARNING: %s(): %s: error on hard disk dev %d,%d
during write.\n", __FUNCTION__, ide->drive[drive].dev_name, MAJOR(dev), MINOR(dev));
331:         printk("\tstatus=0x%x ", status);
332:         ide_error(ide, status);
333:         printk("\tblock %d, sector %d.\n", block, offset);
334:         inport_b(ide->base + IDE_STATUS); /* clear any pen
ding interrupt */
335:         unlock_resource(&ide_hd_resource);
336:         return -EIO;
337:     }
338:
339:     if(cmd == ATA_WRITE_MULTIPLE_PIO) {
340:         outport_sw(ide->base + IDE_DATA, (void *)buffer, (IDE_HD
_SECTSIZE * sectors_to_write) / sizeof(short int));
341:     } else {
342:         outport_sw(ide->base + IDE_DATA, (void *)buffer, IDE_HD_
SECTSIZE / sizeof(short int));
343:     }
344:     if(ide->channel == IDE_PRIMARY) {
345:         ide0_wait_interrupt = ide->base;
346:         creq.fn = ide0_timer;
347:         creq.arg = 0;
348:         add_callout(&creq, WAIT_FOR_IDE);
349:         sleep(&irq_ide0, PROC_UNINTERRUPTIBLE);
350:         if(!ide0_timeout) {
351:             del_callout(&creq);
352:         }
353:     }
354:     if(ide->channel == IDE_SECONDARY) {
355:         idel_wait_interrupt = ide->base;
356:         creq.fn = idel_timer;
357:         creq.arg = 0;
358:         add_callout(&creq, WAIT_FOR_IDE);
359:         sleep(&irq_idel, PROC_UNINTERRUPTIBLE);
360:         if(!idel_timeout) {
361:             del_callout(&creq);
362:         }
363:     }
364:
365:     inport_b(ide->ctrl + IDE_ALT_STATUS); /* ignore results */
366:     inport_b(ide->base + IDE_STATUS); /* clear any pending int
errupt */
367:     if(cmd == ATA_WRITE_MULTIPLE_PIO) {
368:         break;
369:     }
370:     n++;
371:     offset++;
372:     buffer += IDE_HD_SECTSIZE;
373: }
374: inport_b(ide->ctrl + IDE_ALT_STATUS); /* ignore results */
375: inport_b(ide->base + IDE_STATUS); /* clear any pending interrupt */
/
376: unlock_resource(&ide_hd_resource);
377: return sectors_to_write * IDE_HD_SECTSIZE;
378: }

```


drivers/block/ide_hd.c

Page 7/9

```

379:
380: int ide_hd_ioctl(struct inode *i, int cmd, unsigned long int arg)
381: {
382:     int minor;
383:     int drive;
384:     struct ide *ide;
385:     struct ide_drv_ident *ident;
386:     struct partition *part;
387:     struct hd_geometry *geom;
388:     int errno;
389:
390:     if(!(ide = get_ide_controller(i->rdev))) {
391:         return -EINVAL;
392:     }
393:
394:     minor = MINOR(i->rdev);
395:     drive = get_ide_drive(i->rdev);
396:     if(drive) {
397:         minor &= ~(1 << IDE_SLAVE_MSF);
398:     }
399:
400:     ident = &ide->drive[drive].ident;
401:     part = ide->drive[drive].part_table;
402:
403:     switch(cmd) {
404:         case HDIO_GETGEO:
405:             if((errno = check_user_area(VERIFY_WRITE, (void *)arg, s
sizeof(struct hd_geometry)))) {
406:                 return errno;
407:             }
408:             geom = (struct hd_geometry *)arg;
409:             geom->cylinders = ident->logic_cyls;
410:             geom->heads = (char)ident->logic_heads;
411:             geom->sectors = (char)ident->logic_spt;
412:             geom->start = 0;
413:             if(minor) {
414:                 geom->start = part[minor - 1].startsect;
415:             }
416:             break;
417:         case BLKGETSIZE:
418:             if((errno = check_user_area(VERIFY_WRITE, (void *)arg, s
sizeof(unsigned int)))) {
419:                 return errno;
420:             }
421:             if(!minor) {
422:                 *(int *)arg = (unsigned int)ide->drive[drive].nr
_sects;
423:             } else {
424:                 *(int *)arg = (unsigned int)ide->drive[drive].pa
rt_table[minor - 1].nr_sects;
425:             }
426:             break;
427:         case BLKFLSBUF:
428:             sync_buffers(i->rdev);
429:             invalidate_buffers(i->rdev);
430:             break;
431:         case BLKRRPART:
432:             read_msdos_partition(i->rdev, part);
433:             assign_minors(i->rdev, ide, part);
434:             break;
435:         default:
436:             return -EINVAL;
437:             break;
438:     }
439:
440:     return 0;
441: }

```

drivers/block/ide_hd.c

Page 8/9

```

442:
443: int ide_hd_init(struct ide *ide, int drive)
444: {
445:     int n;
446:     __dev_t rdev;
447:     struct device *d;
448:     struct partition *part;
449:
450:     rdev = 0;
451:     ide->drive[drive].fsop = &ide_hd_driver_fsop;
452:     part = ide->drive[drive].part_table;
453:
454:     if(ide->channel == IDE_PRIMARY) {
455:         if(!(d = get_device(BLK_DEV, IDE0_MAJOR))) {
456:             return -EINVAL;
457:         }
458:         if(drive == IDE_MASTER) {
459:             rdev = MKDEV(IDE0_MAJOR, drive);
460:             ide->drive[drive].minor_shift = IDE_MASTER_MSF;
461:             SET_MINOR(d->minors, 0);
462:             ((unsigned int *)d->device_data)[0] = ide->drive[drive].
nr_sects / 2;
463:         } else {
464:             rdev = MKDEV(IDE0_MAJOR, 1 << IDE_SLAVE_MSF);
465:             ide->drive[drive].minor_shift = IDE_SLAVE_MSF;
466:             SET_MINOR(d->minors, 1 << IDE_SLAVE_MSF);
467:             ((unsigned int *)d->device_data)[1 << IDE_SLAVE_MSF] = i
de->drive[drive].nr_sects / 2;
468:         }
469:     } else if(ide->channel == IDE_SECONDARY) {
470:         if(!(d = get_device(BLK_DEV, IDE1_MAJOR))) {
471:             return -EINVAL;
472:         }
473:         if(drive == IDE_MASTER) {
474:             rdev = MKDEV(IDE1_MAJOR, drive);
475:             ide->drive[drive].minor_shift = IDE_MASTER_MSF;
476:             SET_MINOR(d->minors, 0);
477:             ((unsigned int *)d->device_data)[0] = ide->drive[drive].
nr_sects / 2;
478:         } else {
479:             rdev = MKDEV(IDE1_MAJOR, 1 << IDE_SLAVE_MSF);
480:             ide->drive[drive].minor_shift = IDE_SLAVE_MSF;
481:             SET_MINOR(d->minors, 1 << IDE_SLAVE_MSF);
482:             ((unsigned int *)d->device_data)[1 << IDE_SLAVE_MSF] = i
de->drive[drive].nr_sects / 2;
483:         }
484:     } else {
485:         printk("WARNING: %s(): invalid drive number %d.\n", __FUNCTION__
, drive);
486:         return 1;
487:     }
488:
489:     read_msdos_partition(rdev, part);
490:     assign_minors(rdev, ide, part);
491:     printk("                partition summary: ");
492:     for(n = 0; n < NR_PARTITIONS; n++) {
493:         if(part[n].type) {
494:             printk("%s%d ", ide->drive[drive].dev_name, n + 1);
495:         }
496:     }
497:     printk("\n");
498:
499:     outport_b(ide->ctrl + IDE_DEV_CTRL, IDE_DEVCTR_NIEN);
500:     if(ide->drive[drive].flags & DEVICE_HAS_RW_MULTIPLE) {
501:         outport_b(ide->base + IDE_SECCNT, BLKSIZE_1K / IDE_HD_SECTSIZE);
502:         outport_b(ide->base + IDE_COMMAND, ATA_SET_MULTIPLE_MODE);
503:         ide_wait400ns(ide);

```

drivers/block/ide_hd.c

Page 9/9

```
504:             while(inport_b(ide->base + IDE_STATUS) & IDE_STAT_BSY);
505:         }
506:         outport_b(ide->ctrl + IDE_DEV_CTRL, IDE_DEVCTR_DRQ);
507:
508:         return 0;
509: }
```

drivers/block/Makefile

Page 1/1

```
1: # fiwix/drivers/block/Makefile
2: #
3: # Copyright 2018, Jordi Sanfeliu. All rights reserved.
4: # Distributed under the terms of the Fiwix License.
5: #
6: #
7: .S.o:
8:     $(CC) -traditional -I$(INCLUDE) -c -o $@ $<
9: .c.o:
10:     $(CC) $(CFLAGS) -c -o $@ $<
11:
12: OBJS = dma.o floppy.o part.o ide.o ide_hd.o ide_cd.o ramdisk.o
13:
14: block:  $(OBJS)
15:           $(LD) $(LDFLAGS) -r $(OBJS) -o block.o
16:
17: clean:
18:           rm -f *.o
19:
```

drivers/block/part.c

Page 1/1

```

1: /*
2:  * fiwix/drivers/block/part.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/ide.h>
9: #include <fiwix/ide_hd.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/part.h>
12: #include <fiwix/mm.h>
13: #include <fiwix/errno.h>
14: #include <fiwix/stdio.h>
15: #include <fiwix/string.h>
16:
17: int read_msdos_partition(__dev_t dev, struct partition *part)
18: {
19:     char *buffer;
20:
21:     if(!(buffer = (void *)kmalloc())) {
22:         return -ENOMEM;
23:     }
24:
25:     if(ide_hd_read(dev, PARTITION_BLOCK, buffer, BLKSIZE_1K) <= 0) {
26:         printk("WARNING: %s(): unable to read partition block in device
%d,%d.\n", __FUNCTION__, MAJOR(dev), MINOR(dev));
27:         kfree((unsigned int)buffer);
28:         return -EIO;
29:     }
30:
31:     memcpy_b(part, (void *)(buffer + MBR_CODE_SIZE), sizeof(struct partition
) * NR_PARTITIONS);
32:     kfree((unsigned int)buffer);
33:     return 0;
34: }

```

drivers/block/ramdisk.c

Page 1/3

```

1: /*
2:  * fiwix/drivers/block/ramdisk.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/ramdisk.h>
10: #include <fiwix/ioctl.h>
11: #include <fiwix/devices.h>
12: #include <fiwix/part.h>
13: #include <fiwix/fs.h>
14: #include <fiwix/errno.h>
15: #include <fiwix/mmm.h>
16: #include <fiwix/stdio.h>
17: #include <fiwix/string.h>
18:
19: static unsigned int rd_sizes[256];
20:
21: static struct fs_operations ramdisk_driver_fsop = {
22:     0,
23:     0,
24:
25:     ramdisk_open,
26:     ramdisk_close,
27:     NULL,                /* read */
28:     NULL,                /* write */
29:     ramdisk_ioctl,
30:     ramdisk_lseek,
31:     NULL,                /* readdir */
32:     NULL,                /* mmap */
33:     NULL,                /* select */
34:
35:     NULL,                /* readlink */
36:     NULL,                /* followlink */
37:     NULL,                /* bmap */
38:     NULL,                /* lockup */
39:     NULL,                /* rmdir */
40:     NULL,                /* link */
41:     NULL,                /* unlink */
42:     NULL,                /* symlink */
43:     NULL,                /* mkdir */
44:     NULL,                /* mknod */
45:     NULL,                /* truncate */
46:     NULL,                /* create */
47:     NULL,                /* rename */
48:
49:     ramdisk_read,
50:     ramdisk_write,
51:
52:     NULL,                /* read_inode */
53:     NULL,                /* write_inode */
54:     NULL,                /* ialloc */
55:     NULL,                /* ifree */
56:     NULL,                /* statfs */
57:     NULL,                /* read_superblock */
58:     NULL,                /* remount_fs */
59:     NULL,                /* write_superblock */
60:     NULL,                /* release_superblock */
61: };
62:
63: static struct device ramdisk_device = {
64:     "ramdisk",
65:     -1,
66:     RAMDISK_MAJOR,
67:     { 0, 0, 0, 0, 0, 0, 0, 0, 0 },

```

drivers/block/ramdisk.c

Page 2/3

```

68:         BLKSIZE_1K,
69:         &rd_sizes,
70:         &ramdisk_driver_fsop,
71:     };
72:
73: static struct ramdisk * get_ramdisk(int minor)
74: {
75:     if(TEST_MINOR(ramdisk_device.minors, minor)) {
76:         return &ramdisk_table[minor];
77:     }
78:     return NULL;
79: }
80:
81: int ramdisk_open(struct inode *i, struct fd *fd_table)
82: {
83:     if(!get_ramdisk(MINOR(i->rdev))) {
84:         return -ENXIO;
85:     }
86:     return 0;
87: }
88:
89: int ramdisk_close(struct inode *i, struct fd *fd_table)
90: {
91:     if(!get_ramdisk(MINOR(i->rdev))) {
92:         return -ENXIO;
93:     }
94:     return 0;
95: }
96:
97: int ramdisk_read(__dev_t dev, __blk_t block, char *buffer, int blksize)
98: {
99:     int size;
100:    __off_t offset;
101:    struct ramdisk *ramdisk;
102:
103:    if(!(ramdisk = get_ramdisk(MINOR(dev)))) {
104:        return -ENXIO;
105:    }
106:
107:    size = rd_sizes[MINOR(dev)] * 1024;
108:    offset = block * blksize;
109:    blksize = MIN(blksize, size - offset);
110:    memcpy_b((void *)buffer, ramdisk->addr + offset, blksize);
111:    return blksize;
112: }
113:
114: int ramdisk_write(__dev_t dev, __blk_t block, char *buffer, int blksize)
115: {
116:     int size;
117:     __off_t offset;
118:     struct ramdisk *ramdisk;
119:
120:     if(!(ramdisk = get_ramdisk(MINOR(dev)))) {
121:         return -ENXIO;
122:     }
123:
124:     size = rd_sizes[MINOR(dev)] * 1024;
125:     offset = block * blksize;
126:     blksize = MIN(blksize, size - offset);
127:     memcpy_b((void *)ramdisk->addr + offset, buffer, blksize);
128:     return blksize;
129: }
130:
131: int ramdisk_ioctl(struct inode *i, int cmd, unsigned long int arg)
132: {
133:     struct hd_geometry *geom;
134:     int errno;

```

drivers/block/ramdisk.c

Page 3/3

```

135:
136:     if(!get_ramdisk(MINOR(i->rdev)) {
137:         return -ENXIO;
138:     }
139:
140:     switch(cmd) {
141:         case HDIO_GETGEO:
142:             if((errno = check_user_area(VERIFY_WRITE, (void *)arg, s
sizeof(struct hd_geometry)))) {
143:                 return errno;
144:             }
145:             geom = (struct hd_geometry *)arg;
146:             geom->heads = 63;
147:             geom->sectors = 16;
148:             geom->cylinders = rd_sizes[MINOR(i->rdev)] * 1024 / BPS;
149:             geom->cylinders /= (geom->heads * geom->sectors);
150:             geom->start = 0;
151:             break;
152:         case BLKRRPART:
153:             break;
154:         case BLKGETSIZE:
155:             if((errno = check_user_area(VERIFY_WRITE, (void *)arg, s
sizeof(unsigned int)))) {
156:                 return errno;
157:             }
158:             *(int *)arg = rd_sizes[MINOR(i->rdev)] * 2;
159:             break;
160:         default:
161:             return -EINVAL;
162:     }
163:     return 0;
164: }
165:
166: int ramdisk_lseek(struct inode *i, __off_t offset)
167: {
168:     return offset;
169: }
170:
171: void ramdisk_init(void)
172: {
173:     int n;
174:     struct ramdisk *ramdisk;
175:
176:     if(!_noramdisk) {
177:         for(n = 0; n < RAMDISK_MINORS; n++) {
178:             SET_MINOR(ramdisk_device.minors, n);
179:             rd_sizes[n] = _ramdisksize;
180:             ramdisk = get_ramdisk(n);
181:             memset_b((void *)ramdisk->addr, NULL, _ramdisksize * 102
4);
182:         }
183:         printk("ram0                -   %2d RAMdisk(s) of %dKB si
ze, %dKB blocksize\n", RAMDISK_MINORS, _ramdisksize, BLKSIZE_1K / 1024);
184:         register_device(BLK_DEV, &ramdisk_device);
185:     }
186: }

```


drivers/char/console.c

Page 2/19

```

68:
69: struct vconsole vc[NR_VCONSOLES + 1];
70: unsigned short int vcbuf[VC_BUF_SIZE];
71:
72: static struct fs_operations tty_driver_fsop = {
73:     0,
74:     0,
75:
76:     tty_open,
77:     tty_close,
78:     tty_read,
79:     tty_write,
80:     tty_ioctl,
81:     tty_lseek,
82:     NULL,                /* readdir */
83:     NULL,                /* mmap */
84:     tty_select,
85:
86:     NULL,                /* readlink */
87:     NULL,                /* followlink */
88:     NULL,                /* bmap */
89:     NULL,                /* lookup */
90:     NULL,                /* rmdir */
91:     NULL,                /* link */
92:     NULL,                /* unlink */
93:     NULL,                /* symlink */
94:     NULL,                /* mkdir */
95:     NULL,                /* mknod */
96:     NULL,                /* truncate */
97:     NULL,                /* create */
98:     NULL,                /* rename */
99:
100:    NULL,                /* read_block */
101:    NULL,                /* write_block */
102:
103:    NULL,                /* read_inode */
104:    NULL,                /* write_inode */
105:    NULL,                /* ialloc */
106:    NULL,                /* ifree */
107:    NULL,                /* statfs */
108:    NULL,                /* read_superblock */
109:    NULL,                /* remount_fs */
110:    NULL,                /* write_superblock */
111:    NULL,                /* release_superblock */
112: };
113:
114: static struct device tty_device = {
115:     "vconsole",
116:     KEYBOARD_IRQ,
117:     VCONSOLES_MAJOR,
118:     { 0, 0, 0, 0, 0, 0, 0, 0 },
119:     0,
120:     NULL,
121:     &tty_driver_fsop,
122: };
123:
124: static struct device console_device = {
125:     "console",
126:     KEYBOARD_IRQ,
127:     SYSCON_MAJOR,
128:     { 0, 0, 0, 0, 0, 0, 0, 0 },
129:     0,
130:     NULL,
131:     &tty_driver_fsop,
132: };
133:
134: unsigned short int ansi_color_table[] = {

```

drivers/char/console.c

Page 3/19

```

135:         COLOR_BLACK,
136:         COLOR_RED,
137:         COLOR_GREEN,
138:         COLOR_BROWN,
139:         COLOR_BLUE,
140:         COLOR_MAGENTA,
141:         COLOR_CYAN,
142:         COLOR_WHITE
143:     };
144:
145:     static void update_curpos(struct vconsole *vc)
146:     {
147:         unsigned short int curpos;
148:
149:         if(vc->has_focus) {
150:             curpos = (vc->y * vc->columns) + vc->x;
151:             outport_b(video_port + CRT_INDEX, CRT_CURSOR_POS_HI);
152:             outport_b(video_port + CRT_DATA, (curpos >> 8) & 0xFF);
153:             outport_b(video_port + CRT_INDEX, CRT_CURSOR_POS_LO);
154:             outport_b(video_port + CRT_DATA, (curpos & 0xFF));
155:         }
156:     }
157:
158:     static void show_cursor(int mode)
159:     {
160:         int status;
161:
162:         switch(mode) {
163:             case ON:
164:                 outport_b(video_port + CRT_INDEX, CRT_CURSOR_STR);
165:                 status = inport_b(video_port + CRT_DATA);
166:                 outport_b(video_port + CRT_DATA, status & CURSOR_MASK);
167:                 break;
168:             case OFF:
169:                 outport_b(video_port + CRT_INDEX, CRT_CURSOR_STR);
170:                 status = inport_b(video_port + CRT_DATA);
171:                 outport_b(video_port + CRT_DATA, status | CURSOR_DISABLE
);
172:                 break;
173:         }
174:     }
175:
176:     static void get_curpos(struct vconsole *vc)
177:     {
178:         unsigned short int curpos;
179:
180:         outport_b(video_port + CRT_INDEX, CRT_CURSOR_POS_HI);
181:         curpos = inport_b(video_port + CRT_DATA) << 8;
182:         outport_b(video_port + CRT_INDEX, CRT_CURSOR_POS_LO);
183:         curpos |= inport_b(video_port + CRT_DATA);
184:
185:         vc->x = curpos % vc->columns;
186:         vc->y = curpos / vc->columns;
187:     }
188:
189:     static void adjust(struct vconsole *vc, int x, int y)
190:     {
191:         if(x < 0) {
192:             x = 0;
193:         }
194:         if(x >= vc->columns) {
195:             x = vc->columns - 1;
196:         }
197:         if(y < 0) {
198:             y = 0;
199:         }
200:         if(y >= vc->lines) {

```

drivers/char/console.c

Page 4/19

```

201:             y = vc->lines - 1;
202:         }
203:         vc->x = x;
204:         vc->y = y;
205:     }
206:
207:     static void delete_char(struct vconsole *vc)
208:     {
209:         int n, from;
210:
211:         from = (vc->y * vc->columns) + vc->x;
212:         n = vc->x;
213:         while(++n < vc->columns) {
214:             memcpy_w(vc->vidmem + from, vc->vidmem + from + 1, 1);
215:             from++;
216:         }
217:         memset_w(vc->vidmem + from, BLANK_MEM, 1);
218:     }
219:
220:     static void insert_char(struct vconsole *vc)
221:     {
222:         int n, from;
223:         unsigned short int tmp, last_char;
224:
225:         from = (vc->y * vc->columns) + vc->x;
226:         n = vc->x + 1;
227:         last_char = BLANK_MEM;
228:         while(++n < vc->columns) {
229:             memcpy_w(&tmp, vc->vidmem + from, 1);
230:             memset_w(vc->vidmem + from, last_char, 1);
231:             last_char = tmp;
232:             from++;
233:         }
234:     }
235:
236:     /* FIXME: scrolling inside a text window (ESC[5;8r) is not supported yet */
237:     static void scroll_screen(struct vconsole *vc, int top, int mode)
238:     {
239:         int n, count, from;
240:
241:         switch(mode) {
242:             case SCROLL_DOWN:
243:                 count = (vc->columns * (vc->lines - top - 1)) * 2;
244:                 from = top * vc->columns;
245:                 top = (top + 1) * vc->columns;
246:                 memcpy_b(vc->vidmem + from, vc->vidmem + top, count);
247:                 memset_w(vc->vidmem + from + (count / 2), BLANK_MEM, (to
p
 * 2) / sizeof(unsigned short int));
248:                 break;
249:             case SCROLL_UP:
250:                 count = vc->columns * 2;
251:                 for(n = vc->lines - 1; n >= top; n--) {
252:                     memcpy_b(vc->vidmem + (vc->columns * (n + 1)), v
c->vidmem + (vc->columns * n), count);
253:                 }
254:                 memset_w(vc->vidmem + (top * vc->columns), BLANK_MEM, co
unt / sizeof(unsigned short int));
255:                 break;
256:             }
257:         return;
258:     }
259:
260:     static void cr(struct vconsole *vc)
261:     {
262:         vc->x = 0;
263:     }
264:

```

drivers/char/console.c

Page 5/19

```

265: static void lf(struct vconsole *vc)
266: {
267:     if(vc->y == vc->lines) {
268:         scroll_screen(vc, 0, SCROLL_DOWN);
269:     } else {
270:         vc->y++;
271:     }
272: }
273:
274: static void ri(struct vconsole *vc)
275: {
276:     if(vc->y == 0) {
277:         scroll_screen(vc, vc->y, SCROLL_UP);
278:     } else {
279:         vc->y--;
280:     }
281: }
282:
283: static void csi_J(struct vconsole *vc, int mode)
284: {
285:     int from, count;
286:
287:     switch(mode) {
288:         case CSI_J_CUR2END: /* Erase Down <ESC>[J */
289:             from = (vc->y * vc->columns) + vc->x;
290:             count = (SCREEN_SIZE - from) / sizeof(unsigned short int
);
291:             break;
292:         case CSI_J_STA2CUR: /* Erase Up <ESC>[1J */
293:             from = 0;
294:             count = (((vc->y * vc->columns) + vc->x) * 2) / sizeof(u
nsigned short int);
295:             break;
296:         case CSI_J_SCREEN: /* Erase Screen <ESC>[2J */
297:             from = 0;
298:             count = SCREEN_SIZE / sizeof(unsigned short int);
299:             break;
300:         default:
301:             return;
302:     }
303:     memset_w(vc->vidmem + from, vc->color_attr, count);
304: }
305:
306: static void csi_K(struct vconsole *vc, int mode)
307: {
308:     int from, count;
309:
310:     switch(mode) {
311:         case CSI_K_CUR2END: /* Erase End of Line <ESC>[K */
312:             from = (vc->y * vc->columns) + vc->x;
313:             count = ((vc->columns - vc->x) * 2) / sizeof(unsigned sh
ort int);
314:             break;
315:         case CSI_K_STA2CUR: /* Erase Start of Line <ESC>[1K */
316:             from = vc->y * vc->columns;
317:             count = (vc->x * 2) / sizeof(unsigned short int);
318:             break;
319:         case CSI_K_LINE: /* Erase Line <ESC>[2K */
320:             from = vc->y * vc->columns;
321:             count = (vc->columns * 2) / sizeof(unsigned short int);
322:             break;
323:         default:
324:             return;
325:     }
326:     memset_w(vc->vidmem + from, vc->color_attr, count);
327: }
328:

```

drivers/char/console.c

Page 6/19

```

329: static void csi_L(struct vconsole *vc, int count)
330: {
331:     if(count > vc->lines) {
332:         count = vc->lines;
333:     }
334:     while(count--> 0) {
335:         scroll_screen(vc, vc->y, SCROLL_UP);
336:     }
337: }
338:
339: static void csi_M(struct vconsole *vc, int count)
340: {
341:     if(count > vc->lines) {
342:         count = vc->lines;
343:     }
344:     while(count--> 0) {
345:         scroll_screen(vc, vc->y, SCROLL_DOWN);
346:     }
347: }
348:
349: static void csi_P(struct vconsole *vc, int count)
350: {
351:     if(count > vc->columns) {
352:         count = vc->columns;
353:     }
354:     while(count--> 0) {
355:         delete_char(vc);
356:     }
357: }
358:
359: static void csi_at(struct vconsole *vc, int count)
360: {
361:     if(count > vc->columns) {
362:         count = vc->columns;
363:     }
364:     while(count--> 0) {
365:         insert_char(vc);
366:     }
367: }
368:
369: static void default_color_attr(struct vconsole *vc)
370: {
371:     vc->color_attr = DEF_MODE;
372:     vc->bold = 0;
373:     vc->underline = 0;
374:     vc->blink = 0;
375:     vc->reverse = 0;
376: }
377:
378: static void csi_m(struct vconsole *vc)
379: {
380:     if(vc->reverse) {
381:         vc->color_attr = ((vc->color_attr & 0x7000) >> 4) | ((vc->color_
attr & 0x0700) << 4) | (vc->color_attr & 0x8800);
382:     }
383:
384:     switch(vc->parmv1) {
385:         case COLOR_NORMAL:
386:             default_color_attr(vc);
387:             break;
388:         case COLOR_BOLD:
389:             vc->bold = 1;
390:             break;
391:         case COLOR_BOLD_OFF:
392:             vc->bold = 0;
393:             break;
394:         case COLOR_BLINK:

```

drivers/char/console.c

Page 7/19

```

395:             vc->blink = 1;
396:             break;
397:         case COLOR_REVERSE:
398:             vc->reverse = 1;
399:             break;
400:         case 21:
401:         case 22:
402:             vc->bold = 1;
403:             break;
404:         case 25:
405:             vc->blink = 0;
406:             break;
407:         case 27:
408:             vc->reverse = 0;
409:             break;
410:     }
411:     if(vc->parmv1 >= 30 && vc->parmv1 <= 37) {
412:         vc->color_attr = (vc->color_attr & 0xF8FF) | (ansi_color_table[v
c->parmv1 - 30]);
413:     }
414:     if(vc->parmv1 >= 40 && vc->parmv1 <= 47) {
415:         vc->color_attr = (vc->color_attr & 0x8FFF) | ((ansi_color_table[
vc->parmv1 - 40]) << 4);
416:     }
417:     if(vc->parmv2 >= 30 && vc->parmv2 <= 37) {
418:         vc->color_attr = (vc->color_attr & 0xF8FF) | (ansi_color_table[v
c->parmv2 - 30]);
419:     }
420:     if(vc->parmv2 >= 40 && vc->parmv2 <= 47) {
421:         vc->color_attr = (vc->color_attr & 0x8FFF) | ((ansi_color_table[
vc->parmv2 - 40]) << 4);
422:     }
423:     if(vc->bold) {
424:         vc->color_attr |= 0x0800;
425:     }
426:     if(vc->blink) {
427:         vc->color_attr |= 0x8000;
428:     }
429:     if(vc->reverse) {
430:         vc->color_attr = ((vc->color_attr & 0x7000) >> 4) | ((vc->color_
attr & 0x0700) << 4) | (vc->color_attr & 0x8800);
431:     }
432: }
433:
434: static void init_vt(struct vconsole *vc)
435: {
436:     vc->vt_mode.mode = VT_AUTO;
437:     vc->vt_mode.waitv = 0;
438:     vc->vt_mode.relsig = 0;
439:     vc->vt_mode.acqsig = 0;
440:     vc->vt_mode.frsig = 0;
441:     vc->vc_mode = KD_TEXT;
442:     vc->tty->pid = 0;
443:     vc->switchto_tty = -1;
444: }
445:
446: static void insert_seq(struct tty *tty, char *buf, int count)
447: {
448:     while(count--) {
449:         tty_queue_putchar(tty, &tty->read_q, *(buf++));
450:     }
451:     tty->input(tty);
452: }
453:
454: static void echo_char(struct vconsole *vc, unsigned char *buf, unsigned int coun
t)
455: {

```

drivers/char/console.c

Page 8/19

```

456:         int n;
457:         unsigned char ch;
458:
459:         if(vc->has_focus) {
460:             if(buf_top) {
461:                 vconsole_restore(vc);
462:                 show_cursor(ON);
463:                 buf_top = 0;
464:             }
465:         }
466:
467:         while(count--) {
468:             ch = *buf++;
469:             if(ch == NULL) {
470:                 continue;
471:
472:             } else if(ch == '\b') {
473:                 if(vc->x) {
474:                     vc->x--;
475:                 }
476:
477:             } else if(ch == '\a') {
478:                 vconsole_beep();
479:
480:             } else if(ch == '\r') {
481:                 cr(vc);
482:
483:             } else if(ch == '\n') {
484:                 cr(vc);
485:                 vc->y++;
486:                 if(vc->has_focus) {
487:                     buf_y++;
488:                 }
489:
490:             } else if(ch == '\t') {
491:                 while(vc->x < (vc->columns - 1)) {
492:                     if(vc->tab_stop[+vc->x]) {
493:                         break;
494:                     }
495:                 }
496:                 /* vc->x += TAB_SIZE - (vc->x % TAB_SIZE); */
497:                 vc->check_x = 1;
498:
499:             } else {
500:                 if((vc->x == vc->columns - 1) && vc->check_x) {
501:                     vc->x = 0;
502:                     vc->y++;
503:                     if(vc->has_focus) {
504:                         buf_y++;
505:                     }
506:                 }
507:                 if(vc->y >= vc->lines) {
508:                     scroll_screen(vc, 0, SCROLL_DOWN);
509:                     vc->y--;
510:                 }
511:                 ch = iso8859[ch];
512:                 vc->vidmem[(vc->y * vc->columns) + vc->x] = vc->color_at
tr | ch;
513:                 if(vc->has_focus) {
514:                     vcbuf[(buf_y * vc->columns) + vc->x] = vc->color
_attr | ch;
515:                 }
516:                 if(vc->x < vc->columns - 1) {
517:                     vc->check_x = 0;
518:                     vc->x++;
519:                 } else {
520:                     vc->check_x = 1;

```


drivers/char/console.c

Page 9/19

```

521:         }
522:     }
523:     if(vc->y >= vc->lines) {
524:         scroll_screen(vc, 0, SCROLL_DOWN);
525:         vc->y--;
526:     }
527:     if(vc->has_focus) {
528:         if(buf_y >= VC_BUF_LINES) {
529:             memcpy_b(vcbuf, vcbuf + SCREEN_COLS, VC_BUF_SIZE
- (SCREEN_COLS * 2));
530:             for(n = (SCREEN_COLS * (VC_BUF_LINES - 1)); n <
(SCREEN_COLS * VC_BUF_LINES); n++) {
531:                 vcbuf[n] = BLANK_MEM;
532:             }
533:             buf_y--;
534:         }
535:     }
536: }
537: update_curpos(vc);
538: }
539:
540: void vconsole_reset(struct tty *tty)
541: {
542:     int n;
543:     struct vconsole *vc;
544:
545:     vc = (struct vconsole *)tty->driver_data;
546:
547:     vc->lines = SCREEN_LINES;
548:     vc->columns = SCREEN_COLS;
549:     vc->check_x = 0;
550:     vc->led_status = 0;
551:     set_leds(vc->led_status);
552:     vc->scrlock = vc->numlock = vc->capslock = 0;
553:     vc->esc = vc->sbracket = vc->semicolon = vc->question = 0;
554:     vc->parmv1 = vc->parmv2 = 0;
555:     default_color_attr(vc);
556:     vc->insert_mode = 0;
557:     vc->saved_x = vc->saved_y = 0;
558:
559:     for(n = 0; n < MAX_TAB_COLS; n++) {
560:         if(!(n % TAB_SIZE)) {
561:             vc->tab_stop[n] = 1;
562:         } else {
563:             vc->tab_stop[n] = 0;
564:         }
565:     }
566:
567:     termios_reset(tty);
568:     vc->tty->winsize.ws_row = vc->lines;
569:     vc->tty->winsize.ws_col = vc->columns;
570:     vc->tty->winsize.ws_xpixel = 0;
571:     vc->tty->winsize.ws_ypixel = 0;
572:     vc->tty->lnext = 0;
573:
574:     init_vt(vc);
575:     vc->blanked = 0;
576:     update_curpos(vc);
577: }
578:
579: void vconsole_write(struct tty *tty)
580: {
581:     int n;
582:     unsigned char ch;
583:     int numeric;
584:     struct vconsole *vc;
585:

```

drivers/char/console.c

Page 10/19

```

586:         vc = (struct vconsole *)tty->driver_data;
587:
588:         if(buf_top) {
589:             vconsole_restore(vc);
590:             buf_top = 0;
591:             show_cursor(ON);
592:             update_curpos(vc);
593:         }
594:
595:         numeric = 0;
596:
597:         while(!vc->scrlock && tty->write_q.count > 0) {
598:             ch = tty_queue_getchar(&tty->write_q);
599:
600:             if(vc->esc) {
601:                 if(vc->sbracket) {
602:                     if(IS_NUMERIC(ch)) {
603:                         numeric = 1;
604:                         if(vc->semicolon) {
605:                             vc->parmv2 *= 10;
606:                             vc->parmv2 += ch - '0';
607:                         } else {
608:                             vc->parmv1 *= 10;
609:                             vc->parmv1 += ch - '0';
610:                         }
611:                         continue;
612:                     }
613:                     switch(ch) {
614:                         case ';':
615:                             vc->semicolon = 1;
616:                             vc->parmv2 = 0;
617:                             continue;
618:                         case '?':
619:                             vc->question = 1;
620:                             continue;
621:                         case 'A':          /* Cursor Up <ESC>[ {COUN
T}A */
622:                             vc->parmv1 = !vc->parmv1 ? 1 : v
c->parmv1;
623:                             adjust(vc, vc->x, vc->y - vc->pa
rmv1);
624:                             CSE;
625:                             continue;
626:                         case 'B':          /* Cursor Down <ESC>[ {CO
UNT}B */
627:                             vc->parmv1 = !vc->parmv1 ? 1 : v
c->parmv1;
628:                             adjust(vc, vc->x, vc->y + vc->pa
rmv1);
629:                             CSE;
630:                             continue;
631:                         case 'C':          /* Cursor Forward <ESC>[
{COUNT}C */
632:                             vc->parmv1 = !vc->parmv1 ? 1 : v
c->parmv1;
633:                             adjust(vc, vc->x + vc->parmv1, v
c->y);
634:                             CSE;
635:                             continue;
636:                         case 'D':          /* Cursor Backward <ESC>
[ {COUNT}D */
637:                             vc->parmv1 = !vc->parmv1 ? 1 : v
c->parmv1;
638:                             adjust(vc, vc->x - vc->parmv1, v
c->y);
639:                             CSE;
640:                             continue;

```

drivers/char/console.c

Page 11/19

```

641:
ESC>[COUNT]E */
642:
c->parmv1;
643:
);
644:
645:
646:
s) <ESC>[COUNT]F */
647:
c->parmv1;
648:
);
649:
650:
651:
ition <ESC>[NUM1]G */
652:
653:
rmv1 - 1 : vc->parmv1;
654:
655:
656:
657:
W};{COLUMN}H */
658:
<ESC>[ROW];{COLUMN}F */
659:
rmv1 - 1 : vc->parmv1;
660:
rmv2 - 1 : vc->parmv2;
661:
1);
662:
663:
664:
) <ESC>[J */
665:
666:
667:
668:
f/) Line <ESC>[K */
669:
670:
671:
672:
{COUNT}L */
673:
c->parmv1;
674:
675:
676:
677:
{COUNT}M */
678:
c->parmv1;
679:
680:
681:
682:
ESC>[COUNT]P */
683:
c->parmv1;
684:
685:
686:

```

```

case 'E':          /* Cursor Next Line(s) <
vc->parmv1 = !vc->parmv1 ? 1 : v
adjust(vc, 0, vc->y + vc->parmv1
CSE;
continue;
case 'F':          /* Cursor Previous Line(
vc->parmv1 = !vc->parmv1 ? 1 : v
adjust(vc, 0, vc->y - vc->parmv1
CSE;
continue;
case 'G':          /* Cursor Horizontal Pos
case '^':
vc->parmv1 = vc->parmv1 ? vc->pa
adjust(vc, vc->parmv1, vc->y);
CSE;
continue;
case 'H':          /* Cursor Home <ESC>[{RO
case 'f':          /* Force Cursor Position
vc->parmv1 = vc->parmv1 ? vc->pa
vc->parmv2 = vc->parmv2 ? vc->pa
adjust(vc, vc->parmv2, vc->parmv
CSE;
continue;
case 'J':          /* Erase (Down/Up/Screen
csi_J(vc, vc->parmv1);
CSE;
continue;
case 'K':          /* Erase (End of/Start o
csi_K(vc, vc->parmv1);
CSE;
continue;
case 'L':          /* Insert Line(s) <ESC>[
vc->parmv1 = !vc->parmv1 ? 1 : v
csi_L(vc, vc->parmv1);
CSE;
continue;
case 'M':          /* Delete Line(s) <ESC>[
vc->parmv1 = !vc->parmv1 ? 1 : v
csi_M(vc, vc->parmv1);
CSE;
continue;
case 'P':          /* Delete Character(s) <
vc->parmv1 = !vc->parmv1 ? 1 : v
csi_P(vc, vc->parmv1);
CSE;
continue;

```

drivers/char/console.c

Page 12/19

```

687:
ESC>[COUNT]@ */
688:
c->parmv1;
689:
690:
691:
692:
C>[c */
693:
694:
7);
695:
696:
697:
698:
ion <ESC>[NUM1]d */
699:
rmv1 - 1 : vc->parmv1;
700:
701:
702:
703:
704:
705:
C>[g */
706:
>x] = 0;
707:
708:
s <ESC>[3g */
709:
AX_TAB_COLS; n++)
710:
stop[n] = 0;
711:
712:
713:
714:
715:
716:
717:
718:
ch Cursor Visible <ESC>[?25h */
719:
sor(ON);
720:
721:
722:
rt_mode = ON; /* not used */
723:
724:
725:
726:
727:
728:
729:
730:
731:
ch Cursor Invisible <ESC>[?25l */
732:
sor(OFF);
733:
734:
735:
rt_mode = OFF; /* not used */
736:

```

```

case '@': /* Insert Character(s) <
vc->parmv1 = !vc->parmv1 ? 1 : v
csi_at(vc, vc->parmv1);
CSE;
continue;
case 'c': /* Query Device Code <ES
if(!numeric) {
insert_seq(tty, VT100ID,
}
CSE;
continue;
case 'd': /* Cursor Vertical Posit
vc->parmv1 = vc->parmv1 ? vc->pa
adjust(vc, vc->x, vc->parmv1);
CSE;
continue;
case 'g':
switch(vc->parmv1) {
case 0: /* Clear Tab <ES
vc->tab_stop[vc-
break;
case 3: /* Clear All Tab
for(n = 0; n < M
vc->tab_
break;
}
CSE;
continue;
case 'h':
if(vc->question) {
switch(vc->parmv1) {
case 25: /* Swit
show_cur
break;
case 4:
vc->inse
break;
}
}
CSE;
continue;
case 'l':
if(vc->question) {
switch(vc->parmv1) {
case 25: /* Swit
show_cur
break;
case 4:
vc->inse
break;
}
}

```

drivers/char/console.c

Page 13/19

```

737:                                     }
738:                                     }
739:                                     CSE;
740:                                     continue;
741: case 'm':                               /* Character Attributes
<ESC>{NUM1}{NUM2}m */
742:                                     csi_m(vc);
743:                                     CSE;
744:                                     continue;
745: case 'n':
746:     if(!vc->question) {
747:         switch(vc->parmv1) {
748:             case 5: /* Query
Device Status <ESC>[5n */
749:                                     insert_s
eq(tty, DEVICE_OK, 4);
750:                                     break;
751:             case 6: /* Query
Cursor Position <ESC>[6n */
752:                                     {
753:                                     }
char curpos[8];
754:
char len;
755:
len = sprintf(curpos, "\033[%d;%dR", vc->y, vc->x);
756:
insert_seq(tty, curpos, len);
757:                                     }
758:                                     break;
759:                                     }
760:                                     }
761:                                     CSE;
762:                                     continue;
763: case 'r':                               /* Scroll Screen <ESC>[r
/ <ESC>[start];end]r */
764:                                     if(!vc->parmv1) {
765:                                         vc->parmv1++;
766:                                     }
767:                                     if(!vc->parmv2) {
768:                                         vc->parmv2 = SCREEN_LINE
S;
769:                                     }
770:                                     if(vc->parmv1 < vc->parmv2 && vc
->parmv2 <= SCREEN_LINES) {
771:                                         /* FIXME: text window no
t supported yet */
772:                                         adjust(vc, 0, 0);
773:                                     }
774:                                     CSE;
775:                                     continue;
776: case 's':                               /* Save Cursor <ESC>[s *
/
777:                                     vc->saved_x = vc->x;
778:                                     vc->saved_y = vc->y;
779:                                     CSE;
780:                                     continue;
781: case 'u':                               /* Restore Cursor <ESC>[
u */
782:                                     vc->x = vc->saved_x;
783:                                     vc->y = vc->saved_y;
784:                                     CSE;
785:                                     continue;
786: default:
787:                                     CSE;
788:                                     break;
789:                                     }

```

drivers/char/console.c

Page 14/19

```

790:             } else {
791:                 switch(ch) {
792:                     case '[':
793:                         vc->sbracket = 1;
794:                         vc->:semicolon = 0;
795:                         vc->question = 0;
796:                         vc->parmv1 = vc->parmv2 = 0;
797:                         continue;
798:                     case '7':          /* Save Cursor & Attrs <
ESC>7 */
799:                         vc->saved_x = vc->x;
800:                         vc->saved_y = vc->y;
801:                         CSE;
802:                         continue;
803:                     case '8':          /* Restore Cursor & Attr
s <ESC>8 */
804:                         vc->x = vc->saved_x;
805:                         vc->y = vc->saved_y;
806:                         CSE;
807:                         continue;
808:                     case 'D':          /* Scroll Down <ESC>D */
809:                         lf(vc);
810:                         CSE;
811:                         continue;
812:                     case 'E':          /* Move To Next Line <ES
C>E */
813:                         cr(vc);
814:                         lf(vc);
815:                         CSE;
816:                         continue;
817:                     case 'H':          /* Set Tab <ESC>H */
818:                         vc->tab_stop[vc->x] = 1;
819:                         CSE;
820:                         continue;
821:                     case 'M':          /* Scroll Up <ESC>M */
822:                         ri(vc);
823:                         CSE;
824:                         continue;
825:                     case 'Z':          /* Identify Terminal <ES
C>Z */
826:                         insert_seq(tty, VT100ID, 7);
827:                         CSE;
828:                         continue;
829:                     case 'c':          /* Reset Device <ESC>c *
/
830:                         vconsole_reset(vc->tty);
831:                         vc->x = vc->y = 0;
832:                         csi_J(vc, CSI_J_SCREEN);
833:                         CSE;
834:                         continue;
835:                     default:
836:                         CSE;
837:                         break;
838:                 }
839:             }
840:         }
841:         switch(ch) {
842:             case '\033':
843:                 vc->esc = 1;
844:                 vc->sbracket = 0;
845:                 vc->:semicolon = 0;
846:                 vc->question = 0;
847:                 vc->parmv1 = vc->parmv2 = 0;
848:                 continue;
849:             default:
850:                 echo_char(vc, &ch, 1);
851:                 continue;

```

drivers/char/console.c

Page 15/19

```

852:         }
853:     }
854:     if(vc->vc_mode != KD_GRAPHICS) {
855:         update_curpos(vc);
856:     }
857:     wakeup(&tty->write_q);
858: }
859:
860: void vconsole_select(int new_cons)
861: {
862:     new_cons++;
863:     if(current_cons != new_cons) {
864:         if(vc[current_cons].vt_mode.mode == VT_PROCESS) {
865:             if(!kill_pid(vc[current_cons].tty->pid, vc[current_cons]
.vt_mode.acqsig)) {
866:                 vc[current_cons].switchto_tty = new_cons;
867:                 return;
868:             }
869:             init_vt(&vc[current_cons]);
870:         }
871:         if(vc[current_cons].vc_mode == KD_GRAPHICS) {
872:             return;
873:         }
874:         vconsole_select_final(new_cons);
875:     }
876: }
877:
878: void vconsole_select_final(int new_cons)
879: {
880:     if(current_cons != new_cons) {
881:         if(vc[new_cons].vt_mode.mode == VT_PROCESS) {
882:             if(kill_pid(vc[new_cons].tty->pid, vc[new_cons].vt_mode.
acqsig)) {
883:                 init_vt(&vc[new_cons]);
884:             }
885:         }
886:         if(buf_top) {
887:             vconsole_restore(&vc[current_cons]);
888:             buf_top = 0;
889:             update_curpos(&vc[current_cons]);
890:         }
891:         if(vc[current_cons].vc_mode != KD_GRAPHICS) {
892:             vconsole_save(&vc[current_cons]);
893:         }
894:         vc[current_cons].vidmem = vc[current_cons].scrbuf;
895:         vc[current_cons].has_focus = 0;
896:         vc[new_cons].vidmem = video_base_address;
897:         vc[new_cons].has_focus = 1;
898:         vconsole_restore(&vc[new_cons]);
899:         current_cons = new_cons;
900:         set_leds(vc[current_cons].led_status);
901:         update_curpos(&vc[current_cons]);
902:
903:         buf_y = vc[current_cons].y;
904:         buf_top = 0;
905:         memset_w(vcbuf, BLANK_MEM, VC_BUF_SIZE / sizeof(unsigned short i
nt));
906:         memcpy_b(vcbuf, vc[current_cons].vidmem, SCREEN_SIZE);
907:         show_cursor(ON);
908:     }
909: }
910:
911: void vconsole_save(struct vconsole *vc)
912: {
913:     memcpy_b(vc->scrbuf, vc->vidmem, SCREEN_SIZE);
914: }
915:

```

drivers/char/console.c

Page 16/19

```

916: void vconsole_restore(struct vconsole *vc)
917: {
918:     memcpy_b(vc->vidmem, vc->scrbuf, SCREEN_SIZE);
919: }
920:
921: void vconsole_buffer_scl(int mode)
922: {
923:     int buf_line = buf_y;
924:
925:     if(buf_line <= SCREEN_LINES) {
926:         return;
927:     }
928:     if(mode == VC_BUF_UP) {
929:         if(buf_top < 0) {
930:             return;
931:         }
932:         if(!buf_top) {
933:             vconsole_save(&vc[current_cons]);
934:             buf_top = (buf_line - SCREEN_LINES + 1) * SCREEN_COLS;
935:             buf_top -= (SCREEN_LINES / 2) * SCREEN_COLS;
936:         } else {
937:             buf_top -= (SCREEN_LINES / 2) * SCREEN_COLS;
938:         }
939:         if(buf_top < 0) {
940:             buf_top = 0;
941:         }
942:         memcpy_b(vc[current_cons].vidmem, vcbuf + buf_top, SCREEN_SIZE);
943:         if(!buf_top) {
944:             buf_top = -1;
945:         }
946:         show_cursor(OFF);
947:         return;
948:     }
949:     if(mode == VC_BUF_DOWN) {
950:         if(!buf_top) {
951:             return;
952:         }
953:         if(buf_top == buf_line * SCREEN_COLS) {
954:             return;
955:         }
956:         if(buf_top < 0) {
957:             buf_top = 0;
958:         }
959:         buf_top += (SCREEN_LINES / 2) * SCREEN_COLS;
960:         if(buf_top >= (buf_line - SCREEN_LINES + 1) * SCREEN_COLS) {
961:             vconsole_restore(&vc[current_cons]);
962:             buf_top = 0;
963:             show_cursor(ON);
964:             update_curpos(&vc[current_cons]);
965:             return;
966:         }
967:         memcpy_b(vc[current_cons].vidmem, vcbuf + buf_top, SCREEN_SIZE);
968:         return;
969:     }
970: }
971:
972: void blank_screen(struct vconsole *vc)
973: {
974:     if(vc->blanked) {
975:         return;
976:     }
977:     vconsole_save(vc);
978:     memset_w(vc->vidmem, BLANK_MEM, SCREEN_SIZE / sizeof(short int));
979:     vc->blanked = 1;
980:     show_cursor(OFF);
981: }
982:

```


drivers/char/console.c

Page 17/19

```

983: void unblank_screen(struct vconsole *vc)
984: {
985:     if(!vc->blanked) {
986:         return;
987:     }
988:     vconsole_restore(vc);
989:     vc->blanked = 0;
990:     show_cursor(ON);
991: }
992:
993: void screen_on(void)
994: {
995:     unsigned long int flags;
996:     struct callout_req creq;
997:
998:     if(screen_is_off) {
999:         SAVE_FLAGS(flags); CLI();
1000:         inport_b(INPUT_STAT1);
1001:         inport_b(0x3BA);
1002:         outport_b(ATTR_CONTROLLER, ATTR_CONTROLLER_PAS);
1003:         RESTORE_FLAGS(flags);
1004:     }
1005:     creq.fn = screen_off;
1006:     creq.arg = 0;
1007:     add_callout(&creq, BLANK_INTERVAL);
1008: }
1009:
1010: void screen_off(unsigned int arg)
1011: {
1012:     unsigned long int flags;
1013:
1014:     screen_is_off = 1;
1015:     SAVE_FLAGS(flags); CLI();
1016:     inport_b(INPUT_STAT1);
1017:     inport_b(0x3BA);
1018:     outport_b(ATTR_CONTROLLER, 0);
1019:     RESTORE_FLAGS(flags);
1020: }
1021:
1022: void vconsole_start(struct tty *tty)
1023: {
1024:     struct vconsole *vc;
1025:
1026:     vc = (struct vconsole *)tty->driver_data;
1027:     if(!vc->scrlock) {
1028:         return;
1029:     }
1030:     vc->led_status &= ~SCLBIT;
1031:     vc->scrlock = 0;
1032:     set_leds(vc->led_status);
1033: }
1034:
1035: void vconsole_stop(struct tty *tty)
1036: {
1037:     struct vconsole *vc;
1038:
1039:     vc = (struct vconsole *)tty->driver_data;
1040:     if(vc->scrlock) {
1041:         return;
1042:     }
1043:     vc->led_status |= SCLBIT;
1044:     vc->scrlock = 1;
1045:     set_leds(vc->led_status);
1046: }
1047:
1048: void vconsole_beep(void)
1049: {

```

drivers/char/console.c

Page 18/19

```

1050:         struct callout_req creq;
1051:
1052:         pit_beep_on();
1053:         creq.fn = pit_beep_off;
1054:         creq.arg = 0;
1055:         add_callout(&creq, HZ / 8);
1056:     }
1057:
1058: void vconsole_deltab(struct tty *tty)
1059: {
1060:     unsigned short int col, n;
1061:     unsigned char count;
1062:     struct vconsole *vc;
1063:     struct cblock *cb;
1064:     unsigned char ch;
1065:
1066:     vc = (struct vconsole *)tty->driver_data;
1067:     cb = tty->cooked_q.head;
1068:     col = count = 0;
1069:
1070:     while(cb) {
1071:         for(n = 0; n < cb->end_off; n++) {
1072:             if(n >= cb->start_off) {
1073:                 ch = cb->data[n];
1074:                 if(ch == '\t') {
1075:                     while(!vc->tab_stop[++col]);
1076:                 } else {
1077:                     col++;
1078:                     if(ISCNTRL(ch) && !ISSPACE(ch) && tty->t
ermios.c_lflag & ECHOCTL) {
1079:                         col++;
1080:                     }
1081:                 }
1082:                 col %= vc->columns;
1083:             }
1084:         }
1085:         cb = cb->next;
1086:     }
1087:     count = vc->x - col;
1088:
1089:     while(count--> 0) {
1090:         tty_queue_putchar(tty, &tty->write_q, '\b');
1091:     }
1092: }
1093:
1094: void console_flush_log_buf(char *buffer, unsigned int count)
1095: {
1096:     char *b;
1097:     struct tty *tty;
1098:
1099:     tty = get_tty(_syscondev);
1100:     b = buffer;
1101:
1102:     while(count) {
1103:         if(tty_queue_putchar(tty, &tty->write_q, *b) < 0) {
1104:             tty->output(tty);
1105:             continue;
1106:         }
1107:         count--;
1108:         b++;
1109:     }
1110:     tty->output(tty);
1111: }
1112:
1113: void vconsole_init(void)
1114: {
1115:     int n;

```

drivers/char/console.c

Page 19/19

```

1116:         struct tty *tty;
1117:
1118:     printk("console");
1119:     if((*unsigned short int *)0x410 & 0x30) == 0x30) {
1120:         /* monochrome = 0x30 */
1121:         video_base_address = (void *)MONO_ADDR;
1122:         video_port = MONO_6845_ADDR;
1123:         printk(" 0x%04X-0x%04X - VGA monochrome 80x25", video_po
rt, video_port + 1);
1124:     } else {
1125:         /* color = 0x00 || 0x20 */
1126:         video_base_address = (void *)COLOR_ADDR;
1127:         video_port = COLOR_6845_ADDR;
1128:         printk(" 0x%04X-0x%04X - VGA color 80x25", video_port, v
ideo_port + 1);
1129:     }
1130:
1131:     printk(" (%d virtual consoles)\n", NR_VCONSOLES);
1132:     screen_on();
1133:
1134:     for(n = 1; n < NR_VCONSOLES + 1; n++) {
1135:         if(!register_tty(MKDEV(VCONSOLES_MAJOR, n))) {
1136:             tty = get_tty(MKDEV(VCONSOLES_MAJOR, n));
1137:             tty->driver_data = (void *)&vc[n];
1138:             tty->stop = vconsole_stop;
1139:             tty->start = vconsole_start;
1140:             tty->deltab = vconsole_deltab;
1141:             tty->reset = vconsole_reset;
1142:             tty->input = do_cook;
1143:             tty->output = vconsole_write;
1144:             vc[n].tty = tty;
1145:             vc[n].vidmem = vc[n].scrbuf;
1146:             memset_w(vc[n].scrbuf, BLANK_MEM, SCREEN_SIZE / sizeof(s
hort int));
1147:             vconsole_reset(tty);
1148:             termios_reset(tty);
1149:             tty_queue_init(tty);
1150:         }
1151:     }
1152:     current_cons = 1;
1153:     vc[current_cons].vidmem = video_base_address;
1154:     vc[current_cons].has_focus = 1;
1155:     // vc[current_cons].count++; /* XXX */
1156:
1157:     /* memset_b(vc[current_cons].vidmem, BLANK_MEM, SCREEN_SIZE); */
1158:     memcpy_b(vcbuf, vc[current_cons].vidmem, SCREEN_SIZE);
1159:
1160:     get_curpos(&vc[current_cons]);
1161:     update_curpos(&vc[current_cons]);
1162:     buf_y = vc[current_cons].y;
1163:     buf_top = 0;
1164:
1165:     register_device(CHR_DEV, &console_device);
1166:     register_device(CHR_DEV, &tty_device);
1167:     register_console(console_flush_log_buf);
1168: }

```

drivers/char/defkeymap.c

```

1: /*
2:  * fiwix/drivers/char/defkeymap.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/keyboard.h>
9: #include <fiwix/string.h>
10:
11: #define BS      127      /* backspace */
12:
13: __key_t keymap[NR_MODIFIERS * NR_SCODES] = {
14: /*
15:  * Standard US keyboard (default keymap) with 16 modifiers
16:  *
17:  *
18:  *
19:  *
20:  * =====
21:  * 00 - NULL */
22:  * 01 - ESC */
23:  * 02 - 1 */
24:  * 03 - 2 */
25:  * 04 - 3 */
26:  * 05 - 4 */
27:  * 06 - 5 */
28:  * 07 - 6 */
29:  * 08 - 7 */
30:  * 09 - 8 */
31:  * 10 - 9 */
32:  * 11 - 0 */
33:  * 12 - _ */
34:  * 13 - =+ */
35:  * 14 - BS */
36:  * 15 - TAB */
37:  * 16 - q */
38:  * 17 - w */
39:  * 18 - e */
40:  * 19 - r */
41:  * 20 - t */

```

drivers/char/defkeymap.c

```

42: /* 21 - y */ L('y'), L('Y'), L('y'), L('Y'), C('Y'), 0, 0,
0, A('y'), 0, 0, 0, 0, 0, 0, 0, 0,
43: /* 22 - u */ L('u'), L('U'), L('u'), L('U'), C('U'), 0, 0,
0, A('u'), 0, 0, 0, 0, 0, 0, 0, 0,
44: /* 23 - i */ L('i'), L('I'), L('i'), L('I'), C('I'), 0, 0,
0, A('i'), 0, 0, 0, 0, 0, 0, 0, 0,
45: /* 24 - o */ L('o'), L('O'), L('o'), L('O'), C('O'), 0, 0,
0, A('o'), 0, 0, 0, 0, 0, 0, 0, 0,
46: /* 25 - p */ L('p'), L('P'), L('p'), L('P'), C('P'), 0, 0,
0, A('p'), 0, 0, 0, 0, 0, 0, 0, 0,
47: /* 26 - [{ */ '[' , '{' , NULL, NULL, C('[') , 0, 0,
0, A('[') , 0, 0, 0, 0, 0, 0, 0, 0,
48: /* 27 - ]} */ ']' , '}' , '~' , NULL, C(']') , 0, 0,
0, A(']') , 0, 0, 0, 0, 0, 0, 0, 0,
49: /* 28 - CR */ CR, CR, CR, CR, CR, 0, 0,
0, A(CR), 0, 0, 0, 0, 0, 0, 0, 0,
50: /* 29 - CTRL */ CTRL, CTRL, CTRL, CTRL, CTRL, 0, 0,
0, A(CTRL), 0, 0, 0, 0, 0, 0, 0, 0,
51: /* 30 - a */ L('a'), L('A'), L('a'), L('A'), C('A'), 0, 0,
0, A('a'), 0, 0, 0, 0, 0, 0, 0, 0,
52: /* 31 - s */ L('s'), L('S'), L('s'), L('S'), C('S'), 0, 0,
0, A('s'), 0, 0, 0, 0, 0, 0, 0, 0,
53: /* 32 - d */ L('d'), L('D'), L('d'), L('D'), C('D'), 0, 0,
0, A('d'), 0, 0, 0, 0, 0, 0, 0, 0,
54: /* 33 - f */ L('f'), L('F'), L('f'), L('F'), C('F'), 0, 0,
0, A('f'), 0, 0, 0, 0, 0, 0, 0, 0,
55: /* 34 - g */ L('g'), L('G'), L('g'), L('G'), C('G'), 0, 0,
0, A('g'), 0, 0, 0, 0, 0, 0, 0, 0,
56: /* 35 - h */ L('h'), L('H'), L('h'), L('H'), C('H'), 0, 0,
0, A('h'), 0, 0, 0, 0, 0, 0, 0, 0,
57: /* 36 - j */ L('j'), L('J'), L('j'), L('J'), C('J'), 0, 0,
0, A('j'), 0, 0, 0, 0, 0, 0, 0, 0,
58: /* 37 - k */ L('k'), L('K'), L('k'), L('K'), C('K'), 0, 0,
0, A('k'), 0, 0, 0, 0, 0, 0, 0, 0,
59: /* 38 - l */ L('l'), L('L'), L('l'), L('L'), C('L'), 0, 0,
0, A('l'), 0, 0, 0, 0, 0, 0, 0, 0,
60: /* 39 - ;: */ ';' , ':' , NULL, NULL, NULL, 0, 0,
0, A(';') , 0, 0, 0, 0, 0, 0, 0, 0,
61: /* 40 - '\" */ '\ ' , '\" ' , NULL, NULL, C('G') , 0, 0,
0, A('\ ') , 0, 0, 0, 0, 0, 0, 0, 0,
62: /* 41 - '~ */ '~ ' , '~ ' , NULL, NULL, NULL, 0, 0,
0, A('~ ') , 0, 0, 0, 0, 0, 0, 0, 0,
63: /* 42 - LSHF */ SHIFT, SHIFT, SHIFT, SHIFT, SHIFT, 0, 0,
0, A(SHIFT), 0, 0, 0, 0, 0, 0, 0, 0,
64: /* 43 - \| */ '\\ ' , '| ' , NULL, NULL, C('\\ ') , 0, 0,
0, A('\\ ') , 0, 0, 0, 0, 0, 0, 0, 0,
65: /* 44 - z */ L('z'), L('Z'), L('z'), L('Z'), C('Z'), 0, 0,
0, A('z'), 0, 0, 0, 0, 0, 0, 0, 0,
66: /* 45 - x */ L('x'), L('X'), L('x'), L('X'), C('X'), 0, 0,
0, A('x'), 0, 0, 0, 0, 0, 0, 0, 0,
67: /* 46 - c */ L('c'), L('C'), L('c'), L('C'), C('C'), 0, 0,
0, A('c'), 0, 0, 0, 0, 0, 0, 0, 0,
68: /* 47 - v */ L('v'), L('V'), L('v'), L('V'), C('V'), 0, 0,
0, A('v'), 0, 0, 0, 0, 0, 0, 0, 0,
69: /* 48 - b */ L('b'), L('B'), L('b'), L('B'), C('B'), 0, 0,
0, A('b'), 0, 0, 0, 0, 0, 0, 0, 0,
70: /* 49 - n */ L('n'), L('N'), L('n'), L('N'), C('N'), 0, 0,
0, A('n'), 0, 0, 0, 0, 0, 0, 0, 0,
71: /* 50 - m */ L('m'), L('M'), L('m'), L('M'), C('M'), 0, 0,
0, A('m'), 0, 0, 0, 0, 0, 0, 0, 0,
72: /* 51 - ,< */ ',' , '<' , NULL, NULL, NULL, 0, 0,
0, A(',') , 0, 0, 0, 0, 0, 0, 0, 0,
73: /* 52 - .> */ '.' , '>' , NULL, NULL, NULL, 0, 0,
0, A('.') , 0, 0, 0, 0, 0, 0, 0, 0,
74: /* 53 - /? */ SLASH, '?' , NULL, NULL, BS, 0, 0,
0, A('/') , 0, 0, 0, 0, 0, 0, 0, 0,
75: /* 54 - RSHF */ SHIFT, SHIFT, SHIFT, SHIFT, SHIFT, 0, 0,

```

drivers/char/defkeymap.c

0,	SHIFT,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
76:	/* 55 - *	*/	ASTSK,	ASTSK,	ASTSK,	ASTSK,	ASTSK,	ASTSK,	0,	0,	0,
0,	ASTSK,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
77:	/* 56 - ALT	*/	ALT,	ALT,	ALT,	ALT,	ALT,	ALT,	0,	0,	0,
0,	ALT,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
78:	/* 57 - SPC	*/	' ',	' ',	NULL,	NULL,	NULL,	NULL,	0,	0,	0,
0,	A(' '),	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
79:	/* 58 - CAPS	*/	CAPS,	CAPS,	CAPS,	CAPS,	CAPS,	CAPS,	0,	0,	0,
0,	CAPS,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
80:	/* 59 - F1	*/	F1,	SF1,	NULL,	NULL,	F1,	0,	0,	0,	0,
0,	AF1,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
81:	/* 60 - F2	*/	F2,	SF2,	NULL,	NULL,	F2,	0,	0,	0,	0,
0,	AF2,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
82:	/* 61 - F3	*/	F3,	SF3,	NULL,	NULL,	F3,	0,	0,	0,	0,
0,	AF3,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
83:	/* 62 - F4	*/	F4,	SF4,	NULL,	NULL,	F4,	0,	0,	0,	0,
0,	AF4,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
84:	/* 63 - F5	*/	F5,	SF5,	NULL,	NULL,	F5,	0,	0,	0,	0,
0,	AF5,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
85:	/* 64 - F6	*/	F6,	SF6,	NULL,	NULL,	F6,	0,	0,	0,	0,
0,	AF6,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
86:	/* 65 - F7	*/	F7,	SF7,	NULL,	NULL,	F7,	0,	0,	0,	0,
0,	AF7,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
87:	/* 66 - F8	*/	F8,	SF8,	NULL,	NULL,	F8,	0,	0,	0,	0,
0,	AF8,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
88:	/* 67 - F9	*/	F9,	SF9,	NULL,	NULL,	F9,	0,	0,	0,	0,
0,	AF9,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
89:	/* 68 - F10	*/	F10,	SF10,	NULL,	NULL,	F10,	0,	0,	0,	0,
0,	AF10,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
90:	/* 69 - NUMS	*/	NUMS,	NUMS,	NUMS,	NUMS,	NUMS,	0,	0,	0,	0,
0,	NUMS,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
91:	/* 70 - SCRL	*/	SCRL,	SCRL3,	SCRL2,	NULL,	SCRL4,	0,	0,	0,	0,
0,	SCRL,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
92:	/* 71 - HOME/7	*/	HOME,	HOME,	HOME,	HOME,	HOME,	0,	0,	0,	0,
0,	NULL,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
93:	/* 72 - UP /8	*/	UP,	UP,	UP,	UP,	UP,	0,	0,	0,	0,
0,	NULL,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
94:	/* 73 - PGUP/9	*/	PGUP,	PGUP,	PGUP,	PGUP,	PGUP,	0,	0,	0,	0,
0,	NULL,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
95:	/* 74 - MINUS	*/	MINUS,	MINUS,	MINUS,	MINUS,	MINUS,	0,	0,	0,	0,
0,	MINUS,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
96:	/* 75 - LEFT/4	*/	LEFT,	LEFT,	LEFT,	LEFT,	LEFT,	0,	0,	0,	0,
0,	NULL,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
97:	/* 76 - MID /5	*/	MID,	MID,	MID,	MID,	MID,	0,	0,	0,	0,
0,	NULL,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
98:	/* 77 - RIGH/6	*/	RIGHT,	RIGHT,	RIGHT,	RIGHT,	RIGHT,	0,	0,	0,	0,
0,	NULL,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
99:	/* 78 - PLUS	*/	PLUS,	PLUS,	PLUS,	PLUS,	PLUS,	0,	0,	0,	0,
0,	PLUS,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
100:	/* 79 - END /1	*/	END,	END,	END,	END,	END,	0,	0,	0,	0,
0,	NULL,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
101:	/* 80 - DOWN/2	*/	DOWN,	DOWN,	DOWN,	DOWN,	DOWN,	0,	0,	0,	0,
0,	NULL,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
102:	/* 81 - PGDN/3	*/	PGDN,	PGDN,	PGDN,	PGDN,	PGDN,	0,	0,	0,	0,
0,	NULL,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
103:	/* 82 - INS /0	*/	INS,	INS,	INS,	INS,	INS,	0,	0,	0,	0,
0,	NULL,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
104:	/* 83 - DEL /.	*/	DEL,	DEL,	DEL,	DEL,	DEL,	0,	0,	0,	0,
0,	DEL,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
105:	/* 84 -	*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,	0,	0,
0,	NULL,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
106:	/* 85 -	*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,	0,	0,
0,	NULL,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
107:	/* 86 - <>	*/	'<',	'>',	' ',	NULL,	NULL,	0,	0,	0,	0,
0,	A('<'),	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,
108:	/* 87 - F11	*/	SF1,	SF1,	NULL,	NULL,	F11,	0,	0,	0,	0,
0,	AF11,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,

drivers/char/defkeymap.c										Page 4/5		
109:	/*	88	-	F12	*/	SF2,	SF2,	NULL,	NULL,	F12,	0,	0,
0,	AF12,	0,			0,	0,	0,	0,	0,	0,		
110:	/*	89	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
111:	/*	90	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
112:	/*	91	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
113:	/*	92	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
114:	/*	93	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
115:	/*	94	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
116:	/*	95	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
117:	/*	96	-		*/	ENTER,	ENTER,	ENTER,	ENTER,	ENTER,	0,	0,
0,	ENTER,	0,			0,	0,	0,	0,	0,	0,		
118:	/*	97	-		*/	CTRL,	CTRL,	CTRL,	CTRL,	CTRL,	0,	0,
0,	CTRL,	0,			0,	0,	0,	0,	0,	0,		
119:	/*	98	-		*/	SLASH,	SLASH,	SLASH,	SLASH,	SLASH,	0,	0,
0,	SLASH,	0,			0,	0,	0,	0,	0,	0,		
120:	/*	99	-		*/	NULL,	NULL,	NULL,	NULL,	C('\'\''),	0,	0,
0,	C('\'\''),	0,			0,	0,	0,	0,	0,	0,		
121:	/*	100	-		*/	ALTGR,	ALTGR,	ALTGR,	ALTGR,	ALTGR,	0,	0,
0,	ALTGR,	0,			0,	0,	0,	0,	0,	0,		
122:	/*	101	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
123:	/*	102	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
124:	/*	103	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
125:	/*	104	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
126:	/*	105	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
127:	/*	106	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
128:	/*	107	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
129:	/*	108	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
130:	/*	109	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
131:	/*	110	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
132:	/*	111	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
133:	/*	112	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
134:	/*	113	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
135:	/*	114	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
136:	/*	115	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
137:	/*	116	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
138:	/*	117	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
139:	/*	118	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
140:	/*	119	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
141:	/*	120	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,
0,	NULL,	0,			0,	0,	0,	0,	0,	0,		
142:	/*	121	-		*/	NULL,	NULL,	NULL,	NULL,	NULL,	0,	0,

drivers/char/defkeymap.c

Page 5/5

```
0,      NULL,  0,    0,    0,    0,    0,    0,    0,    0,    0,
143: /* 122 -    */    NULL,  NULL,  NULL,  NULL,  NULL,  NULL,  NULL,  0,    0,
0,      NULL,  0,    0,    0,    0,    0,    0,    0,    0,    0,
144: /* 123 -    */    NULL,  NULL,  NULL,  NULL,  NULL,  NULL,  NULL,  0,    0,
0,      NULL,  0,    0,    0,    0,    0,    0,    0,    0,    0,
145: /* 124 -    */    NULL,  NULL,  NULL,  NULL,  NULL,  NULL,  NULL,  0,    0,
0,      NULL,  0,    0,    0,    0,    0,    0,    0,    0,    0,
146: /* 125 -    */    NULL,  NULL,  NULL,  NULL,  NULL,  NULL,  NULL,  0,    0,
0,      NULL,  0,    0,    0,    0,    0,    0,    0,    0,    0,
147: /* 126 -    */    NULL,  NULL,  NULL,  NULL,  NULL,  NULL,  NULL,  0,    0,
0,      NULL,  0,    0,    0,    0,    0,    0,    0,    0,    0,
148: /* 127 -    */    NULL,  NULL,  NULL,  NULL,  NULL,  NULL,  NULL,  0,    0,
0,      NULL,  0,    0,    0,    0,    0,    0,    0,    0,
149: };
```


drivers/char/keyboard.c

Page 1/11

```

1: /*
2:  * fiwix/drivers/char/keyboard.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/kernel.h>
10: #include <fiwix/limits.h>
11: #include <fiwix/keyboard.h>
12: #include <fiwix/console.h>
13: #include <fiwix/pic.h>
14: #include <fiwix/signal.h>
15: #include <fiwix/process.h>
16: #include <fiwix/sleep.h>
17: #include <fiwix/kd.h>
18: #include <fiwix/stdio.h>
19: #include <fiwix/string.h>
20:
21: #define KB_DATA          0x60      /* I/O data port */
22: #define KBC_COMMAND     0x64      /* command/control port */
23: #define KBC_STATUS      0x64      /* status register port */
24:
25: /*
26:  * PS/2 System Control Port A
27:  * -----
28:  * bit 7 -> fixed disk activity led
29:  * bit 6 -> fixed disk activity led
30:  * bit 5 -> reserved
31:  * bit 4 -> watchdog timer status
32:  * bit 3 -> security lock latch
33:  * bit 2 -> reserved
34:  * bit 1 -> alternate gate A20
35:  * bit 0 -> alternate hot reset
36:  */
37: #define PS2_SYSCTRL_A   0x92      /* PS/2 system control port A (write) */
38:
39: #define KB_CMD_RESET    0xFF      /* keyboard reset */
40: #define KB_CMD_ENABLE   0xF4      /* keyboard enable scanning */
41: #define KB_CMD_DISABLE  0xF5      /* keyboard disable scanning */
42: #define KB_CMD_IDENTIFY 0xF2      /* keyboard identify (for PS/2 only) */
43: #define KB_CMD_ECHO     0xEE      /* echo (for diagnostics only) */
44:
45: #define KBC_CMD_RECV_CONFIG 0x20   /* read controller's config byte */
46: #define KBC_CMD_SEND_CONFIG 0x60   /* write controller's config byte */
47: #define KBC_CMD_SELF_TEST  0xAA    /* self-test command */
48: #define KBC_CMD_PS2_1_TEST 0xAB    /* first PS/2 interface test command */
49: #define KBC_CMD_PS2_2_TEST 0xA9    /* second PS/2 interface test command */
50: #define KBC_CMD_DISABLE_PS2_1 0xAD  /* disable first PS/2 port */
51: #define KBC_CMD_ENABLE_PS2_1 0xAE   /* enable first PS/2 port */
52: #define KBC_CMD_DISABLE_PS2_2 0xA7  /* disable second PS/2 port (if any) */
53: #define KBC_CMD_ENABLE_PS2_2 0xA8   /* enable second PS/2 port (if any) */
54: #define KBC_CMD_GET_IFACE  0xCA    /* get interface type (AT or MCA) */
55: #define KBC_CMD_HOTRESET   0xFE    /* Hot Reset */
56:
57: /* flags of the status register */
58: #define KB_STR_OUTBUSY   0x01      /* output buffer full, don't read yet */
59: #define KB_STR_INBUSY    0x02      /* input buffer full, don't write yet */
60: #define KB_STR_TXTMOUT   0x20      /* transmit time-out error */
61: #define KB_STR_RXTMOUT   0x40      /* receive time-out error */
62: #define KB_STR_PARERR    0x80      /* parity error */
63: #define KB_STR_COMMERR   (KB_STR_TXTMOUT | KB_STR_RXTMOUT)
64:
65: #define KB_RESET_OK     0xAA      /* self-test passed */
66: #define KB_ACK          0xFA      /* acknowledge */
67: #define KB_SETLED       0xED      /* set/reset status indicators (LEDs) */

```

drivers/char/keyboard.c

Page 2/11

```

68: #define KB_RATE          0xF3      /* set typematic rate/delay */
69: #define DELAY_250        0x00      /* typematic delay at 250ms (default) */
70: #define DELAY_500        0x40      /* typematic delay at 500ms */
71: #define DELAY_750        0x80      /* typematic delay at 750ms */
72: #define DELAY_1000       0xC0      /* typematic delay at 1000ms */
73: #define RATE_30          0x00      /* typematic rate at 30.0 reports/sec (default)
*/
74:
75: #define EXTKEY            0xE0      /* extended key (AltGr, Ctrl-Print, etc.) */
76:
77: __key_t *keymap_line;
78:
79: static unsigned char leds = 0;
80: static unsigned char shift = 0;
81: static unsigned char altgr = 0;
82: static unsigned char ctrl = 0;
83: static unsigned char alt = 0;
84: static unsigned char extkey = 0;
85: static unsigned char deadkey = 0;
86:
87: static unsigned char do_scrl_buf = 0;
88: static char do_switch_console = -1;
89:
90: unsigned char kb_identify[2] = {0, 0};
91: char ps2_active_ports = 0;
92: char ps2_supp_ports = 0;
93: char ps2_iface = 0;
94: short int current_cons;
95: char ctrl_alt_del = 1;
96: char any_key_to_reboot = 0;
97:
98: struct diacritic *diacr;
99: static char *diacr_chars = "`^ \";
100: struct diacritic grave_table[NR_DIACR] = {
101:     { 'A', '\300' },
102:     { 'E', '\310' },
103:     { 'I', '\314' },
104:     { 'O', '\322' },
105:     { 'U', '\331' },
106:     { 'a', '\340' },
107:     { 'e', '\350' },
108:     { 'i', '\354' },
109:     { 'o', '\362' },
110:     { 'u', '\371' },
111: };
112: struct diacritic acute_table[NR_DIACR] = {
113:     { 'A', '\301' },
114:     { 'E', '\311' },
115:     { 'I', '\315' },
116:     { 'O', '\323' },
117:     { 'U', '\332' },
118:     { 'a', '\341' },
119:     { 'e', '\351' },
120:     { 'i', '\355' },
121:     { 'o', '\363' },
122:     { 'u', '\372' },
123: };
124: struct diacritic circum_table[NR_DIACR] = {
125:     { 'A', '\302' },
126:     { 'E', '\312' },
127:     { 'I', '\316' },
128:     { 'O', '\324' },
129:     { 'U', '\333' },
130:     { 'a', '\342' },
131:     { 'e', '\352' },
132:     { 'i', '\356' },
133:     { 'o', '\364' },

```

drivers/char/keyboard.c

Page 3/11

```

134:         { 'u', '\373' },
135:     };
136:     struct diacritic diere_table[NR_DIACR] = {
137:         { 'A', '\304' },
138:         { 'E', '\313' },
139:         { 'I', '\317' },
140:         { 'O', '\326' },
141:         { 'U', '\334' },
142:         { 'a', '\344' },
143:         { 'e', '\353' },
144:         { 'i', '\357' },
145:         { 'o', '\366' },
146:         { 'u', '\374' },
147:     };
148:
149:     static char *pad_chars = "0123456789+--*/\015,.";
150:
151:     static char *pad_seq[] = {
152:         "\033[2~",      /* INS */
153:         "\033[4~",      /* END */
154:         "\033[B",       /* DOWN */
155:         "\033[6~",      /* PGDN */
156:         "\033[D",       /* LEFT */
157:         "\033[G",       /* MID */
158:         "\033[C",       /* RIGHT */
159:         "\033[1~",     /* HOME */
160:         "\033[A",       /* UP */
161:         "\033[5~",     /* PGUP */
162:         "+",            /* PLUS */
163:         "-",            /* MINUS */
164:         "*",            /* ASTERISK */
165:         "/",            /* SLASH */
166:         "\n",           /* ENTER */
167:         ",",            /* COMMA */
168:         "\033[3~",     /* DEL */
169:     };
170:
171:     static char *fn_seq[] = {
172:         "\033[A",       /* F1 */
173:         "\033[B",       /* F2 */
174:         "\033[C",       /* F3 */
175:         "\033[D",       /* F4 */
176:         "\033[E",       /* F5 */
177:         "\033[17~",    /* F6 */
178:         "\033[18~",    /* F7 */
179:         "\033[19~",    /* F8 */
180:         "\033[20~",    /* F9 */
181:         "\033[21~",    /* F10 */
182:         "\033[23~",    /* F11, SF1 */
183:         "\033[24~",    /* F12, SF2 */
184:         "\033[25~",    /* SF3 */
185:         "\033[26~",    /* SF4 */
186:         "\033[28~",    /* SF5 */
187:         "\033[29~",    /* SF6 */
188:         "\033[31~",    /* SF7 */
189:         "\033[32~",    /* SF8 */
190:         "\033[33~",    /* SF9 */
191:         "\033[34~",    /* SF10 */
192:     };
193:
194:     static void keyboard_delay(void)
195:     {
196:         int n;
197:
198:         for(n = 0; n < 1000; n++) {
199:             NOP();
200:         }

```

drivers/char/keyboard.c

Page 4/11

```

201: }
202:
203: /* wait controller input buffer to be clear (ready to write) */
204: static int keyboard_wait_input(void)
205: {
206:     int n;
207:
208:     for(n = 0; n < 500000; n++) {
209:         if(!(inport_b(KBC_STATUS) & KB_STR_INBUSY)) {
210:             return 0;
211:         }
212:     }
213:     return 1;
214: }
215:
216: static int keyboard_write(const unsigned char port, const unsigned char byte)
217: {
218:     if(!keyboard_wait_input()) {
219:         outport_b(port, byte);
220:         if(!keyboard_wait_input()) {
221:             return 0;
222:         }
223:     }
224:
225:     return 1;
226: }
227:
228: /* wait controller output buffer to be full (ready to read) */
229: static int keyboard_wait_output(void)
230: {
231:     int n, value;
232:
233:     for(n = 0; n < 500000; n++) {
234:         if((value = inport_b(KBC_STATUS)) & KB_STR_OUTBUSY) {
235:             if(value & (KB_STR_COMMERR | KB_STR_PARERR)) {
236:                 continue;
237:             }
238:             return 0;
239:         }
240:     }
241:     return 1;
242: }
243:
244: static int keyboard_wait_ack(void)
245: {
246:     int n;
247:
248:     keyboard_wait_output();
249:     for(n = 0; n < 1000; n++) {
250:         if(inport_b(KB_DATA) == KB_ACK) {
251:             return 0;
252:         }
253:         keyboard_delay();
254:     }
255:     return 1;
256: }
257:
258: static void keyboard_identify(void)
259: {
260:     /* disable */
261:     keyboard_write(KB_DATA, KB_CMD_DISABLE);
262:     if(keyboard_wait_ack()) {
263:         printk("WARNING: %s(): ACK not received on disable command!\n",
__FUNCTION__);
264:     }
265:
266:     /* identify */

```

drivers/char/keyboard.c

Page 5/11

```

267:     keyboard_write(KB_DATA, KB_CMD_IDENTIFY);
268:     if(keyboard_wait_ack()) {
269:         printk("WARNING: %s(): ACK not received on identify command!\n",
__FUNCTION__);
270:     }
271:     if(!keyboard_wait_output()) {
272:         kb_identify[0] = inport_b(KB_DATA);
273:     }
274:     if(!keyboard_wait_output()) {
275:         kb_identify[1] = inport_b(KB_DATA);
276:     }
277:
278:     /* enable */
279:     keyboard_write(KB_DATA, KB_CMD_ENABLE);
280:     if(keyboard_wait_ack()) {
281:         printk("WARNING: %s(): ACK not received on enable command!\n", _
__FUNCTION__);
282:     }
283:     keyboard_wait_output();
284:     inport_b(KB_DATA);
285:
286:     /* get the interface type */
287:     keyboard_write(KBC_COMMAND, KBC_CMD_GET_IFACE);
288:     keyboard_wait_output();
289:     ps2_iface = inport_b(KB_DATA);
290: }
291:
292: static void keyboard_reset(void)
293: {
294:     int errno;
295:     unsigned char config;
296:
297:     /* disable device(s) */
298:     keyboard_write(KBC_COMMAND, KBC_CMD_DISABLE_PS2_1);
299:     keyboard_write(KBC_COMMAND, KBC_CMD_DISABLE_PS2_2);
300:
301:     /* flush buffers */
302:     while(!keyboard_wait_output()) {
303:         inport_b(KB_DATA);
304:     }
305:
306:     /* get controller configuration */
307:     keyboard_write(KBC_COMMAND, KBC_CMD_RECV_CONFIG);
308:     keyboard_wait_output();
309:     config = inport_b(KB_DATA);
310:     ps2_active_ports = config & 0x01 ? 1 : 0;
311:     ps2_active_ports += config & 0x02 ? 1 : 0;
312:     ps2_supp_ports = 1 + (config & 0x20 ? 1 : 0);
313:
314:     /* set controller configuration (disabling IRQs) */
315:     /*
316:     keyboard_write(KBC_COMMAND, KBC_CMD_SEND_CONFIG);
317:     keyboard_write(KB_DATA, config & ~(0x01 | 0x02 | 0x40));
318:     */
319:
320:     /* PS/2 controller self-test */
321:     keyboard_write(KBC_COMMAND, KBC_CMD_SELF_TEST);
322:     keyboard_wait_output();
323:     if((errno = inport_b(KB_DATA)) != 0x55) {
324:         printk("WARNING: %s(): keyboard returned 0x%x in self-test.\n",
__FUNCTION__, errno);
325:     }
326:
327:     /*
328:     * This sets again the controller configuration since the previous
329:     * step may also reset the PS/2 controller to its power-on defaults.
330:     */

```

drivers/char/keyboard.c

Page 6/11

```

331:     keyboard_write(KBC_COMMAND, KBC_CMD_SEND_CONFIG);
332:     keyboard_write(KB_DATA, config);
333:
334:     /* first PS/2 interface test */
335:     keyboard_write(KBC_COMMAND, KBC_CMD_PS2_1_TEST);
336:     keyboard_wait_output();
337:     if((errno = inport_b(KB_DATA)) != 0) {
338:         printk("WARNING: %s(): keyboard returned 0x%x in first PS/2 inte
rface test.\n", __FUNCTION__, errno);
339:     }
340:
341:     if(ps2_supp_ports > 1) {
342:         /* second PS/2 interface test */
343:         keyboard_write(KBC_COMMAND, KBC_CMD_PS2_2_TEST);
344:         keyboard_wait_output();
345:         if((errno = inport_b(KB_DATA)) != 0) {
346:             printk("WARNING: %s(): keyboard returned 0x%x in second
PS/2 interface test.\n", __FUNCTION__, errno);
347:         }
348:     }
349:
350:     /* enable device(s) */
351:     keyboard_write(KBC_COMMAND, KBC_CMD_ENABLE_PS2_1);
352:     keyboard_write(KBC_COMMAND, KBC_CMD_ENABLE_PS2_2);
353:
354:     /* reset device(s) */
355:     keyboard_write(KB_DATA, KB_CMD_RESET);
356:     if(keyboard_wait_ack()) {
357:         printk("WARNING: %s(): ACK not received on reset command!\n", __
FUNCTION__);
358:     }
359:     if(!keyboard_wait_output()) {
360:         if((errno = inport_b(KB_DATA)) != KB_RESET_OK) {
361:             printk("WARNING: %s(): keyboard returned 0x%x in reset.\n
n", __FUNCTION__, errno);
362:         }
363:     }
364:
365:     return;
366: }
367:
368: static void putc(struct tty *tty, unsigned char ch)
369: {
370:     if(tty_queue_putchar(tty, &tty->read_q, ch) < 0) {
371:         if(tty->termios.c_iflag & IMAXBEL) {
372:             vconsole_beep();
373:         }
374:     }
375: }
376:
377: static void puts(struct tty *tty, char *seq)
378: {
379:     char ch;
380:
381:     while((ch = *(seq++))) {
382:         putc(tty, ch);
383:     }
384: }
385:
386: void reboot(void)
387: {
388:     CLI();
389:     keyboard_write(PS2_SYSCTRL_A, 0x01);           /* Fast Hot Reset */
390:     keyboard_write(KBC_COMMAND, KBC_CMD_HOTRESET); /* Hot Reset */
391:     HLT();
392: }
393:

```

drivers/char/keyboard.c

Page 7/11

```

394: void set_leds(unsigned char leds)
395: {
396:     keyboard_write(KB_DATA, KB_SETLED);
397:     keyboard_wait_ack();
398:
399:     keyboard_write(KB_DATA, leds);
400:     keyboard_wait_ack();
401: }
402:
403: void irq_keyboard(void)
404: {
405:     __key_t key, type;
406:     unsigned char scode, mod;
407:     struct tty *tty;
408:     struct vconsole *vc;
409:     unsigned char c;
410:     int n;
411:
412:     tty = get_tty(MKDEV(VCONSOLES_MAJOR, current_cons));
413:     vc = (struct vconsole *)tty->driver_data;
414:
415:     scode = inport_b(KB_DATA);
416:
417:     screen_on();
418:     add_bh(keyboard_bh);
419:
420:     if(scode == KB_ACK) {
421:         return;
422:     }
423:
424:     if(scode == EXTKEY) {
425:         extkey = 1;
426:         return;
427:     }
428:
429:     key = keymap[NR_MODIFIERS * (scode & 0x7F)];
430:
431:     /* a key has been released */
432:     if(scode & NR_SCODES) {
433:         switch(key) {
434:             case CTRL:
435:                 ctrl = 0;
436:                 break;
437:             case ALT:
438:                 if(!extkey) {
439:                     alt = 0;
440:                 } else {
441:                     altgr = 0;
442:                 }
443:                 break;
444:             case SHIFT:
445:                 if(!extkey) {
446:                     shift = 0;
447:                 }
448:                 break;
449:             case CAPS:
450:             case NUMS:
451:             case SCRL:
452:                 leds = 0;
453:                 break;
454:         }
455:         extkey = 0;
456:         return;
457:     }
458:
459:     switch(key) {
460:         case CAPS:

```

drivers/char/keyboard.c

Page 8/11

```

461:             if(!leds) {
462:                 vc->led_status ^= CAPSBIT;
463:                 vc->capslock = !vc->capslock;
464:                 set_leds(vc->led_status);
465:             }
466:             leds = 1;
467:             return;
468:         case NUMS:
469:             if(!leds) {
470:                 vc->led_status ^= NUMSBIT;
471:                 vc->numlock = !vc->numlock;
472:                 set_leds(vc->led_status);
473:             }
474:             leds = 1;
475:             return;
476:         case SCRL:
477:             if(!leds) {
478:                 if(vc->scrlock) {
479:                     tty->start(tty);
480:                 } else {
481:                     tty->stop(tty);
482:                 }
483:             }
484:             leds = 1;
485:             return;
486:         case CTRL:
487:             ctrl = 1;
488:             return;
489:         case ALT:
490:             if(!extkey) {
491:                 alt = 1;
492:             } else {
493:                 altgr = 1;
494:             }
495:             return;
496:         case SHIFT:
497:             shift = 1;
498:             extkey = 0;
499:             return;
500:     }
501:
502:     if(ctrl && alt && key == DEL) {
503:         if(ctrl_alt_del) {
504:             reboot();
505:         } else {
506:             send_sig(&proc_table[INIT], SIGINT);
507:         }
508:         return;
509:     }
510:
511:     keymap_line = &keymap[(scode & 0x7F) * NR_MODIFIERS];
512:     mod = 0;
513:
514:     if(vc->capslock && (keymap_line[MOD_BASE] & LETTER_KEYS)) {
515:         mod = !vc->capslock ? shift : vc->capslock - shift;
516:     } else {
517:         if(shift && !extkey) {
518:             mod = 1;
519:         }
520:     }
521:     if(altgr) {
522:         mod = 2;
523:     }
524:     if(ctrl) {
525:         mod = 4;
526:     }
527:     if(alt) {

```


drivers/char/keyboard.c

Page 9/11

```

528:         mod = 8;
529:     }
530:
531:     key = keymap_line[mod];
532:
533:     if(key >= AF1 && key <= AF12) {
534:         do_switch_console = key - CONS_KEYS;
535:         return;
536:     }
537:
538:     if(shift && (key == PGUP)) {
539:         do_scr1_buf = VC_BUF_UP;
540:         return;
541:     }
542:
543:     if(shift && (key == PGDN)) {
544:         do_scr1_buf = VC_BUF_DOWN;
545:         return;
546:     }
547:
548:     if(extkey && (scode == SLASH_NPAD)) {
549:         key = SLASH;
550:     }
551:
552:     if(any_key_to_reboot) {
553:         reboot();
554:     }
555:
556:     if(tty->count) {
557:         type = key & 0xFF00;
558:         c = key & 0xFF;
559:
560:         switch(type) {
561:             case FN_KEYS:
562:                 puts(tty, fn_seq[c]);
563:                 break;
564:
565:             case SPEC_KEYS:
566:                 switch(key) {
567:                     case CR:
568:                         putc(tty, C('M'));
569:                         break;
570:                 }
571:                 break;
572:
573:             case PAD_KEYS:
574:                 if(!vc->numlock) {
575:                     puts(tty, pad_seq[c]);
576:                 } else {
577:                     putc(tty, pad_chars[c]);
578:                 }
579:                 break;
580:
581:             case DEAD_KEYS:
582:                 if(!deadkey) {
583:                     switch(c) {
584:                         case GRAVE ^ DEAD_KEYS:
585:                             deadkey = 1;
586:                             diacr = grave_table;
587:                             break;
588:                         case ACUTE ^ DEAD_KEYS:
589:                             deadkey = 2;
590:                             diacr = acute_table;
591:                             break;
592:                         case CIRCUM ^ DEAD_KEYS:
593:                             deadkey = 3;
594:                             diacr = circm_table;

```

drivers/char/keyboard.c

Page 10/11

```

595:                                     break;
596:                                     case DIERE ^ DEAD_KEYS:
597:                                         deadkey = 5;
598:                                         diacr = diere_table;
599:                                         break;
600:                                     }
601:                                     return;
602:                                     }
603:                                     c = diacr_chars[c];
604:                                     deadkey = 0;
605:                                     putc(tty, c);
606:
607:                                     break;
608:
609:                                     case META_KEYS:
610:                                         putc(tty, '\033');
611:                                         putc(tty, c);
612:                                         break;
613:
614:                                     case LETTER_KEYS:
615:                                         if(deadkey) {
616:                                             for(n = 0; n < NR_DIACR; n++) {
617:                                                 if(diacr[n].letter == c) {
618:                                                     c = diacr[n].code;
619:                                                 }
620:                                             }
621:                                         }
622:                                         putc(tty, c);
623:                                         break;
624:
625:                                     default:
626:                                         if(deadkey && c == ' ') {
627:                                             c = diacr_chars[deadkey - 1];
628:                                         }
629:                                         putc(tty, c);
630:                                         break;
631:                                     }
632:                                     }
633:                                     deadkey = 0;
634:                                     return;
635:     }
636:
637: void keyboard_bh(void)
638: {
639:     int n;
640:     struct tty *tty;
641:
642:     if(do_switch_console >= 0) {
643:         vconsole_select(do_switch_console);
644:         do_switch_console = -1;
645:     }
646:
647:     if(do_scr1_buf) {
648:         vconsole_buffer_scr1(do_scr1_buf);
649:         do_scr1_buf = 0;
650:     }
651:
652:     tty = &tty_table[0];
653:     for(n = 0; n < NR_TTYS; n++, tty++) {
654:         if(!tty->read_q.count) {
655:             continue;
656:         }
657:         if(lock_area(AREA_TTY_READ)) {
658:             continue;
659:         }
660:         tty->input(tty);
661:         unlock_area(AREA_TTY_READ);

```

drivers/char/keyboard.c

Page 11/11

```
662:         }
663:     }
664:
665: void keyboard_init(void)
666: {
667:     keyboard_reset();
668:
669:     /* flush buffers */
670:     while(!keyboard_wait_output()) {
671:         inport_b(KB_DATA);
672:     }
673:
674:     keyboard_identify();
675:
676:     keyboard_write(KB_DATA, KB_RATE);
677:     keyboard_wait_ack();
678:     keyboard_write(KB_DATA, DELAY_250 | RATE_30);
679:     keyboard_wait_ack();
680:
681:     printk("keyboard 0x%04X-0x%04X   %d   type=%s %s PS/2 devices=%d/%d\n",
", 0x60, 0x64, KEYBOARD_IRQ, kb_identify[0] == 0xAB ? "MF2" : "unknown", ps2_iface & 0x
1 ? "MCA" : "AT", ps2_active_ports, ps2_supp_ports);
682:
683:     if(!register_irq(KEYBOARD_IRQ, "keyboard", irq_keyboard)) {
684:         enable_irq(KEYBOARD_IRQ);
685:     }
686: }
```

drivers/char/lp.c

Page 1/4

```

1: /*
2:  * fiwix/drivers/char/lp.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/devices.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/errno.h>
12: #include <fiwix/lp.h>
13: #include <fiwix/stdio.h>
14: #include <fiwix/string.h>
15:
16: struct lp lp_table[LP_MINORS];
17:
18: static struct fs_operations lp_driver_fsop = {
19:     0,
20:     0,
21:
22:     lp_open,
23:     lp_close,
24:     NULL, /* read */
25:     lp_write,
26:     NULL, /* ioctl */
27:     NULL, /* lseek */
28:     NULL, /* readdir */
29:     NULL, /* mmap */
30:     NULL, /* select */
31:
32:     NULL, /* readlink */
33:     NULL, /* followlink */
34:     NULL, /* bmap */
35:     NULL, /* lockup */
36:     NULL, /* rmdir */
37:     NULL, /* link */
38:     NULL, /* unlink */
39:     NULL, /* symlink */
40:     NULL, /* mkdir */
41:     NULL, /* mknod */
42:     NULL, /* truncate */
43:     NULL, /* create */
44:     NULL, /* rename */
45:
46:     NULL, /* read_block */
47:     NULL, /* write_block */
48:
49:     NULL, /* read_inode */
50:     NULL, /* write_inode */
51:     NULL, /* ialloc */
52:     NULL, /* ifree */
53:     NULL, /* statfs */
54:     NULL, /* read_superblock */
55:     NULL, /* remount_fs */
56:     NULL, /* write_superblock */
57:     NULL, /* release_superblock */
58: };
59:
60: static struct device lp_device = {
61:     "lp",
62:     -1,
63:     LP_MAJOR,
64:     { 0, 0, 0, 0, 0, 0, 0, 0 },
65:     0,
66:     NULL,
67:     &lp_driver_fsop,

```

drivers/char/lp.c

Page 2/4

```

68: };
69:
70: struct lp lp_table[LP_MINORS] = {
71:     { LP0_ADDR, LP0_ADDR + 1, LP0_ADDR + 2, 0 }
72: };
73:
74: static void lp_delay(void)
75: {
76:     int n;
77:
78:     for(n = 0; n < 10000; n++) {
79:         NOP();
80:     }
81: }
82:
83: static int lp_ready(int minor)
84: {
85:     int n;
86:
87:     for(n = 0; n < LP_RDY_RETR; n++) {
88:         if(inport_b(lp_table[minor].stat) & LP_STAT_BUS) {
89:             break;
90:         }
91:         lp_delay();
92:     }
93:     if(n == LP_RDY_RETR) {
94:         return 0;
95:     }
96:     return 1;
97: }
98:
99: static int lp_probe(int minor)
100: {
101:     /* first check */
102:     outport_b(lp_table[minor].data, 0x55);
103:     lp_delay();
104:     if(inport_b(lp_table[minor].data) != 0x55) {
105:         return 1; /* did not retain data */
106:     }
107:
108:     /* second check */
109:     outport_b(lp_table[minor].data, 0xAA);
110:     lp_delay();
111:     if(inport_b(lp_table[minor].data) != 0xAA) {
112:         return 1; /* did not retain data */
113:     }
114:     return 0;
115: }
116:
117: static int lp_write_data(int minor, unsigned char c)
118: {
119:     unsigned char ctrl;
120:
121:     if(!lp_ready(minor)) {
122:         return -EBUSY;
123:     }
124:     outport_b(lp_table[minor].data, c);
125:     ctrl = inport_b(lp_table[minor].ctrl);
126:     outport_b(lp_table[minor].ctrl, ctrl | LP_CTRL_STR);
127:     lp_delay();
128:     outport_b(lp_table[minor].ctrl, ctrl);
129:     if(!lp_ready(minor)) {
130:         return -EBUSY;
131:     }
132:     return 1;
133: }
134:

```

drivers/char/lp.c

Page 3/4

```

135: int lp_open(struct inode *i, struct fd *fd_table)
136: {
137:     int minor;
138:
139:     minor = MINOR(i->rdev);
140:     if(!TEST_MINOR(lp_device.minors, minor)) {
141:         return -ENXIO;
142:     }
143:     if(!(lp_table[minor].flags & LP_CTRL_SEL)) {
144:         return -ENXIO;
145:     }
146:     if(lp_table[minor].flags & LP_STAT_BUS) {
147:         return -EBUSY;
148:     }
149:     lp_table[minor].flags |= LP_STAT_BUS;
150:     return 0;
151: }
152:
153: int lp_close(struct inode *i, struct fd *fd_table)
154: {
155:     int minor;
156:
157:     minor = MINOR(i->rdev);
158:     if(!TEST_MINOR(lp_device.minors, minor)) {
159:         return -ENXIO;
160:     }
161:     lp_table[minor].flags &= ~LP_STAT_BUS;
162:     return 0;
163: }
164:
165: int lp_write(struct inode *i, struct fd *fd_table, const char *buffer, __size_t
count)
166: {
167:     unsigned int n;
168:     int bytes_written, total_written;
169:     int minor;
170:
171:     minor = MINOR(i->rdev);
172:     if(!TEST_MINOR(lp_device.minors, minor)) {
173:         return -ENXIO;
174:     }
175:
176:     total_written = 0;
177:     for(n = 0; n < count; n++) {
178:         bytes_written = lp_write_data(minor, buffer[n]);
179:         if(bytes_written != 1) {
180:             break;
181:         }
182:         total_written += bytes_written;
183:     }
184:
185:     return total_written;
186: }
187:
188: void lp_init(void)
189: {
190:     int n;
191:     unsigned char ctrl;
192:
193:     for(n = 0; n < LP_MINORS; n++) {
194:         if(!lp_probe(n)) {
195:             ctrl = inport_b(lp_table[n].ctrl);
196:             ctrl &= ~LP_CTRL_AUT; /* disable auto LF */
197:             ctrl |= LP_CTRL_INI; /* initialize */
198:             ctrl |= LP_CTRL_SEL; /* select in */
199:             ctrl &= ~LP_CTRL_IRQ; /* disable IRQ */
200:             ctrl &= ~LP_CTRL_BID; /* disable bidirectional mode */

```

drivers/char/lp.c

Page 4/4

```
201:         outport_b(lp_table[n].ctrl, ctrl);
202:         lp_table[n].flags |= LP_CTRL_SEL;
203:         printk("lp%d          0x%04X-0x%04X          -          \n", n,
lp_table[n].data, lp_table[n].data + 2);
204:         SET_MINOR(lp_device.minors, n);
205:     }
206: }
207:
208:     for(n = 0; n < LP_MINORS; n++) {
209:         if(lp_table[n].flags & LP_CTRL_SEL) {
210:             if(register_device(CHR_DEV, &lp_device)) {
211:                 printk("WARNING: %s(): unable to register lp dev
ice.\n", __FUNCTION__);
212:             }
213:             break;
214:         }
215:     }
216: }
```

drivers/char/Makefile

Page 1/1

```
1: # fiwix/drivers/char/Makefile
2: #
3: # Copyright 2018, Jordi Sanfeliu. All rights reserved.
4: # Distributed under the terms of the Fiwix License.
5: #
6:
7: .S.o:
8:     $(CC) -traditional -I$(INCLUDE) -c -o $@ $<
9: .c.o:
10:     $(CC) $(CFLAGS) -c -o $@ $<
11:
12: OBJS = console.o tty.o tty_queue.o vt.o defkeymap.o keyboard.o memdev.o lp.o
13:
14: char:     $(OBJS)
15:             $(LD) $(LDFLAGS) -r $(OBJS) -o char.o
16:
17: clean:
18:             rm -f *.o
19:
```


drivers/char/memdev.c

Page 1/7

```

1: /*
2:  * fiwix/drivers/char/memdev.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/kernel.h>
10: #include <fiwix/memdev.h>
11: #include <fiwix/devices.h>
12: #include <fiwix/fs.h>
13: #include <fiwix/errno.h>
14: #include <fiwix/mm.h>
15: #include <fiwix/mman.h>
16: #include <fiwix/bios.h>
17: #include <fiwix/stdio.h>
18: #include <fiwix/string.h>
19:
20: static struct fs_operations mem_driver_fsop = {
21:     0,
22:     0,
23:
24:     mem_open,
25:     mem_close,
26:     mem_read,
27:     mem_write,
28:     NULL,                /* ioctl */
29:     mem_lseek,
30:     NULL,                /* readdir */
31:     mem_mmap,
32:     NULL,                /* select */
33:
34:     NULL,                /* readlink */
35:     NULL,                /* followlink */
36:     NULL,                /* bmap */
37:     NULL,                /* lockup */
38:     NULL,                /* rmdir */
39:     NULL,                /* link */
40:     NULL,                /* unlink */
41:     NULL,                /* symlink */
42:     NULL,                /* mkdir */
43:     NULL,                /* mknod */
44:     NULL,                /* truncate */
45:     NULL,                /* create */
46:     NULL,                /* rename */
47:
48:     NULL,                /* read_block */
49:     NULL,                /* write_block */
50:
51:     NULL,                /* read_inode */
52:     NULL,                /* write_inode */
53:     NULL,                /* ialloc */
54:     NULL,                /* ifree */
55:     NULL,                /* statfs */
56:     NULL,                /* read_superblock */
57:     NULL,                /* remount_fs */
58:     NULL,                /* write_superblock */
59:     NULL,                /* release_superblock */
60: };
61:
62: static struct fs_operations kmem_driver_fsop = {
63:     0,
64:     0,
65:
66:     kmem_open,
67:     kmem_close,

```

drivers/char/memdev.c

Page 2/7

```

68:         kmem_read,
69:         kmem_write,
70:         NULL,                /* ioctl */
71:         kmem_lseek,
72:         NULL,                /* readdir */
73:         mem_mmap,
74:         NULL,                /* select */
75:
76:         NULL,                /* readlink */
77:         NULL,                /* followlink */
78:         NULL,                /* bmap */
79:         NULL,                /* lockup */
80:         NULL,                /* rmdir */
81:         NULL,                /* link */
82:         NULL,                /* unlink */
83:         NULL,                /* symlink */
84:         NULL,                /* mkdir */
85:         NULL,                /* mknod */
86:         NULL,                /* truncate */
87:         NULL,                /* create */
88:         NULL,                /* rename */
89:
90:         NULL,                /* read_block */
91:         NULL,                /* write_block */
92:
93:         NULL,                /* read_inode */
94:         NULL,                /* write_inode */
95:         NULL,                /* ialloc */
96:         NULL,                /* ifree */
97:         NULL,                /* statfs */
98:         NULL,                /* read_superblock */
99:         NULL,                /* remount_fs */
100:        NULL,                /* write_superblock */
101:        NULL,                /* release_superblock */
102:    };
103:
104:    static struct fs_operations null_driver_fsop = {
105:        0,
106:        0,
107:
108:        null_open,
109:        null_close,
110:        null_read,
111:        null_write,
112:        NULL,                /* ioctl */
113:        null_lseek,
114:        NULL,                /* readdir */
115:        NULL,                /* mmap */
116:        NULL,                /* select */
117:
118:        NULL,                /* readlink */
119:        NULL,                /* followlink */
120:        NULL,                /* bmap */
121:        NULL,                /* lockup */
122:        NULL,                /* rmdir */
123:        NULL,                /* link */
124:        NULL,                /* unlink */
125:        NULL,                /* symlink */
126:        NULL,                /* mkdir */
127:        NULL,                /* mknod */
128:        NULL,                /* truncate */
129:        NULL,                /* create */
130:        NULL,                /* rename */
131:
132:        NULL,                /* read_block */
133:        NULL,                /* write_block */
134:

```

drivers/char/memdev.c

Page 3/7

```

135:     NULL,                /* read_inode */
136:     NULL,                /* write_inode */
137:     NULL,                /* ialloc */
138:     NULL,                /* ifree */
139:     NULL,                /* statfs */
140:     NULL,                /* read_superblock */
141:     NULL,                /* remount_fs */
142:     NULL,                /* write_superblock */
143:     NULL,                /* release_superblock */
144: };
145:
146: static struct fs_operations zero_driver_fsop = {
147:     0,
148:     0,
149:
150:     zero_open,
151:     zero_close,
152:     zero_read,
153:     zero_write,
154:     NULL,                /* ioctl */
155:     zero_lseek,
156:     NULL,                /* readdir */
157:     NULL,                /* mmap */
158:     NULL,                /* select */
159:
160:     NULL,                /* readlink */
161:     NULL,                /* followlink */
162:     NULL,                /* bmap */
163:     NULL,                /* lockup */
164:     NULL,                /* rmdir */
165:     NULL,                /* link */
166:     NULL,                /* unlink */
167:     NULL,                /* symlink */
168:     NULL,                /* mkdir */
169:     NULL,                /* mknod */
170:     NULL,                /* truncate */
171:     NULL,                /* create */
172:     NULL,                /* rename */
173:
174:     NULL,                /* read_block */
175:     NULL,                /* write_block */
176:
177:     NULL,                /* read_inode */
178:     NULL,                /* write_inode */
179:     NULL,                /* ialloc */
180:     NULL,                /* ifree */
181:     NULL,                /* statfs */
182:     NULL,                /* read_superblock */
183:     NULL,                /* remount_fs */
184:     NULL,                /* write_superblock */
185:     NULL,                /* release_superblock */
186: };
187:
188: static struct fs_operations memdev_driver_fsop = {
189:     0,
190:     0,
191:
192:     memdev_open,
193:     NULL,                /* close */
194:     NULL,                /* read */
195:     NULL,                /* write */
196:     NULL,                /* ioctl */
197:     NULL,                /* lseek */
198:     NULL,                /* readdir */
199:     NULL,                /* mmap */
200:     NULL,                /* select */
201:

```

drivers/char/memdev.c

Page 4/7

```

202:         NULL,                /* readlink */
203:         NULL,                /* followlink */
204:         NULL,                /* bmap */
205:         NULL,                /* lockup */
206:         NULL,                /* rmdir */
207:         NULL,                /* link */
208:         NULL,                /* unlink */
209:         NULL,                /* symlink */
210:         NULL,                /* mkdir */
211:         NULL,                /* mknod */
212:         NULL,                /* truncate */
213:         NULL,                /* create */
214:         NULL,                /* rename */
215:
216:         NULL,                /* read_block */
217:         NULL,                /* write_block */
218:
219:         NULL,                /* read_inode */
220:         NULL,                /* write_inode */
221:         NULL,                /* ialloc */
222:         NULL,                /* ifree */
223:         NULL,                /* statfs */
224:         NULL,                /* read_superblock */
225:         NULL,                /* remount_fs */
226:         NULL,                /* write_superblock */
227:         NULL,                /* release_superblock */
228: };
229:
230: static struct device memdev_device = {
231:     "mem",
232:     -1,
233:     MEMDEV_MAJOR,
234:     { 0, 0, 0, 0, 0, 0, 0, 0 },
235:     0,
236:     NULL,
237:     &memdev_driver_fsop,
238: };
239:
240: int mem_open(struct inode *i, struct fd *fd_table)
241: {
242:     return 0;
243: }
244:
245: int mem_close(struct inode *i, struct fd *fd_table)
246: {
247:     return 0;
248: }
249:
250: int mem_read(struct inode *i, struct fd *fd_table, char *buffer, __size_t count)
251: {
252:     unsigned int physical_memory;
253:
254:     physical_memory = (kstat.physical_pages << PAGE_SHIFT);
255:     if(fd_table->offset >= physical_memory) {
256:         return 0;
257:     }
258:     count = MIN(count, physical_memory - fd_table->offset);
259:     memcpy_b(buffer, (void *)P2V(fd_table->offset), count);
260:     fd_table->offset += count;
261:     return count;
262: }
263:
264: int mem_write(struct inode *i, struct fd *fd_table, const char *buffer, __size_t
count)
265: {
266:     unsigned int physical_memory;
267:

```

drivers/char/memdev.c

Page 5/7

```

268:     physical_memory = (kstat.physical_pages << PAGE_SHIFT);
269:     if(fd_table->offset >= physical_memory) {
270:         return 0;
271:     }
272:     count = MIN(count, physical_memory - fd_table->offset);
273:     memcpy_b((void *)P2V(fd_table->offset), buffer, count);
274:     fd_table->offset += count;
275:     return count;
276: }
277:
278: int mem_lseek(struct inode *i, __off_t offset)
279: {
280:     return offset;
281: }
282:
283: int kmem_open(struct inode *i, struct fd *fd_table)
284: {
285:     return 0;
286: }
287:
288: int kmem_close(struct inode *i, struct fd *fd_table)
289: {
290:     return 0;
291: }
292:
293: int kmem_read(struct inode *i, struct fd *fd_table, char *buffer, __size_t count
)
294: {
295:     memcpy_b(buffer, (void *)P2V(fd_table->offset), count);
296:     fd_table->offset += count;
297:     return count;
298: }
299:
300: int kmem_write(struct inode *i, struct fd *fd_table, const char *buffer, __size_
t count)
301: {
302:     memcpy_b((void *)P2V(fd_table->offset), buffer, count);
303:     fd_table->offset += count;
304:     return count;
305: }
306:
307: int kmem_lseek(struct inode *i, __off_t offset)
308: {
309:     return offset;
310: }
311:
312: int null_open(struct inode *i, struct fd *fd_table)
313: {
314:     return 0;
315: }
316:
317: int null_close(struct inode *i, struct fd *fd_table)
318: {
319:     return 0;
320: }
321:
322: int null_read(struct inode *i, struct fd *fd_table, char *buffer, __size_t count
)
323: {
324:     return 0;
325: }
326:
327: int null_write(struct inode *i, struct fd *fd_table, const char *buffer, __size_
t count)
328: {
329:     return count;
330: }

```

drivers/char/memdev.c

Page 6/7

```

331:
332: int null_lseek(struct inode *i, __off_t offset)
333: {
334:     return offset;
335: }
336:
337: int zero_open(struct inode *i, struct fd *fd_table)
338: {
339:     return 0;
340: }
341:
342: int zero_close(struct inode *i, struct fd *fd_table)
343: {
344:     return 0;
345: }
346:
347: int zero_read(struct inode *i, struct fd *fd_table, char *buffer, __size_t count
)
348: {
349:     memset_b(buffer, NULL, count);
350:     return count;
351: }
352:
353: int zero_write(struct inode *i, struct fd *fd_table, const char *buffer, __size_
t count)
354: {
355:     return count;
356: }
357:
358: int zero_lseek(struct inode *i, __off_t offset)
359: {
360:     return offset;
361: }
362:
363: int memdev_open(struct inode *i, struct fd *fd_table)
364: {
365:     unsigned char minor;
366:
367:     minor = MINOR(i->rdev);
368:     switch(minor) {
369:         case MEMDEV_MEM:
370:             i->fsop = &mem_driver_fsop;
371:             break;
372:         case MEMDEV_KMEM:
373:             i->fsop = &kmem_driver_fsop;
374:             break;
375:         case MEMDEV_NULL:
376:             i->fsop = &null_driver_fsop;
377:             break;
378:         case MEMDEV_ZERO:
379:             i->fsop = &zero_driver_fsop;
380:             break;
381:         default:
382:             return -ENXIO;
383:     }
384:     if(i->fsop->open) {
385:         return i->fsop->open(i, fd_table);
386:     }
387:     return 0;
388: }
389:
390: /*
391:  * This function maps a range of physical addresses marked as not available for
392:  * use in the BIOS memory map, like the video RAM.
393:  */
394: int mem_mmap(struct inode *i, struct vma *vma)
395: {

```

drivers/char/memdev.c

Page 7/7

```

396:         unsigned int addr, length;
397:
398:         length = (vma->end - vma->start) & PAGE_MASK;
399:
400:         /* this breaks down the range in 4KB chunks */
401:         for(addr = 0; addr < length; addr += PAGE_SIZE) {
402:             /* map the page only if is NOT available in the BIOS map */
403:             if(!addr_in_bios_map(vma->offset + addr)) {
404:                 if(!map_page(current, (vma->start + addr) & PAGE_MASK, (
vma->offset + addr) & PAGE_MASK, PROT_READ | PROT_WRITE)) {
405:                     return -ENOMEM;
406:                 }
407:             } else {
408:                 printk("ERROR: %s(): mapping AVAILABLE pages in BIOS mem
ory map isn't supported.\n", __FUNCTION__);
409:                 printk("\tinvalid mapping: 0x%08x -> 0x%08x\n", (vma->st
art + addr) & PAGE_MASK, (vma->offset + addr) & PAGE_MASK);
410:                 return -EAGAIN;
411:             }
412:         }
413:         invalidate_tlb();
414:         return 0;
415:     }
416:
417: void memdev_init(void)
418: {
419:     if(register_device(CHR_DEV, &memdev_device)) {
420:         printk("ERROR: %s(): unable to register memory devices.\n", __FU
NCTION__);
421:         return;
422:     }
423:     SET_MINOR(memdev_device.minors, MEMDEV_MEM);
424:     SET_MINOR(memdev_device.minors, MEMDEV_KMEM);
425:     SET_MINOR(memdev_device.minors, MEMDEV_NULL);
426:     SET_MINOR(memdev_device.minors, MEMDEV_ZERO);
427: }

```

drivers/char/tty.c

Page 1/14

```

1: /*
2:  * fiwix/drivers/char/tty.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/ioctl.h>
10: #include <fiwix/tty.h>
11: #include <fiwix/ctype.h>
12: #include <fiwix/console.h>
13: #include <fiwix/pic.h>
14: #include <fiwix/devices.h>
15: #include <fiwix/fs.h>
16: #include <fiwix/errno.h>
17: #include <fiwix/sched.h>
18: #include <fiwix/timer.h>
19: #include <fiwix/sleep.h>
20: #include <fiwix/process.h>
21: #include <fiwix/fcntl.h>
22: #include <fiwix/stdio.h>
23: #include <fiwix/string.h>
24:
25: struct tty tty_table[NR_TTYS];
26: extern short int current_cons;
27:
28: static void wait_vtime_off(unsigned int arg)
29: {
30:     unsigned int *fn = (unsigned int *)arg;
31:
32:     wakeup(fn);
33: }
34:
35: static void get_termio(struct tty *tty, struct termio *termio)
36: {
37:     int n;
38:
39:     termio->c_iflag = tty->termios.c_iflag;
40:     termio->c_oflag = tty->termios.c_oflag;
41:     termio->c_cflag = tty->termios.c_cflag;
42:     termio->c_lflag = tty->termios.c_lflag;
43:     termio->c_line = tty->termios.c_line;
44:     for(n = 0; n < NCC; n++) {
45:         termio->c_cc[n] = tty->termios.c_cc[n];
46:     }
47: }
48:
49: static void set_termio(struct tty *tty, struct termio *termio)
50: {
51:     int n;
52:
53:     tty->termios.c_iflag = termio->c_iflag;
54:     tty->termios.c_oflag = termio->c_oflag;
55:     tty->termios.c_cflag = termio->c_cflag;
56:     tty->termios.c_lflag = termio->c_lflag;
57:     tty->termios.c_line = termio->c_line;
58:     for(n = 0; n < NCC; n++) {
59:         tty->termios.c_cc[n] = termio->c_cc[n];
60:     }
61: }
62:
63: static void out_char(struct tty *tty, unsigned char ch)
64: {
65:     if(ISCNTRL(ch) && !ISSPACE(ch) && (tty->termios.c_lflag & ECHOCTL)) {
66:         if(tty->lnext || (!tty->lnext && ch != tty->termios.c_cc[VEOF]))

```


drivers/char/tty.c

Page 2/14

```

67:             tty_queue_putchar(tty, &tty->write_q, '^');
68:             tty_queue_putchar(tty, &tty->write_q, ch + 64);
69:         }
70:     } else {
71:         tty_queue_putchar(tty, &tty->write_q, ch);
72:     }
73: }
74:
75: static void erase_char(struct tty *tty, unsigned char erasechar)
76: {
77:     unsigned char ch;
78:
79:     if(erasechar == tty->termios.c_cc[VERASE]) {
80:         if((ch = tty_queue_unputchar(&tty->cooked_q)) {
81:             if(tty->termios.c_lflag & ECHO) {
82:                 tty_queue_putchar(tty, &tty->write_q, '\b');
83:                 tty_queue_putchar(tty, &tty->write_q, ' ');
84:                 tty_queue_putchar(tty, &tty->write_q, '\b');
85:                 if(ch == '\t') {
86:                     tty->deltab(tty);
87:                 }
88:                 if(ISCNTRL(ch) && !ISSPACE(ch) && tty->termios.c
_lflag & ECHOCTL) {
89:                     tty_queue_putchar(tty, &tty->write_q, '\
b');
90:                     tty_queue_putchar(tty, &tty->write_q, '
');
91:                     tty_queue_putchar(tty, &tty->write_q, '\
b');
92:                 }
93:             }
94:         }
95:     }
96:     if(erasechar == tty->termios.c_cc[VWERASE]) {
97:         unsigned char word_seen = 0;
98:
99:         while(tty->cooked_q.count > 0) {
100:             ch = LAST_CHAR(&tty->cooked_q);
101:             if((ch == ' ' || ch == '\t') && word_seen) {
102:                 break;
103:             }
104:             if(ch != ' ' && ch != '\t') {
105:                 word_seen = 1;
106:             }
107:             erase_char(tty, tty->termios.c_cc[VERASE]);
108:         }
109:     }
110:     if(erasechar == tty->termios.c_cc[VKILL]) {
111:         while(tty->cooked_q.count > 0) {
112:             erase_char(tty, tty->termios.c_cc[VERASE]);
113:         }
114:         if(tty->termios.c_lflag & ECHOK && !(tty->termios.c_lflag & ECHO
E)) {
115:             tty_queue_putchar(tty, &tty->write_q, '\n');
116:         }
117:     }
118: }
119:
120: int register_tty(__dev_t dev)
121: {
122:     int n;
123:
124:     for(n = 0; n < NR_TTYS; n++) {
125:         if(tty_table[n].dev == dev) {
126:             printk("ERROR: %s(): tty device %d,%d already registered
!\n", __FUNCTION__, MAJOR(dev), MINOR(dev));
127:             return 1;

```

drivers/char/tty.c

Page 3/14

```

128:         }
129:         if(!tty_table[n].dev) {
130:             tty_table[n].dev = dev;
131:             tty_table[n].count = 0;
132:             return 0;
133:         }
134:     }
135:     printk("ERROR: %s(): tty table is full!\n", __FUNCTION__);
136:     return 1;
137: }
138:
139: struct tty * get_tty(__dev_t dev)
140: {
141:     int n;
142:
143:     if(!dev) {
144:         return NULL;
145:     }
146:
147:     /* /dev/console = system console */
148:     if(dev == MKDEV(SYSCON_MAJOR, 1)) {
149:         dev = (__dev_t)_syscondev;
150:     }
151:
152:     /* /dev/tty0 = current virtual console */
153:     if(dev == MKDEV(VCONSOLES_MAJOR, 0)) {
154:         dev = MKDEV(VCONSOLES_MAJOR, current_cons);
155:     }
156:
157:     /* /dev/tty = controlling TTY device */
158:     if(dev == MKDEV(SYSCON_MAJOR, 0)) {
159:         if(!current->ctty) {
160:             return NULL;
161:         }
162:         dev = current->ctty->dev;
163:     }
164:
165:     for(n = 0; n < NR_TTYS; n++) {
166:         if(tty_table[n].dev != dev) {
167:             continue;
168:         }
169:         return &tty_table[n];
170:     }
171:     return NULL;
172: }
173:
174: void disassociate_ctty(struct tty *tty)
175: {
176:     struct proc *p;
177:
178:     if(!tty) {
179:         return;
180:     }
181:
182:     /* this tty is no longer the controlling tty of any session */
183:     tty->pgid = tty->sid = 0;
184:
185:     /* clear the controlling tty for all processes in the same SID */
186:     FOR_EACH_PROCESS(p) {
187:         if((p->state != PROC_UNUSED) && (p->sid == current->sid)) {
188:             p->ctty = NULL;
189:         }
190:     }
191:     kill_pgrp(current->pgid, SIGHUP);
192:     kill_pgrp(current->pgid, SIGCONT);
193: }
194:

```

drivers/char/tty.c

Page 4/14

```

195: void termios_reset(struct tty *tty)
196: {
197:     tty->termios.c_iflag = ICRNL | IXON | IXOFF;
198:     tty->termios.c_oflag = OPOST | ONLCR;
199:     tty->termios.c_cflag = B38400 | CS8 | HUPCL | CREAD | CLOCAL;
200:     tty->termios.c_lflag = ISIG | ICANON | ECHO | ECHOE | ECHOK | ECHOCTL |
ECHOKE | IEXTEN;
201:     tty->termios.c_line = 0;
202:     tty->termios.c_cc[VINTR] = 3; /* ^C */
203:     tty->termios.c_cc[VQUIT] = 28; /* ^\ */
204:     tty->termios.c_cc[VERASE] = BS; /* ^? (127) not '\b' (^H) */
205:     tty->termios.c_cc[VKILL] = 21; /* ^U */
206:     tty->termios.c_cc[VEOF] = 4; /* ^D */
207:     tty->termios.c_cc[VTIME] = 0;
208:     tty->termios.c_cc[VMIN] = 1;
209:     tty->termios.c_cc[VSWTC] = 0;
210:     tty->termios.c_cc[VSTART] = 17; /* ^Q */
211:     tty->termios.c_cc[VSTOP] = 19; /* ^S */
212:     tty->termios.c_cc[VSUSP] = 26; /* ^Z */
213:     tty->termios.c_cc[VEOL] = '\n'; /* ^J */
214:     tty->termios.c_cc[VREPRINT] = 18; /* ^R */
215:     tty->termios.c_cc[VDISCARD] = 15; /* ^O */
216:     tty->termios.c_cc[VWERASE] = 23; /* ^W */
217:     tty->termios.c_cc[VLNEXT] = 22; /* ^V */
218:     tty->termios.c_cc[VEOL2] = 0;
219: }
220:
221: void do_cook(struct tty *tty)
222: {
223:     int n;
224:     unsigned char ch;
225:     struct cblock *cb;
226:
227:     while(tty->read_q.count > 0) {
228:         ch = tty_queue_getchar(&tty->read_q);
229:
230:         if((tty->termios.c_lflag & ISIG) && !tty->lnext) {
231:             if(ch == tty->termios.c_cc[VINTR]) {
232:                 if(!(tty->termios.c_lflag & NOFLSH)) {
233:                     tty_queue_flush(&tty->read_q);
234:                     tty_queue_flush(&tty->cooked_q);
235:                 }
236:                 if(tty->pgid > 0) {
237:                     kill_pgrp(tty->pgid, SIGINT);
238:                 }
239:                 break;
240:             }
241:             if(ch == tty->termios.c_cc[VQUIT]) {
242:                 if(tty->pgid > 0) {
243:                     kill_pgrp(tty->pgid, SIGQUIT);
244:                 }
245:                 break;
246:             }
247:             if(ch == tty->termios.c_cc[VSUSP]) {
248:                 if(tty->pgid > 0) {
249:                     kill_pgrp(tty->pgid, SIGTSTP);
250:                 }
251:                 break;
252:             }
253:         }
254:
255:         if(tty->termios.c_iflag & ISTRIP) {
256:             ch = TOASCII(ch);
257:         }
258:         if(tty->termios.c_iflag & IUCLC) {
259:             if(ISUPPER(ch)) {
260:                 ch = TOLOWER(ch);

```

drivers/char/tty.c

Page 5/14

```

261:         }
262:     }
263:
264:     if(!tty->lnext) {
265:         if(ch == '\r') {
266:             if(tty->termios.c_iflag & IGNCR) {
267:                 continue;
268:             }
269:             if(tty->termios.c_iflag & ICRNL) {
270:                 ch = '\n';
271:             }
272:         } else {
273:             if(ch == '\n') {
274:                 if(tty->termios.c_iflag & INLCR) {
275:                     ch = '\r';
276:                 }
277:             }
278:         }
279:     }
280:
281:     if(tty->termios.c_lflag & ICANON && !tty->lnext) {
282:         if(ch == tty->termios.c_cc[VERASE] || ch == tty->termios
.c_cc[VWERASE] || ch == tty->termios.c_cc[VKILL]) {
283:             erase_char(tty, ch);
284:             continue;
285:         }
286:
287:         if(ch == tty->termios.c_cc[VREPRINT]) {
288:             out_char(tty, ch);
289:             tty_queue_putchar(tty, &tty->write_q, '\n');
290:             cb = tty->cooked_q.head;
291:             while(cb) {
292:                 for(n = 0; n < cb->end_off; n++) {
293:                     if(n >= cb->start_off) {
294:                         out_char(tty, cb->data[n
]);
295:                     }
296:                 }
297:                 cb = cb->next;
298:             }
299:             continue;
300:         }
301:
302:         if(ch == tty->termios.c_cc[VLNEXT] && tty->termios.c_lfl
ag & IEXTEN) {
303:             tty->lnext = 1;
304:             if(tty->termios.c_lflag & ECHOCTL) {
305:                 tty_queue_putchar(tty, &tty->write_q, '^
');
306:                 tty_queue_putchar(tty, &tty->write_q, '\
b');
307:             }
308:             break;
309:         }
310:
311:         if(tty->termios.c_iflag & IXON) {
312:             if(ch == tty->termios.c_cc[VSTART]) {
313:                 tty->start(tty);
314:                 continue;
315:             }
316:             if(ch == tty->termios.c_cc[VSTOP]) {
317:                 tty->stop(tty);
318:                 continue;
319:             }
320:             if(tty->termios.c_iflag & IXANY) {
321:                 tty->start(tty);
322:             }

```

drivers/char/tty.c

Page 6/14

```

323:         }
324:     }
325:
326:     /* using ISSPACE here makes LNEXT working incorrectly, FIXME */
327:     if(tty->termios.c_lflag & ICANON) {
328:         if(ISCNTRL(ch) && !ISSPACE(ch) && (tty->termios.c_lflag
& ECHOCTL)) {
329:             out_char(tty, ch);
330:             tty_queue_putchar(tty, &tty->cooked_q, ch);
331:             tty->lnext = 0;
332:             continue;
333:         }
334:         if(ch == '\n') {
335:             tty->canon_data = 1;
336:         }
337:     }
338:
339:     if(tty->termios.c_lflag & ECHO) {
340:         out_char(tty, ch);
341:     } else {
342:         if((tty->termios.c_lflag & ECHONL) && (ch == '\n')) {
343:             out_char(tty, ch);
344:         }
345:     }
346:     tty_queue_putchar(tty, &tty->cooked_q, ch);
347:     tty->lnext = 0;
348: }
349: tty->output(tty);
350: wakeup(&tty->cooked_q);
351: if(!(tty->termios.c_lflag & ICANON) || ((tty->termios.c_lflag & ICANON)
&& tty->canon_data)) {
352:     wakeup(&do_select);
353: }
354: }
355:
356: int tty_open(struct inode *i, struct fd *fd_table)
357: {
358:     int noctty_flag;
359:     __dev_t dev;
360:     struct tty *tty;
361:
362:     noctty_flag = fd_table->flags & O_NOCTTY;
363:
364:     dev = i->rdev;
365:
366:     if(MAJOR(i->rdev) == SYSCON_MAJOR && MINOR(i->rdev) == 0) {
367:         if(!current->ctty) {
368:             return -ENXIO;
369:         }
370:         dev = i->rdev;
371:     }
372:
373:     if(MAJOR(dev) == VCONSOLES_MAJOR && MINOR(dev) == 0) {
374:         noctty_flag = 1;
375:     }
376:
377:     if(!(tty = get_tty(dev))) {
378:         printk("%s(): oops! (%x)\n", __FUNCTION__, dev);
379:         printk("_syscondev = %x\n", _syscondev);
380:         return -ENXIO;
381:     }
382:     tty->count++;
383:
384:     if(SESS_LEADER(current) && !current->ctty && !noctty_flag && !tty->sid)
{
385:         current->ctty = tty;
386:         tty->sid = current->sid;

```

drivers/char/tty.c

Page 7/14

```

387:         tty->pgid = current->pgid;
388:     }
389:     return 0;
390: }
391:
392: int tty_close(struct inode *i, struct fd *fd_table)
393: {
394:     struct proc *p;
395:     struct tty *tty;
396:
397:     if(!(tty = get_tty(i->rdev))) {
398:         printk("%s(): oops! (%x)\n", __FUNCTION__, i->rdev);
399:         return -ENXIO;
400:     }
401:
402:     tty->count = tty->count ? tty->count - 1 : 0;
403:     if(!tty->count) {
404:         tty->reset(tty);
405:         termios_reset(tty);
406:         tty->pgid = tty->sid = 0;
407:
408:         /* this tty is no longer the controlling tty of any process */
409:         FOR_EACH_PROCESS(p) {
410:             if((p->state != PROC_UNUSED) && (p->ctty == tty)) {
411:                 p->ctty = NULL;
412:             }
413:         }
414:     }
415:     return 0;
416: }
417:
418: int tty_read(struct inode *i, struct fd *fd_table, char *buffer, __size_t count)
419: {
420:     unsigned int n, min;
421:     unsigned char ch;
422:     struct tty *tty;
423:     struct callout_req creq;
424:
425:     if(!(tty = get_tty(i->rdev))) {
426:         printk("%s(): oops! (%x)\n", __FUNCTION__, i->rdev);
427:         return -ENXIO;
428:     }
429:
430:     /* only the foreground process group is allowed to read from the tty */
431:     if(i->rdev != MKDEV(VCONSOLES_MAJOR, 0)) { /* /dev/tty0 */
432:         if(current->pgid != tty->pgid) {
433:             if(current->sigaction[SIGTTIN - 1].sa_handler == SIG_IGN
|| current->sigblocked & (1 << (SIGTTIN - 1)) || is_orphaned_pgrp(current->pgid)) {
434:                 return -EIO;
435:             }
436:             kill_pgrp(current->pgid, SIGTTIN);
437:             return -ERESTART;
438:         }
439:     }
440:
441:     n = min = 0;
442:     while(count > 0) {
443:         if(tty->termios.c_lflag & ICANON) {
444:             if((ch = LAST_CHAR(&tty->cooked_q))) {
445:                 if(ch == '\n' || ch == tty->termios.c_cc[VEOL] |
| ch == tty->termios.c_cc[VEOF] || (tty->termios.c_lflag & IEXTEN && ch == tty->termios
.c_cc[VEOL2] && tty->termios.c_cc[VEOL2] != 0)) {
446:
447:                 tty->canon_data = 0;
448:                 /* EOF is not passed to the reading proc
ess */
449:                 if(ch == tty->termios.c_cc[VEOF]) {

```

drivers/char/tty.c

Page 8/14

```

450:                                     tty_queue_unputchar(&tty->cooked
_q);
451:                                     }
452:
453:                                     while(n < count) {
454:                                     if((ch = tty_queue_getchar(&tty-
>cooked_q))) {
455:                                     buffer[n++] = ch;
456:                                     } else {
457:                                     break;
458:                                     }
459:                                     }
460:                                     break;
461:                                     }
462:                                     }
463:                                     } else {
464:                                     if(tty->termios.c_cc[VTIME] > 0) {
465:                                     unsigned int ini_ticks = kstat.ticks;
466:                                     unsigned int timeout;
467:
468:                                     if(!tty->termios.c_cc[VMIN]) {
469:                                     /* VTIME is measured in tenths of second
*/
470:                                     timeout = tty->termios.c_cc[VTIME] * (HZ
/ 10);
471:
472:                                     while(kstat.ticks - ini_ticks < timeout
&& !tty->cooked_q.count) {
473:                                     creq.fn = wait_vtime_off;
474:                                     creq.arg = (unsigned int)&tty->c
ooked_q;
475:                                     add_callout(&creq, timeout);
476:                                     if(fd_table->flags & O_NONBLOCK)
{
477:                                     return -EAGAIN;
478:                                     }
479:                                     if(sleep(&tty->cooked_q, PROC_IN
TERRUPTIBLE)) {
480:                                     return -EINTR;
481:                                     }
482:                                     }
483:                                     while(n < count) {
484:                                     if((ch = tty_queue_getchar(&tty-
>cooked_q))) {
485:                                     buffer[n++] = ch;
486:                                     } else {
487:                                     break;
488:                                     }
489:                                     }
490:                                     break;
491:                                     } else {
492:                                     if(tty->cooked_q.count > 0) {
493:                                     if(n < MIN(tty->termios.c_cc[VMI
N], count)) {
494:                                     ch = tty_queue_getchar(&
tty->cooked_q);
495:                                     buffer[n++] = ch;
496:                                     }
497:                                     if(n >= MIN(tty->termios.c_cc[VM
IN], count)) {
498:                                     del_callout(&creq);
499:                                     break;
500:                                     }
501:                                     timeout = tty->termios.c_cc[VTIM
E] * (HZ / 10);
502:                                     creq.fn = wait_vtime_off;
503:                                     creq.arg = (unsigned int)&tty->c

```

drivers/char/tty.c

Page 9/14

```

cooked_q;
504:                                     add_callout(&creq, timeout);
505:                                     if(fd_table->flags & O_NONBLOCK)
{
506:                                         return -EAGAIN;
507:                                     }
508:                                     if(sleep(&tty->cooked_q, PROC_IN
TERRUPTIBLE)) {
509:                                         return -EINTR;
510:                                     }
511:                                     if(!tty->cooked_q.count) {
512:                                         break;
513:                                     }
514:                                     continue;
515:                                     }
516:                                     }
517:                                     } else {
518:                                         if(tty->cooked_q.count > 0) {
519:                                             if(min < tty->termios.c_cc[VMIN] || !tty
->termios.c_cc[VMIN]) {
520:                                                 if(n < count) {
521:                                                     ch = tty_queue_getchar(&
tty->cooked_q);
522:                                                     buffer[n++] = ch;
523:                                                 }
524:                                                 min++;
525:                                             }
526:                                         }
527:                                         if(min >= tty->termios.c_cc[VMIN]) {
528:                                             break;
529:                                         }
530:                                     }
531:                                     }
532:                                     if(fd_table->flags & O_NONBLOCK) {
533:                                         return -EAGAIN;
534:                                     }
535:                                     if(sleep(&tty->cooked_q, PROC_INTERRUPTIBLE)) {
536:                                         return -EINTR;
537:                                     }
538:                                     }
539:                                     return n;
540:     }
541:
542: int tty_write(struct inode *i, struct fd *fd_table, const char *buffer, __size_t
count)
543: {
544:     unsigned int n;
545:     unsigned char ch;
546:     struct tty *tty;
547:
548:     if(!(tty = get_tty(i->rdev))) {
549:         printk("%s(): oops! (%x)\n", __FUNCTION__, i->rdev);
550:         return -ENXIO;
551:     }
552:
553:     /* only the foreground process group is allowed to write to the tty */
554:     if(i->rdev != MKDEV(VCONSOLES_MAJOR, 0)) { /* /dev/tty0 */
555:         if(current->pgid != tty->pgid && tty->termios.c_lflag & TOSTOP)
{
556:             if(current->sigaction[SIGTTIN - 1].sa_handler != SIG_IGN
&& !(current->sigblocked & (1 << (SIGTTIN - 1)))) {
557:                 if(is_orphaned_pgrp(current->pgid)) {
558:                     return -EIO;
559:                 }
560:                 kill_pgrp(current->pgid, SIGTTOU);
561:                 return -ERESTART;
562:             }

```


drivers/char/tty.c

Page 10/14

```

563:         }
564:     }
565:
566:     n = 0;
567:     for(;;) {
568:         if(current->sigpending & ~current->sigblocked) {
569:             return -ERESTART;
570:         }
571:         while(count && n < count) {
572:             ch = *(buffer + n);
573:             /* FIXME: check if *(buffer + n) address is valid */
574:             if(tty_queue_putchar(tty, &tty->write_q, ch) < 0) {
575:                 break;
576:             }
577:             n++;
578:         }
579:         tty->output(tty);
580:         if(n == count) {
581:             break;
582:         }
583:         if(tty->write_q.count > 0) {
584:             if(sleep(&tty->write_q, PROC_INTERRUPTIBLE)) {
585:                 return -EINTR;
586:             }
587:         }
588:         do_sched();
589:     }
590:     return n;
591: }
592:
593: /* FIXME: http://www.lafn.org/~dave/linux/termios.txt (doc/termios.txt) */
594: int tty_ioctl(struct inode *i, int cmd, unsigned long int arg)
595: {
596:     struct proc *p;
597:     struct tty *tty;
598:     int errno;
599:
600:     if(!(tty = get_tty(i->rdev))) {
601:         printk("%s(): oops! (%x)\n", __FUNCTION__, i->rdev);
602:         return -ENXIO;
603:     }
604:
605:     switch(cmd) {
606:         /*
607:          * Fetch and store the current terminal parameters to a termios
608:          * structure pointed to by the argument.
609:          */
610:         case TCGETS:
611:             if((errno = check_user_area(VERIFY_WRITE, (void *)arg, s
sizeof(struct termios)))) {
612:                 return errno;
613:             }
614:             memcpy_b((void *)arg, &tty->termios, sizeof(struct termi
os));
615:             break;
616:
617:         /*
618:          * Set the current terminal parameters according to the
619:          * values in the termios structure pointed to by the argument.
620:          */
621:         case TCSETS:
622:             if((errno = check_user_area(VERIFY_READ, (void *)arg, si
zeof(struct termios)))) {
623:                 return errno;
624:             }
625:             memcpy_b(&tty->termios, (void *)arg, sizeof(struct termi
os));

```

drivers/char/tty.c

Page 11/14

```

626:                break;
627:
628:                /*
629:                * Same as TCSETS except it doesn't take effect until all
630:                * the characters queued for output have been transmitted.
631:                */
632:                case TCSETSW:
633:                if((errno = check_user_area(VERIFY_READ, (void *)arg, sizeof(struct termios)))) {
zeof(struct termios))) {
634:                return errno;
635:                }
636:                memcpy_b(&tty->termios, (void *)arg, sizeof(struct termios));
os));
637:                break;
638:
639:                /*
640:                * Same as TCSETSW except that all characters queued for
641:                * input are discarded.
642:                */
643:                case TCSETSF:
644:                if((errno = check_user_area(VERIFY_READ, (void *)arg, sizeof(struct termios)))) {
zeof(struct termios))) {
645:                return errno;
646:                }
647:                memcpy_b(&tty->termios, (void *)arg, sizeof(struct termios));
os));
648:                tty_queue_flush(&tty->read_q);
649:                break;
650:
651:                /*
652:                * Fetches and stores the current terminal parameters to a
653:                * termio structure pointed to by the argument.
654:                */
655:                case TCGETA:
656:                if((errno = check_user_area(VERIFY_WRITE, (void *)arg, sizeof(struct termio)))) {
sizeof(struct termio)))) {
657:                return errno;
658:                }
659:                get_termio(tty, (struct termio *)arg);
660:                break;
661:
662:                /*
663:                * Set the current terminal parameters according to the
664:                * values in the termio structure pointed to by the argument.
665:                */
666:                case TCSETA:
667:                if((errno = check_user_area(VERIFY_READ, (void *)arg, sizeof(struct termio)))) {
zeof(struct termio)))) {
668:                return errno;
669:                }
670:                set_termio(tty, (struct termio *)arg);
671:                break;
672:
673:                /*
674:                * Same a TCSET except it doesn't take effect until all
675:                * the characters queued for output have been transmitted.
676:                */
677:                case TCSETAW:
678:                if((errno = check_user_area(VERIFY_READ, (void *)arg, sizeof(struct termio)))) {
zeof(struct termio)))) {
679:                return errno;
680:                }
681:                set_termio(tty, (struct termio *)arg);
682:                break;
683:
684:                /*
685:                * Same as TCSETAW except that all characters queued for

```

drivers/char/tty.c

Page 12/14

```

686:         * input are discarded.
687:         */
688:         case TCSETAF:
689:             if((errno = check_user_area(VERIFY_READ, (void *)arg, si
sizeof(struct termio)))) {
690:                 return errno;
691:             }
692:             set_termio(tty, (struct termio *)arg);
693:             break;
694:
695:         case TCXONC:
696:             switch(arg) {
697:                 case TCOOFF:
698:                     tty->stop(tty);
699:                     break;
700:                 case TCOON:
701:                     tty->start(tty);
702:                     break;
703:                 default:
704:                     return -EINVAL;
705:             }
706:             break;
707:         case TCFLSH:
708:             switch(arg) {
709:                 case TCIFLUSH:
710:                     tty_queue_flush(&tty->read_q);
711:                     tty_queue_flush(&tty->cooked_q);
712:                     break;
713:                 case TCOFLUSH:
714:                     tty_queue_flush(&tty->write_q);
715:                     break;
716:                 case TCIOFLUSH:
717:                     tty_queue_flush(&tty->read_q);
718:                     tty_queue_flush(&tty->cooked_q);
719:                     tty_queue_flush(&tty->write_q);
720:                     break;
721:                 default:
722:                     return -EINVAL;
723:             }
724:             break;
725:         case TIOCSCTTY:
726:             if(SESS_LEADER(current) && (current->sid == tty->sid)) {
727:                 return 0;
728:             }
729:             if(!SESS_LEADER(current) || current->ctty) {
730:                 return -EPERM;
731:             }
732:             if(tty->sid) {
733:                 if((arg == 1) && IS_SUPERUSER) {
734:                     FOR_EACH_PROCESS(p) {
735:                         if((p->state != PROC_UNUSED) &&
(p->ctty == tty)) {
736:                             p->ctty = NULL;
737:                         }
738:                     }
739:                 } else {
740:                     return -EPERM;
741:                 }
742:             }
743:             current->ctty = tty;
744:             tty->sid = current->sid;
745:             tty->pgid = current->pgid;
746:             break;
747:         case TIOCGPGRP:
748:             if((errno = check_user_area(VERIFY_WRITE, (void *)arg, s
sizeof(__pid_t)))) {
749:                 return errno;

```

drivers/char/tty.c

Page 13/14

```

750:         }
751:         memcpy_b((void *)arg, &tty->pgid, sizeof(__pid_t));
752:         break;
753:     case TIOCSGRP:
754:         if(arg < 1) {
755:             return -EINVAL;
756:         }
757:         if((errno = check_user_area(VERIFY_READ, (void *)arg, si
zeof(__pid_t)))) {
758:             return errno;
759:         }
760:         memcpy_b(&tty->pgid, (void *)arg, sizeof(__pid_t));
761:         break;
762:     case TIOCGWINSZ:
763:         if((errno = check_user_area(VERIFY_WRITE, (void *)arg, s
izeof(struct winsize)))) {
764:             return errno;
765:         }
766:         memcpy_b((void *)arg, &tty->winsize, sizeof(struct winsi
ze));
767:         break;
768:     case TIOCSWINSZ:
769:     {
770:         struct winsize *ws = (struct winsize *)arg;
771:         short int changed;
772:
773:         if((errno = check_user_area(VERIFY_READ, (void *)arg, si
zeof(struct winsize)))) {
774:             return errno;
775:         }
776:         changed = 0;
777:         if(tty->winsize.ws_row != ws->ws_row) {
778:             changed = 1;
779:         }
780:         if(tty->winsize.ws_col != ws->ws_col) {
781:             changed = 1;
782:         }
783:         if(tty->winsize.ws_xpixel != ws->ws_xpixel) {
784:             changed = 1;
785:         }
786:         if(tty->winsize.ws_ypixel != ws->ws_ypixel) {
787:             changed = 1;
788:         }
789:         tty->winsize.ws_row = ws->ws_row;
790:         tty->winsize.ws_col = ws->ws_col;
791:         tty->winsize.ws_xpixel = ws->ws_xpixel;
792:         tty->winsize.ws_ypixel = ws->ws_ypixel;
793:         if(changed) {
794:             kill_pgrp(tty->pgid, SIGWINCH);
795:         }
796:     }
797:     break;
798:     case TIOCNOTTY:
799:         if(current->ctty != tty) {
800:             return -ENOTTY;
801:         }
802:         if(SESS_LEADER(current)) {
803:             disassociate_ctty(tty);
804:         }
805:         break;
806:     case TIOCLINUX:
807:     {
808:         int val = *(unsigned char *)arg;
809:         if((errno = check_user_area(VERIFY_READ, (void *)arg, si
zeof(unsigned char)))) {
810:             return errno;
811:         }

```

drivers/char/tty.c

Page 14/14

```
812:             switch(val) {
813:                 case 12:             /* get current console */
814:                     return current_cons;
815:                     break;
816:                 default:
817:                     return -EINVAL;
818:                     break;
819:             }
820:             break;
821:         }
822:
823:         default:
824:             return vt_ioctl(tty, cmd, arg);
825:     }
826:     return 0;
827: }
828:
829: int tty_lseek(struct inode *i, __off_t offset)
830: {
831:     return -ESPIPE;
832: }
833:
834: int tty_select(struct inode *i, int flag)
835: {
836:     struct tty *tty;
837:
838:     if(!(tty = get_tty(i->rdev))) {
839:         printk("%s(): oops! (%x)\n", __FUNCTION__, i->rdev);
840:         return 0;
841:     }
842:
843:     switch(flag) {
844:         case SEL_R:
845:             if(tty->cooked_q.count > 0) {
846:                 if(!(tty->termios.c_lflag & ICANON) || ((tty->te
rmios.c_lflag & ICANON) && tty->canon_data)) {
847:                     return 1;
848:                 }
849:             }
850:             break;
851:         case SEL_W:
852:             if(!tty->write_q.count) {
853:                 return 1;
854:             }
855:             break;
856:     }
857:     return 0;
858: }
859:
860: void tty_init(void)
861: {
862:     memset_b(tty_table, NULL, sizeof(tty_table));
863: }
```

drivers/char/tty_queue.c

Page 1/4

```

1: /*
2:  * fiwix/drivers/char/tty_queue.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/kernel.h>
10: #include <fiwix/tty.h>
11: #include <fiwix/errno.h>
12: #include <fiwix/string.h>
13:
14: /*
15:  * tty_queue.c implements a queue using a static-sized doubly linked list of a
16:  * central pool of buffers which covers all ttys.
17:  *
18:  * head                                     tail
19:  * +-----+ +-----+ ... +-----+
20:  * |prev|data|next| |prev|data|next| ... |prev|data|next|
21:  * | / | | --> <-- | | --> ... <-- | | / |
22:  * +-----+ +-----+ ... +-----+
23:  * (cblock)      (cblock)      (cblock)
24:  */
25:
26: struct cblock cblock_pool[CB_POOL_SIZE];
27: struct cblock *cblock_pool_head;
28:
29: static struct cblock *get_free_cblock(void)
30: {
31:     struct cblock *new = NULL;
32:
33:     if(cblock_pool_head) {
34:         new = cblock_pool_head;
35:         cblock_pool_head = cblock_pool_head->next;
36:         new->prev = new->next = NULL;
37:     }
38:     return new;
39: }
40:
41: static void put_free_cblock(struct cblock *old)
42: {
43:     old->prev = NULL;
44:     old->next = cblock_pool_head;
45:     cblock_pool_head = old;
46: }
47:
48: static struct cblock *insert_cblock_in_head(struct clist *q)
49: {
50:     struct cblock *cb;
51:
52:     if(q->cb_num >= NR_CB_QUEUE) {
53:         return NULL;
54:     }
55:     if(!(cb = get_free_cblock())) {
56:         return NULL;
57:     }
58:
59:     /* initialize cblock */
60:     cb->start_off = cb->end_off = 0;
61:     memset_b(cb->data, 0, CBSIZE);
62:     cb->prev = cb->next = NULL;
63:     q->cb_num++;
64:
65:     if(!q->head) {
66:         q->head = q->tail = cb;
67:     } else {

```

drivers/char/tty_queue.c

Page 2/4

```

68:         cb->prev = NULL;
69:         cb->next = q->head;
70:         q->head->prev = cb;
71:         q->head = cb;
72:     }
73:     return cb;
74: }
75:
76: static struct cblock *insert_cblock_in_tail(struct clist *q)
77: {
78:     struct cblock *cb;
79:
80:     if(q->cb_num >= NR_CB_QUEUE) {
81:         return NULL;
82:     }
83:     if(!(cb = get_free_cblock())) {
84:         return NULL;
85:     }
86:
87:     /* initialize cblock */
88:     cb->start_off = cb->end_off = 0;
89:     memset_b(cb->data, 0, CBSIZE);
90:     cb->prev = cb->next = NULL;
91:     q->cb_num++;
92:
93:     if(!q->tail) {
94:         q->head = q->tail = cb;
95:     } else {
96:         cb->prev = q->tail;
97:         cb->next = NULL;
98:         q->tail->next = cb;
99:         q->tail = cb;
100:    }
101:    return cb;
102: }
103:
104: static void delete_cblock_from_head(struct clist *q)
105: {
106:     struct cblock *tmp;
107:
108:     if(!q->head) {
109:         return;
110:     }
111:
112:     tmp = q->head;
113:     if(q->head == q->tail) {
114:         q->head = q->tail = NULL;
115:     } else {
116:         q->head = q->head->next;
117:         q->head->prev = NULL;
118:     }
119:
120:     q->count -= tmp->end_off - tmp->start_off;
121:     q->cb_num--;
122:     put_free_cblock(tmp);
123: }
124:
125: static void delete_cblock_from_tail(struct clist *q)
126: {
127:     struct cblock *tmp;
128:
129:     if(!q->tail) {
130:         return;
131:     }
132:
133:     tmp = q->tail;
134:     if(q->head == q->tail) {

```

drivers/char/tty_queue.c

Page 3/4

```

135:         q->head = q->tail = NULL;
136:     } else {
137:         q->tail = q->tail->prev;
138:         q->tail->next = NULL;
139:     }
140:
141:     q->count -= tmp->end_off - tmp->start_off;
142:     q->cb_num--;
143:     put_free_cblock(tmp);
144: }
145:
146: int tty_queue_putchar(struct tty *tty, struct clist *q, unsigned char ch)
147: {
148:     unsigned long int flags;
149:     struct cblock *cb;
150:     int errno;
151:
152:     SAVE_FLAGS(flags); CLI();
153:
154:     cb = q->tail;
155:     if(!cb) {
156:         cb = insert_cblock_in_tail(q);
157:         if(!cb) {
158:             RESTORE_FLAGS(flags);
159:             return -EAGAIN;
160:         }
161:     }
162:
163:     if(cb->end_off < CBSIZE) {
164:         cb->data[cb->end_off] = ch;
165:         cb->end_off++;
166:         q->count++;
167:         errno = 0;
168:     } else if(insert_cblock_in_tail(q)) {
169:         tty_queue_putchar(tty, q, ch);
170:         errno = 0;
171:     } else {
172:         errno = -EAGAIN;
173:     }
174:
175:     RESTORE_FLAGS(flags);
176:     return errno;
177: }
178:
179: int tty_queue_unputchar(struct clist *q)
180: {
181:     unsigned long int flags;
182:     struct cblock *cb;
183:     unsigned char ch;
184:
185:     SAVE_FLAGS(flags); CLI();
186:
187:     ch = 0;
188:     cb = q->tail;
189:     if(cb) {
190:         if(cb->end_off > cb->start_off) {
191:             ch = cb->data[cb->end_off - 1];
192:             cb->end_off--;
193:             q->count--;
194:         }
195:         if(cb->end_off - cb->start_off == 0) {
196:             delete_cblock_from_tail(q);
197:         }
198:     }
199:
200:     RESTORE_FLAGS(flags);
201:     return ch;

```


drivers/char/tty_queue.c

Page 4/4

```
202: }
203:
204: unsigned char tty_queue_getchar(struct clist *q)
205: {
206:     unsigned long int flags;
207:     struct cblock *cb;
208:     unsigned char ch;
209:
210:     SAVE_FLAGS(flags); CLI();
211:
212:     ch = 0;
213:     cb = q->head;
214:     if(cb) {
215:         if(cb->start_off < cb->end_off) {
216:             ch = cb->data[cb->start_off];
217:             cb->start_off++;
218:             q->count--;
219:         }
220:         if(cb->end_off - cb->start_off == 0) {
221:             delete_cblock_from_head(q);
222:         }
223:     }
224:
225:     RESTORE_FLAGS(flags);
226:     return ch;
227: }
228:
229: void tty_queue_flush(struct clist *q)
230: {
231:     unsigned long int flags;
232:
233:     SAVE_FLAGS(flags); CLI();
234:
235:     while(q->head != NULL) {
236:         delete_cblock_from_head(q);
237:     }
238:
239:     RESTORE_FLAGS(flags);
240: }
241:
242: void tty_queue_init(struct tty *tty)
243: {
244:     int n;
245:     struct cblock *cb;
246:
247:     memset_b(cblock_pool, NULL, sizeof(cblock_pool));
248:
249:     /* cblock free list initialization */
250:     cblock_pool_head = NULL;
251:     n = CB_POOL_SIZE;
252:     while(n--) {
253:         cb = &cblock_pool[n];
254:         put_free_cblock(cb);
255:     }
256:     tty->read_q.head = tty->read_q.tail = NULL;
257:     tty->cooked_q.head = tty->cooked_q.tail = NULL;
258:     tty->write_q.head = tty->write_q.tail = NULL;
259: }
```

drivers/char/vt.c

Page 1/4

```

1: /*
2:  * fiwix/drivers/char/vt.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/console.h>
10: #include <fiwix/keyboard.h>
11: #include <fiwix/tty.h>
12: #include <fiwix/vt.h>
13: #include <fiwix/kd.h>
14: #include <fiwix/errno.h>
15: #include <fiwix/stdio.h>
16: #include <fiwix/string.h>
17:
18: int vt_ioctl(struct tty *tty, int cmd, unsigned long int arg)
19: {
20:     struct vconsole *vc;
21:     int n, errno;
22:
23:     /* only virtual consoles support the following ioctl commands */
24:     if(MAJOR(tty->dev) != VCONSOLES_MAJOR) {
25:         return -ENXIO;
26:     }
27:
28:     vc = (struct vconsole *)tty->driver_data;
29:
30:     switch(cmd) {
31:         case KDGETLED:
32:             if((errno = check_user_area(VERIFY_WRITE, (void *)arg, s
sizeof(unsigned char)))) {
33:                 return errno;
34:             }
35:             memset_b((void *)arg, vc->led_status, sizeof(char));
36:             break;
37:
38:         case KDSETLED:
39:             if(arg > 7) {
40:                 return -EINVAL;
41:             }
42:             vc->led_status = arg;
43:             set_leds(vc->led_status);
44:             break;
45:
46:         case KDGBKTYPE:
47:             if((errno = check_user_area(VERIFY_WRITE, (void *)arg, s
sizeof(unsigned char)))) {
48:                 return errno;
49:             }
50:             memset_b((void *)arg, KB_101, sizeof(char));
51:             break;
52:
53:         case KDSETMODE:
54:             if(arg != KD_TEXT && arg != KD_GRAPHICS) {
55:                 return -EINVAL;
56:             }
57:             if(vc->vc_mode != arg) {
58:                 vc->vc_mode = arg;
59:                 if(arg == KD_GRAPHICS) {
60:                     blank_screen(vc);
61:                 } else {
62:                     unblank_screen(vc);
63:                 }
64:             }
65:             break;

```

drivers/char/vt.c

Page 2/4

```

66:
67:         case KDGETMODE:
68:             if((errno = check_user_area(VERIFY_WRITE, (void *)arg, s
sizeof(unsigned char)))) {
69:                 return errno;
70:             }
71:             memset_b((void *)arg, vc->vc_mode, sizeof(char));
72:             break;
73:
74:         case KDSKBENT:
75:         {
76:             struct kbentry *k = (struct kbentry *)arg;
77:             if((errno = check_user_area(VERIFY_WRITE, (void *)k, siz
eof(struct kbentry)))) {
78:                 return errno;
79:             }
80:             if(k->kb_table < NR_MODIFIERS) {
81:                 if(k->kb_index < NR_SCODES) {
82:                     keymap[(k->kb_index * NR_MODIFIERS) + k-
>kb_table] = k->kb_value;
83:                 } else {
84:                     return -EINVAL;
85:                 }
86:             } else {
87:                 printk("%s(): kb_table value '%d' not supported.
\n", __FUNCTION__, k->kb_table);
88:                 return -EINVAL;
89:             }
90:         }
91:         break;
92:
93:         case VT_OPENQRY:
94:         {
95:             int *val = (int *)arg;
96:             if((errno = check_user_area(VERIFY_WRITE, (void *)arg, s
sizeof(unsigned int)))) {
97:                 return errno;
98:             }
99:             for(n = 1; n < NR_VCONSOLES + 1; n++) {
100:                 tty = get_tty(MKDEV(VCONSOLES_MAJOR, n));
101:                 if(!tty->count) {
102:                     break;
103:                 }
104:             }
105:             *val = (n < NR_VCONSOLES + 1 ? n : -1);
106:         }
107:         break;
108:
109:         case VT_GETMODE:
110:         {
111:             struct vt_mode *vt_mode = (struct vt_mode *)arg;
112:             if((errno = check_user_area(VERIFY_WRITE, (void *)vt_mod
e, sizeof(struct vt_mode)))) {
113:                 return errno;
114:             }
115:             memcpy_b(vt_mode, &vc->vt_mode, sizeof(struct vt_mode));
116:         }
117:         break;
118:
119:         case VT_SETMODE:
120:         {
121:             struct vt_mode *vt_mode = (struct vt_mode *)arg;
122:             if((errno = check_user_area(VERIFY_READ, (void *)vt_mode
, sizeof(struct vt_mode)))) {
123:                 return errno;
124:             }
125:             if(vt_mode->mode != VT_AUTO && vt_mode->mode != VT_PROCE

```

drivers/char/vt.c

Page 3/4

```

SS) {
126:         return -EINVAL;
127:     }
128:     memcpy_b(&vc->vt_mode, vt_mode, sizeof(struct vt_mode));
129:     vc->vt_mode.frsig = 0; /* ignored */
130:     tty->pid = current->pid;
131:     vc->switchto_tty = 0;
132: }
133:     break;
134:
135:     case VT_GETSTATE:
136:     {
137:         struct vt_stat *vt_stat = (struct vt_stat *)arg;
138:         if((errno = check_user_area(VERIFY_WRITE, (void *)vt_stat,
t, sizeof(struct vt_stat)))) {
139:             return errno;
140:         }
141:         vt_stat->v_active = current_cons;
142:         vt_stat->v_state = 1; /* /dev/tty0 is always opened */
143:         for(n = 1; n < NR_VCONSOLES + 1; n++) {
144:             tty = get_tty(MKDEV(VCONSOLES_MAJOR, n));
145:             if(tty->count) {
146:                 vt_stat->v_state |= (1 << n);
147:             }
148:         }
149:     }
150:     break;
151:
152:     case VT_RELDISP:
153:         if(vc->vt_mode.mode != VT_PROCESS) {
154:             return -EINVAL;
155:         }
156:         if(vc->switchto_tty < 0) {
157:             if(arg != VT_ACKACQ) {
158:                 return -EINVAL;
159:             }
160:         } else {
161:             if(arg) {
162:                 int switchto_tty;
163:                 switchto_tty = vc->switchto_tty;
164:                 vc->switchto_tty = -1;
165:                 vconsole_select_final(switchto_tty);
166:             } else {
167:                 vc->switchto_tty = -1;
168:             }
169:         }
170:         break;
171:
172:     case VT_ACTIVATE:
173:         if(current_cons == MINOR(tty->dev) || IS_SUPERUSER) {
174:             if(!arg || arg > NR_VCONSOLES) {
175:                 return -ENXIO;
176:             }
177:             vconsole_select(--arg);
178:         } else {
179:             return -EPERM;
180:         }
181:         break;
182:
183:     case VT_WAITACTIVE:
184:         if(current_cons == MINOR(tty->dev)) {
185:             break;
186:         }
187:         if(!arg || arg > NR_VCONSOLES) {
188:             return -ENXIO;
189:         }
190:         printk("ACTIVATING another tty!! (cmd = 0x%x)\n", cmd);

```

drivers/char/vt.c

Page 4/4

```
191:                 break;
192:
193:                 default:
194:                 return -EINVAL;
195:             }
196:             return 0;
197: }
```

fs/buffer.c

Page 1/7

```

1: /*
2:  * fiwix/fs/buffer.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: /*
9:  * buffer.c implements a cache with a free list as a doubly circular linked
10: * list and a chained hash table with doubly linked lists.
11: *
12: * hash table
13: * +-----+ +-----+ +-----+ +-----+
14: * | index | |prev|data|next| |prev|data|next| |prev|data|next|
15: * |  0  --> | / | | | | | | | | | | | | | | | | | | | | | | | | | |
16: * +-----+ +-----+ +-----+ +-----+
17: * +-----+ +-----+ +-----+ +-----+
18: * | index | |prev|data|next| |prev|data|next| |prev|data|next|
19: * |  1  --> | / | | | | | | | | | | | | | | | | | | | | | | | | | |
20: * +-----+ +-----+ +-----+ +-----+
21: *                (buffer)          (buffer)          (buffer)
22: *      ...
23: */
24:
25: #include <fiwix/asm.h>
26: #include <fiwix/kernel.h>
27: #include <fiwix/sleep.h>
28: #include <fiwix/sched.h>
29: #include <fiwix/buffer.h>
30: #include <fiwix/devices.h>
31: #include <fiwix/fs.h>
32: #include <fiwix/mm.h>
33: #include <fiwix/errno.h>
34: #include <fiwix/stdio.h>
35: #include <fiwix/string.h>
36: #include <fiwix/stat.h>
37:
38: #define BUFFER_HASH(dev, block) (((__dev_t)(dev) ^ (__blk_t)(block)) % (NR_BUF_H
ASH))
39: #define NR_BUFFERS          buffer_table_size / sizeof(struct buffer)
40: #define NR_BUF_HASH        buffer_hash_table_size / sizeof(unsigned int)
41:
42: struct buffer *buffer_table;          /* buffer pool */
43: struct buffer *buffer_head;          /* buffer pool head */
44: struct buffer **buffer_hash_table;
45:
46: static struct resource sync_resource = { NULL, NULL };
47:
48: static void insert_to_hash(struct buffer *buf)
49: {
50:     struct buffer **h;
51:     int i;
52:
53:     i = BUFFER_HASH(buf->dev, buf->block);
54:     h = &buffer_hash_table[i];
55:
56:     if(!*h) {
57:         *h = buf;
58:         (*h)->prev_hash = (*h)->next_hash = NULL;
59:     } else {
60:         buf->prev_hash = NULL;
61:         buf->next_hash = *h;
62:         (*h)->prev_hash = buf;
63:         *h = buf;
64:     }
65: }
66:

```

fs/buffer.c

Page 2/7

```

67: static void remove_from_hash(struct buffer *buf)
68: {
69:     struct buffer **h;
70:     int i;
71:
72:     i = BUFFER_HASH(buf->dev, buf->block);
73:     h = &buffer_hash_table[i];
74:
75:     while(*h) {
76:         if(*h == buf) {
77:             if((*h)->next_hash) {
78:                 (*h)->next_hash->prev_hash = (*h)->prev_hash;
79:             }
80:             if((*h)->prev_hash) {
81:                 (*h)->prev_hash->next_hash = (*h)->next_hash;
82:             }
83:             if(h == &buffer_hash_table[i]) {
84:                 *h = (*h)->next_hash;
85:             }
86:             break;
87:         }
88:         h = &(*h)->next_hash;
89:     }
90: }
91:
92: static void remove_from_free_list(struct buffer *buf)
93: {
94:     buf->prev_free->next_free = buf->next_free;
95:     buf->next_free->prev_free = buf->prev_free;
96:     if(buf == buffer_head) {
97:         buffer_head = buf->next_free;
98:     }
99: }
100:
101: static void buffer_wait(struct buffer *buf)
102: {
103:     unsigned long int flags;
104:
105:     for(;;) {
106:         SAVE_FLAGS(flags); CLI();
107:         if(buf->locked) {
108:             RESTORE_FLAGS(flags);
109:             sleep(&buffer_wait, PROC_UNINTERRUPTIBLE);
110:         } else {
111:             break;
112:         }
113:     }
114:     buf->locked = 1;
115:     RESTORE_FLAGS(flags);
116: }
117:
118: static struct buffer * get_free_buffer(void)
119: {
120:     unsigned long int flags;
121:     struct buffer *buf;
122:
123:     /* no more buffers on free list */
124:     if(buffer_head == buffer_head->next_free) {
125:         return NULL;
126:     }
127:
128:     for(;;) {
129:         SAVE_FLAGS(flags); CLI();
130:         buf = buffer_head;
131:         if(buf->locked) {
132:             RESTORE_FLAGS(flags);
133:             sleep(&buffer_wait, PROC_UNINTERRUPTIBLE);

```

fs/buffer.c

Page 3/7

```

134:             } else {
135:                 break;
136:             }
137:         }
138:
139:         buf = buffer_head;
140:         remove_from_free_list(buf);
141:         buf->locked = 1;
142:
143:         RESTORE_FLAGS(flags);
144:         return buf;
145:     }
146:
147: static void sync_one_buffer(struct buffer *buf)
148: {
149:     struct device *d;
150:     int errno;
151:
152:     if(!(d = get_device(BLK_DEV, MAJOR(buf->dev)))) {
153:         printk("WARNING: %s(): block device %d,%d not registered!\n", __
FUNCTION__, MAJOR(buf->dev), MINOR(buf->dev));
154:         return;
155:     }
156:
157:     if(d->fsop && d->fsop->write_block) {
158:         errno = d->fsop->write_block(buf->dev, buf->block, buf->data, bu
f->size);
159:         if(errno < 0) {
160:             if(errno == -EROFS) {
161:                 printk("WARNING: %s(): write protection on devic
e %d,%d.\n", __FUNCTION__, MAJOR(buf->dev), MINOR(buf->dev), buf->block);
162:             } else {
163:                 printk("WARNING: %s(): I/O error on device %d,%d
.\n", __FUNCTION__, MAJOR(buf->dev), MINOR(buf->dev), buf->block);
164:             }
165:             return;
166:         }
167:         buf->dirty = 0;
168:     } else {
169:         printk("WARNING: %s(): device %d,%d does not have the write_bloc
k() method!\n", __FUNCTION__, MAJOR(buf->dev), MINOR(buf->dev));
170:     }
171: }
172:
173: static struct buffer * search_buffer_hash(__dev_t dev, __blk_t block, int size)
174: {
175:     struct buffer *buf;
176:     int i;
177:
178:     i = BUFFER_HASH(dev, block);
179:     buf = buffer_hash_table[i];
180:
181:     while(buf) {
182:         if(buf->dev == dev && buf->block == block && buf->size == size)
{
183:             return buf;
184:         }
185:         buf = buf->next_hash;
186:     }
187:
188:     return NULL;
189: }
190:
191: static struct buffer * getblk(__dev_t dev, __blk_t block, int size)
192: {
193:     unsigned long int flags;
194:     struct buffer *buf;

```


fs/buffer.c

Page 4/7

```

195:
196:     for(;;) {
197:         if((buf = search_buffer_hash(dev, block, size)) {
198:             SAVE_FLAGS(flags); CLI();
199:             if(buf->locked) {
200:                 RESTORE_FLAGS(flags);
201:                 sleep(&buffer_wait, PROC_UNINTERRUPTIBLE);
202:                 continue;
203:             }
204:             buf->locked = 1;
205:             remove_from_free_list(buf);
206:             RESTORE_FLAGS(flags);
207:             return buf;
208:         }
209:
210:         if(!(buf = get_free_buffer())) {
211:             printk("WARNING: %s(): no more buffers on free list!\n",
__FUNCTION__);
212:             sleep(&get_free_buffer, PROC_UNINTERRUPTIBLE);
213:             continue;
214:         }
215:
216:         if(buf->dirty) {
217:             sync_one_buffer(buf);
218:         } else {
219:             if(!buf->data) {
220:                 if(!(buf->data = (char *)kmalloc())) {
221:                     brelse(buf);
222:                     printk("%s(): returning NULL\n", __FUNCT
ION__);
223:                     return NULL;
224:                 }
225:                 kstat.buffers += (PAGE_SIZE / 1024);
226:             }
227:         }
228:
229:         SAVE_FLAGS(flags); CLI();
230:         remove_from_hash(buf); /* remove it from old hash */
231:         buf->dev = dev;
232:         buf->block = block;
233:         buf->size = size;
234:         insert_to_hash(buf);
235:         buf->valid = 0;
236:         RESTORE_FLAGS(flags);
237:         return buf;
238:     }
239: }
240:
241: struct buffer * get_dirty_buffer(__dev_t dev, __blk_t block, int size)
242: {
243:     unsigned long int flags;
244:     struct buffer *buf;
245:
246:     for(;;) {
247:         if((buf = search_buffer_hash(dev, block, size)) {
248:             if(buf->dirty) {
249:                 SAVE_FLAGS(flags); CLI();
250:                 if(buf->locked) {
251:                     RESTORE_FLAGS(flags);
252:                     sleep(&buffer_wait, PROC_UNINTERRUPTIBLE
);
253:                     continue;
254:                 }
255:                 buf->locked = 1;
256:                 remove_from_free_list(buf);
257:                 RESTORE_FLAGS(flags);
258:                 break;

```

fs/buffer.c

Page 5/7

```

259:         }
260:     }
261:     buf = NULL;
262:     break;
263: }
264:
265:     return buf;
266: }
267:
268: struct buffer * bread(__dev_t dev, __blk_t block, int size)
269: {
270:     struct buffer *buf;
271:     struct device *d;
272:
273:     if(!(d = get_device(BLK_DEV, MAJOR(dev)))) {
274:         printk("WARNING: %s(): device major %d not found!\n", __FUNCTION
__, MAJOR(dev));
275:         return NULL;
276:     }
277:
278:     if((buf = getblk(dev, block, size)) {
279:         if(!buf->valid) {
280:             if(d->fsop && d->fsop->read_block) {
281:                 if(d->fsop->read_block(dev, block, buf->data, si
ze) >= 0) {
282:                     buf->valid = 1;
283:                 }
284:             }
285:         }
286:         if(buf->valid) {
287:             return buf;
288:         }
289:         brelse(buf);
290:     }
291:
292:     printk("WARNING: %s(): returning NULL!\n", __FUNCTION__);
293:     return NULL;
294: }
295:
296: void bwrite(struct buffer *buf)
297: {
298:     buf->dirty = 1;
299:     buf->valid = 1;
300:     brelse(buf);
301: }
302:
303: void brelse(struct buffer *buf)
304: {
305:     unsigned long int flags;
306:
307:     SAVE_FLAGS(flags); CLI();
308:
309:     if(!buffer_head) {
310:         buf->prev_free = buf->next_free = buf;
311:         buffer_head = buf;
312:     } else {
313:         buf->next_free = buffer_head;
314:         buf->prev_free = buffer_head->prev_free;
315:         buffer_head->prev_free->next_free = buf;
316:         buffer_head->prev_free = buf;
317:
318:         /* if not valid place the buffer at the head of the free list */
319:         if(!buf->valid) {
320:             buffer_head = buf;
321:         }
322:     }
323:     buf->locked = 0;

```

fs/buffer.c

Page 6/7

```

324:
325:     RESTORE_FLAGS(flags);
326:
327:     wakeup(&get_free_buffer);
328:     wakeup(&buffer_wait);
329: }
330:
331: void sync_buffers(__dev_t dev)
332: {
333:     struct buffer *buf;
334:     int n;
335:
336:     buf = &buffer_table[0];
337:
338:     lock_resource(&sync_resource);
339:     for(n = 0; n < NR_BUFFERS; n++) {
340:         if(buf->dirty) {
341:             if(!dev || buf->dev == dev) {
342:                 buffer_wait(buf);
343:                 sync_one_buffer(buf);
344:                 buf->locked = 0;
345:                 wakeup(&buffer_wait);
346:             }
347:         }
348:         buf++;
349:     }
350:     unlock_resource(&sync_resource);
351:     return;
352: }
353:
354: void invalidate_buffers(__dev_t dev)
355: {
356:     unsigned long int flags;
357:     unsigned int n;
358:     struct buffer *buf;
359:
360:     buf = &buffer_table[0];
361:     SAVE_FLAGS(flags); CLI();
362:
363:     for(n = 0; n < NR_BUFFERS; n++) {
364:         if(!buf->locked && buf->dev == dev) {
365:             buffer_wait(buf);
366:             remove_from_hash(buf);
367:             buf->valid = 0;
368:             buf->locked = 0;
369:             wakeup(&buffer_wait);
370:         }
371:         buf++;
372:     }
373:
374:     RESTORE_FLAGS(flags);
375:     /* FIXME: invalidate_pages(dev); */
376: }
377:
378: /*
379:  * When kernel runs out of pages, kswapd is awoken and it calls this function
380:  * which goes through the buffer free list, freeing up to NR_BUF_RECLAIM
381:  * buffers.
382:  */
383: int reclaim_buffers(void)
384: {
385:     struct buffer *buf, *first;
386:     int reclaimed;
387:
388:     reclaimed = 0;
389:     first = NULL;
390:

```

fs/buffer.c

Page 7/7

```

391:         for(;;) {
392:             if(!(buf = get_free_buffer())) {
393:                 printk("WARNING: %s(): no more buffers on free list!\n",
__FUNCTION__);
394:                 sleep(&get_free_buffer, PROC_UNINTERRUPTIBLE);
395:                 continue;
396:             }
397:
398:             remove_from_hash(buf);
399:             if(buf->dirty) {
400:                 sync_one_buffer(buf);
401:             }
402:
403:             /* this ensures the buffer will go to the tail */
404:             buf->valid = 1;
405:
406:             if(first) {
407:                 if(first == buf) {
408:                     brelse(buf);
409:                     break;
410:                 }
411:             } else {
412:                 first = buf;
413:             }
414:             if(buf->data) {
415:                 kfree((unsigned int)buf->data);
416:                 buf->data = NULL;
417:                 kstat.buffers -= (PAGE_SIZE / 1024);
418:                 reclaimed++;
419:                 if(reclaimed == NR_BUF_RECLAIM) {
420:                     brelse(buf);
421:                     break;
422:                 }
423:             }
424:             brelse(buf);
425:             do_sched();
426:         }
427:
428:         wakeup(&buffer_wait);
429:         return reclaimed;
430:     }
431:
432: void buffer_init(void)
433: {
434:     struct buffer *buf;
435:     unsigned int n;
436:
437:     memset_b(buffer_table, NULL, buffer_table_size);
438:     memset_b(buffer_hash_table, NULL, buffer_hash_table_size);
439:     for(n = 0; n < NR_BUFFERS; n++) {
440:         buf = &buffer_table[n];
441:         brelse(buf);
442:     }
443: }

```

fs/devices.c

Page 1/6

```

1: /*
2:  * fiwix/fs/devices.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/errno.h>
10: #include <fiwix/buffer.h>
11: #include <fiwix/devices.h>
12: #include <fiwix/fs.h>
13: #include <fiwix/mm.h>
14: #include <fiwix/process.h>
15: #include <fiwix/stdio.h>
16: #include <fiwix/string.h>
17:
18: struct device chr_device_table[NR_CHRDEV];
19: struct device blk_device_table[NR_BLKDEV];
20:
21: struct fs_operations def_chr_fsop = {
22:     0,
23:     0,
24:
25:     chr_dev_open,
26:     NULL,                /* close */
27:     NULL,                /* read */
28:     NULL,                /* write */
29:     NULL,                /* ioctl */
30:     NULL,                /* lseek */
31:     NULL,                /* readdir */
32:     NULL,                /* mmap */
33:     NULL,                /* select */
34:
35:     NULL,                /* readlink */
36:     NULL,                /* followlink */
37:     NULL,                /* bmap */
38:     NULL,                /* lockup */
39:     NULL,                /* rmdir */
40:     NULL,                /* link */
41:     NULL,                /* unlink */
42:     NULL,                /* symlink */
43:     NULL,                /* mkdir */
44:     NULL,                /* mknod */
45:     NULL,                /* truncate */
46:     NULL,                /* create */
47:     NULL,                /* rename */
48:
49:     NULL,                /* read_block */
50:     NULL,                /* write_block */
51:
52:     NULL,                /* read_inode */
53:     NULL,                /* write_inode */
54:     NULL,                /* ialloc */
55:     NULL,                /* ifree */
56:     NULL,                /* stats */
57:     NULL,                /* read_superblock */
58:     NULL,                /* remount_fs */
59:     NULL,                /* write_superblock */
60:     NULL,                /* release_superblock */
61: };
62:
63: struct fs_operations def_blk_fsop = {
64:     0,
65:     0,
66:
67:     blk_dev_open,

```

fs/devices.c

Page 2/6

```

68:         blk_dev_close,
69:         blk_dev_read,
70:         blk_dev_write,
71:         blk_dev_ioctl,
72:         blk_dev_lseek,
73:         NULL,                /* readdir */
74:         NULL,                /* mmap */
75:         NULL,                /* select */
76:
77:         NULL,                /* readlink */
78:         NULL,                /* followlink */
79:         NULL,                /* bmap */
80:         NULL,                /* lockup */
81:         NULL,                /* rmdir */
82:         NULL,                /* link */
83:         NULL,                /* unlink */
84:         NULL,                /* symlink */
85:         NULL,                /* mkdir */
86:         NULL,                /* mknod */
87:         NULL,                /* truncate */
88:         NULL,                /* create */
89:         NULL,                /* rename */
90:
91:         NULL,                /* read_block */
92:         NULL,                /* write_block */
93:
94:         NULL,                /* read_inode */
95:         NULL,                /* write_inode */
96:         NULL,                /* ialloc */
97:         NULL,                /* ifree */
98:         NULL,                /* stats */
99:         NULL,                /* read_superblock */
100:        NULL,                /* remount_fs */
101:        NULL,                /* write_superblock */
102:        NULL,                /* release_superblock */
103: };
104:
105: int register_device(int type, struct device *new_d)
106: {
107:     struct device *d;
108:
109:     switch(type) {
110:         case CHR_DEV:
111:             if(new_d->major >= NR_CHRDEV) {
112:                 printk("%s(): character device major %d is greater than NR_CHRDEV (%d).\n", __FUNCTION__, new_d->major, NR_CHRDEV);
113:                 return 1;
114:             }
115:             d = chr_device_table;
116:             break;
117:         case BLK_DEV:
118:             if(new_d->major >= NR_BLKDEV) {
119:                 printk("%s(): block device major %d is greater than NR_BLKDEV (%d).\n", __FUNCTION__, new_d->major, NR_BLKDEV);
120:                 return 1;
121:             }
122:             d = blk_device_table;
123:             break;
124:         default:
125:             printk("WARNING: %s(): invalid device type %d.\n", __FUNCTION__, type);
126:             return 1;
127:             break;
128:     }
129:
130:     if(d[new_d->major].major) {
131:         printk("%s(): device '%s' with major %d is already registered.\n

```

fs/devices.c

Page 3/6

```

", __FUNCTION__, new_d->name, new_d->major);
132:         return 1;
133:     }
134:     memcpy_b(d + new_d->major, new_d, sizeof(struct device));
135:     return 0;
136: }
137:
138: struct device * get_device(int type, unsigned char major)
139: {
140:     char *name;
141:     struct device *d;
142:
143:     switch(type) {
144:         case CHR_DEV:
145:             if(major >= NR_CHRDEV) {
146:                 printk("%s(): character device major %d is great
er than NR_CHRDEV (%d).\n", __FUNCTION__, major, NR_CHRDEV);
147:                 return NULL;
148:             }
149:             d = chr_device_table;
150:             name = "character";
151:             break;
152:         case BLK_DEV:
153:             if(major >= NR_BLKDEV) {
154:                 printk("%s(): block device major %d is greater t
han NR_BLKDEV (%d).\n", __FUNCTION__, major, NR_BLKDEV);
155:                 return NULL;
156:             }
157:             d = blk_device_table;
158:             name = "block";
159:             break;
160:         default:
161:             printk("WARNING: %s(): invalid device type %d.\n", __FUN
CTION__, type);
162:             return NULL;
163:     }
164:
165:     if(d[major].major) {
166:         return &d[major];
167:     }
168:
169:     printk("WARNING: %s(): no %s device found with major %d.\n", __FUNCTION_
_, name, major);
170:     return NULL;
171: }
172:
173: int chr_dev_open(struct inode *i, struct fd *fd_table)
174: {
175:     struct device *d;
176:
177:     if((d = get_device(CHR_DEV, MAJOR(i->rdev)))) {
178:         i->fsop = d->fsop;
179:         if(i->fsop && i->fsop->open) {
180:             return i->fsop->open(i, fd_table);
181:         }
182:     }
183:
184:     return -EINVAL;
185: }
186:
187: int blk_dev_open(struct inode *i, struct fd *fd_table)
188: {
189:     struct device *d;
190:
191:     if((d = get_device(BLK_DEV, MAJOR(i->rdev)))) {
192:         if(d->fsop && d->fsop->open) {
193:             return d->fsop->open(i, fd_table);

```

fs/devices.c

Page 4/6

```

194:         }
195:     }
196:
197:     return -EINVAL;
198: }
199:
200: int blk_dev_close(struct inode *i, struct fd *fd_table)
201: {
202:     struct device *d;
203:
204:     if((d = get_device(BLK_DEV, MAJOR(i->rdev)))) {
205:         if(d->fsop && d->fsop->close) {
206:             return d->fsop->close(i, fd_table);
207:         }
208:     }
209:
210:     printk("WARNING: %s(): block device %d,%d does not have the close() meth
od.\n", __FUNCTION__, MAJOR(i->rdev), MINOR(i->rdev));
211:     return -EINVAL;
212: }
213:
214: int blk_dev_read(struct inode *i, struct fd *fd_table, char *buffer, __size_t co
unt)
215: {
216:     __blk_t block;
217:     __off_t total_read, device_size;
218:     int blksize;
219:     unsigned int boffset, bytes;
220:     struct buffer *buf;
221:     struct device *d;
222:
223:     if(!(d = get_device(BLK_DEV, MAJOR(i->rdev)))) {
224:         return -EINVAL;
225:     }
226:
227:     blksize = d->blksize ? d->blksize : BLKSIZE_1K;
228:     total_read = 0;
229:     if(!d->device_data) {
230:         printk("%s(): don't know the size of the block device %d,%d.\n",
__FUNCTION__, MAJOR(i->rdev), MINOR(i->rdev));
231:         return -EIO;
232:     }
233:
234:     /* check if device size is greater than 4GB (in 32bit would overflow) */
235:     if(((__off_t *)d->device_data)[MINOR(i->rdev)] >= (4096 * 1024)) {
236:         printk("WARNING: %s(): device size > 4GB (would overflow). Defau
lting to 4GB.\n", __FUNCTION__);
237:         device_size = (unsigned int)4096 * 1024 * 1023;
238:     } else {
239:         device_size = ((__off_t *)d->device_data)[MINOR(i->rdev)] * 1024
;
240:     }
241:
242:     count = (fd_table->offset + count > device_size) ? device_size - fd_tabl
e->offset : count;
243:     if(!count || fd_table->offset > device_size) {
244:         return 0;
245:     }
246:     while(count) {
247:         boffset = fd_table->offset % blksize;
248:         block = (fd_table->offset / blksize);
249:         if(!(buf = bread(i->rdev, block, blksize))) {
250:             return -EIO;
251:         }
252:         bytes = blksize - boffset;
253:         bytes = MIN(bytes, count);
254:         memcpy_b(buffer + total_read, buf->data + boffset, bytes);

```


fs/devices.c

Page 5/6

```

255:         total_read += bytes;
256:         count -= bytes;
257:         boffset += bytes;
258:         boffset %= blksize;
259:         fd_table->offset += bytes;
260:         brelse(buf);
261:     }
262:     return total_read;
263: }
264:
265: int blk_dev_write(struct inode *i, struct fd *fd_table, const char *buffer, __si
ze_t count)
266: {
267:     __blk_t block;
268:     __off_t total_written, device_size;
269:     int blksize;
270:     unsigned int boffset, bytes;
271:     struct buffer *buf;
272:     struct device *d;
273:
274:     if(!(d = get_device(BLK_DEV, MAJOR(i->rdev)))) {
275:         return -EINVAL;
276:     }
277:
278:     blksize = d->blksize ? d->blksize : BLKSIZE_1K;
279:     total_written = 0;
280:     if(!d->device_data) {
281:         printk("%s(): don't know the size of the block device %d,%d.\n",
__FUNCTION__, MAJOR(i->rdev), MINOR(i->rdev));
282:         return -EIO;
283:     }
284:
285:     /* check if device size is greater than 4GB (in 32bit would overflow) */
286:     if(((__off_t *)d->device_data)[MINOR(i->rdev)] >= (4096 * 1024)) {
287:         printk("WARNING: %s(): device size > 4GB (would overflow). Defau
lting to 4GB.\n", __FUNCTION__);
288:         device_size = (unsigned int)4096 * 1024 * 1023;
289:     } else {
290:         device_size = ((__off_t *)d->device_data)[MINOR(i->rdev)] * 1024
;
291:     }
292:
293:     count = (fd_table->offset + count > device_size) ? device_size - fd_tabl
e->offset : count;
294:     if(!count || fd_table->offset > device_size) {
295:         printk("%s(): I/O error on device %d,%d, offset %u.\n", __FUNCTI
ON, MAJOR(i->rdev), MINOR(i->rdev), fd_table->offset);
296:         return -EIO;
297:     }
298:     while(count) {
299:         boffset = fd_table->offset % blksize;
300:         block = (fd_table->offset / blksize);
301:         if(!(buf = bread(i->rdev, block, blksize))) {
302:             return -EIO;
303:         }
304:         bytes = blksize - boffset;
305:         bytes = MIN(bytes, count);
306:         memcpy_b(buf->data + boffset, buffer + total_written, bytes);
307:         total_written += bytes;
308:         count -= bytes;
309:         boffset += bytes;
310:         boffset %= blksize;
311:         fd_table->offset += bytes;
312:         bwrite(buf);
313:     }
314:     return total_written;
315: }

```

fs/devices.c

Page 6/6

```
316:
317: int blk_dev_ioctl(struct inode *i, int cmd, unsigned long int arg)
318: {
319:     struct device *d;
320:
321:     if((d = get_device(BLK_DEV, MAJOR(i->rdev)))) {
322:         if(d->fsop && d->fsop->ioctl) {
323:             return d->fsop->ioctl(i, cmd, arg);
324:         }
325:     }
326:
327:     printk("WARNING: %s(): block device %d,%d does not have the ioctl() meth
od.\n", __FUNCTION__, MAJOR(i->rdev), MINOR(i->rdev));
328:     return -EINVAL;
329: }
330:
331: int blk_dev_lseek(struct inode *i, __off_t offset)
332: {
333:     struct device *d;
334:
335:     if((d = get_device(BLK_DEV, MAJOR(i->rdev)))) {
336:         if(d->fsop && d->fsop->lseek) {
337:             return d->fsop->lseek(i, offset);
338:         }
339:     }
340:
341:     return offset;
342: }
343:
344: void dev_init(void)
345: {
346:     memset_b(chr_device_table, NULL, sizeof(chr_device_table));
347:     memset_b(blk_device_table, NULL, sizeof(blk_device_table));
348: }
```

fs/elf.c

Page 1/12

```

1: /*
2:  * fiwix/fs/elf.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/asm.h>
10: #include <fiwix/types.h>
11: #include <fiwix/buffer.h>
12: #include <fiwix/fs.h>
13: #include <fiwix/i386elf.h>
14: #include <fiwix/mm.h>
15: #include <fiwix/mman.h>
16: #include <fiwix/fs.h>
17: #include <fiwix/fcntl.h>
18: #include <fiwix/process.h>
19: #include <fiwix/errno.h>
20: #include <fiwix/stdio.h>
21: #include <fiwix/string.h>
22:
23: #define AT_ITEMS          12          /* ELF Auxiliary Vectors */
24:
25: static int check_elf(struct elf32_hdr *elf32_h)
26: {
27:     if(elf32_h->e_ident[EI_MAG0] != ELFMAG0 ||
28:        elf32_h->e_ident[EI_MAG1] != ELFMAG1 ||
29:        elf32_h->e_ident[EI_MAG2] != ELFMAG2 ||
30:        elf32_h->e_ident[EI_MAG3] != ELFMAG3 ||
31:        (elf32_h->e_type != ET_EXEC && elf32_h->e_type != ET_DYN) ||
32:        elf32_h->e_machine != EM_386) {
33:         return -EINVAL;
34:     }
35:     return 0;
36: }
37:
38: static void free_barg_pages(struct binargs *barg)
39: {
40:     int n;
41:
42:     for(n = 0; n < ARG_MAX; n++) {
43:         if(barg->page[n]) {
44:             kfree(barg->page[n]);
45:         }
46:     }
47: }
48:
49: static int copy_strings(struct binargs *barg, char *argv[], char *envp[])
50: {
51:     int n, p, offset;
52:     unsigned int ae_str_len;
53:     char *page, *str;
54:
55:     p = ARG_MAX - 1;
56:     ae_str_len = barg->argv_len + barg->envp_len + 4;
57:     p -= ae_str_len / PAGE_SIZE;
58:     offset = PAGE_SIZE - (ae_str_len % PAGE_SIZE);
59:     if(offset == PAGE_SIZE) {
60:         offset = 0;
61:         p++;
62:     }
63:     barg->offset = offset;
64:     for(n = p; n < ARG_MAX; n++) {
65:         if(!(barg->page[n] = kmalloc())) {
66:             free_barg_pages(barg);
67:             return -ENOMEM;

```

```

68:         }
69:     }
70:     for(n = 0; n < barg->argc; n++) {
71:         str = argv[n];
72:         page = (char *)barg->page[p];
73:         while(*str) {
74:             *(page + offset) = *str;
75:             offset++;
76:             str++;
77:             if(offset == PAGE_SIZE) {
78:                 p++;
79:                 offset = 0;
80:                 page = (char *)barg->page[p];
81:             }
82:         }
83:         *(page + offset++) = NULL;
84:         if(offset == PAGE_SIZE) {
85:             p++;
86:             offset = 0;
87:         }
88:     }
89:     for(n = 0; n < barg->envc; n++) {
90:         str = envp[n];
91:         page = (char *)barg->page[p];
92:         while(*str) {
93:             *(page + offset) = *str;
94:             offset++;
95:             str++;
96:             if(offset == PAGE_SIZE) {
97:                 p++;
98:                 offset = 0;
99:                 page = (char *)barg->page[p];
100:            }
101:        }
102:        *(page + offset++) = NULL;
103:        if(offset == PAGE_SIZE) {
104:            p++;
105:            offset = 0;
106:        }
107:    }
108:
109:    return 0;
110: }
111:
112: /*
113:  * Setup the initial process stack (System V ABI for i386)
114:  * -----
115:  * 0xBFFFFFFF
116:  * +-----+ \
117:  * | envp[] str | \
118:  * +-----+ /
119:  * | argv[] str | /
120:  * +-----+ /
121:  * | NULL | /
122:  * +-----+ /
123:  * | ELF Aux.Vect. | /
124:  * +-----+ /
125:  * | NULL | / elf_create_stack() setups this section
126:  * +-----+ /
127:  * | envp[] ptr | /
128:  * +-----+ /
129:  * | NULL | /
130:  * +-----+ /
131:  * | argv[] ptr | /
132:  * +-----+ /
133:  * | argc | /
134:  * +-----+ /

```

fs/elf.c

Page 3/12

```

135: *      | stack pointer | grows toward lower addresses
136: *      +-----+ ||
137: *      |.....| \\  

138: *      |.....| \  

139: *      |.....| \  

140: *      |.....| /\
141: *      +-----+ ||
142: *      | brk (heap) | grows toward higher addresses
143: *      +-----+
144: *      | .bss section |
145: *      +-----+
146: *      | .data section |
147: *      +-----+
148: *      | .text section |
149: *      +-----+
150: * 0x08048000
151: */
152: static void elf_create_stack(struct binargs *barg, unsigned int *sp, unsigned in
t str_ptr, int at_base, struct elf32_hdr *elf32_h, unsigned int phdr_addr)
153: {
154:     unsigned int n, addr;
155:     char *str;
156:
157:     /* copy strings */
158:     for(n = 0; n < ARG_MAX; n++) {
159:         if(barg->page[n]) {
160:             addr = KERNEL_BASE_ADDR - ((ARG_MAX - n) * PAGE_SIZE);
161:             memcpy_b((void *)addr, (void *)barg->page[n], PAGE_SIZE)
;
162:         }
163:     }
164:
165: #ifdef __DEBUG__
166:     printk("sp = 0x%08x\n", sp);
167: #endif /*__DEBUG__ */
168:
169:     /* copy the value of 'argc' into the stack */
170:     memcpy_l((void *)sp, &barg->argc, 1);
171: #ifdef __DEBUG__
172:     printk("at 0x%08x -> argc\n", sp);
173: #endif /*__DEBUG__ */
174:     sp++;
175:
176:     /* copy as many pointers to strings as 'argc' */
177:     current->argv = (char **)sp;
178:     for(n = 0; n < barg->argc; n++) {
179:         memcpy_l((void *)sp, &str_ptr, 1);
180:         str = (char *)str_ptr;
181: #ifdef __DEBUG__
182:         printk("at 0x%08x -> str_ptr(%d) = 0x%08x (+ %d)\n", sp, n, str_
ptr, strlen(str) + 1);
183: #endif /*__DEBUG__ */
184:         sp++;
185:         str_ptr += strlen(str) + 1;
186:     }
187:
188:     /* the last element of 'argv[]' must be a NULL-pointer */
189:     memset_l((void *)sp, NULL, 1);
190: #ifdef __DEBUG__
191:     printk("at 0x%08x -> ----- = 0x%08x\n", sp, 0);
192: #endif /*__DEBUG__ */
193:     sp++;
194:
195:     /* copy as many pointers to strings as 'envc' */
196:     current->envp = (char **)sp;
197:     for(n = 0; n < barg->envc; n++) {
198:         memcpy_l((void *)sp, &str_ptr, 1);

```

fs/elf.c

Page 4/12

```

199:         str = (char *)str_ptr;
200: #ifdef __DEBUG__
201:     printk("at 0x%08x -> str_ptr(%d) = 0x%08x (+ %d)\n", sp, n, str_
ptr, strlen(str) + 1);
202: #endif /*__DEBUG__ */
203:     sp++;
204:     str_ptr += strlen(str) + 1;
205: }
206:
207:     /* the last element of 'envp[]' must be a NULL-pointer */
208:     memset_l((void *)sp, NULL, 1);
209: #ifdef __DEBUG__
210:     printk("at 0x%08x -> ----- = 0x%08x\n", sp, 0);
211: #endif /*__DEBUG__ */
212:     sp++;
213:
214:
215:     /* copy the Auxiliar Table Items (dlinfo_items) */
216:     if(at_base) {
217:         memset_l((void *)sp, AT_PHDR, 1);
218: #ifdef __DEBUG__
219:         printk("at 0x%08x -> AT_PHDR = %d", sp, *sp);
220: #endif /*__DEBUG__ */
221:         sp++;
222:
223:         memcpy_l((void *)sp, &phdr_addr, 1);
224: #ifdef __DEBUG__
225:         printk("\t\tAT_PHDR = 0x%08x\n", *sp);
226: #endif /*__DEBUG__ */
227:         sp++;
228:
229:         memset_l((void *)sp, AT_PHEMT, 1);
230: #ifdef __DEBUG__
231:         printk("at 0x%08x -> AT_PHEMT = %d", sp, *sp);
232: #endif /*__DEBUG__ */
233:         sp++;
234:
235:         memset_l((void *)sp, sizeof(struct elf32_phdr), 1);
236: #ifdef __DEBUG__
237:         printk("\t\tAT_PHEMT = %d\n", *sp);
238: #endif /*__DEBUG__ */
239:         sp++;
240:
241:         memset_l((void *)sp, AT_PHNUM, 1);
242: #ifdef __DEBUG__
243:         printk("at 0x%08x -> AT_PHNUM = %d", sp, *sp);
244: #endif /*__DEBUG__ */
245:         sp++;
246:
247:         memset_l((void *)sp, 0, 1);
248:         memcpy_w((void *)sp, &elf32_h->e_phnum, 1);
249: #ifdef __DEBUG__
250:         printk("\t\tAT_PHNUM = %d\n", *sp);
251: #endif /*__DEBUG__ */
252:         sp++;
253:
254:         memset_l((void *)sp, AT_PAGESZ, 1);
255: #ifdef __DEBUG__
256:         printk("at 0x%08x -> AT_PGSIZE = %d", sp, *sp);
257: #endif /*__DEBUG__ */
258:         sp++;
259:
260:         memset_l((void *)sp, PAGE_SIZE, 1);
261: #ifdef __DEBUG__
262:         printk("\t\tAT_PGSIZE = %d\n", *sp);
263: #endif /*__DEBUG__ */
264:         sp++;

```

```

265:
266:             memset_l((void *)sp, AT_BASE, 1);
267: #ifdef  __DEBUG__
268:             printk("at 0x%08x -> AT_BASE = %d", sp, *sp);
269: #endif /* __DEBUG__ */
270:             sp++;
271:
272:             memset_l((void *)sp, at_base, 1);
273: #ifdef  __DEBUG__
274:             printk("\t\tAT_BASE = 0x%08x\n", sp);
275: #endif /* __DEBUG__ */
276:             sp++;
277:
278:             memset_l((void *)sp, AT_FLAGS, 1);
279: #ifdef  __DEBUG__
280:             printk("at 0x%08x -> AT_FLAGS = %d", sp, *sp);
281: #endif /* __DEBUG__ */
282:             sp++;
283:
284:             memset_l((void *)sp, NULL, 1);
285: #ifdef  __DEBUG__
286:             printk("\t\tAT_FLAGS = %d\n", *sp);
287: #endif /* __DEBUG__ */
288:             sp++;
289:
290:             memset_l((void *)sp, AT_ENTRY, 1);
291: #ifdef  __DEBUG__
292:             printk("at 0x%08x -> AT_ENTRY = %d ", sp, *sp);
293: #endif /* __DEBUG__ */
294:             sp++;
295:
296:             memcpy_l((void *)sp, &elf32_h->e_entry, 1);
297: #ifdef  __DEBUG__
298:             printk("\t\tAT_ENTRY = 0x%08x\n", *sp);
299: #endif /* __DEBUG__ */
300:             sp++;
301:
302:             memset_l((void *)sp, AT_UID, 1);
303: #ifdef  __DEBUG__
304:             printk("at 0x%08x -> AT_UID = %d", sp, *sp);
305: #endif /* __DEBUG__ */
306:             sp++;
307:
308:             memcpy_l((void *)sp, &current->uid, 1);
309: #ifdef  __DEBUG__
310:             printk("\t\tAT_UID = %d\n", *sp);
311: #endif /* __DEBUG__ */
312:             sp++;
313:
314:             memset_l((void *)sp, AT_EUID, 1);
315: #ifdef  __DEBUG__
316:             printk("at 0x%08x -> AT_EUID = %d", sp, *sp);
317: #endif /* __DEBUG__ */
318:             sp++;
319:
320:             memcpy_l((void *)sp, &current->euid, 1);
321: #ifdef  __DEBUG__
322:             printk("\t\tAT_EUID = %d\n", *sp);
323: #endif /* __DEBUG__ */
324:             sp++;
325:
326:             memset_l((void *)sp, AT_GID, 1);
327: #ifdef  __DEBUG__
328:             printk("at 0x%08x -> AT_GID = %d", sp, *sp);
329: #endif /* __DEBUG__ */
330:             sp++;
331:

```

fs/elf.c

Page 6/12

```

332:             memcpy_l((void *)sp, &current->gid, 1);
333: #ifdef __DEBUG__
334:             printk("\t\tAT_GID = %d\n", *sp);
335: #endif /*__DEBUG__ */
336:             sp++;
337:
338:             memset_l((void *)sp, AT_EGID, 1);
339: #ifdef __DEBUG__
340:             printk("at 0x%08x -> AT_EGID = %d", sp, *sp);
341: #endif /*__DEBUG__ */
342:             sp++;
343:
344:             memcpy_l((void *)sp, &current->egid, 1);
345: #ifdef __DEBUG__
346:             printk("\t\tAT_EGID = %d\n", *sp);
347: #endif /*__DEBUG__ */
348:             sp++;
349:     }
350:
351:     memset_l((void *)sp, AT_NULL, 1);
352: #ifdef __DEBUG__
353:     printk("at 0x%08x -> AT_NULL = %d", sp, *sp);
354: #endif /*__DEBUG__ */
355:     sp++;
356:
357:     memset_l((void *)sp, NULL, 1);
358: #ifdef __DEBUG__
359:     printk("\t\tAT_NULL = %d\n", *sp);
360: #endif /*__DEBUG__ */
361:     sp++;
362:
363: #ifdef __DEBUG__
364:     for(n = 0; n < barg->argc; n++) {
365:         printk("at 0x%08x -> argv[%d] = '%s'\n", current->argv[n], n, cu
rrent->argv[n]);
366:     }
367:     for(n = 0; n < barg->envc; n++) {
368:         printk("at 0x%08x -> envp[%d] = '%s'\n", current->envp[n], n, cu
rrent->envp[n]);
369:     }
370: #endif /*__DEBUG__ */
371: }
372:
373: static int elf_load_interpreter(struct inode *ii)
374: {
375:     int n, errno;
376:     struct buffer *buf;
377:     struct elf32_hdr *elf32_h;
378:     struct elf32_phdr *elf32_ph, *last_ptload;
379:     __blk_t block;
380:     unsigned int start, end, length;
381:     unsigned int prot;
382:     char *data;
383:     char type;
384:
385:     if((block = bmap(ii, 0, FOR_READING)) < 0) {
386:         return block;
387:     }
388:     if(!(buf = bread(ii->dev, block, ii->sb->s_blocksize))) {
389:         return -EIO;
390:     }
391:
392:     /*
393:      * The contents of the buffer is copied and then freed immediately to
394:      * make sure that it won't conflict while zeroing the BSS fractional
395:      * page, in case that the same block is requested during the page fault.
396:      */

```


fs/elf.c

Page 7/12

```

397:         if(!(data = (void *)kmalloc())) {
398:             brelse(buf);
399:             return -ENOMEM;
400:         }
401:         memcpy_b(data, buf->data, ii->sb->s_blocksize);
402:         brelse(buf);
403:
404:         elf32_h = (struct elf32_hdr *)data;
405:         if(check_elf(elf32_h)) {
406:             kfree((unsigned int)data);
407:             return -ELIBBAD;
408:         }
409:
410:         last_ptload = NULL;
411:         for(n = 0; n < elf32_h->e_phnum; n++) {
412:             elf32_ph = (struct elf32_phdr *) (data + elf32_h->e_phoff + (size
of(struct elf32_phdr) * n));
413:             if(elf32_ph->p_type == PT_LOAD) {
414: #ifdef __DEBUG__
415:                 printk("p_offset = 0x%08x\n", elf32_ph->p_offset);
416:                 printk("p_vaddr = 0x%08x\n", elf32_ph->p_vaddr);
417:                 printk("p_paddr = 0x%08x\n", elf32_ph->p_paddr);
418:                 printk("p_filesz = 0x%08x\n", elf32_ph->p_filesz);
419:                 printk("p_memsz = 0x%08x\n\n", elf32_ph->p_memsz);
420: #endif /*__DEBUG__ */
421:                 start = (elf32_ph->p_vaddr & PAGE_MASK) + MMAP_START;
422:                 length = (elf32_ph->p_vaddr & ~PAGE_MASK) + elf32_ph->p_
filesz;
423:                 type = P_DATA;
424:                 prot = 0;
425:                 if(elf32_ph->p_flags & PF_R) {
426:                     prot = PROT_READ;
427:                 }
428:                 if(elf32_ph->p_flags & PF_W) {
429:                     prot |= PROT_WRITE;
430:                 }
431:                 if(elf32_ph->p_flags & PF_X) {
432:                     prot |= PROT_EXEC;
433:                     type = P_TEXT;
434:                 }
435:                 errno = do_mmap(ii, start, length, prot, MAP_PRIVATE | M
AP_FIXED, elf32_ph->p_offset & PAGE_MASK, type, O_RDONLY);
436:                 if(errno < 0 && errno > -PAGE_SIZE) {
437:                     kfree((unsigned int)data);
438:                     send_sig(current, SIGSEGV);
439:                     return -ENOEXEC;
440:                 }
441:                 last_ptload = elf32_ph;
442:             }
443:         }
444:
445:         if(!last_ptload) {
446:             printk("WARNING: 'last_ptload' is NULL!\n");
447:         }
448:         elf32_ph = last_ptload;
449:
450:         /* zero-fill the fractional page of the DATA section */
451:         end = PAGE_ALIGN(elf32_ph->p_vaddr + elf32_ph->p_filesz) + MMAP_START;
452:         start = (elf32_ph->p_vaddr + elf32_ph->p_filesz) + MMAP_START;
453:         length = end - start;
454:
455:         /* this will generate a page fault which will load the page in */
456:         memset_b((void *)start, NULL, length);
457:
458:         /* setup the BSS section */
459:         start = (elf32_ph->p_vaddr + elf32_ph->p_filesz) + MMAP_START;
460:         start = PAGE_ALIGN(start);

```

fs/elf.c

Page 8/12

```

461:     end = (elf32_ph->p_vaddr + elf32_ph->p_memsz) + MMAP_START;
462:     end = PAGE_ALIGN(end);
463:     length = end - start;
464:     errno = do_mmap(NULL, start, length, PROT_READ | PROT_WRITE, MAP_PRIVATE
| MAP_FIXED, 0, P_BSS, 0);
465:     if(errno < 0 && errno > -PAGE_SIZE) {
466:         kfree((unsigned int)data);
467:         send_sig(current, SIGSEGV);
468:         return -ENOEXEC;
469:     }
470:     kfree((unsigned int)data);
471:     return elf32_h->e_entry + MMAP_START;
472: }
473:
474: int elf_load(struct inode *i, char *argv[], char *envp[], struct sigcontext *sc)
475: {
476:     int n, errno;
477:     struct buffer *buf;
478:     struct binargs barg;
479:     struct elf32_hdr *elf32_h;
480:     struct elf32_phdr *elf32_ph, *last_ptload;
481:     struct inode *ii;
482:     __blk_t block;
483:     unsigned int start, end, length;
484:     unsigned int prot;
485:     char *interpreter;
486:     char *data;
487:     int at_base, phdr_addr;
488:     char type;
489:     unsigned int ae_ptr_len, ae_str_len;
490:     unsigned int sp, str;
491:
492:     if((block = bmap(i, 0, FOR_READING)) < 0) {
493:         return block;
494:     }
495:     if(!(buf = bread(i->dev, block, i->sb->s_blocksize))) {
496:         return -EIO;
497:     }
498:
499:     /*
500:      * The contents of the buffer is copied and then freed immediately to
501:      * make sure that it won't conflict while zeroing the BSS fractional
502:      * page, in case that the same block is requested during the page fault.
503:      */
504:     if(!(data = (void *)kmalloc())) {
505:         brelse(buf);
506:         return -ENOMEM;
507:     }
508:     memcpy_b(data, buf->data, i->sb->s_blocksize);
509:     brelse(buf);
510:
511:     elf32_h = (struct elf32_hdr *)data;
512:     if(check_elf(elf32_h)) {
513:         kfree((unsigned int)data);
514:         if(current->pid == INIT) {
515:             PANIC("%s has an unrecognized binary format.\n", INIT_PR
OGRAM);
516:         }
517:         return -ENOEXEC;
518:     }
519:
520:     /* check if an interpreter is required */
521:     interpreter = NULL;
522:     ii = NULL;
523:     phdr_addr = at_base = 0;
524:     for(n = 0; n < elf32_h->e_phnum; n++) {
525:         elf32_ph = (struct elf32_phdr *) (data + elf32_h->e_phoff + (size

```

fs/elf.c

Page 9/12

```

of(struct elf32_phdr * n));
526:         if(elf32_ph->p_type == PT_INTERP) {
527:             at_base = MMAP_START;
528:             interpreter = data + elf32_ph->p_offset;
529:             if(namei(interpreter, &ii, NULL, FOLLOW_LINKS)) {
530:                 printk("%s(): can't find interpreter '%s'.\n", _
_FUNCTION__, interpreter);
531:                 kfree((unsigned int)data);
532:                 send_sig(current, SIGSEGV);
533:                 return -ELIBACC;
534:             }
535: #ifdef __DEBUG__
536:             printk("p_offset = 0x%08x\n", elf32_ph->p_offset);
537:             printk("p_vaddr = 0x%08x\n", elf32_ph->p_vaddr);
538:             printk("p_paddr = 0x%08x\n", elf32_ph->p_paddr);
539:             printk("p_filesz = 0x%08x\n", elf32_ph->p_filesz);
540:             printk("p_memsz = 0x%08x\n", elf32_ph->p_memsz);
541:             printk("using interpreter '%s'\n", interpreter);
542: #endif /*__DEBUG__*/
543:         }
544:     }
545:
546:     for(n = 0; n < ARG_MAX; n++) {
547:         barg.page[n] = 0;
548:     }
549:     barg.argv_len = barg.envp_len = 0;
550:
551:     for(n = 0; argv[n]; n++) {
552:         if((errno = check_user_area(VERIFY_READ, argv[n], sizeof(char *
))) {
553:             kfree((unsigned int)data);
554:             return errno;
555:         }
556:         barg.argv_len += strlen(argv[n]) + 1;
557:     }
558:     barg argc = n;
559:
560:     for(n = 0; envp[n]; n++) {
561:         if((errno = check_user_area(VERIFY_READ, envp[n], sizeof(char *
))) {
562:             kfree((unsigned int)data);
563:             return errno;
564:         }
565:         barg.envp_len += strlen(envp[n]) + 1;
566:     }
567:     barg.envc = n;
568:
569:     strncpy(current->argv0, argv[0], NAME_MAX);
570:
571:     /*
572:     * calculate the final size of 'ae_ptr_len' based on:
573:     * - argc = 4 bytes (unsigned int)
574:     * - barg argc = (num. of pointers to strings + 1 NULL) x 4 bytes (unsi
gned int)
575:     * - barg.envc = (num. of pointers to strings + 1 NULL) x 4 bytes (unsi
gned int)
576:     */
577:     ae_ptr_len = (1 + (barg argc + 1) + (barg.envc + 1)) * sizeof(unsigned i
nt);
578:     ae_str_len = barg.argv_len + barg.envp_len;
579:     if(ae_ptr_len + ae_str_len > (ARG_MAX * PAGE_SIZE)) {
580:         printk("WARNING: %s(): argument list (%d) exceeds ARG_MAX (%d)!\n
n", _FUNCTION__, ae_ptr_len + ae_str_len, ARG_MAX * PAGE_SIZE);
581:         kfree((unsigned int)data);
582:         return -E2BIG;
583:     }
584:

```

fs/elf.c

Page 10/12

```

585: #ifdef __DEBUG__
586:     printk("argc=%d (argv_len=%d) envc=%d (envp_len=%d) ae_ptr_len=%d ae_str
r_len=%d\n", barg.argc, barg.argv_len, barg.envc, barg.envp_len, ae_ptr_len, ae_str_len
);
587: #endif /* __DEBUG__ */
588:
589:     /* save 'argv' and 'envp' into the kernel space */
590:     if((errno = copy_strings(&barg, argv, envp))) {
591:         kfree((unsigned int)data);
592:         return errno;
593:     }
594:
595:
596:     /* point of no return */
597:
598:     release_binary();
599:     current->rss = 0;
600:
601:     current->entry_address = elf32_h->e_entry;
602:     if(interpreter) {
603:         errno = elf_load_interpreter(ii);
604:         if(errno < 0) {
605:             printk("%s(): unable to load the interpreter '%s'.\n", _
_FUNCTION__, interpreter);
606:             kfree((unsigned int)data);
607:             free_barg_pages(&barg);
608:             iput(ii);
609:             send_sig(current, SIGKILL);
610:             return errno;
611:         }
612:         current->entry_address = errno;
613:         iput(ii);
614:     }
615:
616:     elf32_ph = last_ptload = NULL;
617:     for(n = 0; n < elf32_h->e_phnum; n++) {
618:         elf32_ph = (struct elf32_phdr *) (data + elf32_h->e_phoff + (size
of(struct elf32_phdr) * n));
619:         if(elf32_ph->p_type == PT_PHDR) {
620:             phdr_addr = elf32_ph->p_vaddr;
621:         }
622:         if(elf32_ph->p_type == PT_LOAD) {
623:             start = elf32_ph->p_vaddr & PAGE_MASK;
624:             length = (elf32_ph->p_vaddr & ~PAGE_MASK) + elf32_ph->p_
filesz;
625:             type = P_DATA;
626:             prot = 0;
627:             if(elf32_ph->p_flags & PF_R) {
628:                 prot = PROT_READ;
629:             }
630:             if(elf32_ph->p_flags & PF_W) {
631:                 prot |= PROT_WRITE;
632:             }
633:             if(elf32_ph->p_flags & PF_X) {
634:                 prot |= PROT_EXEC;
635:                 type = P_TEXT;
636:             }
637:             errno = do_mmap(i, start, length, prot, MAP_PRIVATE | MA
P_FIXED, elf32_ph->p_offset & PAGE_MASK, type, O_RDONLY);
638:             if(errno < 0 && errno > -PAGE_SIZE) {
639:                 kfree((unsigned int)data);
640:                 free_barg_pages(&barg);
641:                 send_sig(current, SIGSEGV);
642:                 return -ENOEXEC;
643:             }
644:             last_ptload = elf32_ph;
645:         }

```

```

646:         }
647:
648:         elf32_ph = last_ptload;
649:
650:         /* zero-fill the fractional page of the DATA section */
651:         end = PAGE_ALIGN(elf32_ph->p_vaddr + elf32_ph->p_filesz);
652:         start = elf32_ph->p_vaddr + elf32_ph->p_filesz;
653:         length = end - start;
654:
655:         /* this will generate a page fault which will load the page in */
656:         memset_b((void *)start, NULL, length);
657:
658:         /* setup the BSS section */
659:         start = elf32_ph->p_vaddr + elf32_ph->p_filesz;
660:         start = PAGE_ALIGN(start);
661:         end = elf32_ph->p_vaddr + elf32_ph->p_memsz;
662:         end = PAGE_ALIGN(end);
663:         length = end - start;
664:         errno = do_mmap(NULL, start, length, PROT_READ | PROT_WRITE, MAP_PRIVATE
| MAP_FIXED, 0, P_BSS, 0);
665:         if(errno < 0 && errno > -PAGE_SIZE) {
666:             kfree((unsigned int)data);
667:             free_barg_pages(&barg);
668:             send_sig(current, SIGSEGV);
669:             return -ENOEXEC;
670:         }
671:         current->brk_lower = start;
672:
673:         /* setup the HEAP section */
674:         start = elf32_ph->p_vaddr + elf32_ph->p_memsz;
675:         start = PAGE_ALIGN(start);
676:         length = PAGE_SIZE;
677:         errno = do_mmap(NULL, start, length, PROT_READ | PROT_WRITE, MAP_PRIVATE
| MAP_FIXED, 0, P_HEAP, 0);
678:         if(errno < 0 && errno > -PAGE_SIZE) {
679:             kfree((unsigned int)data);
680:             free_barg_pages(&barg);
681:             send_sig(current, SIGSEGV);
682:             return -ENOEXEC;
683:         }
684:         current->brk = start;
685:
686:         /* setup the STACK section */
687:         sp = KERNEL_BASE_ADDR - 4;      /* formerly 0xBFFFFFFC */
688:         sp -= ae_str_len;
689:         str = sp;      /* this is the address of the first string (argv[0]) */
690:         sp &= ~3;
691:         sp -= at_base ? (AT_ITEMS * 2) * sizeof(unsigned int) : 2 * sizeof(unsigned
ned int);
692:         sp -= ae_ptr_len;
693:         length = KERNEL_BASE_ADDR - (sp & PAGE_MASK);
694:         errno = do_mmap(NULL, sp & PAGE_MASK, length, PROT_READ | PROT_WRITE | P
ROT_EXEC, MAP_PRIVATE | MAP_FIXED, 0, P_STACK, 0);
695:         if(errno < 0 && errno > -PAGE_SIZE) {
696:             kfree((unsigned int)data);
697:             free_barg_pages(&barg);
698:             send_sig(current, SIGSEGV);
699:             return -ENOEXEC;
700:         }
701:
702:         elf_create_stack(&barg, (unsigned int *)sp, str, at_base, elf32_h, phdr_
addr);
703:         kfree((unsigned int)data);
704:         free_barg_pages(&barg);
705:
706:         /* set %esp to point to 'argc' */
707:         sc->oldesp = sp;

```

fs/elf.c

Page 12/12

```
708:         sc->eflags = 0x202;        /* FIXME: linux 2.2 = 0x292 */
709:         sc->eip = current->entry_address;
710:         sc->err = 0;
711:         sc->eax = 0;
712:         sc->ecx = 0;
713:         sc->edx = 0;
714:         sc->ebx = 0;
715:         sc->ebp = 0;
716:         sc->esi = 0;
717:         sc->edi = 0;
718:         return 0;
719:     }
```

fs/fd.c

Page 1/1

```
1: /*
2:  * fiwix/fs/fd.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/errno.h>
9: #include <fiwix/types.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/sleep.h>
12: #include <fiwix/stdio.h>
13: #include <fiwix/string.h>
14:
15: struct fd *fd_table;
16:
17: static struct resource fd_resource = { NULL, NULL };
18:
19: int get_new_fd(struct inode *i)
20: {
21:     unsigned int n;
22:
23:     lock_resource(&fd_resource);
24:
25:     for(n = 1; n < NR_OPENS; n++) {
26:         if(fd_table[n].count == 0) {
27:             memset_b(&fd_table[n], NULL, sizeof(struct fd));
28:             fd_table[n].inode = i;
29:             fd_table[n].count = 1;
30:             unlock_resource(&fd_resource);
31:             return n;
32:         }
33:     }
34:
35:     unlock_resource(&fd_resource);
36:
37:     return -ENFILE;
38: }
39:
40: void release_fd(unsigned int fd)
41: {
42:     lock_resource(&fd_resource);
43:     fd_table[fd].count = 0;
44:     unlock_resource(&fd_resource);
45: }
46:
47: void fd_init(void)
48: {
49:     memset_b(fd_table, NULL, fd_table_size);
50: }
```

fs/filesystems.c

Page 1/2

```

1: /*
2:  * fiwix/fs/filesystems.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/errno.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/filesystems.h>
12: #include <fiwix/fs_pipe.h>
13: #include <fiwix/fs_iso9660.h>
14: #include <fiwix/fs_proc.h>
15: #include <fiwix/stdio.h>
16: #include <fiwix/string.h>
17:
18: int register_filesystem(const char *name, struct fs_operations *fsop)
19: {
20:     int n;
21:     __dev_t dev;
22:
23:     for(n = 0; n < NR_FILESYSTEMS; n++) {
24:         if(filesystems_table[n].name) {
25:             if(strcmp(filesystems_table[n].name, name) == 0) {
26:                 printk("WARNING: %s(): filesystem '%s' already r
registered!\n", __FUNCTION__, name);
27:                 return 1;
28:             }
29:         }
30:         if(!filesystems_table[n].name) {
31:             filesystems_table[n].name = name;
32:             filesystems_table[n].fsop = fsop;
33:             if((fsop->flags & FSOP_KERN_MOUNT)) {
34:                 dev = fsop->fsdev;
35:                 return kern_mount(dev, &filesystems_table[n]);
36:             }
37:             return 0;
38:         }
39:     }
40:     printk("WARNING: %s(): filesystems table is full!\n", __FUNCTION__);
41:     return 1;
42: }
43:
44: struct filesystems * get_filesystem(const char *name)
45: {
46:     int n;
47:
48:     if(!name) {
49:         return NULL;
50:     }
51:     for(n = 0; n < NR_FILESYSTEMS; n++) {
52:         if(!filesystems_table[n].name) {
53:             continue;
54:         }
55:         if(strcmp(filesystems_table[n].name, name) == 0) {
56:             return &filesystems_table[n];
57:         }
58:     }
59:     return NULL;
60: }
61:
62: void fs_init(void)
63: {
64:     memset_b(filesystems_table, NULL, sizeof(filesystems_table));
65:
66:     if(minix_init()) {

```


fs/filesystems.c

Page 2/2

```
67:                printk("%s(): unable to register 'minix' filesystem.\n", __FUNCT
ION__);
68:                }
69:                if(ext2_init()) {
70:                    printk("%s(): unable to register 'ext2' filesystem.\n", __FUNCTI
ON__);
71:                }
72:                if(pipefs_init()) {
73:                    printk("%s(): unable to register 'pipefs' filesystem.\n", __FUNC
TION__);
74:                }
75:                if(iso9660_init()) {
76:                    printk("%s(): unable to register 'iso9660' filesystem.\n", __FUN
CTION__);
77:                }
78:                if(procfs_init()) {
79:                    printk("%s(): unable to register 'procfs' filesystem.\n", __FUNC
TION__);
80:                }
81: }
```

fs/inode.c

Page 1/7

```

1: /*
2:  * fiwix/fs/inode.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: /*
9:  * inode.c implements a cache with a free list as a doubly circular linked
10:  * list and a chained hash table with doubly linked lists.
11:  *
12:  * hash table
13:  * +-----+ +-----+ +-----+ +-----+
14:  * | index | |prev|data|next| |prev|data|next| |prev|data|next|
15:  * |   0   --> | / | | | | | <--- | | | | <--- | | / |
16:  * +-----+ +-----+ +-----+ +-----+
17:  * +-----+ +-----+ +-----+ +-----+
18:  * | index | |prev|data|next| |prev|data|next| |prev|data|next|
19:  * |   1   --> | / | | | | | <--- | | | | <--- | | / |
20:  * +-----+ +-----+ +-----+ +-----+
21:  *                (inode)                (inode)                (inode)
22:  *      ...
23:  */
24:
25: #include <fiwix/asm.h>
26: #include <fiwix/sleep.h>
27: #include <fiwix/sched.h>
28: #include <fiwix/fs.h>
29: #include <fiwix/filesystems.h>
30: #include <fiwix/stat.h>
31: #include <fiwix/errno.h>
32: #include <fiwix/mm.h>
33: #include <fiwix/stdio.h>
34: #include <fiwix/string.h>
35:
36: #define INODE_HASH(dev, inode) (((__dev_t)(dev) ^ (__ino_t)(inode)) % (NR_INO_H
ASH))
37: #define NR_INODES                (inode_table_size / sizeof(struct inode))
38: #define NR_INO_HASH              (inode_hash_table_size / sizeof(unsigned int))
39:
40: struct inode *inode_table;          /* inode pool */
41: struct inode *inode_head;          /* inode pool head */
42: struct inode **inode_hash_table;
43:
44: int inodes_on_free_list = 0;
45: static struct resource sync_resource = { NULL, NULL };
46:
47: static void insert_to_hash(struct inode *i)
48: {
49:     struct inode **h;
50:     int n;
51:
52:     n = INODE_HASH(i->dev, i->inode);
53:     h = &inode_hash_table[n];
54:
55:     if(!*h) {
56:         *h = i;
57:         (*h)->prev_hash = (*h)->next_hash = NULL;
58:     } else {
59:         i->prev_hash = NULL;
60:         i->next_hash = *h;
61:         (*h)->prev_hash = i;
62:         *h = i;
63:     }
64: }
65:
66: static void remove_from_hash(struct inode *i)

```

fs/inode.c

Page 2/7

```

67: {
68:     struct inode **h;
69:     int n;
70:
71:     n = INODE_HASH(i->dev, i->inode);
72:     h = &inode_hash_table[n];
73:
74:     while(*h) {
75:         if(*h == i) {
76:             if((*h)->next_hash) {
77:                 (*h)->next_hash->prev_hash = (*h)->prev_hash;
78:             }
79:             if((*h)->prev_hash) {
80:                 (*h)->prev_hash->next_hash = (*h)->next_hash;
81:             }
82:             if(h == &inode_hash_table[n]) {
83:                 *h = (*h)->next_hash;
84:             }
85:             break;
86:         }
87:         h = &(*h)->next_hash;
88:     }
89: }
90:
91: static void remove_from_free_list(struct inode *i)
92: {
93:     i->prev_free->next_free = i->next_free;
94:     i->next_free->prev_free = i->prev_free;
95:     inodes_on_free_list--;
96:     if(i == inode_head) {
97:         inode_head = i->next_free;
98:     }
99: }
100:
101: static void inode_wait(struct inode *i)
102: {
103:     unsigned long int flags;
104:
105:     for(;;) {
106:         SAVE_FLAGS(flags); CLI();
107:         if(i->locked) {
108:             RESTORE_FLAGS(flags);
109:             sleep(i, PROC_UNINTERRUPTIBLE);
110:         } else {
111:             break;
112:         }
113:     }
114:     RESTORE_FLAGS(flags);
115: }
116:
117: static struct inode * get_free_inode(void)
118: {
119:     struct inode *i;
120:
121:     /* no more inodes on free list */
122:     if(inode_head == inode_head->next_free) {
123:         return NULL;
124:     }
125:
126:     i = inode_head;
127:     inode_head->next_free->prev_free = inode_head->prev_free;
128:     inode_head->prev_free->next_free = inode_head->next_free;
129:     inode_head = inode_head->next_free;
130:
131:     return i;
132: }
133:

```

fs/inode.c

Page 3/7

```

134: static int read_inode(struct inode *i)
135: {
136:     int errno;
137:
138:     inode_lock(i);
139:     if(i->sb && i->sb->fsop && i->sb->fsop->read_inode) {
140:         errno = i->sb->fsop->read_inode(i);
141:         inode_unlock(i);
142:         return errno;
143:     }
144:     inode_unlock(i);
145:     return -EINVAL;
146: }
147:
148: static int write_inode(struct inode *i)
149: {
150:     int errno;
151:
152:     errno = 1;
153:
154:     inode_lock(i);
155:     if(i->sb && i->sb->fsop && i->sb->fsop->write_inode) {
156:         errno = i->sb->fsop->write_inode(i);
157:     } else {
158:         /* i.e. PIPE_DEV inodes can't be flushed on disk */
159:         i->dirty = 0;
160:         errno = 0;
161:     }
162:     inode_unlock(i);
163:
164:     return errno;
165: }
166:
167: static struct inode * search_inode_hash(__dev_t dev, __ino_t inode)
168: {
169:     struct inode *i;
170:     int n;
171:
172:     n = INODE_HASH(dev, inode);
173:     i = inode_hash_table[n];
174:
175:     while(i) {
176:         if(i->dev == dev && i->inode == inode) {
177:             return i;
178:         }
179:         i = i->next_hash;
180:     }
181:
182:     return NULL;
183: }
184:
185: static struct inode * get_blank_inode(void)
186: {
187:     unsigned long int flags;
188:     struct inode *i;
189:
190:     SAVE_FLAGS(flags); CLI();
191:
192:     if((i = get_free_inode())) {
193:         remove_from_free_list(i);
194:         remove_from_hash(i);
195:         i->i_mode = 0;
196:         i->i_uid = 0;
197:         i->i_size = 0;
198:         i->i_atime = 0;
199:         i->i_ctime = 0;
200:         i->i_mtime = 0;

```

fs/inode.c

Page 4/7

```

201:         i->i_gid = 0;
202:         i->i_nlink = 0;
203:         i->i_blocks = 0;
204:         i->i_flags = 0;
205:         i->locked = 0;
206:         i->dirty = 0;
207:         i->mount_point = NULL;
208:         i->dev = 0;
209:         i->inode = 0;
210:         i->count = 0;
211:         i->rdev = 0;
212:         i->fsop = NULL;
213:         i->sb = NULL;
214:         memset_b(&i->u, NULL, sizeof(i->u));
215:     }
216:     RESTORE_FLAGS(flags);
217:     return i;
218: }
219:
220: void inode_lock(struct inode *i)
221: {
222:     unsigned long int flags;
223:
224:     for(;;) {
225:         SAVE_FLAGS(flags); CLI();
226:         if(i->locked) {
227:             RESTORE_FLAGS(flags);
228:             sleep(i, PROC_UNINTERRUPTIBLE);
229:         } else {
230:             break;
231:         }
232:     }
233:     i->locked = 1;
234:     RESTORE_FLAGS(flags);
235: }
236:
237: void inode_unlock(struct inode *i)
238: {
239:     unsigned long int flags;
240:
241:     SAVE_FLAGS(flags); CLI();
242:     i->locked = 0;
243:     wakeup(i);
244:     RESTORE_FLAGS(flags);
245: }
246:
247: struct inode * ialloc(struct superblock *sb)
248: {
249:     int errno;
250:     struct inode *i;
251:
252:     if((i = get_blank_inode())) {
253:         i->sb = sb;
254:         i->rdev = sb->dev;
255:         if(i->sb && i->sb->fsop && i->sb->fsop->ialloc) {
256:             errno = i->sb->fsop->ialloc(i);
257:         } else {
258:             printk("WARNING: this filesystem does not have the iallo
c() method!\n");
259:             i->count = 1;
260:             i->sb = NULL;
261:             iput(i);
262:             return NULL;
263:         }
264:         if(errno) {
265:             i->count = 1;
266:             i->sb = NULL;

```

fs/inode.c

Page 5/7

```

267:             iput(i);
268:             return NULL;
269:         }
270:         i->dev = sb->dev;
271:         insert_to_hash(i);
272:         return i;
273:     }
274:     printk("WARNING: %s(): no more inodes on free list!\n", __FUNCTION__);
275:     return NULL;
276: }
277:
278: struct inode * iget(struct superblock *sb, __ino_t inode)
279: {
280:     unsigned long int flags;
281:     struct inode *i;
282:
283:     if(!inode) {
284:         return NULL;
285:     }
286:
287:     for(;;) {
288:         if((i = search_inode_hash(sb->dev, inode))) {
289:             inode_wait(i);
290:             SAVE_FLAGS(flags); CLI();
291:
292:             /* update superblock pointer from mount_table */
293:             i->sb = sb;
294:
295:             if(i->mount_point) {
296:                 i = i->mount_point;
297:             }
298:             /* FIXME: i->locked = 1; ? */
299:             if(++i->count == 1) {
300:                 remove_from_free_list(i);
301:             }
302:             RESTORE_FLAGS(flags);
303:             return i;
304:         }
305:
306:         if(!(i = get_blank_inode())) {
307:             printk("WARNING: %s(): no more inodes on free list! (%d)
.\n", __FUNCTION__, inodes_on_free_list);
308:             return NULL;
309:         }
310:
311:         SAVE_FLAGS(flags); CLI();
312:         i->dev = i->rdev = sb->dev;
313:         i->inode = inode;
314:         i->sb = sb;
315:         i->count = 1;
316:         RESTORE_FLAGS(flags);
317:         if(read_inode(i)) {
318:             iput(i);
319:             return NULL;
320:         }
321:         insert_to_hash(i);
322:         /* FIXME: i->locked = 1; ? */
323:         return i;
324:     }
325: }
326:
327: int bmap(struct inode *i, __off_t offset, int mode)
328: {
329:     if(i->fsop && i->fsop->bmap) {
330:         return i->fsop->bmap(i, offset, mode);
331:     }
332:     return -EPERM;

```

fs/inode.c

Page 6/7

```

333: }
334:
335: int check_fs_busy(__dev_t dev, struct inode *root)
336: {
337:     struct inode *i;
338:     unsigned int n;
339:
340:     i = &inode_table[0];
341:     for(n = 0; n < NR_INODES; n++, i = &inode_table[n]) {
342:         if(i->dev == dev && i->count) {
343:             if(i == root && i->count == 1) {
344:                 continue;
345:             }
346:             /* FIXME: to be removed */
347:             printk("WARNING: root %d with count %d (on dev %d,%d)\n"
, root->inode, root->count, MAJOR(i->dev), MINOR(i->dev));
348:             printk("WARNING: inode %d with count %d (on dev %d,%d)\n"
", i->inode, i->count, MAJOR(i->dev), MINOR(i->dev));
349:             return 1;
350:         }
351:     }
352:     return 0;
353: }
354:
355: void iput(struct inode *i)
356: {
357:     unsigned long int flags;
358:
359:     /* this solves the problem with rmdir('/') and iput(dir) which is NULL */
360:     if(!i) {
361:         return;
362:     }
363:
364:     if(!i->count) {
365:         printk("WARNING: %s(): trying to free an already freed inode (%d
)! \n", __FUNCTION__, i->inode);
366:         return;
367:     }
368:
369:     SAVE_FLAGS(flags); CLI();
370:
371:     if(--i->count == 0) {
372:         if(!i->i_nlink) {
373:             if(i->sb && i->sb->fsop && i->sb->fsop->ifree) {
374:                 inode_lock(i);
375:                 i->sb->fsop->ifree(i);
376:                 remove_from_hash(i);
377:                 inode_unlock(i);
378:             }
379:         }
380:         if(i->dirty) {
381:             if(write_inode(i)) {
382:                 printk("WARNING: %s(): can't write inode %d (%d
%d), will remain as dirty.\n", __FUNCTION__, i->inode, MAJOR(i->dev), MINOR(i->dev));
383:                 RESTORE_FLAGS(flags);
384:                 return;
385:             }
386:         }
387:         if(!inode_head) {
388:             i->prev_free = i->next_free = i;
389:             inode_head = i;
390:         } else {
391:             i->next_free = inode_head;
392:             i->prev_free = inode_head->prev_free;
393:             inode_head->prev_free->next_free = i;
394:             inode_head->prev_free = i;

```

```

395:         }
396:         inodes_on_free_list++;
397:     }
398:
399:     RESTORE_FLAGS(flags);
400: }
401:
402: void sync_inodes(__dev_t dev)
403: {
404:     struct inode *i;
405:     int n;
406:
407:     i = &inode_table[0];
408:
409:     lock_resource(&sync_resource);
410:     for(n = 0; n < NR_INODES; n++) {
411:         if(i->dirty) {
412:             if(!dev || i->dev == dev) {
413:                 inode_wait(i);
414:                 if(write_inode(i)) {
415:                     printk("WARNING: %s(): can't write inode
%d (%d,%d), will remain as dirty.\n", __FUNCTION__, i->inode, MAJOR(i->dev), MINOR(i->
dev));
416:                 }
417:             }
418:         }
419:         i++;
420:     }
421:     unlock_resource(&sync_resource);
422:     return;
423: }
424:
425: void invalidate_inodes(__dev_t dev)
426: {
427:     unsigned long int flags;
428:     unsigned int n;
429:     struct inode *i;
430:
431:     i = &inode_table[0];
432:     SAVE_FLAGS(flags); CLI();
433:
434:     for(n = 0; n < NR_INODES; n++) {
435:         if(i->dev == dev) {
436:             inode_wait(i);
437:             remove_from_hash(i);
438:             i->locked = 0;
439:             wakeup(&inode_wait);
440:         }
441:         i++;
442:     }
443:
444:     RESTORE_FLAGS(flags);
445: }
446:
447: void inode_init(void)
448: {
449:     struct inode *i;
450:     unsigned int n;
451:
452:     memset_b(inode_table, NULL, inode_table_size);
453:     memset_b(inode_hash_table, NULL, inode_hash_table_size);
454:     for(n = 0; n < NR_INODES; n++) {
455:         i = &inode_table[n];
456:         i->count = 1;
457:         iput(i);
458:     }
459: }

```


fs/locks.c

Page 1/4

```

1: /*
2:  * fiwix/fs/locks.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/errno.h>
9: #include <fiwix/types.h>
10: #include <fiwix/locks.h>
11: #include <fiwix/fs.h>
12: #include <fiwix/sleep.h>
13: #include <fiwix/sched.h>
14: #include <fiwix/stdio.h>
15: #include <fiwix/string.h>
16:
17: static struct resource flock_resource = { NULL, NULL };
18:
19: static struct flock_file * get_new_flock(struct inode *i)
20: {
21:     int n;
22:     struct flock_file *ff;
23:
24:     lock_resource(&flock_resource);
25:
26:     for(n = 0; n < NR_FLOCKS; n++) {
27:         ff = &flock_file_table[n];
28:         if(!ff->inode) {
29:             ff->inode = i; /* mark it as busy */
30:             unlock_resource(&flock_resource);
31:             return ff;
32:         }
33:     }
34:
35:     printk("WARNING: %s(): no more free slots in flock file table.\n");
36:     unlock_resource(&flock_resource);
37:     return NULL;
38: }
39:
40: static void release_flock(struct flock_file *ff)
41: {
42:     memset_b(ff, 0, sizeof(struct flock_file));
43: }
44:
45: static struct flock_file * get_flock_file(struct inode *i, int op, struct proc *
p)
46: {
47:     int n;
48:     struct flock_file *ff;
49:
50:     lock_resource(&flock_resource);
51:
52:     ff = NULL;
53:     for(n = 0; n < NR_FLOCKS; n++) {
54:         ff = &flock_file_table[n];
55:         if(ff->inode != i) {
56:             continue;
57:         }
58:         if(p && p != ff->proc) {
59:             continue;
60:         }
61:         break;
62:     }
63:     unlock_resource(&flock_resource);
64:     return ff;
65: }
66:

```

fs/locks.c

Page 2/4

```

67: int posix_lock(int ufd, int cmd, struct flock *fl)
68: {
69:     int n;
70:     struct flock_file *ff;
71:     struct inode *i;
72:     unsigned char type;
73:
74:     lock_resource(&flock_resource);
75:     i = fd_table[current->fd[ufd]].inode;
76:     for(n = 0; n < NR_FLOCKS; n++) {
77:         ff = &flock_file_table[n];
78:         if(ff->inode != i) {
79:             continue;
80:         }
81:         break;
82:     }
83:     unlock_resource(&flock_resource);
84:     if(cmd == F_GETLK) {
85:         if(ff->inode == i) {
86:             fl->l_type = ff->type & LOCK_SH ? F_RDLCK : F_WRLCK;
87:             fl->l_whence = SEEK_SET;
88:             fl->l_start = 0;
89:             fl->l_len = 0;
90:             fl->l_pid = ff->proc->pid;
91:         } else {
92:             fl->l_type = F_UNLCK;
93:         }
94:     }
95:
96:     switch(fl->l_type) {
97:         case F_RDLCK:
98:             type = LOCK_SH;
99:             break;
100:        case F_WRLCK:
101:            type = LOCK_EX;
102:            break;
103:        case F_UNLCK:
104:            type = LOCK_UN;
105:            break;
106:        default:
107:            return -EINVAL;
108:    }
109:    if(cmd == F_SETLK) {
110:        return flock_inode(i, type);
111:    }
112:    if(cmd == F_SETLKW) {
113:        return flock_inode(i, type | LOCK_NB);
114:    }
115:    return 0;
116: }
117:
118: void flock_release_inode(struct inode *i)
119: {
120:     int n;
121:     struct flock_file *ff;
122:
123:     lock_resource(&flock_resource);
124:     for(n = 0; n < NR_FLOCKS; n++) {
125:         ff = &flock_file_table[n];
126:         if(ff->inode != i) {
127:             continue;
128:         }
129:         if(ff->proc != current) {
130:             continue;
131:         }
132:         wakeup(ff);
133:         release_flock(ff);

```

fs/locks.c

Page 3/4

```

134:         }
135:         unlock_resource(&flock_resource);
136:     }
137:
138: int flock_inode(struct inode *i, int op)
139: {
140:     int n;
141:     struct flock_file *ff, *new;
142:
143:     if(op & LOCK_UN) {
144:         if((ff = get_flock_file(i, op, current))) {
145:             wakeup(ff);
146:             release_flock(ff);
147:         }
148:         return 0;
149:     }
150:
151: loop:
152:     lock_resource(&flock_resource);
153:     new = NULL;
154:     for(n = 0; n < NR_FLOCKS; n++) {
155:         ff = &flock_file_table[n];
156:         if(ff->inode != i) {
157:             continue;
158:         }
159:         if(op & LOCK_SH) {
160:             if(ff->type & LOCK_EX) {
161:                 if(ff->proc == current) {
162:                     new = ff;
163:                     wakeup(ff);
164:                     break;
165:                 }
166:                 unlock_resource(&flock_resource);
167:                 if(op & LOCK_NB) {
168:                     return -EWOULDBLOCK;
169:                 }
170:                 if(sleep(ff, PROC_INTERRUPTIBLE)) {
171:                     return -EINTR;
172:                 }
173:                 goto loop;
174:             }
175:         }
176:         if(op & LOCK_EX) {
177:             if(ff->proc == current) {
178:                 new = ff;
179:                 continue;
180:             }
181:             unlock_resource(&flock_resource);
182:             if(op & LOCK_NB) {
183:                 return -EWOULDBLOCK;
184:             }
185:             if(sleep(ff, PROC_INTERRUPTIBLE)) {
186:                 return -EINTR;
187:             }
188:             goto loop;
189:         }
190:     }
191:     unlock_resource(&flock_resource);
192:
193:     if(!new) {
194:         if(!(new = get_new_flock(i))) {
195:             return -ENOLCK;
196:         }
197:     }
198:     new->inode = i;
199:     new->type = op;
200:     new->proc = current;

```

fs/locks.c

Page 4/4

```
201:
202:     return 0;
203: }
204:
205: void flock_init(void)
206: {
207:     memset_b(flock_file_table, NULL, sizeof(flock_file_table));
208: }
```

fs/Makefile

Page 1/1

```
1: # fiwix/fs/Makefile
2: #
3: # Copyright 2018, Jordi Sanfeliu. All rights reserved.
4: # Distributed under the terms of the Fiwix License.
5: #
6:
7: .S.o:
8:     $(CC) -traditional -I$(INCLUDE) -c -o $@ $<
9: .c.o:
10:     $(CC) $(CFLAGS) -c -o $@ $<
11:
12: FSDIRS = minix ext2 pipefs iso9660 procfs
13: FILESYSTEMS = minix/minix.o ext2/ext2.o pipefs/pipefs.o iso9660/iso9660.o \
14:     procfs/procfs.o
15: OBJS = filesystems.o devices.o buffer.o fd.o locks.o super.o inode.o \
16:     namei.o elf.o
17:
18: fs:     $(OBJS)
19:     @for n in $(FSDIRS) ; do (cd $$n ; $(MAKE)) ; done
20:     $(LD) $(LDFLAGS) -r $(FILESYSTEMS) $(OBJS) -o fs.o
21:
22: clean:
23:     @for n in $(FSDIRS) ; do (cd $$n ; $(MAKE) clean) ; done
24:     rm -f *.o
25:
```

fs/namei.c

Page 1/3

```

1: /*
2:  * fiwix/fs/namei.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/sleep.h>
10: #include <fiwix/sched.h>
11: #include <fiwix/fs.h>
12: #include <fiwix/filesystems.h>
13: #include <fiwix/stat.h>
14: #include <fiwix/mm.h>
15: #include <fiwix/mman.h>
16: #include <fiwix/errno.h>
17: #include <fiwix/stdio.h>
18: #include <fiwix/string.h>
19:
20: static int namei_lookup(char *name, struct inode *dir, struct inode **i_res)
21: {
22:     if(dir->fsop && dir->fsop->lookup) {
23:         return dir->fsop->lookup(name, dir, i_res);
24:     }
25:     return -EACCES;
26: }
27:
28: static int do_namei(char *path, struct inode *dir, struct inode **i_res, struct
inode **d_res, int follow_links)
29: {
30:     char *name, *ptr_name;
31:     struct inode *i;
32:     struct superblock *sb;
33:
34:     int errno;
35:
36:     *i_res = dir;
37:     for(;;) {
38:         while(*path == '/') {
39:             path++;
40:         }
41:         if(*path == NULL) {
42:             return 0;
43:         }
44:
45:         /* extracts the next component of the path */
46:         if(!(name = (char *)kmallocc())) {
47:             return -ENOMEM;
48:         }
49:         ptr_name = name;
50:         while(*path != NULL && *path != '/') {
51:             if(ptr_name > name + NAME_MAX - 1) {
52:                 break;
53:             }
54:             *ptr_name++ = *path++;
55:         }
56:         *ptr_name = NULL;
57:
58:         /*
59:          * If the inode is the root of a file system, then return the
60:          * inode on which the file system was mounted.
61:          */
62:         if(name[0] == '.' && name[1] == '.' && name[2] == NULL) {
63:             if(dir == dir->sb->root) {
64:                 sb = dir->sb;
65:                 iput(dir);
66:                 dir = sb->dir;

```

fs/namei.c

Page 2/3

```

67:                dir->count++;
68:            }
69:        }
70:
71:        if((errno = check_permission(TO_EXEC, dir))) {
72:            break;
73:        }
74:
75:        if((errno = namei_lookup(name, dir, &i))) {
76:            break;
77:        }
78:
79:        kfree((unsigned int)name);
80:        if(*path == '/') {
81:            if(!S_ISDIR(i->i_mode) && !S_ISLNK(i->i_mode)) {
82:                iput(dir);
83:                iput(i);
84:                return -ENOTDIR;
85:            }
86:            if(S_ISLNK(i->i_mode)) {
87:                if(i->fsop && i->fsop->followlink) {
88:                    if((errno = i->fsop->followlink(dir, i,
&i))) {
89:                        iput(dir);
90:                        return errno;
91:                    }
92:                }
93:            }
94:        } else {
95:            if((i->fsop && i->fsop->followlink) && follow_links) {
96:                if((errno = i->fsop->followlink(dir, i, &i))) {
97:                    iput(dir);
98:                    return errno;
99:                }
100:            }
101:        }
102:
103:        if(d_res) {
104:            if(*d_res) {
105:                iput(*d_res);
106:            }
107:            *d_res = dir;
108:        } else {
109:            iput(dir);
110:        }
111:        dir = i;
112:        *i_res = i;
113:    }
114:
115:    kfree((unsigned int)name);
116:    if(d_res) {
117:        if(*d_res) {
118:            iput(*d_res);
119:        }
120:        /*
121:         * If that was the last component of the path,
122:         * then return the directory.
123:         */
124:        if(*path == NULL) {
125:            *d_res = dir;
126:            dir->count++;
127:        } else {
128:            /* that's an non-existent directory */
129:            *d_res = NULL;
130:            errno = -ENOTDIR;
131:        }
132:        iput(dir);

```

```
133:         *i_res = NULL;
134:     } else {
135:         iput(dir);
136:     }
137:
138:     return errno;
139: }
140:
141: int parse_namei(char *path, struct inode *base_dir, struct inode **i_res, struct
inode **d_res, int follow_links)
142: {
143:     struct inode *dir;
144:     int errno;
145:
146:     if(!path) {
147:         return -EFAULT;
148:     }
149:     if(*path == NULL) {
150:         return -ENOENT;
151:     }
152:
153:     if(!(dir = base_dir)) {
154:         dir = current->pwd;
155:     }
156:
157:     /* it is definitely an absolute path */
158:     if(path[0] == '/') {
159:         dir = current->root;
160:     }
161:     dir->count++;
162:     errno = do_namei(path, dir, i_res, d_res, follow_links);
163:     return errno;
164: }
165:
166: /*
167:  * namei() returns:
168:  * i_res -> the inode of the last component of the path, or NULL.
169:  * d_res -> the inode of the directory where i_res resides, or NULL.
170:  */
171: int namei(char *path, struct inode **i_res, struct inode **d_res, int follow_lin
ks)
172: {
173:     *i_res = NULL;
174:     if(d_res) {
175:         *d_res = NULL;
176:     }
177:     return parse_namei(path, NULL, i_res, d_res, follow_links);
178: }
```


fs/super.c

Page 1/4

```

1:  /*
2:  *  fiwix/fs/super.c
3:  *
4:  *  Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  *  Distributed under the terms of the Fiwix License.
6:  */
7:
8:  #include <fiwix/asm.h>
9:  #include <fiwix/kernel.h>
10: #include <fiwix/types.h>
11: #include <fiwix/errno.h>
12: #include <fiwix/fs.h>
13: #include <fiwix/stat.h>
14: #include <fiwix/filesystems.h>
15: #include <fiwix/sleep.h>
16: #include <fiwix/sched.h>
17: #include <fiwix/stdio.h>
18: #include <fiwix/string.h>
19:
20: struct mount *mount_table;
21: static struct resource sync_resource = { NULL, NULL };
22:
23: void superblock_lock(struct superblock *sb)
24: {
25:     unsigned long int flags;
26:
27:     for(;;) {
28:         SAVE_FLAGS(flags); CLI();
29:         if(sb->locked) {
30:             sb->wanted = 1;
31:             RESTORE_FLAGS(flags);
32:             sleep(&superblock_lock, PROC_UNINTERRUPTIBLE);
33:         } else {
34:             break;
35:         }
36:     }
37:     sb->locked = 1;
38:     RESTORE_FLAGS(flags);
39: }
40:
41: void superblock_unlock(struct superblock *sb)
42: {
43:     unsigned long int flags;
44:
45:     SAVE_FLAGS(flags); CLI();
46:     sb->locked = 0;
47:     if(sb->wanted) {
48:         sb->wanted = 0;
49:         wakeup(&superblock_lock);
50:     }
51:     RESTORE_FLAGS(flags);
52: }
53:
54: struct mount * get_free_mount_point(__dev_t dev)
55: {
56:     unsigned long int flags;
57:     int n;
58:
59:     if(!dev) {
60:         printk("%s(): invalid device %d,%d.\n", __FUNCTION__, MAJOR(dev)
, MINOR(dev));
61:         return NULL;
62:     }
63:
64:     for(n = 0; n < NR_MOUNT_POINTS; n++) {
65:         if(mount_table[n].dev == dev) {
66:             printk("%s(): device %d,%d already mounted.\n", __FUNCTI

```

```

ON__, MAJOR(dev), MINOR(dev));
67:         return NULL;
68:     }
69: }
70:
71:     SAVE_FLAGS(flags); CLI();
72:     for(n = 0; n < NR_MOUNT_POINTS; n++) {
73:         if(!mount_table[n].used) {
74:             /* 'dev' is saved here now for get_superblock() (which
75:              * in turn is called by read_inode(), which in turn is
76:              * called by iget(), which in turn is called by
77:              * read_superblock) to be able to find the device.
78:              */
79:             mount_table[n].dev = dev;
80:             mount_table[n].used = 1;
81:             RESTORE_FLAGS(flags);
82:             return &mount_table[n];
83:         }
84:     }
85:     RESTORE_FLAGS(flags);
86:
87:     printk("WARNING: %s(): mount-point table is full.\n", __FUNCTION__);
88:     return NULL;
89: }
90:
91: void release_mount_point(struct mount *mt)
92: {
93:     memset_b(mt, NULL, sizeof(struct mount));
94: }
95:
96: struct mount * get_mount_point(struct inode *i_target)
97: {
98:     int n;
99:
100:    for(n = 0; n < NR_MOUNT_POINTS; n++) {
101:        if(mount_table[n].used) {
102:            if(S_ISDIR(i_target->i_mode)) {
103:                if(mount_table[n].sb.root == i_target) {
104:                    return &mount_table[n];
105:                }
106:            }
107:            if(S_ISBLK(i_target->i_mode)) {
108:                if(mount_table[n].dev == i_target->rdev) {
109:                    return &mount_table[n];
110:                }
111:            }
112:        }
113:    }
114:    return NULL;
115: }
116:
117: struct superblock * get_superblock(__dev_t dev)
118: {
119:     int n;
120:
121:     for(n = 0; n < NR_MOUNT_POINTS; n++) {
122:         if(mount_table[n].used && mount_table[n].dev == dev) {
123:             return &mount_table[n].sb;
124:         }
125:     }
126:     return NULL;
127: }
128:
129: void sync_superblocks(__dev_t dev)
130: {
131:     struct superblock *sb;
132:     int n, errno;

```

```

133:
134:     lock_resource(&sync_resource);
135:     for(n = 0; n < NR_MOUNT_POINTS; n++) {
136:         if(mount_table[n].used && (!dev || mount_table[n].dev == dev)) {
137:             sb = &mount_table[n].sb;
138:             if(sb->dirty && !(sb->flags & MS_RDONLY)) {
139:                 if(sb->fsop && sb->fsop->write_superblock) {
140:                     errno = sb->fsop->write_superblock(sb);
141:                     if(errno) {
142:                         printk("WARNING: %s(): I/O error
on device %d,%d while syncing superblock.\n", __FUNCTION__, MAJOR(sb->dev), MINOR(sb->
dev));
143:                     }
144:                 }
145:             }
146:         }
147:     }
148:     unlock_resource(&sync_resource);
149: }
150:
151: /* pseudo-file systems are only mountable by the kernel */
152: int kern_mount(__dev_t dev, struct filesystems *fs)
153: {
154:     struct mount *mt;
155:
156:     if(!(mt = get_free_mount_point(dev))) {
157:         return -EBUSY;
158:     }
159:
160:     if(fs->fsop->read_superblock(dev, &mt->sb)) {
161:         release_mount_point(mt);
162:         return -EINVAL;
163:     }
164:
165:     mt->dev = dev;
166:     strcpy(mt->devname, "none");
167:     strcpy(mt->dirname, "none");
168:     mt->sb.dir = NULL;
169:     mt->fs = fs;
170:     fs->mt = mt;
171:     return 0;
172: }
173:
174: int mount_root(void)
175: {
176:     struct filesystems *fs;
177:     struct mount *mt;
178:
179:     /* FIXME: before trying to mount the filesystem, we should first
180:      * check if '_rootdev' is a device successfully registered.
181:      */
182:
183:     if(!(fs = get_filesystem(_rootfstype))) {
184:         printk("WARNING: %s(): '%s' is not a registered filesystem. Defa
ulting to 'minix'.\n", __FUNCTION__, _rootfstype);
185:         if(!(fs = get_filesystem("minix"))) {
186:             PANIC("minix filesystem is not registered!\n");
187:         }
188:     }
189:
190:     if(!(mt = get_free_mount_point(_rootdev))) {
191:         PANIC("unable to get a free mount point.\n");
192:     }
193:
194:     mt->sb.flags = MS_RDONLY;
195:     if(fs->fsop && fs->fsop->read_superblock) {
196:         if(fs->fsop->read_superblock(_rootdev, &mt->sb)) {

```

fs/super.c

Page 4/4

```
197:                                PANIC("unable to mount root filesystem on %s.\n", _rootd
evname);
198:                                }
199:                                }
200:
201:                                strcpy(mt->devname, "/dev/root");
202:                                strcpy(mt->dirname, "/");
203:                                mt->dev = _rootdev;
204:                                mt->sb.root->mount_point = mt->sb.root;
205:                                mt->sb.root->count++;
206:                                mt->sb.dir = mt->sb.root;
207:                                mt->sb.dir->count++;
208:                                mt->fs = fs;
209:
210:                                current->root = mt->sb.root;
211:                                current->root->count++;
212:                                current->pwd = mt->sb.root;
213:                                current->pwd->count++;
214:                                iput(mt->sb.root);
215:
216:                                printk("mounted root device (%s filesystem) in readonly mode.\n", fs->na
me);
217:                                return 0;
218:                                }
219:
220: void mount_init(void)
221: {
222:     memset_b(mount_table, NULL, mount_table_size);
223: }
```

fs/ext2/dir.c

Page 1/3

```

1: /*
2:  * fiwix/fs/ext2/dir.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/errno.h>
10: #include <fiwix/buffer.h>
11: #include <fiwix/fs.h>
12: #include <fiwix/filesystems.h>
13: #include <fiwix/stat.h>
14: #include <fiwix/dirent.h>
15: #include <fiwix/mm.h>
16: #include <fiwix/stdio.h>
17: #include <fiwix/string.h>
18:
19: struct fs_operations ext2_dir_fsop = {
20:     0,
21:     0,
22:
23:     ext2_dir_open,
24:     ext2_dir_close,
25:     ext2_dir_read,
26:     NULL, /* write */
27:     NULL, /* ioctl */
28:     NULL, /* lseek */
29:     ext2_dir_readdir,
30:     NULL, /* mmap */
31:     NULL, /* select */
32:
33:     NULL, /* readlink */
34:     NULL, /* followlink */
35:     ext2_bmap,
36:     ext2_lookup,
37:     NULL, /* rmdir */
38:     NULL, /* link */
39:     NULL, /* unlink */
40:     NULL, /* symlink */
41:     NULL, /* mkdir */
42:     NULL, /* mknod */
43:     NULL, /* truncate */
44:     NULL, /* create */
45:     NULL, /* rename */
46:
47:     NULL, /* read_block */
48:     NULL, /* write_block */
49:
50:     NULL, /* read_inode */
51:     NULL, /* write_inode */
52:     NULL, /* ialloc */
53:     NULL, /* ifree */
54:     NULL, /* statfs */
55:     NULL, /* read_superblock */
56:     NULL, /* remount_fs */
57:     NULL, /* write_superblock */
58:     NULL, /* release_superblock */
59: };
60:
61: int ext2_dir_open(struct inode *i, struct fd *fd_table)
62: {
63:     fd_table->offset = 0;
64:     return 0;
65: }
66:
67: int ext2_dir_close(struct inode *i, struct fd *fd_table)

```

```

68: {
69:     return 0;
70: }
71:
72: int ext2_dir_read(struct inode *i, struct fd *fd_table, char *buffer, __size_t c
ount)
73: {
74:     return -EISDIR;
75: }
76:
77: int ext2_dir_readdir(struct inode *i, struct fd *fd_table, struct dirent *dirent
, unsigned int count)
78: {
79:     __blk_t block;
80:     unsigned int doffset, offset;
81:     unsigned int size, dirent_len;
82:     struct ext2_dir_entry_2 *d;
83:     int base_dirent_len;
84:     int blksize;
85:     struct buffer *buf;
86:
87:     if(!(S_ISDIR(i->i_mode))) {
88:         return -EBADF;
89:     }
90:
91:     blksize = i->sb->s_blocksize;
92:     if(fd_table->offset > i->i_size) {
93:         fd_table->offset = i->i_size;
94:     }
95:
96:     base_dirent_len = sizeof(dirent->d_ino) + sizeof(dirent->d_off) + sizeof
(dirent->d_reclen);
97:     doffset = offset = size = 0;
98:
99:     while(doffset < count) {
100:         if((block = bmap(i, fd_table->offset, FOR_READING)) < 0) {
101:             return block;
102:         }
103:         if(block) {
104:             if(!(buf = bread(i->dev, block, blksize))) {
105:                 return -EIO;
106:             }
107:
108:             doffset = fd_table->offset;
109:             offset = fd_table->offset % blksize;
110:             while(doffset < i->i_size && offset < blksize) {
111:                 d = (struct ext2_dir_entry_2 *) (buf->data + offs
et);
112:                 if(d->inode) {
113:                     dirent_len = (base_dirent_len + (d->name
_len + 1)) + 3;
114:                     dirent_len &= ~3; /* round up */
115:                     dirent->d_ino = d->inode;
116:                     if((size + dirent_len) < count) {
117:                         dirent->d_off = doffset;
118:                         dirent->d_reclen = dirent_len;
119:                         memcpy_b(dirent->d_name, d->name
, d->name_len);
120:                         dirent->d_name[d->name_len] = NU
LL;
121:                         dirent = (struct dirent *) ((char
*)dirent + dirent_len);
122:                         size += dirent_len;
123:                     } else {
124:                         break;
125:                     }
126:                 }

```

```
127:                doffset += d->rec_len;
128:                offset += d->rec_len;
129:                if(!d->rec_len) {
130:                    break;
131:                }
132:            }
133:            brelse(buf);
134:        }
135:        fd_table->offset &= ~(blksize - 1);
136:        doffset = fd_table->offset;
137:        fd_table->offset += offset;
138:        doffset += blksize;
139:    }
140:
141:    return size;
142: }
```

fs/ext2/file.c

Page 1/2

```

1: /*
2:  * fiwix/fs/ext2/file.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/errno.h>
10: #include <fiwix/buffer.h>
11: #include <fiwix/fs.h>
12: #include <fiwix/filesystems.h>
13: #include <fiwix/mm.h>
14: #include <fiwix/mman.h>
15: #include <fiwix/fcntl.h>
16: #include <fiwix/stdio.h>
17: #include <fiwix/string.h>
18:
19: struct fs_operations ext2_file_fsop = {
20:     0,
21:     0,
22:
23:     ext2_file_open,
24:     ext2_file_close,
25:     file_read,
26:     NULL, /* write */
27:     NULL, /* ioctl */
28:     ext2_file_lseek,
29:     NULL, /* readdir */
30:     NULL, /* mmap */
31:     NULL, /* select */
32:
33:     NULL, /* readlink */
34:     NULL, /* followlink */
35:     ext2_bmap,
36:     NULL, /* lookup */
37:     NULL, /* rmdir */
38:     NULL, /* link */
39:     NULL, /* unlink */
40:     NULL, /* symlink */
41:     NULL, /* mkdir */
42:     NULL, /* mknod */
43:     NULL, /* truncate */
44:     NULL, /* create */
45:     NULL, /* rename */
46:
47:     NULL, /* read_block */
48:     NULL, /* write_block */
49:
50:     NULL, /* read_inode */
51:     NULL, /* write_inode */
52:     NULL, /* ialloc */
53:     NULL, /* ifree */
54:     NULL, /* statfs */
55:     NULL, /* read_superblock */
56:     NULL, /* remount_fs */
57:     NULL, /* write_superblock */
58:     NULL, /* release_superblock */
59: };
60:
61: int ext2_file_open(struct inode *i, struct fd *fd_table)
62: {
63:     if(fd_table->flags & (O_WRONLY | O_RDWR | O_TRUNC | O_APPEND)) {
64:         return -ENOENT;
65:     }
66:     fd_table->offset = 0;
67:     return 0;

```


fs/ext2/file.c

Page 2/2

```
68: }
69:
70: int ext2_file_close(struct inode *i, struct fd *fd_table)
71: {
72:     return 0;
73: }
74:
75: int ext2_file_lseek(struct inode *i, __off_t offset)
76: {
77:     return offset;
78: }
```

fs/ext2/inode.c

Page 1/4

```

1:  /*
2:  *  fiwix/fs/ext2/inode.c
3:  *
4:  *  Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  *  Distributed under the terms of the Fiwix License.
6:  */
7:
8:  #include <fiwix/kernel.h>
9:  #include <fiwix/fs.h>
10: #include <fiwix/filesystems.h>
11: #include <fiwix/fs_ext2.h>
12: #include <fiwix/fs_pipe.h>
13: #include <fiwix/statfs.h>
14: #include <fiwix/sleep.h>
15: #include <fiwix/stat.h>
16: #include <fiwix/sched.h>
17: #include <fiwix/buffer.h>
18: #include <fiwix/mm.h>
19: #include <fiwix/process.h>
20: #include <fiwix/errno.h>
21: #include <fiwix/stdio.h>
22: #include <fiwix/string.h>
23:
24: #define BLOCKS_PER_IND_BLOCK(sb)          (EXT2_BLOCK_SIZE(sb) / sizeof(unsigned i
nt))
25: #define BLOCKS_PER_DIND_BLOCK(sb)        (BLOCKS_PER_IND_BLOCK(sb) * BLOCKS_PER_I
ND_BLOCK(sb))
26: #define BLOCKS_PER_TIND_BLOCK(sb)        (BLOCKS_PER_IND_BLOCK(sb) * BLOCKS_PER_I
ND_BLOCK(sb) * BLOCKS_PER_IND_BLOCK(sb))
27:
28: #define EXT2_INODES_PER_BLOCK(sb)        (EXT2_BLOCK_SIZE(sb) / sizeof(struct ext
2_inode))
29:
30: static int get_group_desc(struct inode *i, struct superblock *sb, struct ext2_gr
oup_desc *gd)
31: {
32:     int block_group;
33:     int desc_per_block, group_desc_block, group_desc;
34:     struct buffer *buf;
35:
36:     block_group = ((i->inode - 1) / sb->u.ext2.s_inodes_per_group);
37:     desc_per_block = sb->s_blocksize / sizeof(struct ext2_group_desc);
38:     group_desc_block = block_group / desc_per_block;
39:     group_desc = block_group % desc_per_block;
40:     if(!(buf = bread(i->dev, SUPERBLOCK + sb->u.ext2.s_first_data_block + gr
oup_desc_block, i->sb->s_blocksize))) {
41:         return -EIO;
42:     }
43:     memcpy_b(gd, (void *) (buf->data + (group_desc * sizeof(struct ext2_group
_desc))), sizeof(struct ext2_group_desc));
44:     brelse(buf);
45:     return 0;
46: }
47:
48: int ext2_read_inode(struct inode *i)
49: {
50:     __ino_t block;
51:     unsigned int offset;
52:     struct superblock *sb;
53:     struct ext2_inode *ii;
54:     struct ext2_group_desc gd;
55:     struct buffer *buf;
56:
57:     if(!(sb = get_superblock(i->dev))) {
58:         printk("WARNING: %s(): get_superblock() has returned NULL.\n");
59:         return -EINVAL;
60:     }

```

fs/ext2/inode.c

Page 2/4

```

61:         if(get_group_desc(i, sb, &gd)) {
62:             return -EIO;
63:         }
64:         block = (((i->inode - 1) % sb->u.ext2.s_inodes_per_group) / EXT2_INODES_
PER_BLOCK(sb));
65:
66:         if(!(buf = bread(i->dev, gd.bg_inode_table + block, i->sb->s_blocksize))
) {
67:             return -EIO;
68:         }
69:         offset = (((i->inode - 1) % sb->u.ext2.s_inodes_per_group) % EXT2_INODE
S_PER_BLOCK(sb)) * sizeof(struct ext2_inode);
70:
71:         ii = (struct ext2_inode *)(buf->data + offset);
72:         memcpy_b(&i->u.ext2.i_block, ii->i_block, sizeof(ii->i_block));
73:
74:         i->i_mode = ii->i_mode;
75:         i->i_uid = ii->i_uid;
76:         i->i_size = ii->i_size;
77:         i->i_atime = ii->i_atime;
78:         i->i_ctime = ii->i_ctime;
79:         i->i_mtime = ii->i_mtime;
80:         i->i_gid = ii->i_gid;
81:         i->i_nlink = ii->i_links_count;
82:         i->i_blocks = ii->i_blocks;
83:         i->i_flags = ii->i_flags;
84:         i->count = 1;
85:         switch(i->i_mode & S_IFMT) {
86:             case S_IFCHR:
87:                 i->fsop = &def_chr_fsop;
88:                 i->rdev = ii->i_block[0];
89:                 break;
90:             case S_IFBLK:
91:                 i->fsop = &def_blk_fsop;
92:                 i->rdev = ii->i_block[0];
93:                 break;
94:             case S_IFIFO:
95:                 i->fsop = &pipefs_fsop;
96:                 /* it's a union so we need to clear pipefs_i */
97:                 memset_b(&i->u.pipefs, NULL, sizeof(struct pipefs_inode)
);
98:                 break;
99:             case S_IFDIR:
100:                 i->fsop = &ext2_dir_fsop;
101:                 break;
102:             case S_IFREG:
103:                 i->fsop = &ext2_file_fsop;
104:                 break;
105:             case S_IFLNK:
106:                 i->fsop = &ext2_symlink_fsop;
107:                 break;
108:             case S_IFSOCK:
109:                 i->fsop = NULL;
110:                 break;
111:             default:
112:                 printk("WARNING: %s(): invalid inode (%d) mode %08o.\n",
__FUNCTION__, i->inode, i->i_mode);
113:                 brelse(buf);
114:                 return -ENOENT;
115:         }
116:         brelse(buf);
117:         return 0;
118:     }
119:
120: int ext2_bmap(struct inode *i, __off_t offset, int mode)
121: {
122:     unsigned char level;

```

fs/ext2/inode.c

Page 3/4

```

123:     short int dind_block;
124:     __blk_t *indblock;
125:     __blk_t *dindblock;
126:     __blk_t block;
127:     struct buffer *buf;
128:
129:     block = offset / i->sb->s_blocksize;
130:     level = 0;
131:
132:     if(block < EXT2_NDIR_BLOCKS) {
133:         level = EXT2_NDIR_BLOCKS - 1;
134:     } else {
135:         if(block < (BLOCKS_PER_IND_BLOCK(i->sb) + EXT2_NDIR_BLOCKS)) {
136:             level = EXT2_IND_BLOCK;
137:             block -= EXT2_NDIR_BLOCKS;
138:         } else {
139:             if(block < BLOCKS_PER_DIND_BLOCK(i->sb)) {
140:                 level = EXT2_DIND_BLOCK;
141:                 block -= EXT2_NDIR_BLOCKS;
142:                 block -= BLOCKS_PER_IND_BLOCK(i->sb);
143:             } else {
144:                 level = EXT2_TIND_BLOCK;
145:                 block = 0;
146:             }
147:         }
148:     }
149:
150:     if(level == EXT2_TIND_BLOCK) {
151:         printk("(level = %d) (offset = %d) (block = %d)\n", level, offset,
t, block);
152:         printk("WARNING: triple-indirect blocks are not supported!\n");
153:         return -EINVAL;
154:     }
155:
156:     if(level < EXT2_NDIR_BLOCKS) {
157:         return i->u.ext2.i_block[block];
158:     }
159:
160:     if(!(indblock = (void *)kmallocc())) {
161:         printk("%s(): returning -ENOMEM.\n", __FUNCTION__);
162:         return -ENOMEM;
163:     }
164:     if(i->u.ext2.i_block[level] == 0) {
165:         printk("WARNING: %s(): will return 0 as an indirect block reques
t! (inode %d).\n", __FUNCTION__, i->inode);
166:         kfree((unsigned int)indblock);
167:         return 0;
168:     }
169:     if(!(buf = bread(i->dev, i->u.ext2.i_block[level], i->sb->s_blocksize)))
{
170:         kfree((unsigned int)indblock);
171:         printk("%s(): returning -EIO.\n", __FUNCTION__);
172:         return -EIO;
173:     }
174:     memcpy_l(indblock, buf->data, BLOCKS_PER_IND_BLOCK(i->sb));
175:     brelse(buf);
176:
177:     if(level == EXT2_IND_BLOCK) {
178:         kfree((unsigned int)indblock);
179:         return indblock[block];
180:     }
181:
182:     if(!(dindblock = (void *)kmallocc())) {
183:         kfree((unsigned int)indblock);
184:         printk("%s(): returning -ENOMEM.\n", __FUNCTION__);
185:         return -ENOMEM;
186:     }

```

fs/ext2/inode.c

Page 4/4

```
187:         dind_block = block / BLOCKS_PER_IND_BLOCK(i->sb);
188:         if(!(buf = bread(i->dev, indblock[dind_block], i->sb->s_blocksize))) {
189:             kfree((unsigned int)indblock);
190:             kfree((unsigned int)dindblock);
191:             printk("%s(): returning -EIO.\n", __FUNCTION__);
192:             return -EIO;
193:         }
194:         memcpy_l(dindblock, buf->data, BLOCKS_PER_IND_BLOCK(i->sb));
195:         brelse(buf);
196:         block = dindblock[block - (dind_block * BLOCKS_PER_IND_BLOCK(i->sb))];
197:         kfree((unsigned int)indblock);
198:         kfree((unsigned int)dindblock);
199:         return block;
200: }
```

fs/ext2/Makefile

Page 1/1

```
1: # fiwix/fs/ext2/Makefile
2: #
3: # Copyright 2018, Jordi Sanfeliu. All rights reserved.
4: # Distributed under the terms of the Fiwix License.
5: #
6: #
7: .S.o:
8:     $(CC) -traditional -I$(INCLUDE) -c -o $@ $<
9: .c.o:
10:     $(CC) $(CFLAGS) -c -o $@ $<
11:
12: OBJS = inode.o super.o namei.o symlink.o dir.o file.o
13:
14: ext2:    $(OBJS)
15:         $(LD) $(LDFLAGS) -r $(OBJS) -o ext2.o
16:
17: clean:
18:         rm -f *.o
19:
```

fs/ext2/namei.c

Page 1/2

```

1: /*
2:  * fiwix/fs/ext2/namei.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/filesystems.h>
11: #include <fiwix/fs_ext2.h>
12: #include <fiwix/buffer.h>
13: #include <fiwix/mm.h>
14: #include <fiwix/errno.h>
15: #include <fiwix/stdio.h>
16: #include <fiwix/string.h>
17:
18: int ext2_lookup(const char *name, struct inode *dir, struct inode **i_res)
19: {
20:     __blk_t block;
21:     unsigned int blksize;
22:     unsigned int offset, doffset;
23:     struct buffer *buf;
24:     struct ext2_dir_entry_2 *d;
25:     __ino_t inode;
26:
27:     blksize = dir->sb->s_blocksize;
28:     inode = offset = 0;
29:     dir->count++;
30:
31:     while(offset < dir->i_size && !inode) {
32:         if((block = bmap(dir, offset, FOR_READING)) < 0) {
33:             return block;
34:         }
35:         if(block) {
36:             if(!(buf = bread(dir->dev, block, blksize))) {
37:                 return -EIO;
38:             }
39:             doffset = 0;
40:             do {
41:                 d = (struct ext2_dir_entry_2 *) (buf->data + doff
set);
42:                 if(d->inode) {
43:                     if(d->name_len == strlen(name)) {
44:                         if(strncmp(d->name, name, d->nam
e_len) == 0) {
45:                             inode = d->inode;
46:                         }
47:                     }
48:                     doffset += d->rec_len;
49:                 } else {
50:                     doffset += sizeof(struct ext2_dir_entry_
2);
51:                 }
52:             } while((doffset < blksize) && (!inode));
53:
54:             brelse(buf);
55:             offset += blksize;
56:             if(inode) {
57:                 /*
58:                  * This prevents a deadlock in iget() when
59:                  * trying to lock '.' when 'dir' is the same
60:                  * directory (ls -lai <dir>).
61:                  */
62:                 if(inode == dir->inode) {
63:                     *i_res = dir;
64:                     return 0;

```

fs/ext2/namei.c

Page 2/2

```
65:                                     }
66:
67:                                     if(!(*i_res = iget(dir->sb, inode))) {
68:                                         return -EACCES;
69:                                     }
70:                                     iput(dir);
71:                                     return 0;
72:                                     }
73:                                     } else {
74:                                         break;
75:                                     }
76:                                     }
77:                                     iput(dir);
78:                                     return -ENOENT;
79: }
```


fs/ext2/super.c

Page 1/3

```

1: /*
2:  * fiwix/fs/ext2/super.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/types.h>
10: #include <fiwix/errno.h>
11: #include <fiwix/fs.h>
12: #include <fiwix/filesystems.h>
13: #include <fiwix/fs_ext2.h>
14: #include <fiwix/buffer.h>
15: #include <fiwix/sched.h>
16: #include <fiwix/stdio.h>
17: #include <fiwix/string.h>
18:
19: struct fs_operations ext2_fsop = {
20:     FSOP_REQUIRES_DEV,
21:     NULL,
22:
23:     NULL,          /* open */
24:     NULL,          /* close */
25:     NULL,          /* read */
26:     NULL,          /* write */
27:     NULL,          /* ioctl */
28:     NULL,          /* lseek */
29:     NULL,          /* readdir */
30:     NULL,          /* mmap */
31:     NULL,          /* select */
32:
33:     NULL,          /* readlink */
34:     NULL,          /* followlink */
35:     NULL,          /* bmap */
36:     NULL,          /* lookup */
37:     NULL,          /* rmdir */
38:     NULL,          /* link */
39:     NULL,          /* unlink */
40:     NULL,          /* symlink */
41:     NULL,          /* mkdir */
42:     NULL,          /* mknod */
43:     NULL,          /* truncate */
44:     NULL,          /* create */
45:     NULL,          /* rename */
46:
47:     NULL,          /* read_block */
48:     NULL,          /* write_block */
49:
50:     ext2_read_inode,
51:     NULL,          /* write_inode */
52:     NULL,          /* ialloc */
53:     NULL,          /* ifree */
54:     ext2_statfs,
55:     ext2_read_superblock,
56:     NULL,          /* remount_fs */
57:     NULL,          /* write_superblock */
58:     NULL,          /* release_superblock */
59: };
60:
61: static void check_superblock(struct ext2_super_block *sb)
62: {
63:     if(!(sb->s_state & EXT2_VALID_FS)) {
64:         printk("WARNING: filesystem unchecked, fsck recommended.\n");
65:     } else if((sb->s_state & EXT2_ERROR_FS)) {
66:         printk("WARNING: filesystem contains errors, fsck recommended.\n
");

```

fs/ext2/super.c

Page 2/3

```

67:         } else if(sb->s_max_mnt_count >= 0 && sb->s_mnt_count >= (unsigned short
int)sb->s_max_mnt_count) {
68:             printk("WARNING: maximal mount count reached, fsck recommended.\n
n");
69:         } else if(sb->s_checkinterval && (sb->s_lastcheck + sb->s_checkinterval
<= CURRENT_TIME)) {
70:             printk("WARNING: checktime reached, fsck recommended.\n");
71:         }
72:     }
73: }
74: void ext2_statfs(struct superblock *sb, struct statfs *statfsbuf)
75: {
76:     statfsbuf->f_type = EXT2_SUPER_MAGIC;
77:     statfsbuf->f_bsize = sb->s_blocksize;
78:     statfsbuf->f_blocks = sb->u.ext2.s_blocks_count;
79:     statfsbuf->f_bfree = sb->u.ext2.s_free_blocks_count;
80:     if(statfsbuf->f_bfree >= sb->u.ext2.s_r_blocks_count) {
81:         statfsbuf->f_bavail = statfsbuf->f_bfree - sb->u.ext2.s_r_blocks
_count;
82:     } else {
83:         statfsbuf->f_bavail = 0;
84:     }
85:     statfsbuf->f_files = sb->u.ext2.s_inodes_count;
86:     statfsbuf->f_ffree = sb->u.ext2.s_free_inodes_count;
87:     /* statfsbuf->f_fsid = ? */
88:     statfsbuf->f_namelen = EXT2_NAME_LEN;
89: }
90:
91: int ext2_read_superblock(__dev_t dev, struct superblock *sb)
92: {
93:     struct buffer *buf;
94:     struct ext2_super_block *ext2sb;
95:
96:     superblock_lock(sb);
97:     if(!(buf = bread(dev, SUPERBLOCK, BLKSIZE_1K))) {
98:         superblock_unlock(sb);
99:         return -EIO;
100:    }
101:
102:    ext2sb = (struct ext2_super_block *)buf->data;
103:    if(ext2sb->s_magic != EXT2_SUPER_MAGIC) {
104:        printk("WARNING: %s(): invalid filesystem type or bad superblock
on device %d,%d.\n", __FUNCTION__, MAJOR(dev), MINOR(dev));
105:        superblock_unlock(sb);
106:        brelse(buf);
107:        return -EINVAL;
108:    }
109:
110:    /* sparse-superblock feature not supported (only for read-write mode) */
111:    if(!sb->flags & MS_RDONLY) {
112:        if(ext2sb->s_feature_ro_compat & EXT2_FEATURE_RO_COMPAT_SPARSE_S
UPER) {
113:            printk("WARNING: %s(): sparse-superblock feature is not
supported.\n", __FUNCTION__);
114:            printk("filesystem structure not supported. Try with '-o
ro'.\n");
115:            superblock_unlock(sb);
116:            brelse(buf);
117:            return -EINVAL;
118:        }
119:    }
120:
121:    sb->dev = dev;
122:    sb->fsop = &ext2_fsop;
123:    sb->s_blocksize = EXT2_MIN_BLOCK_SIZE << ext2sb->s_log_block_size;
124:    memcpy_b(&sb->u.ext2, ext2sb, sizeof(struct ext2_super_block));
125:

```

fs/ext2/super.c

Page 3/3

```
126:         if(!(sb->root = iget(sb, EXT2_ROOT_INO))) {
127:             printk("WARNING: %s(): unable to get root inode.\n", __FUNCTION_
_);
128:             superblock_unlock(sb);
129:             brelse(buf);
130:             return -EINVAL;
131:         }
132:
133:         superblock_unlock(sb);
134:         check_superblock(ext2sb);
135:         brelse(buf);
136:         return 0;
137:     }
138:
139: int ext2_init(void)
140: {
141:     return register_filesystem("ext2", &ext2_fsop);
142: }
```

fs/ext2/symlink.c

Page 1/3

```

1: /*
2:  * fiwix/fs/ext2/symlink.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/errno.h>
10: #include <fiwix/buffer.h>
11: #include <fiwix/fs.h>
12: #include <fiwix/filesystems.h>
13: #include <fiwix/stat.h>
14: #include <fiwix/mm.h>
15: #include <fiwix/stdio.h>
16: #include <fiwix/string.h>
17:
18: struct fs_operations ext2_symlink_fsop = {
19:     0,
20:     0,
21:
22:     NULL,          /* open */
23:     NULL,          /* close */
24:     NULL,          /* read */
25:     NULL,          /* write */
26:     NULL,          /* ioctl */
27:     NULL,          /* lseek */
28:     NULL,          /* readdir */
29:     NULL,          /* mmap */
30:     NULL,          /* select */
31:
32:     ext2_readlink,
33:     ext2_followlink,
34:     NULL,          /* bmap */
35:     NULL,          /* lookup */
36:     NULL,          /* rmdir */
37:     NULL,          /* link */
38:     NULL,          /* unlink */
39:     NULL,          /* symlink */
40:     NULL,          /* mkdir */
41:     NULL,          /* mknod */
42:     NULL,          /* truncate */
43:     NULL,          /* create */
44:     NULL,          /* rename */
45:
46:     NULL,          /* read_block */
47:     NULL,          /* write_block */
48:
49:     NULL,          /* read_inode */
50:     NULL,          /* write_inode */
51:     NULL,          /* ialloc */
52:     NULL,          /* ifree */
53:     NULL,          /* statfs */
54:     NULL,          /* read_superblock */
55:     NULL,          /* remount_fs */
56:     NULL,          /* write_superblock */
57:     NULL,          /* release_superblock */
58: };
59:
60: int ext2_readlink(struct inode *i, char *buffer, __size_t count)
61: {
62:     __u32 blksize;
63:     struct buffer *buf;
64:
65:     if(!S_ISLNK(i->i_mode)) {
66:         printk("%s(): Oops, inode '%d' is not a symlink (!?)\n", __FUNC
TION__, i->inode);

```

fs/ext2/symlink.c

Page 2/3

```

67:         return 0;
68:     }
69:
70:     inode_lock(i);
71:     blksize = i->sb->s_blocksize;
72:     count = MIN(count, i->i_size);
73:     if(!count) {
74:         inode_unlock(i);
75:         return 0;
76:     }
77:     count = MIN(count, blksize);
78:     if(i->i_blocks) { /* slow symlink */
79:         if(!(buf = bread(i->dev, i->u.ext2.i_block[0], blksize))) {
80:             inode_unlock(i);
81:             return -EIO;
82:         }
83:         memcpy_b(buffer, buf->data, count);
84:         brelse(buf);
85:     } else { /* fast symlink */
86:         memcpy_b(buffer, (char *)i->u.ext2.i_block, count);
87:     }
88:     buffer[count] = NULL;
89:     inode_unlock(i);
90:     return count;
91: }
92:
93: int ext2_followlink(struct inode *dir, struct inode *i, struct inode **i_res)
94: {
95:     struct buffer *buf;
96:     char *name;
97:     __ino_t errno;
98:
99:     if(!i) {
100:         return -ENOENT;
101:     }
102:
103:     if(!S_ISLNK(i->i_mode)) {
104:         printk("%s(): Oops, inode '%d' is not a symlink (!?).\n", __FUNC
TION__, i->inode);
105:         return 0;
106:     }
107:
108:     if(current->loopcnt > MAX_SYMLINKS) {
109:         printk("%s(): too many nested symbolic links!\n", __FUNCTION__);
110:         return -ELOOP;
111:     }
112:
113:     inode_lock(i);
114:     if(i->i_blocks) { /* slow symlink */
115:         if(!(buf = bread(i->dev, i->u.ext2.i_block[0], i->sb->s_blocksiz
e))) {
116:             inode_unlock(i);
117:             return -EIO;
118:         }
119:         name = buf->data;
120:     } else { /* fast symlink */
121:         buf = NULL;
122:         name = (char *)i->u.ext2.i_block;
123:     }
124:     inode_unlock(i);
125:
126:     current->loopcnt++;
127:     iput(i);
128:     if(buf) {
129:         brelse(buf);
130:     }
131:     errno = parse_namei(name, dir, i_res, NULL, FOLLOW_LINKS);

```

fs/ext2/symlink.c

Page 3/3

```
132:         current->loopcnt--;  
133:         return errno;  
134:     }
```

fs/iso9660/dir.c

Page 1/3

```

1: /*
2:  * fiwix/fs/iso9660/dir.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/errno.h>
10: #include <fiwix/buffer.h>
11: #include <fiwix/fs.h>
12: #include <fiwix/filesystems.h>
13: #include <fiwix/stat.h>
14: #include <fiwix/dirent.h>
15: #include <fiwix/stdio.h>
16: #include <fiwix/string.h>
17:
18: struct fs_operations iso9660_dir_fsop = {
19:     0,
20:     0,
21:
22:     iso9660_dir_open,
23:     iso9660_dir_close,
24:     iso9660_dir_read,
25:     NULL, /* write */
26:     NULL, /* ioctl */
27:     NULL, /* lseek */
28:     iso9660_dir_readdir,
29:     NULL, /* mmap */
30:     NULL, /* select */
31:
32:     NULL, /* readlink */
33:     NULL, /* followlink */
34:     iso9660_bmap,
35:     iso9660_lookup,
36:     NULL, /* rmdir */
37:     NULL, /* link */
38:     NULL, /* unlink */
39:     NULL, /* symlink */
40:     NULL, /* mkdir */
41:     NULL, /* mknod */
42:     NULL, /* truncate */
43:     NULL, /* create */
44:     NULL, /* rename */
45:
46:     NULL, /* read_block */
47:     NULL, /* write_block */
48:
49:     NULL, /* read_inode */
50:     NULL, /* write_inode */
51:     NULL, /* ialloc */
52:     NULL, /* ifree */
53:     NULL, /* statsfs */
54:     NULL, /* read_superblock */
55:     NULL, /* remount_fs */
56:     NULL, /* write_superblock */
57:     NULL, /* release_superblock */
58: };
59:
60: int iso9660_dir_open(struct inode *i, struct fd *fd_table)
61: {
62:     fd_table->offset = 0;
63:     return 0;
64: }
65:
66: int iso9660_dir_close(struct inode *i, struct fd *fd_table)
67: {

```

fs/iso9660/dir.c

Page 2/3

```

68:         return 0;
69:     }
70:
71: int iso9660_dir_read(struct inode *i, struct fd *fd_table, char *buffer, __size_
t count)
72: {
73:     return -EISDIR;
74: }
75:
76: int iso9660_dir_readdir(struct inode *i, struct fd *fd_table, struct dirent *dir
ent, unsigned int count)
77: {
78:     __blk_t block;
79:     unsigned int doffset, offset;
80:     unsigned int size, dirent_len;
81:     struct iso9660_directory_record *d;
82:     int base_dirent_len;
83:     int blksize;
84:     struct buffer *buf;
85:     int nm_len;
86:     char nm_name[NAME_MAX + 1];
87:
88:     if(!(S_ISDIR(i->i_mode))) {
89:         return -EBADF;
90:     }
91:
92:     blksize = i->sb->s_blocksize;
93:     if(fd_table->offset > i->i_size) {
94:         fd_table->offset = i->i_size;
95:     }
96:
97:     base_dirent_len = sizeof(dirent->d_ino) + sizeof(dirent->d_off) + sizeof
(dirent->d_reclen);
98:     doffset = offset = size = 0;
99:
100:    while(doffset < count) {
101:        if((block = bmap(i, fd_table->offset, FOR_READING)) < 0) {
102:            return block;
103:        }
104:        if(block) {
105:            if(!(buf = bread(i->dev, block, blksize))) {
106:                return -EIO;
107:            }
108:
109:            doffset = fd_table->offset;
110:            offset = fd_table->offset % blksize;
111:
112:            while(doffset < i->i_size && offset < blksize) {
113:                d = (struct iso9660_directory_record *) (buf->dat
a + offset);
114:                if(isonum_711(d->length)) {
115:                    dirent_len = (base_dirent_len + (isonum_
711(d->name_len) + 1)) + 3;
116:                    dirent_len &= ~3;          /* round up */
117:                    if((size + isonum_711(d->length)) < coun
t) {
118:                        dirent->d_ino = (block << ISO966
0_INODE_BITS) + (doffset & ISO9660_INODE_MASK);
119:                        dirent->d_off = doffset;
120:                        dirent->d_reclen = dirent_len;
121:                        if(isonum_711(d->name_len) == 1
&& d->name[0] == 0) {
122:                            dirent->d_name[0] = '.';
123:                            dirent->d_name[1] = NULL
;
124:                        } else if(isonum_711(d->name_len
) == 1 && d->name[0] == 1) {

```


fs/iso9660/dir.c

Page 3/3

```

125:                                dirent->d_name[0] = '.';
126:                                dirent->d_name[1] = '.';
127:                                dirent->d_name[2] = NULL;
;
128:                                dirent_len = 16;
129:                                dirent->d_reclen = 16;
130:                                if(i->u.iso9660.i_parent
) {
131:                                dirent->d_ino =
i->u.iso9660.i_parent->inode;
132:                                } else {
133:                                dirent->d_ino =
i->inode;
134:                                }
135:                                } else {
136:                                nm_len = 0;
137:                                if(i->sb->u.iso9660.rrip
) {
138:                                nm_len = get_rri
p_filename(d, i, nm_name);
139:                                }
140:                                if(nm_len) {
141:                                memcpy_b(dirent-
>d_name, nm_name, nm_len);
142:                                dirent->d_name[n
m_len] = NULL;
143:                                dirent->d_reclen
= (base_dirent_len + nm_len + 1) + 3;
144:                                dirent->d_reclen
&= ~3; /* round up */
145:                                dirent_len = dir
ent->d_reclen;
146:                                } else {
147:                                memcpy_b(dirent-
>d_name, d->name, isonum_711(d->name_len));
148:                                dirent->d_name[i
sonum_711(d->name_len)] = NULL;
149:                                }
150:                                }
151:                                if(!((char)d->flags[0] & ISO9660
_FILE_ISDIR)) {
152:                                iso9660_cleanfilename(di
rent->d_name, isonum_711(d->name_len));
153:                                }
154:                                dirent = (struct dirent *)((char
*)dirent + dirent_len);
155:                                size += dirent_len;
156:                                } else {
157:                                break;
158:                                }
159:                                doffset += isonum_711(d->length);
160:                                offset += isonum_711(d->length);
161:                                } else {
162:                                break;
163:                                }
164:                                }
165:                                brelse(buf);
166:                                }
167:                                fd_table->offset &= ~(blksize - 1);
168:                                doffset = fd_table->offset;
169:                                doffset += blksize;
170:                                fd_table->offset += blksize;
171:                                }
172:                                return size;
173: }

```

fs/iso9660/file.c

Page 1/2

```

1: /*
2:  * fiwix/fs/iso9660/file.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/errno.h>
10: #include <fiwix/buffer.h>
11: #include <fiwix/fs.h>
12: #include <fiwix/filesystems.h>
13: #include <fiwix/mm.h>
14: #include <fiwix/mman.h>
15: #include <fiwix/fcntl.h>
16: #include <fiwix/stdio.h>
17: #include <fiwix/string.h>
18:
19: struct fs_operations iso9660_file_fsop = {
20:     0,
21:     0,
22:
23:     iso9660_file_open,
24:     iso9660_file_close,
25:     file_read,
26:     NULL,                /* write */
27:     NULL,                /* ioctl */
28:     iso9660_file_lseek,
29:     NULL,                /* readdir */
30:     NULL,                /* mmap */
31:     NULL,                /* select */
32:
33:     NULL,                /* readlink */
34:     NULL,                /* followlink */
35:     iso9660_bmap,
36:     NULL,                /* lookup */
37:     NULL,                /* rmdir */
38:     NULL,                /* link */
39:     NULL,                /* unlink */
40:     NULL,                /* symlink */
41:     NULL,                /* mkdir */
42:     NULL,                /* mknod */
43:     NULL,                /* truncate */
44:     NULL,                /* create */
45:     NULL,                /* rename */
46:
47:     NULL,                /* read_block */
48:     NULL,                /* write_block */
49:
50:     NULL,                /* read_inode */
51:     NULL,                /* write_inode */
52:     NULL,                /* ialloc */
53:     NULL,                /* ifree */
54:     NULL,                /* statfs */
55:     NULL,                /* read_superblock */
56:     NULL,                /* remount_fs */
57:     NULL,                /* write_superblock */
58:     NULL,                /* release_superblock */
59: };
60:
61: int iso9660_file_open(struct inode *i, struct fd *fd_table)
62: {
63:     if(fd_table->flags & (O_WRONLY | O_RDWR | O_TRUNC | O_APPEND)) {
64:         return -ENOENT;
65:     }
66:     fd_table->offset = 0;
67:     return 0;

```

fs/iso9660/file.c

Page 2/2

```
68: }
69:
70: int iso9660_file_close(struct inode *i, struct fd *fd_table)
71: {
72:     return 0;
73: }
74:
75: int iso9660_file_lseek(struct inode *i, __off_t offset)
76: {
77:     return offset;
78: }
```

fs/iso9660/inode.c

Page 1/3

```

1: /*
2:  * fiwix/fs/iso9660/inode.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/types.h>
10: #include <fiwix/errno.h>
11: #include <fiwix/fs.h>
12: #include <fiwix/filesystems.h>
13: #include <fiwix/fs_iso9660.h>
14: #include <fiwix/fs_pipe.h>
15: #include <fiwix/buffer.h>
16: #include <fiwix/stat.h>
17: #include <fiwix/mm.h>
18: #include <fiwix/sched.h>
19: #include <fiwix/stdio.h>
20: #include <fiwix/string.h>
21:
22: static int read_pathtable(struct inode *i)
23: {
24:     int n, offset, pt_len, pt_blk;
25:     struct iso9660_sb_info *sbi;
26:     struct iso9660_pathtable_record *ptr;
27:     struct buffer *buf;
28:
29:     sbi = (struct iso9660_sb_info *)&i->sb->u.iso9660;
30:     pt_len = isonum_733(sbi->sb->path_table_size);
31:     pt_blk = isonum_731(sbi->sb->type_l_path_table);
32:
33:     if(pt_len > PAGE_SIZE) {
34:         printk("WARNING: %s(): path table record size (%d) > 4096, not s
supported yet.\n", __FUNCTION__, pt_len);
35:         return -EINVAL;
36:     }
37:
38:     if(!(sbi->pathtable_raw = (void *)kmalloc())) {
39:         return -ENOMEM;
40:     }
41:     offset = 0;
42:     while(offset < pt_len) {
43:         if(!(buf = bread(i->dev, pt_blk++, BLKSIZE_2K))) {
44:             kfree((unsigned int)sbi->pathtable_raw);
45:             return -EIO;
46:         }
47:         memcpy_b(sbi->pathtable_raw + offset, (void *)buf->data, MIN(pt_
len - offset, BLKSIZE_2K));
48:         offset += MIN(pt_len - offset, BLKSIZE_2K);
49:         brelse(buf);
50:     }
51:
52:     /* allocate and count the number of records in the Path Table */
53:     offset = n = 0;
54:     if(!(sbi->pathtable = (struct iso9660_pathtable_record **)kmalloc())) {
55:         kfree((unsigned int)sbi->pathtable_raw);
56:         return -ENOMEM;
57:     }
58:     sbi->pathtable[n] = NULL;
59:     while(offset < pt_len) {
60:         ptr = (struct iso9660_pathtable_record *) (sbi->pathtable_raw + o
ffset);
61:         sbi->pathtable[++n] = ptr;
62:         offset += sizeof(struct iso9660_pathtable_record) + isonum_711(p
tr->length) + (isonum_711(ptr->length) & 1);
63:     }

```

fs/iso9660/inode.c

Page 2/3

```

64:         sbi->paths = n;
65:
66:         return 0;
67:     }
68:
69: static int get_parent_dir_size(struct superblock *sb, __blk_t extent)
70: {
71:     int n;
72:     struct iso9660_pathtable_record *ptr;
73:     __blk_t parent;
74:
75:     for(n = 0; n < sb->u.iso9660.paths; n++) {
76:         ptr = (struct iso9660_pathtable_record *)sb->u.iso9660.pathtable
[n];
77:         if(isonum_731(ptr->extent) == extent) {
78:
79:             parent = isonum_723(ptr->parent);
80:             ptr = (struct iso9660_pathtable_record *)sb->u.iso9660.p
athtable[parent];
81:             parent = isonum_731(ptr->extent);
82:             return parent;
83:         }
84:     }
85:     printk("WARNING: %s(): unable to locate extent '%d' in path table.\n", _
_FUNCTION__, extent);
86:     return 0;
87: }
88:
89: int iso9660_read_inode(struct inode *i)
90: {
91:     int errno;
92:     __u32 blksize;
93:     struct superblock *sb;
94:     struct iso9660_directory_record *d;
95:     struct buffer *buf;
96:     __blk_t dblock;
97:     __off_t doffset;
98:
99:     sb = (struct superblock *)i->sb;
100:    if(!sb->u.iso9660.pathtable) {
101:        if((errno = read_pathtable(i))) {
102:            return errno;
103:        }
104:    }
105:
106:    dblock = (i->inode & ~ISO9660_INODE_MASK) >> ISO9660_INODE_BITS;
107:    doffset = i->inode & ISO9660_INODE_MASK;
108:    blksize = i->sb->s_blocksize;
109:
110:    /* FIXME: it only looks in one directory block */
111:    if(!(buf = bread(i->dev, dblock, blksize))) {
112:        return -EIO;
113:    }
114:
115:    if(doffset >= blksize) {
116:        printk("WARNING: %s(): inode %d (dblock=%d, doffset=%d) not foun
d in directory entry.\n", _FUNCTION__, i->inode, dblock, doffset);
117:        brelse(buf);
118:        return -EIO;
119:    }
120:    d = (struct iso9660_directory_record *) (buf->data + doffset);
121:
122:    i->i_mode = S_IFREG;
123:    if((char)d->flags[0] & ISO9660_FILE_ISDIR) {
124:        i->i_mode = S_IFDIR;
125:    }
126:    if(!((char)d->flags[0] & ISO9660_FILE_HASOWNER)) {

```

fs/iso9660/inode.c

Page 3/3

```

127:             i->i_mode |= S_IRUSR | S_IXUSR | S_IRGRP | S_IXGRP | S_IROTH | S
_IXOTH;
128:         }
129:         i->i_uid = 0;
130:         i->i_size = isonum_733(d->size);
131:         i->i_atime = isodate(d->date);
132:         i->i_ctime = isodate(d->date);
133:         i->i_mtime = isodate(d->date);
134:         i->i_gid = 0;
135:         i->i_nlink = 1;
136:         i->i_blocks = 0;          /* FIXME */
137:         i->i_flags = 0;          /* FIXME */
138:         i->locked = 1;
139:         i->dirty = 0;
140:         i->mount_point = NULL;
141:         i->count = 1;
142:
143:         i->u.iso9660.i_extent = isonum_733(d->extent);
144:         check_rrip_inode(d, i);
145:         brelse(buf);
146:
147:         switch(i->i_mode & S_IFMT) {
148:             case S_IFCHR:
149:                 i->fsop = &def_chr_fsop;
150:                 break;
151:             case S_IFBLK:
152:                 i->fsop = &def_blk_fsop;
153:                 break;
154:             case S_IFIFO:
155:                 i->fsop = &pipefs_fsop;
156:                 /* it's a union so we need to clear pipefs_inode */
157:                 memset_b(&i->u.pipefs, NULL, sizeof(struct pipefs_inode)
);
158:                 break;
159:             case S_IFDIR:
160:                 i->fsop = &iso9660_dir_fsop;
161:                 i->i_nlink++;
162:                 break;
163:             case S_IFREG:
164:                 i->fsop = &iso9660_file_fsop;
165:                 break;
166:             case S_IFLNK:
167:                 i->fsop = &iso9660_symlink_fsop;
168:                 break;
169:             case S_IFSOCK:
170:                 i->fsop = NULL;
171:                 break;
172:             default:
173:                 PANIC("invalid inode (%d) mode %08o.\n", i->inode, i->i
mode);
174:         }
175:         return 0;
176:     }
177:
178: int iso9660_bmap(struct inode *i, __off_t offset, int mode)
179: {
180:     __blk_t block;
181:
182:     block = i->u.iso9660.i_extent + (offset / i->sb->s_blocksize);
183:     return block;
184: }

```

fs/iso9660/Makefile

Page 1/1

```
1: # fiwix/fs/iso9660/Makefile
2: #
3: # Copyright 2018, Jordi Sanfeliu. All rights reserved.
4: # Distributed under the terms of the Fiwix License.
5: #
6: #
7: .S.o:
8:     $(CC) -traditional -I$(INCLUDE) -c -o $@ $<
9: .c.o:
10:     $(CC) $(CFLAGS) -c -o $@ $<
11:
12: OBJS = inode.o super.o namei.o dir.o file.o rrip.o symlink.o
13:
14: iso9660:$(OBJS)
15:     $(LD) $(LDFLAGS) -r $(OBJS) -o iso9660.o
16:
17: clean:
18:     rm -f *.o
19:
```

fs/iso9660/namei.c

Page 1/3

```

1: /*
2:  * fiwix/fs/iso9660/namei.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/filesystems.h>
11: #include <fiwix/fs_iso9660.h>
12: #include <fiwix/buffer.h>
13: #include <fiwix/stat.h>
14: #include <fiwix/mm.h>
15: #include <fiwix/errno.h>
16: #include <fiwix/stdio.h>
17: #include <fiwix/string.h>
18:
19: int iso9660_lookup(const char *name, struct inode *dir, struct inode **i_res)
20: {
21:     __blk_t dblock;
22:     __u32 blksize;
23:     int len, dnlen;
24:     unsigned int offset, doffset;
25:     struct buffer *buf;
26:     struct iso9660_directory_record *d;
27:     __ino_t inode;
28:     int nm_len;
29:     char *nm_name;
30:
31:     blksize = dir->sb->s_blocksize;
32:     inode = offset = 0;
33:     len = strlen(name);
34:     dir->count++;
35:
36:     while(offset < dir->i_size && !inode) {
37:         if((dblock = bmap(dir, offset, FOR_READING)) < 0) {
38:             return dblock;
39:         }
40:         if(dblock) {
41:             if(!(buf = bread(dir->dev, dblock, blksize))) {
42:                 return -EIO;
43:             }
44:             doffset = 0;
45:             do {
46:                 d = (struct iso9660_directory_record *) (buf->data
a + doffset);
47:                 if(isonum_711(d->length) == 0) {
48:                     break;
49:                 }
50:                 if(len == 1) {
51:                     if(name[0] == '.' && name[1] == NULL) {
52:                         if(isonum_711(d->name_len) == 1
&& d->name[0] == 0) {
53:                             inode = dir->inode;
54:                         }
55:                     }
56:                 }
57:                 if(len == 2) {
58:                     if(name[0] == '.' && name[1] == '.' && n
ame[2] == NULL) {
59:                         if(isonum_711(d->name_len) == 1
&& d->name[0] == 1) {
60:                             inode = dir->u.iso9660.i
nfo->parent->inode;
61:                         }
62:                     }

```


fs/iso9660/namei.c

Page 2/3

```

63:         }
64:         if(!(nm_name = (char *)kmalloc())) {
65:             return -ENOMEM;
66:         }
67:         nm_len = 0;
68:         if(dir->sb->u.iso9660.rrip) {
69:             nm_len = get_rrip_filename(d, dir, nm_na
me);
70:         }
71:         if(nm_len) {
72:             dnlen = nm_len;
73:         } else {
74:             dnlen = isonum_711(d->name_len);
75:             if(!((char)d->flags[0] & ISO9660_FILE_IS
DIR)) {
76:                 iso9660_cleanfilename(d->name, d
nlen);
77:                 dnlen = strlen(d->name);
78:             }
79:         }
80:         if(len == dnlen) {
81:             if(nm_len) {
82:                 if(strncmp(nm_name, name, dnlen)
== 0) {
83:                     inode = (dblock << ISO96
60_INODE_BITS) + (doffset & ISO9660_INODE_MASK);
84:                 }
85:             } else {
86:                 if(strncmp(d->name, name, dnlen)
== 0) {
87:                     inode = (dblock << ISO96
60_INODE_BITS) + (doffset & ISO9660_INODE_MASK);
88:                 }
89:             }
90:         }
91:         kfree((unsigned int)nm_name);
92:         doffset += isonum_711(d->length);
93:     } while((doffset < blksize) && (!inode));
94:     brelse(buf);
95:     offset += blksize;
96:     if(inode) {
97:         /*
98:          * This prevents a deadlock in iget() when
99:          * trying to lock '.' when 'dir' is the same
100:          * directory (ls -lai <tmp>).
101:          */
102:         if(inode == dir->inode) {
103:             *i_res = dir;
104:             return 0;
105:         }
106:
107:         if(!(*i_res = iget(dir->sb, inode))) {
108:             return -EACCES;
109:         }
110:         if(S_ISDIR((*i_res)->i_mode)) {
111:             if(!(*i_res)->u.iso9660.i_parent) {
112:                 (*i_res)->u.iso9660.i_parent = d
ir;
113:             }
114:         }
115:         iput(dir);
116:         return 0;
117:     }
118: }
119: }
120: iput(dir);
121: return -ENOENT;

```

```
122: }
```

fs/iso9660/rrip.c

Page 1/6

```

1: /*
2:  * fiwix/fs/iso9660/rrip.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/errno.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/stat.h>
12: #include <fiwix/filesystems.h>
13: #include <fiwix/buffer.h>
14: #include <fiwix/fs_iso9660.h>
15: #include <fiwix/mm.h>
16: #include <fiwix/stdio.h>
17: #include <fiwix/string.h>
18:
19: void check_rrip_inode(struct iso9660_directory_record *d, struct inode *i)
20: {
21:     unsigned int total_len;
22:     unsigned int len;
23:     unsigned int sig;
24:     int n, nm_len, rootflag;
25:     struct susp_rrip *rrip;
26:     unsigned int dev_h, dev_l;
27:     unsigned int ce_block, ce_offset, ce_size;
28:     struct buffer *buf;
29:     unsigned char *sue;
30:     int sl_len;
31:     struct rrip_sl_component *slc;
32:
33:     ce_block = ce_offset = ce_size = 0;
34:     buf = NULL;
35:     total_len = isonum_711(d->length);
36:     len = isonum_711(d->name_len);
37:     if(!(len % 2)) {
38:         len++;
39:     }
40:     sue = (unsigned char *)d->name;
41:     nm_len = 0;
42:
43: loop:
44:     if(ce_block && ce_size) {
45:         /* FIXME: it only looks in one directory block */
46:         if(!(buf = bread(i->dev, ce_block, i->sb->s_blocksize))) {
47:             return;
48:         }
49:         sue = (unsigned char *)buf->data + ce_offset;
50:         total_len = ce_size;
51:         len = 0;
52:     }
53:
54:     while(len < total_len) {
55:         rrip = (struct susp_rrip *)(sue + len);
56:         if(rrip->len == 0) {
57:             break;
58:         }
59:         sig = GET_SIG(rrip->signature[0], rrip->signature[1]);
60:         switch(sig) {
61:             case GET_SIG('S', 'P'):
62:                 if(rrip->u.sp.magic[0] != SP_MAGIC1 || rrip->u.s
p.magic[1] != SP_MAGIC2) {
63:                     if(ce_block) {
64:                         brelse(buf);
65:                     }
66:                     return;

```

fs/iso9660/rrip.c

Page 2/6

```

67:         }
68:         break;
69:     case GET_SIG('C', 'E'):
70:         if(ce_block) {
71:             brelse(buf);
72:         }
73:         ce_block = isonum_733(rrip->u.ce.block);
74:         ce_offset = isonum_733(rrip->u.ce.offset);
75:         ce_size = isonum_733(rrip->u.ce.size);
76:         goto loop;
77:         break;
78:     case GET_SIG('E', 'R'):
79:         i->sb->u.iso9660.rrip = 1;
80:         printk("ISO 9660 Extensions: ");
81:         for(n = 0; n < rrip->u.er.len_id; n++) {
82:             printk("%c", rrip->u.er.data[n]);
83:         }
84:         printk("\n");
85:         break;
86:     case GET_SIG('P', 'X'):
87:         i->i_mode = isonum_733(rrip->u.px.mode);
88:         i->i_nlink = isonum_733(rrip->u.px.nlink);
89:         i->i_uid = isonum_733(rrip->u.px.uid);
90:         i->i_gid = isonum_733(rrip->u.px.gid);
91:         break;
92:     case GET_SIG('P', 'N'):
93:         if(S_ISBLK(i->i_mode) || S_ISCHR(i->i_mode)) {
94:             dev_h = isonum_733(rrip->u.pn.dev_h);
95:             dev_l = isonum_733(rrip->u.pn.dev_l);
96:             i->rdev = MKDEV(dev_h, dev_l);
97:         }
98:         break;
99:     case GET_SIG('S', 'L'):
100:         sl_len = rootflag = 0;
101:         slc = (struct rrip_sl_component *)&rrip->u.sl.ar
ea;
102:         while(sl_len < (rrip->len - 5)) {
103:             if(sl_len && !rootflag) {
104:                 nm_len++;
105:             }
106:             rootflag = 0;
107:             switch(slc->flags & 0xE) {
108:                 case 0:
109:                     nm_len += slc->len;
110:                     break;
111:                 case SL_CURRENT:
112:                     nm_len += 1;
113:                     break;
114:                 case SL_PARENT:
115:                     nm_len += 2;
116:                     break;
117:                 case SL_ROOT:
118:                     nm_len += 1;
119:                     rootflag = 1;
120:                     break;
121:                 default:
122:                     printk("WARNING: %s(): u
nsupported RRIP SL flags %d.\n", __FUNCTION__, slc->flags & 0xE);
123:             }
124:             slc = (struct rrip_sl_component *)(((cha
r *)slc) + slc->len + sizeof(struct rrip_sl_component));
125:             sl_len += slc->len + sizeof(struct rrip_
sl_component);
126:         }
127:         i->i_size = nm_len;
128:         break;
129:     case GET_SIG('T', 'F'):

```

fs/iso9660/rrip.c

Page 3/6

```

130:         n = 0;
131:         if(rrip->u.tf.flags & TF_CREATION) {
132:             i->i_ctime = isodate(rrip->u.tf.times[n+
+].time);
133:         }
134:         if(rrip->u.tf.flags & TF_MODIFY) {
135:             i->i_mtime = isodate(rrip->u.tf.times[n+
+].time);
136:         }
137:         if(rrip->u.tf.flags & TF_ACCESS) {
138:             i->i_atime = isodate(rrip->u.tf.times[n+
+].time);
139:         }
140:         if(rrip->u.tf.flags & TF_ATTRIBUTES) {
141:             i->i_ctime = isodate(rrip->u.tf.times[n+
+].time);
142:         }
143:         break;
144:     }
145:     len += rrip->len;
146: }
147: if(ce_block) {
148:     brelse(buf);
149: }
150: }
151:
152: int get_rrip_filename(struct iso9660_directory_record *d, struct inode *i, char
*name)
153: {
154:     unsigned int total_len;
155:     unsigned int len;
156:     unsigned int sig;
157:     int nm_len;
158:     struct susp_rrip *rrip;
159:     unsigned int ce_block, ce_offset, ce_size;
160:     struct buffer *buf;
161:     unsigned char *sue;
162:
163:     ce_block = ce_offset = ce_size = 0;
164:     buf = NULL;
165:     total_len = isonum_711(d->length);
166:     len = isonum_711(d->name_len);
167:     if(!(len % 2)) {
168:         len++;
169:     }
170:     sue = (unsigned char *)d->name;
171:     nm_len = 0;
172:
173: loop:
174:     if(ce_block && ce_size) {
175:         /* FIXME: it only looks in one directory block */
176:         if(!(buf = bread(i->dev, ce_block, i->sb->s_blocksize))) {
177:             return 0;
178:         }
179:         sue = (unsigned char *)buf->data + ce_offset;
180:         total_len = ce_size;
181:         len = 0;
182:     }
183:
184:     while(len < total_len) {
185:         rrip = (struct susp_rrip *)(sue + len);
186:         if(rrip->len == 0) {
187:             break;
188:         }
189:         sig = GET_SIG(rrip->signature[0], rrip->signature[1]);
190:         switch(sig) {
191:             case GET_SIG('S', 'P'):
```

fs/iso9660/rrip.c

Page 4/6

```

192:                                if(rrip->u.sp.magic[0] != SP_MAGIC1 || rrip->u.s
p.magic[1] != SP_MAGIC2) {
193:                                    if(ce_block) {
194:                                        brelse(buf);
195:                                    }
196:                                    return 0;
197:                                }
198:                                break;
199:                                case GET_SIG('C', 'E'):
200:                                    if(ce_block) {
201:                                        brelse(buf);
202:                                    }
203:                                    ce_block = isonum_733(rrip->u.ce.block);
204:                                    ce_offset = isonum_733(rrip->u.ce.offset);
205:                                    ce_size = isonum_733(rrip->u.ce.size);
206:                                    goto loop;
207:                                case GET_SIG('N', 'M'):
208:                                    if(rrip->u.nm.flags) { /* FIXME: & ~(NM_CONTINUE
| NM_CURRENT | NM_PARENT)) { */
209:                                        printk("WARNING: %s(): unsupported NM fl
ag settings (%d).\n", __FUNCTION__, rrip->u.nm.flags);
210:                                        if(ce_block) {
211:                                            brelse(buf);
212:                                        }
213:                                        return 0;
214:                                    }
215:                                    nm_len = rrip->len - 5;
216:                                    memcpy_b(name, rrip->u.nm.name, nm_len);
217:                                    name[nm_len] = NULL;
218:                                    break;
219:                                }
220:                                len += rrip->len;
221:                            }
222:                            if(ce_block) {
223:                                brelse(buf);
224:                            }
225:                            return nm_len;
226:    }
227:
228: int get_rrip_symlink(struct inode *i, char *name)
229: {
230:     unsigned int total_len;
231:     unsigned int len;
232:     unsigned int sig;
233:     int nm_len;
234:     struct susp_rrip *rrip;
235:     unsigned int ce_block, ce_offset, ce_size;
236:     struct buffer *buf;
237:     struct buffer *buf2;
238:     unsigned char *sue;
239:     struct iso9660_directory_record *d;
240:     __blk_t dblock;
241:     __off_t doffset;
242:     int sl_len, rootflag;
243:     struct rrip_sl_component *slc;
244:
245:     dblock = (i->inode & ~ISO9660_INODE_MASK) >> ISO9660_INODE_BITS;
246:     doffset = i->inode & ISO9660_INODE_MASK;
247:     /* FIXME: it only looks in one directory block */
248:     if(!(buf = bread(i->dev, dblock, i->sb->s_blocksize))) {
249:         return -EIO;
250:     }
251:     d = (struct iso9660_directory_record *) (buf->data + doffset);
252:
253:     ce_block = ce_offset = ce_size = 0;
254:     buf2 = NULL;
255:     total_len = isonum_711(d->length);

```

fs/iso9660/rrip.c

Page 5/6

```

256:     len = isonum_711(d->name_len);
257:     if(!(len % 2)) {
258:         len++;
259:     }
260:     sue = (unsigned char *)d->name;
261:     nm_len = 0;
262:
263: loop:
264:     if(ce_block && ce_size) {
265:         /* FIXME: it only looks in one directory block */
266:         if(!(buf2 = bread(i->dev, ce_block, i->sb->s_blocksize))) {
267:             return 0;
268:         }
269:         sue = (unsigned char *)buf2->data + ce_offset;
270:         total_len = ce_size;
271:         len = 0;
272:     }
273:
274:     while(len < total_len) {
275:         rrip = (struct susp_rrip *) (sue + len);
276:         if(rrip->len == 0) {
277:             break;
278:         }
279:         sig = GET_SIG(rrip->signature[0], rrip->signature[1]);
280:         switch(sig) {
281:             case GET_SIG('S', 'P'):
282:                 if(rrip->u.sp.magic[0] != SP_MAGIC1 || rrip->u.s
p.magic[1] != SP_MAGIC2) {
283:                     if(ce_block) {
284:                         brelse(buf2);
285:                     }
286:                     return 0;
287:                 }
288:                 break;
289:             case GET_SIG('C', 'E'):
290:                 if(ce_block) {
291:                     brelse(buf2);
292:                 }
293:                 ce_block = isonum_733(rrip->u.ce.block);
294:                 ce_offset = isonum_733(rrip->u.ce.offset);
295:                 ce_size = isonum_733(rrip->u.ce.size);
296:                 goto loop;
297:             case GET_SIG('S', 'L'):
298:                 sl_len = rootflag = 0;
299:                 slc = (struct rrip_sl_component *)&rrip->u.sl.ar
ea;
300:                 while(sl_len < (rrip->len - 5)) {
301:                     if(sl_len && !rootflag) {
302:                         strcat(name, "/");
303:                         nm_len++;
304:                     }
305:                     rootflag = 0;
306:                     switch(slc->flags & 0xE) {
307:                         case 0:
308:                             nm_len += slc->len;
309:                             strncat(name, slc->name,
slc->len);
310:                             break;
311:                         case SL_CURRENT:
312:                             nm_len += 1;
313:                             strcat(name, ".");
314:                             break;
315:                         case SL_PARENT:
316:                             nm_len += 2;
317:                             strcat(name, "..");
318:                             break;
319:                         case SL_ROOT:

```

fs/iso9660/rrip.c

Page 6/6

```
320:                                     nm_len += 1;
321:                                     rootflag = 1;
322:                                     strcat(name, "/");
323:                                     break;
324:                                     default:
325:                                     printk("WARNING: %s(): u
nsupported RRIP SL flags %d.\n", __FUNCTION__, slc->flags & 0xE);
326:                                     }
327:                                     slc = (struct rrip_sl_component *)(((cha
r *)slc) + slc->len + sizeof(struct rrip_sl_component));
328:                                     sl_len += slc->len + sizeof(struct rrip_
sl_component);
329:                                     }
330:                                     name[nm_len] = NULL;
331:                                     break;
332:                                     }
333:                                     len += rrip->len;
334:                                     }
335:                                     if(ce_block) {
336:                                     brelse(buf2);
337:                                     }
338:                                     brelse(buf);
339:                                     return nm_len;
340: }

```


fs/iso9660/super.c

Page 1/4

```

1: /*
2:  * fiwix/fs/iso9660/super.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/errno.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/filesystems.h>
12: #include <fiwix/fs_iso9660.h>
13: #include <fiwix/buffer.h>
14: #include <fiwix/time.h>
15: #include <fiwix/sched.h>
16: #include <fiwix/mm.h>
17: #include <fiwix/stdio.h>
18: #include <fiwix/string.h>
19:
20: struct fs_operations iso9660_fsop = {
21:     FSOP_REQUIRES_DEV,
22:     NULL,
23:
24:     NULL, /* open */
25:     NULL, /* close */
26:     NULL, /* read */
27:     NULL, /* write */
28:     NULL, /* ioctl */
29:     NULL, /* lseek */
30:     NULL, /* readdir */
31:     NULL, /* mmap */
32:     NULL, /* select */
33:
34:     NULL, /* readlink */
35:     NULL, /* followlink */
36:     NULL, /* bmap */
37:     NULL, /* lookup */
38:     NULL, /* rmdir */
39:     NULL, /* link */
40:     NULL, /* unlink */
41:     NULL, /* symlink */
42:     NULL, /* mkdir */
43:     NULL, /* mknod */
44:     NULL, /* truncate */
45:     NULL, /* create */
46:     NULL, /* rename */
47:
48:     NULL, /* read_block */
49:     NULL, /* write_block */
50:
51:     iso9660_read_inode,
52:     NULL, /* write_inode */
53:     NULL, /* ialloc */
54:     NULL, /* ifree */
55:     iso9660_statfs,
56:     iso9660_read_superblock,
57:     NULL, /* remount_fs */
58:     NULL, /* write_superblock */
59:     iso9660_release_superblock
60: };
61:
62: int isonum_711(char *str)
63: {
64:     unsigned char *le;
65:
66:     le = (unsigned char *)str;
67:     return le[0];

```

```

68: }
69:
70: /* return a 16bit little-endian number */
71: int isonum_723(char *str)
72: {
73:     unsigned char *le;
74:
75:     le = (unsigned char *)str;
76:     return le[0] | (le[1] << 8);
77: }
78:
79: /* return a 32bit little-endian number */
80: int isonum_731(char *str)
81: {
82:     unsigned char *le;
83:
84:     le = (unsigned char *)str;
85:     return le[0] | (le[1] << 8) | (le[2] << 16) | (le[3] << 24);
86: }
87:
88: /* return a 32bit little-endian number */
89: int isonum_733(char *p)
90: {
91:     return isonum_731(p);
92: }
93:
94: /* return a date and time format */
95: unsigned long int isodate(char *p)
96: {
97:     struct mt mt;
98:
99:     if(!p[0]) {
100:         return 0;
101:     }
102:
103:     mt.mt_sec = p[5];
104:     mt.mt_min = p[4];
105:     mt.mt_hour = p[3];
106:     mt.mt_day = p[2];
107:     mt.mt_month = p[1];
108:     mt.mt_year = p[0];
109:     mt.mt_year += 1900;
110:     mt.mt_min += p[6] * 15;
111:
112:     return mktime(&mt);
113: }
114:
115: /* return a clean filename */
116: int iso9660_cleanfilename(char *filename, int len)
117: {
118:     int n;
119:     char *p;
120:
121:     p = filename;
122:     if(len > 2) {
123:         for(n = 0; n < len; n++) {
124:             if((len - n) == 2) {
125:                 if(p[n] == ';' && p[n + 1] == '1') {
126:                     filename[n] = NULL;
127:                     if(p[n - 1] == '.') {
128:                         filename[n - 1] = NULL;
129:                     }
130:                 }
131:             }
132:         }
133:     }
134: }

```

fs/iso9660/super.c

Page 3/4

```

135:         return 1;
136:     }
137:
138: void iso9660_statfs(struct superblock *sb, struct statfs *statfsbuf)
139: {
140:     statfsbuf->f_type = ISO9660_SUPER_MAGIC;
141:     statfsbuf->f_bsize = sb->s_blocksize;
142:     statfsbuf->f_blocks = isonum_733(sb->u.iso9660.sb->volume_space_size);
143:     statfsbuf->f_bfree = 0;
144:     statfsbuf->f_bavail = 0;
145:     statfsbuf->f_files = 0;          /* FIXME */
146:     statfsbuf->f_ffree = 0;
147:     /* statfsbuf->f_fsid = ? */
148:     statfsbuf->f_namelen = NAME_MAX;
149: }
150:
151: int iso9660_read_superblock(__dev_t dev, struct superblock *sb)
152: {
153:     struct buffer *buf;
154:     struct iso9660_super_block *iso9660sb;
155:     struct iso9660_super_block *pvd;
156:     struct iso9660_directory_record *dr;
157:     __ino_t root_inode;
158:     int n;
159:
160:     superblock_lock(sb);
161:     pvd = NULL;
162:
163:     for(n = 0; n < ISO9660_MAX_VD; n++) {
164:         if(!(buf = bread(dev, ISO9660_SUPERBLOCK + n, BLKSIZE_2K))) {
165:             superblock_unlock(sb);
166:             return -EIO;
167:         }
168:
169:         iso9660sb = (struct iso9660_super_block *)buf->data;
170:         if(strncmp(iso9660sb->id, ISO9660_STANDARD_ID, sizeof(iso9660sb-
>id)) || (isonum_711(iso9660sb->type) == ISO9660_VD_END)) {
171:             break;
172:         }
173:         if(isonum_711(iso9660sb->type) == ISO9660_VD_PRIMARY) {
174:             pvd = (struct iso9660_super_block *)buf->data;
175:             break;
176:         }
177:         brelse(buf);
178:     }
179:     if(!pvd) {
180:         printk("WARNING: %s(): invalid filesystem type or bad superblock
on device %d,%d.\n", __FUNCTION__, MAJOR(dev), MINOR(dev));
181:         superblock_unlock(sb);
182:         brelse(buf);
183:         return -EINVAL;
184:     }
185:
186:     dr = (struct iso9660_directory_record *)pvd->root_directory_record;
187:     root_inode = isonum_711(dr->extent);
188:
189:     sb->dev = dev;
190:     sb->fsop = &iso9660_fsop;
191:     sb->flags = MS_RDONLY;
192:     sb->s_blocksize = isonum_723(pvd->logical_block_size);
193:     sb->u.iso9660.rrip = 0;
194:     if(!(sb->u.iso9660.sb = (void *)kmalloc())) {
195:         superblock_unlock(sb);
196:         brelse(buf);
197:         return -ENOMEM;
198:     }
199:     memcpy_b(sb->u.iso9660.sb, pvd, sizeof(struct iso9660_super_block));

```

fs/iso9660/super.c

Page 4/4

```
200:         brelse(buf);
201:
202:         root_inode = (root_inode << ISO9660_INODE_BITS) + (0 & ISO9660_INODE_MAS
K);
203:         if(!(sb->root = iget(sb, root_inode))) {
204:             printk("WARNING: %s(): unable to get root inode.\n", __FUNCTION_
_);
205:             superblock_unlock(sb);
206:             return -EINVAL;
207:         }
208:         sb->u.iso9660.s_root_inode = root_inode;
209:
210:         superblock_unlock(sb);
211:         return 0;
212:     }
213:
214: void iso9660_release_superblock(struct superblock *sb)
215: {
216:     kfree((unsigned int)sb->u.iso9660.sb);
217:     kfree((unsigned int)sb->u.iso9660.pathtable);
218:     kfree((unsigned int)sb->u.iso9660.pathtable_raw);
219: }
220:
221: int iso9660_init(void)
222: {
223:     return register_filesystem("iso9660", &iso9660_fsop);
224: }
```

fs/iso9660/symlink.c

Page 1/2

```

1: /*
2:  * fiwix/fs/iso9660/symlink.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/errno.h>
10: #include <fiwix/buffer.h>
11: #include <fiwix/fs.h>
12: #include <fiwix/filesystems.h>
13: #include <fiwix/fs_iso9660.h>
14: #include <fiwix/stat.h>
15: #include <fiwix/mm.h>
16: #include <fiwix/stdio.h>
17: #include <fiwix/string.h>
18:
19: struct fs_operations iso9660_symlink_fsop = {
20:     0,
21:     0,
22:
23:     NULL, /* open */
24:     NULL, /* close */
25:     NULL, /* read */
26:     NULL, /* write */
27:     NULL, /* ioctl */
28:     NULL, /* lseek */
29:     NULL, /* readdir */
30:     NULL, /* mmap */
31:     NULL, /* select */
32:
33:     iso9660_readlink,
34:     iso9660_followlink,
35:     NULL, /* bmap */
36:     NULL, /* lookup */
37:     NULL, /* rmdir */
38:     NULL, /* link */
39:     NULL, /* unlink */
40:     NULL, /* symlink */
41:     NULL, /* mkdir */
42:     NULL, /* mknod */
43:     NULL, /* truncate */
44:     NULL, /* create */
45:     NULL, /* rename */
46:
47:     NULL, /* read_block */
48:     NULL, /* write_block */
49:
50:     NULL, /* read_inode */
51:     NULL, /* write_inode */
52:     NULL, /* ialloc */
53:     NULL, /* ifree */
54:     NULL, /* statfs */
55:     NULL, /* read_superblock */
56:     NULL, /* remount_fs */
57:     NULL, /* write_superblock */
58:     NULL, /* release_superblock */
59: };
60:
61: int iso9660_readlink(struct inode *i, char *buffer, __size_t count)
62: {
63:     __off_t size_read;
64:     char *name;
65:
66:     if(!(name = (char *)kmalloc())) {
67:         return -ENOMEM;

```

fs/iso9660/symlink.c

Page 2/2

```

68:         }
69:
70:         inode_lock(i);
71:         name[0] = NULL;
72:         if((size_read = get_rrip_symlink(i, name))) {
73:             size_read = MIN(size_read, count);
74:             memcpy_b(buffer, name, size_read);
75:         }
76:         kfree((unsigned int)name);
77:         inode_unlock(i);
78:         return size_read;
79:     }
80:
81: int iso9660_followlink(struct inode *dir, struct inode *i, struct inode **i_res)
82: {
83:     char *name;
84:     __off_t size_read;
85:     __ino_t errno;
86:
87:     if(!i) {
88:         return -ENOENT;
89:     }
90:     if(!S_ISLNK(i->i_mode)) {
91:         printk("%s(): Oops, inode '%d' is not a symlink (!?)\n", __FUNC
TION__, i->inode);
92:         return 0;
93:     }
94:
95:     if(!(name = (char *)kmalloc())) {
96:         return -ENOMEM;
97:     }
98:
99:     name[0] = NULL;
100:    if((size_read = get_rrip_symlink(i, name))) {
101:        iput(i);
102:        if((errno = parse_namei(name, dir, i_res, NULL, FOLLOW_LINKS)))
{
103:            kfree((unsigned int)name);
104:            return errno;
105:        }
106:    }
107:    kfree((unsigned int)name);
108:    return 0;
109: }

```

fs/minix/bitmaps.c

Page 1/3

```

1: /*
2:  * fiwix/fs/minix/bitmaps.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/filesystems.h>
11: #include <fiwix/fs_minix.h>
12: #include <fiwix/buffer.h>
13: #include <fiwix/errno.h>
14: #include <fiwix/stdio.h>
15: #include <fiwix/string.h>
16:
17: #define COUNT          1
18: #define FIRST_ZERO    2
19:
20: static int count_bits(struct superblock *sb, __blk_t offset, int num, int blocks
, int mode)
21: {
22:     unsigned char c;
23:     int blksize;
24:     int n, n2, last, bits, count, mapb;
25:     struct buffer *buf;
26:
27:     count = mapb = 0;
28:     blksize = sb->s_blocksize;
29:
30:     while(offset < blocks) {
31:         if(!(buf = bread(sb->dev, offset, blksize))) {
32:             return -EIO;
33:         }
34:         last = (num / 8) > blksize ? blksize : (num / 8);
35:         for(n = 0; n < last; n++) {
36:             c = (unsigned char)buf->data[n];
37:             bits = n < last ? 8 : num & 8;
38:             for(n2 = 0; n2 < bits; n2++) {
39:                 if(c & (1 << n2)) {
40:                     if(mode == COUNT) {
41:                         count++;
42:                     }
43:                 } else {
44:                     if(mode == FIRST_ZERO) {
45:                         brelse(buf);
46:                         return n2 + ((n * 8) + (mapb * b
blksize * 8));
47:                     }
48:                 }
49:             }
50:         }
51:         offset++;
52:         mapb++;
53:         num -= (blksize * 8);
54:         brelse(buf);
55:     }
56:     return count;
57: }
58:
59: int minix_change_bit(int mode, struct superblock *sb, int map, int item)
60: {
61:     int byte, bit, mask;
62:     struct buffer *buf;
63:
64:     map += item / (sb->s_blocksize * 8);
65:     byte = (item % (sb->s_blocksize * 8)) / 8;

```

fs/minix/bitmaps.c

Page 2/3

```

66:         bit = (item % (sb->s_blocksize * 8)) % 8;
67:         mask = 1 << bit;
68:
69:         if(!(buf = bread(sb->dev, map, sb->s_blocksize))) {
70:             return -EIO;
71:         }
72:
73:         if(mode == CLEAR_BIT) {
74:             if(!(buf->data[byte] & mask)) {
75:                 brelse(buf);
76:                 return 1;
77:             }
78:             buf->data[byte] &= ~mask;
79:         }
80:         if(mode == SET_BIT) {
81:             if((buf->data[byte] & mask)) {
82:                 brelse(buf);
83:                 return 1;
84:             }
85:             buf->data[byte] |= mask;
86:         }
87:
88:         bwrite(buf);
89:         return 0;
90:     }
91:
92: int minix_balloc(struct superblock *sb)
93: {
94:     int map, block, errno;
95:
96:     superblock_lock(sb);
97:
98:     map = 1 + SUPERBLOCK + sb->u.minix.sb.s_imap_blocks;
99:
100:    if(!(block = minix_find_first_zero(sb, map, sb->u.minix.nzones, map + sb
->u.minix.sb.s_zmap_blocks))) {
101:        superblock_unlock(sb);
102:        return -ENOSPC;
103:    }
104:
105:    errno = minix_change_bit(SET_BIT, sb, map, block);
106:    block += sb->u.minix.sb.s_firstdatazone - 1;
107:
108:    if(errno) {
109:        if(errno < 0) {
110:            printk("WARNING: %s(): unable to set block %d.\n", __FUN
CTION__, block);
111:        } else {
112:            printk("WARNING: %s(): block %d is already marked as use
d!\n", __FUNCTION__, block);
113:        }
114:    }
115:
116:    superblock_unlock(sb);
117:    return block;
118: }
119:
120: void minix_bfree(struct superblock *sb, int block)
121: {
122:     int map, errno;
123:
124:     if(block < sb->u.minix.sb.s_firstdatazone || block > sb->u.minix.nzones)
{
125:         printk("WARNING: %s(): block %d is not in datazone.\n", __FUNCTI
ON__, block);
126:         return;
127:     }

```


fs/minix/bitmaps.c

Page 3/3

```

128:
129:     superblock_lock(sb);
130:
131:     map = 1 + SUPERBLOCK + sb->u.minix.sb.s_imap_blocks;
132:     block -= sb->u.minix.sb.s_firstdatazone - 1;
133:     errno = minix_change_bit(CLEAR_BIT, sb, map, block);
134:
135:     if(errno) {
136:         if(errno < 0) {
137:             printk("WARNING: %s(): unable to free block %d.\n", __FU
NCTION__, block);
138:         } else {
139:             printk("WARNING: %s(): block %d is already marked as fre
e!\n", __FUNCTION__, block);
140:         }
141:     }
142:
143:     superblock_unlock(sb);
144:     return;
145: }
146:
147: int minix_count_free_inodes(struct superblock *sb)
148: {
149:     __blk_t offset;
150:
151:     offset = 1 + SUPERBLOCK;
152:     return count_bits(sb, offset, sb->u.minix.sb.s_ninodes, offset + sb->u.m
inix.sb.s_imap_blocks, COUNT);
153: }
154:
155: int minix_count_free_blocks(struct superblock *sb)
156: {
157:     __blk_t offset;
158:
159:     offset = 1 + SUPERBLOCK + sb->u.minix.sb.s_imap_blocks;
160:     return count_bits(sb, offset, sb->u.minix.nzones, offset + sb->u.minix.s
b.s_zmap_blocks, COUNT);
161: }
162:
163: int minix_find_first_zero(struct superblock *sb, __blk_t offset, int num, int bl
ocks)
164: {
165:     return count_bits(sb, offset, num, blocks, FIRST_ZERO);
166: }

```

fs/minix/dir.c

Page 1/3

```

1: /*
2:  * fiwix/fs/minix/dir.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/errno.h>
10: #include <fiwix/buffer.h>
11: #include <fiwix/fs.h>
12: #include <fiwix/filesystems.h>
13: #include <fiwix/stat.h>
14: #include <fiwix/dirent.h>
15: #include <fiwix/mm.h>
16: #include <fiwix/stdio.h>
17: #include <fiwix/string.h>
18:
19: struct fs_operations minix_dir_fsop = {
20:     0,
21:     0,
22:
23:     minix_dir_open,
24:     minix_dir_close,
25:     minix_dir_read,
26:     minix_dir_write,
27:     NULL, /* ioctl */
28:     NULL, /* lseek */
29:     minix_dir_readdir,
30:     NULL, /* mmap */
31:     NULL, /* select */
32:
33:     NULL, /* readlink */
34:     NULL, /* followlink */
35:     minix_bmap,
36:     minix_lookup,
37:     minix_rmdir,
38:     minix_link,
39:     minix_unlink,
40:     minix_symlink,
41:     minix_mkdir,
42:     minix_mknod,
43:     NULL, /* truncate */
44:     minix_create,
45:     minix_rename,
46:
47:     NULL, /* read_block */
48:     NULL, /* write_block */
49:
50:     NULL, /* read_inode */
51:     NULL, /* write_inode */
52:     NULL, /* ialloc */
53:     NULL, /* ifree */
54:     NULL, /* statfs */
55:     NULL, /* read_superblock */
56:     NULL, /* remount_fs */
57:     NULL, /* write_superblock */
58:     NULL, /* release_superblock */
59: };
60:
61: int minix_dir_open(struct inode *i, struct fd *fd_table)
62: {
63:     fd_table->offset = 0;
64:     return 0;
65: }
66:
67: int minix_dir_close(struct inode *i, struct fd *fd_table)

```

fs/minix/dir.c

Page 2/3

```

68: {
69:     return 0;
70: }
71:
72: int minix_dir_read(struct inode *i, struct fd *fd_table, char *buffer, __size_t
count)
73: {
74:     return -EISDIR;
75: }
76:
77: int minix_dir_write(struct inode *i, struct fd *fd_table, const char *buffer, __
size_t count)
78: {
79:     return -EBADF;
80: }
81:
82: int minix_dir_readdir(struct inode *i, struct fd *fd_table, struct dirent *diren
t, unsigned int count)
83: {
84:     __blk_t block;
85:     unsigned int doffset, offset;
86:     unsigned int size, dirent_len;
87:     struct minix_dir_entry *d;
88:     int base_dirent_len;
89:     int blksize;
90:     struct buffer *buf;
91:
92:     if(!(S_ISDIR(i->i_mode))) {
93:         return -EBADF;
94:     }
95:
96:     blksize = i->sb->s_blocksize;
97:     if(fd_table->offset > i->i_size) {
98:         fd_table->offset = i->i_size;
99:     }
100:
101:     base_dirent_len = sizeof(dirent->d_ino) + sizeof(dirent->d_off) + sizeof
(dirent->d_reclen);
102:     doffset = offset = size = 0;
103:
104:     while(doffset < count) {
105:         if((block = bmap(i, fd_table->offset, FOR_READING)) < 0) {
106:             return block;
107:         }
108:         if(block) {
109:             if(!(buf = bread(i->dev, block, blksize))) {
110:                 return -EIO;
111:             }
112:
113:             doffset = fd_table->offset;
114:             offset = fd_table->offset % blksize;
115:             while(doffset < i->i_size && offset < blksize) {
116:                 d = (struct minix_dir_entry *) (buf->data + offse
t);
117:                 if(d->inode) {
118:                     dirent_len = (base_dirent_len + (strlen(
d->name) + 1)) + 3;
119:                     dirent_len &= ~3; /* round up */
120:                     dirent->d_ino = d->inode;
121:                     if((size + dirent_len) < count) {
122:                         dirent->d_off = doffset;
123:                         dirent->d_reclen = dirent_len;
124:                         memcpy_b(dirent->d_name, d->name
, strlen(d->name));
125:                         dirent->d_name[strlen(d->name)]
= NULL;
126:                         dirent = (struct dirent *) ((char

```

fs/minix/dir.c

Page 3/3

```
*)dirent + dirent_len);
127:                                     size += dirent_len;
128:                                     } else {
129:                                         break;
130:                                     }
131:                                     }
132:                                     doffset += i->sb->u.minix.dirsize;
133:                                     offset += i->sb->u.minix.dirsize;
134:                                     }
135:                                     brelse(buf);
136:                                     }
137:                                     fd_table->offset &= ~(blksize - 1);
138:                                     doffset = fd_table->offset;
139:                                     fd_table->offset += offset;
140:                                     doffset += blksize;
141:                                     }
142:
143:                                     return size;
144: }
```

fs/minix/file.c

Page 1/3

```

1: /*
2:  * fiwix/fs/minix/file.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/types.h>
10: #include <fiwix/errno.h>
11: #include <fiwix/buffer.h>
12: #include <fiwix/fs.h>
13: #include <fiwix/filesystems.h>
14: #include <fiwix/mm.h>
15: #include <fiwix/mman.h>
16: #include <fiwix/fcntl.h>
17: #include <fiwix/stdio.h>
18: #include <fiwix/string.h>
19:
20: struct fs_operations minix_file_fsop = {
21:     0,
22:     0,
23:
24:     minix_file_open,
25:     minix_file_close,
26:     file_read,
27:     minix_file_write,
28:     NULL, /* ioctl */
29:     minix_file_lseek,
30:     NULL, /* readdir */
31:     NULL, /* mmap */
32:     NULL, /* select */
33:
34:     NULL, /* readlink */
35:     NULL, /* followlink */
36:     minix_bmap,
37:     NULL, /* lookup */
38:     NULL, /* rmdir */
39:     NULL, /* link */
40:     NULL, /* unlink */
41:     NULL, /* symlink */
42:     NULL, /* mkdir */
43:     NULL, /* mknod */
44:     minix_truncate,
45:     NULL, /* create */
46:     NULL, /* rename */
47:
48:     NULL, /* read_block */
49:     NULL, /* write_block */
50:
51:     NULL, /* read_inode */
52:     NULL, /* write_inode */
53:     NULL, /* ialloc */
54:     NULL, /* ifree */
55:     NULL, /* statfs */
56:     NULL, /* read_superblock */
57:     NULL, /* remount_fs */
58:     NULL, /* write_superblock */
59:     NULL, /* release_superblock */
60: };
61:
62: int minix_file_open(struct inode *i, struct fd *fd_table)
63: {
64:     if(fd_table->flags & O_APPEND) {
65:         fd_table->offset = i->i_size;
66:     } else {
67:         fd_table->offset = 0;

```

fs/minix/file.c

Page 2/3

```

68:         }
69:         if(fd_table->flags & O_TRUNC) {
70:             i->i_size = 0;
71:             minix_truncate(i, 0);
72:         }
73:         return 0;
74:     }
75:
76: int minix_file_close(struct inode *i, struct fd *fd_table)
77: {
78:     return 0;
79: }
80:
81: int minix_file_write(struct inode *i, struct fd *fd_table, const char *buffer, _
__size_t count)
82: {
83:     __blk_t block;
84:     __off_t total_written;
85:     unsigned int boffset, bytes;
86:     int blksize;
87:     struct buffer *buf;
88:
89:     inode_lock(i);
90:
91:     blksize = i->sb->s_blocksize;
92:     total_written = 0;
93:
94:     if(fd_table->flags & O_APPEND) {
95:         fd_table->offset = i->i_size;
96:     }
97:
98:     while(total_written < count) {
99:         boffset = fd_table->offset % blksize;
100:        if((block = bmap(i, fd_table->offset, FOR_WRITING)) < 0) {
101:            inode_unlock(i);
102:            return block;
103:        }
104:        bytes = blksize - boffset;
105:        bytes = MIN(bytes, (count - total_written));
106:        if(!(buf = bread(i->dev, block, blksize))) {
107:            inode_unlock(i);
108:            return -EIO;
109:        }
110:        memcpy_b(buf->data + boffset, buffer + total_written, bytes);
111:        update_page_cache(i, fd_table->offset, buffer + total_written, b
ytes);
112:        bwrite(buf);
113:        total_written += bytes;
114:        boffset += bytes;
115:        boffset %= blksize;
116:        fd_table->offset += bytes;
117:    }
118:
119:    if(fd_table->offset > i->i_size) {
120:        i->i_size = fd_table->offset;
121:    }
122:    i->i_ctime = CURRENT_TIME;
123:    i->i_mtime = CURRENT_TIME;
124:    i->dirty = 1;
125:
126:    inode_unlock(i);
127:    return total_written;
128: }
129:
130: int minix_file_lseek(struct inode *i, __off_t offset)
131: {
132:     return offset;

```

```
133: }
```

fs/minix/inode.c

Page 1/2

```
1: /*
2:  * fiwix/fs/minix/inode.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/filesystems.h>
11: #include <fiwix/fs_minix.h>
12: #include <fiwix/fs_pipe.h>
13: #include <fiwix/statfs.h>
14: #include <fiwix/sleep.h>
15: #include <fiwix/stat.h>
16: #include <fiwix/sched.h>
17: #include <fiwix/buffer.h>
18: #include <fiwix/process.h>
19: #include <fiwix/errno.h>
20: #include <fiwix/stdio.h>
21: #include <fiwix/string.h>
22:
23: int minix_read_inode(struct inode *i)
24: {
25:     if(i->sb->u.minix.version == 1) {
26:         return v1_minix_read_inode(i);
27:     }
28:
29:     return v2_minix_read_inode(i);
30: }
31:
32: int minix_write_inode(struct inode *i)
33: {
34:     if(i->sb->u.minix.version == 1) {
35:         return v1_minix_write_inode(i);
36:     }
37:
38:     return v2_minix_write_inode(i);
39: }
40:
41: int minix_ialloc(struct inode *i)
42: {
43:     if(i->sb->u.minix.version == 1) {
44:         return v1_minix_ialloc(i);
45:     }
46:
47:     return v2_minix_ialloc(i);
48: }
49:
50: void minix_ifree(struct inode *i)
51: {
52:     if(i->sb->u.minix.version == 1) {
53:         return v1_minix_ifree(i);
54:     }
55:
56:     return v2_minix_ifree(i);
57: }
58:
59: int minix_bmap(struct inode *i, __off_t offset, int mode)
60: {
61:     if(i->sb->u.minix.version == 1) {
62:         return v1_minix_bmap(i, offset, mode);
63:     }
64:
65:     return v2_minix_bmap(i, offset, mode);
66: }
67:
```


fs/minix/inode.c

Page 2/2

```
68: int minix_truncate(struct inode *i, __off_t length)
69: {
70:     if(i->sb->u.minix.version == 1) {
71:         return v1_minix_truncate(i, length);
72:     }
73:
74:     return v2_minix_truncate(i, length);
75: }
```

fs/minix/Makefile

Page 1/1

```
1: # fiwix/fs/minix/Makefile
2: #
3: # Copyright 2018, Jordi Sanfeliu. All rights reserved.
4: # Distributed under the terms of the Fiwix License.
5: #
6: #
7: .S.o:
8:     $(CC) -traditional -I$(INCLUDE) -c -o $@ $<
9: .c.o:
10:     $(CC) $(CFLAGS) -c -o $@ $<
11:
12: OBJS = super.o bitmaps.o inode.o namei.o symlink.o dir.o file.o v1_inode.o v2_in
ode.o
13:
14: minix: $(OBJS)
15:     $(LD) $(LDFLAGS) -r $(OBJS) -o minix.o
16:
17: clean:
18:     rm -f *.o
19:
```

fs/minix/namei.c

Page 1/11

```

1: /*
2:  * fiwix/fs/minix/namei.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/types.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/filesystems.h>
12: #include <fiwix/fs_minix.h>
13: #include <fiwix/buffer.h>
14: #include <fiwix/errno.h>
15: #include <fiwix/stat.h>
16: #include <fiwix/stdio.h>
17: #include <fiwix/string.h>
18:
19: static int is_dir_empty(struct inode *dir)
20: {
21:     __blk_t block;
22:     unsigned int blksize;
23:     unsigned int offset, doffset;
24:     struct buffer *buf;
25:     struct minix_dir_entry *d;
26:
27:     blksize = dir->sb->s_blocksize;
28:     doffset = dir->sb->u.minix.dirsize * 2; /* accept only "." and ".." */
29:     offset = 0;
30:
31:     while(offset < dir->i_size) {
32:         if((block = bmap(dir, offset, FOR_READING)) < 0) {
33:             break;
34:         }
35:         if(block) {
36:             if(!(buf = bread(dir->dev, block, blksize))) {
37:                 break;
38:             }
39:             do {
40:                 if(doffset + offset >= dir->i_size) {
41:                     break;
42:                 }
43:                 d = (struct minix_dir_entry *) (buf->data + doffs
et);
44:                 if(d->inode) {
45:                     brelse(buf);
46:                     return 0;
47:                 }
48:                 doffset += dir->sb->u.minix.dirsize;
49:             } while(doffset < blksize);
50:             brelse(buf);
51:             offset += blksize;
52:             doffset = 0;
53:         } else {
54:             break;
55:         }
56:     }
57:
58:     return 1;
59: }
60:
61: /* finds the entry 'name' with inode 'i' in the directory 'dir' */
62: static struct buffer * find_dir_entry(struct inode *dir, struct inode *i, struct
minix_dir_entry **d_res, char *name)
63: {
64:     __blk_t block;
65:     unsigned int blksize;

```

fs/minix/namei.c

Page 2/11

```

66:         unsigned int offset, doffset;
67:         struct buffer *buf;
68:
69:         blksize = dir->sb->s_blocksize;
70:         offset = 0;
71:
72:         while(offset < dir->i_size) {
73:             if((block = bmap(dir, offset, FOR_READING)) < 0) {
74:                 break;
75:             }
76:             if(block) {
77:                 if(!(buf = bread(dir->dev, block, blksize))) {
78:                     break;
79:                 }
80:                 doffset = 0;
81:                 do {
82:                     *d_res = (struct minix_dir_entry *) (buf->data +
doffset);
83:                     if(!i) {
84:                         /* returns the first empty entry */
85:                         if(!(*d_res)->inode || (doffset + offset
>= dir->i_size)) {
86:                             if(doffset + offset >= dir->i_si
ze) {
87:                                 dir->i_size += dir->sb->
u.minix.dirsize;
88:                             }
89:                             return buf;
90:                         }
91:                     } else {
92:                         if((*d_res)->inode == i->inode) {
93:                             /* returns the first matching in
ode */
94:                             if(!name) {
95:                                 return buf;
96:                             }
97:                             /* returns the matching inode an
d name */
98:                             if(!strcmp((*d_res)->name, name)
) {
99:                                 return buf;
100:                             }
101:                         }
102:                     }
103:                     doffset += dir->sb->u.minix.dirsize;
104:                 } while(doffset < blksize);
105:                 brelse(buf);
106:                 offset += blksize;
107:             } else {
108:                 break;
109:             }
110:         }
111:
112:         *d_res = NULL;
113:         return NULL;
114:     }
115:
116: static struct buffer * add_dir_entry(struct inode *dir, struct minix_dir_entry *
*d_res)
117: {
118:     __blk_t block;
119:     struct buffer *buf;
120:
121:     if(!(buf = find_dir_entry(dir, NULL, d_res, NULL))) {
122:         if((block = bmap(dir, dir->i_size, FOR_WRITING)) < 0) {
123:             return NULL;
124:         }

```

fs/minix/namei.c

Page 3/11

```

125:         if(!(buf = bread(dir->dev, block, dir->sb->s_blocksize))) {
126:             return NULL;
127:         }
128:         *d_res = (struct minix_dir_entry *)buf->data;
129:         dir->i_size += dir->sb->u.minix.dirsize;
130:     }
131:
132:     return buf;
133: }
134:
135: static int is_prefix(struct inode *dir_new, struct inode *i_old)
136: {
137:     __ino_t inode;
138:     int errno;
139:
140:     errno = 0;
141:     for(;;) {
142:         if(dir_new == i_old) {
143:             errno = 1;
144:             break;
145:         }
146:         inode = dir_new->inode;
147:         if(minix_lookup(".", dir_new, &dir_new)) {
148:             break;
149:         }
150:         iput(dir_new); /* lookup eats 1 dir_new */
151:         if(dir_new->inode == inode) {
152:             break;
153:         }
154:     }
155:     return errno;
156: }
157:
158: int minix_lookup(const char *name, struct inode *dir, struct inode **i_res)
159: {
160:     __blk_t block;
161:     unsigned int blksize;
162:     unsigned int offset, doffset;
163:     struct buffer *buf;
164:     struct minix_dir_entry *d;
165:     __ino_t inode;
166:
167:     blksize = dir->sb->s_blocksize;
168:     inode = offset = 0;
169:     dir->count++;
170:
171:     while(offset < dir->i_size && !inode) {
172:         if((block = bmap(dir, offset, FOR_READING)) < 0) {
173:             iput(dir);
174:             return block;
175:         }
176:         if(block) {
177:             if(!(buf = bread(dir->dev, block, blksize))) {
178:                 iput(dir);
179:                 return -EIO;
180:             }
181:             doffset = 0;
182:             do {
183:                 d = (struct minix_dir_entry *) (buf->data + doffs
et);
184:                 if(d->inode) {
185:                     if(strlen(d->name) == strlen(name)) {
186:                         if(!(strcmp(d->name, name))) {
187:                             inode = d->inode;
188:                         }
189:                     }
190:                 }

```

fs/minix/namei.c

Page 4/11

```

191:             doffset += dir->sb->u.minix.dirsize;
192:         } while((doffset < blksize) && (!inode));
193:
194:         brelse(buf);
195:         if(inode) {
196:             if(!(*i_res = iget(dir->sb, inode))) {
197:                 iput(dir);
198:                 return -EACCES;
199:             }
200:             iput(dir);
201:             return 0;
202:         }
203:         offset += blksize;
204:     } else {
205:         break;
206:     }
207: }
208: iput(dir);
209: return -ENOENT;
210: }
211:
212: int minix_rmdir(struct inode *dir, struct inode *i)
213: {
214:     struct buffer *buf;
215:     struct minix_dir_entry *d;
216:
217:     inode_lock(i);
218:
219:     if(!is_dir_empty(i)) {
220:         inode_unlock(i);
221:         return -ENOTEMPTY;
222:     }
223:
224:     inode_lock(dir);
225:
226:     if(!(buf = find_dir_entry(dir, i, &d, NULL))) {
227:         inode_unlock(i);
228:         inode_unlock(dir);
229:         return -ENOENT;
230:     }
231:
232:     d->inode = 0;
233:     i->i_nlink = 0;
234:     dir->i_nlink--;
235:
236:     i->i_ctime = CURRENT_TIME;
237:     dir->i_mtime = CURRENT_TIME;
238:     dir->i_ctime = CURRENT_TIME;
239:
240:     i->dirty = 1;
241:     dir->dirty = 1;
242:
243:     bwrite(buf);
244:
245:     inode_unlock(i);
246:     inode_unlock(dir);
247:     return 0;
248: }
249:
250: int minix_link(struct inode *i_old, struct inode *dir_new, char *name)
251: {
252:     struct buffer *buf;
253:     struct minix_dir_entry *d;
254:     int n;
255:
256:     inode_lock(i_old);
257:     inode_lock(dir_new);

```

fs/minix/namei.c

Page 5/11

```

258:
259:     if (!(buf = add_dir_entry(dir_new, &d))) {
260:         inode_unlock(i_old);
261:         inode_unlock(dir_new);
262:         return -ENOSPC;
263:     }
264:
265:     d->inode = i_old->inode;
266:     for(n = 0; n < i_old->sb->u.minix.namelen; n++) {
267:         d->name[n] = name[n];
268:         if (!name[n]) {
269:             break;
270:         }
271:     }
272:     for(; n < i_old->sb->u.minix.namelen; n++) {
273:         d->name[n] = 0;
274:     }
275:
276:     i_old->i_nlink++;
277:     i_old->i_ctime = CURRENT_TIME;
278:     dir_new->i_mtime = CURRENT_TIME;
279:     dir_new->i_ctime = CURRENT_TIME;
280:
281:     i_old->dirty = 1;
282:     dir_new->dirty = 1;
283:
284:     bwrite(buf);
285:
286:     inode_unlock(i_old);
287:     inode_unlock(dir_new);
288:     return 0;
289: }
290:
291: int minix_unlink(struct inode *dir, struct inode *i, char *name)
292: {
293:     struct buffer *buf;
294:     struct minix_dir_entry *d;
295:
296:     inode_lock(dir);
297:     inode_lock(i);
298:
299:     if (!(buf = find_dir_entry(dir, i, &d, name))) {
300:         inode_unlock(dir);
301:         inode_unlock(i);
302:         return -ENOENT;
303:     }
304:
305:     d->inode = 0;
306:     i->i_nlink--;
307:
308:     i->i_ctime = CURRENT_TIME;
309:     dir->i_mtime = CURRENT_TIME;
310:     dir->i_ctime = CURRENT_TIME;
311:
312:     i->dirty = 1;
313:     dir->dirty = 1;
314:
315:     bwrite(buf);
316:
317:     inode_unlock(dir);
318:     inode_unlock(i);
319:     return 0;
320: }
321:
322: int minix_symlink(struct inode *dir, char *name, char *oldname)
323: {
324:     struct buffer *buf, *buf_new;

```

fs/minix/namei.c

Page 6/11

```

325:     struct inode *i;
326:     struct minix_dir_entry *d;
327:     unsigned int blksize;
328:     int n, block;
329:     char c;
330:
331:     inode_lock(dir);
332:
333:     if(!(i = ialloc(dir->sb))) {
334:         inode_unlock(dir);
335:         return -ENOSPC;
336:     }
337:
338:     i->i_mode = S_IFLNK | (S_IRWXU | S_IRWXG | S_IRWXO);
339:     i->i_uid = current->euid;
340:     i->i_gid = current->egid;
341:     i->i_nlink = 1;
342:     i->dev = dir->dev;
343:     i->count = 1;
344:     i->fsop = &minix_symlink_fsop;
345:     i->dirty = 1;
346:
347:     block = minix_balloc(dir->sb);
348:     if(block < 0) {
349:         i->i_nlink = 0;
350:         iput(i);
351:         inode_unlock(dir);
352:         return -ENOSPC;
353:     }
354:
355:     if(i->sb->u.minix.version == 1) {
356:         i->u.minix.u.il_zone[0] = block;
357:     } else {
358:         i->u.minix.u.i2_zone[0] = block;
359:     }
360:     blksize = dir->sb->s_blocksize;
361:     if(!(buf_new = bread(dir->dev, block, blksize))) {
362:         minix_bfree(dir->sb, block);
363:         i->i_nlink = 0;
364:         iput(i);
365:         inode_unlock(dir);
366:         return -EIO;
367:     }
368:
369:     if(!(buf = add_dir_entry(dir, &d))) {
370:         minix_bfree(dir->sb, block);
371:         i->i_nlink = 0;
372:         iput(i);
373:         inode_unlock(dir);
374:         return -ENOSPC;
375:     }
376:
377:     d->inode = i->inode;
378:     for(n = 0; n < i->sb->u.minix.namelen; n++) {
379:         d->name[n] = name[n];
380:         if(!name[n]) {
381:             break;
382:         }
383:     }
384:     for(; n < i->sb->u.minix.namelen; n++) {
385:         d->name[n] = 0;
386:     }
387:
388:     for(n = 0; n < NAME_MAX; n++) {
389:         if((c = oldname[n])) {
390:             buf_new->data[n] = c;
391:             continue;

```


fs/minix/namei.c

Page 7/11

```

392:         }
393:         break;
394:     }
395:     buf_new->data[n] = 0;
396:     i->i_size = n;
397:
398:     dir->i_mtime = CURRENT_TIME;
399:     dir->i_ctime = CURRENT_TIME;
400:     dir->dirty = 1;
401:
402:     bwrite(buf);
403:     bwrite(buf_new);
404:     iput(i);
405:     inode_unlock(dir);
406:     return 0;
407: }
408:
409: int minix_mkdir(struct inode *dir, char *name, __mode_t mode)
410: {
411:     struct buffer *buf, *buf_new;
412:     struct inode *i;
413:     struct minix_dir_entry *d, *d_new;
414:     unsigned int blksize;
415:     int n, block;
416:
417:     if(strlen(name) > dir->sb->u.minix.namelen) {
418:         return -ENAMETOOLONG;
419:     }
420:
421:     inode_lock(dir);
422:
423:     if(!(i = ialloc(dir->sb))) {
424:         inode_unlock(dir);
425:         return -ENOSPC;
426:     }
427:
428:     i->i_mode = ((mode & (S_IRWXU | S_IRWXG | S_IRWXO)) & ~current->umask);
429:     i->i_mode |= S_IFDIR;
430:     i->i_uid = current->euid;
431:     i->i_gid = current->egid;
432:     i->i_nlink = 1;
433:     i->dev = dir->dev;
434:     i->count = 1;
435:     i->fsop = &minix_dir_fsop;
436:     i->dirty = 1;
437:
438:     if((block = bmap(i, 0, FOR_WRITING)) < 0) {
439:         i->i_nlink = 0;
440:         iput(i);
441:         inode_unlock(dir);
442:         return -ENOSPC;
443:     }
444:
445:     blksize = dir->sb->s_blocksize;
446:     if(!(buf_new = bread(i->dev, block, blksize))) {
447:         minix_bfree(dir->sb, block);
448:         i->i_nlink = 0;
449:         iput(i);
450:         inode_unlock(dir);
451:         return -EIO;
452:     }
453:
454:     if(!(buf = add_dir_entry(dir, &d))) {
455:         minix_bfree(dir->sb, block);
456:         i->i_nlink = 0;
457:         iput(i);
458:         inode_unlock(dir);

```

fs/minix/namei.c

Page 8/11

```

459:         return -ENOSPC;
460:     }
461:
462:     d->inode = i->inode;
463:     for(n = 0; n < i->sb->u.minix.namelen; n++) {
464:         d->name[n] = name[n];
465:         if(!name[n] || name[n] == '/') {
466:             break;
467:         }
468:     }
469:     for(; n < i->sb->u.minix.namelen; n++) {
470:         d->name[n] = 0;
471:     }
472:
473:     d_new = (struct minix_dir_entry *)buf_new->data;
474:     d_new->inode = i->inode;
475:     d_new->name[0] = '.';
476:     d_new->name[1] = 0;
477:     i->i_size += i->sb->u.minix.dirsize;
478:     i->i_nlink++;
479:     d_new = (struct minix_dir_entry *)(buf_new->data + i->sb->u.minix.dirsiz
e);
480:     d_new->inode = dir->inode;
481:     d_new->name[0] = '.';
482:     d_new->name[1] = '.';
483:     d_new->name[2] = 0;
484:     i->i_size += i->sb->u.minix.dirsize;
485:
486:     dir->i_mtime = CURRENT_TIME;
487:     dir->i_ctime = CURRENT_TIME;
488:     dir->i_nlink++;
489:     dir->dirty = 1;
490:
491:     bwrite(buf);
492:     bwrite(buf_new);
493:     iput(i);
494:     inode_unlock(dir);
495:     return 0;
496: }
497:
498: int minix_mknod(struct inode *dir, char *name, __mode_t mode, __dev_t dev)
499: {
500:     struct buffer *buf;
501:     struct inode *i;
502:     struct minix_dir_entry *d;
503:     int n;
504:
505:     inode_lock(dir);
506:
507:     if(!(i = ialloc(dir->sb))) {
508:         inode_unlock(dir);
509:         return -ENOSPC;
510:     }
511:
512:     if(!(buf = add_dir_entry(dir, &d))) {
513:         i->i_nlink = 0;
514:         iput(i);
515:         inode_unlock(dir);
516:         return -ENOSPC;
517:     }
518:
519:     d->inode = i->inode;
520:     for(n = 0; n < i->sb->u.minix.namelen; n++) {
521:         d->name[n] = name[n];
522:         if(!name[n]) {
523:             break;
524:         }

```

fs/minix/namei.c

Page 9/11

```

525:         }
526:         for(; n < i->sb->u.minix.namelen; n++) {
527:             d->name[n] = 0;
528:         }
529:
530:         i->i_mode = (mode & ~current->umask) & ~S_IFMT;
531:         i->i_uid = current->euid;
532:         i->i_gid = current->egid;
533:         i->i_nlink = 1;
534:         i->dev = dir->dev;
535:         i->count = 1;
536:         i->dirty = 1;
537:
538:         switch(mode & S_IFMT) {
539:             case S_IFCHR:
540:                 i->fsop = &def_chr_fsop;
541:                 i->rdev = dev;
542:                 i->i_mode |= S_IFCHR;
543:                 break;
544:             case S_IFBLK:
545:                 i->fsop = &def_blk_fsop;
546:                 i->rdev = dev;
547:                 i->i_mode |= S_IFBLK;
548:                 break;
549:             case S_IFIFO:
550:                 i->fsop = &pipefs_fsop;
551:                 i->i_mode |= S_IFIFO;
552:                 /* it's a union so we need to clear pipefs_i */
553:                 memset_b(&i->u.pipefs, NULL, sizeof(struct pipefs_inode)
);
554:                 break;
555:         }
556:
557:         dir->i_mtime = CURRENT_TIME;
558:         dir->i_ctime = CURRENT_TIME;
559:         dir->dirty = 1;
560:
561:         bwrite(buf);
562:         iput(i);
563:         inode_unlock(dir);
564:         return 0;
565:     }
566:
567: int minix_create(struct inode *dir, char *name, __mode_t mode, struct inode **i_
res)
568: {
569:     struct buffer *buf;
570:     struct inode *i;
571:     struct minix_dir_entry *d;
572:     int n;
573:
574:     if(IS_RDONLY_FS(dir)) {
575:         return -EROFS;
576:     }
577:
578:     inode_lock(dir);
579:
580:     if(!(i = ialloc(dir->sb))) {
581:         inode_unlock(dir);
582:         return -ENOSPC;
583:     }
584:
585:     if(!(buf = add_dir_entry(dir, &d))) {
586:         i->i_nlink = 0;
587:         iput(i);
588:         inode_unlock(dir);
589:         return -ENOSPC;

```

fs/minix/namei.c

Page 10/11

```

590:         }
591:
592:         d->inode = i->inode;
593:         for(n = 0; n < i->sb->u.minix.namelen; n++) {
594:             d->name[n] = name[n];
595:             if(!name[n]) {
596:                 break;
597:             }
598:         }
599:         for(; n < i->sb->u.minix.namelen; n++) {
600:             d->name[n] = 0;
601:         }
602:
603:         i->i_mode = (mode & ~current->umask) & ~S_IFMT;
604:         i->i_mode |= S_IFREG;
605:         i->i_uid = current->euid;
606:         i->i_gid = current->egid;
607:         i->i_nlink = 1;
608:         i->dev = dir->dev;
609:         i->fsop = &minix_file_fsop;
610:         i->count = 1;
611:         i->dirty = 1;
612:
613:         dir->i_mtime = CURRENT_TIME;
614:         dir->i_ctime = CURRENT_TIME;
615:         dir->dirty = 1;
616:
617:         *i_res = i;
618:         bwrite(buf);
619:         inode_unlock(dir);
620:         return 0;
621:     }
622:
623: int minix_rename(struct inode *i_old, struct inode *dir_old, struct inode *i_new
, struct inode *dir_new, char *oldpath, char *newpath)
624: {
625:     struct buffer *buf_old, *buf_new;
626:     struct minix_dir_entry *d_old, *d_new;
627:     int errno;
628:
629:     errno = 0;
630:     buf_new = NULL;
631:
632:     if(is_prefix(dir_new, i_old)) {
633:         return -EINVAL;
634:     }
635:
636:     inode_lock(i_old);
637:     inode_lock(dir_old);
638:     if(dir_old != dir_new) {
639:         inode_lock(dir_new);
640:     }
641:
642:     if(!(buf_old = find_dir_entry(dir_old, i_old, &d_old, oldpath))) {
643:         errno = -ENOENT;
644:         goto end;
645:     }
646:     if(dir_old == dir_new) {
647:         buf_old->locked = 0;
648:     }
649:
650:     if(i_new) {
651:         if(S_ISDIR(i_old->i_mode)) {
652:             if(!is_dir_empty(i_new)) {
653:                 brelse(buf_old);
654:                 errno = -ENOTEMPTY;
655:                 goto end;

```

fs/minix/namei.c

Page 11/11

```
656:                }
657:            }
658:            if(!(buf_new = find_dir_entry(dir_new, i_new, &d_new, newpath)))
{
659:                brelse(buf_old);
660:                errno = -ENOENT;
661:                goto end;
662:            }
663:        } else {
664:            if(!(buf_new = add_dir_entry(dir_new, &d_new))) {
665:                brelse(buf_old);
666:                errno = -ENOSPC;
667:                goto end;
668:            }
669:        }
670:        if(i_new) {
671:            i_new->i_nlink--;
672:        } else {
673:            i_new = i_old;
674:            strcpy(d_new->name, newpath);
675:        }
676:
677:        d_old->inode = 0;
678:        d_new->inode = i_old->inode;
679:        dir_new->i_mtime = CURRENT_TIME;
680:        dir_new->i_ctime = CURRENT_TIME;
681:        i_new->dirty = 1;
682:        dir_new->dirty = 1;
683:
684:        dir_old->i_mtime = CURRENT_TIME;
685:        dir_old->i_ctime = CURRENT_TIME;
686:        i_old->dirty = 1;
687:        dir_old->dirty = 1;
688:
689:        bwrite(buf_old);
690:        if(buf_new) {
691:            bwrite(buf_new);
692:        }
693:
694:    end:
695:        inode_unlock(i_old);
696:        inode_unlock(dir_old);
697:        inode_unlock(dir_new);
698:        return errno;
699:    }
```

fs/minix/super.c

Page 1/5

```

1: /*
2:  * fiwix/fs/minix/super.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/types.h>
10: #include <fiwix/errno.h>
11: #include <fiwix/fs.h>
12: #include <fiwix/filesystems.h>
13: #include <fiwix/fs_minix.h>
14: #include <fiwix/buffer.h>
15: #include <fiwix/sched.h>
16: #include <fiwix/stdio.h>
17: #include <fiwix/string.h>
18:
19: struct fs_operations minix_fsop = {
20:     FSOP_REQUIRES_DEV,
21:     NULL,
22:
23:     NULL,          /* open */
24:     NULL,          /* close */
25:     NULL,          /* read */
26:     NULL,          /* write */
27:     NULL,          /* ioctl */
28:     NULL,          /* lseek */
29:     NULL,          /* readdir */
30:     NULL,          /* mmap */
31:     NULL,          /* select */
32:
33:     NULL,          /* readlink */
34:     NULL,          /* followlink */
35:     NULL,          /* bmap */
36:     NULL,          /* lookup */
37:     NULL,          /* rmdir */
38:     NULL,          /* link */
39:     NULL,          /* unlink */
40:     NULL,          /* symlink */
41:     NULL,          /* mkdir */
42:     NULL,          /* mknod */
43:     NULL,          /* truncate */
44:     NULL,          /* create */
45:     NULL,          /* rename */
46:
47:     NULL,          /* read_block */
48:     NULL,          /* write_block */
49:
50:     minix_read_inode,
51:     minix_write_inode,
52:     minix_ialloc,
53:     minix_ifree,
54:     minix_statfs,
55:     minix_read_superblock,
56:     minix_remount_fs,
57:     minix_write_superblock,
58:     minix_release_superblock
59: };
60:
61: static void check_superblock(struct minix_super_block *sb)
62: {
63:     if(!(sb->s_state & MINIX_VALID_FS)) {
64:         printk("WARNING: filesystem not checked, fsck recommended.\n");
65:     }
66:     if(sb->s_state & MINIX_ERROR_FS) {
67:         printk("WARNING: filesystem contains errors, fsck recommended.\n

```

fs/minix/super.c

Page 2/5

```

");
68:         }
69:     }
70:
71: void minix_statfs(struct superblock *sb, struct statfs *statfsbuf)
72: {
73:     statfsbuf->f_type = sb->u.minix.sb.s_magic;
74:     statfsbuf->f_bsize = sb->s_blocksize;
75:     statfsbuf->f_blocks = sb->u.minix.nzones << sb->u.minix.sb.s_log_zone_si
ze;
76:     statfsbuf->f_bfree = sb->u.minix.nzones - minix_count_free_blocks(sb);
77:     statfsbuf->f_bavail = statfsbuf->f_bfree;
78:
79:     statfsbuf->f_files = sb->u.minix.sb.s_ninodes;
80:     statfsbuf->f_ffree = sb->u.minix.sb.s_ninodes - minix_count_free_inodes(
sb);
81:     /* statfsbuf->f_fsid = ? */
82:     statfsbuf->f_namelen = sb->u.minix.namelen;
83: }
84:
85: int minix_read_superblock(__dev_t dev, struct superblock *sb)
86: {
87:     struct buffer *buf;
88:     int maps;
89:
90:     superblock_lock(sb);
91:     if(!(buf = bread(dev, SUPERBLOCK, BLKSIZE_1K))) {
92:         printk("WARNING: %s(): I/O error on device %d,%d.\n", __FUNCTION
__, MAJOR(dev), MINOR(dev));
93:         superblock_unlock(sb);
94:         return -EIO;
95:     }
96:     memcpy_b(&sb->u.minix.sb, buf->data, sizeof(struct minix_super_block));
97:
98:     switch(sb->u.minix.sb.s_magic) {
99:         case MINIX_SUPER_MAGIC:
100:             sb->u.minix.namelen = 14;
101:             sb->u.minix.dirsize = sizeof(__u16) + sb->u.minix.namele
n;
102:             sb->u.minix.version = 1;
103:             sb->u.minix.nzones = sb->u.minix.sb.s_nzones;
104:             printk("minix v1 (14 char names) filesystem detected on
device %d,%d.\n", MAJOR(dev), MINOR(dev));
105:             break;
106:         case MINIX_SUPER_MAGIC2:
107:             sb->u.minix.namelen = 30;
108:             sb->u.minix.dirsize = sizeof(__u16) + sb->u.minix.namele
n;
109:             sb->u.minix.version = 1;
110:             sb->u.minix.nzones = sb->u.minix.sb.s_nzones;
111:             printk("minix v1 (30 char names) filesystem detected on
device %d,%d.\n", MAJOR(dev), MINOR(dev));
112:             break;
113:         case MINIX2_SUPER_MAGIC:
114:             sb->u.minix.namelen = 14;
115:             sb->u.minix.dirsize = sizeof(__u16) + sb->u.minix.namele
n;
116:             sb->u.minix.version = 2;
117:             sb->u.minix.nzones = sb->u.minix.sb.s_zones;
118:             printk("minix v2 (14 char names) filesystem detected on
device %d,%d.\n", MAJOR(dev), MINOR(dev));
119:             break;
120:         case MINIX2_SUPER_MAGIC2:
121:             sb->u.minix.namelen = 30;
122:             sb->u.minix.dirsize = sizeof(__u16) + sb->u.minix.namele
n;
123:             sb->u.minix.version = 2;

```

fs/minix/super.c

Page 3/5

```

124:             sb->u.minix.nzones = sb->u.minix.sb.s_zones;
125:             printk("minix v2 (30 char names) filesystem detected on
device %d,%d.\n", MAJOR(dev), MINOR(dev));
126:             break;
127:             default:
128:             printk("ERROR: %s(): invalid filesystem type or bad supe
rblock on device %d,%d.\n", __FUNCTION__, MAJOR(dev), MINOR(dev));
129:             superblock_unlock(sb);
130:             brelse(buf);
131:             return -EINVAL;
132:         }
133:
134:         sb->dev = dev;
135:         sb->fsop = &minix_fsop;
136:         sb->s_blocksize = BLKSIZE_1K << sb->u.minix.sb.s_log_zone_size;
137:
138:         if(sb->s_blocksize != BLKSIZE_1K) {
139:             printk("ERROR: %s(): block sizes > %d not supported in this file
system.\n", __FUNCTION__, BLKSIZE_1K);
140:             superblock_unlock(sb);
141:             brelse(buf);
142:             return -EINVAL;
143:         }
144:
145:         /*
146:         printk("s_ninodes          = %d\n", sb->u.minix.sb.s_ninodes);
147:         printk("s_nzones          = %d (nzones = %d)\n", sb->u.minix.sb.s_nzones,
sb->u.minix.nzones);
148:         printk("s_imap_blocks     = %d\n", sb->u.minix.sb.s_imap_blocks);
149:         printk("s_zmap_blocks     = %d\n", sb->u.minix.sb.s_zmap_blocks);
150:         printk("s_firstdatazone = %d\n", sb->u.minix.sb.s_firstdatazone);
151:         printk("s_log_zone_size  = %d\n", sb->u.minix.sb.s_log_zone_size);
152:         printk("s_max_size       = %d\n", sb->u.minix.sb.s_max_size);
153:         printk("s_magic          = %x\n", sb->u.minix.sb.s_magic);
154:         printk("s_state          = %d\n", sb->u.minix.sb.s_state);
155:         printk("s_zones          = %d\n", sb->u.minix.sb.s_zones);
156:         */
157:
158:         /* Minix fs size is limited to: # of bitmaps * 8192 * 1024 */
159:         if(sb->u.minix.version == 1) {
160:             maps = V1_MAX_BITMAP_BLOCKS;    /* 64MB limit */
161:         }
162:         if(sb->u.minix.version == 2) {
163:             maps = V2_MAX_BITMAP_BLOCKS;    /* 1GB limit */
164:         }
165:
166:         if(sb->u.minix.sb.s_imap_blocks > maps) {
167:             printk("ERROR: %s(): number of imap blocks (%d) is greater than
%d!\n", __FUNCTION__, sb->u.minix.sb.s_imap_blocks, maps);
168:             superblock_unlock(sb);
169:             brelse(buf);
170:             return -EINVAL;
171:         }
172:         if(sb->u.minix.sb.s_zmap_blocks > maps) {
173:             printk("ERROR: %s(): number of zmap blocks (%d) is greater than
%d!\n", __FUNCTION__, sb->u.minix.sb.s_zmap_blocks, maps);
174:             superblock_unlock(sb);
175:             brelse(buf);
176:             return -EINVAL;
177:         }
178:
179:         superblock_unlock(sb);
180:
181:         if(!(sb->root = iget(sb, MINIX_ROOT_INO))) {
182:             printk("ERROR: %s(): unable to get root inode.\n", __FUNCTION__
);
183:             brelse(buf);

```


fs/minix/super.c

Page 4/5

```

184:         return -EINVAL;
185:     }
186:
187:     check_superblock(&sb->u.minix.sb);
188:
189:     if(!(sb->flags & MS_RDONLY)) {
190:         sb->u.minix.sb.s_state &= ~MINIX_VALID_FS;
191:         memcpy_b(buf->data, &sb->u.minix.sb, sizeof(struct minix_super_b
lock));
192:         bwrite(buf);
193:     } else {
194:         brelse(buf);
195:     }
196:
197:     return 0;
198: }
199:
200: int minix_remount_fs(struct superblock *sb, int flags)
201: {
202:     struct buffer *buf;
203:     struct minix_super_block *ms;
204:
205:     if((flags & MS_RDONLY) == (sb->flags & MS_RDONLY)) {
206:         return 0;
207:     }
208:
209:     superblock_lock(sb);
210:     if(!(buf = bread(sb->dev, SUPERBLOCK, BLKSIZE_1K))) {
211:         superblock_unlock(sb);
212:         return -EIO;
213:     }
214:     ms = (struct minix_super_block *)buf->data;
215:
216:     if(flags & MS_RDONLY) {
217:         /* switching from RW to RO */
218:         sb->u.minix.sb.s_state |= MINIX_VALID_FS;
219:         ms->s_state |= MINIX_VALID_FS;
220:     } else {
221:         /* switching from RO to RW */
222:         check_superblock(ms);
223:         sb->u.minix.sb.s_state &= ~MINIX_VALID_FS;
224:         ms->s_state &= ~MINIX_VALID_FS;
225:     }
226:
227:     sb->dirty = 1;
228:     superblock_unlock(sb);
229:     bwrite(buf);
230:     return 0;
231: }
232:
233: int minix_write_superblock(struct superblock *sb)
234: {
235:     struct buffer *buf;
236:
237:     superblock_lock(sb);
238:     if(!(buf = bread(sb->dev, SUPERBLOCK, BLKSIZE_1K))) {
239:         superblock_unlock(sb);
240:         return -EIO;
241:     }
242:
243:     memcpy_b(buf->data, &sb->u.minix.sb, sizeof(struct minix_super_block));
244:     sb->dirty = 0;
245:     superblock_unlock(sb);
246:     bwrite(buf);
247:     return 0;
248: }
249:

```

fs/minix/super.c

Page 5/5

```
250: void minix_release_superblock(struct superblock *sb)
251: {
252:     if(sb->flags & MS_RDONLY) {
253:         return;
254:     }
255:
256:     superblock_lock(sb);
257:
258:     sb->u.minix.sb.s_state |= MINIX_VALID_FS;
259:     sb->dirty = 1;
260:
261:     superblock_unlock(sb);
262: }
263:
264: int minix_init(void)
265: {
266:     return register_filesystem("minix", &minix_fsop);
267: }
```

fs/minix/symlink.c

Page 1/3

```

1: /*
2:  * fiwix/fs/minix/symlink.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/errno.h>
10: #include <fiwix/buffer.h>
11: #include <fiwix/fs.h>
12: #include <fiwix/filesystems.h>
13: #include <fiwix/stat.h>
14: #include <fiwix/stdio.h>
15: #include <fiwix/string.h>
16:
17: struct fs_operations minix_symlink_fsop = {
18:     0,
19:     0,
20:
21:     NULL, /* open */
22:     NULL, /* close */
23:     NULL, /* read */
24:     NULL, /* write */
25:     NULL, /* ioctl */
26:     NULL, /* lseek */
27:     NULL, /* readdir */
28:     NULL, /* mmap */
29:     NULL, /* select */
30:
31:     minix_readlink,
32:     minix_followlink,
33:     NULL, /* bmap */
34:     NULL, /* lookup */
35:     NULL, /* rmdir */
36:     NULL, /* link */
37:     NULL, /* unlink */
38:     NULL, /* symlink */
39:     NULL, /* mkdir */
40:     NULL, /* mknod */
41:     NULL, /* truncate */
42:     NULL, /* create */
43:     NULL, /* rename */
44:
45:     NULL, /* read_block */
46:     NULL, /* write_block */
47:
48:     NULL, /* read_inode */
49:     NULL, /* write_inode */
50:     NULL, /* ialloc */
51:     NULL, /* ifree */
52:     NULL, /* statfs */
53:     NULL, /* read_superblock */
54:     NULL, /* remount_fs */
55:     NULL, /* write_superblock */
56:     NULL, /* release_superblock */
57: };
58:
59: int minix_readlink(struct inode *i, char *buffer, __size_t count)
60: {
61:     __u32 blksize;
62:     struct buffer *buf;
63:
64:     if(!S_ISLNK(i->i_mode)) {
65:         printk("%s(): Oops, inode '%d' is not a symlink (!?).\n", __FUNC
TION__, i->inode);
66:         return 0;

```

fs/minix/symlink.c

Page 2/3

```

67:         }
68:
69:         inode_lock(i);
70:         blksize = i->sb->s_blocksize;
71:         count = MIN(count, i->i_size);
72:         if(!count) {
73:             inode_unlock(i);
74:             return 0;
75:         }
76:         count = MIN(count, blksize);
77:         if(i->sb->u.minix.version == 1) {
78:             if(!(buf = bread(i->dev, i->u.minix.u.i1_zone[0], blksize))) {
79:                 inode_unlock(i);
80:                 return -EIO;
81:             }
82:         } else {
83:             if(!(buf = bread(i->dev, i->u.minix.u.i2_zone[0], blksize))) {
84:                 inode_unlock(i);
85:                 return -EIO;
86:             }
87:         }
88:         memcpy_b(buffer, buf->data, count);
89:         brelse(buf);
90:         buffer[count] = NULL;
91:         inode_unlock(i);
92:         return count;
93:     }
94:
95: int minix_followlink(struct inode *dir, struct inode *i, struct inode **i_res)
96: {
97:     struct buffer *buf;
98:     char *name;
99:     __ino_t errno;
100:
101:     if(!i) {
102:         return -ENOENT;
103:     }
104:
105:     if(!S_ISLNK(i->i_mode)) {
106:         printk("%s(): Oops, inode '%d' is not a symlink (!?).\n", __FUNC
TION__, i->inode);
107:         return 0;
108:     }
109:
110:     if(current->loopcnt > MAX_SYMLINKS) {
111:         printk("%s(): too many nested symbolic links!\n", __FUNCTION__);
112:         return -ELOOP;
113:     }
114:
115:     inode_lock(i);
116:     if(i->sb->u.minix.version == 1) {
117:         if(!(buf = bread(i->dev, i->u.minix.u.i1_zone[0], i->sb->s_block
size))) {
118:             inode_unlock(i);
119:             return -EIO;
120:         }
121:     } else {
122:         if(!(buf = bread(i->dev, i->u.minix.u.i2_zone[0], i->sb->s_block
size))) {
123:             inode_unlock(i);
124:             return -EIO;
125:         }
126:     }
127:     name = buf->data;
128:     inode_unlock(i);
129:
130:     current->loopcnt++;

```

fs/minix/symlink.c

Page 3/3

```
131:         iput(i);
132:         brelse(buf);
133:         errno = parse_namei(name, dir, i_res, NULL, FOLLOW_LINKS);
134:         current->loopcnt--;
135:         return errno;
136: }
```

fs/minix/v1_inode.c

Page 1/7

```

1: /*
2:  * fiwix/fs/minix/v1_inode.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/filesystems.h>
11: #include <fiwix/fs_minix.h>
12: #include <fiwix/fs_pipe.h>
13: #include <fiwix/statfs.h>
14: #include <fiwix/sleep.h>
15: #include <fiwix/stat.h>
16: #include <fiwix/sched.h>
17: #include <fiwix/buffer.h>
18: #include <fiwix/process.h>
19: #include <fiwix/errno.h>
20: #include <fiwix/stdio.h>
21: #include <fiwix/string.h>
22:
23: #define BLOCKS_PER_IND_BLOCK(sb)          (sb->s_blocksize / sizeof(__u16))
24: #define MINIX_INODES_PER_BLOCK(sb)       (sb->s_blocksize / sizeof(struct minix_i
node))
25:
26: #define MINIX_NDIR_BLOCKS                  7
27: #define MINIX_IND_BLOCK                   MINIX_NDIR_BLOCKS
28: #define MINIX_DIND_BLOCK                  (MINIX_NDIR_BLOCKS + 1)
29:
30: static void free_zone(struct inode *i, int block, int offset)
31: {
32:     int n;
33:     struct buffer *buf;
34:     __u16 *zone;
35:
36:     if(!(buf = bread(i->dev, block, i->sb->s_blocksize))) {
37:         printk("WARNING: %s(): error reading block %d.\n", __FUNCTION__,
block);
38:         return;
39:     }
40:     zone = (__u16 *)buf->data;
41:     for(n = offset; n < BLOCKS_PER_IND_BLOCK(i->sb); n++) {
42:         if(zone[n]) {
43:             minix_bfree(i->sb, zone[n]);
44:             zone[n] = 0;
45:         }
46:     }
47:     bwrite(buf);
48: }
49:
50: int v1_minix_read_inode(struct inode *i)
51: {
52:     __ino_t block;
53:     short int offset;
54:     struct minix_inode *ii;
55:     struct buffer *buf;
56:     int errno;
57:
58:     block = 1 + SUPERBLOCK + i->sb->u.minix.sb.s_imap_blocks + i->sb->u.mini
x.sb.s_zmap_blocks + (i->inode - 1) / MINIX_INODES_PER_BLOCK(i->sb);
59:
60:     if(!(buf = bread(i->dev, block, i->sb->s_blocksize))) {
61:         return -EIO;
62:     }
63:     offset = (i->inode - 1) % MINIX_INODES_PER_BLOCK(i->sb);
64:     ii = ((struct minix_inode *)buf->data) + offset;

```

fs/minix/v1_inode.c

Page 2/7

```

65:
66:     i->i_mode = ii->i_mode;
67:     i->i_uid = ii->i_uid;
68:     i->i_size = ii->i_size;
69:     i->i_atime = ii->i_time;
70:     i->i_ctime = ii->i_time;
71:     i->i_mtime = ii->i_time;
72:     i->i_gid = ii->i_gid;
73:     i->i_nlink = ii->i_nlinks;
74:     memcpy_b(i->u.minix.u.il_zone, ii->i_zone, sizeof(ii->i_zone));
75:     i->count = 1;
76:
77:     errno = 0;
78:     switch(i->i_mode & S_IFMT) {
79:         case S_IFCHR:
80:             i->fsop = &def_chr_fsop;
81:             i->rdev = ii->i_zone[0];
82:             break;
83:         case S_IFBLK:
84:             i->fsop = &def_blk_fsop;
85:             i->rdev = ii->i_zone[0];
86:             break;
87:         case S_IFIFO:
88:             i->fsop = &pipefs_fsop;
89:             /* it's a union so we need to clear pipefs_i */
90:             memset_b(&i->u.pipefs, NULL, sizeof(struct pipefs_inode)
);
91:             break;
92:         case S_IFDIR:
93:             i->fsop = &minix_dir_fsop;
94:             break;
95:         case S_IFREG:
96:             i->fsop = &minix_file_fsop;
97:             break;
98:         case S_IFLNK:
99:             i->fsop = &minix_symlink_fsop;
100:            break;
101:         case S_IFSOCK:
102:             i->fsop = NULL;
103:             break;
104:         default:
105:             printk("WARNING: %s(): invalid inode (%d) mode %o.\n", _
_FUNCTION__, i->inode, i->i_mode);
106:             errno = -ENOENT;
107:             break;
108:     }
109:
110:     brelse(buf);
111:     return errno;
112: }
113:
114: int v1_minix_write_inode(struct inode *i)
115: {
116:     __ino_t block;
117:     short int offset;
118:     struct minix_inode *ii;
119:     struct buffer *buf;
120:
121:     block = 1 + SUPERBLOCK + i->sb->u.minix.sb.s_imap_blocks + i->sb->u.mini
x.sb.s_zmap_blocks + (i->inode - 1) / MINIX_INODES_PER_BLOCK(i->sb);
122:
123:     if(!(buf = bread(i->dev, block, i->sb->s_blocksize))) {
124:         return -EIO;
125:     }
126:     offset = (i->inode - 1) % MINIX_INODES_PER_BLOCK(i->sb);
127:     ii = ((struct minix_inode *)buf->data) + offset;
128:

```

fs/minix/v1_inode.c

Page 3/7

```

129:         ii->i_mode = i->i_mode;
130:         ii->i_uid = i->i_uid;
131:         ii->i_size = i->i_size;
132:         ii->i_time = i->i_mtime;
133:         ii->i_gid = i->i_gid;
134:         ii->i_nlinks = i->i_nlink;
135:         if(S_ISCHR(i->i_mode) || S_ISBLK(i->i_mode)) {
136:             ii->i_zone[0] = i->rdev;
137:         } else {
138:             memcpy_b(ii->i_zone, i->u.minix.u.il_zone, sizeof(i->u.minix.u.i
l_zone));
139:         }
140:         i->dirty = 0;
141:         bwrite(buf);
142:         return 0;
143:     }
144:
145: int v1_minix_ialloc(struct inode *i)
146: {
147:     __blk_t offset;
148:     int inode, errno;
149:     struct superblock *sb;
150:
151:     sb = i->sb;
152:     superblock_lock(sb);
153:
154:     offset = 1 + SUPERBLOCK;
155:
156:     if(!(inode = minix_find_first_zero(sb, offset, sb->u.minix.sb.s_ninodes,
offset + sb->u.minix.sb.s_imap_blocks))) {
157:         superblock_unlock(sb);
158:         return -ENOSPC;
159:     }
160:
161:     errno = minix_change_bit(SET_BIT, sb, offset, inode);
162:
163:     if(errno) {
164:         if(errno < 0) {
165:             printk("WARNING: %s(): unable to set inode %d.\n", __FUN
CTION__, i->inode);
166:         } else {
167:             printk("WARNING: %s(): inode %d is already marked as use
d!\n", __FUNCTION__, i->inode);
168:         }
169:     }
170:
171:     i->inode = inode;
172:     i->i_atime = CURRENT_TIME;
173:     i->i_mtime = CURRENT_TIME;
174:     i->i_ctime = CURRENT_TIME;
175:     superblock_unlock(sb);
176:     return 0;
177: }
178:
179: void v1_minix_ifree(struct inode *i)
180: {
181:     int errno;
182:     struct superblock *sb;
183:
184:     minix_truncate(i, 0);
185:
186:     sb = i->sb;
187:     superblock_lock(sb);
188:
189:     errno = minix_change_bit(CLEAR_BIT, i->sb, 1 + SUPERBLOCK, i->inode);
190:
191:     if(errno) {

```


fs/minix/v1_inode.c

Page 4/7

```

192:             if(errno < 0) {
193:                 printk("WARNING: %s(): unable to clear inode %d.\n", __F
UNCTION__, i->inode);
194:             } else {
195:                 printk("WARNING: %s(): inode %d is already marked as fre
e!\n", __FUNCTION__, i->inode);
196:             }
197:         }
198:
199:         i->i_size = 0;
200:         i->i_mtime = CURRENT_TIME;
201:         i->i_ctime = CURRENT_TIME;
202:         i->dirty = 1;
203:         superblock_unlock(sb);
204:     }
205:
206: int v1_minix_bmap(struct inode *i, __off_t offset, int mode)
207: {
208:     unsigned char level;
209:     __ul6 *indblock, *dindblock;
210:     __blk_t block, iblock, dblock, newblock;
211:     int blksize;
212:     struct buffer *buf, *buf2, *buf3;
213:
214:     blksize = i->sb->s_blocksize;
215:     block = offset / blksize;
216:     level = 0;
217:
218:     if(block < MINIX_NDIR_BLOCKS) {
219:         level = MINIX_NDIR_BLOCKS - 1;
220:     } else {
221:         if(block < (BLOCKS_PER_IND_BLOCK(i->sb) + MINIX_NDIR_BLOCKS)) {
222:             level = MINIX_IND_BLOCK;
223:         } else {
224:             level = MINIX_DIND_BLOCK;
225:         }
226:         block -= MINIX_NDIR_BLOCKS;
227:     }
228:
229:     if(level < MINIX_NDIR_BLOCKS) {
230:         if(!i->u.minix.u.il_zone[block] && mode == FOR_WRITING) {
231:             if((newblock = minix_balloc(i->sb)) < 0) {
232:                 return -ENOSPC;
233:             }
234:             /* initialize the new block */
235:             if(!(buf = bread(i->dev, newblock, blksize))) {
236:                 minix_bfree(i->sb, newblock);
237:                 return -EIO;
238:             }
239:             memset_b(buf->data, 0, blksize);
240:             bwrite(buf);
241:             i->u.minix.u.il_zone[block] = newblock;
242:         }
243:         return i->u.minix.u.il_zone[block];
244:     }
245:
246:     if(!i->u.minix.u.il_zone[level]) {
247:         if(mode == FOR_WRITING) {
248:             if((newblock = minix_balloc(i->sb)) < 0) {
249:                 return -ENOSPC;
250:             }
251:             /* initialize the new block */
252:             if(!(buf = bread(i->dev, newblock, blksize))) {
253:                 minix_bfree(i->sb, newblock);
254:                 return -EIO;
255:             }
256:             memset_b(buf->data, 0, blksize);

```

```

257:                bwrite(buf);
258:                i->u.minix.u.il_zone[level] = newblock;
259:            } else {
260:                return 0;
261:            }
262:        }
263:        if(!(buf = bread(i->dev, i->u.minix.u.il_zone[level], blksize))) {
264:            return -EIO;
265:        }
266:        indblock = (__u16 *)buf->data;
267:        dblock = block - BLOCKS_PER_IND_BLOCK(i->sb);
268:
269:        if(level == MINIX_DIND_BLOCK) {
270:            block = dblock / BLOCKS_PER_IND_BLOCK(i->sb);
271:        }
272:
273:        if(!indblock[block]) {
274:            if(mode == FOR_WRITING) {
275:                if((newblock = minix_balloc(i->sb)) < 0) {
276:                    brelse(buf);
277:                    return -ENOSPC;
278:                }
279:                /* initialize the new block */
280:                if(!(buf2 = bread(i->dev, newblock, blksize))) {
281:                    minix_bfree(i->sb, newblock);
282:                    brelse(buf);
283:                    return -EIO;
284:                }
285:                memset_b(buf2->data, 0, blksize);
286:                bwrite(buf2);
287:                indblock[block] = newblock;
288:                if(level == MINIX_IND_BLOCK) {
289:                    bwrite(buf);
290:                    return newblock;
291:                }
292:                buf->dirty = 1;
293:                buf->valid = 1;
294:            } else {
295:                brelse(buf);
296:                return 0;
297:            }
298:        }
299:        if(level == MINIX_IND_BLOCK) {
300:            newblock = indblock[block];
301:            brelse(buf);
302:            return newblock;
303:        }
304:
305:        iblock = block;
306:        if(!(buf2 = bread(i->dev, indblock[iblock], blksize))) {
307:            printk("%s(): returning -EIO\n", __FUNCTION__);
308:            brelse(buf);
309:            return -EIO;
310:        }
311:        dindblock = (__u16 *)buf2->data;
312:        block = dindblock[dblock - (iblock * BLOCKS_PER_IND_BLOCK(i->sb))];
313:        if(!block && mode == FOR_WRITING) {
314:            if((newblock = minix_balloc(i->sb)) < 0) {
315:                brelse(buf);
316:                brelse(buf2);
317:                return -ENOSPC;
318:            }
319:            /* initialize the new block */
320:            if(!(buf3 = bread(i->dev, newblock, blksize))) {
321:                minix_bfree(i->sb, newblock);
322:                brelse(buf);
323:                brelse(buf2);

```

fs/minix/v1_inode.c

Page 6/7

```

324:                 return -EIO;
325:             }
326:             memset_b(buf3->data, 0, blksize);
327:             bwrite(buf3);
328:             dindblock[dblock - (iblock * BLOCKS_PER_IND_BLOCK(i->sb))] = new
block;
329:             buf2->dirty = 1;
330:             buf2->valid = 1;
331:             block = newblock;
332:         }
333:         brelse(buf);
334:         brelse(buf2);
335:         return block;
336:     }
337:
338: int v1_minix_truncate(struct inode *i, __off_t length)
339: {
340:     int n;
341:     __blk_t block, dblock;
342:     __ul6 *zone;
343:     struct buffer *buf;
344:
345:     block = length / i->sb->s_blocksize;
346:
347:     if(!S_ISDIR(i->i_mode) && !S_ISREG(i->i_mode) && !S_ISLNK(i->i_mode)) {
348:         return -EINVAL;
349:     }
350:
351:     if(block < MINIX_NDIR_BLOCKS) {
352:         for(n = block; n < MINIX_NDIR_BLOCKS; n++) {
353:             if(i->u.minix.u.il_zone[n]) {
354:                 minix_bfree(i->sb, i->u.minix.u.il_zone[n]);
355:                 i->u.minix.u.il_zone[n] = 0;
356:             }
357:         }
358:         block = 0;
359:     }
360:
361:     if(!block || block < (BLOCKS_PER_IND_BLOCK(i->sb) + MINIX_NDIR_BLOCKS))
{
362:         if(block) {
363:             block -= MINIX_NDIR_BLOCKS;
364:         }
365:         if(i->u.minix.u.il_zone[MINIX_IND_BLOCK]) {
366:             free_zone(i, i->u.minix.u.il_zone[MINIX_IND_BLOCK], bloc
k);
367:             if(!block) {
368:                 minix_bfree(i->sb, i->u.minix.u.il_zone[MINIX_IN
D_BLOCK]);
369:                 i->u.minix.u.il_zone[MINIX_IND_BLOCK] = 0;
370:             }
371:         }
372:         block = 0;
373:     }
374:
375:     if(block) {
376:         block -= MINIX_NDIR_BLOCKS;
377:         block -= BLOCKS_PER_IND_BLOCK(i->sb);
378:     }
379:     if(i->u.minix.u.il_zone[MINIX_DIND_BLOCK]) {
380:         if(!(buf = bread(i->dev, i->u.minix.u.il_zone[MINIX_DIND_BLOCK],
i->sb->s_blocksize))) {
381:             printk("%s(): error reading block %d.\n", __FUNCTION__,
i->u.minix.u.il_zone[MINIX_DIND_BLOCK]);
382:         }
383:         zone = (__ul6 *)buf->data;
384:         dblock = block % BLOCKS_PER_IND_BLOCK(i->sb);

```

fs/minix/v1_inode.c

Page 7/7

```
385:          for(n = block / BLOCKS_PER_IND_BLOCK(i->sb); n < BLOCKS_PER_IND_
BLOCK(i->sb); n++) {
386:              if(zone[n]) {
387:                  free_zone(i, zone[n], dblock);
388:                  if(!dblock) {
389:                      minix_bfree(i->sb, zone[n]);
390:                  }
391:              }
392:              dblock = 0;
393:          }
394:          bwrite(buf);
395:          if(!block) {
396:              minix_bfree(i->sb, i->u.minix.u.il_zone[MINIX_DIND_BLOCK
]);
397:              i->u.minix.u.il_zone[MINIX_DIND_BLOCK] = 0;
398:          }
399:      }
400:
401:      i->i_mtime = CURRENT_TIME;
402:      i->i_ctime = CURRENT_TIME;
403:      i->i_size = length;
404:      i->dirty = 1;
405:
406:      return 0;
407: }
```

fs/minix/v2_inode.c

Page 1/8

```

1: /*
2:  * fiwix/fs/minix/v2_inode.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/filesystems.h>
11: #include <fiwix/fs_minix.h>
12: #include <fiwix/fs_pipe.h>
13: #include <fiwix/statfs.h>
14: #include <fiwix/sleep.h>
15: #include <fiwix/stat.h>
16: #include <fiwix/sched.h>
17: #include <fiwix/buffer.h>
18: #include <fiwix/process.h>
19: #include <fiwix/errno.h>
20: #include <fiwix/stdio.h>
21: #include <fiwix/string.h>
22:
23: #define BLOCKS_PER_IND_BLOCK(sb)          (sb->s_blocksize / sizeof(__u32))
24: #define MINIX2_INODES_PER_BLOCK(sb)      (sb->s_blocksize / sizeof(struct minix2_
inode))
25:
26: #define MINIX_NDIR_BLOCKS                7
27: #define MINIX_IND_BLOCK                  MINIX_NDIR_BLOCKS
28: #define MINIX_DIND_BLOCK                  (MINIX_NDIR_BLOCKS + 1)
29: #define MINIX_TIND_BLOCK                  (MINIX_NDIR_BLOCKS + 2)
30:
31: static void free_zone(struct inode *i, int block, int offset)
32: {
33:     int n;
34:     struct buffer *buf;
35:     __u32 *zone;
36:
37:     if(!(buf = bread(i->dev, block, i->sb->s_blocksize))) {
38:         printk("WARNING: %s(): error reading block %d.\n", __FUNCTION__,
block);
39:         return;
40:     }
41:     zone = (__u32 *)buf->data;
42:     for(n = offset; n < BLOCKS_PER_IND_BLOCK(i->sb); n++) {
43:         if(zone[n]) {
44:             minix_bfree(i->sb, zone[n]);
45:             zone[n] = 0;
46:         }
47:     }
48:     bwrite(buf);
49: }
50:
51: int v2_minix_read_inode(struct inode *i)
52: {
53:     __ino_t block;
54:     short int offset;
55:     struct minix2_inode *ii;
56:     struct buffer *buf;
57:     int errno;
58:
59:     block = 1 + SUPERBLOCK + i->sb->u.minix.sb.s_imap_blocks + i->sb->u.mini
x.sb.s_zmap_blocks + (i->inode - 1) / MINIX2_INODES_PER_BLOCK(i->sb);
60:
61:     if(!(buf = bread(i->dev, block, i->sb->s_blocksize))) {
62:         return -EIO;
63:     }
64:     offset = (i->inode - 1) % MINIX2_INODES_PER_BLOCK(i->sb);

```

fs/minix/v2_inode.c

Page 2/8

```

65:         ii = ((struct minix2_inode *)buf->data) + offset;
66:
67:         i->i_mode = ii->i_mode;
68:         i->i_nlink = ii->i_nlink;
69:         i->i_uid = ii->i_uid;
70:         i->i_gid = ii->i_gid;
71:         i->i_size = ii->i_size;
72:         i->i_atime = ii->i_atime;
73:         i->i_mtime = ii->i_mtime;
74:         i->i_ctime = ii->i_ctime;
75:         memcpy_b(i->u.minix.u.i2_zone, ii->i_zone, sizeof(ii->i_zone));
76:         i->count = 1;
77:
78:         errno = 0;
79:         switch(i->i_mode & S_IFMT) {
80:             case S_IFCHR:
81:                 i->fsop = &def_chr_fsop;
82:                 i->rdev = ii->i_zone[0];
83:                 break;
84:             case S_IFBLK:
85:                 i->fsop = &def_blk_fsop;
86:                 i->rdev = ii->i_zone[0];
87:                 break;
88:             case S_IFIFO:
89:                 i->fsop = &pipefs_fsop;
90:                 /* it's a union so we need to clear pipefs_i */
91:                 memset_b(&i->u.pipefs, NULL, sizeof(struct pipefs_inode)
);
92:                 break;
93:             case S_IFDIR:
94:                 i->fsop = &minix_dir_fsop;
95:                 break;
96:             case S_IFREG:
97:                 i->fsop = &minix_file_fsop;
98:                 break;
99:             case S_IFLNK:
100:                i->fsop = &minix_symlink_fsop;
101:                break;
102:             case S_IFSOCK:
103:                i->fsop = NULL;
104:                break;
105:             default:
106:                printk("WARNING: %s(): invalid inode (%d) mode %o.\n", _
_FUNCTION__, i->inode, i->i_mode);
107:                errno = -ENOENT;
108:                break;
109:         }
110:
111:         brelse(buf);
112:         return errno;
113: }
114:
115: int v2_minix_write_inode(struct inode *i)
116: {
117:     __ino_t block;
118:     short int offset;
119:     struct minix2_inode *ii;
120:     struct buffer *buf;
121:
122:     block = 1 + SUPERBLOCK + i->sb->u.minix.sb.s_imap_blocks + i->sb->u.mini
x.sb.s_zmap_blocks + (i->inode - 1) / MINIX2_INODES_PER_BLOCK(i->sb);
123:
124:     if(!(buf = bread(i->dev, block, i->sb->s_blocksize))) {
125:         return -EIO;
126:     }
127:     offset = (i->inode - 1) % MINIX2_INODES_PER_BLOCK(i->sb);
128:     ii = ((struct minix2_inode *)buf->data) + offset;

```

```

129:
130:     ii->i_mode = i->i_mode;
131:     ii->i_nlink = i->i_nlink;
132:     ii->i_uid = i->i_uid;
133:     ii->i_gid = i->i_gid;
134:     ii->i_size = i->i_size;
135:     ii->i_atime = i->i_atime;
136:     ii->i_mtime = i->i_mtime;
137:     ii->i_ctime = i->i_ctime;
138:     if(S_ISCHR(i->i_mode) || S_ISBLK(i->i_mode)) {
139:         ii->i_zone[0] = i->rdev;
140:     } else {
141:         memcpy_b(ii->i_zone, i->u.minix.u.i2_zone, sizeof(i->u.minix.u.i
2_zone));
142:     }
143:     i->dirty = 0;
144:     bwrite(buf);
145:     return 0;
146: }
147:
148: int v2_minix_ialloc(struct inode *i)
149: {
150:     __blk_t offset;
151:     int inode, errno;
152:     struct superblock *sb;
153:
154:     sb = i->sb;
155:     superblock_lock(sb);
156:
157:     offset = 1 + SUPERBLOCK;
158:
159:     if(!(inode = minix_find_first_zero(sb, offset, sb->u.minix.sb.s_ninodes,
offset + sb->u.minix.sb.s_imap_blocks))) {
160:         superblock_unlock(sb);
161:         return -ENOSPC;
162:     }
163:
164:     errno = minix_change_bit(SET_BIT, sb, offset, inode);
165:
166:     if(errno) {
167:         if(errno < 0) {
168:             printk("WARNING: %s(): unable to set inode %d.\n", __FUN
CTION__, i->inode);
169:         } else {
170:             printk("WARNING: %s(): inode %d is already marked as use
d!\n", __FUNCTION__, i->inode);
171:         }
172:     }
173:
174:     i->inode = inode;
175:     i->i_atime = CURRENT_TIME;
176:     i->i_mtime = CURRENT_TIME;
177:     i->i_ctime = CURRENT_TIME;
178:     superblock_unlock(sb);
179:     return 0;
180: }
181:
182: void v2_minix_ifree(struct inode *i)
183: {
184:     int errno;
185:     struct superblock *sb;
186:
187:     minix_truncate(i, 0);
188:
189:     sb = i->sb;
190:     superblock_lock(sb);
191:

```

fs/minix/v2_inode.c

Page 4/8

```

192:         errno = minix_change_bit(CLEAR_BIT, i->sb, 1 + SUPERBLOCK, i->inode);
193:
194:         if(errno) {
195:             if(errno < 0) {
196:                 printk("WARNING: %s(): unable to clear inode %d.\n", __F
UNCTION__, i->inode);
197:             } else {
198:                 printk("WARNING: %s(): inode %d is already marked as fre
e!\n", __FUNCTION__, i->inode);
199:             }
200:         }
201:
202:         i->i_size = 0;
203:         i->i_mtime = CURRENT_TIME;
204:         i->i_ctime = CURRENT_TIME;
205:         i->dirty = 1;
206:         superblock_unlock(sb);
207:     }
208:
209: int v2_minix_bmap(struct inode *i, __off_t offset, int mode)
210: {
211:     unsigned char level;
212:     __u32 *indblock, *dindblock, *tindblock;
213:     __blk_t block, iblock, dblock, tblock, newblock;
214:     int blksize;
215:     struct buffer *buf, *buf2, *buf3, *buf4;
216:
217:     blksize = i->sb->s_blocksize;
218:     block = offset / blksize;
219:     level = 0;
220:     buf3 = NULL;    /* makes GCC happy */
221:
222:     if(block < MINIX_NDIR_BLOCKS) {
223:         level = MINIX_NDIR_BLOCKS - 1;
224:     } else {
225:         if(block < (BLOCKS_PER_IND_BLOCK(i->sb) + MINIX_NDIR_BLOCKS)) {
226:             level = MINIX_IND_BLOCK;
227:         } else if(block < ((BLOCKS_PER_IND_BLOCK(i->sb) * BLOCKS_PER_IND
_BLOCK(i->sb)) + BLOCKS_PER_IND_BLOCK(i->sb) + MINIX_NDIR_BLOCKS)) {
228:             level = MINIX_DIND_BLOCK;
229:         } else {
230:             level = MINIX_TIND_BLOCK;
231:         }
232:         block -= MINIX_NDIR_BLOCKS;
233:     }
234:
235:     if(level < MINIX_NDIR_BLOCKS) {
236:         if(!i->u.minix.u.i2_zone[block] && mode == FOR_WRITING) {
237:             if((newblock = minix_balloc(i->sb)) < 0) {
238:                 return -ENOSPC;
239:             }
240:             /* initialize the new block */
241:             if(!(buf = bread(i->dev, newblock, blksize))) {
242:                 minix_bfree(i->sb, newblock);
243:                 return -EIO;
244:             }
245:             memset_b(buf->data, 0, blksize);
246:             bwrite(buf);
247:             i->u.minix.u.i2_zone[block] = newblock;
248:         }
249:         return i->u.minix.u.i2_zone[block];
250:     }
251:
252:     if(!i->u.minix.u.i2_zone[level]) {
253:         if(mode == FOR_WRITING) {
254:             if((newblock = minix_balloc(i->sb)) < 0) {
255:                 return -ENOSPC;

```


fs/minix/v2_inode.c

Page 5/8

```

256:         }
257:         /* initialize the new block */
258:         if(!(buf = bread(i->dev, newblock, blksize))) {
259:             minix_bfree(i->sb, newblock);
260:             return -EIO;
261:         }
262:         memset_b(buf->data, 0, blksize);
263:         bwrite(buf);
264:         i->u.minix.u.i2_zone[level] = newblock;
265:     } else {
266:         return 0;
267:     }
268: }
269: if(!(buf = bread(i->dev, i->u.minix.u.i2_zone[level], blksize))) {
270:     return -EIO;
271: }
272: indblock = ((__u32 *)buf->data;
273: dblock = block - BLOCKS_PER_IND_BLOCK(i->sb);
274: tblock = block - (BLOCKS_PER_IND_BLOCK(i->sb) * BLOCKS_PER_IND_BLOCK(i->
sb)) - BLOCKS_PER_IND_BLOCK(i->sb);
275:
276:     if(level == MINIX_DIND_BLOCK) {
277:         block = dblock / BLOCKS_PER_IND_BLOCK(i->sb);
278:     }
279:     if(level == MINIX_TIND_BLOCK) {
280:         block = tblock / (BLOCKS_PER_IND_BLOCK(i->sb) * BLOCKS_PER_IND_B
LOCK(i->sb));
281:     }
282:
283:     if(!indblock[block]) {
284:         if(mode == FOR_WRITING) {
285:             if((newblock = minix_balloc(i->sb)) < 0) {
286:                 brelse(buf);
287:                 return -ENOSPC;
288:             }
289:             /* initialize the new block */
290:             if(!(buf2 = bread(i->dev, newblock, blksize))) {
291:                 minix_bfree(i->sb, newblock);
292:                 brelse(buf);
293:                 return -EIO;
294:             }
295:             memset_b(buf2->data, 0, blksize);
296:             bwrite(buf2);
297:             indblock[block] = newblock;
298:             if(level == MINIX_IND_BLOCK) {
299:                 bwrite(buf);
300:                 return newblock;
301:             }
302:             buf->dirty = 1;
303:             buf->valid = 1;
304:         } else {
305:             brelse(buf);
306:             return 0;
307:         }
308:     }
309:     if(level == MINIX_IND_BLOCK) {
310:         newblock = indblock[block];
311:         brelse(buf);
312:         return newblock;
313:     }
314:
315:     if(level == MINIX_TIND_BLOCK) {
316:         if(!(buf3 = bread(i->dev, indblock[block], blksize))) {
317:             printk("%s(): returning -EIO\n", __FUNCTION__);
318:             brelse(buf);
319:             return -EIO;
320:         }

```

fs/minix/v2_inode.c

Page 6/8

```

321:         tindblock = ((__u32 *)buf3->data;
322:         block = tindblock[tblock / BLOCKS_PER_IND_BLOCK(i->sb)];
323:         if(!block) {
324:             if(mode == FOR_WRITING) {
325:                 if((newblock = minix_balloc(i->sb)) < 0) {
326:                     brelse(buf);
327:                     brelse(buf3);
328:                     return -ENOSPC;
329:                 }
330:                 /* initialize the new block */
331:                 if(!(buf4 = bread(i->dev, newblock, blksize))) {
332:                     minix_bfree(i->sb, newblock);
333:                     brelse(buf);
334:                     brelse(buf3);
335:                     return -EIO;
336:                 }
337:                 memset_b(buf4->data, 0, blksize);
338:                 bwrite(buf4);
339:                 tindblock[tblock / BLOCKS_PER_IND_BLOCK(i->sb)]
= newblock;
340:                 buf3->dirty = 1;
341:                 buf3->valid = 1;
342:                 block = newblock;
343:             } else {
344:                 brelse(buf);
345:                 brelse(buf3);
346:                 return 0;
347:             }
348:         }
349:         dblock = tblock;
350:         iblock = tblock / BLOCKS_PER_IND_BLOCK(i->sb);
351:         if(!(buf2 = bread(i->dev, block, blksize))) {
352:             printk("%s(): returning -EIO\n", __FUNCTION__);
353:             brelse(buf);
354:             brelse(buf3);
355:             return -EIO;
356:         }
357:     } else {
358:         iblock = block;
359:         if(!(buf2 = bread(i->dev, indblock[iblock], blksize))) {
360:             printk("%s(): returning -EIO\n", __FUNCTION__);
361:             brelse(buf);
362:             return -EIO;
363:         }
364:     }
365:
366:     dindblock = ((__u32 *)buf2->data;
367:     block = dindblock[dblock - (iblock * BLOCKS_PER_IND_BLOCK(i->sb))];
368:     if(!block && mode == FOR_WRITING) {
369:         if((newblock = minix_balloc(i->sb)) < 0) {
370:             brelse(buf);
371:             if(level == MINIX_TIND_BLOCK) {
372:                 brelse(buf3);
373:             }
374:             brelse(buf2);
375:             return -ENOSPC;
376:         }
377:         /* initialize the new block */
378:         if(!(buf4 = bread(i->dev, newblock, blksize))) {
379:             minix_bfree(i->sb, newblock);
380:             brelse(buf);
381:             if(level == MINIX_TIND_BLOCK) {
382:                 brelse(buf3);
383:             }
384:             brelse(buf2);
385:             return -EIO;
386:         }

```

fs/minix/v2_inode.c

Page 7/8

```

387:         memset_b(buf4->data, 0, blksize);
388:         bwrite(buf4);
389:         dindblock[dblock - (iblock * BLOCKS_PER_IND_BLOCK(i->sb))] = new
block;
390:         buf2->dirty = 1;
391:         buf2->valid = 1;
392:         block = newblock;
393:     }
394:     brelse(buf);
395:     if(level == MINIX_TIND_BLOCK) {
396:         brelse(buf3);
397:     }
398:     brelse(buf2);
399:     return block;
400: }
401:
402: int v2_minix_truncate(struct inode *i, __off_t length)
403: {
404:     int n;
405:     __blk_t block, dblock;
406:     __u32 *zone;
407:     struct buffer *buf;
408:
409:     block = length / i->sb->s_blocksize;
410:
411:     if(!S_ISDIR(i->i_mode) && !S_ISREG(i->i_mode) && !S_ISLNK(i->i_mode)) {
412:         return -EINVAL;
413:     }
414:
415:     if(block < MINIX_NDIR_BLOCKS) {
416:         for(n = block; n < MINIX_NDIR_BLOCKS; n++) {
417:             if(i->u.minix.u.i2_zone[n]) {
418:                 minix_bfree(i->sb, i->u.minix.u.i2_zone[n]);
419:                 i->u.minix.u.i2_zone[n] = 0;
420:             }
421:         }
422:         block = 0;
423:     }
424:
425:     if(!block || block < (BLOCKS_PER_IND_BLOCK(i->sb) + MINIX_NDIR_BLOCKS))
{
426:         if(block) {
427:             block -= MINIX_NDIR_BLOCKS;
428:         }
429:         if(i->u.minix.u.i2_zone[MINIX_IND_BLOCK]) {
430:             free_zone(i, i->u.minix.u.i2_zone[MINIX_IND_BLOCK], bloc
k);
431:             if(!block) {
432:                 minix_bfree(i->sb, i->u.minix.u.i2_zone[MINIX_IN
D_BLOCK]);
433:                 i->u.minix.u.i2_zone[MINIX_IND_BLOCK] = 0;
434:             }
435:         }
436:         block = 0;
437:     }
438:
439:     if(block) {
440:         block -= MINIX_NDIR_BLOCKS;
441:         block -= BLOCKS_PER_IND_BLOCK(i->sb);
442:     }
443:     if(i->u.minix.u.i2_zone[MINIX_DIND_BLOCK]) {
444:         if(!(buf = bread(i->dev, i->u.minix.u.i2_zone[MINIX_DIND_BLOCK],
i->sb->s_blocksize))) {
445:             printk("%s(): error reading block %d.\n", __FUNCTION__,
i->u.minix.u.i2_zone[MINIX_DIND_BLOCK]);
446:         }
447:         zone = (__u32 *)buf->data;

```

fs/minix/v2_inode.c

Page 8/8

```
448:         dblock = block % BLOCKS_PER_IND_BLOCK(i->sb);
449:         for(n = block / BLOCKS_PER_IND_BLOCK(i->sb); n < BLOCKS_PER_IND_
BLOCK(i->sb); n++) {
450:             if(zone[n]) {
451:                 free_zone(i, zone[n], dblock);
452:                 if(!dblock) {
453:                     minix_bfree(i->sb, zone[n]);
454:                 }
455:             }
456:             dblock = 0;
457:         }
458:         bwrite(buf);
459:         if(!block) {
460:             minix_bfree(i->sb, i->u.minix.u.i2_zone[MINIX_DIND_BLOCK
]);
461:             i->u.minix.u.i2_zone[MINIX_DIND_BLOCK] = 0;
462:         }
463:     }
464:
465:     i->i_mtime = CURRENT_TIME;
466:     i->i_ctime = CURRENT_TIME;
467:     i->i_size = length;
468:     i->dirty = 1;
469:
470:     return 0;
471: }
```

fs/pipefs/fifo.c

Page 1/2

```

1: /*
2:  * fiwix/fs/pipefs/fifo.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/errno.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/filesystems.h>
12: #include <fiwix/fs_pipe.h>
13: #include <fiwix/stat.h>
14: #include <fiwix/mm.h>
15: #include <fiwix/sleep.h>
16: #include <fiwix/fcntl.h>
17: #include <fiwix/sched.h>
18: #include <fiwix/stdio.h>
19:
20: int fifo_open(struct inode *i, struct fd *fd_table)
21: {
22:     /* first open */
23:     if(i->count == 1) {
24:         if(!(i->u.pipefs.i_data = (void *)kmalloc())) {
25:             return -ENOMEM;
26:         }
27:         i->u.pipefs.i_readoff = 0;
28:         i->u.pipefs.i_writeoff = 0;
29:     }
30:
31:     if((fd_table->flags & O_ACCMODE) == O_RDONLY) {
32:         i->u.pipefs.i_readers++;
33:         wakeup(&pipefs_write);
34:         if(!(fd_table->flags & O_NONBLOCK)) {
35:             while(!i->u.pipefs.i_writers) {
36:                 if(sleep(&pipefs_read, PROC_INTERRUPTIBLE)) {
37:                     if(!--i->u.pipefs.i_readers) {
38:                         wakeup(&pipefs_write);
39:                     }
40:                     return -EINTR;
41:                 }
42:             }
43:         }
44:     }
45:
46:     if((fd_table->flags & O_ACCMODE) == O_WRONLY) {
47:         if((fd_table->flags & O_NONBLOCK) && !i->u.pipefs.i_readers) {
48:             return -ENXIO;
49:         }
50:
51:         i->u.pipefs.i_writers++;
52:         wakeup(&pipefs_read);
53:         if(!(fd_table->flags & O_NONBLOCK)) {
54:             while(!i->u.pipefs.i_readers) {
55:                 if(sleep(&pipefs_write, PROC_INTERRUPTIBLE)) {
56:                     if(!--i->u.pipefs.i_writers) {
57:                         wakeup(&pipefs_read);
58:                     }
59:                     return -EINTR;
60:                 }
61:             }
62:         }
63:     }
64:
65:     if((fd_table->flags & O_ACCMODE) == O_RDWR) {
66:         i->u.pipefs.i_readers++;
67:         i->u.pipefs.i_writers++;

```

fs/pipefs/fifo.c

Page 2/2

```
68:                wakeup(&pipefs_write);
69:                wakeup(&pipefs_read);
70:            }
71:
72:            return 0;
73: }
```

fs/pipefs/Makefile

Page 1/1

```
1: # fiwix/fs/pipefs/Makefile
2: #
3: # Copyright 2018, Jordi Sanfeliu. All rights reserved.
4: # Distributed under the terms of the Fiwix License.
5: #
6: #
7: .S.o:
8:     $(CC) -traditional -I$(INCLUDE) -c -o $@ $<
9: .c.o:
10:     $(CC) $(CFLAGS) -c -o $@ $<
11:
12: OBJS = super.o fifo.o pipe.o
13:
14: pipefs: $(OBJS)
15:     $(LD) $(LDFLAGS) -r $(OBJS) -o pipefs.o
16:
17: clean:
18:     rm -f *.o
19:
```

fs/pipefs/pipe.c

Page 1/4

```

1: /*
2:  * fiwix/fs/pipefs/pipe.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/errno.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/filesystems.h>
12: #include <fiwix/fs_pipe.h>
13: #include <fiwix/stat.h>
14: #include <fiwix/fcntl.h>
15: #include <fiwix/ioctl.h>
16: #include <fiwix/sleep.h>
17: #include <fiwix/sched.h>
18: #include <fiwix/stdio.h>
19: #include <fiwix/string.h>
20:
21: static struct resource pipe_resource = { NULL, NULL };
22:
23: int pipefs_close(struct inode *i, struct fd *fd_table)
24: {
25:     if((fd_table->flags & O_ACCMODE) == O_RDONLY) {
26:         if(!--i->u.pipefs.i_readers) {
27:             wakeup(&pipefs_write);
28:         }
29:     }
30:     if((fd_table->flags & O_ACCMODE) == O_WRONLY) {
31:         if(!--i->u.pipefs.i_writers) {
32:             wakeup(&pipefs_read);
33:         }
34:     }
35:     if((fd_table->flags & O_ACCMODE) == O_RDWR) {
36:         if(!--i->u.pipefs.i_readers) {
37:             wakeup(&pipefs_write);
38:         }
39:         if(!--i->u.pipefs.i_writers) {
40:             wakeup(&pipefs_read);
41:         }
42:     }
43:     return 0;
44: }
45:
46: int pipefs_read(struct inode *i, struct fd *fd_table, char *buffer, __size_t count)
47: {
48:     __off_t bytes_read;
49:     __size_t n, limit;
50:     char *data;
51:
52:     bytes_read = 0;
53:     data = i->u.pipefs.i_data;
54:
55:     while(count) {
56:         if(i->u.pipefs.i_writeoff) {
57:             if(i->u.pipefs.i_readoff >= i->u.pipefs.i_writeoff) {
58:                 limit = PIPE_BUF - i->u.pipefs.i_readoff;
59:             } else {
60:                 limit = i->u.pipefs.i_writeoff - i->u.pipefs.i_readoff;
61:             }
62:         } else {
63:             limit = PIPE_BUF - i->u.pipefs.i_readoff;
64:         }
65:         n = MIN(limit, count);

```


fs/pipefs/pipe.c

Page 2/4

```

66:         if(i->i_size && n) {
67:             lock_resource(&pipe_resource);
68:             memcpy_b(buffer + bytes_read, data + i->u.pipefs.i_reado
ff, n);
69:             bytes_read += n;
70:             i->u.pipefs.i_readoff += n;
71:             i->i_size -= n;
72:             if(i->u.pipefs.i_writeoff >= PIPE_BUF) {
73:                 i->u.pipefs.i_writeoff = 0;
74:             }
75:             unlock_resource(&pipe_resource);
76:             wakeup(&pipefs_write);
77:             break;
78:         } else {
79:             if(i->u.pipefs.i_writers) {
80:                 if(fd_table->flags & O_NONBLOCK) {
81:                     return -EAGAIN;
82:                 }
83:                 if(sleep(&pipefs_read, PROC_INTERRUPTIBLE)) {
84:                     return -EINTR;
85:                 }
86:             } else {
87:                 if(i->i_size) {
88:                     if(i->u.pipefs.i_readoff >= PIPE_BUF) {
89:                         i->u.pipefs.i_readoff = 0;
90:                         continue;
91:                     }
92:                 }
93:                 break;
94:             }
95:         }
96:     }
97:     if(!i->i_size) {
98:         i->u.pipefs.i_readoff = 0;
99:         i->u.pipefs.i_writeoff = 0;
100:     }
101:     return bytes_read;
102: }
103:
104: int pipefs_write(struct inode *i, struct fd *fd_table, const char *buffer, __siz
e_t count)
105: {
106:     __off_t bytes_written;
107:     __size_t n;
108:     char *data;
109:     int limit;
110:
111:     bytes_written = 0;
112:     data = i->u.pipefs.i_data;
113:
114:     while(bytes_written < count) {
115:         /* if the read end closes then send signal and return */
116:         if(!i->u.pipefs.i_readers) {
117:             send_sig(current, SIGPIPE);
118:             return -EPIPE;
119:         }
120:
121:         if(i->u.pipefs.i_readoff) {
122:             if(i->u.pipefs.i_writeoff <= i->u.pipefs.i_readoff) {
123:                 limit = i->u.pipefs.i_readoff;
124:             } else {
125:                 limit = PIPE_BUF;
126:             }
127:         } else {
128:             limit = PIPE_BUF;
129:         }
130:     }

```

fs/pipefs/pipe.c

Page 3/4

```

131:         n = MIN((count - bytes_written), (limit - i->u.pipefs.i_writeoff
));
132:
133:         /*
134:          * POSIX requires that any write operation involving fewer than
135:          * PIPE_BUF bytes must be automatically executed and finished
136:          * without being interleaved with write operations of other
137:          * processes to the same pipe.
138:          */
139:         if(n && n <= PIPE_BUF) {
140:             lock_resource(&pipe_resource);
141:             memcpy_b(data + i->u.pipefs.i_writeoff, buffer + bytes_w
ritten, n);
142:             bytes_written += n;
143:             i->u.pipefs.i_writeoff += n;
144:             i->i_size += n;
145:             if(i->u.pipefs.i_readoff >= PIPE_BUF) {
146:                 i->u.pipefs.i_readoff = 0;
147:             }
148:             unlock_resource(&pipe_resource);
149:             wakeup(&pipefs_read);
150:             continue;
151:         }
152:
153:         wakeup(&pipefs_read);
154:         if(!(fd_table->flags & O_NONBLOCK)) {
155:             if(sleep(&pipefs_write, PROC_INTERRUPTIBLE)) {
156:                 return -EINTR;
157:             }
158:         } else {
159:             return -EAGAIN;
160:         }
161:     }
162:     return bytes_written;
163: }
164:
165: int pipefs_ioctl(struct inode *i, int cmd, unsigned long int arg)
166: {
167:     int errno;
168:
169:     switch(cmd) {
170:         case FIONREAD:
171:             if((errno = check_user_area(VERIFY_WRITE, (void *)arg, s
izeof(unsigned int)))) {
172:                 return errno;
173:             }
174:             memcpy_b((void *)arg, &i->i_size, sizeof(unsigned int));
175:             break;
176:         default:
177:             return -EINVAL;
178:     }
179:     return 0;
180: }
181:
182: int pipefs_lseek(struct inode *i, __off_t offset)
183: {
184:     return -ESPIPE;
185: }
186:
187: int pipefs_select(struct inode *i, int flag)
188: {
189:     switch(flag) {
190:         case SEL_R:
191:             if(i->i_size || !i->u.pipefs.i_writers) {
192:                 return 1;
193:             }
194:             break;

```

fs/pipefs/pipe.c

Page 4/4

```
195:                 case SEL_W:
196:                     if(i->i_size < PIPE_BUF || !i->u.pipefs.i_readers) {
197:                         return 1;
198:                     }
199:                     break;
200:                 }
201:                 return 0;
202: }
```

fs/pipefs/super.c

Page 1/2

```

1: /*
2:  * fiwix/fs/pipefs/super.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/errno.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/filesystems.h>
12: #include <fiwix/fs_pipe.h>
13: #include <fiwix/stat.h>
14: #include <fiwix/mm.h>
15: #include <fiwix/sched.h>
16: #include <fiwix/stdio.h>
17: #include <fiwix/string.h>
18:
19: static unsigned int i_counter;
20:
21: struct fs_operations pipefs_fsop = {
22:     FSOP_KERN_MOUNT,
23:     PIPE_DEV,
24:
25:     fifo_open,
26:     pipefs_close,
27:     pipefs_read,
28:     pipefs_write,
29:     pipefs_ioctl,
30:     pipefs_lseek,
31:     NULL,                /* readdir */
32:     NULL,                /* mmap */
33:     pipefs_select,
34:
35:     NULL,                /* readlink */
36:     NULL,                /* followlink */
37:     NULL,                /* bmap */
38:     NULL,                /* lookup */
39:     NULL,                /* rmdir */
40:     NULL,                /* link */
41:     NULL,                /* unlink */
42:     NULL,                /* symlink */
43:     NULL,                /* mkdir */
44:     NULL,                /* mknod */
45:     NULL,                /* truncate */
46:     NULL,                /* create */
47:     NULL,                /* rename */
48:
49:     NULL,                /* read_block */
50:     NULL,                /* write_block */
51:
52:     NULL,                /* read_inode */
53:     NULL,                /* write_inode */
54:     pipefs_ialloc,
55:     pipefs_ifree,
56:     NULL,                /* statfs */
57:     pipefs_read_superblock,
58:     NULL,                /* remount_fs */
59:     NULL,                /* write_superblock */
60:     NULL,                /* release_superblock */
61: };
62:
63: int pipefs_read_superblock(__dev_t dev, struct superblock *sb)
64: {
65:     superblock_lock(sb);
66:     sb->dev = dev;
67:     sb->fsop = &pipefs_fsop;

```

fs/pipefs/super.c

Page 2/2

```
68:         sb->s_blocksize = BLKSIZE_1K;
69:         i_counter = 0;
70:         superblock_unlock(sb);
71:         return 0;
72:     }
73:
74: int pipefs_ialloc(struct inode *i)
75: {
76:     struct superblock *sb = i->sb;
77:
78:     superblock_lock(sb);
79:     i_counter++;
80:     superblock_unlock(sb);
81:
82:     i->i_mode = S_IFIFO;
83:     i->dev = i->rdev = sb->dev;
84:     i->fsop = &pipefs_fsop;
85:     i->inode = i_counter;
86:     i->count = 2;
87:     if(!(i->u.pipefs.i_data = (void *)kmalloc())) {
88:         return -ENOMEM;
89:     }
90:     i->u.pipefs.i_readoff = 0;
91:     i->u.pipefs.i_writeoff = 0;
92:     i->u.pipefs.i_readers = 1;
93:     i->u.pipefs.i_writers = 1;
94:     return 0;
95: }
96:
97: void pipefs_ifree(struct inode *i)
98: {
99:     if(!(i->u.pipefs.i_readers && !i->u.pipefs.i_writers) {
100:         /*
101:          * We need to ask before to kfree() because this function is
102:          * also called to free removed (with sys_unlink) fifo files.
103:          */
104:         if(i->u.pipefs.i_data) {
105:             kfree((unsigned int)i->u.pipefs.i_data);
106:         }
107:     }
108: }
109:
110: int pipefs_init(void)
111: {
112:     return register_filesystem("pipefs", &pipefs_fsop);
113: }
```

fs/procfs/data.c

Page 1/12

```

1: /*
2:  * fiwix/fs/procfs/data.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/system.h>
10: #include <fiwix/types.h>
11: #include <fiwix/process.h>
12: #include <fiwix/cmos.h>
13: #include <fiwix/dma.h>
14: #include <fiwix/ide.h>
15: #include <fiwix/fs.h>
16: #include <fiwix/filesystems.h>
17: #include <fiwix/devices.h>
18: #include <fiwix/locks.h>
19: #include <fiwix/mm.h>
20: #include <fiwix/mman.h>
21: #include <fiwix/fs_proc.h>
22: #include <fiwix/cpu.h>
23: #include <fiwix/pic.h>
24: #include <fiwix/sched.h>
25: #include <fiwix/timer.h>
26: #include <fiwix/utsname.h>
27: #include <fiwix/version.h>
28: #include <fiwix/errno.h>
29: #include <fiwix/stdio.h>
30: #include <fiwix/string.h>
31:
32: #define FSHIFT16          16
33: #define FIXED16_1        (1 << FSHIFT16)
34: #define LOAD_INT(x)      ((x) >> FSHIFT16)
35: #define LOAD_FRAC(x)     LOAD_INT(((x) & (FIXED16_1 - 1)) * 100)
36:
37: static const char *pstate[] = {
38:     "? (unused!)",
39:     "R (running)",
40:     "S (sleeping)",
41:     "Z (zombie)",
42:     "T (stopped)",
43:     "D (idle)",
44: };
45:
46: /*
47:  * procfs root directory related functions
48:  * -----
49:  */
50: int data_proc_self(char *buffer, __pid_t pid)
51: {
52:     return sprintk(buffer, "%s", current->pidstr);
53: }
54:
55: int data_proc_cmdline(char *buffer, __pid_t pid)
56: {
57:     return sprintk(buffer, "%s\n", cmdline);
58: }
59:
60: int data_proc_cpuinfo(char *buffer, __pid_t pid)
61: {
62:     int size;
63:
64:     size = sprintk(buffer, "processor          : 0\n");
65:     size += sprintk(buffer + size, "cpu family          : %d86\n", cpu_table.family
ily <= 6 ? cpu_table.family : 6);
66:     if(cpu_table.model >= 0) {

```

fs/procfs/data.c

Page 2/12

```

67:             size += sprintf(buffer + size, "model           : %d\n", cpu_tab
le.model);
68:         } else {
69:             size += sprintf(buffer + size, "model           : unknown\n");
70:         }
71:
72:         if(cpu_table.vendor_id) {
73:             size += sprintf(buffer + size, "vendor_id        : %s\n", cpu_tab
le.vendor_id);
74:         }
75:         if(cpu_table.model_name) {
76:             size += sprintf(buffer + size, "model name       : %s\n", cpu_tab
le.model_name);
77:         }
78:         if(cpu_table.stepping >= 0) {
79:             size += sprintf(buffer + size, "stepping         : %d\n", cpu_tab
le.stepping);
80:         } else {
81:             size += sprintf(buffer + size, "stepping         : unknown\n");
82:         }
83:
84:         size += sprintf(buffer + size, "cpu MHz           : ");
85:         if(cpu_table.hz) {
86:             size += sprintf(buffer + size, "%d.%d\n", (cpu_table.hz / 100000
0), ((cpu_table.hz % 1000000) / 100000));
87:         } else {
88:             size += sprintf(buffer + size, "unknown\n");
89:         }
90:         if(cpu_table.cache) {
91:             size += sprintf(buffer + size, "cache size      : %s\n", cpu_tab
le.cache);
92:         }
93:         size += sprintf(buffer + size, "cpuid            : %s\n", cpu_table.has_cp
uid ? "yes" : "no");
94:         size += sprintf(buffer + size, "fpu              : %s\n", cpu_table.has_fp
u ? "yes" : "no");
95:         size += get_cpu_flags(buffer, size);
96:         return size;
97:     }
98:
99: int data_proc_devices(char *buffer, __pid_t pid)
100: {
101:     int n, size;
102:     struct device *d;
103:
104:     d = chr_device_table;
105:     size = sprintf(buffer, "Character devices:\n");
106:     for(n = 0; n < NR_CHRDEV; n++, d++) {
107:         if(d->major) {
108:             size += sprintf(buffer + size, "%3d %s\n", d->major, d->
name);
109:         }
110:     }
111:
112:     size += sprintf(buffer + size, "\nBlock devices:\n");
113:     d = blk_device_table;
114:     for(n = 0; n < NR_BLKDEV; n++, d++) {
115:         if(d->major) {
116:             size += sprintf(buffer + size, "%3d %s\n", d->major, d->
name);
117:         }
118:     }
119:     return size;
120: }
121:
122: int data_proc_dma(char *buffer, __pid_t pid)
123: {

```

fs/procfs/data.c

Page 3/12

```

124:         int n, size;
125:
126:         size = 0;
127:         for(n = 0; n < DMA_CHANNELS; n++) {
128:             if(dma_resources[n]) {
129:                 size += sprintf(buffer + size, "%2d: %s\n", n, dma_resou
rces[n]);
130:             }
131:         }
132:         return size;
133:     }
134:
135: int data_proc_filesystems(char *buffer, __pid_t pid)
136: {
137:     int n, size;
138:     int nodev;
139:
140:     size = 0;
141:     for(n = 0; n < NR_FILESYSTEMS; n++) {
142:         if(filesystems_table[n].name) {
143:             nodev = 0;
144:             if(filesystems_table[n].fsop->flags != FSOP_REQUIRES_DEV
) {
145:                 nodev = 1;
146:             }
147:             size += sprintf(buffer + size, "%s %s\n", nodev ? "nodev
" : " ", filesystems_table[n].name);
148:         }
149:     }
150:     return size;
151: }
152:
153: int data_proc_interrupts(char *buffer, __pid_t pid)
154: {
155:     int n, size;
156:
157:     size = 0;
158:     for(n = 0; n < NR_IRQS; n++) {
159:         if(irq_table[n].registered) {
160:             size += sprintf(buffer + size, "%3d: %9u %s\n", n, irq_t
able[n].ticks, irq_table[n].name);
161:         }
162:     }
163:     size += sprintf(buffer + size, "SPU: %9u %s\n", kstat.sirqs, "Spurious i
nterrupts");
164:     return size;
165: }
166:
167: int data_proc_loadavg(char *buffer, __pid_t pid)
168: {
169:     int a, b, c;
170:     int size;
171:     struct proc *p;
172:     int nrun = 0;
173:     int nprocs = 0;
174:
175:     a = avenrun[0] << (SI_LOAD_SHIFT - FSHIFT);
176:     b = avenrun[1] << (SI_LOAD_SHIFT - FSHIFT);
177:     c = avenrun[2] << (SI_LOAD_SHIFT - FSHIFT);
178:
179:     FOR_EACH_PROCESS(p) {
180:         if(p->state) {
181:             nprocs++;
182:             if(p->state == PROC_RUNNING) {
183:                 nrun++;
184:             }
185:         }

```


fs/procfs/data.c

Page 4/12

```

186:         }
187:
188:         size = sprintk(buffer, "%d.%02d %d.%02d %d/%d %d\n", LOAD_INT(a)
, LOAD_FRAC(a), LOAD_INT(b), LOAD_FRAC(b), LOAD_INT(c), LOAD_FRAC(c), nrun, nprocs, las
tpid);
189:         return size;
190:     }
191:
192: int data_proc_locks(char *buffer, __pid_t pid)
193: {
194:     int n, size;
195:     struct flock_file *ff;
196:
197:     size = 0;
198:
199:     for(n = 0; n < NR_FLOCKS; n++) {
200:         ff = &flock_file_table[n];
201:         if(ff->inode) {
202:             size += sprintk(buffer + size, "%d: FLOCK ADVISORY %s
", n + 1, ff->type & LOCK_SH ? "READ " : "WRITE");
203:             size += sprintk(buffer + size, "%d %x:%d:%d 0 EOF\n", ff
->proc->pid, MAJOR(ff->inode->dev), MINOR(ff->inode->dev), ff->inode->inode);
204:         }
205:     }
206:
207:     return size;
208: }
209:
210: int data_proc_meminfo(char *buffer, __pid_t pid)
211: {
212:     struct page *pg;
213:     int n, size;
214:
215:     kstat.shared = 0;
216:     for(n = 0; n < kstat.physical_pages; n++) {
217:         pg = &page_table[n];
218:         if(pg->flags & PAGE_RESERVED) {
219:             continue;
220:         }
221:         if(!pg->count) {
222:             continue;
223:         }
224:         kstat.shared += pg->count - 1;
225:     }
226:
227:     size = 0;
228:     size += sprintk(buffer + size, "          total:    used:    free:    shared
: buffers:  cached:\n");
229:     size += sprintk(buffer + size, "Mem:  %8u %8u %8u %8u %8u %8u\n", kstat.
total_mem_pages << PAGE_SHIFT, (kstat.total_mem_pages << PAGE_SHIFT) - (kstat.free_page
s << PAGE_SHIFT), kstat.free_pages << PAGE_SHIFT, kstat.shared * 1024, kstat.buffers *
1024, kstat.cached * 1024);
230:     size += sprintk(buffer + size, "Swap: %8u %8u %8u\n", 0, 0, 0);
231:     size += sprintk(buffer + size, "MemTotal: %9d kB\n", kstat.total_mem_pag
es << 2);
232:     size += sprintk(buffer + size, "MemFree:  %9d kB\n", kstat.free_pages <<
2);
233:     size += sprintk(buffer + size, "MemShared:%9d kB\n", kstat.shared);
234:     size += sprintk(buffer + size, "Buffers:  %9d kB\n", kstat.buffers);
235:     size += sprintk(buffer + size, "Cached:   %9d kB\n", kstat.cached);
236:     size += sprintk(buffer + size, "SwapTotal:%9d kB\n", 0);
237:     size += sprintk(buffer + size, "SwapFree:  %9d kB\n", 0);
238:     return size;
239: }
240:
241: int data_proc_mounts(char *buffer, __pid_t pid)
242: {

```

fs/procfs/data.c

Page 5/12

```

243:     int n, size;
244:     char *flag;
245:
246:     size = 0;
247:     for(n = 0; n < NR_MOUNT_POINTS; n++) {
248:         if(mount_table[n].used) {
249:             if(mount_table[n].fs->fsop->flags != FSOP_KERN_MOUNT) {
250:                 flag = "rw";
251:                 if(mount_table[n].sb.flags & MS_RDONLY) {
252:                     flag = "ro";
253:                 }
254:                 size += sprintf(buffer + size, "%s %s %s %s 0 0\
n", mount_table[n].devname, mount_table[n].dirname, mount_table[n].fs->name, flag);
255:             }
256:         }
257:     }
258:     return size;
259: }
260:
261: int data_proc_partitions(char *buffer, __pid_t pid)
262: {
263:     int n, ctrl, drv, size;
264:     int minor, major;
265:     unsigned int blocks;
266:     struct ide *ide;
267:     struct ide_drv *drive;
268:
269:     size = 0;
270:     size += sprintf(buffer + size, "major minor #blocks name\n\n");
271:
272:     for(ctrl = 0; ctrl < NR_IDE_CTRLs; ctrl++) {
273:         ide = &ide_table[ctrl];
274:         for(drv = 0; drv < NR_IDE_DRVS; drv++) {
275:             drive = &ide->drive[drv];
276:             if(!drive->nr_sects) {
277:                 continue;
278:             }
279:             if(drive->flags & DEVICE_IS_DISK) {
280:                 major = (int)drive->major;
281:                 minor = (int)drive->minor_shift;
282:                 blocks = drive->nr_sects / 2;
283:                 size += sprintf(buffer + size, "%4d %4d %9d %s
\n", major, 0, blocks, drive->dev_name);
284:                 for(n = 0; n < NR_PARTITIONS; n++) {
285:                     if(drive->part_table[n].type) {
286:                         blocks = drive->part_table[n].nr
_sects / 2;
287:                         size += sprintf(buffer + size, "
%4d %4d %9u %s%d\n", major, (n + 1) << minor, blocks, drive->dev_name, n + 1);
288:                     }
289:                 }
290:             }
291:         }
292:     }
293:     return size;
294: }
295:
296: int data_proc_rtc(char *buffer, __pid_t pid)
297: {
298:     int size;
299:     short int sec, min, hour;
300:     short int day, month, year, century;
301:
302:     sec = cmos_read_date(CMOS_SEC);
303:     min = cmos_read_date(CMOS_MIN);
304:     hour = cmos_read_date(CMOS_HOUR);
305:     day = cmos_read_date(CMOS_DAY);

```

fs/procfs/data.c

Page 6/12

```

306:         month = cmos_read_date(CMOS_MONTH);
307:         year = cmos_read_date(CMOS_YEAR);
308:         century = cmos_read_date(CMOS_CENTURY);
309:         year += century * 100;
310:
311:         size = 0;
312:         size += sprintf(buffer + size, "rtc_time\t: %02d:%02d:%02d\n", hour, min
, sec);
313:         size += sprintf(buffer + size, "rtc_date\t: %02d-%02d-%02d\n", year, mon
th, day);
314:         sec = cmos_read_date(CMOS_ASEC);
315:         min = cmos_read_date(CMOS_AMIN);
316:         hour = cmos_read_date(CMOS_AHOUR);
317:         size += sprintf(buffer + size, "alarm\t\t: %02d:%02d:%02d\n", hour, min,
sec);
318:         size += sprintf(buffer + size, "DST_enable\t: %s\n", cmos_read(CMOS_STAT
B) & CMOS_STATB_DSE ? "yes" : "no");
319:         size += sprintf(buffer + size, "BCD\t\t: %s\n", cmos_read(CMOS_STATB) &
CMOS_STATB_DM ? "no" : "yes");
320:         size += sprintf(buffer + size, "24hr\t\t: %s\n", cmos_read(CMOS_STATB) &
CMOS_STATB_24H ? "yes" : "no");
321:         size += sprintf(buffer + size, "square_wave\t: %s\n", cmos_read(CMOS_STA
TB) & CMOS_STATB_SQWE ? "yes" : "no");
322:         size += sprintf(buffer + size, "alarm_IRQ\t: %s\n", cmos_read(CMOS_STATB
) & CMOS_STATB_AIE ? "yes" : "no");
323:         size += sprintf(buffer + size, "update_IRQ\t: %s\n", cmos_read(CMOS_STAT
B) & CMOS_STATB_UIE ? "yes" : "no");
324:         size += sprintf(buffer + size, "periodic_IRQ\t: %s\n", cmos_read(CMOS_ST
ATB) & CMOS_STATB_PIE ? "yes" : "no");
325:         size += sprintf(buffer + size, "periodic_freq\t: %s\n", (cmos_read(CMOS_
STATA) & CMOS_STATA_IRQF) == 0x6 ? "1024" : "?");
326:         size += sprintf(buffer + size, "batt_status\t: %s\n", cmos_read(CMOS_STA
TD) & CMOS_STATD_VRT ? "okay" : "dead");
327:         return size;
328:     }
329:
330: int data_proc_stat(char *buffer, __pid_t pid)
331: {
332:     int n, size;
333:     unsigned int idle;
334:
335:     idle = kstat.ticks - (kstat.cpu_user + kstat.cpu_nice + kstat.cpu_system
);
336:     size = 0;
337:     size += sprintf(buffer + size, "cpu %d %d %d %d\n", kstat.cpu_user, ksta
t.cpu_nice, kstat.cpu_system, idle);
338:     size += sprintf(buffer + size, "disk 0 0 0 0\n");
339:     size += sprintf(buffer + size, "page 0 0\n");
340:     size += sprintf(buffer + size, "swap 0 0\n");
341:     size += sprintf(buffer + size, "intr %u", kstat.irqs);
342:     for(n = 0; n < NR_IRQS; n++) {
343:         size += sprintf(buffer + size, " %u", irq_table[n].ticks);
344:     }
345:     size += sprintf(buffer + size, "\n");
346:     size += sprintf(buffer + size, "ctxt %u\n", kstat.ctxt);
347:     size += sprintf(buffer + size, "btime %d\n", kstat.boot_time);
348:     size += sprintf(buffer + size, "processes %d\n", kstat.processes);
349:     return size;
350: }
351:
352: int data_proc_uptime(char *buffer, __pid_t pid)
353: {
354:     struct proc *p;
355:     unsigned long int idle;
356:
357:     p = &proc_table[IDLE];
358:     idle = tv2ticks(&p->usage.ru_utime);

```

fs/procfs/data.c

Page 7/12

```

359:         idle += tv2ticks(&p->usage.ru_stime);
360:         return sprintf(buffer, "%u.%02u %u.%02u\n", kstat.uptime, kstat.ticks %
HZ, idle / HZ, idle % HZ);
361:     }
362:
363: int data_proc_fullversion(char *buffer, __pid_t pid)
364: {
365:     return sprintf(buffer, "Fiwix version %s %s\n", UTS_RELEASE, UTS_VERSION
);
366: }
367:
368: int data_proc_domainname(char *buffer, __pid_t pid)
369: {
370:     return sprintf(buffer, "%s\n", sys_utsname.domainname);
371: }
372:
373: int data_proc_filemax(char *buffer, __pid_t pid)
374: {
375:     return sprintf(buffer, "%d\n", NR_OPENS);
376: }
377:
378: int data_proc_filenr(char *buffer, __pid_t pid)
379: {
380:     int n, nr;
381:
382:     nr = 0;
383:     for(n = 1; n < NR_OPENS; n++) {
384:         if(fd_table[n].count != 0) {
385:             nr++;
386:         }
387:     }
388:     return sprintf(buffer, "%d\n", nr);
389: }
390:
391: int data_proc_hostname(char *buffer, __pid_t pid)
392: {
393:     return sprintf(buffer, "%s\n", sys_utsname.nodename);
394: }
395:
396: int data_proc_inodemax(char *buffer, __pid_t pid)
397: {
398:     return sprintf(buffer, "%d\n", inode_table_size / sizeof(struct inode));
399: }
400:
401: int data_proc_inodenr(char *buffer, __pid_t pid)
402: {
403:     return sprintf(buffer, "%d\n", (inode_table_size / sizeof(struct inode))
- inodes_on_free_list);
404: }
405:
406: int data_proc_osrelease(char *buffer, __pid_t pid)
407: {
408:     return sprintf(buffer, "%s\n", UTS_RELEASE);
409: }
410:
411: int data_proc_ostype(char *buffer, __pid_t pid)
412: {
413:     return sprintf(buffer, "%s\n", UTS_SYSNAME);
414: }
415:
416: int data_proc_version(char *buffer, __pid_t pid)
417: {
418:     return sprintf(buffer, "%s\n", UTS_VERSION);
419: }
420:
421:
422: /*

```

fs/procfs/data.c

Page 8/12

```

423:  * PID directory related functions
424:  * -----
425:  */
426:  int data_proc_pid_cmdline(char *buffer, __pid_t pid)
427:  {
428:      int n, size;
429:      char *arg;
430:      char **argv;
431:      unsigned int paddr, offset;
432:      struct proc *p;
433:
434:      size = 0;
435:      if((p = get_proc_by_pid(pid))) {
436:          if(p->argv) {
437:              offset = (int)p->argv & ~PAGE_MASK;
438:              paddr = get_mapped_addr(p, (int)p->argv) & PAGE_MASK;
439:              paddr = P2V(paddr);
440:              argv = (char **)(paddr + offset);
441:              for(n = 0; argv[n]; n++) {
442:                  offset = (int)argv[n] & ~PAGE_MASK;
443:                  paddr = get_mapped_addr(p, (int)argv[n]) & PAGE_
MASK;
444:
445:                  paddr = P2V(paddr);
446:                  arg = (char *) (paddr + offset);
447:                  size += sprintf(buffer + size, "%s", arg);
448:                  buffer[size++] = NULL;
449:              }
450:          }
451:          return size;
452:      }
453:
454:  int data_proc_pid_cwd(char *buffer, __pid_t pid)
455:  {
456:      int size;
457:      struct proc *p;
458:      struct inode *i;
459:
460:      size = 0;
461:      if((p = get_proc_by_pid(pid))) {
462:
463:          /* zombie processes don't have current working directory */
464:          if(!p->pwd) {
465:              return -ENOENT;
466:          }
467:
468:          i = p->pwd;
469:          size = sprintf(buffer, "[%02d%02d]:%d", MAJOR(i->rdev), MINOR(i-
>rdev), i->inode);
470:      }
471:      return size;
472:  }
473:
474:  int data_proc_pid_envron(char *buffer, __pid_t pid)
475:  {
476:      int n, size;
477:      char *env;
478:      char **envp;
479:      unsigned int paddr, offset;
480:      struct proc *p;
481:
482:      size = 0;
483:      if((p = get_proc_by_pid(pid))) {
484:          if(p->envp) {
485:              offset = (int)p->envp & ~PAGE_MASK;
486:              paddr = get_mapped_addr(p, (int)p->envp) & PAGE_MASK;
487:              paddr = P2V(paddr);

```

fs/procfs/data.c

Page 9/12

```

488:         envp = (char **)(paddr + offset);
489:         for(n = 0; envp[n]; n++) {
490:             offset = (int)envp[n] & ~PAGE_MASK;
491:             paddr = get_mapped_addr(p, (int)envp[n]) & PAGE_
MASK;
492:             paddr = P2V(paddr);
493:             env = (char *) (paddr + offset);
494:             size += sprintf(buffer + size, "%s", env);
495:             buffer[size++] = NULL;
496:         }
497:     }
498: }
499:     return size;
500: }
501:
502: int data_proc_pid_exe(char *buffer, __pid_t pid)
503: {
504:     int size;
505:     struct proc *p;
506:     struct inode *i;
507:
508:     size = 0;
509:     if((p = get_proc_by_pid(pid))) {
510:
511:         /* kernel and zombie processes are programless */
512:         if(!p->vma || !p->vma->inode) {
513:             return -ENOENT;
514:         }
515:
516:         i = p->vma->inode;
517:         size = sprintf(buffer, "[%02d%02d]:%d", MAJOR(i->rdev), MINOR(i-
>rdev), i->inode);
518:     }
519:     return size;
520: }
521:
522: int data_proc_pid_maps(char *buffer, __pid_t pid)
523: {
524:     unsigned int n;
525:     int size, len;
526:     __ino_t inode;
527:     int major, minor;
528:     char *section;
529:     char r, w, x, f;
530:     struct proc *p;
531:     struct vma *vma;
532:
533:     size = 0;
534:     if((p = get_proc_by_pid(pid))) {
535:         if(!p->vma) {
536:             return 0;
537:         }
538:         vma = p->vma;
539:         for(n = 0; n < VMA_REGIONS && vma->start; n++, vma++) {
540:             r = vma->prot & PROT_READ ? 'r' : '-';
541:             w = vma->prot & PROT_WRITE ? 'w' : '-';
542:             x = vma->prot & PROT_EXEC ? 'x' : '-';
543:             if(vma->flags & MAP_SHARED) {
544:                 f = 's';
545:             } else if(vma->flags & MAP_PRIVATE) {
546:                 f = 'p';
547:             } else {
548:                 f = '-';
549:             }
550:             switch(vma->s_type) {
551:                 case P_TEXT:     section = "text";
552:                                 break;

```

fs/procfs/data.c

Page 10/12

```

553:         case P_DATA:      section = "data";
554:                         break;
555:         case P_BSS:       section = "bss";
556:                         break;
557:         case P_HEAP:      section = "heap";
558:                         break;
559:         case P_STACK:     section = "stack";
560:                         break;
561:         case P_MMAP:      section = "mmap";
562:                         break;
563:         default:
564:             section = NULL;
565:             break;
566:     }
567:     inode = major = minor = 0;
568:     if(vma->inode) {
569:         inode = vma->inode->inode;
570:         major = MAJOR(vma->inode->dev);
571:         minor = MINOR(vma->inode->dev);
572:     }
573:     len = sprintf(buffer + size, "%08x-%08x %c%c%c%c %08x %0
2d:%02d %- 10u [%s]\n", vma->start, vma->end, r, w, x, f, vma->offset, major, minor, in
ode, section);
574:     size += len;
575:     }
576: }
577: return size;
578: }
579:
580: int data_proc_pid_mountinfo(char *buffer, __pid_t pid)
581: {
582:     int n, size;
583:     char *flag, *devname;
584:
585:     size = 0;
586:     for(n = 0; n < NR_MOUNT_POINTS; n++) {
587:         if(mount_table[n].used) {
588:             if(mount_table[n].fs->fsop->flags != FSOP_KERN_MOUNT) {
589:                 flag = "rw";
590:                 if(mount_table[n].sb.flags & MS_RDONLY) {
591:                     flag = "ro";
592:                 }
593:                 devname = mount_table[n].devname;
594:                 if(!strcmp(mount_table[n].devname, "/dev/root"))
{
595:                     devname = _rootdevname;
596:                 }
597:                 size += sprintf(buffer + size, "%d 0 %d:%d %s %s
%s - %s %s %s\n", n, MAJOR(mount_table[n].dev), MINOR(mount_table[n].dev), "/", mount_
table[n].dirname, flag, mount_table[n].fs->name, devname, flag);
598:             }
599:         }
600:     }
601:     return size;
602: }
603:
604: int data_proc_pid_root(char *buffer, __pid_t pid)
605: {
606:     int size;
607:     struct proc *p;
608:     struct inode *i;
609:
610:     size = 0;
611:     if((p = get_proc_by_pid(pid))) {
612:
613:         /* zombie processes don't have root directory */
614:         if(!p->root) {

```

fs/procfs/data.c

Page 11/12

```

615:                 return -ENOENT;
616:             }
617:
618:             i = p->root;
619:             size = sprintf(buffer, "[%02d%02d]:%d", MAJOR(i->rdev), MINOR(i-
>rdev), i->inode);
620:         }
621:         return size;
622:     }
623:
624: int data_proc_pid_stat(char *buffer, __pid_t pid)
625: {
626:     int size, vma_start, vma_end;
627:     unsigned int esp, eip;
628:     int signum, mask;
629:     __sigset_t sigignored, sigcaught;
630:     struct proc *p;
631:     struct sigcontext *sc;
632:
633:     size = vma_start = vma_end = 0;
634:     if((p = get_proc_by_pid(pid)) {
635:         if(p->vma) {
636:             vma_start = p->vma[0].start;
637:             vma_end = p->vma[0].end;
638:         }
639:
640:         sigignored = sigcaught = 0;
641:         for(signum = 0, mask = 1; signum < NSIG; signum++, mask <= 1) {
642:             if(p->sigaction[signum].sa_handler == SIG_IGN) {
643:                 sigignored |= mask;
644:             }
645:             if(p->sigaction[signum].sa_handler == SIG_DFL) {
646:                 sigcaught |= mask;
647:             }
648:         }
649:
650:         esp = eip = 0;
651:         if(p->sp) {
652:             sc = (struct sigcontext *)p->sp;
653:             esp = sc->oldesp;
654:             eip = sc->eip;
655:         }
656:         size = sprintf(buffer, "%d (%s) %c %d %d %d %d %d %d %d %d %d %d
%u %u %u %u %d %d %d %d %d %d %u %u %u %u %u %u %u %d %d %u %u %u\n",
657:             p->pid,
658:             p->argv0,
659:             pstate[p->state][0],
660:             p->ppid, p->pgid, p->sid,
661:             p->ctty ? p->ctty->dev : 0,
662:             p->ctty ? p->ctty->pgid : - 1,
663:             0, /* flags */
664:             0, 0, 0, 0, /* minflt, cminflt, majflt, cmajflt */
665:             tv2ticks(&p->usage.ru_utime),
666:             tv2ticks(&p->usage.ru_stime),
667:             tv2ticks(&p->cusage.ru_utime),
668:             tv2ticks(&p->cusage.ru_stime),
669:             0, /* counter */
670:             0, /* priority */
671:             0, /* timeout */
672:             0, /* itrealvalue */
673:             p->start_time,
674:             0, /* vsize */
675:             p->rss,
676:             0x7FFFFFFF, /* rlim */
677:             vma_start, /* startcode */
678:             vma_end, /* endcode */
679:             KERNEL_BASE_ADDR - 1, /* startstack */

```


fs/procfs/data.c

Page 12/12

```

680:             esp,             /* kstkesp */
681:             eip,             /* kstkeip */
682:             p->sigpending,
683:             p->sigblocked,
684:             sigignored,
685:             sigcaught,
686:             p->sleep_address
687:         );
688:     }
689:     return size;
690: }
691:
692: int data_proc_pid_status(char *buffer, __pid_t pid)
693: {
694:     int size;
695:     int signum, mask;
696:     __sigset_t sigignored, sigcaught;
697:     struct proc *p;
698:
699:     size = 0;
700:     if((p = get_proc_by_pid(pid)) {
701:         size = sprintk(buffer, "Name:\t%s\n", p->argv0);
702:         size += sprintk(buffer + size, "State:\t%s\n", pstate[p->state])
;
703:         size += sprintk(buffer + size, "Pid:\t%d\n", p->pid);
704:         size += sprintk(buffer + size, "PPid:\t%d\n", p->ppid);
705:         size += sprintk(buffer + size, "Uid:\t%d\t%d\t%d\t-\n", p->uid,
p->euid, p->suid);
706:         size += sprintk(buffer + size, "Gid:\t%d\t%d\t%d\t-\n", p->gid,
p->egid, p->sgid);
707:         size += sprintk(buffer + size, "VmSize:\t\t%c kB\n", '-');
708:         size += sprintk(buffer + size, "VmLck:\t\t%c kB\n", '-');
709:         size += sprintk(buffer + size, "VmRSS:\t\t%c kB\n", '-');
710:         size += sprintk(buffer + size, "VmData:\t\t%c kB\n", '-');
711:         size += sprintk(buffer + size, "VmStk:\t\t%c kB\n", '-');
712:         size += sprintk(buffer + size, "VmExe:\t\t%c kB\n", '-');
713:         size += sprintk(buffer + size, "VmLib:\t\t%c kB\n", '-');
714:         size += sprintk(buffer + size, "SigPnd:\t%08x\n", p->sigpending)
;
715:         size += sprintk(buffer + size, "SigBlk:\t%08x\n", p->sigblocked)
;
716:         sigignored = sigcaught = 0;
717:         for(signum = 0, mask = 1; signum < NSIG; signum++, mask <= 1) {
718:             if(p->sigaction[signum].sa_handler == SIG_IGN) {
719:                 sigignored |= mask;
720:             }
721:             if(p->sigaction[signum].sa_handler == SIG_DFL) {
722:                 sigcaught |= mask;
723:             }
724:         }
725:         size += sprintk(buffer + size, "SigIgn:\t%08x\n", sigignored);
726:         size += sprintk(buffer + size, "SigCgt:\t%08x\n", sigcaught);
727:     }
728:     return size;
729: }

```

fs/procfs/dir.c

Page 1/5

```

1: /*
2:  * fiwix/fs/procfs/dir.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/errno.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/filesystems.h>
12: #include <fiwix/fs_proc.h>
13: #include <fiwix/dirent.h>
14: #include <fiwix/stat.h>
15: #include <fiwix/mm.h>
16: #include <fiwix/stdio.h>
17: #include <fiwix/string.h>
18:
19: struct fs_operations procfs_dir_fsop = {
20:     0,
21:     0,
22:
23:     procfs_dir_open,
24:     procfs_dir_close,
25:     procfs_dir_read,
26:     NULL, /* write */
27:     NULL, /* ioctl */
28:     NULL, /* lseek */
29:     procfs_dir_readdir,
30:     NULL, /* mmap */
31:     NULL, /* select */
32:
33:     NULL, /* readlink */
34:     NULL, /* followlink */
35:     procfs_bmap,
36:     procfs_lookup,
37:     NULL, /* rmdir */
38:     NULL, /* link */
39:     NULL, /* unlink */
40:     NULL, /* symlink */
41:     NULL, /* mkdir */
42:     NULL, /* mknod */
43:     NULL, /* truncate */
44:     NULL, /* create */
45:     NULL, /* rename */
46:
47:     NULL, /* read_block */
48:     NULL, /* write_block */
49:
50:     NULL, /* read_inode */
51:     NULL, /* write_inode */
52:     NULL, /* ialloc */
53:     NULL, /* ifree */
54:     NULL, /* statfs */
55:     NULL, /* read_superblock */
56:     NULL, /* remount_fs */
57:     NULL, /* write_superblock */
58:     NULL, /* release_superblock */
59: };
60:
61: static int proc_listdir(char *buffer)
62: {
63:     int n;
64:     struct proc *p;
65:     struct procfs_dir_entry *pd;
66:     struct procfs_dir_entry d;
67:     int size;

```

fs/procfs/dir.c

Page 2/5

```

68:
69:     size = n = 0;
70:     pd = (struct procfs_dir_entry *)buffer;
71:
72:     FOR_EACH_PROCESS(p) {
73:         if(p->state) {
74:             d.inode = PROC_PID_INO + (p->pid << 12);
75:             d.mode = S_IFDIR | S_IRUSR | S_IXUSR | S_IRGRP | S_IXGRP
| S_IROTH | S_IXOTH;
76:             d.lev = -1;
77:             d.name_len = 1;
78:             n = p->pid;
79:             while(n) {
80:                 n /= 10;
81:                 d.name_len++;
82:             }
83:             d.name = p->pidstr;
84:             d.data_fn = NULL;
85:
86:             if(size + sizeof(d) >= 4096) {
87:                 printk("WARNING: kmalloc() is limited to 4096 by
tes.\n");
88:                 break;
89:             }
90:
91:             size += sizeof(d);
92:             memcpy_b((void *)pd, (void *)&d, sizeof(d));
93:             pd++;
94:         }
95:     }
96:     memset_b((void *)pd + size, NULL, sizeof(d));
97:     return size;
98: }
99:
100: static int proc_listfd(struct inode *i, char *buffer)
101: {
102:     int n;
103:     struct proc *p;
104:     struct procfs_dir_entry *pd;
105:     struct procfs_dir_entry d;
106:     int size;
107:
108:     size = 0;
109:     pd = (struct procfs_dir_entry *)buffer;
110:
111:     p = get_proc_by_pid((i->inode >> 12) & 0xFFFF);
112:     for(n = 0; n < OPEN_MAX; n++) {
113:         if(p->fd[n]) {
114:             d.inode = PROC_PID_INO + (p->pid << 12) + n;
115:             d.mode = S_IFREG | S_IRWXU;
116:             d.nlink = 1;
117:             d.lev = -1;
118:             d.name_len = sprintk(d.name, "%d", n);
119:             d.data_fn = NULL;
120:
121:             if(size + sizeof(d) >= 4096) {
122:                 printk("WARNING: kmalloc() is limited to 4096 by
tes.\n");
123:                 break;
124:             }
125:
126:             size += sizeof(d);
127:             memcpy_b((void *)pd, (void *)&d, sizeof(d));
128:             pd++;
129:         }
130:     }
131:     memset_b((void *)pd + size, NULL, sizeof(d));

```

fs/procfs/dir.c

Page 3/5

```

132:         return size;
133:     }
134:
135: int procfs_dir_open(struct inode *i, struct fd *fd_table)
136: {
137:     fd_table->offset = 0;
138:     return 0;
139: }
140:
141: int procfs_dir_close(struct inode *i, struct fd *fd_table)
142: {
143:     return 0;
144: }
145:
146: int procfs_dir_read(struct inode *i, struct fd *fd_table, char *buffer, __size_t
count)
147: {
148:     __off_t total_read;
149:     unsigned int boffset, bytes;
150:     int blksize, len;
151:     int lev;
152:     char *buf;
153:
154:     if(!(buf = (void *)kmalloc())) {
155:         return -ENOMEM;
156:     }
157:
158:     /* create the list of directories for each process */
159:     len = 0;
160:     if(i->inode == PROC_ROOT_INO) {
161:         len = proc_listdir(buf);
162:     }
163:
164:     /* create the list of fds used for each process (TODO)
165:     if((i->inode & 0xF0000FFF) == PROC_PID_FD) {
166:         len = proc_listfd(i, buf);
167:     }
168:     */
169:
170:     /* add the rest of static files in the main directory */
171:     lev = i->u.procfs.i_lev;
172:     if((len + sizeof(procfs_array[lev])) > (PAGE_SIZE - 1)) {
173:         printk("WARNING: %s(): len > 4096 (%d)!\n", __FUNCTION__, len);
174:     }
175:     memcpy_b(buf + len, (char *)&procfs_array[lev], sizeof(procfs_array[lev]
));
176:     len += sizeof(procfs_array[lev]);
177:     blksize = i->sb->s_blocksize;
178:     if(fd_table->offset > len) {
179:         fd_table->offset = len;
180:     }
181:
182:     total_read = 0;
183:
184:     for(;;) {
185:         count = (fd_table->offset + count > len) ? len - fd_table->offse
t : count;
186:         if(!count) {
187:             break;
188:         }
189:
190:         boffset = fd_table->offset % blksize;
191:         bytes = blksize - boffset;
192:         bytes = MIN(bytes, count);
193:         memcpy_b(buffer + total_read, buf + boffset, bytes);
194:         total_read += bytes;
195:         count -= bytes;

```

fs/procfs/dir.c

Page 4/5

```

196:         boffset += bytes;
197:         boffset %= blksize;
198:         fd_table->offset += bytes;
199:     }
200:
201:     kfree((unsigned int)buf);
202:     return total_read;
203: }
204:
205: int procfs_dir_readdir(struct inode *i, struct fd *fd_table, struct dirent *dire
nt, unsigned int count)
206: {
207:     unsigned int offset, boffset, dirent_offset, doffset;
208:     int dirent_len;
209:     unsigned int total_read;
210:     struct procfs_dir_entry *d;
211:     int base_dirent_len;
212:     char *buffer;
213:     int lev;
214:
215:     if(!i->fsop || !i->fsop->read) {
216:         return -EBADF;
217:     }
218:     if(!(buffer = (void *)kmalloc())) {
219:         return -ENOMEM;
220:     }
221:
222:     lev = i->u.procfs.i_lev;
223:     base_dirent_len = sizeof(dirent->d_ino) + sizeof(dirent->d_off) + sizeof
(dirent->d_reclen);
224:
225:     offset = fd_table->offset;
226:     boffset = dirent_offset = doffset = 0;
227:
228:     boffset = offset % i->sb->s_blocksize;
229:
230:     total_read = i->fsop->read(i, fd_table, buffer, count);
231:     if((count = MIN(total_read, count)) == 0) {
232:         kfree((unsigned int)buffer);
233:         return dirent_offset;
234:     }
235:
236:     while(boffset < total_read) {
237:         d = (struct procfs_dir_entry *)(buffer + boffset);
238:         if(!d->inode) {
239:             break;
240:         }
241:         dirent_len = (base_dirent_len + (d->name_len + 1)) + 3;
242:         dirent_len &= ~3; /* round up */
243:         if((doffset + sizeof(struct procfs_dir_entry)) <= count) {
244:             boffset += sizeof(struct procfs_dir_entry);
245:             offset += sizeof(struct procfs_dir_entry);
246:             doffset += sizeof(struct procfs_dir_entry);
247:             dirent->d_ino = d->inode;
248:             dirent->d_off = offset;
249:             dirent->d_reclen = dirent_len;
250:             memcpy_b(dirent->d_name, d->name, d->name_len);
251:             dirent->d_name[d->name_len] = NULL;
252:             dirent = (struct dirent *)((char *)dirent + dirent_len);
253:             dirent_offset += dirent_len;
254:         } else {
255:             break;
256:         }
257:     }
258:     fd_table->offset = offset;
259:     kfree((unsigned int)buffer);
260:     return dirent_offset;

```

```
261: }
```

fs/procfs/file.c

Page 1/2

```

1: /*
2:  * fiwix/fs/procfs/file.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/errno.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/filesystems.h>
12: #include <fiwix/fs_proc.h>
13: #include <fiwix/fcntl.h>
14: #include <fiwix/mm.h>
15: #include <fiwix/stdio.h>
16: #include <fiwix/string.h>
17:
18: struct fs_operations procfs_file_fsop = {
19:     0,
20:     0,
21:
22:     procfs_file_open,
23:     procfs_file_close,
24:     procfs_file_read,
25:     NULL, /* write */
26:     NULL, /* ioctl */
27:     procfs_file_lseek,
28:     NULL, /* readdir */
29:     NULL, /* mmap */
30:     NULL, /* select */
31:
32:     NULL, /* readlink */
33:     NULL, /* followlink */
34:     procfs_bmap,
35:     NULL, /* lookup */
36:     NULL, /* rmdir */
37:     NULL, /* link */
38:     NULL, /* unlink */
39:     NULL, /* symlink */
40:     NULL, /* mkdir */
41:     NULL, /* mknod */
42:     NULL, /* truncate */
43:     NULL, /* create */
44:     NULL, /* rename */
45:
46:     NULL, /* read_block */
47:     NULL, /* write_block */
48:
49:     NULL, /* read_inode */
50:     NULL, /* write_inode */
51:     NULL, /* ialloc */
52:     NULL, /* ifree */
53:     NULL, /* statfs */
54:     NULL, /* read_superblock */
55:     NULL, /* remount_fs */
56:     NULL, /* write_superblock */
57:     NULL, /* release_superblock */
58: };
59:
60: int procfs_file_open(struct inode *i, struct fd *fd_table)
61: {
62:     if(fd_table->flags & (O_WRONLY | O_RDWR | O_TRUNC | O_APPEND)) {
63:         return -EINVAL;
64:     }
65:     fd_table->offset = 0;
66:     return 0;
67: }

```

fs/procfs/file.c

Page 2/2

```

68:
69: int procfs_file_close(struct inode *i, struct fd *fd_table)
70: {
71:     return 0;
72: }
73:
74: int procfs_file_read(struct inode *i, struct fd *fd_table, char *buffer, __size_
t count)
75: {
76:     __off_t total_read;
77:     unsigned int boffset, bytes, size;
78:     int blksize;
79:     struct procfs_dir_entry *d;
80:     char *buf;
81:
82:     if(!(d = get_procfs_by_inode(i))) {
83:         return -EINVAL;
84:     }
85:     if(!d->data_fn) {
86:         return -EINVAL;
87:     }
88:     if(!(buf = (void *)kmalloc())) {
89:         return -ENOMEM;
90:     }
91:
92:     size = d->data_fn(buf, (i->inode >> 12) & 0xFFFF);
93:     blksize = i->sb->s_blocksize;
94:     if(fd_table->offset > size) {
95:         fd_table->offset = size;
96:     }
97:
98:     total_read = 0;
99:
100:    for(;;) {
101:        count = (fd_table->offset + count > size) ? size - fd_table->off
set : count;
102:        if(!count) {
103:            break;
104:        }
105:
106:        boffset = fd_table->offset % blksize;
107:        bytes = blksize - boffset;
108:        bytes = MIN(bytes, count);
109:        memcpy_b(buffer + total_read, buf + boffset, bytes);
110:        total_read += bytes;
111:        count -= bytes;
112:        boffset += bytes;
113:        boffset %= blksize;
114:        fd_table->offset += bytes;
115:    }
116:
117:    kfree((unsigned int)buf);
118:    return total_read;
119: }
120:
121: int procfs_file_lseek(struct inode *i, __off_t offset)
122: {
123:     return offset;
124: }

```


fs/procfs/inode.c

Page 1/2

```

1: /*
2:  * fiwix/fs/procfs/inode.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/filesystems.h>
11: #include <fiwix/fs_proc.h>
12: #include <fiwix/statfs.h>
13: #include <fiwix/sleep.h>
14: #include <fiwix/stat.h>
15: #include <fiwix/sched.h>
16: #include <fiwix/mm.h>
17: #include <fiwix/process.h>
18: #include <fiwix/errno.h>
19: #include <fiwix/stdio.h>
20: #include <fiwix/string.h>
21:
22: int procfs_read_inode(struct inode *i)
23: {
24:     int lev;
25:     __mode_t mode;
26:     __nlink_t nlink;
27:     struct procfs_dir_entry *d;
28:
29:     if((i->inode & 0xF0000FFF) == PROC_PID_INO) { /* dynamic PID dir */
30:         mode = S_IFDIR | S_IRUSR | S_IXUSR | S_IRGRP | S_IXGRP | S_IROTH
| S_IXOTH;
31:         nlink = 3;
32:         lev = PROC_PID_LEV;
33:     } else {
34:         if(!(d = get_procfs_by_inode(i))) {
35:             return NULL;
36:         }
37:         mode = d->mode;
38:         nlink = d->nlink;
39:         lev = d->lev;
40:     }
41:
42:     i->i_mode = mode;
43:     i->i_uid = 0;
44:     i->i_size = 0;
45:     i->i_atime = CURRENT_TIME;
46:     i->i_ctime = CURRENT_TIME;
47:     i->i_mtime = CURRENT_TIME;
48:     i->i_gid = 0;
49:     i->i_nlink = nlink;
50:     i->i_blocks = 0;
51:     i->i_flags = 0;
52:     i->locked = 1;
53:     i->dirty = 0;
54:     i->mount_point = NULL;
55:     i->count = 1;
56:     i->u.procfs.i_lev = lev;
57:     switch(i->i_mode & S_IFMT) {
58:         case S_IFDIR:
59:             i->fsop = &procfs_dir_fsop;
60:             break;
61:         case S_IFREG:
62:             i->fsop = &procfs_file_fsop;
63:             break;
64:         case S_IFLNK:
65:             i->fsop = &procfs_symlink_fsop;
66:             break;

```

fs/procfs/inode.c

Page 2/2

```
67:             default:
68:                 PANIC("invalid inode (%d) mode %08o.\n", i->inode, i->i_
mode);
69:             }
70:             return 0;
71: }
72:
73: int procfs_bmap(struct inode *i, __off_t offset, int mode)
74: {
75:     return i->u.procfs.i_lev;
76: }
77:
78: void procfs_statfs(struct superblock *sb, struct statfs *statfsbuf)
79: {
80:     statfsbuf->f_type = PROC_SUPER_MAGIC;
81:     statfsbuf->f_bsize = sb->s_blocksize;
82:     statfsbuf->f_blocks = 0;
83:     statfsbuf->f_bfree = 0;
84:     statfsbuf->f_bavail = 0;
85:     statfsbuf->f_files = 0;
86:     statfsbuf->f_ffree = 0;
87:     /* statfsbuf->f_fsid = ? */
88:     statfsbuf->f_namelen = NAME_MAX;
89: }
```

fs/procfs/Makefile

Page 1/1

```
1: # fiwix/fs/procfs/Makefile
2: #
3: # Copyright 2018, Jordi Sanfeliu. All rights reserved.
4: # Distributed under the terms of the Fiwix License.
5: #
6: #
7: .S.o:
8:     $(CC) -traditional -I$(INCLUDE) -c -o $@ $<
9: .c.o:
10:     $(CC) $(CFLAGS) -c -o $@ $<
11:
12: OBJS = super.o inode.o namei.o dir.o file.o symlink.o tree.o data.o
13:
14: procfs: $(OBJS)
15:     $(LD) $(LDFLAGS) -r $(OBJS) -o procfs.o
16:
17: clean:
18:     rm -f *.o
19:
```

fs/procfs/namei.c

Page 1/2

```

1: /*
2:  * fiwix/fs/procfs/namei.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/fs.h>
10: #include <fiwix/filesystems.h>
11: #include <fiwix/fs_proc.h>
12: #include <fiwix/process.h>
13: #include <fiwix/stat.h>
14: #include <fiwix/mm.h>
15: #include <fiwix/errno.h>
16: #include <fiwix/stdio.h>
17: #include <fiwix/string.h>
18:
19: int procfs_lookup(const char *name, struct inode *dir, struct inode **i_res)
20: {
21:     int len, lev;
22:     __ino_t inode;
23:     __pid_t pid;
24:     struct proc *p;
25:     struct procfs_dir_entry *pdirent;
26:
27:     pid = inode = 0;
28:     len = strlen(name);
29:     if((dir->inode & 0xF0000000) == PROC_PID_INO) {
30:         pid = (dir->inode >> 12) & 0xFFFF;
31:     }
32:     dir->count++;
33:
34:     lev = bmap(dir, 0, FOR_READING);
35:     pdirent = procfs_array[lev];
36:     while(pdirent->inode && !inode) {
37:         if(len == pdirent->name_len) {
38:             if(!(strcmp(pdirent->name, name))) {
39:                 inode = pdirent->inode;
40:                 if(pid) {
41:                     inode = (PROC_PID_INO + (pid << 12)) + (
inode & 0xFFFF);
42:                     if(strcmp(".", name) == 0) {
43:                         inode = dir->inode;
44:                     }
45:                     if(strcmp("../", name) == 0) {
46:                         inode = pdirent->inode;
47:                     }
48:                 }
49:             }
50:         }
51:         if(inode) {
52:             /*
53:              * This prevents a deadlock in iget() when
54:              * trying to lock '.' when 'dir' is the same
55:              * directory (ls -lai <dir>).
56:              */
57:             if(inode == dir->inode) {
58:                 *i_res = dir;
59:                 return 0;
60:             }
61:
62:             if(!(*i_res = iget(dir->sb, inode))) {
63:                 return -EACCES;
64:             }
65:             iput(dir);
66:             return 0;

```

fs/procfs/namei.c

Page 2/2

```
67:         }
68:         pdirent++;
69:     }
70:
71:     FOR_EACH_PROCESS(p) {
72:         if(p->state) {
73:             if(len == strlen(p->pidstr)) {
74:                 if(!(strcmp(p->pidstr, name))) {
75:                     inode = PROC_PID_INO + (p->pid << 12);
76:                 }
77:             }
78:             if(inode) {
79:                 if(!(*i_res = iget(dir->sb, inode))) {
80:                     return -EACCES;
81:                 }
82:                 iput(dir);
83:                 return 0;
84:             }
85:         }
86:     }
87:     iput(dir);
88:     return -ENOENT;
89: }
```

fs/procfs/super.c

Page 1/2

```

1: /*
2:  * fiwix/fs/procfs/super.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/errno.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/filesystems.h>
12: #include <fiwix/fs_proc.h>
13: #include <fiwix/stat.h>
14: #include <fiwix/mm.h>
15: #include <fiwix/sched.h>
16: #include <fiwix/stdio.h>
17: #include <fiwix/string.h>
18:
19: struct fs_operations procfs_fsop = {
20:     0,
21:     PROC_DEV,
22:
23:     NULL,          /* open */
24:     NULL,          /* close */
25:     NULL,          /* read */
26:     NULL,          /* write */
27:     NULL,          /* ioctl */
28:     NULL,          /* lseek */
29:     NULL,          /* readdir */
30:     NULL,          /* mmap */
31:     NULL,          /* select */
32:
33:     NULL,          /* readlink */
34:     NULL,          /* followlink */
35:     NULL,          /* bmap */
36:     NULL,          /* lookup */
37:     NULL,          /* rmdir */
38:     NULL,          /* link */
39:     NULL,          /* unlink */
40:     NULL,          /* symlink */
41:     NULL,          /* mkdir */
42:     NULL,          /* mknod */
43:     NULL,          /* truncate */
44:     NULL,          /* create */
45:     NULL,          /* rename */
46:
47:     NULL,          /* read_block */
48:     NULL,          /* write_block */
49:
50:     procfs_read_inode,
51:     NULL,          /* write_inode */
52:     NULL,          /* ialloc */
53:     NULL,          /* ifree */
54:     procfs_statfs,
55:     procfs_read_superblock,
56:     NULL,          /* remount_fs */
57:     NULL,          /* write_superblock */
58:     NULL,          /* release_superblock */
59: };
60:
61: int procfs_read_superblock(__dev_t dev, struct superblock *sb)
62: {
63:     superblock_lock(sb);
64:     sb->dev = dev;
65:     sb->fsop = &procfs_fsop;
66:     sb->s_blocksize = PAGE_SIZE;
67:

```

fs/procfs/super.c

Page 2/2

```
68:         if(!(sb->root = iget(sb, PROC_ROOT_INO))) {
69:             printk("WARNING: %s(): unable to get root inode.\n", __FUNCTION_
_);
70:             superblock_unlock(sb);
71:             return -EINVAL;
72:         }
73:         sb->root->u.procfs.i_lev = 0;
74:
75:         superblock_unlock(sb);
76:         return 0;
77:     }
78:
79: int procfs_init(void)
80: {
81:     return register_filesystem("proc", &procfs_fsop);
82: }
```

fs/procfs/symlink.c

Page 1/3

```

1: /*
2:  * fiwix/fs/procfs/symlink.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/errno.h>
10: #include <fiwix/buffer.h>
11: #include <fiwix/fs.h>
12: #include <fiwix/filesystems.h>
13: #include <fiwix/fs_proc.h>
14: #include <fiwix/stat.h>
15: #include <fiwix/stdio.h>
16: #include <fiwix/string.h>
17:
18: struct fs_operations procfs_symlink_fsop = {
19:     0,
20:     0,
21:
22:     NULL,          /* open */
23:     NULL,          /* close */
24:     NULL,          /* read */
25:     NULL,          /* write */
26:     NULL,          /* ioctl */
27:     NULL,          /* lseek */
28:     NULL,          /* readdir */
29:     NULL,          /* mmap */
30:     NULL,          /* select */
31:
32:     procfs_readlink,
33:     procfs_followlink,
34:     NULL,          /* bmap */
35:     NULL,          /* lookup */
36:     NULL,          /* rmdir */
37:     NULL,          /* link */
38:     NULL,          /* unlink */
39:     NULL,          /* symlink */
40:     NULL,          /* mkdir */
41:     NULL,          /* mknod */
42:     NULL,          /* truncate */
43:     NULL,          /* create */
44:     NULL,          /* rename */
45:
46:     NULL,          /* read_block */
47:     NULL,          /* write_block */
48:
49:     NULL,          /* read_inode */
50:     NULL,          /* write_inode */
51:     NULL,          /* ialloc */
52:     NULL,          /* ifree */
53:     NULL,          /* statfs */
54:     NULL,          /* read_superblock */
55:     NULL,          /* remount_fs */
56:     NULL,          /* write_superblock */
57:     NULL,          /* release_superblock */
58: };
59:
60: int procfs_readlink(struct inode *i, char *buffer, __size_t count)
61: {
62:     __off_t size_read;
63:     struct procfs_dir_entry *d;
64:
65:     if(!(d = get_procfs_by_inode(i))) {
66:         return -EINVAL;
67:     }

```


fs/procfs/symlink.c

Page 2/3

```

68:
69:     if(!d->data_fn) {
70:         return -EINVAL;
71:     }
72:
73:     size_read = d->data_fn(buffer, (i->inode >> 12) & 0xFFFF);
74:     return size_read;
75: }
76:
77: int procfs_followlink(struct inode *dir, struct inode *i, struct inode **i_res)
78: {
79:     __ino_t errno;
80:     __pid_t pid;
81:     struct proc *p;
82:
83:     if(!i) {
84:         return -ENOENT;
85:     }
86:     if(!(S_ISLNK(i->i_mode))) {
87:         printk("%s(): Oops, inode '%d' is not a symlink (!?)\n", __FUNC
TION_, i->inode);
88:         return 0;
89:     }
90:
91:     p = NULL;
92:     if((pid = (i->inode >> 12) & 0xFFFF)) {
93:         if(!(p = get_proc_by_pid(pid))) {
94:             return -ENOENT;
95:         }
96:     }
97:
98:     /* FIXME!
99:     if(p && p->root) {
100:         printk("(pid %d) p->root->inode = %d (count = %d)\n", p->pid, p-
>root->inode, p->root->count);
101:     }
102:     */
103:
104:     switch(i->inode & 0xF0000FFF) {
105:         case PROC_PID_CWD:
106:             if(!p->pwd) {
107:                 return -ENOENT;
108:             }
109:             *i_res = p->pwd;
110:             p->pwd->count++;
111:             iput(i);
112:             break;
113:         case PROC_PID_EXE:
114:             if(!p->vma || !p->vma->inode) {
115:                 return -ENOENT;
116:             }
117:             *i_res = p->vma->inode;
118:             p->vma->inode->count++;
119:             iput(i);
120:             break;
121:         case PROC_PID_ROOT:
122:             if(!p->root) {
123:                 return -ENOENT;
124:             }
125:             *i_res = p->root;
126:             p->root->count++;
127:             iput(i);
128:             break;
129:         default:
130:             iput(i);
131:             if((errno = parse_namei(current->pidstr, dir, i_res, NUL
L, FOLLOW_LINKS))) {

```

fs/procfs/symlink.c

Page 3/3

```
132:                                     return errno;
133:                                     }
134:     }
135:     return 0;
136: }
```

fs/procfs/tree.c

Page 1/2

```

1: /*
2:  * fiwix/fs/procfs/tree.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/stat.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/fs_proc.h>
12: #include <fiwix/errno.h>
13: #include <fiwix/stdio.h>
14: #include <fiwix/string.h>
15:
16: #define DIR      S_IFDIR | S_IRUSR | S_IXUSR | S_IRGRP | S_IXGRP | S_IROTH | \
17:                S_IXOTH /* dr-xr-xr-x */
18: #define REG      S_IFREG | S_IRUSR | S_IRGRP | S_IROTH /* -r--r--r-- */
19: #define REGUSR   S_IFREG | S_IRUSR /* -r----- */
20: #define LNK      S_IFLNK | S_IRWXU | S_IRWXG | S_IRWXO /* lrwxrwxrwx */
21: #define LNKPID   S_IFLNK | S_IRWXU /* lrwx----- */
22:
23: /*
24:  * WARNING: every time a new entry is added to this array you must also change
25:  * the PROC_ARRAY_ENTRIES value defined in fs_proc.h.
26:  */
27: struct procfs_dir_entry procfs_array[][PROC_ARRAY_ENTRIES + 1] = {
28:     { /* [0] / */
29:         { 1, DIR, 2, 0, 1, ".", NULL },
30:         { 2, DIR, 2, 0, 2, "..", NULL },
31:         { 3, DIR, 3, 3, 3, "sys", NULL },
32:         { 4, REG, 1, 0, 7, "cmdline", data_proc_cmdline },
33:         { 5, REG, 1, 0, 7, "cpuinfo", data_proc_cpuinfo },
34:         { 6, REG, 1, 0, 7, "devices", data_proc_devices },
35:         { 7, REG, 1, 0, 3, "dma", data_proc_dma },
36:         { 8, REG, 1, 0, 11, "filesystems", data_proc_filesystems },
37:         { 9, REG, 1, 0, 10, "interrupts", data_proc_interrupts },
38:         { 10, REG, 1, 0, 7, "loadavg", data_proc_loadavg },
39:         { 11, REG, 1, 0, 5, "locks", data_proc_locks },
40:         { 12, REG, 1, 0, 7, "meminfo", data_proc_meminfo },
41:         { 13, REG, 1, 0, 6, "mounts", data_proc_mounts },
42:         { 14, REG, 1, 0, 10, "partitions", data_proc_partitions },
43:         { 15, REG, 1, 0, 3, "rtc", data_proc_rtc },
44:         { 16, LNK, 1, 0, 4, "self", data_proc_self },
45:         { 17, REG, 1, 0, 4, "stat", data_proc_stat },
46:         { 18, REG, 1, 0, 6, "uptime", data_proc_uptime },
47:         { 19, REG, 1, 0, 7, "version", data_proc_fullversion },
48:         { 0, 0, 0, 0, 0, NULL, NULL }
49:     },
50:     { /* [1] /PID/ */
51:         { 1000, DIR, 2, 1, 1, ".", NULL },
52:         { 1, DIR, 2, 0, 2, "..", NULL },
53:         /* { PROC_PID_FD, DIR, 2, 2, 2, "fd", data_proc_pid_fd }, */
54:         { PROC_PID_CMDLINE, REG, 1, 1, 7, "cmdline", data_proc_pid_cmdline }
55:     },
56:     { PROC_PID_CWD, LNKPID, 1, 1, 3, "cwd", data_proc_pid_cwd },
57:     { PROC_PID_ENVIRON, REGUSR, 1, 1, 7, "environ", data_proc_pid_environ }
58: },
59: { PROC_PID_EXE, LNKPID, 1, 1, 3, "exe", data_proc_pid_exe },
60: { PROC_PID_MAPS, REG, 1, 1, 4, "maps", data_proc_pid_maps },
61: { PROC_PID_MOUNTINFO, REG, 1, 1, 9, "mountinfo", data_proc_pid_mountinf
62: },
63: { PROC_PID_ROOT, LNKPID, 1, 1, 4, "root", data_proc_pid_root },
64: { PROC_PID_STAT, REG, 1, 1, 4, "stat", data_proc_pid_stat },
65: { PROC_PID_STATUS, REG, 1, 1, 6, "status", data_proc_pid_status }
66: },
67: { 0, 0, 0, 0, 0, NULL, NULL }

```

fs/procfs/tree.c

Page 2/2

```

64:     },
65:
66:     {
67:     },
68:
69:     { /* [3] /sys/ */
70:     { 3,     DIR,  2, 3, 1,  ".",      NULL },
71:     { 1,     DIR,  2, 0, 2,  "..",     NULL },
72:     { 2001,  DIR,  2, 4, 6,  "kernel", NULL },
73:     { 0, 0, 0, 0, 0, NULL, NULL }
74:     },
75:     { /* [4] /sys/kernel/ */
76:     { 2001,  DIR,  2, 4, 1,  ".",      NULL },
77:     { 3,     DIR,  2, 3, 2,  "..",     NULL },
78:     { 3001,  REG,  1, 4, 10, "domainname", data_proc_domainname },
79:     { 3002,  REG,  1, 4, 8,  "file-max",  data_proc_filemax },
80:     { 3003,  REG,  1, 4, 7,  "file-nr",   data_proc_filenr },
81:     { 3004,  REG,  1, 4, 8,  "hostname",  data_proc_hostname },
82:     { 3005,  REG,  1, 4, 9,  "inode-max", data_proc_inodemax },
83:     { 3006,  REG,  1, 4, 8,  "inode-nr",  data_proc_inodenr },
84:     { 3007,  REG,  1, 4, 9,  "osrelease", data_proc_osrelease },
85:     { 3008,  REG,  1, 4, 6,  "ostype",    data_proc_ostype },
86:     { 3009,  REG,  1, 4, 7,  "version",   data_proc_version },
87:     { 0, 0, 0, 0, 0, NULL, NULL }
88:     }
89: };
90:
91: struct procfs_dir_entry * get_procfs_by_inode(struct inode *i)
92: {
93:     __ino_t inode;
94:     int n, lev;
95:     struct procfs_dir_entry *d;
96:
97:     inode = i->inode;
98:     for(lev = 0; procfs_array[lev]; lev++) {
99:         if(lev == PROC_PID_LEV) { /* PID entries */
100:             if((i->inode & 0xF0000000) == PROC_PID_INO) {
101:                 inode = i->inode & 0xF0000FFF;
102:             }
103:         }
104:         d = procfs_array[lev];
105:         for(n = 0; n < PROC_ARRAY_ENTRIES && d->inode; n++) {
106:             if(d->inode == inode) {
107:                 return d;
108:             }
109:             d++;
110:         }
111:     }
112:
113:     return NULL;
114: }

```

mm/alloc.c

Page 1/1

```
1: /*
2:  * fiwix/mm/alloc.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/mm.h>
9: #include <fiwix/stdio.h>
10: #include <fiwix/string.h>
11:
12: /*
13:  * The implementation of kernel memory allocation is extremely simple, it works
14:  * with a granularity of PAGE_SIZE (4096 bytes). There is indeed a lot of room
15:  * for improvements here.
16:  */
17: unsigned int kmalloc(void)
18: {
19:     struct page *pg;
20:     unsigned int addr;
21:
22:     if((pg = get_free_page())) {
23:         addr = pg->page << PAGE_SHIFT;
24:         return P2V(addr);
25:     }
26:
27:     /* out of memory! */
28:     return 0;
29: }
30:
31: void kfree(unsigned int addr)
32: {
33:     addr = V2P(addr);
34:     release_page(addr >> PAGE_SHIFT);
35: }
```

mm/bios_map.c

Page 1/2

```

1:  /*
2:  * fiwix/mm/bios_map.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8:  #include <fiwix/kernel.h>
9:  #include <fiwix/mm.h>
10: #include <fiwix/bios.h>
11: #include <fiwix/stdio.h>
12: #include <fiwix/string.h>
13:
14: /* check if an specific address is available in the BIOS memory map */
15: int addr_in_bios_map(unsigned int addr)
16: {
17:     int n;
18:     struct bios_mem_map *bmm;
19:
20:     bmm = &bios_mem_map[0];
21:     for(n = 0; n < NR_BIOS_MM_ENT; n++, bmm++) {
22:         if(bmm->to && bmm->type == BIOS_MEM_AVAIL) {
23:             if(addr >= bmm->from && addr < (bmm->to & PAGE_MASK)) {
24:                 return 1;
25:             }
26:         }
27:     }
28:     return 0;        /* not in BIOS map or not available (reserved, ...) */
29: }
30:
31: void bios_map_init(memory_map_t *bmmmap_addr, unsigned long int bmmmap_length)
32: {
33:     unsigned int n;
34:     unsigned int mem_from, mem_to, len_low, len_high;
35:     memory_map_t *bmmmap;
36:     char *bios_mem_type[] = { NULL, "available", "reserved",
37:                             "ACPI Reclaim", "ACPI NVS", "unusable",
38:                             "disabled" };
39:
40:     bmmmap = bmmmap_addr;
41:     if(bmmmap) {
42:         n = 0;
43:
44:         while((unsigned int)bmmmap < (unsigned int)bmmmap_addr + bmmmap_length) {
45:             mem_from = (unsigned int)bmmmap->base_addr_low;
46:             len_low = (unsigned int)bmmmap->length_low;
47:             if((((mem_from >> 16) & 0xFFFF) + ((len_low >> 16) & 0xFFFF) > 0xFFFF) {
48:                 mem_to = ~0;
49:                 len_high = (mem_from >> 16) + (len_low >> 16);
50:                 len_high >>= 16;
51:             } else {
52:                 mem_to = mem_from + len_low;
53:                 len_high = 0;
54:             }
55:             printk("%s      0x%08X%08X-0x%08X%08X %s\n",
56:                 n ? "      " : "memory",
57:                 bmmmap->base_addr_high, bmmmap->base_addr_low,
58:                 len_high, mem_from + len_low,
59:                 bios_mem_type[(int)bmmmap->type]);
60:             /* only memory addresses below 4GB are accepted */
61:             if(!bmmmap->base_addr_high) {
62:                 if(n < NR_BIOS_MM_ENT && len_low) {
63:                     bios_mem_map[n].from = mem_from;
64:                     bios_mem_map[n].to = mem_to;
65:                     bios_mem_map[n].type = (int)bmmmap->type;

```

mm/bios_map.c

Page 2/2

```
66:                                     n++;
67:                                     }
68:                                     }
69:                                     bmmap = (memory_map_t *)((unsigned int)bmmap + bmmap->size
ze + sizeof(bmmap->size));
70:                                     }
71:     } else {
72:         printk("WARNING: your BIOS has not provided a memory map.\n");
73:         bios_mem_map[0].from = 0;
74:         bios_mem_map[0].to = _memsize * 1024;
75:         bios_mem_map[0].type = BIOS_MEM_AVAIL;
76:         bios_mem_map[1].from = 0x00100000;
77:         bios_mem_map[1].to = (_extmemsize + 1024) * 1024;
78:         bios_mem_map[1].type = BIOS_MEM_AVAIL;
79:     }
80:     kstat.physical_pages = (_extmemsize + 1024) >> 2;
81:
82:     /*
83:     * This truncates to 1GB since it's the maximum physical memory
84:     * currently supported.
85:     */
86:     if(kstat.physical_pages & (0x40000000 >> PAGE_SHIFT)) {
87:         kstat.physical_pages &= (0x40000000 >> PAGE_SHIFT);
88:         printk("WARNING: only up to 1GB of physical memory will be used.
\n");
89:     }
90: }
```

mm/fault.c

Page 1/5

```

1: /*
2:  * fiwix/mm/fault.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/sigcontext.h>
10: #include <fiwix/asm.h>
11: #include <fiwix/mm.h>
12: #include <fiwix/process.h>
13: #include <fiwix/traps.h>
14: #include <fiwix/sched.h>
15: #include <fiwix/fs.h>
16: #include <fiwix/mman.h>
17: #include <fiwix/errno.h>
18: #include <fiwix/stdio.h>
19: #include <fiwix/string.h>
20:
21: /* send the SIGSEGV signal to the ofending process */
22: static void send_sigsegv(struct sigcontext *sc)
23: {
24:     dump_registers(14, sc);
25:     printk("Memory map:\n");
26:     show_vma_regions(current);
27:     send_sig(current, SIGSEGV);
28: }
29:
30: static int page_protection_violation(struct vma *vma, unsigned int cr2, struct s
igcontext *sc)
31: {
32:     unsigned int *pgdir;
33:     unsigned int *pgtbl;
34:     unsigned int page, newpage;
35:     unsigned int pde, pte;
36:     struct page *pg;
37:
38:     pde = GET_PGDIR(cr2);
39:     pte = GET_PGTBL(cr2);
40:     pgdir = (unsigned int *)P2V(current->tss.cr3);
41:     pgtbl = (unsigned int *)P2V((pgdir[pde] & PAGE_MASK));
42:     page = (pgtbl[pte] & PAGE_MASK) >> PAGE_SHIFT;
43:
44:     pg = &page_table[page];
45:
46:     /* Copy On Write feature */
47:     if(pg->count > 1) {
48:         /* a page not marked as COW means it's read-only */
49:         if(!(pg->flags & PAGE_COW)) {
50:             printk("Oops!, page %d NOT marked for COW.\n", pg->page)
;
51:             send_sigsegv(sc);
52:             return 0;
53:         }
54:         if(!(newpage = kmalloc())) {
55:             printk("%s(): not enough memory!\n", __FUNCTION__);
56:             return 1;
57:         }
58:         current->rss++;
59:         memcpy_b((void *)newpage, (void *)P2V((page << PAGE_SHIFT)), PAG
E_SIZE);
60:         pgtbl[pte] = V2P(newpage) | PAGE_PRESENT | PAGE_RW | PAGE_USER;
61:         kfree(P2V((page << PAGE_SHIFT)));
62:         current->rss--;
63:         invalidate_tlb();
64:         return 0;

```


mm/fault.c

Page 2/5

```

65:         } else {
66:             /* last page of Copy On Write procedure */
67:             if(pg->count == 1) {
68:                 /* a page not marked as COW means it's read-only */
69:                 if(!(pg->flags & PAGE_COW)) {
70:                     printk("Oops!, last page %d NOT marked for COW.\n",
n", pg->page);
71:                     send_sigsegv(sc);
72:                     return 0;
73:                 }
74:                 pgtbl[pte] = (page << PAGE_SHIFT) | PAGE_PRESENT | PAGE_
RW | PAGE_USER;
75:                 invalidate_tlb();
76:                 return 0;
77:             }
78:         }
79:         printk("WARNING: %s(): page %d with pg->count = 0!\n", __FUNCTION__, pg-
>page);
80:         return 1;
81:     }
82:
83:     static int page_not_present(struct vma *vma, unsigned int cr2, struct sigcontext
*sc)
84:     {
85:         unsigned int page, file_offset;
86:         struct page *pg;
87:
88:         if(!vma) {
89:             if(cr2 >= (sc->oldesp - 32)) {
90:                 if(!(vma = find_vma_region(KERNEL_BASE_ADDR - 1))) {
91:                     printk("WARNING: %s(): process %d doesn't have a
n stack region in vma!\n", __FUNCTION__, current->pid);
92:                     send_sigsegv(sc);
93:                     return 0;
94:                 } else {
95:                     /* assuming stack will never reach heap */
96:                     vma->start = cr2;
97:                     vma->start = vma->start & PAGE_MASK;
98:                 }
99:             }
100:         }
101:
102:         /* if still a non-valid vma is found then kill the process! */
103:         if(!vma || vma->prot == PROT_NONE) {
104:             send_sigsegv(sc);
105:             return 0;
106:         }
107:
108:         /* fill the page with its corresponding file content */
109:         if(vma->inode) {
110:             file_offset = (cr2 & PAGE_MASK) - vma->start + vma->offset;
111:             file_offset &= PAGE_MASK;
112:             pg = NULL;
113:
114:             if(!(vma->prot & PROT_WRITE) || vma->flags & MAP_SHARED) {
115:                 /* check if it's already in cache */
116:                 if((pg = search_page_hash(vma->inode, file_offset))) {
117:                     if(!map_page(current, cr2, (unsigned int)V2P(pg-
>data), vma->prot)) {
118:                         printk("%s(): Oops, map_page() returned
0!\n", __FUNCTION__);
119:                         return 1;
120:                     }
121:                     page = (unsigned int)pg->data;
122:                 }
123:             }
124:             if(!pg) {

```

mm/fault.c

Page 3/5

```

125:             if(!(page = map_page(current, cr2, 0, vma->prot))) {
126:                 printk("%s(): Oops, map_page() returned 0!\n", _
_FUNCTION__);
127:                 return 1;
128:             }
129:             pg = &page_table[V2P(page) >> PAGE_SHIFT];
130:             if(bread_page(pg, vma->inode, file_offset, vma->prot, vm
a->flags)) {
131:                 unmap_page(page);
132:                 return 1;
133:             }
134:             current->usage.ru_majflt++;
135:         }
136:     } else {
137:         current->usage.ru_minflt++;
138:         page = 0;
139:     }
140:
141:     if(vma->flags & ZERO_PAGE) {
142:         if(!page) {
143:             if(!(page = map_page(current, cr2, 0, vma->prot))) {
144:                 printk("%s(): Oops, map_page() returned 0!\n", _
_FUNCTION__);
145:                 return 1;
146:             }
147:         }
148:         memset_b((void *) (page & PAGE_MASK), NULL, PAGE_SIZE);
149:     }
150:
151:     return 0;
152: }
153:
154: /*
155:  * Exception 0xE: Page Fault
156:  *
157:  *           +-----+-----+-----+-----+-----+-----+
158:  *           | user |kernel|  PV  |  PF  | read |write |
159:  * +-----+-----+-----+-----+-----+-----+
160:  * |the page   | U1   |   K1| U1 K1|       | U1 K1|   K1|
161:  * |has        | U2   |   K2| U2   |       | K2|   U2 K2|
162:  * |a vma region| U3   |   |       | U3   | U3   | U3   |
163:  * +-----+-----+-----+-----+-----+-----+
164:  * |the page   | U1   |   K1| U1 K1|   K1| U1 K1| U1 K1|
165:  * |doesn't have| U2   |   |       | U2   | U2   | U2   |
166:  * |a vma region|     |   |       |     |     |     |
167:  * +-----+-----+-----+-----+-----+-----+
168:  *
169:  * U1 - vma + user + PV + read
170:  *      (vma page in user-mode, page-violation during read)
171:  *      U1.1) if flags match                -> Demand paging
172:  *      U1.2) if flags don't match          -> SIGSEV
173:  *
174:  * U2 - vma + user + PV + write
175:  *      (vma page in user-mode, page-violation during write)
176:  *      U2.1) if flags match                -> Copy-On-Write
177:  *      U2.2) if flags don't match          -> SIGSEGV
178:  *
179:  * U3 - vma + user + PF + (read | write)    -> Demand paging
180:  *      (vma page in user-mode, page-fault during read or write)
181:  *
182:  * K1 - vma + kernel + PV + (read | write)  -> PANIC
183:  *      (vma page in kernel-mode, page-violation during read or write)
184:  * K2 - vma + kernel + PF + (read | write)  -> Demand paging (mmap)
185:  *      (vma page in kernel-mode, page-fault during read or write)
186:  *
187:  * -----
188:  *

```

mm/fault.c

Page 4/5

```

189:  * U1 - !vma + user + PV + (read | write)      -> SIGSEGV
190:  *      (!vma page in user-mode, page-violation during read or write)
191:  * U2 - !vma + user + PF + (read | write)      -> STACK grows
192:  *      (!vma page in user-mode, page-fault during read or write)
193:  *
194:  * K1 - !vma + kernel + (PV | PF) + (read | write)  -> PANIC
195:  *      (!vma page in kernel-mode, page-fault or page-violation during read
196:  *      or write)
197:  */
198: void do_page_fault(unsigned int trap, struct sigcontext *sc)
199: {
200:     unsigned int cr2;
201:     struct vma *vma;
202:
203:     GET_CR2(cr2);
204:     if((vma = find_vma_region(cr2))) {
205:
206:         /* in user mode */
207:         if(sc->err & PFAULT_U) {
208:             if(sc->err & PFAULT_V) {          /* violation */
209:                 if(sc->err & PFAULT_W) {
210:                     if((page_protection_violation(vma, cr2,
sc))) {
211:                         send_sig(current, SIGKILL);
212:                     }
213:                     return;
214:                 }
215:                 send_sigsegv(sc);
216:             } else {                          /* page not present */
217:                 if((page_not_present(vma, cr2, sc))) {
218:                     send_sig(current, SIGKILL);
219:                 }
220:             }
221:             return;
222:
223:             /* in kernel mode */
224:         } else {
225:             /*
226:             * WP bit marks the order: first check if the page is
227:             * present, then check for protection violation.
228:             */
229:             if(!(sc->err & PFAULT_V)) {      /* page not present */
230:                 if((page_not_present(vma, cr2, sc))) {
231:                     send_sig(current, SIGKILL);
232:                     printk("%s(): kernel was unable to read
a page of process '%s' (pid %d).\n", __FUNCTION__, current->argv0, current->pid);
233:                 }
234:                 return;
235:             }
236:             if(sc->err & PFAULT_W) {        /* copy-on-write? */
237:                 if((page_protection_violation(vma, cr2, sc))) {
238:                     send_sig(current, SIGKILL);
239:                     printk("%s(): kernel was unable to write
a page of process '%s' (pid %d).\n", __FUNCTION__, current->argv0, current->pid);
240:                 }
241:                 return;
242:             }
243:         }
244:     } else {
245:         /* in user mode */
246:         if(sc->err & PFAULT_U) {
247:             if(sc->err & PFAULT_V) {          /* violation */
248:                 send_sigsegv(sc);
249:             } else {                          /* stack? */
250:                 if((page_not_present(vma, cr2, sc))) {
251:                     send_sig(current, SIGKILL);
252:                 }

```

mm/fault.c

Page 5/5

```
253:                }
254:                return;
255:            }
256:        }
257:
258:        dump_registers(trap, sc);
259:        show_vma_regions(current);
260:        PANIC("\n");
261: }
```

mm/Makefile

Page 1/1

```
1: # fiwix/mm/Makefile
2: #
3: # Copyright 2018, Jordi Sanfeliu. All rights reserved.
4: # Distributed under the terms of the Fiwix License.
5: #
6: #
7: .S.o:
8:     $(CC) -traditional -I$(INCLUDE) -c -o $@ $<
9: .c.o:
10:     $(CC) $(CFLAGS) -c -o $@ $<
11:
12: OBJS = bios_map.o memory.o page.o alloc.o fault.o mmap.o swapper.o
13:
14: mm:    $(OBJS)
15:     $(LD) $(LDFLAGS) -r $(OBJS) -o mm.o
16:
17: clean:
18:     rm -f *.o
19:
```

mm/memory.c

Page 1/7

```

1: /*
2:  * fiwix/mm/memory.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/asm.h>
10: #include <fiwix/mm.h>
11: #include <fiwix/mman.h>
12: #include <fiwix/bios.h>
13: #include <fiwix/ramdisk.h>
14: #include <fiwix/process.h>
15: #include <fiwix/buffer.h>
16: #include <fiwix/fs.h>
17: #include <fiwix/filesystems.h>
18: #include <fiwix/stdio.h>
19: #include <fiwix/string.h>
20:
21: #define KERNEL_TEXT_SIZE      ((int)_etext - (KERNEL_BASE_ADDR + KERNEL_ENTRY_
ADDR))
22: #define KERNEL_DATA_SIZE     ((int)_edata - (int)_etext)
23: #define KERNEL_BSS_SIZE      ((int)_end - (int)_edata)
24:
25: #define PGDIR_4MB_ADDR        0x90000
26:
27: unsigned int *kpage_dir;
28: unsigned int *kpage_table;
29:
30: unsigned int _last_data_addr;
31:
32: unsigned int proc_table_size = 0;
33: struct proc *proc_table;
34:
35: unsigned int buffer_table_size = 0;
36: unsigned int buffer_hash_table_size = 0;
37: struct buffer *buffer_table;
38: struct buffer **buffer_hash_table;
39:
40: unsigned int inode_table_size = 0;
41: unsigned int inode_hash_table_size = 0;
42: struct inode *inode_table;
43: struct inode **inode_hash_table;
44:
45: unsigned int fd_table_size = 0;
46: struct fd *fd_table;
47:
48: unsigned int mount_table_size = 0;
49: struct mount *mount_table;
50:
51: struct ramdisk ramdisk_table[RAMDISK_MINORS];
52:
53: unsigned int page_table_size = 0;
54: unsigned int page_hash_table_size = 0;
55: struct page *page_table;
56: struct page **page_hash_table;
57:
58: static void map_kaddr(unsigned int from, unsigned int to, int flags)
59: {
60:     unsigned int n;
61:     unsigned int *pgtbl;
62:     unsigned int pde, pte;
63:
64:     for(n = from >> PAGE_SHIFT; n < (to >> PAGE_SHIFT); n++) {
65:         pde = GET_PGDIR(n << PAGE_SHIFT);
66:         pte = GET_PGTBL(n << PAGE_SHIFT);

```

mm/memory.c

Page 2/7

```

67:         if(!(kpage_dir[pde] & ~PAGE_MASK)) {
68:             unsigned int addr;
69:             addr = _last_data_addr;
70:             _last_data_addr += PAGE_SIZE;
71:             kpage_dir[pde] = addr | flags;
72:             memset_b((void *)addr, NULL, PAGE_SIZE);
73:         }
74:         pgtbl = (unsigned int *) (kpage_dir[pde] & PAGE_MASK);
75:         pgtbl[pte] = (kpage_table[(pde * 1024) + pte] & PAGE_MASK) | fla
gs;
76:     }
77: }
78:
79: void bss_init(void)
80: {
81:     memset_b((void *)((int)_edata), NULL, KERNEL_BSS_SIZE);
82: }
83:
84: /*
85:  * This function creates a minimal Page Directory covering only the first 4MB
86:  * of physical memory. Just enough to boot the kernel.
87:  * (it returns the address to be used by the CR3 register)
88:  */
89: unsigned int setup_minmem(void)
90: {
91:     int n;
92:     unsigned int addr;
93:     short int pd, mb4;
94:
95:     mb4 = 1;          /* 4MB units */
96:     addr = KERNEL_BASE_ADDR + PGDIR_4MB_ADDR;
97:
98:     kpage_dir = (unsigned int *)addr;
99:     memset_b(kpage_dir, NULL, PAGE_SIZE);
100:
101:     addr += PAGE_SIZE;
102:     kpage_table = (unsigned int *)addr;
103:     memset_b(kpage_table, NULL, PAGE_SIZE * mb4);
104:
105:     for(n = 0; n < (1024 * mb4); n++) {
106:         kpage_table[n] = (n << PAGE_SHIFT) | PAGE_PRESENT | PAGE_RW;
107:         if(!(n % 1024)) {
108:             pd = n / 1024;
109:             kpage_dir[pd] = (unsigned int)(addr + (PAGE_SIZE * pd) +
0x40000000) | PAGE_PRESENT | PAGE_RW;
110:             kpage_dir[GET_PGDIR(KERNEL_BASE_ADDR) + pd] = (unsigned
int)(addr + (PAGE_SIZE * pd) + 0x40000000) | PAGE_PRESENT | PAGE_RW;
111:         }
112:     }
113:     return (unsigned int)kpage_dir + 0x40000000;
114: }
115:
116: /* returns the mapped address of a virtual address */
117: unsigned int get_mapped_addr(struct proc *p, unsigned int addr)
118: {
119:     unsigned int *pgdir, *pgtbl;
120:     unsigned int pde, pte;
121:
122:     pgdir = (unsigned int *)P2V(p->tss.cr3);
123:     pde = GET_PGDIR(addr);
124:     pte = GET_PGTBL(addr);
125:     pgtbl = (unsigned int *)P2V((pgdir[pde] & PAGE_MASK));
126:     return pgtbl[pte];
127: }
128:
129: int clone_pages(struct proc *child)
130: {

```

mm/memory.c

Page 3/7

```

131:     unsigned int *src_pgdirt, *dst_pgdirt;
132:     unsigned int *src_pgtbl, *dst_pgtbl;
133:     unsigned int pde, pte;
134:     unsigned int p_page, c_page;
135:     unsigned int n, n2, pages;
136:     struct page *pg;
137:     struct vma *vma;
138:
139:     src_pgdirt = (unsigned int *)P2V(current->tss.cr3);
140:     dst_pgdirt = (unsigned int *)P2V(child->tss.cr3);
141:     vma = current->vma;
142:
143:     for(n = 0, pages = 0; n < VMA_REGIONS && vma->start; n++, vma++) {
144:         for(n2 = vma->start; n2 < vma->end; n2 += PAGE_SIZE) {
145:             pde = GET_PGDIR(n2);
146:             pte = GET_PGTBL(n2);
147:             if(src_pgdirt[pde] & PAGE_PRESENT) {
148:                 src_pgtbl = (unsigned int *)P2V((src_pgdirt[pde]
& PAGE_MASK));
149:                 if(!(dst_pgdirt[pde] & PAGE_PRESENT)) {
150:                     if(!(c_page = kmalloc())) {
151:                         printk("%s(): returning 0!\n", __
_FUNCTION__);
152:                         return 0;
153:                     }
154:                     current->rss++;
155:                     pages++;
156:                     dst_pgdirt[pde] = V2P(c_page) | PAGE_PRES
ENT | PAGE_RW | PAGE_USER;
157:                     memset_b((void *)c_page, NULL, PAGE_SIZE
);
158:                 }
159:                 dst_pgtbl = (unsigned int *)P2V((dst_pgdirt[pde]
& PAGE_MASK));
160:                 if(src_pgtbl[pte] & PAGE_PRESENT) {
161:                     p_page = src_pgtbl[pte] >> PAGE_SHIFT;
162:                     pg = &page_table[p_page];
163:                     if(pg->flags & PAGE_RESERVED) {
164:                         continue;
165:                     }
166:                     src_pgtbl[pte] &= ~PAGE_RW;
167:                     /* mark as COW only writable pages */
168:                     if(vma->prot & PROT_WRITE) {
169:                         pg->flags |= PAGE_COW;
170:                     }
171:                     dst_pgtbl[pte] = src_pgtbl[pte];
172:                     if(!valid_page((dst_pgtbl[pte] & PAGE_MA
SK) >> PAGE_SHIFT)) {
173:                         PANIC("%s: missing page %d durin
g copy-on-write process.\n", __FUNCTION__, (dst_pgtbl[pte] & PAGE_MASK) >> PAGE_SHIFT);
174:                     }
175:                     pg = &page_table[(dst_pgtbl[pte] & PAGE_
MASK) >> PAGE_SHIFT];
176:                     pg->count++;
177:                 }
178:             }
179:         }
180:     }
181:     return pages;
182: }
183:
184: int free_page_tables(struct proc *p)
185: {
186:     unsigned int *pgdir;
187:     unsigned int n, count;
188:
189:     pgdir = (unsigned int *)P2V(p->tss.cr3);

```


mm/memory.c

Page 4/7

```

190:         for(n = 0, count = 0; n < PD_ENTRIES; n++) {
191:             if((pgdir[n] & (PAGE_PRESENT | PAGE_RW | PAGE_USER)) == (PAGE_PR
ESENT | PAGE_RW | PAGE_USER)) {
192:                 kfree(P2V(pgdir[n]) & PAGE_MASK);
193:                 pgdir[n] = NULL;
194:                 count++;
195:             }
196:         }
197:         return count;
198:     }
199:
200: unsigned int map_page(struct proc *p, unsigned int vaddr, unsigned int addr, uns
igned int prot)
201: {
202:     unsigned int *pgdir, *pgtbl;
203:     unsigned int vpage;
204:     int pde, pte;
205:
206:     pgdir = (unsigned int *)P2V(p->tss.cr3);
207:     pde = GET_PGDIR(vaddr);
208:     pte = GET_PGTBL(vaddr);
209:
210:     if(!(pgdir[pde] & PAGE_PRESENT)) {           /* allocating page table */
211:         if(!(vpage = kmalloc())) {
212:             return 0;
213:         }
214:         p->rss++;
215:         pgdir[pde] = V2P(vpage) | PAGE_PRESENT | PAGE_RW | PAGE_USER;
216:         memset_b((void *)vpage, NULL, PAGE_SIZE);
217:     }
218:     pgtbl = (unsigned int *)P2V((pgdir[pde] & PAGE_MASK));
219:     if(!(pgtbl[pte] & PAGE_PRESENT)) {           /* allocating page */
220:         if(!addr) {
221:             if(!(addr = kmalloc())) {
222:                 return 0;
223:             }
224:             addr = V2P(addr);
225:             p->rss++;
226:         }
227:     }
228:     pgtbl[pte] = addr | PAGE_PRESENT | PAGE_USER;
229:     if(prot & PROT_WRITE) {
230:         pgtbl[pte] |= PAGE_RW;
231:     }
232:     return P2V(addr);
233: }
234:
235: int unmap_page(unsigned int vaddr)
236: {
237:     unsigned int *pgdir, *pgtbl;
238:     unsigned int addr;
239:     int pde, pte;
240:
241:     pgdir = (unsigned int *)P2V(current->tss.cr3);
242:     pde = GET_PGDIR(vaddr);
243:     pte = GET_PGTBL(vaddr);
244:     if(!(pgdir[pde] & PAGE_PRESENT)) {
245:         printk("WARNING: %s(): trying to unmap an unallocated pde '0x%08
x'\n", __FUNCTION__, vaddr);
246:         return 1;
247:     }
248:
249:     pgtbl = (unsigned int *)P2V((pgdir[pde] & PAGE_MASK));
250:     if(!(pgtbl[pte] & PAGE_PRESENT)) {
251:         printk("WARNING: %s(): trying to unmap an unallocated page '0x%0
8x'\n", __FUNCTION__, vaddr);
252:         return 1;

```

mm/memory.c

Page 5/7

```

253:     }
254:
255:     addr = pgtbl[pte] & PAGE_MASK;
256:     pgtbl[pte] = NULL;
257:     kfree(P2V(addr));
258:     current->rss--;
259:     return 0;
260: }
261:
262: void mem_init(void)
263: {
264:     unsigned int pages, sizek;
265:     unsigned int n;
266:     unsigned int physical_page_tables;
267:     unsigned int physical_memory;
268:
269:     physical_page_tables = (kstat.physical_pages / 1024) + ((kstat.physical_
pages % 1024) ? 1 : 0);
270:     physical_memory = (kstat.physical_pages << PAGE_SHIFT); /* in bytes */
271:
272:     /* Page Directory will be aligned to the next page */
273:     _last_data_addr = PAGE_ALIGN(_last_data_addr);
274:     kpage_dir = (unsigned int *)_last_data_addr;
275:     memset_b(kpage_dir, NULL, PAGE_SIZE);
276:     _last_data_addr += PAGE_SIZE;
277:
278:     /* Page Tables */
279:     kpage_table = (unsigned int *)_last_data_addr;
280:     memset_b(kpage_table, NULL, physical_page_tables * PAGE_SIZE);
281:     _last_data_addr += physical_page_tables * PAGE_SIZE;
282:
283:     /* Page Directory and Page Tables initialization */
284:     for(n = 0; n < kstat.physical_pages; n++) {
285:         kpage_table[n] = (n << PAGE_SHIFT) | PAGE_PRESENT | PAGE_RW;
286:     }
287:     for(n = 0; n < physical_page_tables; n++) {
288:         kpage_dir[GET_PGDIR(KERNEL_BASE_ADDR) + n] = (unsigned int)&kpag
e_table[n * 1024] | PAGE_PRESENT | PAGE_RW;
289:     }
290:
291:     map_kaddr(0xA0000, KERNEL_ENTRY_ADDR, PAGE_PRESENT | PAGE_RW);
292:     map_kaddr(KERNEL_ENTRY_ADDR, _last_data_addr, PAGE_PRESENT | PAGE_RW);
293:     /* printk("_last_data_addr = 0x%08x-0x%08x (kernel)\n", KERNEL_ENTRY_ADDR,
_last_data_addr); */
294:     activate_kpage_dir();
295:
296:     /* since Page Directory is now activated we can use virtual addresses */
297:     _last_data_addr = P2V(_last_data_addr);
298:
299:
300:     /* reserve memory space for proc_table[NR_PROCS] */
301:     proc_table_size = PAGE_ALIGN(sizeof(struct proc) * NR_PROCS);
302:     if(!addr_in_bios_map(V2P(_last_data_addr) + proc_table_size)) {
303:         PANIC("Not enough memory for proc_table.\n");
304:     }
305:     /* printk("_last_data_addr = 0x%08x-0x%08x (proc_table)\n", _last_data_addr
, _last_data_addr + proc_table_size); */
306:     proc_table = (struct proc *)_last_data_addr;
307:     _last_data_addr += proc_table_size;
308:
309:
310:     /* reserve memory space for buffer_table */
311:     buffer_table_size = (kstat.physical_pages * BUFFER_PERCENTAGE) / 100;
312:     buffer_table_size *= sizeof(struct buffer);
313:     pages = buffer_table_size >> PAGE_SHIFT;
314:     buffer_table_size = !pages ? 4096 : pages << PAGE_SHIFT;
315:     /* printk("_last_data_addr = 0x%08x-0x%08x (buffer_table)\n", _last_data_ad

```

mm/memory.c

Page 6/7

```

dr, _last_data_addr + buffer_table_size); */
316:     if(!addr_in_bios_map(V2P(_last_data_addr) + buffer_table_size)) {
317:         PANIC("Not enough memory for buffer_table.\n");
318:     }
319:     buffer_table = (struct buffer *)_last_data_addr;
320:     _last_data_addr += buffer_table_size;
321:
322:
323:     /* reserve memory space for buffer_hash_table */
324:     n = (buffer_table_size / sizeof(struct buffer) * BUFFER_HASH_PERCENTAGE)
/ 100;
325:     n = MAX(n, 10); /* 10 buffer hashes as minimum */
326:     /* buffer_hash_table is an array of pointers */
327:     pages = ((n * sizeof(unsigned int)) / PAGE_SIZE) + 1;
328:     buffer_hash_table_size = pages << PAGE_SHIFT;
329: /*
330:     printk("_last_data_addr = 0x%08x-0x%08x (buffer_hash_table)\n", _last_da
ta_addr, _last_data_addr + buffer_hash_table_size); */
330:     if(!addr_in_bios_map(V2P(_last_data_addr) + buffer_hash_table_size)) {
331:         PANIC("Not enough memory for buffer_hash_table.\n");
332:     }
333:     buffer_hash_table = (struct buffer **)_last_data_addr;
334:     _last_data_addr += buffer_hash_table_size;
335:
336:
337:     /* reserve memory space for inode_table */
338:     sizek = physical_memory / 1024; /* this helps to avoid overflow */
339:     inode_table_size = (sizek * INODE_PERCENTAGE) / 100;
340:     inode_table_size *= 1024;
341:     pages = inode_table_size >> PAGE_SHIFT;
342:     inode_table_size = pages << PAGE_SHIFT;
343: /*
344:     printk("_last_data_addr = 0x%08x-0x%08x (inode_table)\n", _last_data_add
r, _last_data_addr + inode_table_size); */
344:     if(!addr_in_bios_map(V2P(_last_data_addr) + inode_table_size)) {
345:         PANIC("Not enough memory for inode_table.\n");
346:     }
347:     inode_table = (struct inode *)_last_data_addr;
348:     _last_data_addr += inode_table_size;
349:
350:
351:     /* reserve memory space for inode_hash_table */
352:     n = ((inode_table_size / sizeof(struct inode)) * INODE_HASH_PERCENTAGE)
/ 100;
353:     n = MAX(n, 10); /* 10 inodes hashes as minimum */
354:     /* inode_hash_table is an array of pointers */
355:     pages = ((n * sizeof(unsigned int)) / PAGE_SIZE) + 1;
356:     inode_hash_table_size = pages << PAGE_SHIFT;
357: /*
358:     printk("_last_data_addr = 0x%08x-0x%08x (inode_hash_table)\n", _last_dat
a_addr, _last_data_addr + inode_hash_table_size); */
358:     if(!addr_in_bios_map(V2P(_last_data_addr) + inode_hash_table_size)) {
359:         PANIC("Not enough memory for inode_hash_table.\n");
360:     }
361:     inode_hash_table = (struct inode **)_last_data_addr;
362:     _last_data_addr += inode_hash_table_size;
363:
364:
365:     /* reserve memory space for fd_table[NR_OPENS] */
366:     fd_table_size = PAGE_ALIGN(sizeof(struct fd) * NR_OPENS);
367: /*
368:     printk("_last_data_addr = 0x%08x-0x%08x (fd_table)\n", _last_data_addr,
_last_data_addr + fd_table_size); */
368:     if(!addr_in_bios_map(V2P(_last_data_addr) + fd_table_size)) {
369:         PANIC("Not enough memory for fd_table.\n");
370:     }
371:     fd_table = (struct fd *)_last_data_addr;
372:     _last_data_addr += fd_table_size;
373:
374:
375:     /* reserve memory space for mount_table[NR_MOUNT_POINTS] */

```

mm/memory.c

Page 7/7

```

376:         mount_table_size = PAGE_ALIGN(sizeof(struct mount) * NR_MOUNT_POINTS);
377:  /*      printk("_last_data_addr = 0x%08x-0x%08x (mount_table)\n", _last_data_addr
r, _last_data_addr + mount_table_size); */
378:         if(!addr_in_bios_map(V2P(_last_data_addr) + mount_table_size)) {
379:             PANIC("Not enough memory for mount_table.\n");
380:         }
381:         mount_table = (struct mount *)_last_data_addr;
382:         _last_data_addr += mount_table_size;
383:
384:
385:         /* reserve memory space for RAMdisk(s) */
386:         if(!_noramdisk) {
387:             if(!_ramdisksize) {
388:                 _ramdisksize = RAMDISK_SIZE;
389:             }
390:             if(!addr_in_bios_map(V2P(_last_data_addr) + (_ramdisksize * 1024
))) {
391:                 printk("WARNING: RAMdisk device disabled (not enough phy
sical memory).\n");
392:                 _noramdisk = 1;
393:             } else {
394:                 for(n = 0; n < RAMDISK_MINORS; n++) {
395:  /*      printk("_last_data_addr = 0x%08x-0x%08x (/dev/ra
m%d)\n", _last_data_addr, _last_data_addr + (_ramdisksize * 1024), n); */
396:                 ramdisk_table[n].addr = (char *)_last_data_addr;
397:                 _last_data_addr += _ramdisksize * 1024;
398:             }
399:         }
400:     }
401:
402:
403:     /* the last one must be the page_table structure */
404:     page_hash_table_size = 1 * PAGE_SIZE; /* only 1 page size */
405:     if(!addr_in_bios_map(V2P(_last_data_addr) + page_hash_table_size)) {
406:         PANIC("Not enough memory for page_hash_table.\n");
407:     }
408:     page_hash_table = (struct page **)_last_data_addr;
409:  /*      printk("_last_data_addr = 0x%08x-0x%08x (page_hash_table)\n", _last_data
_addr, _last_data_addr + page_hash_table_size); */
410:     _last_data_addr += page_hash_table_size;
411:
412:     page_table_size = PAGE_ALIGN(kstat.physical_pages * sizeof(struct page))
;
413:     if(!addr_in_bios_map(V2P(_last_data_addr) + page_table_size)) {
414:         PANIC("Not enough memory for page_table.\n");
415:     }
416:     page_table = (struct page *)_last_data_addr;
417:  /*      printk("page_table_size = %d\n", page_table_size); */
418:  /*      printk("_last_data_addr = 0x%08x-0x%08x (page_table)\n", _last_data_addr
, _last_data_addr + page_table_size); */
419:     _last_data_addr += page_table_size;
420:
421:     page_init(kstat.physical_pages);
422: }
423:
424: void mem_stats(void)
425: {
426:     printk("\n");
427:     printk("memory: total/available=%dKB/%dKB, kernel=%dKB, reserved=%dKB\n"
, kstat.physical_pages << 2, kstat.total_mem_pages << 2, kstat.kernel_reserved, kstat.p
hysical_reserved);
428:     printk("kernel: text=%dKB, data=%dKB, bss=%dKB, i/o buffers=%d (%dKB)\n"
, KERNEL_TEXT_SIZE / 1024, KERNEL_DATA_SIZE / 1024, KERNEL_BSS_SIZE / 1024, buffer_tabl
e_size / sizeof(struct buffer), (buffer_table_size + buffer_hash_table_size) / 1024);
429:     printk("\tinode=%d (%dKB)\n\n", inode_table_size / sizeof(struct inode)
, (inode_table_size + inode_hash_table_size) / 1024);
430: }

```

mm/mmap.c

Page 1/8

```

1: /*
2:  * fiwix/mm/mmap.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/asm.h>
9: #include <fiwix/mm.h>
10: #include <fiwix/fs.h>
11: #include <fiwix/fcntl.h>
12: #include <fiwix/stat.h>
13: #include <fiwix/process.h>
14: #include <fiwix/mman.h>
15: #include <fiwix/errno.h>
16: #include <fiwix/stdio.h>
17: #include <fiwix/string.h>
18:
19: void show_vma_regions(struct proc *p)
20: {
21:     __ino_t inode;
22:     int major, minor;
23:     char *section;
24:     char r, w, x, f;
25:     struct vma *vma;
26:     unsigned int n;
27:     int count;
28:
29:     vma = p->vma;
30:     printk("num  address range          flag offset      dev  inode      mod
section cnt\n");
31:     printk("-----\n");
32:     for(n = 0; n < VMA_REGIONS && vma->start; n++, vma++) {
33:         r = vma->prot & PROT_READ ? 'r' : '-';
34:         w = vma->prot & PROT_WRITE ? 'w' : '-';
35:         x = vma->prot & PROT_EXEC ? 'x' : '-';
36:         if(vma->flags & MAP_SHARED) {
37:             f = 's';
38:         } else if(vma->flags & MAP_PRIVATE) {
39:             f = 'p';
40:         } else {
41:             f = '-';
42:         }
43:         switch(vma->s_type) {
44:             case P_TEXT:      section = "text ";
45:                             break;
46:             case P_DATA:      section = "data ";
47:                             break;
48:             case P_BSS:       section = "bss  ";
49:                             break;
50:             case P_HEAP:      section = "heap ";
51:                             break;
52:             case P_STACK:     section = "stack";
53:                             break;
54:             case P_MMAP:      section = "mmap ";
55:                             break;
56:             default:
57:                 section = NULL;
58:                 break;
59:         }
60:         inode = major = minor = count = 0;
61:         if(vma->inode) {
62:             inode = vma->inode->inode;
63:             major = MAJOR(vma->inode->dev);
64:             minor = MINOR(vma->inode->dev);
65:             count = vma->inode->count;

```

mm/mmap.c

Page 2/8

```

66:         }
67:         printk("[%02d] 0x%08x-0x%08x %c%c%c%c 0x%08x %02d:%02d %- 10u <%
d> [%s] (%d)\n", n, vma->start, vma->end, r, w, x, f, vma->offset, major, minor, inode
, vma->o_mode, section, count);
68:     }
69:     if(!n) {
70:         printk("[no vma regions]\n");
71:     }
72: }
73:
74: static struct vma * get_new_vma_region(void)
75: {
76:     unsigned int n;
77:     struct vma *vma;
78:
79:     vma = current->vma;
80:
81:     for(n = 0; n < VMA_REGIONS; n++, vma++) {
82:         if(!vma->start && !vma->end) {
83:             return vma;
84:         }
85:     }
86:     return NULL;
87: }
88:
89: /*
90:  * This sorts regions (in ascending order), merging equal regions and keeping
91:  * the unused ones at the end of the array.
92:  */
93: static void sort_vma(void)
94: {
95:     unsigned int n, n2, needs_sort;
96:     struct vma *vma, tmp;
97:
98:     vma = current->vma;
99:
100:    do {
101:        needs_sort = 0;
102:        for(n = 0, n2 = 1; n2 < VMA_REGIONS; n++, n2++) {
103:            if(vma[n].end && vma[n2].start) {
104:                if((vma[n].end == vma[n2].start) &&
105:                    (vma[n].prot == vma[n2].prot) &&
106:                    (vma[n].flags == vma[n2].flags) &&
107:                    (vma[n].offset == vma[n2].offset) &&
108:                    (vma[n].s_type == vma[n2].s_type) &&
109:                    (vma[n].inode == vma[n2].inode)) {
110:                    vma[n].end = vma[n2].end;
111:                    memset_b(&vma[n2], NULL, sizeof(struct v
ma));
112:                    needs_sort++;
113:                }
114:            }
115:            if((vma[n2].start && (vma[n].start > vma[n2].start)) ||
(!vma[n].start && vma[n2].start)) {
116:                memcpy_b(&tmp, &vma[n], sizeof(struct vma));
117:                memcpy_b(&vma[n], &vma[n2], sizeof(struct vma));
118:                memcpy_b(&vma[n2], &tmp, sizeof(struct vma));
119:                needs_sort++;
120:            }
121:        }
122:    } while(needs_sort);
123: }
124:
125: /*
126:  * This function removes all redundant entries.
127:  *
128:  * for example, if for any reason the map looks like this:

```

mm/mmap.c

Page 3/8

```

129:  * [01] 0x0808e984-0x08092000 rw-p 0x00000000 0
130:  * [02] 0x0808f000-0x0808ffff rw-p 0x000c0000 4066
131:  *
132:  * this function converts it to this:
133:  * [01] 0x0808e984-0x0808f000 rw-p 0x00000000 0
134:  * [02] 0x0808f000-0x0808ffff rw-p 0x000c0000 4066
135:  * [03] 0x08090000-0x08092000 rw-p 0x00000000 0
136:  */
137: static int optimize_vma(void)
138: {
139:     unsigned int n, needs_sort;
140:     struct vma *vma, *prev, *new;
141:
142:     for(;;) {
143:         needs_sort = 0;
144:         prev = new = NULL;
145:         vma = current->vma;
146:         for(n = 0; n < VMA_REGIONS && vma->start; n++, vma++) {
147:             if(!prev) {
148:                 prev = vma;
149:                 continue;
150:             }
151:             if((vma->start < prev->end)) {
152:                 if(!(new = get_new_vma_region())) {
153:                     printk("WARNING: %s(): unable to get a f
ree vma region.\n", __FUNCTION__);
154:                     return -ENOMEM;
155:                 }
156:                 new->start = vma->end;
157:                 new->end = prev->end;
158:                 new->prot = prev->prot;
159:                 new->flags = prev->flags;
160:                 new->offset = prev->offset;
161:                 new->s_type = prev->s_type;
162:                 new->inode = prev->inode;
163:                 new->o_mode = prev->o_mode;
164:                 prev->end = vma->start;
165:                 needs_sort++;
166:                 if(prev->start == prev->end) {
167:                     memset_b(prev, NULL, sizeof(struct vma))
;
168:                 }
169:                 if(new->start == new->end) {
170:                     memset_b(new, NULL, sizeof(struct vma));
171:                 }
172:                 break;
173:             }
174:             prev = vma;
175:         }
176:         if(!needs_sort) {
177:             break;
178:         }
179:         sort_vma();
180:     }
181:
182:     return 0;
183: }
184:
185: /* return the first free address that matches with the size of length */
186: static unsigned int get_unmapped_vma_region(unsigned int length)
187: {
188:     unsigned int n, addr;
189:     struct vma *vma;
190:
191:     if(!length) {
192:         return 0;
193:     }

```

mm/mmap.c

Page 4/8

```

194:
195:     addr = MMAP_START;
196:     vma = current->vma;
197:
198:     for(n = 0; n < VMA_REGIONS && vma->start; n++, vma++) {
199:         if(vma->start < MMAP_START) {
200:             continue;
201:         }
202:         if((addr + length) < vma->start) {
203:             return PAGE_ALIGN(addr);
204:         }
205:         addr = PAGE_ALIGN(vma->end);
206:     }
207:     return 0;
208: }
209:
210: static void free_vma_pages(unsigned int start, __size_t length, struct vma *vma)
211: {
212:     unsigned int n, addr;
213:     unsigned int *pgdir, *pgtbl;
214:     unsigned int pde, pte, page;
215:     struct page *pg;
216:
217:     pgdir = (unsigned int *)P2V(current->tss.cr3);
218:     pgtbl = NULL;
219:
220:     for(n = 0; n < (length / PAGE_SIZE); n++) {
221:         pde = GET_PGDIR(start + (n * PAGE_SIZE));
222:         pte = GET_PGTBL(start + (n * PAGE_SIZE));
223:         if(pgdir[pde] & PAGE_PRESENT) {
224:             pgtbl = (unsigned int *)P2V((pgdir[pde] & PAGE_MASK));
225:             if(pgtbl[pte] & PAGE_PRESENT) {
226:                 /* make sure to not free reserved pages */
227:                 page = pgtbl[pte] >> PAGE_SHIFT;
228:                 pg = &page_table[page];
229:                 if(pg->flags & PAGE_RESERVED) {
230:                     continue;
231:                 }
232:
233:                 if(vma->prot & PROT_WRITE && vma->flags & MAP_SH
234: ARED) {
235:                     addr = start - vma->start + vma->offset;
236:                     write_page(pg, vma->inode, addr, length)
237: ;
238:                 }
239:
240:                 kfree(P2V(pgtbl[pte]) & PAGE_MASK);
241:                 current->rss--;
242:                 pgtbl[pte] = NULL;
243:
244:                 /* check if a page table can be freed */
245:                 for(pte = 0; pte < PT_ENTRIES; pte++) {
246:                     if(pgtbl[pte] & PAGE_MASK) {
247:                         break;
248:                     }
249:                 }
250:                 if(pte == PT_ENTRIES) {
251:                     kfree((unsigned int)pgtbl & PAGE_MASK);
252:                     current->rss--;
253:                     pgdir[pde] = NULL;
254:                 }
255:             }
256:         }
257:     }
258: static int free_vma_region(struct vma *vma, unsigned int start, __ssize_t length

```


mm/mmap.c

Page 5/8

```

)
259: {
260:     struct vma *new;
261:
262:     if(!(new = get_new_vma_region())) {
263:         printk("WARNING: %s(): unable to get a free vma region.\n", __FU
NCTION__);
264:         return -ENOMEM;
265:     }
266:
267:     new->start = start + length;
268:     new->end = vma->end;
269:     new->prot = vma->prot;
270:     new->flags = vma->flags;
271:     new->offset = vma->offset;
272:     new->s_type = vma->s_type;
273:     new->inode = vma->inode;
274:     new->o_mode = vma->o_mode;
275:
276:     vma->end = start;
277:
278:     if(vma->start == vma->end) {
279:         if(vma->inode) {
280:             iput(vma->inode);
281:         }
282:         memset_b(vma, NULL, sizeof(struct vma));
283:     }
284:     if(new->start == new->end) {
285:         memset_b(new, NULL, sizeof(struct vma));
286:     }
287:     return 0;
288: }
289:
290: void release_binary(void)
291: {
292:     unsigned int n;
293:     struct vma *vma;
294:
295:     vma = current->vma;
296:
297:     for(n = 0; n < VMA_REGIONS && vma->start; n++, vma++) {
298:         free_vma_pages(vma->start, vma->end - vma->start, vma);
299:         free_vma_region(vma, vma->start, vma->end - vma->start);
300:     }
301:     sort_vma();
302:     optimize_vma();
303:     invalidate_tlb();
304: }
305:
306: struct vma * find_vma_region(unsigned int addr)
307: {
308:     unsigned int n;
309:     struct vma *vma;
310:
311:     if(!addr) {
312:         return NULL;
313:     }
314:
315:     addr &= PAGE_MASK;
316:     vma = current->vma;
317:
318:     for(n = 0; n < VMA_REGIONS && vma->start; n++, vma++) {
319:         if((addr >= vma->start) && (addr < vma->end)) {
320:             return vma;
321:         }
322:     }
323:     return NULL;

```

```

324: }
325:
326: int expand_heap(unsigned int new)
327: {
328:     unsigned int n;
329:     struct vma *vma, *heap;
330:
331:     vma = current->vma;
332:     heap = NULL;
333:
334:     for(n = 0; n < VMA_REGIONS && vma->start; n++, vma++) {
335:         /* make sure the new heap won't overlap the next region */
336:         if(heap && new < vma->start) {
337:             heap->end = new;
338:             return 0;
339:         } else {
340:             heap = NULL;    /* was a bad candidate */
341:         }
342:         if(!heap && vma->s_type == P_HEAP) {
343:             heap = vma;    /* possible candidate */
344:             continue;
345:         }
346:     }
347:
348:     /* out of memory! */
349:     return 1;
350: }
351:
352: int do_mmap(struct inode *i, unsigned int start, unsigned int length, unsigned i
nt prot, unsigned int flags, unsigned int offset, char type, char mode)
353: {
354:     struct vma *vma;
355:     int errno;
356:
357:     if(!(length = PAGE_ALIGN(length))) {
358:         return start;
359:     }
360:
361:     /* file mapping */
362:     if(i) {
363:         if(!S_ISREG(i->i_mode) && !S_ISCHR(i->i_mode)) {
364:             return -ENODEV;
365:         }
366:
367:         /*
368:          * The file shall have been opened with read permission,
369:          * regardless of the protection options specified.
370:          * IEEE Std 1003.1, 2004 Edition.
371:          */
372:         if(mode == O_WRONLY) {
373:             return -EACCES;
374:         }
375:         switch(flags & MAP_TYPE) {
376:             case MAP_SHARED:
377:                 if(prot & PROT_WRITE) {
378:                     if(!(mode & (O_WRONLY | O_RDWR))) {
379:                         return -EACCES;
380:                     }
381:                 }
382:                 break;
383:             case MAP_PRIVATE:
384:                 break;
385:             default:
386:                 return -EINVAL;
387:         }
388:         i->count++;
389:

```

mm/mmap.c

Page 7/8

```

390:         /* anonymous mapping */
391:     } else {
392:         if((flags & MAP_TYPE) != MAP_PRIVATE) {
393:             return -EINVAL;
394:         }
395:
396:         /* anonymous objects must be filled with zeros */
397:         flags |= ZERO_PAGE;
398:     }
399:
400:     if(flags & MAP_FIXED) {
401:         if(start & ~PAGE_MASK) {
402:             return -EINVAL;
403:         }
404:     } else {
405:         start = get_unmapped_vma_region(length);
406:         if(!start) {
407:             printk("WARNING: %s(): unable to get an unmapped vma reg
ion.\n", __FUNCTION__);
408:             return -ENOMEM;
409:         }
410:     }
411:
412:     if(!(vma = get_new_vma_region())) {
413:         printk("WARNING: %s(): unable to get a free vma region.\n", __FU
NCTION__);
414:         return -ENOMEM;
415:     }
416:
417:     vma->start = start;
418:     vma->end = start + length;
419:     vma->prot = prot;
420:     vma->flags = flags;
421:     vma->offset = offset;
422:     vma->s_type = type;
423:     vma->inode = i;
424:     vma->o_mode = mode;
425:
426:     if(i && i->fsop->mmap) {
427:         if((errno = i->fsop->mmap(i, vma))) {
428:             int errno2;
429:
430:             if((errno2 = free_vma_region(vma, start, length))) {
431:                 return errno2;
432:             }
433:             sort_vma();
434:             if((errno2 = optimize_vma())) {
435:                 return errno2;
436:             }
437:             return errno;
438:         }
439:     }
440:
441:     sort_vma();
442:     if((errno = optimize_vma())) {
443:         return errno;
444:     }
445:     return start;
446: }
447:
448: int do_munmap(unsigned int addr, __size_t length)
449: {
450:     struct vma *vma;
451:     unsigned int size;
452:     int errno;
453:
454:     if((addr & ~PAGE_MASK) || length < 0) {

```

mm/mmap.c

Page 8/8

```

455:         return -EINVAL;
456:     }
457:
458:     length = PAGE_ALIGN(length);
459:
460:     while(length) {
461:         if((vma = find_vma_region(addr))) {
462:             if((addr + length) > vma->end) {
463:                 size = vma->end - addr;
464:             } else {
465:                 size = length;
466:             }
467:
468:             free_vma_pages(addr, size, vma);
469:             invalidate_tlb();
470:             if((errno = free_vma_region(vma, addr, size))) {
471:                 return errno;
472:             }
473:             sort_vma();
474:             if((errno = optimize_vma())) {
475:                 return errno;
476:             }
477:             length -= size;
478:             addr += size;
479:         } else {
480:             break;
481:         }
482:     }
483:
484:     return 0;
485: }
486:
487: int do_mprotect(struct vma *vma, unsigned int addr, __size_t length, int prot)
488: {
489:     struct vma *new;
490:     int errno;
491:
492:     if(!(new = get_new_vma_region())) {
493:         printk("WARNING: %s(): unable to get a free vma region.\n", __FU
NCTION__);
494:         return -ENOMEM;
495:     }
496:
497:     new->start = addr;
498:     new->end = addr + length;
499:     new->prot = prot;
500:     new->flags = vma->flags;
501:     new->offset = vma->offset;
502:     new->s_type = vma->s_type;
503:     new->inode = vma->inode;
504:     new->o_mode = vma->o_mode;
505:
506:     sort_vma();
507:     if((errno = optimize_vma())) {
508:         return errno;
509:     }
510:     return 0;
511: }

```

mm/page.c

Page 1/7

```

1: /*
2:  * fiwix/mm/page.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: /*
9:  * page.c implements a cache with a free list as a doubly circular linked
10:  * list and a chained hash table with doubly linked lists.
11:  *
12:  * hash table
13:  * +-----+ +-----+ +-----+ +-----+
14:  * | index | |prev|data|next| |prev|data|next| |prev|data|next|
15:  * |  0  --> | / | | | | | | | | | | | | | | | | | | | | | |
16:  * +-----+ +-----+ +-----+ +-----+
17:  * +-----+ +-----+ +-----+ +-----+
18:  * | index | |prev|data|next| |prev|data|next| |prev|data|next|
19:  * |  1  --> | / | | | | | | | | | | | | | | | | | | | | | |
20:  * +-----+ +-----+ +-----+ +-----+
21:  *                (page)                (page)                (page)
22:  *      ...
23:  */
24:
25: #include <fiwix/asm.h>
26: #include <fiwix/kernel.h>
27: #include <fiwix/mm.h>
28: #include <fiwix/mman.h>
29: #include <fiwix/bios.h>
30: #include <fiwix/sleep.h>
31: #include <fiwix/sched.h>
32: #include <fiwix/devices.h>
33: #include <fiwix/buffer.h>
34: #include <fiwix/errno.h>
35: #include <fiwix/stdio.h>
36: #include <fiwix/string.h>
37:
38: #define PAGE_HASH(inode, offset)      (((__ino_t)(inode) ^ (__off_t)(offset))
% NR_PAGE_HASH)
39: #define NR_PAGES      page_table_size / sizeof(struct page)
40: #define NR_PAGE_HASH  page_hash_table_size / sizeof(unsigned int)
41:
42: struct page *page_table;          /* page pool */
43: struct page *page_head;          /* page pool head */
44: struct page **page_hash_table;
45:
46: static void insert_to_hash(struct page *pg)
47: {
48:     struct page **h;
49:     int i;
50:
51:     i = PAGE_HASH(pg->inode->inode, pg->offset);
52:     h = &page_hash_table[i];
53:
54:     if(!*h) {
55:         *h = pg;
56:         (*h)->prev_hash = (*h)->next_hash = NULL;
57:     } else {
58:         pg->prev_hash = NULL;
59:         pg->next_hash = *h;
60:         (*h)->prev_hash = pg;
61:         *h = pg;
62:     }
63:     kstat.cached += (PAGE_SIZE / 1024);
64: }
65:
66: static void remove_from_hash(struct page *pg)

```

mm/page.c

Page 2/7

```

67: {
68:     struct page **h;
69:     int i;
70:
71:     if(!pg->inode) {
72:         return;
73:     }
74:
75:     i = PAGE_HASH(pg->inode->inode, pg->offset);
76:     h = &page_hash_table[i];
77:
78:     while(*h) {
79:         if(*h == pg) {
80:             if((*h)->next_hash) {
81:                 (*h)->next_hash->prev_hash = (*h)->prev_hash;
82:             }
83:             if((*h)->prev_hash) {
84:                 (*h)->prev_hash->next_hash = (*h)->next_hash;
85:             }
86:             if(h == &page_hash_table[i]) {
87:                 *h = (*h)->next_hash;
88:             }
89:             kstat.cached -= (PAGE_SIZE / 1024);
90:             break;
91:         }
92:         h = &(*h)->next_hash;
93:     }
94: }
95:
96: static void remove_from_free_list(struct page *pg)
97: {
98:     pg->prev_free->next_free = pg->next_free;
99:     pg->next_free->prev_free = pg->prev_free;
100:    kstat.free_pages--;
101:    if(pg == page_head) {
102:        page_head = pg->next_free;
103:    }
104: }
105:
106: void page_lock(struct page *pg)
107: {
108:     unsigned long int flags;
109:
110:     for(;;) {
111:         SAVE_FLAGS(flags); CLI();
112:         if(pg->locked) {
113:             RESTORE_FLAGS(flags);
114:             sleep(&pg, PROC_UNINTERRUPTIBLE);
115:         } else {
116:             break;
117:         }
118:     }
119:     pg->locked = 1;
120:     RESTORE_FLAGS(flags);
121: }
122:
123: void page_unlock(struct page *pg)
124: {
125:     unsigned long int flags;
126:
127:     SAVE_FLAGS(flags); CLI();
128:     pg->locked = 0;
129:     wakeup(pg);
130:     RESTORE_FLAGS(flags);
131: }
132:
133: struct page * get_free_page(void)

```

mm/page.c

Page 3/7

```

134: {
135:     unsigned long int flags;
136:     struct page *pg;
137:
138:     /* if no more pages on free list */
139:     while(page_head == page_head->next_free) {
140:         /* reclaim some memory from buffer cache */
141:         wakeup(&kswapd);
142:         sleep(&get_free_page, PROC_UNINTERRUPTIBLE);
143:
144:         if(page_head == page_head->next_free) {
145:             /* definitely out of memory! (no more pages) */
146:             printk("%s(): pid %d ran out of memory. OOM killer needs
d!\n", __FUNCTION__, current->pid);
147:             return NULL;
148:         }
149:     }
150:
151:     SAVE_FLAGS(flags); CLI();
152:
153:     pg = page_head;
154:     remove_from_free_list(pg);
155:     remove_from_hash(pg); /* remove it from its old hash */
156:     pg->count = 1;
157:     pg->inode = NULL;
158:     pg->offset = 0;
159:
160:     RESTORE_FLAGS(flags);
161:     return pg;
162: }
163:
164: struct page * search_page_hash(struct inode *inode, __off_t offset)
165: {
166:     struct page *pg;
167:     int i;
168:
169:     i = PAGE_HASH(inode->inode, offset);
170:     pg = page_hash_table[i];
171:
172:     while(pg) {
173:         if(pg->inode == inode && pg->offset == offset) {
174:             if(!pg->count) {
175:                 remove_from_free_list(pg);
176:             }
177:             pg->count++;
178:             return pg;
179:         }
180:         pg = pg->next_hash;
181:     }
182:
183:     return NULL;
184: }
185:
186: void release_page(unsigned int page)
187: {
188:     unsigned long int flags;
189:     struct page *pg;
190:
191:     if(!valid_page(page)) {
192:         PANIC("Unexpected inconsistency in hash_table. Missing page %d (
0x%x).\n", page, page);
193:     }
194:
195:     pg = &page_table[page];
196:     if(--pg->count > 0) {
197:         return;
198:     }

```

mm/page.c

Page 4/7

```

199:
200:     SAVE_FLAGS(flags); CLI();
201:
202:     if(!page_head) {
203:         pg->prev_free = pg->next_free = pg;
204:         page_head = pg;
205:     } else {
206:         pg->next_free = page_head;
207:         pg->prev_free = page_head->prev_free;
208:         page_head->prev_free->next_free = pg;
209:         page_head->prev_free = pg;
210:     }
211:
212:     /* if page is not cached then place it at the head of the free list */
213:     if(!pg->inode) {
214:         page_head = pg;
215:     }
216:
217:     kstat.free_pages++;
218:
219:     RESTORE_FLAGS(flags);
220:     wakeup(&get_free_page);
221: }
222:
223: int valid_page(unsigned int page)
224: {
225:     return (page >= 0 && page < NR_PAGES);
226: }
227:
228: void update_page_cache(struct inode *i, __off_t offset, const char *buf, int cou
nt)
229: {
230:     __off_t poffset;
231:     struct page *pg;
232:     int bytes;
233:
234:     poffset = offset % PAGE_SIZE;
235:     offset &= PAGE_MASK;
236:     bytes = PAGE_SIZE - poffset;
237:
238:     if(count) {
239:         bytes = MIN(bytes, count);
240:         if((pg = search_page_hash(i, offset))) {
241:             page_lock(pg);
242:             memcpy_b(pg->data + poffset, buf, bytes);
243:             page_unlock(pg);
244:             release_page(pg->page);
245:         }
246:     }
247: }
248:
249: int write_page(struct page *pg, struct inode *i, __off_t offset, unsigned int le
ngth)
250: {
251:     struct fd fd_table;
252:     unsigned int size;
253:     int errno;
254:
255:     size = MIN(i->i_size, length);
256:     fd_table.inode = i;
257:     fd_table.flags = 0;
258:     fd_table.count = 0;
259:     fd_table.offset = offset;
260:     if(i->fsop && i->fsop->write) {
261:         errno = i->fsop->write(i, &fd_table, pg->data, size);
262:     } else {
263:         errno = -EINVAL;

```


mm/page.c

Page 5/7

```

264:         }
265:
266:         return errno;
267:     }
268:
269: int bread_page(struct page *pg, struct inode *i, __off_t offset, char prot, char
flags)
270: {
271:     __blk_t block;
272:     __off_t size_read;
273:     int blksize;
274:     struct device *d;
275:     struct buffer *buf;
276:
277:     blksize = i->sb->s_blocksize;
278:     size_read = 0;
279:
280:     if(!(d = get_device(BLK_DEV, MAJOR(i->dev)))) {
281:         printk("WARNING: %s: device major %d not found!\n", __FUNCTION__
, MAJOR(i->dev));
282:         return 1;
283:     }
284:     if(!d->fsop || !d->fsop->read_block) {
285:         printk("WARNING: %s: device %d,%d does not have the read_block()
method!\n", __FUNCTION__, MAJOR(i->dev), MINOR(i->dev));
286:         return 1;
287:     }
288:
289:     pg->inode = i;
290:     pg->offset = offset;
291:     if(!(prot & PROT_WRITE) || flags & MAP_SHARED) {
292:         while(size_read < PAGE_SIZE) {
293:             if((block = bmap(i, offset, FOR_READING)) < 0) {
294:                 return 1;
295:             }
296:             if(block) {
297:                 /* does exist a buffer with recent data? */
298:                 if(!(buf = get_dirty_buffer(i->dev, block, blksize))) {
299:                     if(d->fsop->read_block(i->dev, block, pg
->data + size_read, blksize) < 0) {
300:                         return 1;
301:                     }
302:                 } else {
303:                     memcpy_b(pg->data + size_read, buf->data
, blksize);
304:                     brelse(buf);
305:                 }
306:             } else {
307:                 /* fill the hole with zeros */
308:                 memset_b(pg->data + size_read, 0, blksize);
309:             }
310:             size_read += blksize;
311:             offset += blksize;
312:         }
313:         /* cache all read-only and public (shared) pages */
314:         insert_to_hash(pg);
315:     } else {
316:         while(size_read < PAGE_SIZE) {
317:             if((block = bmap(i, offset, FOR_READING)) < 0) {
318:                 return 1;
319:             }
320:             if(block) {
321:                 /*
322:                  * This feeds the buffer cache by reading only
323:                  * the writable pages which aren't included in
324:                  * the page cache. This will speed up things by

```

mm/page.c

Page 6/7

```

325:         * keeping in buffer cache the writable pages
326:         * with its original (disk) content (i.e. pages
327:         * of the data section of an ELF).
328:         */
329:         if(!(buf = bread(i->dev, block, blksize))) {
330:             return 1;
331:         }
332:         memcpy_b(pg->data + size_read, buf->data, blksize);
e);
333:         brelse(buf);
334:     }
335:     size_read += blksize;
336:     offset += blksize;
337: }
338: pg->inode = NULL;
339: pg->offset = 0;
340: }
341: return 0;
342: }
343:
344: int file_read(struct inode *i, struct fd *fd_table, char *buffer, __size_t count
)
345: {
346:     __off_t total_read;
347:     unsigned int page, poffset, bytes;
348:     struct page *pg;
349:
350:     inode_lock(i);
351:
352:     if(fd_table->offset > i->i_size) {
353:         fd_table->offset = i->i_size;
354:     }
355:
356:     total_read = 0;
357:
358:     for(;;) {
359:         count = (fd_table->offset + count > i->i_size) ? i->i_size - fd_
table->offset : count;
360:         if(!count) {
361:             break;
362:         }
363:
364:         poffset = fd_table->offset % PAGE_SIZE;
365:         if(!(pg = search_page_hash(i, fd_table->offset & PAGE_MASK))) {
366:             if(!(page = kmalloc())) {
367:                 inode_unlock(i);
368:                 printk("%s(): returning -ENOMEM\n", __FUNCTION__
);
369:                 return -ENOMEM;
370:             }
371:             page = V2P(page);
372:             pg = &page_table[page >> PAGE_SHIFT];
373:             if(bread_page(pg, i, fd_table->offset & PAGE_MASK, 0, MA
P_SHARED)) {
374:                 kfree((unsigned int)pg->data);
375:                 inode_unlock(i);
376:                 printk("%s(): returning -EIO\n", __FUNCTION__);
377:                 return -EIO;
378:             }
379:         }
380:
381:         page_lock(pg);
382:         bytes = PAGE_SIZE - poffset;
383:         bytes = MIN(bytes, count);
384:         memcpy_b(buffer + total_read, pg->data + poffset, bytes);
385:         total_read += bytes;
386:         count -= bytes;

```

mm/page.c

Page 7/7

```

387:         poffset += bytes;
388:         poffset %= PAGE_SIZE;
389:         fd_table->offset += bytes;
390:         page_unlock(pg);
391:         kfree((unsigned int)pg->data);
392:     }
393:
394:     inode_unlock(i);
395:     return total_read;
396: }
397:
398: void page_init(unsigned int pages)
399: {
400:     struct page *pg;
401:     unsigned int n, addr;
402:
403:     memset_b(page_table, NULL, page_table_size);
404:     memset_b(page_hash_table, NULL, page_hash_table_size);
405:
406:     for(n = 0; n < pages; n++) {
407:         pg = &page_table[n];
408:         pg->page = n;
409:
410:         addr = n << PAGE_SHIFT;
411:         if(addr >= KERNEL_ENTRY_ADDR && addr < V2P(_last_data_addr)) {
412:             pg->flags = PAGE_RESERVED;
413:             kstat.kernel_reserved++;
414:             continue;
415:         }
416:
417:         /*
418:          * Some memory addresses are reserved, like the memory between
419:          * 0xA0000 and 0xFFFFF and other addresses, mostly used by the
420:          * VGA graphics adapter and BIOS.
421:          */
422:         if(!addr_in_bios_map(addr)) {
423:             pg->flags = PAGE_RESERVED;
424:             kstat.physical_reserved++;
425:             continue;
426:         }
427:
428:         pg->data = (char *)P2V(addr);
429:         if(!page_head) {
430:             pg->prev_free = pg->next_free = pg;
431:             page_head = pg;
432:         } else {
433:             pg->next_free = page_head;
434:             pg->prev_free = page_head->prev_free;
435:             page_head->prev_free->next_free = pg;
436:             page_head->prev_free = pg;
437:         }
438:         kstat.free_pages++;
439:     }
440:     kstat.total_mem_pages = kstat.free_pages;
441:     kstat.kernel_reserved <=< 2;
442:     kstat.physical_reserved <=< 2;
443: }

```

mm/swapper.c

Page 1/1

```

1: /*
2:  * fiwix/mm/swapper.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/limits.h>
10: #include <fiwix/process.h>
11: #include <fiwix/sleep.h>
12: #include <fiwix/sched.h>
13: #include <fiwix/tty.h>
14: #include <fiwix/memdev.h>
15: #include <fiwix/lp.h>
16: #include <fiwix/ramdisk.h>
17: #include <fiwix/floppy.h>
18: #include <fiwix/ide.h>
19: #include <fiwix/buffer.h>
20: #include <fiwix/mm.h>
21: #include <fiwix/fs.h>
22: #include <fiwix/locks.h>
23: #include <fiwix/filesystems.h>
24: #include <fiwix/stdio.h>
25:
26: /* kswapd continues the kernel initialization */
27: int kswapd(void)
28: {
29:     printk(current->argv0, "%s", "kswapd");
30:
31:     /* char devices */
32:     memdev_init();
33:     lp_init();
34:
35:     /* block devices */
36:     ramdisk_init();
37:     floppy_init();
38:     ide_init();
39:
40:     /* data structures */
41:     sleep_init();
42:     buffer_init();
43:     sched_init();
44:     mount_init();
45:     inode_init();
46:     fd_init();
47:     flock_init();
48:
49:     mem_stats();
50:     fs_init();
51:     mount_root();
52:     init_init();
53:
54:     for(;;) {
55:         sleep(&kswapd, PROC_UNINTERRUPTIBLE);
56:         if(reclaim_buffers()) {
57:             continue;
58:         }
59:         printk("WARNING: %s(): out of memory and swapping is not impleme
nted yet, sorry.\n", __FUNCTION__);
60:         wakeup(&get_free_page);
61:     }
62: }

```

lib/ctype.c

```

1: /*
2:  * fiwix/lib/ctype.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/ctype.h>
9:
10: unsigned char _ctype[] = {
11:     0,
12:     _C,          /* ^@  0x00 (NUL '\0') */
13:     _C,          /* ^A  0x01 (SOH) */
14:     _C,          /* ^B  0x02 (STX) */
15:     _C,          /* ^C  0x03 (ETX) */
16:     _C,          /* ^D  0x04 (EOT) */
17:     _C,          /* ^E  0x05 (ENQ) */
18:     _C,          /* ^F  0x06 (ACK) */
19:     _C,          /* ^G  0x07 (BEL '\a') */
20:     _C,          /* ^H  0x08 (BS '\b') */
21:     _C | _S,     /* ^I  0x09 (HT '\t') */
22:     _C | _S,     /* ^J  0x0A (LF '\n') */
23:     _C | _S,     /* ^K  0x0B (VT '\v') */
24:     _C | _S,     /* ^L  0x0C (FF '\f') */
25:     _C | _S,     /* ^M  0x0D (CR '\r') */
26:     _C,          /* ^N  0x0E (SO) */
27:     _C,          /* ^O  0x0F (SI) */
28:     _C,          /* ^P  0x10 (DLE) */
29:     _C,          /* ^Q  0x11 (DC1) */
30:     _C,          /* ^R  0x12 (DC2) */
31:     _C,          /* ^S  0x13 (DC3) */
32:     _C,          /* ^T  0x14 (DC4) */
33:     _C,          /* ^U  0x15 (NAK) */
34:     _C,          /* ^V  0x16 (SYN) */
35:     _C,          /* ^W  0x17 (ETB) */
36:     _C,          /* ^X  0x18 (CAN) */
37:     _C,          /* ^Y  0x19 (EM) */
38:     _C,          /* ^Z  0x1A (SUB) */
39:     _C,          /* ^[  0x1B (ESC) */
40:     _C,          /* ^\  0x1C (FS) */
41:     _C,          /* ^]  0x1D (GS) */
42:     _C,          /* ^^  0x1E (RS) */
43:     _C,          /* ^_  0x1F (US) */
44:     _S,          /* ' '  0x20 */
45:     _P,          /* '! ' 0x21 */
46:     _P,          /* '" ' 0x22 */
47:     _P,          /* '# ' 0x23 */
48:     _P,          /* '$ ' 0x24 */
49:     _P,          /* '% ' 0x25 */
50:     _P,          /* '& ' 0x26 */
51:     _P,          /* '' ' 0x27 */
52:     _P,          /* '(' ' 0x28 */
53:     _P,          /* ')' ' 0x29 */
54:     _P,          /* '*' ' 0x2A */
55:     _P,          /* '+' ' 0x2B */
56:     _P,          /* ',' ' 0x2C */
57:     _P,          /* '-' ' 0x2D */
58:     _P,          /* '.' ' 0x2E */
59:     _P,          /* '/' ' 0x2F */
60:     _N,          /* '0'  0x30 */
61:     _N,          /* '1'  0x31 */
62:     _N,          /* '2'  0x32 */
63:     _N,          /* '3'  0x33 */
64:     _N,          /* '4'  0x34 */
65:     _N,          /* '5'  0x35 */
66:     _N,          /* '6'  0x36 */
67:     _N,          /* '7'  0x37 */

```

lib/ctype.c

Page 2/3

```

68:      _N,      /* '8' 0x38 */
69:      _N,      /* '9' 0x39 */
70:      _P,      /* ':' 0x3A */
71:      _P,      /* ';' 0x3B */
72:      _P,      /* '<' 0x3C */
73:      _P,      /* '=' 0x3D */
74:      _P,      /* '>' 0x3E */
75:      _P,      /* '?' 0x3F */
76:      _P,      /* '@' 0x40 */
77:      _U,      _X, /* 'A' 0x41 */
78:      _U,      _X, /* 'B' 0x42 */
79:      _U,      _X, /* 'C' 0x43 */
80:      _U,      _X, /* 'D' 0x44 */
81:      _U,      _X, /* 'E' 0x45 */
82:      _U,      _X, /* 'F' 0x46 */
83:      _U,      /* 'G' 0x47 */
84:      _U,      /* 'H' 0x48 */
85:      _U,      /* 'I' 0x49 */
86:      _U,      /* 'J' 0x4A */
87:      _U,      /* 'K' 0x4B */
88:      _U,      /* 'L' 0x4C */
89:      _U,      /* 'M' 0x4D */
90:      _U,      /* 'N' 0x4E */
91:      _U,      /* 'O' 0x4F */
92:      _U,      /* 'P' 0x50 */
93:      _U,      /* 'Q' 0x51 */
94:      _U,      /* 'R' 0x52 */
95:      _U,      /* 'S' 0x53 */
96:      _U,      /* 'T' 0x54 */
97:      _U,      /* 'U' 0x55 */
98:      _U,      /* 'V' 0x56 */
99:      _U,      /* 'W' 0x57 */
100:     _U,      /* 'X' 0x58 */
101:     _U,      /* 'Y' 0x59 */
102:     _U,      /* 'Z' 0x5A */
103:     _P,      /* '[' 0x5B */
104:     _P,      /* '\' 0x5C */
105:     _P,      /* ']' 0x5D */
106:     _P,      /* '^' 0x5E */
107:     _P,      /* '_' 0x5F */
108:     _P,      /* '`' 0x60 */
109:     _L,      _X, /* 'a' 0x61 */
110:     _L,      _X, /* 'b' 0x62 */
111:     _L,      _X, /* 'c' 0x63 */
112:     _L,      _X, /* 'd' 0x64 */
113:     _L,      _X, /* 'e' 0x65 */
114:     _L,      _X, /* 'f' 0x66 */
115:     _L,      /* 'g' 0x67 */
116:     _L,      /* 'h' 0x68 */
117:     _L,      /* 'i' 0x69 */
118:     _L,      /* 'j' 0x6A */
119:     _L,      /* 'k' 0x6B */
120:     _L,      /* 'l' 0x6C */
121:     _L,      /* 'm' 0x6D */
122:     _L,      /* 'n' 0x6E */
123:     _L,      /* 'o' 0x6F */
124:     _L,      /* 'p' 0x70 */
125:     _L,      /* 'q' 0x71 */
126:     _L,      /* 'r' 0x72 */
127:     _L,      /* 's' 0x73 */
128:     _L,      /* 't' 0x74 */
129:     _L,      /* 'u' 0x75 */
130:     _L,      /* 'v' 0x76 */
131:     _L,      /* 'w' 0x77 */
132:     _L,      /* 'x' 0x78 */
133:     _L,      /* 'y' 0x79 */
134:     _L,      /* 'z' 0x7A */

```

lib/ctype.c

Page 3/3

```
135:         _P,           /* '{' 0x7B */
136:         _P,           /* '|' 0x7C */
137:         _P,           /* '}' 0x7D */
138:         _P,           /* '~' 0x7E */
139:         _C,           /* DEL 0x7F */
140:     };
```

lib/Makefile

Page 1/1

```
1: # fiwix/lib/Makefile
2: #
3: # Copyright 2018, Jordi Sanfeliu. All rights reserved.
4: # Distributed under the terms of the Fiwix License.
5: #
6: #
7: .S.o:
8:     $(CC) -traditional -I$(INCLUDE) -c -o $@ $<
9: .c.o:
10:     $(CC) $(CFLAGS) -c -o $@ $<
11:
12: OBJS = ctype.o strings.o printk.o
13:
14: lib:    $(OBJS)
15:     $(LD) $(LDFLAGS) -r $(OBJS) -o lib.o
16:
17: clean:
18:     rm -f *.o
19:
```


lib/printk.c

Page 1/6

```

1: /*
2:  * fiwix/lib/printk.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/kernel.h>
9: #include <fiwix/tty.h>
10: #include <fiwix/stdio.h>
11: #include <fiwix/string.h>
12: #include <fiwix/stdarg.h>
13:
14: #define LOG_BUF_LEN      4096
15: #define MAX_BUF          1024    /* printk() and sprintf() size limit */
16:
17: static char log_buf[LOG_BUF_LEN];
18: static unsigned int log_start;
19:
20: static void puts(char *buffer)
21: {
22:     struct tty *tty;
23:     unsigned short int count;
24:     char *b;
25:
26:     /* for special debugging purposes only (X11, SVGAlib, ...)
27:     {
28:         struct inode dummy_i;
29:         memset_b(&dummy_i, 0, sizeof(struct inode));
30:         dummy_i.dev = dummy_i.rdev = 0x0600;          // /dev/lp0
31:         lp_write(&dummy_i, NULL, buffer, strlen(buffer));
32:     }
33:     */
34:
35:     tty = get_tty(_syscondev);
36:     count = strlen(buffer);
37:     b = buffer;
38:
39:     while(count-->0) {
40:         if(!tty) {
41:             if(log_start < LOG_BUF_LEN) {
42:                 log_buf[log_start++] = *(b++);
43:             }
44:         } else {
45:             tty_queue_putchar(tty, &tty->write_q, *(b++));
46:
47:             /* kernel messages must be shown immediately */
48:             tty->output(tty);
49:         }
50:     }
51: }
52:
53: /*
54:  * format identifiers
55:  * -----
56:  *      %d      decimal conversion
57:  *      %u      unsigned decimal conversion
58:  *      %x      hexadecimal conversion (lower case)
59:  *      %X      hexadecimal conversion (upper case)
60:  *      %b      binary conversion
61:  *      %o      octal conversion
62:  *      %c      character
63:  *      %s      string
64:  *
65:  * flags
66:  * -----
67:  *      0      result is padded with zeros (e.g.: '%06d')

```

lib/printk.c

Page 2/6

```

68:  *           (maximum value is 32)
69:  *   blank   result is padded with spaces (e.g.: '% 6d')
70:  *           (maximum value is 32)
71:  *   -       the numeric result is left-justified
72:  *           (default is right-justified)
73:  */
74: static void do_printk(char *buffer, const char *format, va_list args)
75: {
76:     char sw_neg, in_identifier, n_pad, lf;
77:     char ch_pad, basecase, c;
78:     char str[] = {
79:         NULL, NULL, NULL, NULL, NULL, NULL, NULL, NULL,
80:         NULL, NULL, NULL, NULL, NULL, NULL, NULL, NULL,
81:         NULL, NULL, NULL, NULL, NULL, NULL, NULL, NULL,
82:         NULL, NULL, NULL, NULL, NULL, NULL, NULL, NULL,
83:         NULL
84:     };
85:     char nullstr[7] = { '<', 'N', 'U', 'L', 'L', '>', '\0' };
86:     char *ptr_s, *p;
87:     int num, count;
88:     char simplechar;
89:     unsigned int unum, digit;
90:
91:     sw_neg = in_identifier = n_pad = lf = 0;
92:     count = 0;
93:     basecase = 'A';
94:     ch_pad = ' ';
95:     p = NULL;
96:
97:     /* assumes buffer has a maximum size of MAX_BUF */
98:     while((c = *(format++)) && count < MAX_BUF) {
99:         if((c != '%') && !in_identifier) {
100:             *(buffer++) = c;
101:             memset_b(str, NULL, 32);
102:         } else {
103:             in_identifier = 1;
104:             switch(c = *(format)) {
105:                 case 'd':
106:                     num = va_arg(args, int);
107:                     if(num < 0) {
108:                         num *= -1;
109:                         sw_neg = 1;
110:                     }
111:                     ptr_s = str;
112:                     do {
113:                         *(ptr_s++) = '0' + (num % 10);
114:                     } while(num /= 10);
115:                     if(lf) {
116:                         p = ptr_s;
117:                     } else {
118:                         while(*ptr_s) {
119:                             ptr_s++;
120:                         }
121:                     }
122:                     if(sw_neg) {
123:                         sw_neg = 0;
124:                         *(ptr_s++) = '-';
125:                     }
126:                     do {
127:                         *(buffer++) = *(--ptr_s);
128:                         count++;
129:                     } while(ptr_s != str && count < MAX_BUF)
;
130:                     if(lf) {
131:                         while(*p && count < MAX_BUF) {
132:                             *(buffer++) = *(p++);
133:                             count++;

```

lib/printk.c

Page 3/6

```

134:                                     }
135:                                     }
136:                                     format++;
137:                                     ch_pad = ' ';
138:                                     n_pad = 0;
139:                                     in_identifier = 0;
140:                                     lf = 0;
141:                                     break;
142:
143:                                     case 'u':
144:                                         unum = va_arg(args, unsigned int);
145:                                         ptr_s = str;
146:                                         do {
147:                                             *(ptr_s++) = '0' + (unum % 10);
148:                                         } while(unum /= 10);
149:                                         if(lf) {
150:                                             p = ptr_s;
151:                                         } else {
152:                                             while(*ptr_s) {
153:                                                 ptr_s++;
154:                                             }
155:                                         }
156:                                         do {
157:                                             *(buffer++) = *(--ptr_s);
158:                                             count++;
159:                                         } while(ptr_s != str && count < MAX_BUF)
;
160:                                     if(lf) {
161:                                         while(*p && count < MAX_BUF) {
162:                                             *(buffer++) = *(p++);
163:                                             count++;
164:                                         }
165:                                     }
166:                                     format++;
167:                                     ch_pad = ' ';
168:                                     n_pad = 0;
169:                                     in_identifier = 0;
170:                                     lf = 0;
171:                                     break;
172:
173:                                     case 'x':
174:                                         basecase = 'a';
175:                                     case 'X':
176:                                         unum = va_arg(args, unsigned int);
177:                                         ptr_s = str;
178:                                         do {
179:                                             *(ptr_s++) = (digit = (unum & 0x
0F)) > 9 ? basecase + digit - 10 : '0' + digit;
180:                                         } while(unum /= 16);
181:                                         if(lf) {
182:                                             p = ptr_s;
183:                                         } else {
184:                                             while(*ptr_s) {
185:                                                 ptr_s++;
186:                                             }
187:                                         }
188:                                         do {
189:                                             *(buffer++) = *(--ptr_s);
190:                                             count++;
191:                                         } while(ptr_s != str && count < MAX_BUF)
;
192:                                     if(lf) {
193:                                         while(*p && count < MAX_BUF) {
194:                                             *(buffer++) = *(p++);
195:                                             count++;
196:                                         }
197:                                     }

```

lib/printk.c

Page 4/6

```

198:         format++;
199:         ch_pad = ' ';
200:         n_pad = 0;
201:         in_identifier = 0;
202:         lf = 0;
203:         break;
204:
205:     case 'b':
206:         num = va_arg(args, unsigned int);
207:         if(num < 0) {
208:             num *= -1;
209:         }
210:         ptr_s = str;
211:         do {
212:             *(ptr_s++) = '0' + (num % 2);
213:         } while(num /= 2);
214:         if(lf) {
215:             p = ptr_s;
216:         } else {
217:             while(*ptr_s) {
218:                 ptr_s++;
219:             }
220:         }
221:         do {
222:             *(buffer++) = *(--ptr_s);
223:             count++;
224:         } while(ptr_s != str && count < MAX_BUF)
;
225:
226:         if(lf) {
227:             while(*p && count < MAX_BUF) {
228:                 *(buffer++) = *(p++);
229:                 count++;
230:             }
231:         }
232:         format++;
233:         ch_pad = ' ';
234:         n_pad = 0;
235:         in_identifier = 0;
236:         lf = 0;
237:         break;
238:
239:     case 'o':
240:         num = va_arg(args, unsigned int);
241:         if(num < 0) {
242:             num *= -1;
243:         }
244:         ptr_s = str;
245:         do {
246:             *(ptr_s++) = '0' + (num % 8);
247:         } while(num /= 8);
248:         if(lf) {
249:             p = ptr_s;
250:         } else {
251:             while(*ptr_s) {
252:                 ptr_s++;
253:             }
254:         }
255:         do {
256:             *(buffer++) = *(--ptr_s);
257:             count++;
258:         } while(ptr_s != str && count < MAX_BUF)
;
259:
260:         if(lf) {
261:             while(*p && count < MAX_BUF) {
262:                 *(buffer++) = *(p++);

```

lib/printk.c

Page 5/6

```

263:                                     }
264:                                     format++;
265:                                     ch_pad = ' ';
266:                                     n_pad = 0;
267:                                     in_identifier = 0;
268:                                     lf = 0;
269:                                     break;
270:
271:     case 'c':
272:         simplechar = va_arg(args, int);
273:         *(buffer++) = simplechar;
274:         format++;
275:         in_identifier = 0;
276:         lf = 0;
277:         break;
278:
279:     case 's':
280:         num = 0;
281:         ptr_s = va_arg(args, char *);
282:         if(n_pad) {
283:             num = n_pad - strlen(ptr_s);
284:             if(num < 0) {
285:                 num *= -1;
286:             }
287:         }
288:         /* if it's a NULL then show "<NULL>" */
289:         if(ptr_s == NULL) {
290:             ptr_s = (char *)nullstr;
291:         }
292:         while((c = *(ptr_s++)) && count < MAX_BU
F) {
293:             *(buffer++) = c;
294:             count++;
295:         }
296:         while(num-- && count < MAX_BUF) {
297:             *(buffer++) = ' ';
298:             count++;
299:         }
300:         format++;
301:         n_pad = 0;
302:         in_identifier = 0;
303:         lf = 0;
304:         break;
305:
306:     case ' ':
307:         ch_pad = ' ';
308:         break;
309:
310:     case '0':
311:         if(!n_pad) {
312:             ch_pad = '0';
313:         }
314:     case '1':
315:     case '2':
316:     case '3':
317:     case '4':
318:     case '5':
319:     case '6':
320:     case '7':
321:     case '8':
322:     case '9':
323:         n_pad = !n_pad ? c - '0': ((n_pad * 10)
+ (c - '0'));
324:         n_pad = n_pad > 32 ? 32 : n_pad;
325:         for(unum = 0; unum < n_pad; unum++) {
326:             str[unum] = ch_pad;
327:         }

```

lib/printk.c

Page 6/6

```
328:                                     break;
329:
330:                                     case '-':
331:                                         lf = 1;
332:                                         break;
333:                                     case '%':
334:                                         *(buffer++) = c;
335:                                         format++;
336:                                         in_identifier = 0;
337:                                         break;
338:                                     }
339:                                 }
340:                             count++;
341:     }
342:     *buffer = NULL;
343: }
344:
345: void register_console(void (*fn)(char *, unsigned int))
346: {
347:     (*fn)(log_buf, log_start);
348: }
349:
350: void printk(const char *format, ...)
351: {
352:     va_list args;
353:     char buffer[MAX_BUF];
354:
355:     va_start(args, format);
356:     do_printk(buffer, format, args);
357:     puts(buffer);
358:     va_end(args);
359: }
360:
361: int sprintf(char *buffer, const char *format, ...)
362: {
363:     va_list args;
364:
365:     va_start(args, format);
366:     do_printk(buffer, format, args);
367:     va_end(args);
368:     return strlen(buffer);
369: }
```

lib/strings.c

```

1: /*
2:  * fiwix/lib/strings.c
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9: #include <fiwix/tty.h>
10: #include <fiwix/mm.h>
11: #include <fiwix/stdio.h>
12: #include <fiwix/string.h>
13:
14: /* convert from big-endian to little-endian (word swap) */
15: void swap_asc_word(char *str, int len)
16: {
17:     int n, n2;
18:     short int *ptr;
19:     char *buf;
20:
21:     if(!(buf = (void *)kmalloc())) {
22:         return;
23:     }
24:
25:     ptr = (short int *)str;
26:
27:     for(n = 0, n2 = 0; n < len; n++) {
28:         buf[n2++] = *ptr >> 8;
29:         buf[n2++] = *ptr & 0xFF;
30:         ptr++;
31:     }
32:     for(n = len - 1; n > 0; n--) {
33:         if(buf[n] == NULL || buf[n] == ' ') {
34:             buf[n] = NULL;
35:         } else {
36:             break;
37:         }
38:     }
39:     memcpy_b(str, buf, len);
40:     kfree((unsigned int)buf);
41: }
42:
43: int strcmp(const char *str1, const char *str2)
44: {
45:     while(*str1) {
46:         if(*str1 != *str2) {
47:             return 1;
48:         }
49:         str1++;
50:         str2++;
51:     }
52:     if(!(*str2)) {
53:         return 0;
54:     }
55:     return 1;
56: }
57:
58: int strncmp(const char *str1, const char *str2, __ssize_t n)
59: {
60:     while(n > 0) {
61:         if(*str1 != *str2) {
62:             return 1;
63:         }
64:         str1++;
65:         str2++;
66:         n--;
67:     }

```

lib/strings.c

Page 2/5

```
68:         return 0;
69:     }
70:
71: char *strcpy(char *dest, const char *src)
72: {
73:     if(!dest || !src) {
74:         return NULL;
75:     }
76:
77:     while(*src) {
78:         *dest = *src;
79:         dest++;
80:         src++;
81:     }
82:     *dest = NULL;          /* NULL-terminated */
83:     return dest;
84: }
85:
86: void strncpy(char *dest, const char *src, int len)
87: {
88:     if(!dest || !src) {
89:         return;
90:     }
91:
92:     while((*src) && len) {
93:         *dest = *src;
94:         dest++;
95:         src++;
96:         len--;
97:     }
98:     *dest = NULL;        /* NULL-terminated */
99: }
100:
101: char *strcat(char *dest, const char *src)
102: {
103:     char *orig;
104:
105:     orig = dest;
106:     while(*dest) {
107:         dest++;
108:     }
109:     while(*src) {
110:         *dest = *src;
111:         dest++;
112:         src++;
113:     }
114:     *dest = NULL;
115:     return orig;
116: }
117:
118: char *strncat(char *dest, const char *src, __ssize_t len)
119: {
120:     char *orig;
121:
122:     orig = dest;
123:     while(*dest) {
124:         dest++;
125:     }
126:     while(*src && len) {
127:         *dest = *src;
128:         dest++;
129:         src++;
130:         len--;
131:     }
132:     *dest = NULL;
133:     return orig;
134: }
```



```
135:
136: int strlen(const char *str)
137: {
138:     int n;
139:
140:     n = 0;
141:     while(str && *str) {
142:         n++;
143:         str++;
144:     }
145:     return n;
146: }
147:
148: char * get_basename(const char *path)
149: {
150:     char *basename;
151:     char c;
152:
153:     basename = NULL;
154:
155:     while(path) {
156:         while(*path == '/') {
157:             path++;
158:         }
159:         if(*path != NULL) {
160:             basename = (char *)path;
161:         }
162:         while((c = *(path++)) && (c != '/'));
163:         if(!c) {
164:             break;
165:         }
166:     }
167:     return basename;
168: }
169:
170: char * remove_trailing_slash(char *path)
171: {
172:     char *p;
173:
174:     p = path + (strlen(path) - 1);
175:     while(p > path && *p == '/') {
176:         *p = NULL;
177:         p--;
178:     }
179:     return path;
180: }
181:
182: int is_dir(const char *path)
183: {
184:     while(*(path + 1)) {
185:         path++;
186:     }
187:     if(*path == '/') {
188:         return 1;
189:     }
190:     return 0;
191: }
192:
193: int atoi(const char *str)
194: {
195:     int n;
196:
197:     n = 0;
198:     while(IS_SPACE(*str)) {
199:         str++;
200:     }
201:     while(IS_NUMERIC(*str)) {
```

lib/strings.c

Page 4/5

```
202:             n = (n * 10) + (*str++ - '0');
203:         }
204:         return n;
205:     }
206:
207: void memcpy_b(void *dest, const void *src, unsigned int count)
208: {
209:     unsigned char *d;
210:     unsigned char *s;
211:
212:     d = (unsigned char *)dest;
213:     s = (unsigned char *)src;
214:     while(count--) {
215:         *d = *s;
216:         d++;
217:         s++;
218:     }
219: }
220:
221: void memcpy_w(void *dest, const void *src, unsigned int count)
222: {
223:     unsigned short int *d;
224:     unsigned short int *s;
225:
226:     d = (unsigned short int *)dest;
227:     s = (unsigned short int *)src;
228:     while(count--) {
229:         *d = *s;
230:         d++;
231:         s++;
232:     }
233: }
234:
235: void memcpy_l(void *dest, const void *src, unsigned int count)
236: {
237:     unsigned int *d;
238:     unsigned int *s;
239:
240:     d = (unsigned int *)dest;
241:     s = (unsigned int *)src;
242:     while(count--) {
243:         *d = *s;
244:         d++;
245:         s++;
246:     }
247: }
248:
249: void memset_b(void *dest, unsigned char value, unsigned int count)
250: {
251:     unsigned char *d;
252:
253:     d = (unsigned char *)dest;
254:     while(count--) {
255:         *d = value;
256:         d++;
257:     }
258: }
259:
260: void memset_w(void *dest, unsigned short int value, unsigned int count)
261: {
262:     unsigned short int *d;
263:
264:     d = (unsigned short int *)dest;
265:     while(count--) {
266:         *d = value;
267:         d++;
268:     }

```

lib/strings.c

Page 5/5

```
269: }
270:
271: void memset_l(void *dest, unsigned int value, unsigned int count)
272: {
273:     unsigned int *d;
274:
275:     d = (unsigned int *)dest;
276:     while(count--) {
277:         *d = value;
278:         d++;
279:     }
280: }
```

include/fiwix/asm.h

Page 1/3

```
1: /*
2:  * fiwix/include/fiwix/asm.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_ASM_H
9: #define _FIWIX_ASM_H
10:
11: extern void except0(void);
12: extern void except1(void);
13: extern void except2(void);
14: extern void except3(void);
15: extern void except4(void);
16: extern void except5(void);
17: extern void except6(void);
18: extern void except7(void);
19: extern void except8(void);
20: extern void except9(void);
21: extern void exceptA(void);
22: extern void exceptB(void);
23: extern void exceptC(void);
24: extern void exceptD(void);
25: extern void exceptE(void);
26: extern void exceptF(void);
27: extern void except10(void);
28: extern void except11(void);
29: extern void except12(void);
30: extern void except13(void);
31: extern void except14(void);
32: extern void except15(void);
33: extern void except16(void);
34: extern void except17(void);
35: extern void except18(void);
36: extern void except19(void);
37: extern void except1A(void);
38: extern void except1B(void);
39: extern void except1C(void);
40: extern void except1D(void);
41: extern void except1E(void);
42: extern void except1F(void);
43:
44: extern void irq0(void);
45: extern void irq1(void);
46: extern void irq2(void);
47: extern void irq3(void);
48: extern void irq4(void);
49: extern void irq5(void);
50: extern void irq6(void);
51: extern void irq7(void);
52: extern void irq8(void);
53: extern void irq9(void);
54: extern void irq10(void);
55: extern void irq11(void);
56: extern void irq12(void);
57: extern void irq13(void);
58: extern void irq14(void);
59: extern void irq15(void);
60: extern void unknown_irq(void);
61:
62: extern void switch_to_user_mode(void);
63: extern void sighandler_trampoline(void);
64: extern void end_sighandler_trampoline(void);
65: extern void syscall(void);
66: extern void return_from_syscall(void);
67: extern void do_switch(unsigned int *, unsigned int *, unsigned int, unsigned int
```

include/fiwix/asm.h

Page 2/3

```

, unsigned int, unsigned short int);
68:
69: int cpuid(void);
70: int getfpu(void);
71: int vendor_id(void);
72: int signature_flags(void);
73: int brand_str(void);
74: int tlbinfo(void);
75:
76: unsigned char inport_b(unsigned int);
77: short int inport_w(unsigned int);
78: void inport_sw(unsigned int, void *, unsigned int);
79: void outport_b(unsigned int, unsigned char);
80: void outport_w(unsigned int, unsigned int);
81: void outport_sw(unsigned int, void *, unsigned int);
82:
83: void load_gdt(unsigned int);
84: void load_idt(unsigned int);
85: void activate_kpage_dir(void);
86: void load_tr(unsigned int);
87: unsigned long long int get_rdtsc(void);
88: void invalidate_tlb(void);
89:
90: #define CLI() __asm__ __volatile__ ("cli"::"memory")
91: #define STI() __asm__ __volatile__ ("sti"::"memory")
92: #define NOP() __asm__ __volatile__ ("nop"::"memory")
93: #define HLT() __asm__ __volatile__ ("hlt"::"memory")
94:
95: #define GET_CR2(cr2) __asm__ __volatile__ ("movl %%cr2, %0" : "=r" (cr2));
96: #define GET_ESP(esp) __asm__ __volatile__ ("movl %%esp, %0" : "=r" (esp));
97: #define SET_ESP(esp) __asm__ __volatile__ ("movl %0, %%esp" :: "r" (esp));
98:
99: #define SAVE_FLAGS(flags) \
100:     __asm__ __volatile__( \
101:         "pushfl ; popl %0\n\t" \
102:         : "=r" (flags) \
103:         : /* no input */ \
104:         : "memory" \
105:     );
106:
107: #define RESTORE_FLAGS(x) \
108:     __asm__ __volatile__( \
109:         "pushl %0 ; popfl\n\t" \
110:         : /* no output */ \
111:         : "r" (flags) \
112:         : "memory" \
113:     );
114:
115: #define USER_SYSCALL(num, arg1, arg2, arg3) \
116:     __asm__ __volatile__( \
117:         "movl %0, %%eax\n\t" \
118:         "movl %1, %%ebx\n\t" \
119:         "movl %2, %%ecx\n\t" \
120:         "movl %3, %%edx\n\t" \
121:         "int $0x80\n\t" \
122:         : /* no output */ \
123:         : "eax"((unsigned int)num), "ebx"((unsigned int)arg1), "ecx"((un-
signed int)arg2), "edx"((unsigned int)arg3) \
124:     );
125:
126: /*
127: static inline unsigned long long int get_rdtsc(void)
128: {
129:     unsigned int eax, edx;
130:
131:     __asm__ __volatile__("rdtsc" : "=a" (eax), "=d" (edx));
132:     return (((unsigned long long int)eax) | (((unsigned long long int)edx) <<

```

include/fiwix/asm.h

Page 3/3

```
32);  
133: }  
134: */  
135:  
136: #endif /* _FIWIX_ASM_H */
```

include/fiwix/bios.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/bios.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_BIOS_H
9: #define _FIWIX_BIOS_H
10:
11: #include <fiwix/multiboot.h>
12:
13: #define BIOS_MEM_AVAIL          1      /* BIOS memory available */
14: #define BIOS_MEM_RES           2      /* BIOS memory reserved */
15: #define BIOS_MEM_ACPI_REC      3      /* BIOS memory ACPI reclaim */
16: #define BIOS_MEM_ACPI_NVS     4      /* BIOS memory ACPI NVS */
17: #define NR_BIOS_MM_ENT         25     /* entries in BIOS memory map */
18:
19: struct bios_mem_map {
20:     unsigned long int from;
21:     unsigned long int to;
22:     unsigned long int type;
23: };
24: struct bios_mem_map bios_mem_map[NR_BIOS_MM_ENT];
25:
26: int addr_in_bios_map(unsigned int);
27: void bios_map_init(memory_map_t *, unsigned long int);
28:
29: #endif /* _FIWIX_BIOS_H */
```

include/fiwix/buffer.h

Page 1/1

```

1: /*
2:  * fiwix/include/fiwix/buffer.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_BUFFER_H
9: #define _FIWIX_BUFFER_H
10:
11: #include <fiwix/types.h>
12: #include <fiwix/fs.h>
13:
14: struct buffer {
15:     __dev_t dev;                /* device number */
16:     __blk_t block;             /* block number */
17:     int size;                  /* block size (in bytes) */
18:     char valid;                /* 1 = valid */
19:     unsigned char locked;      /* 1 = locked */
20:     unsigned char dirty;       /* 1 = delayed write */
21:     char *data;                /* block contents */
22:     struct buffer *prev_hash;
23:     struct buffer *next_hash;
24:     struct buffer *prev_free;
25:     struct buffer *next_free;
26: };
27: extern struct buffer *buffer_table;
28: extern struct buffer **buffer_hash_table;
29:
30: /* values to be determined during system startup */
31: extern unsigned int buffer_table_size;    /* size in bytes */
32: extern unsigned int buffer_hash_table_size; /* size in bytes */
33:
34: struct buffer * get_dirty_buffer(__dev_t, __blk_t, int);
35: struct buffer * bread(__dev_t, __blk_t, int);
36: void bwrite(struct buffer *);
37: void brelse(struct buffer *);
38: void sync_buffers(__dev_t);
39: void invalidate_buffers(__dev_t);
40: int reclaim_buffers(void);
41: void buffer_init(void);
42:
43: #endif /* _FIWIX_BUFFER_H */

```


include/fiwix/cmos.h

Page 1/1

```

1: /*
2:  * fiwix/include/fiwix/cmos.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_CMOS_H
9: #define _FIWIX_CMOS_H
10:
11: #define CMOS_INDEX      0x70
12: #define CMOS_DATA       0x71
13:
14: #define CMOS_STATB_IRQF 0x0F    /* periodic interrupt frequency */
15: #define CMOS_STATB_UIP  0x80    /* time update in progress */
16:
17: #define CMOS_STATB_DSE  0x01    /* enable daylight savings */
18: #define CMOS_STATB_24H  0x02    /* 24-hour mode (0=12h, 1=24h) */
19: #define CMOS_STATB_DM   0x04    /* time/date in binary mode (0=BCD, 1=binary) */
20: #define CMOS_STATB_SQWE 0x08    /* enable square wave frequency */
21: #define CMOS_STATB_UIE  0x10    /* enable update-ended interrupt */
22: #define CMOS_STATB_AIE  0x20    /* enable alarm interrupt */
23: #define CMOS_STATB_PIE  0x40    /* enable periodic interrupt */
24: #define CMOS_STATB_SET  0x80    /* abort clock update */
25:
26: #define CMOS_STATD_VRT  0x80    /* valid RAM and time */
27:
28: /* CMOS RAM data registers */
29: #define CMOS_SEC        0x00    /* second */
30: #define CMOS_ASEC       0x01    /* alarm second */
31: #define CMOS_MIN        0x02    /* minute */
32: #define CMOS_AMIN       0x03    /* alarm minute */
33: #define CMOS_HOUR       0x04    /* hour */
34: #define CMOS_AHOUR      0x05    /* alarm hour */
35: #define CMOS_DOW        0x06    /* day of week */
36: #define CMOS_DAY        0x07    /* day */
37: #define CMOS_MONTH      0x08    /* month */
38: #define CMOS_YEAR       0x09    /* last two digits of year */
39: #define CMOS_STATA      0x0A    /* status register A */
40: #define CMOS_STATB      0x0B    /* status register B */
41: #define CMOS_STATC      0x0C    /* status register C */
42: #define CMOS_STATD      0x0D    /* status register D */
43: #define CMOS_DIAG       0x0E    /* diagnostics status */
44: #define CMOS_FDDTYPE    0x10    /* floppy disk drive type */
45: #define CMOS_HDDTYPE    0x12    /* hard disk drive type */
46: #define CMOS_CENTURY    0x32    /* century */
47:
48: /* conversions */
49: #define BCD2BIN(bcd)    (((bcd) >> 4) * 10) + ((bcd) & 0x0F)
50: #define BIN2BCD(bin)   ((bin) % 10) | (((bin) / 10) << 4)
51:
52: int cmos_update_in_progress(void);
53: unsigned char cmos_read_date(unsigned char);
54: void cmos_write_date(unsigned char, unsigned char);
55: unsigned char cmos_read(unsigned char);
56: void cmos_write(unsigned char, unsigned char);
57:
58: #endif /* _FIWIX_CMOS_H */

```

include/fiwix/config.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/config.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_CONFIG_H
9: #define _FIWIX_CONFIG_H
10:
11: /* maximum number of processes */
12: #define NR_PROCS          64
13:
14: /* maximum number of callout functions (timer) */
15: #define NR_CALLOUTS      NR_PROCS
16:
17: /* maximum number of bottom halves in pool */
18: #define NR_BH             NR_PROCS
19:
20: /* maximum number of mounted filesystems */
21: #define NR_MOUNT_POINTS  8
22:
23: /* maximum number of opened files in system */
24: #define NR_OPENS         1024
25:
26: /* maximum number of flocks in system */
27: #define NR_FLOCKS        (NR_PROCS * 5)
28:
29:
30:
31: /* percentage of memory that buffer cache will borrow from available memory */
32: #define BUFFER_PERCENTAGE 100
33:
34: /* percentage of hash buckets relative to the size of the buffer table */
35: #define BUFFER_HASH_PERCENTAGE 10
36:
37: /* buffers reclaimed in a single call */
38: #define NR_BUF_RECLAIM   150
39:
40:
41: /* percentage of memory assigned to the inode table and hash table */
42: #define INODE_PERCENTAGE 5
43: #define INODE_HASH_PERCENTAGE 10
44:
45: /* percentage of memory assigned to the page hash table */
46: #define PAGE_HASH_PERCENTAGE 10
47:
48:
49: /* maximum value for PID */
50: #define MAX_PID_VALUE    32767
51:
52: /* number of screens in console' scroll back */
53: #define SCREENS_LOG      6
54:
55: #endif /* _FIWIX_CONFIG_H */
```

include/fiwix/console.h

Page 1/2

```

1: /*
2:  * fiwix/include/fiwix/console.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_CONSOLE_H
9: #define _FIWIX_CONSOLE_H
10:
11: #include <fiwix/config.h>
12: #include <fiwix/termios.h>
13: #include <fiwix/vt.h>
14:
15: #define NR_VCONSOLES          12      /* number of virtual consoles */
16:
17: #define VCONSOLES_MAJOR      4        /* virtual consoles major number */
18: #define SYSCON_MAJOR        5        /* system console major number */
19:
20: #define MONO_ADDR            0xB0000L
21: #define COLOR_ADDR          0xB8000L
22:
23: #define MONO_6845_ADDR      0x3B4    /* i/o address (+1 for data register) */
24: #define COLOR_6845_ADDR    0x3D4    /* i/o address (+1 for data register) */
25:
26: #define ATTR_CONTROLLER     0x3C0    /* attribute controller register */
27: #define ATTR_CONTROLLER_PAS 0x20     /* palette address source */
28: #define INPUT_STAT1        0x3DA    /* input status #1 register */
29: #define BLANK_INTERVAL     (600 * HZ) /* 600 seconds (10 minutes) */
30:
31: #define CRT_INDEX           0
32: #define CRT_DATA            1
33: #define CRT_CURSOR_STR     0xA
34: #define CRT_CURSOR_END     0xB
35: #define CRT_START_ADDR_HI  0xC
36: #define CRT_START_ADDR_LO  0xD
37: #define CRT_CURSOR_POS_HI  0xE
38: #define CRT_CURSOR_POS_LO  0xF
39:
40: #define CURSOR_MASK        0x1F
41: #define CURSOR_DISABLE    0x20
42:
43: #define COLOR_NORMAL       0
44: #define COLOR_BOLD         1
45: #define COLOR_BOLD_OFF    2
46: #define COLOR_UNDERLINE    4
47: #define COLOR_BLINK       5
48: #define COLOR_REVERSE     7
49:
50: #define COLOR_BLACK        0x0000
51: #define COLOR_BLUE         0x0100
52: #define COLOR_GREEN        0x0200
53: #define COLOR_CYAN         0x0300
54: #define COLOR_RED          0x0400
55: #define COLOR_MAGENTA      0x0500
56: #define COLOR_BROWN       0x0600
57: #define COLOR_WHITE        0x0700
58: #define BG_BLACK           0x0000
59: #define BG_BLUE            0x1000
60: #define BG_GREEN           0x2000
61: #define BG_CYAN            0x3000
62: #define BG_RED              0x4000
63: #define BG_MAGENTA         0x5000
64: #define BG_BROWN           0x6000
65: #define BG_WHITE           0x7000
66:
67: #define DEF_MODE            (COLOR_WHITE | BG_BLACK)

```

include/fiwix/console.h

Page 2/2

```

68: #define BLANK_MEM                (DEF_MODE | ' ')
69:
70: #define SCREEN_COLS              80
71: #define SCREEN_LINES            25
72: #define SCREEN_SIZE              (SCREEN_COLS * SCREEN_LINES * 2)
73:
74: #define TAB_SIZE                 8
75: #define BS                       127      /* backspace */
76:
77: #define MAX_TAB_COLS             132      /* maximum number of tab stops */
78:
79: #define VC_BUF_LINES             (SCREEN_LINES * SCREENS_LOG)
80: #define VC_BUF_SIZE              (SCREEN_COLS * VC_BUF_LINES * 2)
81: #define VC_BUF_UP                1
82: #define VC_BUF_DOWN              2
83:
84: unsigned int video_port;
85: extern short int current_cons; /* current console (/dev/tty1 ... /dev/tty12) */
86:
87: struct vconsole {
88:     int x;          /* current column */
89:     int y;          /* current line */
90:     int lines, columns;
91:     short int check_x;
92:     unsigned char led_status;
93:     unsigned char scrlock, numlock, capslock;
94:     unsigned char esc, sbracket, semicolon, question;
95:     int parmvl, parmvt;
96:     unsigned short int color_attr;
97:     unsigned char bold, underline, blink, reverse;
98:     int insert_mode;
99:     unsigned short int *vidmem;
100:    short int has_focus;
101:    unsigned short int scrbuf[SCREEN_SIZE / 2];
102:    int saved_x;
103:    int saved_y;
104:    char tab_stop[MAX_TAB_COLS];
105:    struct vt_mode vt_mode;
106:    unsigned char vc_mode;
107:    unsigned char blanked;
108:    int switchto_tty;
109:    struct tty *tty;
110: };
111:
112: void vconsole_reset(struct tty *);
113: void vconsole_write(struct tty *);
114: void vconsole_select(int);
115: void vconsole_select_final(int);
116: void vconsole_save(struct vconsole *);
117: void vconsole_restore(struct vconsole *);
118: void vconsole_buffer_sctl(int);
119: void blank_screen(struct vconsole *);
120: void unblank_screen(struct vconsole *);
121: void screen_on(void);
122: void screen_off(unsigned int);
123: void vconsole_start(struct tty *);
124: void vconsole_stop(struct tty *);
125: void vconsole_beep(void);
126: void vconsole_deltab(struct tty *);
127: void console_flush_log_buf(char *, unsigned int);
128: void vconsole_init(void);
129:
130: #endif /* _FIWIX_CONSOLE_H */

```

include/fiwix/const.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/const.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_CONST_H
9: #define _FIWIX_CONST_H
10:
11: #define KERNEL_BASE_ADDR      0xC0000000
12: #define KERNEL_ENTRY_ADDR    0x100000
13:
14: #define KERNEL_CS              0x08      /* kernel code segment */
15: #define KERNEL_DS              0x10      /* kernel data segment */
16: #define USER_CS                0x18      /* user code segment */
17: #define USER_DS                0x20      /* user data segment */
18: #define TSS                    0x28      /* TSS segment */
19:
20: #endif /* _FIWIX_CONST_H */
```

include/fiwix/cpu.h

Page 1/2

```

1: /*
2:  * fiwix/include/fiwix/cpu.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_CPU_H
9: #define _FIWIX_CPU_H
10:
11: #define CPU_FPU          0x00000001    /* Floating-Point Unit on chip */
12: #define CPU_VME         0x00000002    /* Virtual 8086 Mode Enhancements */
13: #define CPU_DE          0x00000004    /* Debugging Extensions */
14: #define CPU_PSE        0x00000008    /* Page Size Extension */
15: #define CPU_TSC        0x00000010    /* Time Stamp Counter */
16: #define CPU_MSR        0x00000020    /* Model Specific Registers */
17: #define CPU_PAE        0x00000040    /* Physical Address Extension */
18: #define CPU_MCE        0x00000080    /* Machine Check Exception */
19: #define CPU_CX8        0x00000100    /* CMPXCHG8B instruction supported */
20: #define CPU_APIC       0x00000200    /* On-chip APIC hardware supported */
21: #define CPU_RES10      0x00000400    /* Reserved */
22: #define CPU_SEP        0x00000800    /* Fast System Call */
23: #define CPU_MTRR       0x00001000    /* Memory Type Range Registers */
24: #define CPU_PGE        0x00002000    /* Page Global Enable */
25: #define CPU_MCA        0x00004000    /* Machine Check Architecture */
26: #define CPU_CMOV       0x00008000    /* Conditional Move Instruction */
27: #define CPU_PAT        0x00010000    /* Page Attribute Table */
28: #define CPU_PSE36      0x00020000    /* 36-bit Page Size Extension */
29: #define CPU_PSN        0x00040000    /* Processor Serial Number */
30: #define CPU_CLFSH      0x00080000    /* CLFLUSH instruction supported */
31: #define CPU_RES20      0x00100000    /* Reserved */
32: #define CPU_DS         0x00200000    /* Debug Store */
33: #define CPU ACPI       0x00400000    /* Thermal Monitor and others */
34: #define CPU_MMX        0x00800000    /* Intel Architecture MMX Technology */
35: #define CPU_FXSR       0x01000000    /* Fast Floating Point Save and Rest. */
36: #define CPU_SSE        0x02000000    /* Streaming SIMD Extensions */
37: #define CPU_SSE2       0x04000000    /* Streaming SIMD Extensions 2 */
38: #define CPU_SS         0x08000000    /* Self-Snoop */
39: #define CPU_HTT        0x10000000    /* Hyper-Threading Technology */
40: #define CPU_TM         0x20000000    /* Thermal Monitor */
41: #define CPU_RES30      0x40000000    /* Reserved */
42: #define CPU_PBE        0x80000000    /* Pending Break Enable */
43:
44: #define RESERVED_DESC  0x80000000    /* TLB descriptor reserved */
45:
46: struct cpu {
47:     char *vendor_id;
48:     char family;
49:     char model;
50:     char *model_name;
51:     char stepping;
52:     unsigned long int hz;
53:     char *cache;
54:     char has_cpuid;
55:     char has_fpu;
56:     int flags;
57: };
58: struct cpu cpu_table;
59:
60: struct cpu_type {
61:     int cpu;
62:     char *name[20];
63: };
64:
65: int get_cpu_flags(char *, int);
66: void cpu_init(void);
67:

```

include/fiwix/cpu.h

Page 2/2

```
68: #endif /* _FIWIX_CPU_H */
```

include/fiwix/ctype.h

Page 1/1

```

1: /*
2:  * fiwix/include/fiwix/ctype.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_CTYPE_H
9: #define _FIWIX_CTYPE_H
10:
11: #define _U      0x01    /* upper case */
12: #define _L      0x02    /* lower case */
13: #define _N      0x04    /* numeral (digit) */
14: #define _S      0x08    /* spacing character */
15: #define _P      0x10    /* punctuation */
16: #define _C      0x20    /* control character */
17: #define _X      0x40    /* hexadecimal */
18: #define _B      0x80    /* blank */
19:
20: extern unsigned char _ctype[];
21:
22: #define ISALPHA(ch)      ((_ctype + 1)[ch] & (_U | _L))
23: #define ISUPPER(ch)     ((_ctype + 1)[ch] & _U)
24: #define ISLOWER(ch)    ((_ctype + 1)[ch] & _L)
25: #define ISDIGIT(ch)    ((_ctype + 1)[ch] & _N)
26: #define ISALNUM(ch)    ((_ctype + 1)[ch] & (_U | _L | _N))
27: #define ISSPACE(ch)    ((_ctype + 1)[ch] & _S)
28: #define ISPUNCT(ch)    ((_ctype + 1)[ch] & _P)
29: #define ISCNTRL(ch)    ((_ctype + 1)[ch] & _C)
30: #define ISXDIGIT(ch)   ((_ctype + 1)[ch] & (_N | _X))
31:
32: #define ISASCII(ch)    ((unsigned) ch <= 0x7F)
33: #define TOASCII(ch)    ((unsigned) ch & 0x7F)
34:
35: #define TOUPPER(ch)    ((ch) & ~32)
36: #define TOLOWER(ch)   ((ch) | 32)
37:
38: #endif /* _FIWIX_CTYPE_H */

```


include/fiwix/devices.h

Page 1/1

```

1: /*
2:  * fiwix/include/fiwix/devices.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_DEVICES_H
9: #define _FIWIX_DEVICES_H
10:
11: #include <fiwix/types.h>
12: #include <fiwix/fs.h>
13:
14: #define NR_BLKDEV          128      /* maximum number of block devices */
15: #define NR_CHRDEV          128      /* maximum number of char devices */
16:
17: #define BLK_DEV             1        /* block device */
18: #define CHR_DEV             2        /* character device */
19:
20: #define SET_MINOR(minors, bit) ((minors[(bit) / 32]) |= (1 << ((bit) % 32)))
21: #define CLEAR_MINOR(minors, bit) ((minors[(bit) / 32]) &= ~(1 << ((bit) % 32)))
22: #define TEST_MINOR(minors, bit) ((minors[(bit) / 32]) & (1 << ((bit) % 32)))
23:
24: struct device {
25:     char *name;
26:     int irq;
27:     unsigned char major;
28:     unsigned int minors[8];        /* bitmap of 256 bits */
29:     int blksize;
30:     void *device_data;            /* mostly used for minor sizes in KB */
31:     struct fs_operations *fsop;
32: };
33:
34: extern struct device chr_device_table[NR_CHRDEV];
35: extern struct device blk_device_table[NR_BLKDEV];
36:
37: int register_device(int, struct device *);
38: struct device * get_device(int, unsigned char);
39: int chr_dev_open(struct inode *, struct fd *);
40: int blk_dev_open(struct inode *, struct fd *);
41: int blk_dev_close(struct inode *, struct fd *);
42: int blk_dev_read(struct inode *, struct fd *, char *, __size_t);
43: int blk_dev_write(struct inode *, struct fd *, const char *, __size_t);
44: int blk_dev_ioctl(struct inode *, int, unsigned long int);
45: int blk_dev_lseek(struct inode *, __off_t);
46:
47: void dev_init(void);
48:
49: #endif /* _FIWIX_DEVICES_H */

```

include/fiwix/dirent.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/dirent.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_DIRENT_H
9: #define _FIWIX_DIRENT_H
10:
11: #include <fiwix/types.h>
12: #include <fiwix/limits.h>
13:
14: struct dirent {
15:     __ino_t d_ino;           /* inode number */
16:     __off_t d_off;          /* offset to next dirent */
17:     unsigned short int d_reclen; /* length of this dirent */
18:     char d_name[NAME_MAX + 1]; /* file name (null-terminated) */
19: };
20:
21: #endif /* _FIWIX_DIRENT_H */
```

include/fiwix/dma.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/dma.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_DMA_H
9: #define _FIWIX_DMA_H
10:
11: #define DMA_CHANNELS          8          /* max. number of DMA channels */
12:
13: #define DMA_MASK_CHANNEL     0x04
14: #define DMA_UNMASK_CHANNEL   0x00
15:
16: #define DMA_MODE_VERIFY      0x00
17: #define DMA_MODE_WRITE       0x04      /* read device -> write memory */
18: #define DMA_MODE_READ        0x08      /* read memory -> write device */
19: #define DMA_MODE_AUTOINIT    0x10
20: #define DMA_MODE_ADDRES_DEC   0x20
21: #define DMA_MODE_DEMAND      0x00
22: #define DMA_MODE_SINGLE      0x40
23: #define DMA_MODE_BLOCK       0x80
24: #define DMA_MODE_CASCADE     0xC0
25:
26: char *dma_resources[DMA_CHANNELS];
27:
28: void start_dma(int, void *, unsigned int, int);
29: int dma_register(int, char *);
30: int dma_unregister(int);
31: void dma_init(void);
32:
33: #endif /* _FIWIX_DMA_H */
```

include/fiwix/errno.h

Page 1/3

```

1: #ifndef _FIWIX_ERRNO_H
2: #define _FIWIX_ERRNO_H
3:
4: #define EPERM          1      /* Operation not permitted - Not owner */
5: #define ENOENT         2      /* No such file or directory */
6: #define ESRCH         3      /* No such process */
7: #define EINTR         4      /* Interrupted system call */
8: #define EIO           5      /* I/O error */
9: #define ENXIO         6      /* No such device or address */
10: #define E2BIG         7      /* Arg list too long */
11: #define ENOEXEC       8      /* Exec format error */
12: #define EBADF         9      /* Bad file number */
13: #define ECHILD        10     /* No child processes */
14: #define EAGAIN        11     /* Try again - No more processes */
15: #define ENOMEM        12     /* Out of memory - No enough space */
16: #define EACCES        13     /* Permission denied */
17: #define EFAULT        14     /* Bad address */
18: #define ENOTBLK       15     /* Block device required */
19: #define EBUSY         16     /* Device or resource busy */
20: #define EEXIST        17     /* File exists */
21: #define EXDEV         18     /* Cross-device link */
22: #define ENODEV        19     /* No such device */
23: #define ENOTDIR       20     /* Not a directory */
24: #define EISDIR        21     /* Is a directory */
25: #define EINVAL        22     /* Invalid argument */
26: #define ENFILE        23     /* File table overflow */
27: #define EMFILE        24     /* Too many open files */
28: #define ENOTTY        25     /* Not a typewriter */
29: #define ETXTBSY       26     /* Text file busy */
30: #define EFBIG         27     /* File too large */
31: #define ENOSPC        28     /* No space left on device */
32: #define ESPIPE        29     /* Illegal seek */
33: #define EROFS         30     /* Read-only file system */
34: #define EMLINK        31     /* Too many links */
35: #define EPIPE         32     /* Broken pipe */
36: #define EDOM          33     /* Math argument out of domain of func */
37: #define ERANGE        34     /* Math result not representable */
38: #define EDEADLK       35     /* Resource deadlock would occur */
39: #define ENAMETOOLONG  36     /* File name too long */
40: #define ENOLCK        37     /* No record locks available */
41: #define ENOSYS        38     /* Function not implemented */
42: #define ENOTEMPTY     39     /* Directory not empty */
43: #define ELOOP         40     /* Too many symbolic links encountered */
44: #define EWOULDBLOCK   EAGAIN  /* Operation would block */
45: #define ENOMSG        42     /* No message of desired type */
46: #define EIDRM         43     /* Identifier removed */
47: #define ECHRNG        44     /* Channel number out of range */
48: #define EL2NSYNC      45     /* Level 2 not synchronized */
49: #define EL3HLT        46     /* Level 3 halted */
50: #define EL3RST        47     /* Level 3 reset */
51: #define ELNRNG        48     /* Link number out of range */
52: #define EUNATCH       49     /* Protocol driver not attached */
53: #define ENOCCSI       50     /* No CSI structure available */
54: #define EL2HLT        51     /* Level 2 halted */
55: #define EBADE         52     /* Invalid exchange */
56: #define EBADR         53     /* Invalid request descriptor */
57: #define EXFULL        54     /* Exchange full */
58: #define ENOANO        55     /* No anode */
59: #define EBADRQC       56     /* Invalid request code */
60: #define EBADSLT       57     /* Invalid slot */
61:
62: #define EDEADLOCK     EDEADLK
63:
64: #define EBFONT        59     /* Bad font file format */
65: #define ENOSTR        60     /* Device not a stream */
66: #define ENODATA       61     /* No data available */
67: #define ETIME         62     /* Timer expired */

```

include/fiwix/errno.h

Page 2/3

```

68: #define ENOSR          63      /* Out of streams resources */
69: #define ENONET         64      /* Machine is not on the network */
70: #define ENOPKG         65      /* Package not installed */
71: #define EREMOTE        66      /* Object is remote */
72: #define ENOLINK        67      /* Link has been severed */
73: #define EADV           68      /* Advertise error */
74: #define ESRMNT         69      /* Srmount error */
75: #define ECOMM          70      /* Communication error on send */
76: #define EPROTO         71      /* Protocol error */
77: #define EMULTIHOP       72      /* Multihop attempted */
78: #define EDOTDOT        73      /* RFS specific error */
79: #define EBADMSG        74      /* Not a data message */
80: #define EOVERFLOW      75      /* Value too large for defined data type */
81: #define ENOTUNIQ       76      /* Name not unique on network */
82: #define EBADF          77      /* File descriptor in bad state */
83: #define EREMCHG        78      /* Remote address changed */
84: #define ELIBACC        79      /* Can not access a needed shared library */
85: #define ELIBBAD        80      /* Accessing a corrupted shared library */
86: #define ELIBSCN        81      /* .lib section in a.out corrupted */
87: #define ELIBMAX        82      /* Attempting to link in too many shared librari
es */
88: #define ELIBEXEC       83      /* Cannot exec a shared library directly */
89: #define EILSEQ         84      /* Illegal byte sequence */
90: #define ERESTART       85      /* Interrupted system call should be restarted */
/
91: #define ESTRPIPE       86      /* Streams pipe error */
92: #define EUSERS         87      /* Too many users */
93: #define ENOTSOCK       88      /* Socket operation on non-socket */
94: #define EDESTADDRREQ   89      /* Destination address required */
95: #define EMSGSIZE       90      /* Message too long */
96: #define EPROTOTYPE     91      /* Protocol wrong type for socket */
97: #define ENOPROTOOPT    92      /* Protocol not available */
98: #define EPROTONOSUPPORT 93      /* Protocol not supported */
99: #define ESOCKTNOSUPPORT 94      /* Socket type not supported */
100: #define EOPNOTSUPP     95      /* Operation not supported on transport endpoint
*/
101: #define EPFNOSUPPORT    96      /* Protocol family not supported */
102: #define EAFNOSUPPORT    97      /* Address family not supported by protocol */
103: #define EADDRINUSE     98      /* Address already in use */
104: #define EADDRNOTAVAIL  99      /* Cannot assign requested address */
105: #define ENETDOWN       100     /* Network is down */
106: #define ENETUNREACH    101     /* Network is unreachable */
107: #define ENETRESET      102     /* Network dropped connection because of reset */
/
108: #define ECONNABORTED   103     /* Software caused connection abort */
109: #define ECONNRESET     104     /* Connection reset by peer */
110: #define ENOBUFS        105     /* No buffer space available */
111: #define EISCONN        106     /* Transport endpoint is already connected */
112: #define ENOTCONN       107     /* Transport endpoint is not connected */
113: #define ESHUTDOWN      108     /* Cannot send after transport endpoint shutdown
*/
114: #define ETOOMANYREFS   109     /* Too many references: cannot splice */
115: #define ETIMEDOUT      110     /* Connection timed out */
116: #define ECONNREFUSED   111     /* Connection refused */
117: #define EHOSTDOWN      112     /* Host is down */
118: #define EHOSTUNREACH   113     /* No route to host */
119: #define EALREADY       114     /* Operation already in progress */
120: #define EINPROGRESS    115     /* Operation now in progress */
121: #define ESTALE         116     /* Stale NFS file handle */
122: #define EUCLEAN        117     /* Structure needs cleaning */
123: #define ENOTNAM        118     /* Not a XENIX named type file */
124: #define ENAVAIL        119     /* No XENIX semaphores available */
125: #define EISNAM         120     /* Is a named type file */
126: #define EREMOTEIO      121     /* Remote I/O error */
127: #define EDQUOT         122     /* Quota exceeded */
128:
129: #define ENOMEDIUM     123     /* No medium found */

```

include/fiwix/errno.h

Page 3/3

```
130: #define EMEDIUMTYPE      124      /* Wrong medium type          */
131:
132: #endif /* _FIWIX_ERRNO_H */
```

include/fiwix/fcntl.h

Page 1/1

```

1: /*
2:  * fiwix/include/fiwix/fcntl.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_FCNTL_H
9: #define _FIWIX_FCNTL_H
10:
11: #include <fiwix/types.h>
12:
13: #define O_ACCMODE          0003
14: #define O_RDONLY          00
15: #define O_WRONLY          01
16: #define O_RDWR           02
17:
18: /* for open() only */
19: #define O_CREAT            0100 /* create file if it does not exist */
20: #define O_EXCL             0200 /* exclusive use flag */
21: #define O_NOCTTY          0400 /* do not assign controlling terminal */
22: #define O_TRUNC           01000 /* truncate flag */
23: #define O_NOFOLLOW        0400000 /* do not follow symbolic links */
24:
25: #define O_APPEND          02000
26: #define O_NONBLOCK        04000
27: #define O_NDELAY          O_NONBLOCK
28: #define O_SYNC            010000
29:
30: #define F_DUPFD           0      /* duplicate file descriptor */
31: #define F_GETFD           1      /* get file descriptor flags */
32: #define F_SETFD           2      /* set file descriptor flags */
33: #define F_GETFL           3      /* get status flags and file access modes */
34: #define F_SETFL           4      /* set file status flags */
35: #define F_GETLK           5      /* get record locking information */
36: #define F_SETLK           6      /* set record locking information */
37: #define F_SETLKW          7      /* same as F_SETLK; wait if blocked */
38:
39: /* get/set process or process group ID to receive SIGURG signals */
40: #define F_SETOWN           8      /* for sockets only */
41: #define F_GETOWN           9      /* for sockets only */
42:
43: /* for F_[GET|SET]FL */
44: #define FD_CLOEXEC         1      /* close the file descriptor upon exec() */
45:
46: /* for POSIX fcntl() */
47: #define F_RDLCK            0      /* shared or read lock */
48: #define F_WRLCK            1      /* exclusive or write lock */
49: #define F_UNLCK            2      /* unlock */
50:
51: /* for BSD flock() */
52: #define LOCK_SH             1      /* shared lock */
53: #define LOCK_EX             2      /* exclusive lock */
54: #define LOCK_NB             4      /* or'd with one of the above to prevent
55:                                     blocking */
56: #define LOCK_UN            8      /* unlock */
57:
58: /* IEEE Std 1003.1, 2004 Edition */
59: struct flock {
60:     short int l_type;          /* type of lock: F_RDLCK, F_WRLCK, F_UNLCK */
61:     short int l_whence;        /* flag for 'l_start': SEEK_SET, SEEK_CUR, ... */
62:     __off_t l_start;           /* relative offset in bytes */
63:     __off_t l_len;             /* size; if 0 then until EOF */
64:     __pid_t l_pid;             /* PID holding the lock; returned in F_GETLK */
65: };
66:
67: #endif /* _FIWIX_FCNTL_H */

```

include/fiwix/filesystems.h

Page 1/3

```

1: /*
2:  * fiwix/include/fiwix/filesystems.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_FILESYSTEMS_H
9: #define _FIWIX_FILESYSTEMS_H
10:
11: #include <fiwix/types.h>
12: #include <fiwix/limits.h>
13:
14: #define NR_FILESYSTEMS          5          /* supported filesystems */
15:
16: /* value to be determined during system startup */
17: extern unsigned int mount_table_size; /* size in bytes */
18:
19: struct filesystems {
20:     const char *name;          /* filesystem name */
21:     struct fs_operations *fsop; /* filesystem operations */
22:     struct mount *mt;         /* mount-table entry (only for nodev) */
23: };
24: struct filesystems filesystems_table[NR_FILESYSTEMS];
25:
26: struct mount {
27:     __dev_t dev;              /* device number */
28:     char devname[DEVNAME_MAX + 1]; /* device name */
29:     char dirname[NAME_MAX + 1]; /* mount point directory name */
30:     unsigned char used;       /* 1=busy, 0=free */
31:     struct superblock sb;     /* superblock */
32:     struct filesystems *fs;    /* pointer to filesystem structure */
33: };
34: extern struct mount *mount_table;
35:
36: int register_filesystem(const char *, struct fs_operations *);
37: struct filesystems * get_filesystem(const char *);
38: void fs_init(void);
39:
40: struct superblock * get_superblock(__dev_t);
41: void sync_superblocks(__dev_t);
42: int kern_mount(__dev_t, struct filesystems *);
43: int mount_root(void);
44: void mount_init(void);
45:
46:
47: /* minix prototypes */
48: int minix_file_open(struct inode *, struct fd *);
49: int minix_file_close(struct inode *, struct fd *);
50: int minix_file_write(struct inode *, struct fd *, const char *, __size_t);
51: int minix_file_lseek(struct inode *, __off_t);
52: int minix_dir_open(struct inode *, struct fd *);
53: int minix_dir_close(struct inode *, struct fd *);
54: int minix_dir_read(struct inode *, struct fd *, char *, __size_t);
55: int minix_dir_write(struct inode *, struct fd *, const char *, __size_t);
56: int minix_dir_readdir(struct inode *, struct fd *, struct dirent *, unsigned int
);
57: int minix_readlink(struct inode *, char *, __size_t);
58: int minix_followlink(struct inode *, struct inode *, struct inode **);
59: int minix_bmap(struct inode *, __off_t, int);
60: int minix_lookup(const char *, struct inode *, struct inode **);
61: int minix_rmdir(struct inode *, struct inode *);
62: int minix_link(struct inode *, struct inode *, char *);
63: int minix_unlink(struct inode *, struct inode *, char *);
64: int minix_symlink(struct inode *, char *, char *);
65: int minix_mkdir(struct inode *, char *, __mode_t);
66: int minix_mknod(struct inode *, char *, __mode_t, __dev_t);

```


include/fiwix/filesystems.h

Page 2/3

```

67: int minix_truncate(struct inode *, __off_t);
68: int minix_create(struct inode *, char *, __mode_t, struct inode **);
69: int minix_rename(struct inode *, struct inode *, struct inode *, struct inode *,
char *, char *);
70: int minix_read_inode(struct inode *);
71: int minix_write_inode(struct inode *);
72: int minix_ialloc(struct inode *);
73: void minix_ifree(struct inode *);
74: void minix_statfs(struct superblock *, struct statfs *);
75: int minix_read_superblock(__dev_t, struct superblock *);
76: int minix_remount_fs(struct superblock *, int);
77: int minix_write_superblock(struct superblock *);
78: void minix_release_superblock(struct superblock *);
79: int minix_init(void);
80:
81:
82: /* ext2 prototypes */
83: int ext2_file_open(struct inode *, struct fd *);
84: int ext2_file_close(struct inode *, struct fd *);
85: int ext2_file_lseek(struct inode *, __off_t);
86: int ext2_dir_open(struct inode *, struct fd *);
87: int ext2_dir_close(struct inode *, struct fd *);
88: int ext2_dir_read(struct inode *, struct fd *, char *, __size_t);
89: int ext2_dir_readdir(struct inode *, struct fd *, struct dirent *, unsigned int)
;
90: int ext2_readlink(struct inode *, char *, __size_t);
91: int ext2_followlink(struct inode *, struct inode *, struct inode **);
92: int ext2_bmap(struct inode *, __off_t, int);
93: int ext2_lookup(const char *, struct inode *, struct inode **);
94: int ext2_read_inode(struct inode *);
95: void ext2_statfs(struct superblock *, struct statfs *);
96: int ext2_read_superblock(__dev_t, struct superblock *);
97: int ext2_init(void);
98:
99:
100: /* pipefs prototypes */
101: int fifo_open(struct inode *, struct fd *);
102: int pipefs_close(struct inode *, struct fd *);
103: int pipefs_read(struct inode *, struct fd *, char *, __size_t);
104: int pipefs_write(struct inode *, struct fd *, const char *, __size_t);
105: int pipefs_ioctl(struct inode *, int, unsigned long int);
106: int pipefs_lseek(struct inode *, __off_t);
107: int pipefs_select(struct inode *, int);
108: int pipefs_ialloc(struct inode *);
109: void pipefs_ifree(struct inode *);
110: int pipefs_read_superblock(__dev_t, struct superblock *);
111: int pipefs_init(void);
112:
113:
114: /* iso9660 prototypes */
115: int iso9660_file_open(struct inode *, struct fd *);
116: int iso9660_file_close(struct inode *, struct fd *);
117: int iso9660_file_lseek(struct inode *, __off_t);
118: int iso9660_dir_open(struct inode *, struct fd *);
119: int iso9660_dir_close(struct inode *, struct fd *);
120: int iso9660_dir_read(struct inode *, struct fd *, char *, __size_t);
121: int iso9660_dir_readdir(struct inode *, struct fd *, struct dirent *, unsigned i
nt);
122: int iso9660_readlink(struct inode *, char *, __size_t);
123: int iso9660_followlink(struct inode *, struct inode *, struct inode **);
124: int iso9660_bmap(struct inode *, __off_t, int);
125: int iso9660_lookup(const char *, struct inode *, struct inode **);
126: int iso9660_read_inode(struct inode *);
127: void iso9660_statfs(struct superblock *, struct statfs *);
128: int iso9660_read_superblock(__dev_t, struct superblock *);
129: void iso9660_release_superblock(struct superblock *);
130: int iso9660_init(void);

```

include/fiwix/filesystems.h

Page 3/3

```
131:
132:
133: /* procfs prototypes */
134: int procfs_file_open(struct inode *, struct fd *);
135: int procfs_file_close(struct inode *, struct fd *);
136: int procfs_file_read(struct inode *, struct fd *, char *, __size_t);
137: int procfs_file_lseek(struct inode *, __off_t);
138: int procfs_dir_open(struct inode *, struct fd *);
139: int procfs_dir_close(struct inode *, struct fd *);
140: int procfs_dir_read(struct inode *, struct fd *, char *, __size_t);
141: int procfs_dir_readdir(struct inode *, struct fd *, struct dirent *, unsigned in
t);
142: int procfs_readlink(struct inode *, char *, __size_t);
143: int procfs_followlink(struct inode *, struct inode *, struct inode **);
144: int procfs_bmap(struct inode *, __off_t, int);
145: int procfs_lookup(const char *, struct inode *, struct inode **);
146: int procfs_read_inode(struct inode *);
147: void procfs_statfs(struct superblock *, struct statfs *);
148: int procfs_read_superblock(__dev_t, struct superblock *);
149: int procfs_init(void);
150:
151: #endif /* _FIWIX_FILESYSTEMS_H */
```

include/fiwix/floppy.h

Page 1/2

```

1: /*
2:  * fiwix/include/fiwix/floppy.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_FLOPPY_H
9: #define _FIWIX_FLOPPY_H
10:
11: #include <fiwix/fs.h>
12:
13: #define FLOPPY_IRQ        6
14: #define FLOPPY_DMA        2        /* DMA channel */
15:
16: #define FDC_MAJOR        2        /* fdd major number */
17:
18: #define FDC_SECTSIZE      512      /* sector size (in bytes) */
19: #define FDC_TR_DEFAULT    0        /* timer reason is IRQ */
20: #define FDC_TR_MOTOR      1        /* timer reason is motor on */
21:
22: #define FDC_SRA           0x3F0     /* Status Register A */
23: #define FDC_SRB           0x3F1     /* Status Register B */
24: #define FDC_DOR           0x3F2     /* Digital Output Register */
25: #define FDC_MSR           0x3F4     /* Main Status Register */
26: #define FDC_DATA          0x3F5     /* command/data register */
27: #define FDC_DIR           0x3F7     /* Digital Input Register */
28: #define FDC_CCR           0x3F7     /* Configuration Control Register */
29:
30: #define FDC_ENABLE        0x04      /* bit #2 FDC enabled (normal op) */
31: #define FDC_DMA_ENABLE    0x08      /* bit #3 DMA enabled */
32: #define FDC_DRIVE0        0x10      /* motor on for the first drive, the rest will
33:  * be calculated by left-shifting this value
34:  * with 'current_fdd'.
35:  */
36:
37: #define FDC_DIO           0x40      /* bit #6 DIO I/O direction */
38: #define FDC_RQM           0x80      /* bit #7 RQM is ready for I/O */
39:
40: #define MAX_FDC_RESULTS   7
41: #define MAX_FDC_ERR       5
42:
43: #define FDC_RESET         0xFF      /* reset indicator */
44: #define FDC_READ          0xE6
45: #define FDC_WRITE         0xC5
46: #define FDC_VERSION       0x10
47: #define FDC_FORMAT_TRK    0x4D
48: #define FDC_RECALIBRATE   0x07
49: #define FDC_SENSEI        0x08
50: #define FDC_SPECIFY        0x03
51: #define FDC_SEEK          0x0F
52: #define FDC_LOCK          0x14
53: #define FDC_PARTID        0x18
54:
55: #define ST0               0x00      /* Status Register 0 */
56: #define ST1               0x01      /* Status Register 1 */
57: #define ST2               0x02      /* Status Register 2 */
58:
59: #define ST0_IC            0xC0      /* bits #7 and #6 interrupt code */
60: #define ST0_SE            0x20      /* bit #5 successful implied seek */
61: #define ST0_RECALIBRATE   ST0_SE    /* bit #5 successful FDC_RECALIBRATE */
62: #define ST0_SEEK          ST0_SE    /* bit #5 successful FDC_SEEK */
63: #define ST0_UC            0x10      /* bit #4 unit needs check (fault) */
64: #define ST0_NR            0x8       /* bit #3 drive not ready */
65:
66: #define ST1_NW            0x02      /* bit #1 not writable */
67:

```

include/fiwix/floppy.h

Page 2/2

```

68: #define ST_PCN          0x01    /* present cylinder */
69: #define ST_CYL          0x03    /* cylinder returned */
70: #define ST_HEAD         0x04    /* head returned */
71: #define ST_SECTOR       0x05    /* sector returned */
72:
73: /* floppy disk drive type */
74: struct fdtd {
75:     short int size;           /* number of sectors */
76:     short int sizekb;        /* size in KB */
77:     char tracks;             /* number of tracks */
78:     char spt;                /* number of sectors per track */
79:     char heads;             /* number of heads */
80:     char gpl1;              /* GAP in READ/WRITE operations */
81:     char gpl2;              /* GAP in FORMAT TRACK operations */
82:     char rate;              /* data rate value */
83:     char spec;              /* SRT+HUT (StepRate + HeadUnload) Time */
84:     char hlt;               /* HLT (Head Load Time) */
85:     char *name;             /* unit name */
86: };
87:
88: void irq_floppy(void);
89: void fdc_timer(unsigned int);
90:
91: int fdc_open(struct inode *, struct fd *);
92: int fdc_close(struct inode *, struct fd *);
93: int fdc_read(__dev_t, __blk_t, char *, int);
94: int fdc_write(__dev_t, __blk_t, char *, int);
95: int fdc_ioctl(struct inode *, int, unsigned long int);
96: int fdc_lseek(struct inode *, __off_t);
97:
98: void floppy_init(void);
99:
100: #endif /* _FIWIX_FLOPPY_H */

```

include/fiwix/fs_ext2.h

Page 1/4

```

1: /*
2:  * fiwix/include/fiwix/fs_ext2.h
3:  *
4:  * This file from: Linux 2.0.40
5:  * Copyright (C) 1992, 1993, 1994, 1995
6:  * Remy Card (card@masi.ibp.fr)
7:  * Laboratoire MASI - Institut Blaise Pascal
8:  * Universite Pierre et Marie Curie (Paris VI)
9:  * Copyright (C) 1991, 1992 Linus Torvalds
10: */
11:
12: #ifndef _FIWIX_FS_EXT2_H
13: #define _FIWIX_FS_EXT2_H
14:
15: #include <fiwix/types.h>
16:
17: #define EXT2_ROOT_INO          2          /* Root inode */
18: #define EXT2_SUPER_MAGIC      0xEF53
19:
20: /*
21:  * Macro-instructions used to manage several block sizes
22:  */
23: #define EXT2_MIN_BLOCK_SIZE    1024
24: #define EXT2_MAX_BLOCK_SIZE    4096
25: #define EXT2_MIN_BLOCK_LOG_SIZE 10
26: # define EXT2_BLOCK_SIZE(s)    ((s)->s_blocksize)
27: # define EXT2_BLOCK_SIZE_BITS(s) ((s)->s_blocksize_bits)
28:
29: /*
30:  * Structure of a blocks group descriptor
31:  */
32: struct ext2_group_desc
33: {
34:     __u32    bg_block_bitmap;          /* Blocks bitmap block */
35:     __u32    bg_inode_bitmap;         /* Inodes bitmap block */
36:     __u32    bg_inode_table;          /* Inodes table block */
37:     __u16    bg_free_blocks_count;    /* Free blocks count */
38:     __u16    bg_free_inodes_count;    /* Free inodes count */
39:     __u16    bg_used_dirs_count;      /* Directories count */
40:     __u16    bg_pad;
41:     __u32    bg_reserved[3];
42: };
43:
44: /*
45:  * Macro-instructions used to manage group descriptors
46:  */
47: # define EXT2_BLOCKS_PER_GROUP(s)    ((s)->u.ext2_sb.s_blocks_per_group)
48: # define EXT2_DESC_PER_BLOCK(s)      ((s)->u.ext2_sb.s_desc_per_block)
49: # define EXT2_INODES_PER_GROUP(s)    ((s)->u.ext2_sb.s_inodes_per_group)
50: # define EXT2_DESC_PER_BLOCK_BITS(s) ((s)->u.ext2_sb.s_desc_per_block_bits)
51:
52: /*
53:  * Constants relative to the data blocks
54:  */
55: #define EXT2_NDIR_BLOCKS        12
56: #define EXT2_IND_BLOCK          EXT2_NDIR_BLOCKS
57: #define EXT2_DIND_BLOCK         (EXT2_IND_BLOCK + 1)
58: #define EXT2_TIND_BLOCK         (EXT2_DIND_BLOCK + 1)
59: #define EXT2_N_BLOCKS           (EXT2_TIND_BLOCK + 1)
60:
61: /*
62:  * Structure of an inode on the disk
63:  */
64: struct ext2_inode {
65:     __u16    i_mode;                  /* File mode */
66:     __u16    i_uid;                   /* Low 16 bits of Owner Uid */
67:     __u32    i_size;                  /* Size in bytes */

```

include/fiwix/fs_ext2.h

Page 2/4

```

68:     __u32    i_atime;        /* Access time */
69:     __u32    i_ctime;        /* Creation time */
70:     __u32    i_mtime;        /* Modification time */
71:     __u32    i_dtime;        /* Deletion Time */
72:     __u16    i_gid;          /* Low 16 bits of Group Id */
73:     __u16    i_links_count;  /* Links count */
74:     __u32    i_blocks;       /* Blocks count */
75:     __u32    i_flags;        /* File flags */
76:     union {
77:         struct {
78:             __u32    l_i_reserved1;
79:         } linux1;
80:         struct {
81:             __u32    h_i_translator;
82:         } hurd1;
83:         struct {
84:             __u32    m_i_reserved1;
85:         } masix1;
86:     } osd1;                    /* OS dependent 1 */
87:     __u32    i_block[EXT2_N_BLOCKS]; /* Pointers to blocks */
88:     __u32    i_generation;    /* File version (for NFS) */
89:     __u32    i_file_acl;      /* File ACL */
90:     __u32    i_dir_acl;       /* Directory ACL */
91:     __u32    i_faddr;         /* Fragment address */
92:     union {
93:         struct {
94:             __u8     l_i_frag;    /* Fragment number */
95:             __u8     l_i_fsize;   /* Fragment size */
96:             __u16    i_pad1;
97:             __u16    l_i_uid_high; /* these 2 fields */
98:             __u16    l_i_gid_high; /* were reserved2[0] */
99:             __u32    l_i_reserved2;
100:        } linux2;
101:        struct {
102:            __u8     h_i_frag;    /* Fragment number */
103:            __u8     h_i_fsize;   /* Fragment size */
104:            __u16    h_i_mode_high;
105:            __u16    h_i_uid_high;
106:            __u16    h_i_gid_high;
107:            __u32    h_i_author;
108:        } hurd2;
109:        struct {
110:            __u8     m_i_frag;    /* Fragment number */
111:            __u8     m_i_fsize;   /* Fragment size */
112:            __u16    m_pad1;
113:            __u32    m_i_reserved2[2];
114:        } masix2;
115:    } osd2;                    /* OS dependent 2 */
116: };
117:
118: /*
119:  * File system states
120:  */
121: #define EXT2_VALID_FS          0x0001 /* Unmounted cleanly */
122: #define EXT2_ERROR_FS         0x0002 /* Errors detected */
123:
124: /*
125:  * Structure of the super block
126:  */
127: struct ext2_super_block {
128:     __u32    s_inodes_count;    /* Inodes count */
129:     __u32    s_blocks_count;    /* Blocks count */
130:     __u32    s_r_blocks_count;  /* Reserved blocks count */
131:     __u32    s_free_blocks_count; /* Free blocks count */
132:     __u32    s_free_inodes_count; /* Free inodes count */
133:     __u32    s_first_data_block; /* First Data Block */
134:     __u32    s_log_block_size;  /* Block size */

```

include/fiwix/fs_ext2.h

Page 3/4

```

135:     __s32    s_log_frag_size;        /* Fragment size */
136:     __u32    s_blocks_per_group;     /* # Blocks per group */
137:     __u32    s_frags_per_group;     /* # Fragments per group */
138:     __u32    s_inodes_per_group;    /* # Inodes per group */
139:     __u32    s_mtime;               /* Mount time */
140:     __u32    s_wtime;               /* Write time */
141:     __ul6    s_mnt_count;           /* Mount count */
142:     __sl6    s_max_mnt_count;       /* Maximal mount count */
143:     __ul6    s_magic;               /* Magic signature */
144:     __ul6    s_state;               /* File system state */
145:     __ul6    s_errors;              /* Behaviour when detecting errors */
146:     __ul6    s_minor_rev_level;     /* minor revision level */
147:     __u32    s_lastcheck;           /* time of last check */
148:     __u32    s_checkinterval;       /* max. time between checks */
149:     __u32    s_creator_os;          /* OS */
150:     __u32    s_rev_level;           /* Revision level */
151:     __ul6    s_def_resuid;          /* Default uid for reserved blocks */
152:     __ul6    s_def_resgid;          /* Default gid for reserved blocks */
153: /*
154:  * These fields are for EXT2_DYNAMIC_REV superblocks only.
155:  *
156:  * Note: the difference between the compatible feature set and
157:  * the incompatible feature set is that if there is a bit set
158:  * in the incompatible feature set that the kernel doesn't
159:  * know about, it should refuse to mount the filesystem.
160:  *
161:  * e2fsck's requirements are more strict; if it doesn't know
162:  * about a feature in either the compatible or incompatible
163:  * feature set, it must abort and not try to meddle with
164:  * things it doesn't understand...
165:  */
166:     __u32    s_first_ino;            /* First non-reserved inode */
167:     __ul6    s_inode_size;          /* size of inode structure */
168:     __ul6    s_block_group_nr;     /* block group # of this superblock */
169:     __u32    s_feature_compat;     /* compatible feature set */
170:     __u32    s_feature_incompat;   /* incompatible feature set */
171:     __u32    s_feature_ro_compat;  /* readonly-compatible feature set */
172:     __u8     s_uuid[16];            /* 128-bit uuid for volume */
173:     char     s_volume_name[16];     /* volume name */
174:     char     s_last_mounted[64];    /* directory where last mounted */
175:     __u32    s_algorithm_usage_bitmap; /* For compression */
176: /*
177:  * Performance hints. Directory preallocation should only
178:  * happen if the EXT2_COMPAT_PREALLOC flag is on.
179:  */
180:     __u8     s_prealloc_blocks;     /* Nr of blocks to try to preallocate*/
181:     __u8     s_prealloc_dir_blocks; /* Nr to preallocate for dirs */
182:     __ul6    s_padding1;
183: /*
184:  * Journaling support valid if EXT3_FEATURE_COMPAT_HAS_JOURNAL set.
185:  */
186:     __u8     s_journal_uuid[16];    /* uuid of journal superblock */
187:     __u32    s_journal_inum;        /* inode number of journal file */
188:     __u32    s_journal_dev;         /* device number of journal file */
189:     __u32    s_last_orphan;        /* start of list of inodes to delete */
190:     __u32    s_hash_seed[4];        /* HTREE hash seed */
191:     __u8     s_def_hash_version;    /* Default hash version to use */
192:     __u8     s_reserved_char_pad;
193:     __ul6    s_reserved_word_pad;
194:     __u32    s_default_mount_opts;
195:     __u32    s_first_meta_bg;       /* First metablock block group */
196:     __u32    s_reserved[190];       /* Padding to the end of the block */
197: };
198:
199: #define EXT2_FEATURE_RO_COMPAT_SPARSE_SUPER    0x0001
200:
201: /*

```

include/fiwix/fs_ext2.h

Page 4/4

```
202:  * Structure of a directory entry
203:  */
204:  #define EXT2_NAME_LEN 255
205:
206:  struct ext2_dir_entry {
207:      __u32   inode;           /* Inode number */
208:      __u16   rec_len;        /* Directory entry length */
209:      __u16   name_len;       /* Name length */
210:      char    name[EXT2_NAME_LEN]; /* File name */
211:  };
212:
213:  /*
214:   * The new version of the directory entry. Since EXT2 structures are
215:   * stored in intel byte order, and the name_len field could never be
216:   * bigger than 255 chars, it's safe to reclaim the extra byte for the
217:   * file_type field.
218:   */
219:  struct ext2_dir_entry_2 {
220:      __u32   inode;           /* Inode number */
221:      __u16   rec_len;        /* Directory entry length */
222:      __u8    name_len;       /* Name length */
223:      __u8    file_type;
224:      char    name[EXT2_NAME_LEN]; /* File name */
225:  };
226:
227:  /* inode in memory */
228:  struct ext2_i_info {
229:      __u32   i_block[EXT2_N_BLOCKS]; /* Pointers to blocks */
230:  };
231:
232:  #endif /* _FIWIX_FS_EXT2_H */
```


include/fiwix/fs.h

Page 1/4

```

1: /*
2:  * fiwix/include/fiwix/fs.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_FS_H
9: #define _FIWIX_FS_H
10:
11: #include <fiwix/config.h>
12: #include <fiwix/types.h>
13:
14: #define CHECK_UFD(ufd)                                     \
15: {                                                         \
16:     if((ufd) > OPEN_MAX || current->fd[(ufd)] == 0) {   \
17:         return -EBADF;                                   \
18:     }                                                     \
19: }                                                         \
20:
21: struct fd {
22:     struct inode *inode;           /* file inode */
23:     unsigned short int flags;     /* flags */
24:     unsigned short int count;     /* number of opened instances */
25:     __off_t offset;              /* r/w pointer position */
26: };
27:
28: #include <fiwix/statfs.h>
29: #include <fiwix/limits.h>
30: #include <fiwix/process.h>
31: #include <fiwix/dirent.h>
32: #include <fiwix/fs_minix.h>
33: #include <fiwix/fs_ext2.h>
34: #include <fiwix/fs_pipe.h>
35: #include <fiwix/fs_iso9660.h>
36: #include <fiwix/fs_proc.h>
37:
38: #define BPS 512 /* bytes per sector */
39: #define BLKSIZE_1K 1024 /* 1KB block size */
40: #define BLKSIZE_2K 2048 /* 2KB block size */
41: #define SUPERBLOCK 1 /* block 1 is for superblock */
42:
43: #define MAJOR(dev) (((__dev_t) (dev)) >> 8)
44: #define MINOR(dev) (((__dev_t) (dev)) & 0xFF)
45: #define MKDEV(major, minor) (((major) << 8) | (minor))
46:
47: /* filesystem independent mount-flags */
48: #define MS_RDONLY 1 /* mount read-only */
49: #define MS_REMOUNT 32 /* alter flags of a mounted FS */
50:
51: /* old magic mount flag and mask */
52: #define MS_MGC_VAL 0xC0ED0000
53: #define MS_MGC_MSK 0xFFFF0000
54:
55: #define IS_RDONLY_FS(inode) (((inode)->sb) && ((inode)->sb->flags & MS_RDONLY))
56:
57: #define FOLLOW_LINKS 1
58: #define MAX_SYMLINKS 8 /* this prevents infinite loops in symlinks */
59:
60: #define SEEK_SET 0
61: #define SEEK_CUR 1
62: #define SEEK_END 2
63:
64: #define FOR_READING 0
65: #define FOR_WRITING 1
66:
67: #define VERIFY_READ 1

```

include/fiwix/fs.h

Page 2/4

```

68: #define VERIFY_WRITE    2
69:
70: #define SEL_R            1
71: #define SEL_W            2
72: #define SEL_E            4
73:
74: struct inode {
75:     __mode_t            i_mode;        /* file mode */
76:     __uid_t             i_uid;        /* owner uid */
77:     __size_t            i_size;       /* size in bytes */
78:     __u32               i_atime;     /* access time */
79:     __u32               i_ctime;     /* creation time */
80:     __u32               i_mtime;     /* modification time */
81:     __gid_t             i_gid;        /* group id */
82:     __nlink_t           i_nlink;     /* links count */
83:     __blk_t             i_blocks;    /* blocks count */
84:     __u32               i_flags;     /* file flags */
85:     unsigned char       locked;
86:     unsigned char       dirty;       /* 1 = delayed write */
87:     struct inode *mount_point;
88:     __dev_t             dev;
89:     __ino_t             inode;
90:     __s16               count;
91:     __dev_t             rdev;
92:     struct fs_operations *fsop;
93:     struct superblock *sb;
94:     struct inode *prev_hash;
95:     struct inode *next_hash;
96:     struct inode *prev_free;
97:     struct inode *next_free;
98:     union {
99:         struct minix_i_info minix;
100:        struct ext2_i_info ext2;
101:        struct pipefs_inode pipefs;
102:        struct iso9660_inode iso9660;
103:        struct procfs_inode procfs;
104:    } u;
105: };
106: extern struct inode *inode_table;
107: extern struct inode **inode_hash_table;
108: extern int inodes_on_free_list;
109:
110: /* values to be determined during system startup */
111: extern unsigned int inode_table_size;    /* size in bytes */
112: extern unsigned int inode_hash_table_size; /* size in bytes */
113: extern unsigned int fd_table_size;      /* size in bytes */
114:
115: extern struct fd *fd_table;
116:
117: struct superblock {
118:     __dev_t dev;
119:     unsigned char locked;
120:     unsigned char wanted;
121:     struct inode *root;        /* root inode of mounted fs */
122:     struct inode *dir;        /* inode on which the fs was mounted */
123:     unsigned int flags;
124:     unsigned char dirty;     /* 1 = delayed write */
125:     struct fs_operations *fsop;
126:     __u32 s_blocksize;
127:     union {
128:         struct minix_sb_info minix;
129:         struct ext2_super_block ext2;
130:         struct iso9660_sb_info iso9660;
131:     } u;
132: };
133:
134:

```

include/fiwix/fs.h

Page 3/4

```

135: #define FSOP_REQUIRES_DEV      1      /* requires a block device */
136: #define FSOP_KERN_MOUNT        2      /* mounted by kernel */
137:
138: struct fs_operations {
139:     int flags;
140:     int fsdev;                  /* internal filesystem (nodev) */
141:
142: /* file operations */
143:     int (*open)(struct inode *, struct fd *);
144:     int (*close)(struct inode *, struct fd *);
145:     int (*read)(struct inode *, struct fd *, char *, __size_t);
146:     int (*write)(struct inode *, struct fd *, const char *, __size_t);
147:     int (*ioctl)(struct inode *, int, unsigned long int);
148:     int (*lseek)(struct inode *, __off_t);
149:     int (*readdir)(struct inode *, struct fd *, struct dirent *, unsigned in
t);
150:     int (*mmap)(struct inode *, struct vma *);
151:     int (*select)(struct inode *, int);
152:
153: /* inode operations */
154:     int (*readlink)(struct inode *, char *, __size_t);
155:     int (*followlink)(struct inode *, struct inode *, struct inode **);
156:     int (*bmap)(struct inode *, __off_t, int);
157:     int (*lookup)(const char *, struct inode *, struct inode **);
158:     int (*rmdir)(struct inode *, struct inode *);
159:     int (*link)(struct inode *, struct inode *, char *);
160:     int (*unlink)(struct inode *, struct inode *, char *);
161:     int (*symlink)(struct inode *, char *, char *);
162:     int (*mkdir)(struct inode *, char *, __mode_t);
163:     int (*mknod)(struct inode *, char *, __mode_t, __dev_t);
164:     int (*truncate)(struct inode *, __off_t);
165:     int (*create)(struct inode *, char *, __mode_t, struct inode **);
166:     int (*rename)(struct inode *, struct inode *, struct inode *, struct ino
de *, char *, char *);
167:
168: /* block device I/O operations */
169:     int (*read_block)(__dev_t, __blk_t, char *, int);
170:     int (*write_block)(__dev_t, __blk_t, char *, int);
171:
172: /* superblock operations */
173:     int (*read_inode)(struct inode *);
174:     int (*write_inode)(struct inode *);
175:     int (*ialloc)(struct inode *);
176:     void (*ifree)(struct inode *);
177:     void (*statfs)(struct superblock *, struct statfs *);
178:     int (*read_superblock)(__dev_t, struct superblock *);
179:     int (*remount_fs)(struct superblock *, int);
180:     int (*write_superblock)(struct superblock *);
181:     void (*release_superblock)(struct superblock *);
182: };
183:
184: extern struct fs_operations def_chr_fsop;
185: extern struct fs_operations def_blk_fsop;
186:
187: /* fs_minix.h prototypes */
188: extern struct fs_operations minix_fsop;
189: extern struct fs_operations minix_file_fsop;
190: extern struct fs_operations minix_dir_fsop;
191: extern struct fs_operations minix_symlink_fsop;
192: extern int minix_count_free_inodes(struct superblock *);
193: extern int minix_count_free_blocks(struct superblock *);
194: extern int minix_find_first_zero(struct superblock *, __blk_t, int, int);
195: extern int minix_change_bit(int, struct superblock *, int, int);
196: extern void minix_bfree(struct superblock *, int);
197: extern int minix_balloc(struct superblock *);
198:
199: /* fs_ext2.h prototypes */

```

include/fiwix/fs.h

Page 4/4

```

200: extern struct fs_operations ext2_fsop;
201: extern struct fs_operations ext2_file_fsop;
202: extern struct fs_operations ext2_dir_fsop;
203: extern struct fs_operations ext2_symlink_fsop;
204:
205: /* fs_proc.h prototypes */
206: extern struct fs_operations procfs_fsop;
207: extern struct fs_operations procfs_file_fsop;
208: extern struct fs_operations procfs_dir_fsop;
209: extern struct fs_operations procfs_symlink_fsop;
210: struct procfs_dir_entry * get_procfs_by_inode(struct inode *);
211:
212: /* fs_iso9660.h prototypes */
213: extern int isonum_711(char *);
214: extern int isonum_723(char *);
215: extern int isonum_731(char *);
216: extern int isonum_733(char *);
217: extern unsigned long int isodate(char *);
218: extern int iso9660_cleanfilename(char *, int);
219: extern struct fs_operations iso9660_fsop;
220: extern struct fs_operations iso9660_file_fsop;
221: extern struct fs_operations iso9660_dir_fsop;
222: extern struct fs_operations iso9660_symlink_fsop;
223: void check_rrip_inode(struct iso9660_directory_record *, struct inode *);
224: int get_rrip_filename(struct iso9660_directory_record *, struct inode *, char *)
;
225: int get_rrip_symlink(struct inode *, char *);
226:
227:
228: /* generic VFS function prototypes */
229: void inode_lock(struct inode *);
230: void inode_unlock(struct inode *);
231: struct inode * ialloc(struct superblock *);
232: struct inode * iget(struct superblock *, __ino_t);
233: int bmap(struct inode *, __off_t, int);
234: int check_fs_busy(__dev_t, struct inode *);
235: void iput(struct inode *);
236: void sync_inodes(__dev_t);
237: void invalidate_inodes(__dev_t);
238: void inode_init(void);
239:
240: int parse_namei(char *, struct inode *, struct inode **, struct inode **, int);
241: int namei(char *, struct inode **, struct inode **, int);
242:
243: void superblock_lock(struct superblock *);
244: void superblock_unlock(struct superblock *);
245: struct mount * get_free_mount_point(__dev_t);
246: void release_mount_point(struct mount *);
247: struct mount * get_mount_point(struct inode *);
248:
249: int elf_load(struct inode *, char **, char **, struct sigcontext *);
250:
251: int get_new_fd(struct inode *);
252: void release_fd(unsigned int);
253: void fd_init(void);
254:
255: void free_name(const char *);
256: int malloc_name(const char *, char **);
257: int check_user_permission(struct inode *);
258: int check_group(struct inode *);
259: int check_user_area(int, const void *, unsigned int);
260: int check_permission(int, struct inode *);
261:
262: int do_select(int, fd_set *, fd_set *, fd_set *, fd_set *, fd_set *, fd_set *);
263:
264: #endif /* _FIWIX_FS_H */

```

include/fiwix/fs_iso9660.h

Page 1/4

```

1: /*
2:  * fiwix/include/fiwix/fs_iso9660.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_FS_ISO9660_H
9: #define _FIWIX_FS_ISO9660_H
10:
11: #include <fiwix/types.h>
12: #include <fiwix/limits.h>
13:
14: #define ISO9660_SUPERBLOCK      16      /* ISO9660 superblock is in block 16 */
15: #define ISO9660_STANDARD_ID    "CD001" /* standard identification */
16: #define ISO9660_SUPER_MAGIC    0x9660
17:
18: #define ISO9660_VD_BOOT        0
19: #define ISO9660_VD_PRIMARY     1
20: #define ISO9660_VD_SUPPLEMENTARY 2
21: #define ISO9660_VD_PARTITION  3
22: #define ISO9660_VD_END        255
23:
24: #define ISODCL(from, to)      ((to - from) + 1)      /* descriptor length */
25:
26: #define ISO9660_MAX_VD       10      /* maximum number of VD per CDROM */
27:
28: /* inodes will have their directory block and their offset packed as follows:
29:  * 7FF7FF
30:  * \-/\-/\-
31:  * ^ ^
32:  * | +----- offset value          (11bit entries)
33:  * +----- directory block where to find it (11bit entries)
34:  */
35: #define ISO9660_INODE_BITS    11      /* FIXME: it could be greater (16bit) */
36: #define ISO9660_INODE_MASK    0x7FF
37:
38: #define ISO9660_FILE_NOTEXIST  0x01   /* file shouldn't exists for the user */
39: #define ISO9660_FILE_ISDIR     0x02   /* is a directory */
40: #define ISO9660_FILE_ISASSOC   0x04   /* associated file */
41: #define ISO9660_FILE_HASRECFMT 0x08   /* has a record format */
42: #define ISO9660_FILE_HASOWNER  0x10   /* has owner and group defined */
43: #define ISO9660_FILE_RESERVED5 0x20   /* reserved */
44: #define ISO9660_FILE_RESERVED6 0x40   /* reserved */
45: #define ISO9660_FILE_ISMULTIEXT 0x80  /* has more directory records */
46:
47: #define SP_MAGIC1              0xBE
48: #define SP_MAGIC2              0xEF
49: #define GET_SIG(s1, s2)       ((s1 << 8) | s2)
50:
51: #define SL_CURRENT             0x02
52: #define SL_PARENT              0x04
53: #define SL_ROOT                0x08
54:
55: #define TF_CREATION            0x01
56: #define TF_MODIFY              0x02
57: #define TF_ACCESS              0x04
58: #define TF_ATTRIBUTES          0x08
59: #define TF_BACKUP              0x10
60: #define TF_EXPIRATION          0x20
61: #define TF_EFFECTIVE           0x40
62: #define TF_LONG_FORM           0x80
63:
64: #define NM_CONTINUE            0
65: #define NM_CURRENT             1
66: #define NM_PARENT              2
67:

```

include/fiwix/fs_iso9660.h

Page 2/4

```

68: /* formerly Primary Volume Descriptor */
69: struct iso9660_super_block {
70:     char type [ISODCL( 1, 1)]; /* 7.1.1 */
71:     char id [ISODCL( 2, 6)];
72:     char version [ISODCL( 7, 7)]; /* 7.1.1 */
73:     char unused1 [ISODCL( 8, 8)];
74:     char system_id [ISODCL( 9, 40)]; /* a-chars */
75:     char volume_id [ISODCL( 41, 72)]; /* d-chars */
76:     char unused2 [ISODCL( 73, 80)];
77:     char volume_space_size [ISODCL( 81, 88)]; /* 7.3.3 */
78:     char unused3 [ISODCL( 89, 120)];
79:     char volume_set_size [ISODCL(121, 124)]; /* 7.2.3 */
80:     char volume_sequence_number [ISODCL(125, 128)]; /* 7.2.3 */
81:     char logical_block_size [ISODCL(129, 132)]; /* 7.2.3 */
82:     char path_table_size [ISODCL(133, 140)]; /* 7.3.3 */
83:     char type_l_path_table [ISODCL(141, 144)]; /* 7.3.1 */
84:     char opt_type_l_path_table [ISODCL(145, 148)]; /* 7.3.1 */
85:     char type_m_path_table [ISODCL(149, 152)]; /* 7.3.2 */
86:     char opt_type_m_path_table [ISODCL(153, 156)]; /* 7.3.2 */
87:     char root_directory_record [ISODCL(157, 190)]; /* 9.1 */
88:     char volume_set_id [ISODCL(191, 318)]; /* d-chars */
89:     char publisher_id [ISODCL(319, 446)]; /* a-chars */
90:     char preparer_id [ISODCL(447, 574)]; /* a-chars */
91:     char application_id [ISODCL(575, 702)]; /* a-chars */
92:     char copyright_file_id [ISODCL(703, 739)]; /* 7.5 d-chars */
/
93:     char abstract_file_id [ISODCL(740, 776)]; /* 7.5 d-chars */
/
94:     char bibliographic_file_id [ISODCL(777, 813)]; /* 7.5 d-chars */
/
95:     char creation_date [ISODCL(814, 830)]; /* 8.4.26.1 */
96:     char modification_date [ISODCL(831, 847)]; /* 8.4.26.1 */
97:     char expiration_date [ISODCL(848, 864)]; /* 8.4.26.1 */
98:     char effective_date [ISODCL(865, 881)]; /* 8.4.26.1 */
99:     char file_structure_version [ISODCL(882, 882)];
100:    char unused4 [ISODCL(883, 883)];
101:    char application_data [ISODCL(884, 1395)];
102:    char unused5 [ISODCL(1396, 2048)];
103: };
104:
105: struct iso9660_directory_record
106: {
107:     char length [ISODCL( 1, 1)]; /* 7.1.1 */
108:     char ext_attr_length [ISODCL( 2, 2)]; /* 7.1.1 */
109:     char extent [ISODCL( 3, 10)]; /* 7.3.3 */
110:     char size [ISODCL(11, 18)]; /* 7.3.3 */
111:     char date [ISODCL(19, 25)]; /* 7 by 7.1.1 */
112:     char flags [ISODCL(26, 26)];
113:     char file_unit_size [ISODCL(27, 27)]; /* 7.1.1 */
114:     char interleave [ISODCL(28, 28)]; /* 7.1.1 */
115:     char volume_sequence_number [ISODCL(29, 32)]; /* 7.2.3 */
116:     char name_len [ISODCL(33, 33)]; /* 7.1.1 */
117:     char name[0];
118: };
119:
120: struct iso9660_pathtable_record
121: {
122:     char length [ISODCL( 1, 1)]; /* 7.1.1 */
123:     char ext_attr_length [ISODCL( 2, 2)]; /* 7.1.1 */
124:     char extent [ISODCL( 3, 6)]; /* 7.3 */
125:     char parent [ISODCL( 7, 8)]; /* 7.2 */
126:     char name[0];
127: };
128:
129: struct susp_sp {
130:     unsigned char magic[2];
131:     char len_skip;

```

include/fiwix/fs_iso9660.h

Page 3/4

```

132: };
133:
134: struct susp_ce {
135:     char block[8];
136:     char offset[8];
137:     char size[8];
138: };
139:
140: struct susp_er {
141:     char len_id;
142:     char len_des;
143:     char len_src;
144:     char ext_ver;
145:     char data[0];
146: };
147:
148: struct rrip_px {
149:     char mode[8];
150:     char nlink[8];
151:     char uid[8];
152:     char gid[8];
153:     char sn[8];
154: };
155:
156: struct rrip_pn {
157:     char dev_h[8];
158:     char dev_l[8];
159: };
160:
161: struct rrip_sl_component {
162:     unsigned char flags;
163:     unsigned char len;
164:     char name[0];
165: };
166:
167: struct rrip_sl {
168:     unsigned char flags;
169:     struct rrip_sl_component area;
170: };
171:
172: struct rrip_nm {
173:     unsigned char flags;
174:     char name[0];
175: };
176:
177: struct rrip_tf_timestamp {
178:     char time[7];           /* assumes LONG_FORM bit always set to zero */
179: };
180:
181: struct rrip_tf {
182:     char flags;
183:     struct rrip_tf_timestamp times[0];
184: };
185:
186: struct susp_rrip {
187:     char signature[2];
188:     unsigned char len;
189:     unsigned char version;
190:     union {
191:         struct susp_sp sp;
192:         struct susp_ce ce;
193:         struct susp_er er;
194:         struct rrip_px px;
195:         struct rrip_pn pn;
196:         struct rrip_sl sl;
197:         struct rrip_nm nm;
198:         struct rrip_tf tf;

```

include/fiwix/fs_iso9660.h

Page 4/4

```
199:         } u;
200: };
201:
202: struct iso9660_inode {
203:     __blk_t i_extent;
204:     struct inode *i_parent;           /* inode of its parent directory */
205: };
206:
207: struct iso9660_sb_info {
208:     __u32 s_root_inode;
209:     char *pathtable_raw;
210:     struct iso9660_pathtable_record **pathtable;
211:     int paths;
212:     unsigned char rrip;
213:     struct iso9660_super_block *sb;
214: };
215:
216: #endif /* _FIWIX_FS_ISO9660_H */
```


include/fiwix/fs_minix.h

Page 2/2

```

68:         __u16 s_magic;           /* magic number */
69:         __u16 s_state;           /* filesystem state */
70:         __u32 s_zones;          /* number of data zones (for v2 only) */
71:     };
72:
73:     struct minix_inode {
74:         __u16 i_mode;
75:         __u16 i_uid;
76:         __u32 i_size;
77:         __u32 i_time;
78:         __u8 i_gid;
79:         __u8 i_nlinks;
80:         __u16 i_zone[9];
81:     };
82:
83:     struct minix2_inode {
84:         __u16 i_mode;
85:         __u16 i_nlink;
86:         __u16 i_uid;
87:         __u16 i_gid;
88:         __u32 i_size;
89:         __u32 i_atime;
90:         __u32 i_mtime;
91:         __u32 i_ctime;
92:         __u32 i_zone[10];
93:     };
94:
95:     struct minix_dir_entry {
96:         __u16 inode;
97:         char name[0];
98:     };
99:
100: /* super block in memory */
101: struct minix_sb_info {
102:     unsigned char namelen;
103:     unsigned char dirsize;
104:     unsigned short int version;
105:     unsigned int nzones;
106:     struct minix_super_block sb;
107: };
108:
109: /* inode in memory */
110: struct minix_i_info {
111:     union {
112:         __u16 i1_zone[9];
113:         __u32 i2_zone[10];
114:     } u;
115: };
116:
117: int v1_minix_read_inode(struct inode *);
118: int v1_minix_write_inode(struct inode *);
119: int v1_minix_ialloc(struct inode *);
120: void v1_minix_ifree(struct inode *);
121: int v1_minix_bmap(struct inode *, __off_t, int);
122: int v1_minix_truncate(struct inode *, __off_t);
123:
124: int v2_minix_read_inode(struct inode *);
125: int v2_minix_write_inode(struct inode *);
126: int v2_minix_ialloc(struct inode *);
127: void v2_minix_ifree(struct inode *);
128: int v2_minix_bmap(struct inode *, __off_t, int);
129: int v2_minix_truncate(struct inode *, __off_t);
130:
131: #endif /* _FIWIX_FS_MINIX_H */

```

include/fiwix/fs_pipe.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/fs_pipe.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_FS_PIPE_H
9: #define _FIWIX_FS_PIPE_H
10:
11: #define PIPE_DEV          0xFFFF0          /* special device number for nodev fs */
12:
13: extern struct fs_operations pipefs_fsop;
14:
15: struct pipefs_inode {
16:     char *i_data;                /* buffer */
17:     unsigned int i_readoff;      /* offset for reads */
18:     unsigned int i_writeoff;     /* offset for writes */
19:     unsigned int i_readers;      /* number of readers */
20:     unsigned int i_writers;      /* number of writers */
21: };
22:
23: #endif /* _FIWIX_FS_PIPE_H */
```

include/fiwix/fs_proc.h

Page 1/2

```

1: /*
2:  * fiwix/include/fiwix/fs_proc.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_FS_PROC_H
9: #define _FIWIX_FS_PROC_H
10:
11: #include <fiwix/types.h>
12:
13: #define PROC_DEV          0xFFFF1 /* special device number for nodev fs */
14: #define PROC_ROOT_INO    1        /* root inode */
15: #define PROC_SUPER_MAGIC 0x9FA0   /* same as in Linux */
16:
17: #define PROC_PID_INO     0x40000000 /* base for PID inodes */
18: #define PROC_PID_LEV    1         /* array level for PID */
19:
20: #define PROC_ARRAY_ENTRIES 19
21:
22: enum pid_dir_inodes {
23:     PROC_PID_FD = PROC_PID_INO + 1001,
24:     PROC_PID_CMDLINE,
25:     PROC_PID_CWD,
26:     PROC_PID_ENVIRON,
27:     PROC_PID_EXE,
28:     PROC_PID_MAPS,
29:     PROC_PID_MOUNTINFO,
30:     PROC_PID_ROOT,
31:     PROC_PID_STAT,
32:     PROC_PID_STATUS
33: };
34:
35: struct procfs_inode {
36:     unsigned int i_lev; /* array level (directory depth) */
37: };
38:
39: struct procfs_dir_entry {
40:     __ino_t inode;
41:     __mode_t mode;
42:     __nlink_t nlink;
43:     int lev; /* array level (directory depth) */
44:     unsigned short int name_len;
45:     char *name;
46:     int (*data_fn)(char *, __pid_t);
47: };
48:
49: extern struct procfs_dir_entry procfs_array[][PROC_ARRAY_ENTRIES + 1];
50:
51: int data_proc_cmdline(char *, __pid_t);
52: int data_proc_cpuinfo(char *, __pid_t);
53: int data_proc_devices(char *, __pid_t);
54: int data_proc_dma(char *, __pid_t);
55: int data_proc_filesystems(char *, __pid_t);
56: int data_proc_interrupts(char *, __pid_t);
57: int data_proc_loadavg(char *, __pid_t);
58: int data_proc_locks(char *, __pid_t);
59: int data_proc_meminfo(char *, __pid_t);
60: int data_proc_mounts(char *, __pid_t);
61: int data_proc_partitions(char *, __pid_t);
62: int data_proc_rtc(char *, __pid_t);
63: int data_proc_self(char *, __pid_t);
64: int data_proc_stat(char *, __pid_t);
65: int data_proc_uptime(char *, __pid_t);
66: int data_proc_fullversion(char *, __pid_t);
67: int data_proc_domainname(char *, __pid_t);

```

include/fiwix/fs_proc.h

Page 2/2

```
68: int data_proc_filemax(char *, __pid_t);
69: int data_proc_filenr(char *, __pid_t);
70: int data_proc_hostname(char *, __pid_t);
71: int data_proc_inodemax(char *, __pid_t);
72: int data_proc_inodenr(char *, __pid_t);
73: int data_proc_osrelease(char *, __pid_t);
74: int data_proc_ostype(char *, __pid_t);
75: int data_proc_version(char *, __pid_t);
76:
77: /* PID related functions */
78: int data_proc_pid_fd(char *, __pid_t);
79: int data_proc_pid_cmdline(char *, __pid_t);
80: int data_proc_pid_cwd(char *, __pid_t);
81: int data_proc_pid_envIRON(char *, __pid_t);
82: int data_proc_pid_exe(char *, __pid_t);
83: int data_proc_pid_maps(char *, __pid_t);
84: int data_proc_pid_mountinfo(char *, __pid_t);
85: int data_proc_pid_root(char *, __pid_t);
86: int data_proc_pid_stat(char *, __pid_t);
87: int data_proc_pid_status(char *, __pid_t);
88:
89: #endif /* _FIWIX_FS_PROC_H */
```

include/fiwix/i386elf.h

Page 1/5

```

1:  /*
2:  * fiwix/include/fiwix/i386elf.h
3:  */
4:
5:  #ifndef _FIWIX_ELF_H
6:  #define _FIWIX_ELF_H
7:
8:  typedef unsigned long   Elf32_Addr;
9:  typedef unsigned short Elf32_Half;
10: typedef unsigned long   Elf32_Off;
11: typedef long            Elf32_Sword;
12: typedef unsigned long   Elf32_Word;
13:
14: #define ELFMAG0          0x7f          /* EI_MAG */
15: #define ELFMAG1          'E'
16: #define ELFMAG2          'L'
17: #define ELFMAG3          'F'
18: #define ELFMAG           "\177ELF"
19: #define SELFMAG          4
20:
21: #define EI_NIDENT        16
22:
23: typedef struct elf32_hdr{
24:     unsigned char e_ident[EI_NIDENT]; /* ELF "magic number" */
25:     Elf32_Half    e_type;             /* File type */
26:     Elf32_Half    e_machine;          /* Target machine */
27:     Elf32_Word    e_version;          /* File version */
28:     Elf32_Addr    e_entry;            /* Entry point virtual address */
29:     Elf32_Off     e_phoff;            /* Program header table file offset */
30:     Elf32_Off     e_shoff;            /* Section header table file offset */
31:     Elf32_Word    e_flags;            /* File flags */
32:     Elf32_Half    e_ehsize;           /* Sizeof Ehdr (ELF header) */
33:     Elf32_Half    e_phentsize;        /* Sizeof Phdr (Program header) */
34:     Elf32_Half    e_phnum;            /* Number Phdrs (Program header) */
35:     Elf32_Half    e_shentsize;        /* Sizeof Shdr (Section header) */
36:     Elf32_Half    e_shnum;            /* Number Shdrs (Section header) */
37:     Elf32_Half    e_shstrndx;         /* Shdr string index */
38: } Elf32_Ehdr;
39:
40: #define EI_MAG0          0             /* e_ident[] indexes */
41: #define EI_MAG1          1
42: #define EI_MAG2          2
43: #define EI_MAG3          3
44: #define EI_CLASS         4
45: #define EI_DATA          5
46: #define EI_VERSION       6
47: #define EI_PAD           7
48:
49: #define ELFCLASSNONE     0             /* EI_CLASS */
50: #define ELFCLASS32       1
51: #define ELFCLASS64       2
52: #define ELFCLASSNUM      3
53:
54: #define ELFDATANONE      0             /* e_ident[EI_DATA] */
55: #define ELFDATA2LSB      1
56: #define ELFDATA2MSB      2
57: #define ELFDATANUM       3
58:
59: /* ELF file types */
60: #define ET_NONE          0
61: #define ET_REL           1
62: #define ET_EXEC          2
63: #define ET_DYN           3
64: #define ET_CORE          4
65: #define ET_LOPROC        5
66: #define ET_HIPROC        6
67:

```

include/fiwix/i386elf.h

Page 2/5

```

68: #define EM_386      3
69:
70: #define EV_NONE      0          /* e_version, EI_VERSION */
71: #define EV_CURRENT   1
72: #define EV_NUM       2
73:
74: typedef struct elf32_phdr{
75:     Elf32_Word      p_type;      /* Entry type */
76:     Elf32_Off       p_offset;    /* File offset */
77:     Elf32_Addr      p_vaddr;    /* Virtual address */
78:     Elf32_Addr      p_paddr;    /* Physical address */
79:     Elf32_Word      p_filesz;    /* File size */
80:     Elf32_Word      p_memsz;    /* Memory size */
81:     Elf32_Word      p_flags;    /* Entry flags */
82:     Elf32_Word      p_align;    /* Memory & file alignment */
83: } Elf32_Phdr;
84:
85: /* segment types stored in the image headers */
86: #define PT_NULL      0
87: #define PT_LOAD      1
88: #define PT_DYNAMIC   2
89: #define PT_INTERP    3
90: #define PT_NOTE      4
91: #define PT_SHLIB     5
92: #define PT_PHDR      6
93: #define PT_NUM       7
94: #define PT_LOPROC    0x70000000
95: #define PT_HIPROC    0x7fffffff
96:
97: /* permission types on sections in the program header, p_flags. */
98: #define PF_R         0x4
99: #define PF_W         0x2
100: #define PF_X         0x1
101:
102: #define PF_MASKPROC  0xf0000000
103:
104: typedef struct {
105:     Elf32_Word      sh_name;     /* Section name, index in string tbl */
106:     Elf32_Word      sh_type;     /* Type of section */
107:     Elf32_Word      sh_flags;    /* Miscellaneous section attributes */
108:     Elf32_Addr      sh_addr;     /* Section virtual addr at execution */
109:     Elf32_Off       sh_offset;   /* Section file offset */
110:     Elf32_Word      sh_size;     /* Size of section in bytes */
111:     Elf32_Word      sh_link;     /* Index of another section */
112:     Elf32_Word      sh_info;     /* Additional section information */
113:     Elf32_Word      sh_addralign; /* Section alignment */
114:     Elf32_Word      sh_entsize;  /* Entry size if section holds table */
115: } Elf32_Shdr;
116:
117: /* sh_type */
118: #define SHT_NULL      0
119: #define SHT_PROGBITS  1
120: #define SHT_SYMTAB    2
121: #define SHT_STRTAB    3
122: #define SHT_RELA      4
123: #define SHT_HASH      5
124: #define SHT_DYNAMIC   6
125: #define SHT_NOTE      7
126: #define SHT_NOBITS    8
127: #define SHT_REL       9
128: #define SHT_SHLIB     10
129: #define SHT_DYNSYM    11
130: #define SHT_NUM       12
131:
132: #define SHT_LOPROC    0x70000000
133: #define SHT_HIPROC    0x7fffffff
134: #define SHT_LOUSER    0x80000000

```

include/fiwix/i386elf.h

Page 3/5

```

135: #define SHT_HIUSER          0xffffffff
136:
137: /* sh_flags */
138: #define SHF_WRITE           0x1
139: #define SHF_ALLOC           0x2
140: #define SHF_EXECINSTR      0x4
141:
142: /* special section indexes */
143: #define SHN_UNDEF           0
144: #define SHN_LORESERVE      0xff00
145: #define SHN_ABS             0xffff1
146: #define SHN_COMMON         0xffff2
147: #define SHN_HIRESERVE      0xffff
148: #define SHN_LOPROC         0xff00
149: #define SHN_HIPROC         0xffff1f
150:
151: typedef struct elf32_sym{
152:     Elf32_Word    st_name;           /* Symbol name, index in string tbl */
153:     Elf32_Addr    st_value;         /* Value of the symbol */
154:     Elf32_Word    st_size;         /* Associated symbol size */
155:     unsigned char st_info;         /* Type and binding attributes */
156:     unsigned char st_other;        /* No defined meaning, 0 */
157:     Elf32_Half    st_shndx;        /* Associated section index */
158: } Elf32_Sym;
159:
160: #define ELF32_ST_BIND(info)      ((info) >> 4)
161: #define ELF32_ST_TYPE(info)      (((unsigned int) info) & 0xf)
162:
163: /* This info is needed when parsing the symbol table */
164: #define STB_LOCAL              0
165: #define STB_GLOBAL              1
166: #define STB_WEAK                2
167: #define STB_NUM                  3
168:
169: #define STT_NOTYPE              0
170: #define STT_OBJECT              1
171: #define STT_FUNC                2
172: #define STT_SECTION              3
173: #define STT_FILE                4
174: #define STT_NUM                  5
175:
176: typedef struct elf32_rel {
177:     Elf32_Addr    r_offset;         /* Location at which to apply the action */
178:     Elf32_Word    r_info;          /* Index and type of relocation */
179: } Elf32_Rel;
180:
181: typedef struct elf32_rela{
182:     Elf32_Addr    r_offset;         /* Location at which to apply the action */
183:     Elf32_Word    r_info;          /* Index and type of relocation */
184:     Elf32_Sword   r_addend;        /* Constant addend used to compute value */
185: } Elf32_Rela;
186:
187: /* The following are used with relocations */
188: #define ELF32_R_SYM(info)        ((info) >> 8)
189: #define ELF32_R_TYPE(info)       ((info) & 0xff)
190:
191: /* This is the info that is needed to parse the dynamic section of the file */
192: #define DT_NULL                  0
193: #define DT_NEEDED                 1
194: #define DT_PLTRELSZ               2
195: #define DT_PLTGOT                 3
196: #define DT_HASH                   4
197: #define DT_STRTAB                 5
198: #define DT_SYMTAB                 6
199: #define DT_RELA                   7
200: #define DT_RELASZ                 8
201: #define DT_RELAENT                9

```


include/fiwix/i386elf.h

Page 4/5

```

202: #define DT_STRSZ          10
203: #define DT_SYMENT        11
204: #define DT_INIT          12
205: #define DT_FINI          13
206: #define DT_SONAME        14
207: #define DT_RPATH         15
208: #define DT_SYMBOLIC      16
209: #define DT_REL           17
210: #define DT_RELSZ        18
211: #define DT_RELENT       19
212: #define DT_PLTREL       20
213: #define DT_DEBUG        21
214: #define DT_TEXTREL      22
215: #define DT_JMPREL       23
216: #define DT_LOPROC       0x70000000
217: #define DT_HIPROC       0x7fffffff
218:
219: /* Symbolic values for the entries in the auxiliary table
220:    put on the initial stack */
221: #define AT_NULL          0    /* end of vector */
222: #define AT_IGNORE       1    /* entry should be ignored */
223: #define AT_EXECFD       2    /* file descriptor of program */
224: #define AT_PHDR         3    /* program headers for program */
225: #define AT_PHEMT        4    /* size of program header entry */
226: #define AT_PHNUM        5    /* number of program headers */
227: #define AT_PAGESZ       6    /* system page size */
228: #define AT_BASE         7    /* base address of interpreter */
229: #define AT_FLAGS        8    /* flags */
230: #define AT_ENTRY        9    /* entry point of program */
231: #define AT_NOTELF      10    /* program is not ELF */
232: #define AT_UID          11    /* real uid */
233: #define AT_EUID         12    /* effective uid */
234: #define AT_GID          13    /* real gid */
235: #define AT_EGID         14    /* effective gid */
236:
237:
238: typedef struct dynamic{
239:     Elf32_Sword d_tag;          /* entry tabg value */
240:     union{
241:         Elf32_Sword d_val;
242:         Elf32_Addr d_ptr;
243:     } d_un;
244: } Elf32_Dyn;
245:
246: #define R_386_NONE        0
247: #define R_386_32         1
248: #define R_386_PC32       2
249: #define R_386_GOT32      3
250: #define R_386_PLT32      4
251: #define R_386_COPY       5
252: #define R_386_GLOB_DAT   6
253: #define R_386_JMP_SLOT   7
254: #define R_386_RELATIVE   8
255: #define R_386_GOTOFF     9
256: #define R_386_GOTPC     10
257: #define R_386_NUM        11
258:
259: /* Notes used in ET_CORE */
260: #define NT_PRSTATUS      1
261: #define NT_PRFPREG       2
262: #define NT_PRPSINFO      3
263: #define NT_TASKSTRUCT    4
264:
265: /* Note header in a PT_NOTE section */
266: typedef struct elf32_note {
267:     Elf32_Word    n_namesz;    /* Name size */
268:     Elf32_Word    n_descsz;    /* Content size */

```

include/fiwix/i386elf.h

Page 5/5

```
269:   Elf32_Word    n_type;           /* Content type */
270: } Elf32_Nhdr;
271:
272: #define ELF_START_MMAP 0x80000000
273:
274: extern Elf32_Dyn _DYNAMIC [];
275: #define elfhdr      elf32_hdr
276: #define elf_phdr    elf32_phdr
277: #define elf_note    elf32_note
278:
279: #endif /* _FIWIX_ELF_H */
```

include/fiwix/ide_cd.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/ide_cd.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_IDE_CD_H
9: #define _FIWIX_IDE_CD_H
10:
11: #include <fiwix/fs.h>
12:
13: #define IDE_CD_SECTSIZE          BLKSIZE_2K          /* sector size (in bytes) */
14:
15: void ide_cd_timer(unsigned int);
16:
17: int ide_cd_open(struct inode *, struct fd *);
18: int ide_cd_close(struct inode *, struct fd *);
19: int ide_cd_read(__dev_t, __blk_t, char *, int);
20: int ide_cd_ioctl(struct inode *, int, unsigned long int);
21:
22: int ide_cd_init(struct ide *, int);
23:
24: #endif /* _FIWIX_IDE_CD_H */
```

include/fiwix/ide.h

Page 1/5

```

1: /*
2:  * fiwix/include/fiwix/ide.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_IDE_H
9: #define _FIWIX_IDE_H
10:
11: #include <fiwix/fs.h>
12: #include <fiwix/part.h>
13:
14: #define IDE0_IRQ          14      /* primary controller interrupt */
15: #define IDE1_IRQ          15      /* secondary controller interrupt */
16:
17: #define IDE0_MAJOR        3      /* 1st controller major number */
18: #define IDE1_MAJOR        22     /* 2nd controller major number */
19: #define IDE_MINORS        4      /* max. minors/partitions per unit */
20: #define IDE_MASTER_MSF    0      /* IDE master minor shift factor */
21: #define IDE_SLAVE_MSF    6      /* IDE slave minor shift factor */
22:
23: #define IDE_PRIMARY        0
24: #define IDE_SECONDARY     1
25: #define IDE_MASTER        0
26: #define IDE_SLAVE        1
27: #define IDE_ATA           0
28: #define IDE_ATAPI         1
29:
30: #define NR_IDE_CTRL        2      /* IDE controllers */
31: #define NR_IDE_DRVS       2      /* max. drives per IDE controller */
32:
33: /* controller addresses */
34: #define IDE0_BASE         0x1f0   /* primary controller base addr */
35: #define IDE0_CTRL         0x3f4   /* primary controller control port */
36: #define IDE1_BASE         0x170   /* secondary controller base addr */
37: #define IDE1_CTRL         0x374   /* secondary controller control port */
38:
39: #define IDE_BASE_LEN      7      /* controller address length */
40:
41: #define IDE_RDY_RETR_LONG  50000  /* long delay for fast CPUs */
42: #define IDE_RDY_RETR_SHORT 500    /* short delay for slow CPUs */
43: #define MAX_IDE_ERR       10     /* number of retries */
44: #define MAX_CD_ERR        5      /* number of retries in CDRoms */
45:
46: #define SET_IDE_RDY_RETR(retries) \
47:     if((cpu_table.hz / 1000000) <= 100) { \
48:         retries = IDE_RDY_RETR_SHORT; \
49:     } else { \
50:         retries = IDE_RDY_RETR_LONG; \
51:     }
52:
53: #define WAIT_FOR_IDE      (1 * HZ) /* timeout for hard disk */
54: #define WAIT_FOR_CD       (3 * HZ) /* timeout for cdrom */
55:
56: /* controller registers */
57: #define IDE_DATA          0x0     /* Data Port Register (R/W) */
58: #define IDE_ERROR         0x1     /* Error Register (R) */
59: #define IDE_FEATURES     0x1     /* Features Register (W) */
60: #define IDE_SECCNT       0x2     /* Sector Count Register (R/W) */
61: #define IDE_SECNUM       0x3     /* Sector Number Register (R/W) */
62: #define IDE_LCYL         0x4     /* Cylinder Low Register (R/W) */
63: #define IDE_HCYL         0x5     /* Cylinder High Register (R/W) */
64: #define IDE_DRVHD        0x6     /* Drive/Head Register (R/W) */
65: #define IDE_STATUS       0x7     /* Status Register (R) */
66: #define IDE_COMMAND      0x7     /* Command Register (W) */
67:

```

include/fiwix/ide.h

Page 2/5

```

68: #define IDE_ALT_STATUS      0x2      /* Alternate Register (R) */
69: #define IDE_DEV_CTRL        0x2      /* Device Control Register (W) */
70:
71: /* error register bits */
72: #define IDE_ERR_AMNF        0x01     /* Address Mark Not Found */
73: #define IDE_ERR_TK0NF      0x02     /* Track 0 Not Found */
74: #define IDE_ERR_ABRT       0x04     /* Aborted Command */
75: #define IDE_ERR_MCR        0x08     /* Media Change Registered */
76: #define IDE_ERR_IDNF       0x10     /* Sector ID Field Not Found */
77: #define IDE_ERR_MC         0x20     /* Media Changed */
78: #define IDE_ERR_UNC        0x40     /* Uncorrectable Data Error */
79: #define IDE_ERR_BBK        0x80     /* Bad Block */
80:
81: /* status register bits */
82: #define IDE_STAT_ERR        0x01     /* an error occurred */
83: #define IDE_STAT_SENS      0x02     /* sense data available */
84: #define IDE_STAT_CORR      0x04     /* a correctable error occurred */
85: #define IDE_STAT_DRQ       0x08     /* device is ready to transfer */
86: #define IDE_STAT_DSC       0x10     /* device requests service o intr. */
87: #define IDE_STAT_DWF       0x20     /* drive write fault */
88: #define IDE_STAT_RDY       0x40     /* drive is ready */
89: #define IDE_STAT_BSY       0x80     /* drive is busy */
90:
91: #define IDE_CHS_MODE        0xA0     /* select CHS mode */
92: #define IDE_LBA_MODE        0xE0     /* select LBA mode */
93:
94: /* alternate & device control register bits */
95: #define IDE_DEVCTR_DRQ     0x08     /* Data Request */
96: #define IDE_DEVCTR_NIEN    0x02     /* Disable Interrupt */
97: #define IDE_DEVCTR_SRST    0x04     /* Software Reset */
98:
99: /* ATA commands */
100: #define ATA_READ_PIO       0x20     /* read sector(s) with retries */
101: #define ATA_READ_MULTIPLE_PIO 0xC4  /* read multiple sectors */
102: #define ATA_WRITE_PIO      0x30     /* write sector(s) with retries */
103: #define ATA_WRITE_MULTIPLE_PIO 0xC5  /* write multiple sectors */
104: #define ATA_SET_MULTIPLE_MODE 0xC6  /*
105: #define ATA_PACKET         0xA0
106: #define ATA_IDENTIFY_PACKET 0xA1     /* identify ATAPI device */
107: #define ATA_IDENTIFY       0xEC     /* identify ATA device */
108:
109: /* ATAPI commands */
110: #define ATAPI_TEST_UNIT    0x00
111: #define ATAPI_REQUEST_SENSE 0x03
112: #define ATAPI_START_STOP  0x1B
113: #define ATAPI_MEDIUM_REMOVAL 0x1E
114: #define ATAPI_READ10      0x28
115:
116: #define CD_UNLOCK_MEDIUM   0x00     /* allow medium removal */
117: #define CD_LOCK_MEDIUM     0x01     /* prevent medium removal */
118: #define CD_EJECT           0x02     /* eject the CD if possible */
119: #define CD_LOAD            0x03     /* load the CD (closes tray) */
120:
121: /* ATAPI CD additional sense code */
122: #define ASC_NOT_READY      0x04
123: #define ASC_NO_MEDIUM      0x3A
124:
125: /* capabilities */
126: #define IDE_SUPPORTS_CFA   0x848A
127: #define IDE_HAS_DMA        0x100
128: #define IDE_HAS_LBA        0x200
129: #define IDE_MIN_LBA        16514064 /* sectors limit for using CHS */
130:
131: /* general configuration bits */
132: #define IDE_HAS_UDMA       0x04     /* device supports UDMA */
133: #define IDE_REMOVABLE      0x80     /* removable media device */
134:

```

include/fiwix/ide.h

Page 3/5

```

135: /* ATAPI types */
136: #define ATAPI_IS_SEQ_ACCESS      0x01    /* sequential-access device */
137: #define ATAPI_IS_PRINTER        0x02
138: #define ATAPI_IS_PROCESSOR      0x03
139: #define ATAPI_IS_WRITE_ONCE     0x04
140: #define ATAPI_IS_CDROM          0x05
141: #define ATAPI_IS_SCANNER        0x06
142:
143: /* IDE drive flags */
144: #define DEVICE_IS_ATAPI          0x01
145: #define DEVICE_IS_CFA            0x02
146: #define DEVICE_IS_DISK          0x04
147: #define DEVICE_IS_CDROM         0x08
148: #define DEVICE_REQUIRES_LBA     0x10
149: #define DEVICE_HAS_RW_MULTIPLE  0x20
150:
151: /* ATA/ATAPI-4 based */
152: struct ide_drv_ident {
153:     unsigned short int gen_config;      /* general configuration bits */
154:     unsigned short int logic_cyls;     /* logical cylinders */
155:     unsigned short int reserved2;
156:     unsigned short int logic_heads;    /* logical heads */
157:     unsigned short int retired4;
158:     unsigned short int retired5;
159:     unsigned short int logic_spt;     /* logical sectors/track */
160:     unsigned short int retired7;
161:     unsigned short int retired8;
162:     unsigned short int retired9;
163:     char serial_number[20];           /* serial number */
164:     unsigned short int vendor_spec20;
165:     unsigned short int buffer_cache;
166:     unsigned short int vendor_spec22; /* reserved */
167:     char firmware_rev[8];            /* firmware version */
168:     char model_number[40];           /* model number */
169:     unsigned short int rw_multiple;
170:     unsigned short int reserved48;
171:     unsigned short int capabilities;   /* capabilities */
172:     unsigned short int reserved50;
173:     unsigned short int pio_mode;      /* PIO data transfer mode*/
174:     unsigned short int dma_mode;
175:     unsigned short int fields_validity; /* fields validity */
176:     unsigned short int cur_log_cyls;  /* current logical cylinders */
177:     unsigned short int cur_log_heads; /* current logical heads */
178:     unsigned short int cur_log_spt;   /* current logical sectors/track */
179:     unsigned short int cur_capacity;   /* current capacity in sectors */
180:     unsigned short int cur_capacity2; /* 32bit number */
181:     unsigned short int mult_sect_set; /* multiple sector settings */
182:     unsigned short int tot_sectors;   /* sectors (LBA only) */
183:     unsigned short int tot_sectors2; /* 32bit number */
184:     unsigned short int singleword_dma;
185:     unsigned short int multiword_dma; /* multiword DMA settings */
186:     unsigned short int adv_pio_modes; /* advanced PIO modes */
187:     unsigned short int min_multiword; /* min. Multiword DMA transfer */
188:     unsigned short int rec_multiword; /* recommended Multiword DMS tra
nsfer */
189:     unsigned short int min_pio_wo_fc; /* min. PIO w/o flow control */
190:     unsigned short int min_pio_w_fc; /* min. PIO with flow control */
191:     unsigned short int reserved69;
192:     unsigned short int reserved70;
193:     unsigned short int reserved71;
194:     unsigned short int reserved72;
195:     unsigned short int reserved73;
196:     unsigned short int reserved74;
197:     unsigned short int queue_depth;   /* queue depth */

```

include/fiwix/ide.h

Page 4/5

```

198:         unsigned short int reserved76;
199:         unsigned short int reserved77;
200:         unsigned short int reserved78;
201:         unsigned short int reserved79;
202:         unsigned short int majorver;           /* major version number */
203:         unsigned short int minorver;          /* minor version number */
204:         unsigned short int cmdset1;           /* command set supported */
205:         unsigned short int cmdset2;           /* command set supported */
206:         unsigned short int cmdsf_ext;         /* command set/feature sup.ext.
*/
207:         unsigned short int cmdsf_enable1;     /* command s/f enabled */
208:         unsigned short int cmdsf_enable2;     /* command s/f enabled */
209:         unsigned short int cmdsf_default;     /* command s/f default */
210:         unsigned short int ultradma;         /* ultra DMA mode */
211:         unsigned short int reserved89;
212:         unsigned short int reserved90;
213:         unsigned short int curapm;           /* current APM values */
214:         unsigned short int reserved92_126[35];
215:         unsigned short int r_status_notif;    /* removable media status notif.
*/
216:         unsigned short int security_status;   /* security status */
217:         unsigned short int vendor_spec129_159[31];
218:         unsigned short int reserved160_255[96];
219:     };
220:
221:     struct ide_drv {
222:         int drive;                            /* master or slave */
223:         char *dev_name;
224:         unsigned char major;                  /* major number */
225:         unsigned int flags;
226:         int minor_shift;                     /* shift factor to get the real minor */
227:         int lba_cyls;
228:         int lba_heads;
229:         short int lba_factor;
230:         unsigned int nr_sects;               /* total sectors (LBA) */
231:         struct fs_operations *fsop;
232:         struct ide_drv_ident ident;
233:         struct partition part_table[NR_PARTITIONS];
234:     };
235:
236:     struct ide {
237:         int channel;                          /* primary or secondary */
238:         int base;                             /* base address */
239:         int ctrl;                             /* control port address */
240:         short int irq;
241:         struct ide_drv drive[NR_IDE_DRVS];
242:     };
243:
244:     extern struct ide ide_table[NR_IDE_CTRLs];
245:
246:     extern int ide0_need_reset;
247:     extern int ide0_wait_interrupt;
248:     extern int ide0_timeout;
249:     extern int idel_need_reset;
250:     extern int idel_wait_interrupt;
251:     extern int idel_timeout;
252:
253:     void irq_ide0(void);
254:     void ide0_timer(unsigned int);
255:     void irq_idel(void);
256:     void idel_timer(unsigned int);
257:
258:     void ide_error(struct ide *, int);
259:     void ide_delay(void);
260:     void ide_wait400ns(struct ide *);
261:     int ide_ready(struct ide *);
262:     int ide_drvsel(struct ide *, int, int, unsigned char);

```

include/fiwix/ide.h

Page 5/5

```
263: int ide_softreset(struct ide *);
264:
265: struct ide * get_ide_controller(__dev_t);
266: int get_ide_drive(__dev_t);
267:
268: int ide_open(struct inode *, struct fd *);
269: int ide_close(struct inode *, struct fd *);
270: int ide_read(__dev_t, __blk_t, char *, int);
271: int ide_write(__dev_t, __blk_t, char *, int);
272: int ide_ioctl(struct inode *, int, unsigned long int);
273:
274: void ide_init(void);
275:
276: #endif /* _FIWIX_IDE_H */
```


include/fiwix/ide_hd.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/ide_hd.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_IDE_HD_H
9: #define _FIWIX_IDE_HD_H
10:
11: #include <fiwix/types.h>
12:
13: #define IDE_HD_SECTSIZE          512      /* sector size (in bytes) */
14:
15: int ide_hd_open(struct inode *, struct fd *);
16: int ide_hd_close(struct inode *, struct fd *);
17: int ide_hd_read(__dev_t, __blk_t, char *, int);
18: int ide_hd_write(__dev_t, __blk_t, char *, int);
19: int ide_hd_ioctl(struct inode *, int, unsigned long int);
20:
21: int ide_hd_init(struct ide *, int);
22:
23: #endif /* _FIWIX_IDE_HD_H */
```

include/fiwix/ioctl.h

Page 1/2

```

1: /*
2:  * fiwix/include/fiwix/ioctl.h
3:  */
4:
5: #ifndef _FIWIX_IOCTL_H
6: #define _FIWIX_IOCTL_H
7:
8: #define HDIO_GETGEO      0x0301          /* get device geometry */
9:
10: #define BLKRRPART       0x125F          /* re-read partition table */
11: #define BLKGETSIZE      0x1260          /* return device size */
12: #define BLKFLSBUF       0x1261          /* flush buffer cache */
13:
14: /* 0x54 is just a magic number to make these relatively unique ('T') */
15: #define TCGETS          0x5401
16: #define TCSETS          0x5402
17: #define TCSETSW         0x5403
18: #define TCSETSF         0x5404
19: #define TCGETA          0x5405
20: #define TCSETA          0x5406
21: #define TCSETAW         0x5407
22: #define TCSETAF         0x5408
23: #define TCSBRK          0x5409
24: #define TCXONC          0x540A
25: #define TCFLSH          0x540B
26: #define TIOCEXCL        0x540C
27: #define TIOCNXCL        0x540D
28: #define TIOCSCTTY       0x540E
29: #define TIOCGPGRP       0x540F
30: #define TIOCSPPGRP      0x5410
31: #define TIOCOUTQ        0x5411
32: #define TIOCSTI         0x5412
33: #define TIOCGWINSZ      0x5413
34: #define TIOCSWINSZ      0x5414
35: #define TIOCMGET        0x5415
36: #define TIOCMBIS        0x5416
37: #define TIOCMBIC        0x5417
38: #define TIOCMSET        0x5418
39: #define TIOCGSOFTCAR    0x5419
40: #define TIOCSSOFTCAR    0x541A
41: #define FIONREAD        0x541B
42: #define TIOCINQ          FIONREAD
43: #define TIOCLINUX       0x541C
44: #define TIOCCONS        0x541D
45: #define TIOCGSERIAL     0x541E
46: #define TIOCSSERIAL     0x541F
47: #define TIOCPKT         0x5420
48: #define FIONBIO         0x5421
49: #define TIOCNOTTY       0x5422
50: #define TIOCSETD        0x5423
51: #define TIOCGETD        0x5424
52: #define TCSBRKP         0x5425          /* Needed for POSIX tcsendbreak() */
53: #define TIOCTTYGSTRUCT  0x5426          /* For debugging only */
54: #define TIOCSBRK        0x5427          /* BSD compatibility */
55: #define TIOCCBRK        0x5428          /* BSD compatibility */
56: #define TIOCGSID        0x5429          /* Return the session ID of FD */
57: #define TIOCGPTN        _IOR('T',0x30, unsigned int) /* Get Pty Number (of pty-m
ux device) */
58: #define TIOCSPTLCK      _IOW('T',0x31, int) /* Lock/unlock Pty */
59:
60: #define FIONCLEX        0x5450          /* these numbers need to be adjusted. */
61: #define FIOCLEX         0x5451
62: #define FIOASYNC        0x5452
63: #define TIOCSERCONFIG   0x5453
64: #define TIOCSERGWILD    0x5454
65: #define TIOCSERSWILD    0x5455
66: #define TIOCGLCCKTRMIOS 0x5456

```

include/fiwix/ioctl.h

Page 2/2

```
67: #define TIOCSLCKTRMIOS 0x5457
68: #define TIOCSESGSTRUCT 0x5458 /* For debugging only */
69: #define TIOCSEGETLSR 0x5459 /* Get line status register */
70: #define TIOCSEGETMULTI 0x545A /* Get multiport config */
71: #define TIOCSESETMULTI 0x545B /* Set multiport config */
72:
73: #define TIOCMWAIT 0x545C /* wait for a change on serial input line(s) */
74: #define TIOCGICOUNT 0x545D /* read serial port inline interrupt counts */
75: #define TIOCGHAYESES 0x545E /* Get Hayes ESP configuration */
76: #define TIOCSHAYESES 0x545F /* Set Hayes ESP configuration */
77:
78: /* Used for packet mode */
79: #define TIOCPKT_DATA 0
80: #define TIOCPKT_FLUSHREAD 1
81: #define TIOCPKT_FLUSHWRITE 2
82: #define TIOCPKT_STOP 4
83: #define TIOCPKT_START 8
84: #define TIOCPKT_NOSTOP 16
85: #define TIOCPKT_DOSTOP 32
86:
87: #define TIOCSERT 0x01 /* Transmitter physically empty */
88:
89: #endif /* _FIWIX_IOCTL_H */
```

include/fiwix/kd.h

Page 1/3

```

1: /*
2:  * fiwix/include/fiwix/kd.h
3:  */
4:
5: #ifndef _LINUX_KD_H
6: #define _LINUX_KD_H
7:
8: /* Prefix 0x4B is 'K', to avoid collision with termios and vt */
9:
10: #define GIO_FONT          0x4B60 /* gets font in expanded form */
11: #define PIO_FONT          0x4B61 /* use font in expanded form */
12:
13: #define GIO_FONTX         0x4B6B /* get font using struct consolefontdesc */
14: #define PIO_FONTX         0x4B6C /* set font using struct consolefontdesc */
15: struct consolefontdesc {
16:     unsigned short int charcount; /* characters in font (256 or 512) */
17:     unsigned short int charheight; /* scan lines per character (1-32) */
18:     char *chardata; /* font data in expanded form */
19: };
20:
21: #define PIO_FONTRESET     0x4B6D /* reset to default font */
22:
23: #define GIO_CMAP          0x4B70 /* gets colour palette on VGA+ */
24: #define PIO_CMAP          0x4B71 /* sets colour palette on VGA+ */
25:
26: #define KIOCSOUND         0x4B2F /* start sound generation (0 for off) */
27: #define KDMKTONE         0x4B30 /* generate tone */
28:
29: #define KDGETLED          0x4B31 /* return current led state */
30: #define KDSETLED          0x4B32 /* set led state [lights, not flags] */
31: #define LED_SCR           0x01 /* scroll lock led */
32: #define LED_NUM           0x02 /* num lock led */
33: #define LED_CAP           0x04 /* caps lock led */
34:
35: #define KDGBKTYPE         0x4B33 /* get keyboard type */
36: #define KB_84             0x01
37: #define KB_101            0x02 /* this is what we always answer */
38: #define KB_OTHER          0x03
39:
40: #define KDADDIO           0x4B34 /* add i/o port as valid */
41: #define KDDELIO           0x4B35 /* del i/o port as valid */
42: #define KDENABIO         0x4B36 /* enable i/o to video board */
43: #define KDDISABIO        0x4B37 /* disable i/o to video board */
44:
45: #define KDSETMODE         0x4B3A /* set text/graphics mode */
46: #define KD_TEXT           0x00
47: #define KD_GRAPHICS       0x01
48: #define KD_TEXT0          0x02 /* obsolete */
49: #define KD_TEXT1          0x03 /* obsolete */
50: #define KDGETMODE         0x4B3B /* get current mode */
51:
52: #define KDMAPDISP         0x4B3C /* map display into address space */
53: #define KDUNMAPDISP       0x4B3D /* unmap display from address space */
54:
55: typedef char scrnmap_t;
56: #define E_TABSZ           256
57: #define GIO_SCRNMAP       0x4B40 /* get screen mapping from kernel */
58: #define PIO_SCRNMAP       0x4B41 /* put screen mapping table in kernel */
59: #define GIO_UNISCRNMAP    0x4B69 /* get full Unicode screen mapping */
60: #define PIO_UNISCRNMAP    0x4B6A /* set full Unicode screen mapping */
61:
62: #define GIO_UNIMAP        0x4B66 /* get unicode-to-font mapping from kernel */
63: struct unipair {
64:     unsigned short int unicode;
65:     unsigned short int fontpos;
66: };
67: struct unimapdesc {

```

include/fiwix/kd.h

Page 2/3

```

68:         unsigned short int entry_ct;
69:         struct unipair *entries;
70: };
71: #define PIO_UNIMAP      0x4B67 /* put unicode-to-font mapping in kernel */
72: #define PIO_UNIMAPCLR  0x4B68 /* clear table, possibly advise hash algorithm */
/
73: struct unimapinit {
74:     unsigned short int advised_hashsize; /* 0 if no opinion */
75:     unsigned short int advised_hashstep; /* 0 if no opinion */
76:     unsigned short int advised_hashlevel; /* 0 if no opinion */
77: };
78:
79: #define UNI_DIRECT_BASE 0xF000 /* start of Direct Font Region */
80: #define UNI_DIRECT_MASK 0x01FF /* Direct Font Region bitmask */
81:
82: #define K_RAW          0x00
83: #define K_XLATE        0x01
84: #define K_MEDIUMRAW   0x02
85: #define K_UNICODE      0x03
86: #define KDGBKMODE     0x4B44 /* gets current keyboard mode */
87: #define KDSKMODE      0x4B45 /* sets current keyboard mode */
88:
89: #define K_METABIT     0x03
90: #define K_ESCPREFIX   0x04
91: #define KDGBKMETA     0x4B62 /* gets meta key handling mode */
92: #define KDSKBMETA     0x4B63 /* sets meta key handling mode */
93:
94: #define K_SCROLLLOCK  0x01
95: #define K_NUMLOCK     0x02
96: #define K_CAPSLOCK    0x04
97: #define KDGBKLED      0x4B64 /* get led flags (not lights) */
98: #define KDSKLED       0x4B65 /* set led flags (not lights) */
99:
100: struct kentry {
101:     unsigned char kb_table;
102:     unsigned char kb_index;
103:     unsigned short int kb_value;
104: };
105: #define K_NORMTAB      0x00
106: #define K_SHIFTTAB    0x01
107: #define K_ALTTAB      0x02
108: #define K_ALTSHIFTTAB 0x03
109:
110: #define KDGBKENT      0x4B46 /* gets one entry in translation table */
111: #define KDSKENT       0x4B47 /* sets one entry in translation table */
112:
113: struct kbsentry {
114:     unsigned char kb_func;
115:     unsigned char kb_string[512];
116: };
117: #define KDGBKSENT     0x4B48 /* gets one function key string entry */
118: #define KDSKSENT      0x4B49 /* sets one function key string entry */
119:
120: struct kbdiacr {
121:     unsigned char diacr, base, result;
122: };
123: struct kbdiacrs {
124:     unsigned int kb_cnt; /* number of entries in following array */
125:     struct kbdiacr kbdiacr[256]; /* MAX_DIACR from keyboard.h */
126: };
127: #define KDGBKDIACR    0x4B4A /* read kernel accent table */
128: #define KDSKDIACR     0x4B4B /* write kernel accent table */
129:
130: struct kbkeycode {
131:     unsigned int scancode, keycode;
132: };
133: #define KDGETKEYCODE  0x4B4C /* read kernel keycode table entry */

```

include/fiwix/kd.h

Page 3/3

```

134: #define KDSETKEYCODE    0x4B4D /* write kernel keycode table entry */
135:
136: #define KDSIGACCEPT     0x4B4E /* accept kbd generated signals */
137:
138: struct kbd_repeat {
139:     int delay;          /* in msec; <= 0: don't change */
140:     int rate;           /* in msec; <= 0: don't change */
141: };
142:
143: #define KDKBDREP        0x4B52 /* set keyboard delay/repeat rate;
144:                                * actually used values are returned */
145:
146: #define KDFONTOP        0x4B72 /* font operations */
147:
148: struct console_font_op {
149:     unsigned int op;    /* operation code KD_FONT_OP_* */
150:     unsigned int flags; /* KD_FONT_FLAG_* */
151:     unsigned int width, height; /* font size */
152:     unsigned int charcount;
153:     unsigned char *data; /* font data with height fixed to 32 */
154: };
155:
156: #define KD_FONT_OP_SET      0 /* Set font */
157: #define KD_FONT_OP_GET      1 /* Get font */
158: #define KD_FONT_OP_SET_DEFAULT 2 /* Set font to default, data points to name / NULL */
159: #define KD_FONT_OP_COPY    3 /* Copy from another console */
160:
161: #define KD_FONT_FLAG_DONT_RECALC 1 /* Don't recalculate hw charcell size [compat] */
162:
163: /* note: 0x4B00-0x4B4E all have had a value at some time;
164:    don't reuse for the time being */
165: /* note: 0x4B60-0x4B6D, 0x4B70-0x4B72 used above */
166:
167: #endif /* _LINUX_KD_H */

```

include/fiwix/kernel.h

Page 1/2

```

1: /*
2:  * fiwix/include/fiwix/kernel.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_KERNEL_H
9: #define _FIWIX_KERNEL_H
10:
11: #include <fiwix/limits.h>
12: #include <fiwix/i386elf.h>
13:
14: #define PANIC(format, args...)                                \
15: {                                                            \
16:     printk("\nPANIC: in %s()", __FUNCTION__);                \
17:     printk("\n");                                           \
18:     printk(format, ## args);                                \
19:     stop_kernel();                                         \
20: }
21:
22: #define CURRENT_TIME      (kstat.system_time)
23: #define INIT_PROGRAM      "/sbin/init"
24:
25: extern char *init_argv[];
26: extern char *init_envp[];
27:
28: extern Elf32_Shdr *symtab, *strtab;
29: extern unsigned int _last_data_addr;
30:
31: extern int _memsize;
32: extern int _extmemsize;
33: extern int _rootdev;
34: extern int _noramdisk;
35: extern int _ramdisksize;
36: extern char _rootfstype[10];
37: extern char _rootdevname[DEVNAME_MAX + 1];
38: extern int _syscondev;
39:
40: extern int _cputype;
41: extern int _cpusignature;
42: extern int _cpuflags;
43: extern int _brandid;
44: extern char _vendorid[12];
45: extern char _brandstr[48];
46: extern unsigned int _tlbinfo_eax;
47: extern unsigned int _tlbinfo_ebx;
48: extern unsigned int _tlbinfo_ecx;
49: extern unsigned int _tlbinfo_edx;
50: extern char _etext[], _edata[], _end[];
51:
52: extern char cmdline[NAME_MAX + 1];
53:
54: struct kernel_stat {
55:     unsigned int cpu_user;           /* ticks in user-mode */
56:     unsigned int cpu_nice;          /* ticks in user-mode (with priority) */
57:     unsigned int cpu_system;        /* ticks in kernel-mode */
58:     unsigned int irqs;              /* irq counter */
59:     unsigned int sirqs;             /* spurious irq counter */
60:     unsigned int ctxt;              /* context switches */
61:     unsigned int ticks;             /* ticks (1/HZths of sec) since boot */
62:     unsigned int system_time;       /* current system time (since the Epoch) */
63:
64:     unsigned int boot_time;         /* boot time (since the Epoch) */
65:     int tz_minuteswest;             /* minutes west of GMT */
66:     int tz_dsttime;                /* type of DST correction */
67:     unsigned int uptime;            /* seconds since boot */

```

include/fiwix/kernel.h

Page 2/2

```
67:         unsigned int processes;          /* number of forks since boot */
68:         unsigned int physical_pages;     /* physical memory in pages */
69:         unsigned int kernel_reserved;    /* kernel memory reserved in KB */
70:         unsigned int physical_reserved;  /* physical memory reserved in KB */
71:         unsigned int total_mem_pages;    /* total memory in pages */
72:         unsigned int free_pages;         /* pages on free list (available) */
73:         unsigned int buffers;           /* memory used by buffers in KB */
74:         unsigned int cached;            /* memory used to cache file pages */
75:         unsigned int shared;            /* pages with count > 1 */
76:     };
77: extern struct kernel_stat kstat;
78:
79: unsigned int get_last_elf_addr(unsigned int);
80: void start_kernel(unsigned long, unsigned long, unsigned int);
81: void stop_kernel(void);
82: void init_init(void);
83: void cpu_idle(void);
84:
85: #endif /* _FIWIX_KERNEL_H */
```


include/fiwix/keyboard.h

Page 1/2

```

1: /*
2:  * fiwix/include/fiwix/keyboard.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #include <fiwix/types.h>
9:
10: #ifndef _FIWIX_KEYBOARD_H
11: #define _FIWIX_KEYBOARD_H
12:
13: #define KEYBOARD_IRQ    1
14:
15: #define NR_MODIFIERS    16      /* max. number of modifiers per keymap */
16: #define NR_SCODES      128     /* max. number of scancodes */
17: #define NR_DIACR       10
18:
19: #define SCRLBIT        0x01    /* scroll lock led */
20: #define NUMSBIT       0x02    /* num lock led */
21: #define CAPSBIT       0x04    /* caps lock led */
22:
23: #define C(ch)          ((ch) & 0x1F)
24: #define A(ch)          ((ch) | META_KEYS)
25: #define L(ch)          ((ch) | LETTER_KEYS)
26:
27: #define SLASH_NPAD     53
28:
29: #define MOD_BASE       0
30: #define MOD_SHIFT     1
31: #define MOD_ALTGR     2
32: #define MOD_CTRL      3
33: #define MOD_ALT       4
34: #define MOD_SHIFTL    5
35: #define MOD_SHIFTR    6
36: #define MOD_CTRLL    7
37: #define MOD_CTRLR    8
38:
39: #define FN_KEYS        0x100
40: #define SPEC_KEYS     0x200
41: #define PAD_KEYS      0x300
42: #define DEAD_KEYS     0x400
43: #define CONS_KEYS     0x500
44: #define SHIFT_KEYS   0x700
45: #define META_KEYS     0x800
46: #define LETTER_KEYS   0xB00
47:
48: #define CR              (0x01 + SPEC_KEYS)
49: #define SCRL2          (0x02 + SPEC_KEYS)      /* SH_REGS (show registers) */
50: #define SCRL3          (0x03 + SPEC_KEYS)      /* SH_MEM (show memory) */
51: #define SCRL4          (0x04 + SPEC_KEYS)      /* SH_STAT (show status) */
52: #define CAPS           (0x07 + SPEC_KEYS)
53: #define NUMS           (0x08 + SPEC_KEYS)
54: #define SCRL           (0x09 + SPEC_KEYS)
55:
56: #define INS            (0x00 + PAD_KEYS)
57: #define END            (0x01 + PAD_KEYS)
58: #define DOWN          (0x02 + PAD_KEYS)
59: #define PGDN          (0x03 + PAD_KEYS)
60: #define LEFT          (0x04 + PAD_KEYS)
61: #define MID           (0x05 + PAD_KEYS)
62: #define RIGHT         (0x06 + PAD_KEYS)
63: #define HOME          (0x07 + PAD_KEYS)
64: #define UP            (0x08 + PAD_KEYS)
65: #define PGUP          (0x09 + PAD_KEYS)
66: #define PLUS          (0x0A + PAD_KEYS)
67: #define MINUS         (0x0B + PAD_KEYS)

```

include/fiwix/keyboard.h

Page 2/2

```

68: #define ASTSK          (0x0C + PAD_KEYS)
69: #define SLASH          (0x0D + PAD_KEYS)
70: #define ENTER          (0x0E + PAD_KEYS)
71: #define DEL            (0x10 + PAD_KEYS)
72:
73: #define GRAVE          (0x00 + DEAD_KEYS)
74: #define ACUTE          (0x01 + DEAD_KEYS)
75: #define CIRCUM          (0x02 + DEAD_KEYS)
76: #define DIERE          (0x04 + DEAD_KEYS)
77:
78: #define SHIFT          (0x00 + SHIFT_KEYS)
79: #define ALTGR          (0x01 + SHIFT_KEYS)
80: #define CTRL           (0x02 + SHIFT_KEYS)
81: #define ALT            (0x03 + SHIFT_KEYS)
82:
83: #define F1             (0x00 + FN_KEYS)
84: #define F2             (0x01 + FN_KEYS)
85: #define F3             (0x02 + FN_KEYS)
86: #define F4             (0x03 + FN_KEYS)
87: #define F5             (0x04 + FN_KEYS)
88: #define F6             (0x05 + FN_KEYS)
89: #define F7             (0x06 + FN_KEYS)
90: #define F8             (0x07 + FN_KEYS)
91: #define F9             (0x08 + FN_KEYS)
92: #define F10            (0x09 + FN_KEYS)
93: #define F11            (0x0A + FN_KEYS)
94: #define F12            (0x0B + FN_KEYS)
95:
96: #define SF1            (0x0A + FN_KEYS)
97: #define SF2            (0x0B + FN_KEYS)
98: #define SF3            (0x0C + FN_KEYS)
99: #define SF4            (0x0D + FN_KEYS)
100: #define SF5            (0x0E + FN_KEYS)
101: #define SF6            (0x0F + FN_KEYS)
102: #define SF7            (0x10 + FN_KEYS)
103: #define SF8            (0x11 + FN_KEYS)
104: #define SF9            (0x12 + FN_KEYS)
105: #define SF10           (0x13 + FN_KEYS)
106: #define SF11           (0x0A + SHIFT)
107: #define SF12           (0x0B + SHIFT)
108:
109: #define AF1            (0x00 + CONS_KEYS)
110: #define AF2            (0x01 + CONS_KEYS)
111: #define AF3            (0x02 + CONS_KEYS)
112: #define AF4            (0x03 + CONS_KEYS)
113: #define AF5            (0x04 + CONS_KEYS)
114: #define AF6            (0x05 + CONS_KEYS)
115: #define AF7            (0x06 + CONS_KEYS)
116: #define AF8            (0x07 + CONS_KEYS)
117: #define AF9            (0x08 + CONS_KEYS)
118: #define AF10           (0x09 + CONS_KEYS)
119: #define AF11           (0x0A + CONS_KEYS)
120: #define AF12           (0x0B + CONS_KEYS)
121:
122: struct diacritic {
123:     unsigned char letter;
124:     unsigned char code;
125: };
126:
127: extern __key_t keymap[NR_MODIFIERS * NR_SCODES];
128:
129: void set_leds(unsigned char);
130: void irq_keyboard(void);
131: void keyboard_bh(void);
132: void keyboard_init(void);
133:
134: #endif /* _FIWIX_KEYBOARD_H */

```

include/fiwix/kparms.h

Page 1/1

```

1: /*
2:  * fiwix/include/fiwix/kparms.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_KPARMS_H
9: #define _FIWIX_KPARMS_H
10:
11: #define CMDL_ARG_LEN 25 /* max length of cmdline argument */
12: #define CMDL_NUM_VALUES 30 /* max values of cmdline parameter */
13:
14: struct kparms {
15:     char *name;
16:     char *value[CMDL_NUM_VALUES];
17:     unsigned int sysval[CMDL_NUM_VALUES];
18: };
19:
20: static struct kparms parm_table[] = {
21:     { "root=",
22:       { "/dev/fd0", "/dev/fd1",
23:         "/dev/hda", "/dev/hda1", "/dev/hda2", "/dev/hda3", "/dev/hda4",
24:         "/dev/hdb", "/dev/hdb1", "/dev/hdb2", "/dev/hdb3", "/dev/hdb4",
25:         "/dev/hdc", "/dev/hdc1", "/dev/hdc2", "/dev/hdc3", "/dev/hdc4",
26:         "/dev/hdd", "/dev/hdd1", "/dev/hdd2", "/dev/hdd3", "/dev/hdd4" },
27:       { 0x200, 0x201,
28:         0x300, 0x301, 0x302, 0x303, 0x304,
29:         0x340, 0x341, 0x342, 0x343, 0x344,
30:         0x1600, 0x1601, 0x1602, 0x1603, 0x1604,
31:         0x1640, 0x1641, 0x1642, 0x1643, 0x1644 }
32:     },
33:     { "noramdisk",
34:       { NULL },
35:       { NULL },
36:     },
37:     { "ramdisksize=",
38:       { NULL },
39:       { NULL },
40:     },
41:     { "rootfstype=",
42:       { "minix", "ext2", "iso9660" },
43:       { 0, 0 }
44:     },
45:     { "console=",
46:       { "/dev/tty1", "/dev/tty2", "/dev/tty3", "/dev/tty4", "/dev/tty5",
47:         "/dev/tty6", "/dev/tty7", "/dev/tty8", "/dev/tty9", "/dev/tty10",
48:         "/dev/tty11", "/dev/tty12" },
49:       { 0x401, 0x402, 0x403, 0x404, 0x405,
50:         0x406, 0x407, 0x408, 0x409, 0x410,
51:         0x411, 0x412 }
52:     },
53:     { NULL }
54: };
55: };
56:
57: #endif /* _FIWIX_KPARMS_H */

```

include/fiwix/limits.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/limits.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_LIMITS_H
9: #define _FIWIX_LIMITS_H
10:
11: #define DEVNAME_MAX      25      /* device name length in mount table */
12: #define ARG_MAX          32      /* length (in pages) of argv+env in 'execve' */
13: #define CHILD_MAX       64      /* simultaneous processes per real user ID */
14: #define LINK_MAX        255     /* maximum number of links to a file */
15: #define MAX_CANON       255     /* bytes in a terminal canonical input queue */
16: #define MAX_INPUT       255     /* bytes for which space will be available in a
17:                                terminal input queue */
18: #define NGROUPS_MAX     32      /* simultaneous supplementary group IDs */
19: #define OPEN_MAX        256     /* files one process can have opened at once */
20: #define FD_SETSIZE     OPEN_MAX /* descriptors that a process may examine with
21:                                'pselect' or 'select' */
22: #define NAME_MAX        255     /* bytes in a filename */
23: #define PATH_MAX        1024    /* bytes in a pathname */
24: #define PIPE_BUF        4096    /* bytes than can be written atomically to a
25:                                pipe */
26:
27: #endif /* _FIWIX_LIMITS_H */
```

include/fiwix/locks.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/locks.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_LOCKS_H
9: #define _FIWIX_LOCKS_H
10:
11: #include <fiwix/config.h>
12: #include <fiwix/fs.h>
13: #include <fiwix/fcntl.h>
14:
15: struct flock_file {
16:     struct inode *inode;    /* file */
17:     unsigned char type;    /* type of lock */
18:     struct proc *proc;     /* owner */
19: };
20:
21: struct flock_file flock_file_table[NR_FLOCKS];
22:
23: int posix_lock(int, int, struct flock *);
24:
25: void flock_release_inode(struct inode *);
26: int flock_inode(struct inode *, int);
27: void flock_init(void);
28:
29: #endif /* _FIWIX_LOCKS_H */
```

include/fiwix/lp.h

Page 1/1

```

1: /*
2:  * fiwix/include/fiwix/lp.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_LP_H
9: #define _FIWIX_LP_H
10:
11: #include <fiwix/fs.h>
12:
13: #define LP_MAJOR          6          /* major number for /dev/lp[n] */
14: #define LP_MINORS        1
15:
16: /*#define LP0_ADDR        0x3BC */
17: #define LP0_ADDR          0x378
18: /*#define LP2_ADDR        0x278 */
19:
20: #define LP_STAT_ERR      0x08      /* printer error */
21: #define LP_STAT_SEL      0x10      /* select in */
22: #define LP_STAT_PE       0x20      /* paper empty or no paper */
23: #define LP_STAT_ACK      0x40      /* ack */
24: #define LP_STAT_BUS      0x80      /* printer busy */
25:
26: #define LP_CTRL_STR       0x01      /* strobe */
27: #define LP_CTRL_AUT       0x02      /* auto line feed */
28: #define LP_CTRL_INI       0x04      /* initialize printer (reset) */
29: #define LP_CTRL_SEL       0x08      /* select printer */
30: #define LP_CTRL_IRQ       0x10      /* enable IRQ */
31: #define LP_CTRL_BID       0x20      /* bidireccional (on PS/2 ports) */
32:
33: #define LP_RDY_RETR       100      /* retries before timeout */
34:
35: struct lp {
36:     int data;             /* data port address */
37:     int stat;             /* status port address */
38:     int ctrl;            /* control port address */
39:     char flags;          /* flags */
40: };
41:
42: int lp_open(struct inode *, struct fd *);
43: int lp_close(struct inode *, struct fd *);
44: int lp_write(struct inode *, struct fd *, const char *, __size_t);
45:
46: void lp_init(void);
47:
48: #endif /* _FIWIX_LP_H */

```

include/fiwix/memdev.h

Page 1/1

```

1: /*
2:  * fiwix/include/fiwix/memdev.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_MEMDEV_H
9: #define _FIWIX_MEMDEV_H
10:
11: #include <fiwix/fs.h>
12:
13: #define MEMDEV_MAJOR    1      /* major number */
14: #define MEMDEV_MINORS  5      /* number of supported minors */
15:
16: #define MEMDEV_MEM      1      /* minor for /dev/mem */
17: #define MEMDEV_KMEM     2      /* minor for /dev/kmem */
18: #define MEMDEV_NULL     3      /* minor for /dev/null */
19: #define MEMDEV_ZERO     5      /* minor for /dev/zero */
20:
21: int mem_open(struct inode *, struct fd *);
22: int mem_close(struct inode *, struct fd *);
23: int mem_read(struct inode *, struct fd *, char *, __size_t);
24: int mem_write(struct inode *, struct fd *, const char *, __size_t);
25: int mem_lseek(struct inode *, __off_t);
26:
27: int kmem_open(struct inode *, struct fd *);
28: int kmem_close(struct inode *, struct fd *);
29: int kmem_read(struct inode *, struct fd *, char *, __size_t);
30: int kmem_write(struct inode *, struct fd *, const char *, __size_t);
31: int kmem_lseek(struct inode *, __off_t);
32:
33: int null_open(struct inode *, struct fd *);
34: int null_close(struct inode *, struct fd *);
35: int null_read(struct inode *, struct fd *, char *, __size_t);
36: int null_write(struct inode *, struct fd *, const char *, __size_t);
37: int null_lseek(struct inode *, __off_t);
38:
39: int zero_open(struct inode *, struct fd *);
40: int zero_close(struct inode *, struct fd *);
41: int zero_read(struct inode *, struct fd *, char *, __size_t);
42: int zero_write(struct inode *, struct fd *, const char *, __size_t);
43: int zero_lseek(struct inode *, __off_t);
44:
45: int memdev_open(struct inode *, struct fd *);
46: int mem_mmap(struct inode *, struct vma *);
47: void memdev_init(void);
48:
49: #endif /* _FIWIX_MEMDEV_H */

```

include/fiwix/mman.h

Page 1/1

```

1: /*
2:  * fiwix/include/fiwix/mman.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_MMAN_H
9: #define _FIWIX_MMAN_H
10:
11: #include <fiwix/fs.h>
12:
13: #define PROT_READ          0x1          /* page can be read */
14: #define PROT_WRITE        0x2          /* page can be written */
15: #define PROT_EXEC         0x4          /* page can be executed */
16: #define PROT_NONE         0x0          /* page cannot be accessed */
17:
18: #define MAP_SHARED        0x01         /* share changes */
19: #define MAP_PRIVATE       0x02         /* changes are private */
20: #define MAP_TYPE          0x0f         /* mask for type of mapping */
21: #define MAP_FIXED         0x10         /* interpret address exactly */
22: #define MAP_ANONYMOUS     0x20         /* don't use the file descriptor */
23:
24: #define MAP_GROWSDOWN     0x0100       /* stack-like segment */
25: #define MAP_DENYWRITE     0x0800       /* -ETXTBSY */
26: #define MAP_EXECUTABLE    0x1000       /* mark it as a executable */
27: #define MAP_LOCKED        0x2000       /* pages are locked */
28:
29: #define ZERO_PAGE         0x80000000    /* this page must be zero-filled */
30:
31: #define MS_ASYNC          1            /* sync memory asynchronously */
32: #define MS_INVALIDATE    2            /* invalidate the caches */
33: #define MS_SYNC           4            /* synchronous memory sync */
34:
35: #define MCL_CURRENT       1            /* lock all current mappings */
36: #define MCL_FUTURE       2            /* lock all future mappings */
37:
38: /* compatibility flags */
39: #define MAP_ANON          MAP_ANONYMOUS
40: #define MAP_FILE          0
41:
42: struct mmap {
43:     unsigned int start;
44:     unsigned int length;
45:     unsigned int prot;
46:     unsigned int flags;
47:     int fd;
48:     unsigned int offset;
49: };
50:
51: void show_vma_regions(struct proc *);
52: void release_binary(void);
53: struct vma * find_vma_region(unsigned int);
54: int expand_heap(unsigned int);
55: int do_mmap(struct inode *, unsigned int, unsigned int, unsigned int, unsigned i
nt, unsigned int, char, char);
56: int do_munmap(unsigned int, __size_t);
57: int do_mprotect(struct vma *, unsigned int, __size_t, int);
58:
59: #endif /* _FIWIX_MMAN_H */

```


include/fiwix/mm.h

Page 1/2

```

1: /*
2:  * fiwix/include/fiwix/mm.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_MEMORY_H
9: #define _FIWIX_MEMORY_H
10:
11: #include <fiwix/types.h>
12: #include <fiwix/const.h>
13: #include <fiwix/process.h>
14:
15: #define P2V(addr)                (addr + KERNEL_BASE_ADDR)
16: #define V2P(addr)                (addr - KERNEL_BASE_ADDR)
17:
18: #define PAGE_SIZE                4096
19: #define PAGE_SHIFT               0x0C
20: #define PAGE_MASK                ~(PAGE_SIZE - 1)          /* 0xFFFFF000 */
21: #define PAGE_ALIGN(addr)        (((addr) + (PAGE_SIZE - 1)) & PAGE_MASK)
22: #define PT_ENTRIES               (PAGE_SIZE / sizeof(unsigned int))
23: #define PD_ENTRIES               (PAGE_SIZE / sizeof(unsigned int))
24:
25: #define PAGE_PRESENT              0x001    /* Present */
26: #define PAGE_RW                  0x002    /* Read/Write */
27: #define PAGE_USER                 0x004    /* User */
28:
29: #define PAGE_RESERVED            0x100    /* kernel, BIOS address, ... */
30: #define PAGE_COW                 0x200    /* marked for Copy-On-Write */
31:
32: #define PFAULT_V                 0x01    /* protection violation */
33: #define PFAULT_W                 0x02    /* during write */
34: #define PFAULT_U                 0x04    /* in user mode */
35:
36: #define GET_PGDIR(address)       ((unsigned int)((address) >> 22) & 0x3FF)
37: #define GET_PGTBL(address)       ((unsigned int)((address) >> 12) & 0x3FF)
38:
39: #define P_TEXT    1    /* text section */
40: #define P_DATA    2    /* data section */
41: #define P_BSS     3    /* BSS section */
42: #define P_HEAP   4    /* heap section (sys_brk()) */
43: #define P_STACK  5    /* stack section */
44: #define P_MMAP   6    /* mmap() section */
45:
46: struct page {
47:     unsigned int page;    /* page number */
48:     unsigned int count;  /* usage counter */
49:     unsigned int flags;
50:     unsigned char locked; /* 1 = locked */
51:     struct inode *inode;
52:     __off_t offset;    /* file offset */
53:     char *data;        /* page contents */
54:     struct page *prev_hash;
55:     struct page *next_hash;
56:     struct page *prev_free;
57:     struct page *next_free;
58: };
59:
60: extern struct page *page_table;
61: extern struct page **page_hash_table;
62:
63: /* values to be determined during system startup */
64: extern unsigned int page_table_size;    /* size in bytes */
65: extern unsigned int page_hash_table_size; /* size in bytes */
66:
67: extern unsigned int *kpage_dir;

```

include/fiwix/mm.h

Page 2/2

```
68: extern unsigned int *kpage_table;
69:
70: /* alloc.c */
71: unsigned int kmalloc(void);
72: void kfree(unsigned int);
73:
74: /* page.c */
75: void page_lock(struct page *);
76: void page_unlock(struct page *);
77: struct page * get_free_page(void);
78: struct page * search_page_hash(struct inode *, __off_t);
79: void release_page(unsigned int);
80: int valid_page(unsigned int);
81: void update_page_cache(struct inode *, __off_t, const char *, int);
82: int write_page(struct page *, struct inode *, __off_t, unsigned int);
83: int bread_page(struct page *, struct inode *, __off_t, char, char);
84: int file_read(struct inode *, struct fd *, char *, __size_t);
85: void page_init(unsigned int);
86:
87: /* memory.c */
88: void bss_init(void);
89: unsigned int setup_minmem(void);
90: unsigned int get_mapped_addr(struct proc *, unsigned int);
91: int clone_pages(struct proc *);
92: int free_page_tables(struct proc *);
93: unsigned int map_page(struct proc *, unsigned int, unsigned int, unsigned int);
94: int unmap_page(unsigned int);
95: void mem_init(void);
96: void mem_stats(void);
97:
98: /* swapper.c */
99: int kswapd(void);
100:
101: #endif /* _FIWIX_MEMORY_H */
```

include/fiwix/multiboot.h

Page 1/2

```

1:  /* multiboot.h - the header for Multiboot */
2:  /* Copyright (C) 1999, 2001 Free Software Foundation, Inc.
3:
4:  This program is free software; you can redistribute it and/or modify
5:  it under the terms of the GNU General Public License as published by
6:  the Free Software Foundation; either version 2 of the License, or
7:  (at your option) any later version.
8:
9:  This program is distributed in the hope that it will be useful,
10: but WITHOUT ANY WARRANTY; without even the implied warranty of
11: MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
12: GNU General Public License for more details.
13:
14: You should have received a copy of the GNU General Public License
15: along with this program; if not, write to the Free Software
16: Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA. */
17:
18: /* Macros. */
19:
20: #ifndef _FIWIX_MULTIBOOT_H
21: #define _FIWIX_MULTIBOOT_H
22:
23: /* The magic number for the Multiboot header. */
24: #define MULTIBOOT_HEADER_MAGIC      0x1BADB002
25:
26: /* The flags for the Multiboot header. */
27: #ifdef __ELF__
28: # define MULTIBOOT_HEADER_FLAGS    0x00000003
29: #else
30: # define MULTIBOOT_HEADER_FLAGS    0x00010003
31: #endif
32:
33: /* The magic number passed by a Multiboot-compliant boot loader. */
34: #define MULTIBOOT_BOOTLOADER_MAGIC  0x2BADB002
35:
36: /* The size of our stack (16KB). */
37: #define STACK_SIZE                   0x4000
38:
39: /* C symbol format. HAVE_ASM_USCORE is defined by configure. */
40: #ifdef HAVE_ASM_USCORE
41: # define EXT_C(sym)                  _ ## sym
42: #else
43: # define EXT_C(sym)                  sym
44: #endif
45:
46: #ifndef ASM
47: /* Do not include here in boot.S. */
48:
49: /* Types. */
50:
51: /* The Multiboot header. */
52: typedef struct multiboot_header
53: {
54:     unsigned long magic;
55:     unsigned long flags;
56:     unsigned long checksum;
57:     unsigned long header_addr;
58:     unsigned long load_addr;
59:     unsigned long load_end_addr;
60:     unsigned long bss_end_addr;
61:     unsigned long entry_addr;
62: } multiboot_header_t;
63:
64: /* The symbol table for a.out. */
65: typedef struct aout_symbol_table
66: {
67:     unsigned long tabsize;

```

include/fiwix/multiboot.h

Page 2/2

```

68:  unsigned long strsize;
69:  unsigned long addr;
70:  unsigned long reserved;
71: } aout_symbol_table_t;
72:
73: /* The section header table for ELF. */
74: typedef struct elf_section_header_table
75: {
76:  unsigned long num;
77:  unsigned long size;
78:  unsigned long addr;
79:  unsigned long shndx;
80: } elf_section_header_table_t;
81:
82: /* The Multiboot information. */
83: typedef struct multiboot_info
84: {
85:  unsigned long flags;
86:  unsigned long mem_lower;
87:  unsigned long mem_upper;
88:  unsigned long boot_device;
89:  unsigned long cmdline;
90:  unsigned long mods_count;
91:  unsigned long mods_addr;
92:  union
93:  {
94:    aout_symbol_table_t aout_sym;
95:    elf_section_header_table_t elf_sec;
96:  } u;
97:  unsigned long mmap_length;
98:  unsigned long mmap_addr;
99: } multiboot_info_t;
100:
101: /* The module structure. */
102: typedef struct module
103: {
104:  unsigned long mod_start;
105:  unsigned long mod_end;
106:  unsigned long string;
107:  unsigned long reserved;
108: } module_t;
109:
110: /* The memory map. Be careful that the offset 0 is base_addr_low
111:    but no size. */
112: typedef struct memory_map
113: {
114:  unsigned long size;
115:  unsigned long base_addr_low;
116:  unsigned long base_addr_high;
117:  unsigned long length_low;
118:  unsigned long length_high;
119:  unsigned long type;
120: } memory_map_t;
121:
122: #endif /* ! ASM */
123:
124: #endif /* _FIWIX_MULTIBOOT_H */

```

include/fiwix/part.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/part.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_PART_H
9: #define _FIWIX_PART_H
10:
11: #define PARTITION_BLOCK          0
12: #define NR_PARTITIONS           4      /* partitions in the MBR */
13: #define MBR_CODE_SIZE           446
14: #define ACTIVE_PART             0x80
15:
16: struct hd_geometry {
17:     unsigned char heads;
18:     unsigned char sectors;
19:     unsigned short int cylinders;
20:     unsigned long int start;
21: };
22:
23: struct partition {
24:     unsigned char status;
25:     unsigned char head;
26:     unsigned char sector;
27:     unsigned char cyl;
28:     unsigned char type;
29:     unsigned char endhead;
30:     unsigned char endsector;
31:     unsigned char endcyl;
32:     unsigned int startsect;
33:     unsigned int nr_sects;
34: };
35:
36: int read_msdos_partition(__dev_t, struct partition *);
37:
38: #endif /* _FIWIX_PART_H */
```

include/fiwix/pic.h

Page 1/1

```

1: /*
2:  * fiwix/include/fiwix/pic.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_PIC_H
9: #define _FIWIX_PIC_H
10:
11: #include <fiwix/sigcontext.h>
12:
13: #define NR_IRQS          16          /* hardware interrupts */
14: #define PIC_MASTER      0x20        /* I/O base address for master PIC */
15: #define PIC_SLAVE       0xA0        /* I/O base address for slave PIC */
16:
17: #define DATA           0x01        /* offset to data port */
18: #define EOI             0x20        /* End-Of-Interrupt command code */
19:
20: /* Inicialization Command Words */
21: #define ICW1_RESET      0x11        /* ICW1_INIT + ICW1_ICW4 */
22: #define CASCADE_IRQ     0x02
23: #define ICW4_8086EOI    0x01
24:
25: #define PIC_READ_IRR    0x0A        /* OCW3 irq ready */
26: #define PIC_READ_ISR    0x0B        /* OCW3 irq service */
27:
28: /* Operational Command Words */
29: #define OCW1            0xFF        /* mask (disable) all IRQs */
30:
31: struct interrupts {
32:     unsigned int ticks;
33:     char *name;
34:     char registered;
35:     void (*handler)(void *);
36: };
37: struct interrupts irq_table[NR_IRQS];
38:
39: struct bh {
40:     void (*fn)(void);
41:     struct bh *next;
42: };
43:
44: void add_bh(void (*fn)(void));
45: void del_bh(void);
46: void enable_irq(int);
47: void disable_irq(int);
48: int register_irq(int, char *, void *);
49: int unregister_irq(int);
50: void irq_handler(int, struct sigcontext);
51: void do_bh(void);
52: void pic_init(void);
53:
54: #endif /* _FIWIX_PIC_H */

```

include/fiwix/pit.h

Page 1/1

```

1: /*
2:  * fiwix/include/fiwix/pit.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_PIT_H
9: #define _FIWIX_PIT_H
10:
11: /* Intel 8253/82c54 Programmable Interval Timer */
12:
13: #define OSCIL          1193182 /* oscillator frequency */
14:
15: #define MODEREG        0x43 /* mode/command register (w) */
16: #define CHANNEL0       0x40 /* channel 0 data port (rw) */
17: #define CHANNEL1       0x41 /* channel 1 data port (rw) */
18: #define CHANNEL2       0x42 /* channel 2 data port (rw) */
19:
20: #define BINARY_CTR     0x00 /* 16bit binary mode counter */
21: #define TERM_COUNT     0x00 /* mode 0 (Terminal Count) */
22: #define RATE_GEN       0x04 /* mode 2 (Rate Generator) */
23: #define SQUARE_WAVE   0x06 /* mode 3 (Square Wave) */
24: #define LSB_MSB        0x30 /* LSB then MSB */
25: #define SEL_CHAN0      0x00 /* select channel 0 */
26: #define SEL_CHAN2      0x80 /* select channel 2 */
27:
28: /*
29:  * PS/2 System Control Port B
30:  * -----
31:  * bit 7 -> IRQ=1, 0=reset
32:  * bit 6 -> reserved
33:  * bit 5 -> reserved
34:  * bit 4 -> reserved
35:  * bit 3 -> channel check enable
36:  * bit 2 -> parity check enable
37:  * bit 1 -> speaker data enable
38:  * bit 0 -> timer 2 gate to speaker enable
39:  */
40: #define PS2_SYSCTRL_B  0x61 /* PS/2 system control port B (write) */
41:
42: #define ENABLE_TMR2G   0x01 /* timer 2 gate to speaker enable */
43: #define ENABLE_SDATA   0x02 /* speaker data enable */
44:
45: #define BEEP_FREQ      900 /* 900Hz */
46:
47: void pit_beep_on(void);
48: void pit_beep_off(unsigned int);
49: void pit_init(unsigned short int);
50:
51: #endif /* _FIWIX_PIT_H */

```

include/fiwix/process.h

Page 1/3

```

1: /*
2:  * fiwix/include/fiwix/process.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_PROCESS_H
9: #define _FIWIX_PROCESS_H
10:
11: struct vma {
12:     unsigned int start;
13:     unsigned int end;
14:     char prot; /* PROT_READ, PROT_WRITE, ... */
15:     unsigned int flags; /* MAP_SHARED, MAP_PRIVATE, ... */
16:     unsigned int offset;
17:     char s_type; /* section type (P_TEXT, P_DATA, ...) */
18:     struct inode *inode; /* file inode */
19:     char o_mode; /* open mode (O_RDONLY, O_RDWR, ...) */
20: };
21:
22: #include <fiwix/types.h>
23: #include <fiwix/signal.h>
24: #include <fiwix/limits.h>
25: #include <fiwix/sigcontext.h>
26: #include <fiwix/time.h>
27: #include <fiwix/resource.h>
28: #include <fiwix/tty.h>
29:
30: #define IDLE 0 /* PID of idle */
31: #define INIT 1 /* PID of /sbin/init */
32: #define SAFE_SLOTS 2 /* process slots reserved for root */
33: #define SLOT(p) ((p) - (&proc_table[0]))
34:
35: /* bits in flags */
36: #define PF_KPROC 0x00000001 /* kernel internal process */
37: #define PF_PEEXEC 0x00000002 /* has performed a sys_execve() */
38: #define PF_USEREAL 0x00000004 /* use real UID in permission checks */
39:
40: #define MMAP_START 0x40000000 /* mmap()'s start at 1GB */
41: #define IS_SUPERUSER (current->euid == 0)
42:
43: #define IO_BITMAP_SIZE 32 /* 32 * 32bit = 1024 = 0x3FF */
44: /* 2048 * 32bit = 65536 = 0xFFFF */
45:
46: #define VMA_REGIONS (PAGE_SIZE / sizeof(struct vma))
47:
48: #define PG_LEADER(p) ((p)->pid == (p)->pgid)
49: #define SESS_LEADER(p) ((p)->pid == (p)->pgid && (p)->pid == (p)->sid)
50:
51: #define FOR_EACH_PROCESS(p) for(p = &proc_table[INIT]; p; p = p->next)
52:
53: /* value to be determined during system startup */
54: extern unsigned int proc_table_size; /* size in bytes */
55:
56: extern char any_key_to_reboot;
57: extern int nr_processes;
58: extern __pid_t lastpid;
59:
60: struct binargs {
61:     unsigned int page[ARG_MAX];
62:     int argc;
63:     int argv_len;
64:     int envc;
65:     int envp_len;
66:     int offset;
67: };

```


include/fiwix/process.h

Page 2/3

```

68:
69:  /* Intel 386 Task Switch State */
70:  struct i386tss {
71:      unsigned int prev_tss;
72:      unsigned int esp0;
73:      unsigned int ss0;
74:      unsigned int esp1;
75:      unsigned int ss1;
76:      unsigned int esp2;
77:      unsigned int ss2;
78:      unsigned int cr3;
79:      unsigned int eip;
80:      unsigned int eflags;
81:      unsigned int eax;
82:      unsigned int ecx;
83:      unsigned int edx;
84:      unsigned int ebx;
85:      unsigned int esp;
86:      unsigned int ebp;
87:      unsigned int esi;
88:      unsigned int edi;
89:      unsigned int es;
90:      unsigned int cs;
91:      unsigned int ss;
92:      unsigned int ds;
93:      unsigned int fs;
94:      unsigned int gs;
95:      unsigned int ldt;
96:      unsigned short int debug_trap;
97:      unsigned short int io_bitmap_addr;
98:  };
99:
100: struct proc {
101:     struct i386tss tss;
102:     unsigned int io_bitmap[IO_BITMAP_SIZE + 1];
103:     __pid_t pid; /* process ID */
104:     __pid_t ppid; /* parent process ID */
105:     __pid_t pgid; /* process group ID */
106:     __pid_t sid; /* session ID */
107:     int flags;
108:     int groups[NGROUPS_MAX];
109:     int children; /* number of children */
110:     struct tty *ctty; /* controlling terminal */
111:     int state; /* process state */
112:     int priority;
113:     int cpu_count; /* time of process running */
114:     __time_t start_time;
115:     int exit_code;
116:     void *sleep_address;
117:     unsigned short int uid; /* real user ID */
118:     unsigned short int gid; /* real group ID */
119:     unsigned short int euid; /* effective user ID */
120:     unsigned short int egid; /* effective group ID */
121:     unsigned short int suid; /* saved user ID */
122:     unsigned short int sgid; /* saved group ID */
123:     unsigned short int fd[OPEN_MAX];
124:     unsigned char fd_flags[OPEN_MAX];
125:     struct inode *root;
126:     struct inode *pwd; /* process working directory */
127:     unsigned int entry_address;
128:     char argv0[NAME_MAX + 1];
129:     char **argv;
130:     char **envp;
131:     char pidstr[5]; /* pid number converted to string */
132:     struct vma *vma; /* virtual memory-map addresses */
133:     unsigned int brk_lower; /* lower limit of the heap section */
134:     unsigned int brk; /* current limit of the heap */

```

include/fiwix/process.h

Page 3/3

```

135:     __sigset_t sigpending;
136:     __sigset_t sigblocked;
137:     __sigset_t sigexecuting;
138:     struct sigaction sigaction[NSIG];
139:     struct sigcontext sc[NSIG];      /* each signal has its own context */
140:     unsigned int sp;                /* current process' stack frame */
141:     struct rusage usage;            /* process resource usage */
142:     struct rusage cusage;          /* children resource usage */
143:     unsigned long int it_real_interval, it_real_value;
144:     unsigned long int it_virt_interval, it_virt_value;
145:     unsigned long int it_prof_interval, it_prof_value;
146:     unsigned long int timeout;
147:     struct rlimit rlim[RLIM_NLIMITS];
148:     unsigned long int rss;
149:     __mode_t umask;
150:     unsigned char loopcnt;          /* nested symlinks counter */
151:     struct proc *prev;
152:     struct proc *next;
153:     struct proc *sleep_prev;
154:     struct proc *sleep_next;
155: };
156:
157: extern struct proc *current;
158: extern struct proc *proc_table;
159:
160: int send_sig(struct proc *, __sigset_t);
161: int kill_pid(__pid_t, __sigset_t);
162: int kill_pgrp(__pid_t, __sigset_t);
163: void add_crusage(struct proc *, struct rusage *);
164: void get_rusage(struct proc *, struct rusage *);
165: void add_rusage(struct proc *);
166: struct proc * get_next_zombie(struct proc *);
167: __pid_t remove_zombie(struct proc *);
168: int is_orphaned_pgrp(__pid_t);
169: struct proc * get_proc_free(void);
170: void release_proc(struct proc *);
171: int get_unused_pid(void);
172: struct proc * get_proc_by_pid(__pid_t);
173:
174: int get_new_user_fd(int);
175: void release_user_fd(int);
176:
177: struct proc * kernel_process(int (*fn)(void));
178: void proc_slot_init(struct proc *);
179: void proc_init(void);
180:
181: #endif /* _FIWIX_PROCESS_H */

```

include/fiwix/ramdisk.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/ramdisk.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_RAMDISK_H
9: #define _FIWIX_RAMDISK_H
10:
11: #include <fiwix/fs.h>
12:
13: #define RAMDISK_MAJOR 1      /* ramdisk device major number */
14: #define RAMDISK_MINORS 1    /* number of minors */
15: #define RAMDISK_SIZE 4096   /* default ramdisk size in KBs */
16: #define RAMDISK_MAXSIZE 131072 /* maximum ramdisk size in KBs */
17:
18: struct ramdisk {
19:     char *addr;             /* ramdisk memory address */
20: };
21:
22: extern struct ramdisk ramdisk_table[RAMDISK_MINORS];
23:
24: int ramdisk_open(struct inode *, struct fd *);
25: int ramdisk_close(struct inode *, struct fd *);
26: int ramdisk_read(__dev_t, __blk_t, char *, int);
27: int ramdisk_write(__dev_t, __blk_t, char *, int);
28: int ramdisk_ioctl(struct inode *, int, unsigned long int);
29: int ramdisk_lseek(struct inode *, __off_t);
30:
31: void ramdisk_init(void);
32:
33: #endif /* _FIWIX_RAMDISK_H */
```

include/fiwix/reboot.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/reboot.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_REBOOT_H
9: #define _FIWIX_REBOOT_H
10:
11: #define BMAGIC_HARD      0x89ABCDEF
12: #define BMAGIC_SOFT     0
13: #define BMAGIC_REBOOT   0x01234567
14: #define BMAGIC_HALT     0xCDEF0123
15: #define BMAGIC_POWEROFF 0x4321FEDC
16:
17: #define BMAGIC_1        0xFEE1DEAD
18: #define BMAGIC_2        672274793
19:
20: extern char ctrl_alt_del;
21: void reboot(void);
22:
23: #endif /* _FIWIX_REBOOT_H */
```

include/fiwix/resource.h

Page 1/2

```

1: /*
2:  * fiwix/include/fiwix/resource.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_RESOURCE_H
9: #define _FIWIX_RESOURCE_H
10:
11: #include <fiwix/time.h>
12:
13: #define RLIMIT_INFINITY 0x7FFFFFFF /* value to indicate "no limit" */
14: #define RLIM_INFINITY RLIMIT_INFINITY /* traditional name */
15:
16: #define RUSAGE_SELF 0 /* the calling process */
17: #define RUSAGE_CHILDREN (-1) /* all of its termin. child processes */
18:
19: #define RLIMIT_CPU 0 /* per-process CPU limit (secs) */
20: #define RLIMIT_FSIZE 1 /* largest file that can be created
21: (bytes) */
22: #define RLIMIT_DATA 2 /* maximum size of data segment
23: (bytes) */
24: #define RLIMIT_STACK 3 /* maximum size of stack segment
25: (bytes) */
26: #define RLIMIT_CORE 4 /* largest core file that can be created
27: (bytes) */
28: #define RLIMIT_RSS 5 /* largest resident set size (bytes) */
29: #define RLIMIT_NPROC 6 /* number of processes */
30: #define RLIMIT_NOFILE 7 /* number of open files */
31: #define RLIMIT_MEMLOCK 8 /* locked-in-memory address space */
32: #define RLIMIT_AS 9 /* address space limit */
33:
34: #define RLIM_NLIMITS 10
35:
36: struct rusage {
37:     struct timeval ru_utime; /* total amount of user time used */
38:     struct timeval ru_stime; /* total amount of system time used */
39:     long ru_maxrss; /* maximum resident set size (KB) */
40:     long ru_ixrss; /* amount of sharing of text segment
41: memory with other processes
42: (KB-secs) */
43:     long ru_idrss; /* amount of data segment memory used
44: (KB-secs) */
45:     long ru_isrss; /* amount of stack memory used
46: (KB-secs) */
47:     long ru_minflt; /* number of soft page faults (i.e.
48: those serviced by reclaiming a page
49: from the list of pages awaiting
50: relocation) */
51:     long ru_majflt; /* number of hard page faults (i.e.
52: those that required I/O) */
53:     long ru_nswap; /* number of times a process was swapped
54: out of physical memory */
55:     long ru_inblock; /* number of input operations via the
56: file system. Note this and
57: 'ru_outblock' do not include
58: operations with the cache */
59:     long ru_oublock; /* number of output operations via the
60: file system */
61:     long ru_msgsnd; /* number of IPC messages sent */
62:     long ru_msrvcv; /* number of IPC messages received */
63:     long ru_nsignals; /* number of signals delivered */
64:     long ru_nvcsw; /* number of voluntary context switches,
65: i.e. because the process gave up the
66: process before it had to (usually to
67: wait for some resource to be

```

include/fiwix/resource.h

Page 2/2

```
68:                                     availabe */
69:         long ru_nivcsw;                /* number of involuntary context
70:                                     switches. i.e. a higher priority
71:                                     process became runnable or the
72:                                     current process used up its time
73:                                     slice */
74: };
75:
76: struct rlimit {
77:     int rlim_cur;                       /* the current (soft) limit */
78:     int rlim_max;                       /* the maximum (hard) limit */
79: };
80:
81: #endif /* _FIWIX_RESOURCE_H */
```

include/fiwix/sched.h

Page 1/1

```

1: /*
2:  * fiwix/include/fiwix/sched.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_SCHED_H
9: #define _FIWIX_SCHED_H
10:
11: #include <fiwix/process.h>
12:
13: #define PRIO_PROCESS    0
14: #define PRIO_PGRP      1
15: #define PRIO_USER      2
16:
17: #define PROC_UNUSED    0
18: #define PROC_RUNNING   1
19: #define PROC_SLEEPING  2
20: #define PROC_ZOMBIE    3
21: #define PROC_STOPPED   4
22: #define PROC_IDLE      5
23:
24: #define PROC_INTERRUPTIBLE    1
25: #define PROC_UNINTERRUPTIBLE  2
26:
27: #define DEF_PRIORITY    (20 * HZ / 100) /* 200ms of time slice */
28:
29: extern int need_resched;
30:
31: #define SI_LOAD_SHIFT   16
32:
33: /*
34:  * This was brought from Linux 2.0.30 (sched.h).
35:  * Copyright Linus Torvalds et al.
36:  */
37: extern unsigned int avenrun[3];          /* Load averages */
38: #define FSHIFT          11              /* nr of bits of precision */
39: #define FIXED_1         (1<<FSHIFT)    /* 1.0 as fixed-point */
40: #define LOAD_FREQ       (5*HZ)         /* 5 sec intervals */
41: #define EXP_1           1884           /* 1/exp(5sec/1min) as fixed-point */
42: #define EXP_5           2014           /* 1/exp(5sec/5min) */
43: #define EXP_15          2037           /* 1/exp(5sec/15min) */
44:
45: #define CALC_LOAD(load,exp,n) \
46:     load *= exp; \
47:     load += n*(FIXED_1-exp); \
48:     load >>= FSHIFT;
49: /* ----- */
50:
51:
52: void do_sched(void);
53: void set_tss(struct proc *);
54: void sched_init(void);
55:
56: #endif /* _FIWIX_SCHED_H */

```

include/fiwix/segments.h

Page 1/2

```

1: /*
2:  * fiwix/include/fiwix/segments.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_SEGMENTS_H
9: #define _FIWIX_SEGMENTS_H
10:
11: #include <fiwix/types.h>
12:
13: #define NR_GDT_ENTRIES 6 /* entries in GDT descriptor */
14: #define NR_IDT_ENTRIES 256 /* entries in IDT descriptor */
15:
16: /* low flags of Segment Descriptors */
17: #define SD_DATA 0x02 /* DATA Read/Write */
18: #define SD_CODE 0x0A /* CODE Exec/Read */
19:
20: #define SD_32TSSA 0x09 /* 32-bit TSS (Available) */
21: #define SD_32TSSB 0x0B /* 32-bit TSS (Busy) */
22: #define SD_32CALLGATE 0x0C /* 32-bit Call Gate */
23: #define SD_32INTRGATE 0x0E /* 32-bit Interrupt Gate (0D110) */
24: #define SD_32TRAPGATE 0x0F /* 32-bit Trap Gate (0D111) */
25:
26: #define SD_CD 0x10 /* 0 = system / 1 = code/data */
27: #define SD_DPL0 0x00 /* priority level 0 */
28: #define SD_DPL1 0x20 /* priority level 1 (unused) */
29: #define SD_DPL2 0x40 /* priority level 2 (unused) */
30: #define SD_DPL3 0x60 /* priority level 3 (user) */
31: #define SD_PRESENT 0x80 /* segment present or valid */
32:
33: /* high flags Segment Descriptors */
34: #define SD_OPSIZE32 0x04 /* 32-bit code and data segments */
35: #define SD_PAGE4KB 0x08 /* page granularity (4KB) */
36:
37: /* low flags of the TSS Descriptors */
38: #define SD_TSSPRESENT 0x89 /* TSS present and not busy flag */
39:
40: #define USR_PL 3 /* User Privilege Level */
41:
42: /* EFLAGS */
43: #define EF_IOPL 12 /* IOPL bit */
44:
45: struct desc_r {
46:     __u16 limit;
47:     __u32 base_addr;
48: } __attribute__((packed));
49:
50: struct seg_desc {
51:     unsigned sd_lolimit : 16; /* segment limit 0-15 bits */
52:     unsigned sd_lobase : 24; /* base address 0-23 bits */
53:     unsigned sd_loflags : 8; /* flags (P, DPL, S and TYPE) */
54:     unsigned sd_hilimit : 4; /* segment limit 16-19 bits */
55:     unsigned sd_hiflags : 4; /* flags (G, DB, 0 and AVL) */
56:     unsigned sd_hibase : 8; /* base address 24-31 bits */
57: } __attribute__((packed));
58:
59: struct gate_desc {
60:     unsigned gd_looffset : 16; /* offset 0-15 bits */
61:     unsigned gd_selector : 16; /* segment selector */
62:     unsigned gd_flags : 16; /* flags (P, DPL, TYPE, 0 and NULL) */
63:     unsigned gd_hioffset : 16; /* offset 16-31 bits */
64: } __attribute__((packed));
65:
66: void gdt_init(void);
67: void idt_init(void);

```


include/fiwix/segments.h

Page 2/2

```
68:
69: #endif /* _FIWIX_SEGMENTS_H */
```

include/fiwix/sigcontext.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/sigcontext.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_SIGCONTEXT_H
9: #define _FIWIX_SIGCONTEXT_H
10:
11: struct sigcontext {
12:     unsigned int gs;
13:     unsigned int fs;
14:     unsigned int es;
15:     unsigned int ds;
16:     unsigned int edi;
17:     unsigned int esi;
18:     unsigned int ebp;
19:     unsigned int esp;
20:     int ebx;
21:     int edx;
22:     int ecx;
23:     int eax;
24:     int err;
25:     unsigned int eip;
26:     unsigned int cs;
27:     unsigned int eflags;
28:     unsigned int oldesp;
29:     unsigned int oldss;
30: };
31:
32: #endif /* _FIWIX_SIGCONTEXT_H */
```

include/fiwix/signal.h

Page 1/2

```

1: /*
2:  * fiwix/include/fiwix/signal.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_SIGNAL_H
9: #define _FIWIX_SIGNAL_H
10:
11: #define NSIG          32
12:
13: #define SIGHUP        1      /* Hangup or Reset */
14: #define SIGINT        2      /* Interrupt */
15: #define SIGQUIT       3      /* Quit */
16: #define SIGILL        4      /* Illegal Instruction */
17: #define SIGTRAP       5      /* Trace Trap */
18: #define SIGABRT       6      /* Abort Instruction */
19: #define SIGIOT        SIGABRT /* I/O Trap Instruction */
20: #define SIGBUS        7      /* Bus Error */
21: #define SIGFPE        8      /* Floating Point Exception */
22: #define SIGKILL       9      /* Kill */
23: #define SIGUSR1       10     /* User Defined #1 */
24: #define SIGSEGV       11     /* Segmentation Violation */
25: #define SIGUSR2       12     /* User Defined #2 */
26: #define SIGPIPE       13     /* Broken Pipe */
27: #define SIGALRM       14     /* Alarm Clock */
28: #define SIGTERM       15     /* Software Termination */
29: #define SIGSTKFLT     16     /* Stack Fault */
30: #define SIGCHLD       17     /* Child Termination */
31: #define SIGCONT       18     /* Continue */
32: #define SIGSTOP       19     /* Stop */
33: #define SIGTSTP       20     /* Terminal Stop */
34: #define SIGTTIN       21     /* Background Read */
35: #define SIGTTOU       22     /* Background Write */
36: #define SIGURG        23     /* Urgent Data */
37: #define SIGXCPU       24     /* CPU eXceeded */
38: #define SIGXFSZ       25     /* File Size eXceeded */
39: #define SIGVTALRM     26     /* Virtual Time Alarm */
40: #define SIGPROF       27     /* Profile Alarm */
41: #define SIGWINCH      28     /* Window Change */
42: #define SIGIO         29     /* I/O Asynchronous */
43: #define SIGPOLL       SIGIO
44: #define SIGPWR        30     /* Power Fault */
45: #define SIGUNUSED     31
46:
47: typedef unsigned long int __sigset_t;
48: typedef void (*__sighandler_t)(int);
49:
50: struct sigaction {
51:     __sighandler_t sa_handler;
52:     __sigset_t sa_mask;
53:     int sa_flags;
54:     void (*sa_restorer)(void);
55: };
56:
57: #define SIG_DFL        ((__sighandler_t) 0)
58: #define SIG_IGN        ((__sighandler_t) 1)
59: #define SIG_ERR        ((__sighandler_t) -1)
60:
61: /* bits in sa_flags */
62: #define SA_NOCLDSTOP    0x00000001    /* don't send SIGCHLD when children stop
*/
63: #define SA_NOCLDWAIT    0x00000002    /* don't create zombie on child death */
64: #define SA_ONSTACK      0x08000000    /* invoke handler on alternate stack */
65: #define SA_RESTART      0x10000000    /* automatically restart system call */
66: #define SA_INTERRUPT    0x20000000    /* unused */

```

include/fiwix/signal.h

Page 2/2

```
67:
68: /* don't automatically block signal when the handler is executing */
69: #define SA_NODEFER      0x40000000
70: #define SA_NOMASK      SA_NODEFER
71:
72: /* reset signal disposition to SIG_DFL before invoking handler */
73: #define SA_RESETHAND    0x80000000
74: #define SA_ONESHOT      SA_RESETHAND
75:
76: /* bits in the third argument to 'waitpid/wait4' */
77: #define WNOHANG          1      /* don't block waiting */
78: #define WUNTRACED        2      /* report status of stopped children */
79:
80: #define SIG_BLOCK         0      /* for blocking signals */
81: #define SIG_UNBLOCK      1      /* for unblocking signals */
82: #define SIG_SETMASK      2      /* for setting the signal mask */
83:
84: /* SIGKILL and SIGSTOP can't ever be set as blockable signals */
85: #define SIG_BLOCKABLE    (~(1 << (SIGKILL - 1)) | (1 << (SIGSTOP - 1)))
86:
87: #define SIG_MASK(sig)    (~(1 << ((sig) - 1)))
88:
89: int issig(void);
90: void psig(unsigned int);
91:
92: #endif /* _FIWIX_SIGNAL_H */
```

include/fiwix/sleep.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/sleep.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_SLEEP_H
9: #define _FIWIX_SLEEP_H
10:
11: #include <fiwix/process.h>
12:
13: #define AREA_TTY_READ    0x00000001
14: #define AREA_CALLOUT    0x00000002
15:
16: struct sleep {
17:     unsigned short int next;
18:     void *address;
19:     struct proc *proc;
20: };
21:
22: struct resource {
23:     char locked;
24:     char wanted;
25: };
26:
27: int sleep(void *, int);
28: void wakeup(void *);
29: void wakeup_proc(struct proc *);
30:
31: void lock_resource(struct resource *);
32: void unlock_resource(struct resource *);
33: int lock_area(unsigned int);
34: int unlock_area(unsigned int);
35:
36: void sleep_init(void);
37:
38: #endif /* _FIWIX_SLEEP_H */
```

include/fiwix/statbuf.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/statbuf.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_STATBUF_H
9: #define _FIWIX_STATBUF_H
10:
11: struct old_stat {
12:     __dev_t st_dev;
13:     unsigned short int st_ino;
14:     __mode_t st_mode;
15:     __nlink_t st_nlink;
16:     __uid_t st_uid;
17:     __gid_t st_gid;
18:     __dev_t st_rdev;
19:     unsigned int st_size;
20:     __time_t st_atime;
21:     __time_t st_mtime;
22:     __time_t st_ctime;
23: };
24:
25: struct new_stat {
26:     __dev_t st_dev;
27:     unsigned short int __pad1;
28:     __ino_t st_ino;
29:     __mode_t st_mode;
30:     __nlink_t st_nlink;
31:     __uid_t st_uid;
32:     __gid_t st_gid;
33:     __dev_t st_rdev;
34:     unsigned short int __pad2;
35:     __off_t st_size;
36:     __blk_t st_blksize;
37:     __blk_t st_blocks;
38:     __time_t st_atime;
39:     unsigned int __unused1;
40:     __time_t st_mtime;
41:     unsigned int __unused2;
42:     __time_t st_ctime;
43:     unsigned int __unused3;
44:     unsigned int __unused4;
45:     unsigned int __unused5;
46: };
47:
48: #endif /* _FIWIX_STATBUF_H */
```

include/fiwix/statfs.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/statfs.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_STATFS_H
9: #define _FIWIX_STATFS_H
10:
11: typedef struct {
12:     long int val[2];
13: } fsid_t;
14:
15: struct statfs {
16:     long int f_type;
17:     long int f_bsize;
18:     long int f_blocks;
19:     long int f_bfree;
20:     long int f_bavail;
21:     long int f_files;
22:     long int f_ffree;
23:     fsid_t f_fsid;
24:     long int f_namelen;
25:     long int f_spare[6];
26: };
27:
28: #endif /* _FIWIX_STATFS_H */
```

include/fiwix/stat.h

Page 1/1

```

1: #ifndef _FIWIX_STAT_H
2: #define _FIWIX_STAT_H
3:
4: #include <fiwix/statbuf.h>
5:
6: /* Encoding of the file mode. These are the standard Unix values,
7:    but POSIX.1 does not specify what values should be used. */
8:
9: #define S_IFMT          0170000          /* Type of file mask */
10:
11: /* File types. */
12: #define S_IFIFO          0010000          /* Named pipe (fifo) */
13: #define S_IFCHR          0020000          /* Character special */
14: #define S_IFDIR          0040000          /* Directory */
15: #define S_IFBLK          0060000          /* Block special */
16: #define S_IFREG          0100000          /* Regular */
17: #define S_IFLNK          0120000          /* Symbolic link */
18: #define S_IFSOCK          0140000          /* Socket */
19:
20: /* Protection bits. */
21: #define S_IXUSR          00100          /* USER  --x----- */
22: #define S_IWUSR          00200          /* USER  -w----- */
23: #define S_IRUSR          00400          /* USER  r----- */
24: #define S_IRWXU          00700          /* USER  rwx----- */
25:
26: #define S_IXGRP          00010          /* GROUP  -----x--- */
27: #define S_IWGRP          00020          /* GROUP  -----w--- */
28: #define S_IRGRP          00040          /* GROUP  ---r----- */
29: #define S_IRWXG          00070          /* GROUP  ---rwx--- */
30:
31: #define S_IXOTH          00001          /* OTHERS  -----x */
32: #define S_IWOTH          00002          /* OTHERS  -----w- */
33: #define S_IROTH          00004          /* OTHERS  -----r-- */
34: #define S_IRWXO          00007          /* OTHERS  -----rwx */
35:
36: #define S_ISUID          0004000          /* set user id on execution */
37: #define S_ISGID          0002000          /* set group id on execution */
38: #define S_ISVTX          0001000          /* sticky bit */
39:
40: #define S_IREAD          S_IRUSR          /* Read by owner. */
41: #define S_IWRITE         S_IWUSR          /* Write by owner. */
42: #define S_IEXEC          S_IXUSR          /* Execute by owner. */
43:
44: #define S_ISFIFO(m)      (((m) & S_IFMT) == S_IFIFO)
45: #define S_ISCHR(m)      (((m) & S_IFMT) == S_IFCHR)
46: #define S_ISDIR(m)      (((m) & S_IFMT) == S_IFDIR)
47: #define S_ISBLK(m)      (((m) & S_IFMT) == S_IFBLK)
48: #define S_ISREG(m)      (((m) & S_IFMT) == S_IFREG)
49: #define S_ISLNK(m)      (((m) & S_IFMT) == S_IFLNK)
50: #define S_ISSOCK(m)     (((m) & S_IFMT) == S_IFSOCK)
51:
52: #define TO_READ          4          /* test for read permission */
53: #define TO_WRITE         2          /* test for write permission */
54: #define TO_EXEC          1          /* test for execute permission */
55:
56: #endif /* _FIWIX_STAT_H */

```


include/fiwix/stdarg.h

Page 1/1

```

1: /*
2: Copyright (C) 1988 Free Software Foundation
3:
4: This file is part of GNU CC.
5:
6: GNU CC is distributed in the hope that it will be useful,
7: but WITHOUT ANY WARRANTY. No author or distributor
8: accepts responsibility to anyone for the consequences of using it
9: or for whether it serves any particular purpose or works at all,
10: unless he says so in writing. Refer to the GNU CC General Public
11: License for full details.
12:
13: Everyone is granted permission to copy, modify and redistribute
14: GNU CC, but only under the conditions described in the
15: GNU CC General Public License. A copy of this license is
16: supposed to have been given to you along with GNU CC so you
17: can know your rights and responsibilities. It should be in a
18: file named COPYING. Among other things, the copyright notice
19: and this notice must be preserved on all copies.
20: */
21:
22: #ifndef __stdarg_h
23: #define __stdarg_h
24:
25: typedef char *va_list;
26:
27: /* Amount of space required in an argument list for an arg of type TYPE.
28:    TYPE may alternatively be an expression whose type is used. */
29:
30: #define __va_rounded_size(TYPE) \
31:    (((sizeof (TYPE) + sizeof (int) - 1) / sizeof (int)) * sizeof (int))
32:
33: #define va_start(AP, LASTARG) \
34:    (AP = ((char *) &(LASTARG) + __va_rounded_size(LASTARG)))
35:
36: extern void va_end (va_list);
37: #define va_end(AP) /* Nothing */
38:
39: #define va_arg(AP, TYPE) (AP += __va_rounded_size (TYPE), \
40:    *((TYPE *) (AP - __va_rounded_size (TYPE))))
41:
42: #endif /* __stdarg_h */

```

include/fiwix/stdio.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/stdio.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _INCLUDE_STDIO_H
9: #define _INCLUDE_STDIO_H
10:
11: void register_console(void (*fn)(char *, unsigned int));
12: void printk(const char *, ...);
13: int sprintk(char *, const char *, ...);
14:
15: #endif /* _INCLUDE_STDIO_H */
```

include/fiwix/string.h

Page 1/1

```

1: /*
2:  * fiwix/include/fiwix/string.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _INCLUDE_STRING_H
9: #define _INCLUDE_STRING_H
10:
11: #include <fiwix/types.h>
12:
13: #ifndef NULL
14: #define NULL    '\0'    /* ((void *)0) */
15: #endif
16:
17: #define MIN(a,b)    ((a) < (b) ? (a) : (b))
18: #define MAX(a,b)    ((a) > (b) ? (a) : (b))
19:
20: #define IS_NUMERIC(c)    ((c) >= '0' && (c) <= '9')
21: #define IS_SPACE(c)    ((c) == ' ')
22:
23: void swap_asc_word(char *, int);
24: int strcmp(const char *, const char *);
25: int strncmp(const char *, const char *, __ssize_t);
26: char * strcpy(char *, const char *);
27: void strncpy(char *, const char *, int);
28: char * strcat(char *, const char *);
29: char * strncat(char *, const char *, __ssize_t);
30: int strlen(const char *);
31: char * get_basename(const char *);
32: char * remove_trailing_slash(char *);
33: int is_dir(const char *);
34: int atoi(const char *);
35: void memcpy_b(void *, const void *, unsigned int);
36: void memcpy_w(void *, const void *, unsigned int);
37: void memcpy_l(void *, const void *, unsigned int);
38: void memset_b(void *, unsigned char, unsigned int);
39: void memset_w(void *, unsigned short int, unsigned int);
40: void memset_l(void *, unsigned int, unsigned int);
41:
42: #endif /* _INCLUDE_STRING_H */

```

include/fiwix/syscalls.h

```

1: /*
2:  * fiwix/include/fiwix/syscalls.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_SYSCALLS_H
9: #define _FIWIX_SYSCALLS_H
10:
11: #include <fiwix/types.h>
12: #include <fiwix/system.h>
13: #include <fiwix/time.h>
14: #include <fiwix/times.h>
15: #include <fiwix/timeb.h>
16: #include <fiwix/utime.h>
17: #include <fiwix/statbuf.h>
18: #include <fiwix/ustat.h>
19: #include <fiwix/signal.h>
20: #include <fiwix/utsname.h>
21: #include <fiwix/resource.h>
22: #include <fiwix/dirent.h>
23: #include <fiwix/statfs.h>
24: #include <fiwix/sigcontext.h>
25: #include <fiwix/mman.h>
26:
27: #define NR_SYSCALLS      (sizeof(syscall_table) / sizeof(unsigned int))
28:
29: int do_syscall(unsigned int, int, int, int, int, int, struct sigcontext);
30:
31: int sys_exit(int);
32: void do_exit(int);
33: int sys_fork(int, int, int, int, int, struct sigcontext *);
34: int sys_read(unsigned int, char *, int);
35: int sys_write(unsigned int, const char *, int);
36: int sys_open(const char *, int, __mode_t);
37: int sys_close(unsigned int);
38: int sys_waitpid(__pid_t, int *, int);
39: int sys_creat(const char *, __mode_t);
40: int sys_link(const char *, const char *);
41: int sys_unlink(const char *);
42: int sys_execve(const char *, char **, char **, int, int, struct sigcontext *);
43: int sys_chdir(const char *);
44: int sys_time(__time_t *);
45: int sys_mknod(const char *, __mode_t, __dev_t);
46: int sys_chmod(const char *, __mode_t);
47: int sys_chown(const char *, __uid_t, __gid_t);
48: int sys_stat(const char *, struct old_stat *);
49: int sys_lseek(unsigned int, __off_t, unsigned int);
50: int sys_getpid(void);
51: int sys_mount(const char *, const char *, const char *, unsigned long int, const
void *);
52: int sys_umount(const char *);
53: int sys_setuid(__uid_t);
54: int sys_getuid(void);
55: int sys_stime(__time_t *);
56: int sys_alarm(unsigned int);
57: int sys_fstat(unsigned int, struct old_stat *);
58: int sys_pause(void);
59: int sys_utime(const char *, struct utimbuf *);
60: int sys_access(const char *, __mode_t);
61: int sys_ftime(struct timeb *);
62: void sys_sync(void);
63: int sys_kill(__pid_t, __sigset_t);
64: int sys_rename(const char *, const char *);
65: int sys_mkdir(const char *, __mode_t);
66: int sys_rmdir(const char *);

```

include/fiwix/syscalls.h

Page 2/3

```

67: int sys_dup(unsigned int);
68: int sys_pipe(int *);
69: int sys_times(struct tms *);
70: int sys_brk(unsigned int);
71: int sys_setgid(__gid_t);
72: int sys_getgid(void);
73: unsigned int sys_signal(__sigset_t, void(*sighandler)(int));
74: int sys_geteuid(void);
75: int sys_getegid(void);
76: int sys_umount2(const char *, int);
77: int sys_ioctl(unsigned int, int, unsigned long int);
78: int sys_fcntl(int, int, unsigned long int);
79: int sys_setpgid(__pid_t, __pid_t);
80: int sys_olduname(struct oldold_utsname *);
81: int sys_umask(__mode_t);
82: int sys_chroot(const char *);
83: int sys_ustat(__dev_t, struct ustat *);
84: int sys_dup2(int, int);
85: int sys_getppid(void);
86: int sys_getpgrp(void);
87: int sys_setsid(void);
88: int sys_sigaction(__sigset_t, const struct sigaction *, struct sigaction *);
89: int sys_sgetmask(void);
90: int sys_ssetmask(int);
91: int sys_setreuid(__uid_t, __uid_t);
92: int sys_setregid(__gid_t, __gid_t);
93: int sys_sigsuspend(__sigset_t *);
94: int sys_sigpending(__sigset_t *);
95: int sys_sethostname(const char *, int);
96: int sys_setrlimit(int, const struct rlimit *);
97: int sys_getrlimit(int, struct rlimit *);
98: int sys_getrusage(int, struct rusage *);
99: int sys_gettimeofday(struct timeval *, struct timezone *);
100: int sys_settimeofday(const struct timeval *, const struct timezone *);
101: int sys_getgroups(__ssize_t, __gid_t *);
102: int sys_setgroups(__ssize_t, const __gid_t *);
103: int old_select(unsigned long int *);
104: int sys_symlink(const char *, const char *);
105: int sys_lstat(const char *, struct old_stat *);
106: int sys_readlink(const char *, char *, __size_t);
107: int sys_reboot(int, int, int);
108: int old_mmap(struct mmap *);
109: int sys_munmap(unsigned int, __size_t);
110: int sys_truncate(const char *, __off_t);
111: int sys_ftruncate(int, __off_t);
112: int sys_fchmod(int, __mode_t);
113: int sys_fchown(int, __uid_t, __gid_t);
114: int sys_statfs(const char *, struct statfs *);
115: int sys_fstatfs(unsigned int, struct statfs *);
116: int sys_ioperm(unsigned long int, unsigned long int, int);
117: int sys_socketcall(int, unsigned long int *);
118: int sys_setitimer(int, const struct itimerval *, struct itimerval *);
119: int sys_getitimer(int, struct itimerval *);
120: int sys_newstat(const char *, struct new_stat *);
121: int sys_newlstat(const char *, struct new_stat *);
122: int sys_newfstat(unsigned int, struct new_stat *);
123: int sys_uname(struct old_utsname *);
124: int sys_iopl(int, int, int, int, int, struct sigcontext *);
125: int sys_wait4(__pid_t, int *, int, struct rusage *);
126: int sys_sysinfo(struct sysinfo *);
127: int sys_fsync(int);
128: int sys_sigreturn(unsigned int, int, int, int, int, int, struct sigcontext *);
129: int sys_setdomainname(const char *, int);
130: int sys_newuname(struct new_utsname *);
131: int sys_mprotect(unsigned int, __size_t, int);
132: int sys_sigprocmask(int, const __sigset_t *, __sigset_t *);
133: int sys_getpgid(__pid_t);

```

include/fiwix/syscalls.h

Page 3/3

```
134: int sys_fchdir(unsigned int);
135: int sys_personality(unsigned long int);
136: int sys_setfsuid(__uid_t);
137: int sys_setfsgid(__gid_t);
138: int sys_llseek(unsigned int, unsigned long int, unsigned long int, __loff_t *, u
nsigned int);
139: int sys_getdents(unsigned int, struct dirent *, unsigned int);
140: int sys_select(int, fd_set *, fd_set *, fd_set *, struct timeval *);
141: int sys_flock(int, int);
142: int sys_getsid(__pid_t);
143: int sys_fdatasync(int);
144: int sys_nanosleep(const struct timespec *, struct timespec *);
145: int sys_getcwd(char *, __size_t);
146:
147: #endif /* _FIWIX_SYSCALLS_H */
```

include/fiwix/system.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/system.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_SYSTEM_H
9: #define _FIWIX_SYSTEM_H
10:
11: #define UTS_SYSNAME      "Fiwix"
12: #define UTS_NODENAME    "(none)"
13: #define UTS_RELEASE     "1.0.0"
14: #define UTS_DOMAINNAME  "(none)"
15:
16: struct sysinfo {
17:     long int uptime;           /* seconds since boot */
18:     unsigned long int loads[3]; /* load average (1, 5 and 15 minutes) */
19:     unsigned long int totalram; /* total usable main memory size */
20:     unsigned long int freeram;  /* available memory size */
21:     unsigned long int sharedram; /* amount of shared memory */
22:     unsigned long int bufferram; /* amount of memory used by buffers */
23:     unsigned long int totalswap; /* total swap space size */
24:     unsigned long int freeswap; /* available swap space */
25:     unsigned short int procs;  /* number of current processes */
26:     char _f[22];              /* pads structure to 64 bytes */
27: };
28:
29: #endif /* _FIWIX_SYSTEM_H */
```

include/fiwix/termbits.h

Page 1/3

```

1: /*
2:  * fiwix/include/fiwix/termbits.h
3:  *
4:  */
5:
6: #ifndef _FIWIX_TERMBITS_H
7: #define _FIWIX_TERMBITS_H
8:
9: /* These definitions match those used by the 4.4 BSD kernel.
10:    If the operating system has termios system calls or ioctls that
11:    correctly implement the POSIX.1 behavior, there should be a
12:    system-dependent version of this file that defines 'struct termios',
13:    'tcflag_t', 'cc_t', 'speed_t' and the 'TC*' constants appropriately.  */
14:
15: /* Type of terminal control flag masks.  */
16: typedef unsigned long int tcflag_t;
17:
18: /* Type of control characters.  */
19: typedef unsigned char cc_t;
20:
21: /* Type of baud rate specifiers.  */
22: typedef long int speed_t;
23:
24: #define NCCS 19
25:
26: /* Terminal control structure.  */
27: struct termios {
28:     tcflag_t c_iflag;        /* Input mode flags */
29:     tcflag_t c_oflag;        /* Output mode flags */
30:     tcflag_t c_cflag;        /* Control mode flags */
31:     tcflag_t c_lflag;        /* Local mode flags */
32:     cc_t c_line;             /* Line discipline */
33:     cc_t c_cc[NCCS];         /* Control characters */
34: };
35:
36: /* c_iflag bits */
37: #define IGNBRK 0000001        /* Ignore break condition */
38: #define BRKINT 0000002        /* Signal interrupt on break */
39: #define IGNPAR 0000004        /* Ignore characters with parity errors */
40: #define PARMRK 0000010        /* Mark parity and framing errors */
41: #define INPCK 0000020        /* Enable input parity check */
42: #define ISTRIP 0000040        /* Strip 8th bit off characters */
43: #define INLCR 0000100        /* Map NL to CR on input */
44: #define IGNCR 0000200        /* Ignore CR */
45: #define ICRNL 0000400        /* Map CR to NL on input */
46: #define IUCLC 0001000        /* Convert to lowercase */
47: #define IXON 0002000         /* Enable start/stop output control */
48: #define IXANY 0004000        /* Any character will restart after stop */
49: #define IXOFF 0010000        /* Enable start/stop input control */
50: #define IMAXBEL 0020000       /* Ring bell when input queue is full */
51:
52: /* c_oflag bits */
53: #define OPOST 0000001        /* Perform output processing */
54: #define OLCUC 0000002
55: #define ONLCR 0000004        /* Map NL to CR-NL on output */
56: #define OCRNL 0000010
57: #define ONOCR 0000020
58: #define ONLRET 0000040
59: #define OFILL 0000100
60: #define OFDEL 0000200
61: #define NLDLY 0000400
62: #define NL0 0000000
63: #define NL1 0000400
64: #define CRDLY 0003000
65: #define CR0 0000000
66: #define CR1 0001000
67: #define CR2 0002000

```


include/fiwix/termbits.h

Page 2/3

```

68: #define CR3 0003000
69: #define TABDLY 0014000
70: #define TAB0 0000000
71: #define TAB1 0004000
72: #define TAB2 0010000
73: #define TAB3 0014000
74: #define XTABS 0014000
75: #define BSDLY 0020000
76: #define BS0 0000000
77: #define BS1 0020000
78: #define VTDLY 0040000
79: #define VT0 0000000
80: #define VT1 0040000
81: #define FFDLY 0100000
82: #define FF0 0000000
83: #define FF1 0100000
84:
85: /* c_cflag bit meaning */
86: #define CBAUD 0010017
87: #define B0 0000000 /* hang up */
88: #define B50 0000001 /* 50 baud */
89: #define B75 0000002 /* 75 baud */
90: #define B110 0000003 /* 110 baud */
91: #define B134 0000004 /* 134 baud */
92: #define B150 0000005 /* 150 baud */
93: #define B200 0000006 /* 200 baud */
94: #define B300 0000007 /* 300 baud */
95: #define B600 0000010 /* 600 baud */
96: #define B1200 0000011 /* 1200 baud */
97: #define B1800 0000012 /* 1800 baud */
98: #define B2400 0000013 /* 2400 baud */
99: #define B4800 0000014 /* 4800 baud */
100: #define B9600 0000015 /* 9600 baud */
101: #define B19200 0000016 /* 19200 baud */
102: #define B38400 0000017 /* 38400 baud */
103: #define EXTA B19200
104: #define EXTB B38400
105: #define CSIZE 0000060 /* Number of bits per byte (mask) */
106: #define CS5 0000000 /* 5 bits per byte */
107: #define CS6 0000020 /* 6 bits per byte */
108: #define CS7 0000040 /* 7 bits per byte */
109: #define CS8 0000060 /* 8 bits per byte */
110: #define CSTOPB 0000100 /* Two stop bits instead of one */
111: #define CREAD 0000200 /* Enable receiver */
112: #define PARENB 0000400 /* Parity enable */
113: #define PARODD 0001000 /* Odd parity instead of even */
114: #define HUPCL 0002000 /* Hang up on last close */
115: #define CLOCAL 0004000 /* Ignore modem status lines */
116: #define CBAUDEX 0010000
117: #define B57600 0010001
118: #define B115200 0010002
119: #define B230400 0010003
120: #define B460800 0010004
121: #define B500000 0010005
122: #define B576000 0010006
123: #define B921600 0010007
124: #define B1000000 0010010
125: #define B1152000 0010011
126: #define B1500000 0010012
127: #define B2000000 0010013
128: #define B2500000 0010014
129: #define B3000000 0010015
130: #define B3500000 0010016
131: #define B4000000 0010017
132: #define CIBAUD 002003600000 /* input baud rate (not used) */
133: #define CMSPAR 010000000000 /* mark or space (stick) parity */
134: #define CRTSCTS 020000000000 /* flow control */

```

include/fiwix/termbits.h

Page 3/3

```

135:
136: /* c_lflag bits */
137: #define ISIG      0000001    /* Enable signals */
138: #define ICANON    0000002    /* Do erase and kill processing */
139: #define XCASE     0000004
140: #define ECHO      0000010    /* Enable echo */
141: #define ECHOE     0000020    /* Visual erase for ERASE */
142: #define ECHOK     0000040    /* Echo NL after KILL */
143: #define ECHONL   0000100    /* Echo NL even if echo is OFF */
144: #define NOFLSH   0000200    /* Disable flush after interrupt */
145: #define TOSTOP   0000400    /* Send SIGTTOU for background output */
146: #define ECHOCTL  0001000    /* Echo control characters as ^X */
147: #define ECHOPRT  0002000    /* Hardcopy visual erase */
148: #define ECHO     0004000    /* Visual erase for KILL */
149: #define FLUSHO   0010000    /* Output being flushed (state) */
150: #define PENDIN   0040000    /* Retype pending input (state) */
151: #define IEXTEN   0100000    /* Enable DISCARD and LNEXT */
152:
153: /* c_cc characters */
154: #define VINTR    0          /* Interrupt character [ISIG] */
155: #define VQUIT    1          /* Quit character [ISIG] */
156: #define VERASE   2          /* Erase character [ICANON] */
157: #define VKILL    3          /* Kill-line character [ICANON] */
158: #define VEOF     4          /* End-of-file character [ICANON] */
159: #define VTIME    5          /* Time-out value (1/10 secs) [!ICANON] */
160: #define VMIN     6          /* Minimum # of bytes read at once [!ICANON] */
161: #define VSWTC    7
162: #define VSTART   8          /* Start (X-ON) character [IXON, IXOFF] */
163: #define VSTOP    9          /* Stop (X-OFF) character [IXON, IXOFF] */
164: #define VSUSP   10         /* Suspend character [ISIG] */
165: #define VEOL    11         /* End-of-line character [ICANON] */
166: #define VREPRINT 12        /* Reprint-line character [ICANON] */
167: #define VDISCARD 13        /* Discard character [IEXTEN] */
168: #define VWERASE  14        /* Word-erase character [ICANON] */
169: #define VLNEXT   15        /* Literal-next character [IEXTEN] */
170: #define VEOL2   16        /* Second EOL character [ICANON] */
171:
172: /* Values for the ACTION argument to 'tcflow'. */
173: #define TCOOFF   0          /* Suspend output */
174: #define TCOON    1          /* Restart suspended output */
175: #define TCIOFF   2          /* Send a STOP character */
176: #define TCION    3          /* Send a START character */
177:
178: /* Values for the QUEUE_SELECTOR argument to 'tcflush'. */
179: #define TCIFLUSH 0          /* Discard data received but not yet read */
180: #define TCOFLUSH 1          /* Discard data written but not yet sent */
181: #define TCIOFLUSH 2        /* Discard all pending data */
182:
183: /* Values for the OPTIONAL_ACTIONS argument to 'tcsetattr'. */
184: #define TCSANOW  0          /* Change immediately */
185: #define TCSADRAIN 1         /* Change when pending output is written */
186: #define TCSAFLUSH 2         /* Flush pending input before changing */
187:
188: #endif /* _FIWIX_TERMBITS_H */

```

include/fiwix/termios.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/termios.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_TERMIOS_H
9: #define _FIWIX_TERMIOS_H
10:
11: #include <fiwix/termbits.h>
12:
13: struct winsize {
14:     unsigned short int ws_row;
15:     unsigned short int ws_col;
16:     unsigned short int ws_xpixel;
17:     unsigned short int ws_ypixel;
18: };
19:
20: #define NCC      8
21:
22: struct termio {
23:     unsigned short int c_iflag;    /* input mode flags */
24:     unsigned short int c_oflag;    /* output mode flags */
25:     unsigned short int c_cflag;    /* control mode flags */
26:     unsigned short int c_lflag;    /* local mode flags */
27:     unsigned char c_line;          /* line discipline */
28:     unsigned char c_cc[NCC];       /* control characters */
29: };
30:
31: #endif /* _FIWIX_TERMIOS_H */
```

include/fiwix/timeb.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/timeb.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_TIMEB_H
9: #define _FIWIX_TIMEB_H
10:
11: struct timeb {
12:     unsigned int time;           /* in seconds since Epoch */
13:     unsigned short int millitm; /* additional milliseconds */
14:     short int timezone;         /* minutes west of GMT */
15:     short int dstflag;          /* nonzero if DST is used */
16: };
17:
18: #endif /* _FIWIX_TIMEB_H */
```

include/fiwix/time.h

Page 1/1

```

1: /*
2:  * fiwix/include/fiwix/time.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_TIME_H
9: #define _FIWIX_TIME_H
10:
11: #define ITIMER_REAL    0
12: #define ITIMER_VIRTUAL 1
13: #define ITIMER_PROF   2
14:
15: struct timespec {
16:     long int tv_sec;          /* seconds since 00:00:00, 1 Jan 1970 UTC */
17:     long int tv_nsec;        /* nanoseconds (1000000000ns = 1sec) */
18: };
19:
20: struct timeval {
21:     long int tv_sec;          /* seconds since 00:00:00, 1 Jan 1970 UTC */
22:     long int tv_usec;        /* microseconds (1000000us = 1sec) */
23: };
24:
25: struct timezone {
26:     int tz_minuteswest;      /* minutes west of GMT */
27:     int tz_dsttime;          /* type of DST correction */
28: };
29:
30: struct itimerval {
31:     struct timeval it_interval;
32:     struct timeval it_value;
33: };
34:
35: struct mt {
36:     int mt_sec;
37:     int mt_min;
38:     int mt_hour;
39:     int mt_day;
40:     int mt_month;
41:     int mt_year;
42: };
43:
44: unsigned long int tv2ticks(const struct timeval *);
45: void ticks2tv(long int, struct timeval *);
46: int setitimer(int, const struct itimerval *, struct itimerval *);
47: unsigned long int mktime(struct mt *);
48:
49: #endif /* _FIWIX_TIME_H */

```

include/fiwix/timer.h

Page 1/1

```

1: /*
2:  * fiwix/include/fiwix/timer.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_TIMER_H
9: #define _FIWIX_TIMER_H
10:
11: #include <fiwix/types.h>
12: #include <fiwix/sigcontext.h>
13:
14: #define TIMER_IRQ      0
15: #define HZ              100      /* kernel's Hertz rate (100 = 10ms) */
16: #define TICK           (1000000 / HZ)
17:
18: #define UNIX_EPOCH     1970
19:
20: #define LEAP_YEAR(y)   ((y % 4) == 0 && ((y % 100) != 0 || (y % 400) == 0))
21: #define DAYS_PER_YEAR(y) ((LEAP_YEAR(y)) ? 366 : 365)
22:
23: #define SECS_PER_MIN   60
24: #define SECS_PER_HOUR (SECS_PER_MIN * 60)
25: #define SECS_PER_DAY   (SECS_PER_HOUR * 24)
26:
27: #define INFINITE_WAIT  0xFFFFFFFF
28:
29: struct callout {
30:     int expires;
31:     void (*fn)(unsigned int);
32:     unsigned int arg;
33:     struct callout *next;
34: };
35:
36: struct callout_req {
37:     void (*fn)(unsigned int);
38:     unsigned int arg;
39: };
40:
41: void add_callout(struct callout_req *, unsigned int);
42: void del_callout(struct callout_req *);
43: void irq_timer(struct sigcontext *);
44: void timer_bh(void);
45: void callouts_bh(void);
46: void get_system_time(void);
47: void set_system_time(__time_t);
48: void timer_init(void);
49:
50: #endif /* _FIWIX_TIMER_H */

```

include/fiwix/times.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/times.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_TIMES_H
9: #define _FIWIX_TIMES_H
10:
11: struct tms {
12:     __clock_t tms_utime;    /* CPU time spent in user-mode */
13:     __clock_t tms_stime;    /* CPU time spent in kernel-mode */
14:     __clock_t tms_cutime;   /* (tms_utime + tms_cutime) of children */
15:     __clock_t tms_cstime;   /* (tms_stime + tms_cstime) of children */
16: };
17:
18: #endif /* _FIWIX_TIMES_H */
```

include/fiwix/traps.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/traps.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_TRAPS_H
9: #define _FIWIX_TRAPS_H
10:
11: #include <fiwix/sigcontext.h>
12:
13: #define NR_EXCEPTIONS    32
14:
15: struct traps {
16:     char *name;
17:     void (*handler)(unsigned int, struct sigcontext *);
18:     char errcode;
19: };
20:
21: void do_divide_error(unsigned int, struct sigcontext *);
22: void do_debug(unsigned int, struct sigcontext *);
23: void do_nmi_interrupt(unsigned int, struct sigcontext *);
24: void do_breakpoint(unsigned int, struct sigcontext *);
25: void do_overflow(unsigned int, struct sigcontext *);
26: void do_bound(unsigned int, struct sigcontext *);
27: void do_invalid_opcode(unsigned int, struct sigcontext *);
28: void do_no_math_coprocessor(unsigned int, struct sigcontext *);
29: void do_double_fault(unsigned int, struct sigcontext *);
30: void do_coprocessor_segment_overrun(unsigned int, struct sigcontext *);
31: void do_invalid_tss(unsigned int, struct sigcontext *);
32: void do_segment_not_present(unsigned int, struct sigcontext *);
33: void do_stack_segment_fault(unsigned int, struct sigcontext *);
34: void do_general_protection(unsigned int, struct sigcontext *);
35: void do_page_fault(unsigned int, struct sigcontext *);
36: void do_reserved(unsigned int, struct sigcontext *);
37: void do_floating_point_error(unsigned int, struct sigcontext *);
38: void do_alignment_check(unsigned int, struct sigcontext *);
39: void do_machine_check(unsigned int, struct sigcontext *);
40: void do_simd_fault(unsigned int, struct sigcontext *);
41:
42: void trap_handler(unsigned int, struct sigcontext);
43:
44: int dump_registers(unsigned int, struct sigcontext *);
45:
46: #endif /* _FIWIX_TRAPS_H */
```


include/fiwix/tty.h

Page 1/2

```

1: /*
2:  * fiwix/include/fiwix/tty.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_TTY_H
9: #define _FIWIX_TTY_H
10:
11: #include <fiwix/termios.h>
12: #include <fiwix/fs.h>
13:
14: #define NR_TTYS          15          /* maximum number of tty devices */
15:
16: #define CBSIZE           32          /* number of characters in cblock */
17: #define NR_CB_QUEUE     10          /* number of cblocks per queue */
18: #define CB_POOL_SIZE    128         /* number of cblocks in the central pool */
19:
20: #define LAST_CHAR(q)    ((q)->tail ? (q)->tail->data[(q)->tail->end_off - 1] : N
ULL)
21:
22: struct clist {
23:     unsigned short int count;
24:     unsigned short int cb_num;
25:     struct cblock *head;
26:     struct cblock *tail;
27: };
28:
29: struct cblock {
30:     unsigned short int start_off;
31:     unsigned short int end_off;
32:     unsigned char data[CBSIZE];
33:     struct cblock *prev;
34:     struct cblock *next;
35: };
36:
37: struct tty {
38:     __dev_t dev;
39:     struct clist read_q;
40:     struct clist cooked_q;
41:     struct clist write_q;
42:     unsigned short int count;
43:     struct termios termios;
44:     struct winsize winsize;
45:     __pid_t pid, pgid, sid;
46:     unsigned char lnext;
47:     void *driver_data;
48:     int canon_data;
49:
50:     /* formerly tty_operations */
51:     void (*stop)(struct tty *);
52:     void (*start)(struct tty *);
53:     void (*deltab)(struct tty *);
54:     void (*reset)(struct tty *);
55:     void (*input)(struct tty *);
56:     void (*output)(struct tty *);
57: };
58: extern struct tty tty_table[];
59:
60: int register_tty(__dev_t);
61: struct tty * get_tty(__dev_t);
62: void disassociate_ctty(struct tty *);
63: void termios_reset(struct tty *);
64: void do_cook(struct tty *);
65: int tty_putchar(struct tty *, unsigned char);
66: int tty_open(struct inode *, struct fd *);

```

include/fiwix/tty.h

Page 2/2

```
67: int tty_close(struct inode *, struct fd *);
68: int tty_read(struct inode *, struct fd *, char *, __size_t);
69: int tty_write(struct inode *, struct fd *, const char *, __size_t);
70: int tty_ioctl(struct inode *, int cmd, unsigned long int);
71: int tty_lseek(struct inode *, __off_t);
72: int tty_select(struct inode *, int);
73: void tty_init(void);
74:
75: int tty_queue_putchar(struct tty *, struct clist *, unsigned char);
76: int tty_queue_unputchar(struct clist *);
77: unsigned char tty_queue_getchar(struct clist *);
78: void tty_queue_flush(struct clist *);
79: void tty_queue_init(struct tty *);
80:
81: int vt_ioctl(struct tty *, int, unsigned long int);
82:
83: #endif /* _FIWIX_TTY_H */
```

include/fiwix/types.h

Page 1/1

```

1: /*
2:  * fiwix/include/fiwix/types.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_TYPES_H
9: #define _FIWIX_TYPES_H
10:
11: typedef __signed__ char __s8;
12: typedef unsigned char __u8;
13: typedef __signed__ short int __s16;
14: typedef unsigned short int __u16;
15: typedef __signed__ int __s32;
16: typedef unsigned int __u32;
17:
18: typedef __u16 __uid_t;
19: typedef __u16 __gid_t;
20: typedef __u32 __ino_t;
21: typedef __u16 __mode_t;
22: typedef __u16 __nlink_t;
23: typedef __u32 __off_t;
24: typedef __s32 __pid_t;
25: typedef __s32 __ssize_t;
26: typedef __u32 __size_t;
27: typedef unsigned long int __clock_t;
28: typedef __u32 __time_t;
29: typedef __u16 __dev_t;
30: typedef __u16 __key_t;
31: typedef __s32 __blk_t;          /* must be signed in order to return -EIO */
32: typedef __s32 __daddr_t;
33: typedef unsigned long long int __loff_t;
34:
35: /* number of descriptors that can fit in an 'fd_set' */
36: /* WARNING: this value must be the same as in the C Library */
37: #define __FD_SETSIZE      64
38:
39: #define __NFDBITS          (sizeof(unsigned long int) * 8)
40: #define __FDELTD(d)       ((d) / __NFDBITS)
41: #define __FDMASK(d)       (1 << ((d) % __NFDBITS))
42:
43: /* define the fd_set structure for select() */
44: typedef struct {
45:     unsigned long int fds_bits[__FD_SETSIZE / __NFDBITS];
46: } fd_set;
47:
48: #define __FD_ZERO(set)     (memset_b((void *) (set), 0, sizeof(fd_set)))
49: #define __FD_SET(d, set)  ((set)->fds_bits[__FDELTD(d)] |= __FDMASK(d))
50: #define __FD_CLR(d, set)  ((set)->fds_bits[__FDELTD(d)] &= ~__FDMASK(d))
51: #define __FD_ISSET(d, set) ((set)->fds_bits[__FDELTD(d)] & __FDMASK(d))
52:
53: #endif /* _FIWIX_TYPES_H */

```

include/fiwix/unistd.h

Page 1/4

```

1: /*
2:  * fiwix/include/fiwix/unistd.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_UNISTD_H
9: #define _FIWIX_UNISTD_H
10:
11: /* Linux 2.0.40 ABI (one syscall from Linux 2.2.26) */
12: /* #define SYS_setup */
13: #define SYS_exit 1
14: #define SYS_fork 2
15: #define SYS_read 3
16: #define SYS_write 4
17: #define SYS_open 5
18: #define SYS_close 6
19: #define SYS_waitpid 7
20: #define SYS_creat 8
21: #define SYS_link 9
22: #define SYS_unlink 10
23: #define SYS_execve 11
24: #define SYS_chdir 12
25: #define SYS_time 13
26: #define SYS_mknod 14
27: #define SYS_chmod 15
28: #define SYS_chown 16
29: #define SYS_break 17 /* -ENOSYS */
30: #define SYS_oldstat 18
31: #define SYS_lseek 19
32: #define SYS_getpid 20
33: #define SYS_mount 21
34: #define SYS_umount 22
35: #define SYS_setuid 23
36: #define SYS_getuid 24
37: #define SYS_stime 25
38: /* #define SYS_ptrace */
39: #define SYS_alarm 27
40: #define SYS_oldfstat 28
41: #define SYS_pause 29
42: #define SYS_utime 30
43: #define SYS_stty 31 /* -ENOSYS */
44: #define SYS_gtty 32 /* -ENOSYS */
45: #define SYS_access 33
46: /* #define SYS_nice */
47: #define SYS_ftime 35
48: #define SYS_sync 36
49: #define SYS_kill 37
50: #define SYS_rename 38
51: #define SYS_mkdir 39
52: #define SYS_rmdir 40
53: #define SYS_dup 41
54: #define SYS_pipe 42
55: #define SYS_times 43
56: #define SYS_prof 44 /* -ENOSYS */
57: #define SYS_brk 45
58: #define SYS_setgid 46
59: #define SYS_getgid 47
60: #define SYS_signal 48
61: #define SYS_geteuid 49
62: #define SYS_getegid 50
63: /* #define SYS_acct */
64: #define SYS_umount2 52 /* from 2.2.26, it was sys_phys() */
65: #define SYS_lock 53 /* -ENOSYS */
66: #define SYS_ioctl 54
67: #define SYS_fcntl 55

```

include/fiwix/unistd.h

Page 2/4

```

68: #define SYS_mpx 56 /* -ENOSYS */
69: #define SYS_setpgid 57
70: #define SYS_ulimit 58 /* -ENOSYS */
71: #define SYS_olduname 59
72: #define SYS_umask 60
73: #define SYS_chroot 61
74: #define SYS_ustat 62
75: #define SYS_dup2 63
76: #define SYS_getppid 64
77: #define SYS_getpgrp 65
78: #define SYS_setsid 66
79: #define SYS_sigaction 67
80: #define SYS_sgetmask 68
81: #define SYS_ssetmask 69
82: #define SYS_setreuid 70
83: #define SYS_setregid 71
84: #define SYS_sigsuspend 72
85: #define SYS_sigpending 73
86: #define SYS_sethostname 74
87: #define SYS_setrlimit 75
88: #define SYS_getrlimit 76
89: #define SYS_getrusage 77
90: #define SYS_gettimeofday 78
91: #define SYS_settimeofday 79
92: #define SYS_getgroups 80
93: #define SYS_setgroups 81
94: #define SYS_oldselect 82
95: #define SYS_symlink 83
96: #define SYS_oldlstat 84
97: #define SYS_readlink 85
98: /* #define SYS_uselib */
99: /* #define SYS_swapon */
100: #define SYS_reboot 88
101: /* #define SYS_oldreaddir */
102: #define SYS_old_mmap 90
103: #define SYS_munmap 91
104: #define SYS_truncate 92
105: #define SYS_ftruncate 93
106: #define SYS_fchmod 94
107: #define SYS_fchown 95
108: /* #define SYS_getpriority */
109: /* #define SYS_setpriority */
110: /* #define SYS_profil */
111: #define SYS_statfs 99
112: #define SYS_fstatfs 100
113: #define SYS_ioperm 101
114: #define SYS_socketcall 102
115: /* #define SYS_syslog */
116: #define SYS_setitimer 104
117: #define SYS_getitimer 105
118: #define SYS_newstat 106
119: #define SYS_newlstat 107
120: #define SYS_newfstat 108
121: #define SYS_uname 109
122: #define SYS_iopl 110
123: /* #define SYS_vhangup */
124: /* #define SYS_idle 112 -ENOSYS */
125: /* #define SYS_vm86old */
126: #define SYS_wait4 114
127: /* #define SYS_swapoff */
128: #define SYS_sysinfo 116
129: /* #define SYS_ipc */
130: #define SYS_fsync 118
131: #define SYS_sigreturn 119
132: /* #define SYS_clone */
133: #define SYS_setdomainname 121
134: #define SYS_newuname 122

```

include/fiwix/unistd.h

Page 3/4

```

135: /* #define SYS_modify_ldt */
136: /* #define SYS_adjtimex */
137: #define SYS_mprotect          125
138: #define SYS_sigprocmask      126
139: /* #define SYS_create_module */
140: /* #define SYS_init_module */
141: /* #define SYS_delete_module */
142: /* #define SYS_get_kernel_syms */
143: /* #define SYS_quotactl */
144: #define SYS_getpgid          132
145: #define SYS_fchdir           133
146: /* #define SYS_bdflush */
147: /* #define SYS_sysfs */
148: #define SYS_personality      136
149: /* #define afs_syscall */
150: #define SYS_setfsuid         138
151: #define SYS_setfsgid         139
152: #define SYS_llseek           140
153: #define SYS_getdents         141
154: #define SYS_select           142
155: #define SYS_flock            143
156: /* #define SYS_msync */
157: /* #define SYS_readv */
158: /* #define SYS_writev */
159: #define SYS_getsid           147
160: #define SYS_fdatasync        148
161: /* #define SYS_sysctl */
162: /* #define SYS_mlock */
163: /* #define SYS_munlock */
164: /* #define SYS_mlockall */
165: /* #define SYS_munlockall */
166: /* #define SYS_sched_setparam */
167: /* #define SYS_sched_getparam */
168: /* #define SYS_sched_setscheduler */
169: /* #define SYS_sched_getscheduler */
170: /* #define SYS_sched_yield */
171: /* #define SYS_sched_get_priority_max */
172: /* #define SYS_sched_get_priority_min */
173: /* #define SYS_sched_rr_get_interval */
174: #define SYS_nanosleep        162
175: /* #define SYS_mremap */
176:
177: /* extra system calls from Linux 2.2.26 */
178: /* #define SYS_mremap */
179: /* #define SYS_setresuid */
180: /* #define SYS_getresuid */
181: /* #define SYS_ni_syscall */
182: /* #define SYS_query_module */
183: /* #define SYS_poll */
184: /* #define SYS_nfsservctl */
185: /* #define SYS_setresgid */
186: /* #define SYS_getresgid */
187: /* #define SYS_prctl */
188: /* #define SYS_rt_sigreturn_wrapper */
189: /* #define SYS_rt_sigaction */
190: /* #define SYS_rt_sigprocmask */
191: /* #define SYS_rt_sigpending */
192: /* #define SYS_rt_sigtimedwait */
193: /* #define SYS_rt_sigqueueinfo */
194: /* #define SYS_rt_sigsuspend_wrapper */
195: /* #define SYS_pread */
196: /* #define SYS_pwrite */
197: /* #define SYS_chown */
198: #define SYS_getcwd           183
199: /* #define SYS_capget */
200: /* #define SYS_capset */
201: /* #define SYS_sigaltstack_wrapper */

```

include/fiwix/unistd.h

Page 4/4

```
202: /* #define SYS_sendfile */
203: /* #define SYS_ni_syscall */
204: /* #define SYS_ni_syscall */
205: #define SYS_vfork                190
206:
207: #endif /* _FIWIX_UNISTD_H */
```

include/fiwix/ustat.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/ustat.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_USTAT_H
9: #define _FIWIX_USTAT_H
10:
11: #include <fiwix/types.h>
12:
13: struct ustat {
14:     __daddr_t f_tfree;        /* total free blocks */
15:     __ino_t f_tinode;        /* number of free inodes */
16:     char f_fname;            /* filesystem name */
17:     char f_fpack;            /* filesystem pack name */
18: };
19:
20: #endif /* _FIWIX_USTAT_H */
```


include/fiwix/utime.h

Page 1/1

```
1: /*
2:  * fiwix/include/fiwix/utime.h
3:  *
4:  * Copyright 2018, Jordi Sanfeliu. All rights reserved.
5:  * Distributed under the terms of the Fiwix License.
6:  */
7:
8: #ifndef _FIWIX_UTIME_H
9: #define _FIWIX_UTIME_H
10:
11: #include <fiwix/types.h>
12:
13: struct utimbuf {
14:     __time_t actime;           /* access time */
15:     __time_t modtime;        /* modification time */
16: };
17:
18: #endif /* _FIWIX_UTIME_H */
```

include/fiwix/utsname.h

Page 1/2

```

1:  /* Copyright (C) 1991, 1992, 1994, 1996 Free Software Foundation, Inc.
2:    This file is part of the GNU C Library.
3:
4:    The GNU C Library is free software; you can redistribute it and/or
5:    modify it under the terms of the GNU Library General Public License as
6:    published by the Free Software Foundation; either version 2 of the
7:    License, or (at your option) any later version.
8:
9:    The GNU C Library is distributed in the hope that it will be useful,
10:   but WITHOUT ANY WARRANTY; without even the implied warranty of
11:   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
12:   Library General Public License for more details.
13:
14:   You should have received a copy of the GNU Library General Public
15:   License along with the GNU C Library; see the file COPYING.LIB.  If not,
16:   write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330,
17:   Boston, MA 02111-1307, USA.  */
18:
19:  /*
20:   *      POSIX Standard: 4.4 System Identification      <fiwix/utsname.h>
21:   */
22:
23:  #ifndef _FIWIX_UTSNAME_H
24:  #define _FIWIX_UTSNAME_H
25:
26:  #define _OLD_UTSNAME_LENGTH      9
27:  #define _UTSNAME_LENGTH         65
28:
29:  #ifndef _UTSNAME_NODENAME_LENGTH
30:  #define _UTSNAME_NODENAME_LENGTH _UTSNAME_LENGTH
31:  #endif
32:
33:  /* Very OLD structure describing the system and machine.  */
34:  struct oldold_utsname
35:  {
36:      char sysname[_OLD_UTSNAME_LENGTH];
37:      char nodename[_OLD_UTSNAME_LENGTH];
38:      char release[_OLD_UTSNAME_LENGTH];
39:      char version[_OLD_UTSNAME_LENGTH];
40:      char machine[_OLD_UTSNAME_LENGTH];
41:  };
42:
43:  /* OLD structure describing the system and machine.  */
44:  struct old_utsname
45:  {
46:      char sysname[_UTSNAME_LENGTH];
47:      char nodename[_UTSNAME_NODENAME_LENGTH];
48:      char release[_UTSNAME_LENGTH];
49:      char version[_UTSNAME_LENGTH];
50:      char machine[_UTSNAME_LENGTH];
51:  };
52:
53:  /* NEW structure describing the system and machine.  */
54:  struct new_utsname
55:  {
56:      /* Name of the implementation of the operating system.  */
57:      char sysname[_UTSNAME_LENGTH];
58:
59:      /* Name of this node on the network.  */
60:      char nodename[_UTSNAME_NODENAME_LENGTH];
61:
62:      /* Current release level of this implementation.  */
63:      char release[_UTSNAME_LENGTH];
64:      /* Current version level of this release.  */
65:      char version[_UTSNAME_LENGTH];
66:
67:      /* Name of the hardware type the system is running on.  */

```

include/fiwix/utsname.h

Page 2/2

```
68:     char machine[_UTSNAME_LENGTH];
69:     char domainname[_UTSNAME_LENGTH];
70: };
71:
72: extern struct new_utsname sys_utsname;
73: extern char UTS_MACHINE[_UTSNAME_LENGTH];
74:
75: #endif /* _FIWIX_UTSNAME_H */
```

include/fiwix/version.h

Page 1/1

```
1: #define UTS_VERSION "Sat Apr 21 09:32:24 CEST 2018"
```

include/fiwix/vt.h

Page 1/1

```

1: #ifndef VT_H
2: #define VT_H
3:
4: /* prefix 0x56 is 'V', to avoid collision with terminos and kd */
5:
6: #define VT_OPENQRY      0x5600 /* find available vt */
7:
8: struct vt_mode {
9:     char mode; /* vt mode */
10:    char waitv; /* if set, hang on writes if not active */
11:    short int relsig; /* signal to raise on release req */
12:    short int acqsig; /* signal to raise on acquisition */
13:    short int frsig; /* unused (set to 0) */
14: };
15: #define VT_GETMODE      0x5601 /* get mode of active vt */
16: #define VT_SETMODE      0x5602 /* set mode of active vt */
17: #define VT_AUTO          0x00 /* auto vt switching */
18: #define VT_PROCESS       0x01 /* process controls switching */
19: #define VT_ACKACQ       0x02 /* acknowledge switch */
20:
21: struct vt_stat {
22:    unsigned short int v_active; /* active vt */
23:    unsigned short int v_signal; /* signal to send */
24:    unsigned short int v_state; /* vt bitmask */
25: };
26: #define VT_GETSTATE     0x5603 /* get global vt state info */
27: #define VT_SENDSIG      0x5604 /* signal to send to bitmask of vts */
28:
29: #define VT_RELDISP      0x5605 /* release display */
30:
31: #define VT_ACTIVATE     0x5606 /* make vt active */
32: #define VT_WAITACTIVE   0x5607 /* wait for vt active */
33: #define VT_DISALLOCATE  0x5608 /* free memory associated to vt */
34:
35: struct vt_sizes {
36:    unsigned short int v_rows; /* number of rows */
37:    unsigned short int v_cols; /* number of columns */
38:    unsigned short int v_scrollsize; /* number of lines of scrollbar */
39: };
40: #define VT_RESIZE       0x5609 /* set kernel's idea of screensize */
41:
42: struct vt_consize {
43:    unsigned short int v_rows; /* number of rows */
44:    unsigned short int v_cols; /* number of columns */
45:    unsigned short int v_vlin; /* number of pixel rows on screen */
46:    unsigned short int v_clin; /* number of pixel rows per character */
47:    unsigned short int v_vcol; /* number of pixel columns on screen */
48:    unsigned short int v_ccol; /* number of pixel columns per character */
49: };
50: #define VT_RESIZEX      0x560A /* set kernel's idea of screensize + more */
51: #define VT_LOCKSWITCH  0x560B /* disallow vt switching */
52: #define VT_UNLOCKSWITCH 0x560C /* allow vt switching */
53:
54: #endif /* VT_H */

```

README

Page 1/3

```

1:          Fiwix kernel release 1.0.0
2:          ~~~~~
3:
4: Fiwix is an operating system kernel, written by Jordi Sanfeliu from scratch,
5: based on the UNIX architecture and fully focused on being POSIX compatible.
6: It is designed and developed mainly as a hobby OS but also for educational
7: purposes, therefore the kernel code is kept as simple as possible.
8:
9: It runs on the i386 (x86 32bit) hardware architecture and is compatible with
10: a good base of existing GNU applications. It offers many UNIX-like features:
11:
12: - Mostly written in C language (Assembler only used in the needed parts).
13: - GRUB Multiboot Specification v1 compliant.
14: - Full 32bit protected mode non-preemptive kernel.
15: - For i386 processors and higher.
16: - Preemptive multitasking.
17: - Protected task environment (independent memory address per process).
18: - Interrupt and exception handling.
19: - POSIX-compliant (mostly).
20: - Process groups, sessions and job control.
21: - Interprocess communication with pipes and signals.
22: - BSD file locking mechanism (POSIX restricted to file and advisory only).
23: - Virtual memory management up to 4GB (1GB physical only and no swapping yet).
24: - Demand paging with Copy-On-Write feature.
25: - Linux 2.0 ABI system calls compatibility (mostly).
26: - ELF-386 executable format support (statically and dynamically linked).
27: - Round Robin based scheduler algorithm (no priorities yet).
28: - VFS abstraction layer.
29: - Minix v1 and v2 filesystem support.
30: - EXT2 filesystem support (read only) with 1KB, 2KB and 4KB block sizes.
31: - Linux-like PROC filesystem support (read only).
32: - PIPE pseudo-filesystem support.
33: - ISO9660 filesystem support with Rock Ridge extensions.
34: - RAMdisk device support.
35: - SVGAlib based applications support.
36: - Keyboard driver with Linux keymaps support.
37: - Parallel port printer driver support.
38: - Floppy disk device driver and DMA management.
39: - IDE/ATA hard disk device driver.
40: - IDE/ATA ATAPI CDROM device driver.
41:
42: Fiwix is distributed under the terms of the MIT License, see the LICENSE file
43: for more details.
44:
45:
46: COMPILING
47: =====
48: Before compiling you might want to tweak the kernel configuration by changing
49: the values in the 'include/fiwix/config.h' file.
50:
51: The command needed to make a full compilation of the Fiwix kernel is:
52:
53: make clean ; make
54:
55: This will create the files 'fiwix' (the kernel itself) and 'System.map.gz' (the
56: symbol table) in the root directory of the source code tree.
57:
58: Keep in mind that the kernel doesn't do anything on its own, you need to create
59: a user-space environment to make use of it. Upon booting, the kernel mounts the
60: root filesystem and tries to run '/sbin/init' on it, so you need to provide this
61: program yourself.
62:
63:
64: TESTING
65: =====
66: To create a complete bootable floppy disk you need to download the Fiwix Test
67: Suite archive and symlink the directory 'tools/' into the root directory of the

```

README

Page 2/3

```
68: kernel source code. Then insert a floppy disk into the drive and then type the
69: following:
70:
71: make floppy
72:
73: If you only want to update an existing floppy disk with a newer or modified
74: kernel version, then type the following:
75:
76: make floppy_update
77:
78:
79: If you don't have a floppy drive but a bootable CDROM IDE/ATA drive, you can
80: create your own Fiwix Installation CDROM by using your current operating system
81: (i.e. GNU/Linux). To do this, you might want to use the scripts and tools that
82: come with the Fiwix Test Suite archive.
83:
84: The scripts to create such bootable images cannot be executed under Fiwix
85: because they need support for the loop device and the ISO9660 creation tools.
86:
87: To create your own bootable CDROM ISO image you must do the following steps:
88:
89: 1. Download the Fiwix Installation CDROM ISO image.
90: 2. Download the Fiwix floppy image or create a new one with 'make_image'.
91: 3. Edit the 'make_cdrom' script and adjust the values of the $INSTALLCD and
92:    $FIWIX_VERSION variables.
93: 4. Execute './make_cdrom'.
94:
95:
96: INSTALLING
97: =====
98: Please keep in mind that this is a kernel in its very early stages and may well
99: have serious bugs and broken features which have not yet been identified or
100: resolved.
101:
102: Let me repeat that.
103:
104: Please keep in mind that this is a kernel in its very early stages and may well
105: have serious bugs and broken features which have not yet been identified or
106: resolved.
107:
108:          *****
109:          *** USE AT YOUR OWN RISK! ***
110:          *****
111:
112:
113: You can proceed to install the Fiwix OS on a hard disk either once booted from
114: the floppy or from the Live CDROM. If you chosen the former, you will also need
115: the Live CDROM inserted in order to install the packages that form all the
116: system environment.
117:
118: I recommend using QEMU or VMware Player, but if you want to use it on a real
119: hardware you will need a PC with either a bootable floppy 1.44MB drive or an
120: IDE/ATAPI CDROM drive.
121:
122: The minimal requirements to use Fiwix are as follows:
123:
124: - Standard IBM PC-AT architecture.
125: - i386 processor or higher.
126: - 2MB of RAM memory (64MB recommended).
127: - Floppy disk (3.5", 1.44MB) or IDE/ATAPI CDROM.
128: - 500MB IDE Hard disk (1GB recommended).
129:
130: Let the system boot either from a floppy or a CDROM, and when you are ready
131: just type:
132:
133: install.sh
134:
```

README

Page 3/3

```
135:
136: Happy hacking.
137:
138: --
139: Copyright (C) 2018, Jordi Sanfeliu.
140: http://www.fiwix.org
141:
```


LICENSE

Page 1/1

1: **Copyright** (c) 2018 Jordi Sanfeliu
2:
3: Permission is hereby granted, free of charge, to any person obtaining a copy
4: of this software and associated documentation **files** (the "**Software**"), to deal
5: in the Software without restriction, including without limitation the rights
6: to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
7: copies of the Software, and to permit persons to whom the Software is
8: furnished to **do** so, subject to the following conditions:
9:
10: The above copyright notice and this permission notice shall be included in all
11: copies or substantial portions of the Software.
12:
13: THE SOFTWARE IS PROVIDED "**AS IS**", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
14: IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
15: FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
16: AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
17: LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
18: OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
19: SOFTWARE.

CODING

```
1: Fiwix kernel coding standards
2: -----
3: It's easier on everyone if all authors working on a shared code base are
4: consistent in the way they write their programs. Fiwix has the following
5: conventions in its code:
6:
7: - Use of snake_case (multi-word names are lower_case_with_underscores) for
8:   everything except for macro and constant names.
9:
10: - No space after the name of a function in a call.
11:   For example, printk("hello") not printk ("hello").
12:
13: - No space after keywords "if", "for", "while", "switch".
14:   For example, if(x) not if (x).
15:
16: - Space before braces.
17:   For example, if(x) { not if(x){.
18:
19: - Space between operands.
20:   For example, for(n = 0; n < 10; n++), not for(n=0;n<10;n++).
21:
22: - Beginning-of-line indentation via tabs, not spaces.
23:
24: - Preprocessor macros are always UPPERCASE.
25:
26: - Pointer types have spaces: (uint16_t *) not (uint16_t*).
27:
28: - Comments in code are always as in C89 /* ... */.
29:
30: - Multiline comments start always with a capital letter and the last sentence
31:   ends with a period.
32:
33: - In a function definition, the function name starts a new line.
34:   Then you can grep -n '^foo' /*.c to find the definition of foo.
35:
36: - Functions that take no arguments are declared as f(void) not f().
37:
38:
```

THANKS

Page 1/1

```
1: THANKS!  
2:  
3: A huge THANKS to all people who created their own hobby, and not so hobby,  
4: operating systems and made them freely available on Internet.  
5:  
6: From those simple "Hello world!\n" kernels to a real self-hosting operating  
7: system, their projects were a invaluable source of information and inspiration  
8: to create the Fiwix kernel.  
9:  
10: A special thanks to OSDEV Community for their tutorials, documents, wikis, etc.  
11:  
12: Jordi Sanfeliu  
13: http://www.fiwix.org  
14:
```

Table of Contents

Page -1/5

1	Makefile	1	pages	55	lines	18/04/21	18:45:47
2	fiwix.ld	1	pages	55	lines	18/04/21	18:45:47
3	kernel/boot.S	3	pages	151	lines	18/04/21	18:45:47
4	kernel/cmos.c	1	pages	57	lines	18/04/21	18:45:47
5	kernel/core386.S	15	pages	943	lines	18/04/21	18:45:47
6	kernel/cpu.c	5	pages	263	lines	18/04/21	18:45:47
7	kernel/gdt.c	1	pages	54	lines	18/04/21	18:45:47
8	kernel/idt.c	2	pages	93	lines	18/04/21	18:45:47
9	kernel/init.c	2	pages	125	lines	18/04/21	18:45:47
10	kernel/main.c	6	pages	337	lines	18/04/21	18:45:47
11	kernel/Makefile	1	pages	20	lines	18/04/21	18:45:47
12	kernel/pic.c	5	pages	266	lines	18/04/21	18:45:47
13	kernel/pit.c	1	pages	29	lines	18/04/21	18:45:47
14	kernel/process.c	7	pages	399	lines	18/04/21	18:45:47
15	kernel/sched.c	2	pages	85	lines	18/04/21	18:45:47
16	kernel/signal.c	4	pages	202	lines	18/04/21	18:45:47
17	kernel/sleep.c	3	pages	198	lines	18/04/21	18:45:47
18	kernel/syscalls	0	pages	0	lines	18/04/21	18:45:47
19	kernel/syscalls.c	7	pages	407	lines	18/04/21	18:45:47
20	kernel/timer.c	7	pages	451	lines	18/04/21	18:45:47
21	kernel/traps.c	6	pages	341	lines	18/04/21	18:45:47
22	kernel/syscalls/access.c	1	pages	61	lines	18/04/21	18:45:47
23	kernel/syscalls/alarm.c	1	pages	39	lines	18/04/21	18:45:47
24	kernel/syscalls/brk.c	1	pages	54	lines	18/04/21	18:45:47
25	kernel/syscalls/chdir.c	1	pages	49	lines	18/04/21	18:45:47
26	kernel/syscalls/chmod.c	1	pages	56	lines	18/04/21	18:45:47
27	kernel/syscalls/chown.c	2	pages	68	lines	18/04/21	18:45:47
28	kernel/syscalls/chroot.c	1	pages	44	lines	18/04/21	18:45:47
29	kernel/syscalls/close.c	1	pages	39	lines	18/04/21	18:45:47
30	kernel/syscalls/creat.c	1	pages	23	lines	18/04/21	18:45:47
31	kernel/syscalls/dup2.c	1	pages	41	lines	18/04/21	18:45:47
32	kernel/syscalls/dup.c	1	pages	37	lines	18/04/21	18:45:47
33	kernel/syscalls/execve.c	2	pages	83	lines	18/04/21	18:45:47
34	kernel/syscalls/exit.c	2	pages	118	lines	18/04/21	18:45:47
35	kernel/syscalls/fchdir.c	1	pages	34	lines	18/04/21	18:45:47
36	kernel/syscalls/fchmod.c	1	pages	42	lines	18/04/21	18:45:47
37	kernel/syscalls/fchown.c	1	pages	53	lines	18/04/21	18:45:47
38	kernel/syscalls/fcntl.c	2	pages	64	lines	18/04/21	18:45:47
39	kernel/syscalls/fdatasync.c	1	pages	22	lines	18/04/21	18:45:47
40	kernel/syscalls/flock.c	1	pages	28	lines	18/04/21	18:45:47
41	kernel/syscalls/fork.c	3	pages	155	lines	18/04/21	18:45:47
42	kernel/syscalls/fstat.c	1	pages	44	lines	18/04/21	18:45:47
43	kernel/syscalls/fstatfs.c	1	pages	36	lines	18/04/21	18:45:47
44	kernel/syscalls/fsync.c	1	pages	39	lines	18/04/21	18:45:47
45	kernel/syscalls/ftime.c	1	pages	34	lines	18/04/21	18:45:47
46	kernel/syscalls/ftruncate.c	1	pages	53	lines	18/04/21	18:45:47
47	kernel/syscalls/getcwd.c	1	pages	29	lines	18/04/21	18:45:47
48	kernel/syscalls/getdents.c	1	pages	45	lines	18/04/21	18:45:47
49	kernel/syscalls/getegid.c	1	pages	20	lines	18/04/21	18:45:47
50	kernel/syscalls/geteuid.c	1	pages	20	lines	18/04/21	18:45:47
51	kernel/syscalls/getgid.c	1	pages	20	lines	18/04/21	18:45:47
52	kernel/syscalls/getgroups.c	1	pages	40	lines	18/04/21	18:45:47
53	kernel/syscalls/getitimer.c	1	pages	48	lines	18/04/21	18:45:47
54	kernel/syscalls/getpgid.c	1	pages	37	lines	18/04/21	18:45:47
55	kernel/syscalls/getpgrp.c	1	pages	20	lines	18/04/21	18:45:47
56	kernel/syscalls/getpid.c	1	pages	20	lines	18/04/21	18:45:47
57	kernel/syscalls/getppid.c	1	pages	20	lines	18/04/21	18:45:47
58	kernel/syscalls/getrlimit.c	1	pages	35	lines	18/04/21	18:45:47
59	kernel/syscalls/getrusage.c	1	pages	40	lines	18/04/21	18:45:47
60	kernel/syscalls/getsid.c	1	pages	38	lines	18/04/21	18:45:47
61	kernel/syscalls/gettimeofday.c	1	pages	41	lines	18/04/21	18:45:47
62	kernel/syscalls/getuid.c	1	pages	21	lines	18/04/21	18:45:47
63	kernel/syscalls/ioctl.c	1	pages	41	lines	18/04/21	18:45:47
64	kernel/syscalls/ioperm.c	1	pages	28	lines	18/04/21	18:45:47
65	kernel/syscalls/iopl.c	1	pages	58	lines	18/04/21	18:45:47
66	kernel/syscalls/kill.c	1	pages	46	lines	18/04/21	18:45:47
67	kernel/syscalls/link.c	2	pages	113	lines	18/04/21	18:45:47

Table of Contents

68	kernel/syscalls/llseek.c	1 pages	56 lines	18/04/21	18:45:47
69	kernel/syscalls/lseek.c	1 pages	58 lines	18/04/21	18:45:47
70	kernel/syscalls/lstat.c	1 pages	51 lines	18/04/21	18:45:47
71	kernel/syscalls/Makefile	1 pages	20 lines	18/04/21	18:45:47
72	kernel/syscalls/mkdir.c	1 pages	66 lines	18/04/21	18:45:47
73	kernel/syscalls/mknod.c	2 pages	71 lines	18/04/21	18:45:47
74	kernel/syscalls/mount.c	4 pages	221 lines	18/04/21	18:45:47
75	kernel/syscalls/mprotect.c	1 pages	49 lines	18/04/21	18:45:47
76	kernel/syscalls/munmap.c	1 pages	22 lines	18/04/21	18:45:47
77	kernel/syscalls/nanosleep.c	1 pages	50 lines	18/04/21	18:45:47
78	kernel/syscalls/newfstat.c	1 pages	56 lines	18/04/21	18:45:47
79	kernel/syscalls/newlstat.c	1 pages	64 lines	18/04/21	18:45:47
80	kernel/syscalls/newstat.c	1 pages	64 lines	18/04/21	18:45:47
81	kernel/syscalls/newuname.c	1 pages	34 lines	18/04/21	18:45:47
82	kernel/syscalls/old_mmap.c	1 pages	52 lines	18/04/21	18:45:47
83	kernel/syscalls/old_select.c	1 pages	42 lines	18/04/21	18:45:47
84	kernel/syscalls/olduname.c	1 pages	39 lines	18/04/21	18:45:47
85	kernel/syscalls/open.c	3 pages	143 lines	18/04/21	18:45:47
86	kernel/syscalls/pause.c	1 pages	30 lines	18/04/21	18:45:47
87	kernel/syscalls/personality.c	1 pages	19 lines	18/04/21	18:45:47
88	kernel/syscalls/pipe.c	2 pages	71 lines	18/04/21	18:45:47
89	kernel/syscalls/read.c	1 pages	49 lines	18/04/21	18:45:47
90	kernel/syscalls/readlink.c	1 pages	57 lines	18/04/21	18:45:47
91	kernel/syscalls/reboot.c	1 pages	49 lines	18/04/21	18:45:47
92	kernel/syscalls/rename.c	2 pages	117 lines	18/04/21	18:45:47
93	kernel/syscalls/rmdir.c	2 pages	87 lines	18/04/21	18:45:47
94	kernel/syscalls/select.c	3 pages	166 lines	18/04/21	18:45:47
95	kernel/syscalls/setdomainname.c	1 pages	38 lines	18/04/21	18:45:47
96	kernel/syscalls/setfsuid.c	1 pages	21 lines	18/04/21	18:45:47
97	kernel/syscalls/setfsuid.c	1 pages	21 lines	18/04/21	18:45:47
98	kernel/syscalls/setgid.c	1 pages	32 lines	18/04/21	18:45:47
99	kernel/syscalls/setgroups.c	1 pages	41 lines	18/04/21	18:45:47
100	kernel/syscalls/sethostname.c	1 pages	42 lines	18/04/21	18:45:47
101	kernel/syscalls/setitimer.c	1 pages	31 lines	18/04/21	18:45:47
102	kernel/syscalls/setpgid.c	2 pages	67 lines	18/04/21	18:45:47
103	kernel/syscalls/setregid.c	1 pages	49 lines	18/04/21	18:45:47
104	kernel/syscalls/setreuid.c	1 pages	49 lines	18/04/21	18:45:47
105	kernel/syscalls/setrlimit.c	1 pages	42 lines	18/04/21	18:45:47
106	kernel/syscalls/setsid.c	1 pages	36 lines	18/04/21	18:45:47
107	kernel/syscalls/settimeofday.c	1 pages	46 lines	18/04/21	18:45:47
108	kernel/syscalls/setuid.c	1 pages	31 lines	18/04/21	18:45:47
109	kernel/syscalls/sgetmask.c	1 pages	20 lines	18/04/21	18:45:47
110	kernel/syscalls/sigaction.c	1 pages	54 lines	18/04/21	18:45:47
111	kernel/syscalls/signal.c	1 pages	56 lines	18/04/21	18:45:47
112	kernel/syscalls/sigpending.c	1 pages	30 lines	18/04/21	18:45:47
113	kernel/syscalls/sigprocmask.c	1 pages	51 lines	18/04/21	18:45:47
114	kernel/syscalls/sigreturn.c	1 pages	31 lines	18/04/21	18:45:47
115	kernel/syscalls/sigsuspend.c	1 pages	44 lines	18/04/21	18:45:47
116	kernel/syscalls/socketcall.c	1 pages	24 lines	18/04/21	18:45:47
117	kernel/syscalls/ssetmask.c	1 pages	26 lines	18/04/21	18:45:47
118	kernel/syscalls/stat.c	1 pages	52 lines	18/04/21	18:45:47
119	kernel/syscalls/statfs.c	1 pages	47 lines	18/04/21	18:45:47
120	kernel/syscalls/stime.c	1 pages	35 lines	18/04/21	18:45:47
121	kernel/syscalls/symlink.c	2 pages	73 lines	18/04/21	18:45:47
122	kernel/syscalls/sync.c	1 pages	27 lines	18/04/21	18:45:47
123	kernel/syscalls/sysinfo.c	1 pages	52 lines	18/04/21	18:45:47
124	kernel/syscalls/time.c	1 pages	37 lines	18/04/21	18:45:47
125	kernel/syscalls/times.c	1 pages	37 lines	18/04/21	18:45:47
126	kernel/syscalls/truncate.c	1 pages	66 lines	18/04/21	18:45:47
127	kernel/syscalls/umask.c	1 pages	27 lines	18/04/21	18:45:47
128	kernel/syscalls/umount2.c	2 pages	115 lines	18/04/21	18:45:47
129	kernel/syscalls/umount.c	1 pages	22 lines	18/04/21	18:45:47
130	kernel/syscalls/uname.c	1 pages	34 lines	18/04/21	18:45:47
131	kernel/syscalls/unlink.c	2 pages	78 lines	18/04/21	18:45:47
132	kernel/syscalls/ustat.c	1 pages	44 lines	18/04/21	18:45:47
133	kernel/syscalls/utime.c	2 pages	72 lines	18/04/21	18:45:47
134	kernel/syscalls/wait4.c	2 pages	98 lines	18/04/21	18:45:47

Table of Contents

Page -3/5

135	kernel/syscalls/waitpid.c	1	pages	23	lines	18/04/21	18:45:47
136	kernel/syscalls/write.c	1	pages	49	lines	18/04/21	18:45:47
137	drivers/block/dma.c	2	pages	93	lines	18/04/21	18:45:47
138	drivers/block/floppy.c	14	pages	858	lines	18/04/21	18:45:47
139	drivers/block/ide.c	14	pages	833	lines	18/04/21	18:45:47
140	drivers/block/ide_cd.c	9	pages	528	lines	18/04/21	18:45:47
141	drivers/block/ide_hd.c	9	pages	509	lines	18/04/21	18:45:47
142	drivers/block/Makefile	1	pages	19	lines	18/04/21	18:45:47
143	drivers/block/part.c	1	pages	34	lines	18/04/21	18:45:47
144	drivers/block/ramdisk.c	3	pages	186	lines	18/04/21	18:45:47
145	drivers/char/console.c	19	pages	1168	lines	18/04/21	18:45:47
146	drivers/char/defkeymap.c	5	pages	149	lines	18/04/21	18:45:47
147	drivers/char/keyboard.c	11	pages	686	lines	18/04/21	18:45:47
148	drivers/char/lp.c	4	pages	216	lines	18/04/21	18:45:47
149	drivers/char/Makefile	1	pages	19	lines	18/04/21	18:45:47
150	drivers/char/memdev.c	7	pages	427	lines	18/04/21	18:45:47
151	drivers/char/tty.c	14	pages	863	lines	18/04/21	18:45:47
152	drivers/char/tty_queue.c	4	pages	259	lines	18/04/21	18:45:47
153	drivers/char/vt.c	4	pages	197	lines	18/04/21	18:45:47
154	fs/buffer.c	7	pages	443	lines	18/04/21	18:45:47
155	fs/devices.c	6	pages	348	lines	18/04/21	18:45:47
156	fs/elf.c	12	pages	719	lines	18/04/21	18:45:47
157	fs/ext2	0	pages	0	lines	18/04/21	18:45:47
158	fs/fd.c	1	pages	50	lines	18/04/21	18:45:47
159	fs/filesystems.c	2	pages	81	lines	18/04/21	18:45:47
160	fs/inode.c	7	pages	459	lines	18/04/21	18:45:47
161	fs/iso9660	0	pages	0	lines	18/04/21	18:45:47
162	fs/locks.c	4	pages	208	lines	18/04/21	18:45:47
163	fs/Makefile	1	pages	25	lines	18/04/21	18:45:47
164	fs/minix	0	pages	0	lines	18/04/21	18:45:47
165	fs/namei.c	3	pages	178	lines	18/04/21	18:45:47
166	fs/pipefs	0	pages	0	lines	18/04/21	18:45:47
167	fs/procfs	0	pages	0	lines	18/04/21	18:45:47
168	fs/super.c	4	pages	223	lines	18/04/21	18:45:47
169	fs/ext2/dir.c	3	pages	142	lines	18/04/21	18:45:47
170	fs/ext2/file.c	2	pages	78	lines	18/04/21	18:45:47
171	fs/ext2/inode.c	4	pages	200	lines	18/04/21	18:45:47
172	fs/ext2/Makefile	1	pages	19	lines	18/04/21	18:45:47
173	fs/ext2/namei.c	2	pages	79	lines	18/04/21	18:45:47
174	fs/ext2/super.c	3	pages	142	lines	18/04/21	18:45:47
175	fs/ext2/symlink.c	3	pages	134	lines	18/04/21	18:45:47
176	fs/iso9660/dir.c	3	pages	173	lines	18/04/21	18:45:47
177	fs/iso9660/file.c	2	pages	78	lines	18/04/21	18:45:47
178	fs/iso9660/inode.c	3	pages	184	lines	18/04/21	18:45:47
179	fs/iso9660/Makefile	1	pages	19	lines	18/04/21	18:45:47
180	fs/iso9660/namei.c	3	pages	122	lines	18/04/21	18:45:47
181	fs/iso9660/rrip.c	6	pages	340	lines	18/04/21	18:45:47
182	fs/iso9660/super.c	4	pages	224	lines	18/04/21	18:45:47
183	fs/iso9660/symlink.c	2	pages	109	lines	18/04/21	18:45:47
184	fs/minix/bitmaps.c	3	pages	166	lines	18/04/21	18:45:47
185	fs/minix/dir.c	3	pages	144	lines	18/04/21	18:45:47
186	fs/minix/file.c	3	pages	133	lines	18/04/21	18:45:47
187	fs/minix/inode.c	2	pages	75	lines	18/04/21	18:45:47
188	fs/minix/Makefile	1	pages	19	lines	18/04/21	18:45:47
189	fs/minix/namei.c	11	pages	699	lines	18/04/21	18:45:47
190	fs/minix/super.c	5	pages	267	lines	18/04/21	18:45:47
191	fs/minix/symlink.c	3	pages	136	lines	18/04/21	18:45:47
192	fs/minix/v1_inode.c	7	pages	407	lines	18/04/21	18:45:47
193	fs/minix/v2_inode.c	8	pages	471	lines	18/04/21	18:45:47
194	fs/pipefs/fifo.c	2	pages	73	lines	18/04/21	18:45:47
195	fs/pipefs/Makefile	1	pages	19	lines	18/04/21	18:45:47
196	fs/pipefs/pipe.c	4	pages	202	lines	18/04/21	18:45:47
197	fs/pipefs/super.c	2	pages	113	lines	18/04/21	18:45:47
198	fs/procfs/data.c	12	pages	729	lines	18/04/21	18:45:47
199	fs/procfs/dir.c	5	pages	261	lines	18/04/21	18:45:47
200	fs/procfs/file.c	2	pages	124	lines	18/04/21	18:45:47
201	fs/procfs/inode.c	2	pages	89	lines	18/04/21	18:45:47

Table of Contents

Page -4/5

202	fs/procfs/Makefile	1	pages	19	lines	18/04/21	18:45:47
203	fs/procfs/namei.c	2	pages	89	lines	18/04/21	18:45:47
204	fs/procfs/super.c	2	pages	82	lines	18/04/21	18:45:47
205	fs/procfs/symlink.c	3	pages	136	lines	18/04/21	18:45:47
206	fs/procfs/tree.c	2	pages	114	lines	18/04/21	18:45:47
207	mm/alloc.c	1	pages	35	lines	18/04/21	18:45:47
208	mm/bios_map.c	2	pages	90	lines	18/04/21	18:45:47
209	mm/fault.c	5	pages	261	lines	18/04/21	18:45:47
210	mm/Makefile	1	pages	19	lines	18/04/21	18:45:47
211	mm/memory.c	7	pages	430	lines	18/04/21	18:45:47
212	mm/mmap.c	8	pages	511	lines	18/04/21	18:45:47
213	mm/page.c	7	pages	443	lines	18/04/21	18:45:47
214	mm/swapper.c	1	pages	62	lines	18/04/21	18:45:47
215	lib/ctype.c	3	pages	140	lines	18/04/21	18:45:47
216	lib/Makefile	1	pages	19	lines	18/04/21	18:45:47
217	lib/printk.c	6	pages	369	lines	18/04/21	18:45:47
218	lib/strings.c	5	pages	280	lines	18/04/21	18:45:47
219	include/fiwix/asm.h	3	pages	136	lines	18/04/21	18:45:47
220	include/fiwix/bios.h	1	pages	29	lines	18/04/21	18:45:47
221	include/fiwix/buffer.h	1	pages	43	lines	18/04/21	18:45:47
222	include/fiwix/cmos.h	1	pages	58	lines	18/04/21	18:45:47
223	include/fiwix/config.h	1	pages	55	lines	18/04/21	18:45:47
224	include/fiwix/console.h	2	pages	130	lines	18/04/21	18:45:47
225	include/fiwix/const.h	1	pages	20	lines	18/04/21	18:45:47
226	include/fiwix/cpu.h	2	pages	68	lines	18/04/21	18:45:47
227	include/fiwix/ctype.h	1	pages	38	lines	18/04/21	18:45:47
228	include/fiwix/devices.h	1	pages	49	lines	18/04/21	18:45:47
229	include/fiwix/dirent.h	1	pages	21	lines	18/04/21	18:45:47
230	include/fiwix/dma.h	1	pages	33	lines	18/04/21	18:45:47
231	include/fiwix/errno.h	3	pages	132	lines	18/04/21	18:45:47
232	include/fiwix/fcntl.h	1	pages	67	lines	18/04/21	18:45:47
233	include/fiwix/filesystems.h	3	pages	151	lines	18/04/21	18:45:47
234	include/fiwix/floppy.h	2	pages	100	lines	18/04/21	18:45:47
235	include/fiwix/fs_ext2.h	4	pages	232	lines	18/04/21	18:45:47
236	include/fiwix/fs.h	4	pages	264	lines	18/04/21	18:45:47
237	include/fiwix/fs_iso9660.h	4	pages	216	lines	18/04/21	18:45:47
238	include/fiwix/fs_minix.h	2	pages	131	lines	18/04/21	18:45:47
239	include/fiwix/fs_pipe.h	1	pages	23	lines	18/04/21	18:45:47
240	include/fiwix/fs_proc.h	2	pages	89	lines	18/04/21	18:45:47
241	include/fiwix/i386elf.h	5	pages	279	lines	18/04/21	18:45:47
242	include/fiwix/ide_cd.h	1	pages	24	lines	18/04/21	18:45:47
243	include/fiwix/ide.h	5	pages	276	lines	18/04/21	18:45:47
244	include/fiwix/ide_hd.h	1	pages	23	lines	18/04/21	18:45:47
245	include/fiwix/ioctl.h	2	pages	89	lines	18/04/21	18:45:47
246	include/fiwix/kd.h	3	pages	167	lines	18/04/21	18:45:47
247	include/fiwix/kernel.h	2	pages	85	lines	18/04/21	18:45:47
248	include/fiwix/keyboard.h	2	pages	134	lines	18/04/21	18:45:47
249	include/fiwix/kparms.h	1	pages	57	lines	18/04/21	18:45:47
250	include/fiwix/limits.h	1	pages	27	lines	18/04/21	18:45:47
251	include/fiwix/locks.h	1	pages	29	lines	18/04/21	18:45:47
252	include/fiwix/lp.h	1	pages	48	lines	18/04/21	18:45:47
253	include/fiwix/memdev.h	1	pages	49	lines	18/04/21	18:45:47
254	include/fiwix/mman.h	1	pages	59	lines	18/04/21	18:45:47
255	include/fiwix/mm.h	2	pages	101	lines	18/04/21	18:45:47
256	include/fiwix/multiboot.h	2	pages	124	lines	18/04/21	18:45:47
257	include/fiwix/part.h	1	pages	38	lines	18/04/21	18:45:47
258	include/fiwix/pic.h	1	pages	54	lines	18/04/21	18:45:47
259	include/fiwix/pit.h	1	pages	51	lines	18/04/21	18:45:47
260	include/fiwix/process.h	3	pages	181	lines	18/04/21	18:45:47
261	include/fiwix/ramdisk.h	1	pages	33	lines	18/04/21	18:45:47
262	include/fiwix/reboot.h	1	pages	23	lines	18/04/21	18:45:47
263	include/fiwix/resource.h	2	pages	81	lines	18/04/21	18:45:47
264	include/fiwix/sched.h	1	pages	56	lines	18/04/21	18:45:47
265	include/fiwix/segments.h	2	pages	69	lines	18/04/21	18:45:47
266	include/fiwix/sigcontext.h	1	pages	32	lines	18/04/21	18:45:47
267	include/fiwix/signal.h	2	pages	92	lines	18/04/21	18:45:47
268	include/fiwix/sleep.h	1	pages	38	lines	18/04/21	18:45:47

Table of Contents

Page -5/5

269	include/fiwix/statbuf.h	1	pages	48	lines	18/04/21	18:45:47
270	include/fiwix/statfs.h	1	pages	28	lines	18/04/21	18:45:47
271	include/fiwix/stat.h	1	pages	56	lines	18/04/21	18:45:47
272	include/fiwix/stdarg.h	1	pages	42	lines	18/04/21	18:45:47
273	include/fiwix/stdio.h	1	pages	15	lines	18/04/21	18:45:47
274	include/fiwix/string.h	1	pages	42	lines	18/04/21	18:45:47
275	include/fiwix/syscalls.h	3	pages	147	lines	18/04/21	18:45:47
276	include/fiwix/system.h	1	pages	29	lines	18/04/21	18:45:47
277	include/fiwix/termbits.h	3	pages	188	lines	18/04/21	18:45:47
278	include/fiwix/termios.h	1	pages	31	lines	18/04/21	18:45:47
279	include/fiwix/timeb.h	1	pages	18	lines	18/04/21	18:45:47
280	include/fiwix/time.h	1	pages	49	lines	18/04/21	18:45:47
281	include/fiwix/timer.h	1	pages	50	lines	18/04/21	18:45:47
282	include/fiwix/times.h	1	pages	18	lines	18/04/21	18:45:47
283	include/fiwix/traps.h	1	pages	46	lines	18/04/21	18:45:47
284	include/fiwix/tty.h	2	pages	83	lines	18/04/21	18:45:47
285	include/fiwix/types.h	1	pages	53	lines	18/04/21	18:45:47
286	include/fiwix/unistd.h	4	pages	207	lines	18/04/21	18:45:47
287	include/fiwix/ustat.h	1	pages	20	lines	18/04/21	18:45:47
288	include/fiwix/utime.h	1	pages	18	lines	18/04/21	18:45:47
289	include/fiwix/utsname.h	2	pages	75	lines	18/04/21	18:45:47
290	include/fiwix/version.h	1	pages	1	lines	18/04/21	18:45:47
291	include/fiwix/vt.h	1	pages	54	lines	18/04/21	18:45:47
292	README	3	pages	140	lines	18/04/21	18:45:47
293	LICENSE	1	pages	19	lines	18/04/21	18:45:47
294	CODING	1	pages	37	lines	18/04/21	18:45:47
295	THANKS	1	pages	13	lines	18/04/21	18:45:47